How-To Library

Informatica

Address Verification 6.x Best Practices for Austria

© Copyright Informatica LLC 2023. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in an Austria address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in Austria.

Supported Versions

- Informatica Address Verification 6.4
- Informatica Address Verification (On-Premises) 6.4

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 4
Mapping Input Address Data to Address Elements. . . . 4
Input and Result JSON in Address Verification (On-Prem). . . . 4
Input and Result JSON in Address Verification. . . . 6
Address Enrichments. . . . 8
Reference Address Databases. . . . 8
Additional Documentation Resources. . . . 9

Introduction

Informatica Address Verification can validate and enhance addresses in Austria. This how-to article provides you with configuration information and best practices that you can follow to get the most from the addresses. The best practices include advice on how to select the appropriate JSON elements for Austria address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to identify the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Austria addresses:

- ADDRESS CODE LOOKUP
- BATCH
- GEOCODE TO ADDRESS
- STANDARD GEOCODING
- ARRIVAL POINT GEOCODING

- ROOFTOP GEOCODING
- INTERACTIVE
- QUICK CAPTURE

Character Set

Austria reference address databases store address data in the Latin-1 script.

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

A typical Austria address contains the following elements in this order:

```
RECIPIENT
STREET_NAME HOUSE_NUMBER /[ENTRANCE] /[FLOOR] /APARTMENT]
POSTAL_CODE LOCALITY
AUSTRIA
```

Austria addresses do not always contain subbuilding information, such as Apartment or Floor. However, if the address contains subbuilding information, Informatica Address Verification verifies addresses up to the subbuilding level.

In Austria addresses, the forward slash (/) mark separates building and subbuilding elements. When you write an Austria address, you can either use the forward slash mark to separate subbuilding elements or include the subbuilding descriptors. For example, consider the address 'Wiener Brauhausstraße 6/6/2' . Wiener Brauhausstraße is the street name, 6 is the building number, and 6 and 2 are the subbuilding details such as the block and house number respectively. If the reference address database contains the subbuilding information, Address Verification includes the subbuilding descriptors, such as block, floor, and apartment, in the subbuilding field of the result. However, in the AddressComplete output, Address Verification returns the building and subbuilding details in the same format you entered the details in the input.

The following table lists the elements in an Austria address, and provides examples:

Address Element	Example 1	Example 2
RECIPIENT	John Doe	-
STREET_NAME HOUSE_NUMBER/ [ENTRANCE]/[FLOOR]/ [APARTMENT]	Brauhausstraße 6 Reihe 6 Haus 2	Bartbergstraße 5/1/2
POSTAL_CODE LOCALITY	2351 Wiener Neudorf	3013 Pressbaum
COUNTRY	Austria	Austria
Complete Address	Brauhausstraße 6 Reihe 6 Haus 2 2351 Wiener Neudorf AUSTRIA	Bartbergstraße 5/1/2 3013 Pressbaum AUSTRIA

Key Address Elements

Informatica Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Subbuilding
- House Number
- Locality
- Postal Code
- Street Name

Typically a combination of street name, house number, and locality resolve to the correct address. However, some locality names are common in multiple provinces. In such cases, the postal code helps the Address Verification engine resolve the address to the correct locality.

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information Example	Address Elements
Street Name	Brauhausstraße 6 Reihe 6 Haus 2	Street
House Number	6	HouseNumber
Floor	2	SubBuilding
Postal Code	2351 Wiener	PostalCode
Locality	Neudorf	Locality

Input and Result JSON in Address Verification (On-Prem)

The following example shows how you can map the address information to the JSON address elements in Address Verification (On-Premises).

You enter the following input address:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
 "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "Ackergasse" } ],
          "HouseNumber": [ { "Value": "3" } ],
          "Locality": [ { "Value": "Graz" } ],
          "PostalCode": [ { "Value": "8010" } ],
          "AdministrativeDivision": [ { "Value": "Steiermark" } ],
          "Country": "AUT"
        }
      }
    ]
```

```
  }
}
```

Informatica Address Verification (On-Premises) returns the following result:


```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
  "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "Ackergasse" } ],
          "HouseNumber": [ { "Value": "3" } ],
          "Locality": [ { "Value": "Graz" } ],
          "PostalCode": [ { "Value": "8010" } ],
          "AdministrativeDivision": [ { "Value": "Steiermark" } ],
          "Country": "AUT"
        }
      }
    ],
    "Outputs": [
      {
        "ResultInfo": {
          "ProcessStatus": "V",
          "ProcessModeUsed": "Batch",
          "DeliverAdditionalSuggestions": "No",
          "ResultCount": 1,
          "ResultCountOverflow": false,
          "ResultCountries": [ "AUT" ]
        },
        "Results": [
          {
            "Variants": [
              {
                "StatusValues": {
                  "AddressType": "S",
                  "LanguageISO3": "DEU",
                  "UsedVerificationLevel": "All",
                  "MatchPercentage": "100.00",
                  "Script": "Native Primary",
                  "AddressCount": "",
                  "ResultQuality": 6
                },
                "AddressElements": {
                  "Street": [ { "Value": "Ackergasse" } ],
                  "HouseNumber": [ { "Value": "3" } ],
                  "Locality": [
                    { "Value": "Graz" }, { "Value": "Graz,06.Bez.:Jakomini" }
                  ],
                  "PostalCode": [ { "Value": "8010" } ],
                  "AdministrativeDivision": [
                    { "Value": "Steiermark" }, { "Value": "Graz(Stadt)" }
                  ],
                  "Country": [ { "Code": "AUT", "Name": "AUSTRIA" } ]
                },
                "PreformattedData": {
                  "PostalDeliveryAddressLines": [ { "Value": "Ackergasse 3" } ],
                  "PostalFormattedAddressLines": [
                    { "Value": "Ackergasse 3" }, { "Value": "8010 Graz" }
                  ],
                  "PostalLocalityLine": { "Value": "8010 Graz" }
                }
              }
            ]
          }
        ]
      }
```

```
    ]
  }
}
```

Input and Result JSON in Address Verification

The following example shows how you can verify an Austria address in a REST call to Address Verification.

You submit the following request:

```
{
  "Login": *****,
  "Password": *****,
  "CampaignId": "Campaign222",
  "UseTransactions": "TEST",
  "Request": {
    "Parameters": {
      "Mode": "Batch",
      "CountryDetermination": {},
      "DataSetDetermination": {},
      "CountrySets": [
        {
          "Process": {
            "AlternativeHandling": {
              "OutdatedAddresses": { "Match": "Off", "GetNewAddress": false },
              "AliasAddresses": { "Match": "Off" }
            },
            "VerificationLevel": {
              "PreferredVerificationLevel": "All",
              "MinimumVerificationLevel": "All"
            },
            "Geocode": { "SearchRadius": "50" },
            "Enrichments": {
              "Geocoding": {
                "Rooftop": false,
                "ArrivalPoint": false,
                "StreetCenter": false,
                "PostalCodeCenter": false,
                "LocalityCenter": false
              },
              "Global": false,
              "CountrySpecific": false,
              "CAMEO": false
            }
          }
        }
      ]
    },
         "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "Ackergasse" } ],
          "HouseNumber": [ { "Value": "3" } ],
          "Locality": [ { "Value": "Graz" } ],
          "PostalCode": [ { "Value": "8010" } ],
          "AdministrativeDivision": [ { "Value": "Steiermark" } ],
          "Country": "AUT"
        }
      }
    ]
  }
  }
}
```

Informatica Address Verification returns the following response:

```
{
    "Status": "Ok",
    "StatusDescription": "No error",
```

```
"TransactionInfo": {
    "TotalTransactionsCharged": 1,
    "TransactionPools": [
        {
            "Type": "BATCH",
            "TransactionsCharged": 1
        }
    ]
},
"CampaignId": "Campaign222",
"Response": [
    {
        "ResultInfo": {
            "ProcessStatus": "V",
            "ProcessModeUsed": "Batch",
            "DeliverAdditionalSuggestions": "No",
            "ResultCount": 1,
            "ResultCountOverflow": false,
            "ResultCountries": [
                "AUT"
            ]
        },
        "Results": [
            {
                "Variants": [
                    {
                        "StatusValues": {
                            "AddressType": "S",
                            "LanguageISO3": "DEU",
                            "UsedVerificationLevel": "All",
                            "MatchPercentage": "100.00",
                            "Script": "Native Primary",
                            "AddressCount": "",
                            "ResultQuality": 6
                        },
                        "AddressElements": {
                            "Street": [
                                {
                                    "Value": "Ackergasse"
                                }
                            ],
                            "HouseNumber": [
                                {
                                    "Value": "3"
                                }
                            ],
                            "Locality": [
                                {
                                    "Value": "Graz"
                                },
                                {
                                    "Value": "Graz,06.Bez.:Jakomini"
                                }
                            ],
                            "PostalCode": [
                                {
                                    "Value": "8010"
                                }
                            ],
                            "AdministrativeDivision": [
                                {
                                    "Value": "Steiermark"
                                },
                                {
                                    "Value": "Graz(Stadt)"
                                }
                            ],
                            "Country": [
                                {
                                    "Code": "AUT",
                                    "Name": "AUSTRIA"
```

```
                        }
                    ]
                },
                "PreformattedData": {
                    "PostalDeliveryAddressLines": [
                        {
                            "Value": "Ackergasse 3"
                        }
                    ],
                    "PostalFormattedAddressLines": [
                        {
                            "Value": "Ackergasse 3"
                        },
                        {
                            "Value": "8010 Graz"
                        }
                    ],
                    "PostalLocalityLine": {
                        "Value": "8010 Graz"
                    }
                }
            }
        ]
    }
  ]
}
```


Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Austria addresses.

The following table lists the types of enrichment that you can add to an Austria address:

Enrichment Type	Description
CAMEO	You can retrieve CAMEO profiles as enrichments for valid Austria addresses. CAMEO profiles are consumer classification systems that provide socio-economic and demographic indicators about the residents at the address.
Geocoding	You can perform geocoding for Austria addresses to the following levels of precision: - ArrivalPoint - Rooftop - Standard

Reference Address Databases

Informatica updates some Austria reference address databases every month, and some every quarter. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Argentina addresses every month:

- `AUT_ADV_RLK_ACL_000_6_x_0.MD6`. AddressCodeLookUp.
- `AUT_ADV_VRF_BIA_000_6_x_0.MD6`. Batch and interactive data.
- `AUT_ADV_VRF_QCP_000_6_x_0.MD6`. QuickCapture data.
- `AUT_ADV_ENR_GAP_000_6_x_0.MD6`. ArrivalPoint geocoding data.

- `AUT_ADV_ENR_GRT_000_6_x_0.MD6`. Rooftop geocoding data.

Informatica Address Verification provides the following reference databases for Argentina addresses every quarter:

- `AUT_ADV_ENR_GST_000_6_x_0.MD6`. Standard geocoding data.
- `AUT_ADV_RLK_GTA_000_6_x_0.MD6`. GeocodeToAddress data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, click the following links:

https://docs.informatica.com/data-as-a-service/address-verification-(on-premises)/6-4-0.html

https://docs.informatica.com/data-as-a-service/address-verification/6-4-0.html

Author

Dishari Dutta