Address Verification 6.8.0 Release Notes (On-Premises)

April 2026

© Copyright Informatica LLC 1998, 2026

Contents

Informatica Address Verification Installation. 1
System and Memory Requirements. 1
System Configuration. 2
Developer Support. 2
Informatica Address Verification Version 6.8.0. 3
Fixed Issues in Version 6.8.0. 3
Known Limitations in Version 6.8.0. 5
Informatica Global Customer Support. 6

Read the release notes to learn important information about known limitations and fixed issues in Informatica Address Verification (On-Premises) 6.8.0.

If you connect to Informatica Address Verification in the cloud, you can use this document to learn about the current capabilities of the Address Verification engine.

Informatica Address Verification Installation

System and Memory Requirements

The system resources that Informatica Address Verification requires can vary according to your installation and your data requirements.

The machine on which you install Address Verification must have a minimum of 1 GB RAM for a C++ installation. Java and Microsoft .NET installations require additional memory.

The main address verification functionality is encapsulated in one or more *function servers*. A function server is a running instance of the Informatica data verification engine.

Each function server, including standby function servers, require 455 MB of RAM for processing and data structure operations. If you enable hot swapping, the total memory usage doubles for Address Verification.

Before you finalize the memory requirements, consider the size of the reference address databases that you require. The complete set of worldwide postal reference databases, including supplementary databases for address enrichments, consumes approximately 55 GB of storage space.

Preloading databases into memory significantly improves the performance of Address Verification. The machine on which you install Address Verification must have sufficient RAM to preload the databases that you require.

As the total size of the worldwide databases is approximately 55 GB, the RAM required to preload all databases and perform address processing is approximately 60 GB.

The IDVEConfig.json file stores the properties that define the memory requirements. Update the property values if necessary to suit your installation.

The default configuration values on the IDVEConfig.json file are sufficient to initialize the engine, but they are not likely to be adequate for data preloading.

Tip: If fully preloading databases is not an option, use solid-state drives to store the reference address databases. Solid-state drives are faster than hard-disk drives and can significantly improve performance, especially when multithreading is used.

For more information about system and memory requirements, see the *Address Verification (On-Premises) Installation and Getting Started Guide*.

System Configuration

When you install Informatica Address Verification, verify that the operating system and the processor architecture are compatible on the installation host machine. Verify also that the installation host machine runs a Java Development Kit that is compatible with the processor architecture and the operating system.

You must install a Java Development Kit on the machine that hosts the Address Verification engine.

The following table lists the system configurations that you can use for Informatica Address Verification installation:

Operating System	Processor Architecture
Windows Server 2019	x64 (64-bit)
Windows Server 2016	x64 (64-bit)
Windows 10	x64 (64-bit)
Ubuntu 20	x64 (64-bit)
SUSE Linux Enterprise Server 15	x64 (64-bit)
RedHat Enterprise Linux 8	x64 (64-bit)

Developer Support

Informatica develops Informatica Address Verification in the C/C++ programming language. The Informatica Address Verification software packages contain APIs in C/C++, Java, and .NET.

You can model Address Verification implementations for other languages, such as C#, PHP, Perl, Ruby, and Python.

Informatica Address Verification provides technical support for C/C++, Java, and .NET-based APIs. Informatica Address Verification does not provide implementation-specific technical support.

For more information about or assistance with address verification projects, contact the Informatica Professional Services team.

Informatica Address Verification Version 6.8.0

Fixed Issues in Version 6.8.0

The following table describes customer-reported issues that are fixed in version 6.8.0:

Country	CR Number	Description
All	HDS-32869	Addresses from Thailand and India generate parsing errors in limited circumstances that cause the engine to stop unexpectedly.
Australia	HDS-32505	When you enter an address that contains a house number, street, locality, and postcode in interactive mode, Address Verification prioritizes matching street and locality information above matching house number and post code information.
Australia	HDS-32528	When you validate an address in interactive mode, Address Verification returns the locality "Bairsdale" twice in the output.
Canada	HDS-29394	If you don't specify a postal code to the address, Address Verification fails to validate the address. With postal code, the engine returns a V process status. Without a postal code, the engine returns an I process status.
Canada	HDS-32311	If an address contains a post directional information "N", Address Verification fails to validate the address.
Canada	HDS-31055	Address Verification can change an English-language street descriptor to a French-language street descriptor. For example, Address Verification corrects "ROAD 18 West" and "ROAD 18 W" to "18 RD O" in the following input address: 15041 Road 18 West Greenfarm Manitoba R6P 0J4
Canada	HDS-29394	If you don't specify a postal code in a Canada address in Interactive mode, Address Verification returns the address with an I process status and the address suggestions don't include the correct address.
Germany	HDS-32335	Address Verification fails to return the correct current address for an archive address when you set the GetNewAddress property to true.
Germany	HDS-32558	Address Verification incorrectly abbreviates "Noltenweg" to "Noltenwg" if the engine fails to validate the address properly in batch mode.
Hong Kong	HDS-28887	Address Verification returns multiple incorrect suggestions for an adddress. For example, the engine adds a sub building level zero information and returns the output with an I process status for the following address: Flat B Kung Lok Building Block A 44 Kung Lok Road
Ireland	HDS-33013	If you enter a single letter as the Province element value in an otherwise valid address, Address Verification returns the address with an I process status.

Country	CR Number	Description
Israel	HDS-33089	Address Verification returns incorrect results when you provide multi-line input in an address line 1 field in a mixed Hebrew script. For example, Address Verification fails to validate house numbers from PostalDeliveryAddressLines 2 and 3 in the following address:
Japan	HDS-33102	Address Verification takes more than 80 seconds to validate an address when you set the PreformattedLineDelimiter value to None.
Japan	HDS-33005	Addresses from Japan generate parsing errors in limited circumstances that lead to very slow processing.
Japan	HDS-31819	Addres Verification returns a contradictory output for an address. The engine returns the address with a C process status and result quality as zero for the following address: Worldplay KK, JA Building 12F,1-2-1 Otemachi, Chiyoda-Ku,Tokyo 100-6812
Japan	HDS-7106	Address Verification fails to correct locality level 3 information in an input address. For example, Addres Verification returns 二又瀬新町 instead of 二又瀬新田町 as locality 3 value for the following address: 二又瀬新田町 14-22-510 福岡市東区 Japan
Mexico	HDS-32623	Address Verification doesn't recognize Avenida as a matching street descriptor for Av. or Avenid. For example, if you add "Avenida Providencia" to PostalDeliveryAddressLines 1, Address Verification returns the address with an I process status. However, if you add "Av. Providencia" or "Avenid Providencia" to PostalDeliveryAddressLines 1, Address Verification returns the address with a C process status in the following address: Avenida Providencia Fracc. San Cristóbal 42186 Mineral de La Reforma Hidalgo Mexico
Spain	HDS-31700	Address Verification returns duplicate sub-building data in the output for a Spain address.
Spain	HDS-31833	In interactive mode, Address Verification suggests incorrect sub building details. The engine returns "Planta 0" instead of "Planta 1" for the following address: Calle de Escocia 6 Planta 1 Puerta C 28942 FUENLABRADA Madrid Spain
United Kingdom	HDS-31936	If your address contains an organization name in a PostalFormattedAddressLines element, Address Verification incorrectly parses the organization name to the **Contact** field.
United States	HDS-33068	When you set the Match property of the OutdatedAddress element to Off, Address Verification returns the address with an I process status.
United States	HDS-32620	If your input address doesn't exist in the reference database and you set the Casing to Mixed, DescriptorLength to Long, and AliasHandling to PreserveAll, Address Verification fails to apply proper casing to the street name.
United States	HDS-32448	Address Verification fails to return a valid address in the following scenario: - The street information matches the ZIP Code in the input address. - The city and state information in the input address does not match the street and ZIP Code information.

Country	CR Number	Description
United States	HDS-32288	Address Verification returns address without the ZIP Codes. If you add the post directional descriptor at the end of the address, the engine fails to recognize the descriptor in the following address: 12400 Hwy 281 North San Antonio TX 78216
United States	HDS-32120	Address Verification changes the casing of the street to uppercase in a valid address when you set the Casing property to Mixed and the AliasHandling property to PreserveOfficial.
United States	HDS-32117	Address Verification returns different outputs for the same address in version 5 and version 6.
United States	HDS-32048	Address Verification returns a valid address with a Result Quality value of 4.
United States	HDS-31368	Address Verification can return highway information in the Residue field if the engine does not recognize KK as as part of the highway name.
United States	HDS-31367	Address Verification can return street information in the Residue field if the input address contains a space between the street name and the directional identifier. For example, Address Verification returns "RTE 9 W" in the Residue field.
United States	HDS-32304	If you don't specify a ZIP Code in your input address, Address Verification does not correct an incorrect locality.
United States	HDS-32139	If you set the Casing parameter to Mixed or Preserve, Address Verification returns street directional indicator values in upper case.

Known Limitations in Version 6.8.0

The following table describes known limitations in 6.8.0:

Country	CR Number	Description
All	HDS-33337	The DataFilesUsed element in the job output lists a data file multiple times in the following scenario: - You add multiple Standardization output elements to the job request, and the Standardization elements specify the data file multiple times.
Canada	HDS-33831	Address Verification corrects valid street name information in an input address in certified mode when the house number input is incorrect.
Canada	HDS-33827	Address Verification can fail to complete a partial locality name in certified mode in the following scenario: - The address is a rural route. - The first delivery address line element is empty.
Canada	HDS-33825	Address Verification fails to add absent delivery service information to an address in certified mode in the following scenario: - The address is a delivery service address. - The first delivery address line element is empty.

Country	CR Number	Description
Canada	HDS-33682	Address Verification can assign an incorrect SERP category to an address in certified mode in the following scenario: - The address is a rural route. - The first delivery address line element is empty.
Canada	HDS-33671	Address Verification fails to add absent delivery service information to an address in certified mode in the following scenario: - The address is a rural route. - The first delivery address line element is empty.
Canada	HDS-28576	If an input address contains postal code V0A IH0, Address Verification returns the address with an V process status in GeocodeToAddress mode. The engine returns the same address with an I process status in batch and interactive modes.
China	HDS-20917	Address Verification doesn't return postal code information in an output address when the country name appears in the first postal delivery address line.
China	HDS-20918	Address Verification can fail to return a section of the street name. The engine doesn't return the 东段 section of the street when you enter 秀厢大道东段 as the street name in a PostalDeliveryAddressLines field.
Czech Republic	HDS-33546	Address Verification fails to correct the post code in an address that contains a valid street and locality information.
Hong Kong	HDS-33970	Address Verification fails to validate an address that contains two levels of province information.
Hong Kong	HDS-33969	Address Verification fails to recognize a building name in an input address in the following scenario: - The address job uses the default country data sets. - The building name appears in a Latin script on a delivery address line.
Hong Kong	HDS-33945	Address Verification can fail to validate a postally correct unfielded address.
Hong Kong	HDS-27847	Address Verification fails to recognize a valid address in the input data when you set the PreferredScript property to NativePrimary and the input data include extraneous or duplicate address information.
Malaysia	HDS-33514	Address Verification rejects an address that contains mostly valid information and does not make corrections.
Romania	HDS-33529	Address Verification can fail to validate an address when the street name is incomplete. For example, Address Verification fails to recognize Gladiol as an incomplete version for Gladiolelor in the post code area 510218.
Spain	HDS-33466	When you enter an address that contains a valid house number and street combination in interactive mode, Address Verification fails to correct the locality.
Spain	HDS-33301	Address Verification returns different match and process status values for the same address elements in version 6.7 and version 6.7.2 when the address includes PISO as a sub-building descriptor.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.