How-To Library

Informatica

Address Verification Best Practices for Switzerland

© Copyright Informatica LLC 1993, 2022. Informatica LLC. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. All other company and product names may be trade names or trademarks of their respective owners and/or copyrighted materials of such owners.

Abstract

This document provides a high-level overview of the Informatica Address Verification, powered by AddressDoctor, support for Switzerland addresses. This document also contains information that are specific to Switzerland address verification.

Supported Versions

- Informatica AddressDoctor 5.7.0
- Informatica AddressDoctor Cloud 2.0.0

Table of Contents

Languages and Character Set. . . . 2
Multilanguage Support for Switzerland Addresses. . . . 2
Process Modes. . . . 4
Address Enrichments. . . . 4
Address Format and Address Examples. . . . 4
Key Address Elements. . . . 5
Address Verification Notes. . . . 5
Frequently Asked Questions. . . . 6
Reference Address Databases. . . . 6
Additional Documentation Resources. . . . 6

Languages and Character Set

Informatica Address Verification supports multiple languages for Switzerland addresses. By default, you receive a verified Switzerland address in the main language of the region, such as French, German, and Italian, to which the address belongs. You can also configure Address Verification to return the locality information in Switzerland address results across regions consistently in French, German, or Italian.

The default character set for Switzerland addresses is Latin 1 - Western European

The following sections explain the multilanguage support for Switzerland addresses.

Multilanguage Support for Switzerland Addresses

You can configure Address Verification to return locality information and province (Canton) information in valid Switzerland addresses in French, German, or Italian.

To set the preferred language, configure the `PreferredLanguage` attribute of the `Result` element in `Parameters.xml`.

The following table describes the `PreferredLanguage` values that you can set for Switzerland address data:

Option	Description
DATABASE	Default value. Returns addresses in the main language of the region to which the address belongs. For example, Address Verification returns a Zurich address in German and a Geneva address in French.
ENGLISH	Returns the locality and province information in English if the reference address database contains the information in English. Returns the other address elements in the main language of the region to which the address belongs. Address Verification returns the locality information in English for select localities such as Geneva and Zurich.
ALTERNATIVE_1	Returns the province and locality information in German.
ALTERNATIVE_2	Returns the province and locality information in French.
ALTERNATIVE_3	Returns the province and locality information in Italian.
PRESERVE_INPUT	Returns addresses in the language that the input address uses. Address Verification preserves the language if the reference address database contains the address in the input language. If the input address contains more than one language, Address Verification returns the output in the database language.

Note: Address Verification also returns street information for addresses in Biel/Bienne in the alternative language that you configure.

Example: PreferredLanguage Settings and Results for Switzerland Addresses

You enter the following Switzerland address for verification:

Beundenweg 36

2503 Biel/Bienne

The following table shows the validated results for different `PreferredLanguage` settings when you enter the address:

DATABASE	ENGLISH	ALTERNATIVE_1 (German)	ALTERNATIVE_2 (French)	ALTERNATIVE_3 (Italian)	PRESERVE_INPUT
Beundenweg 36 2503 Biel/ Bienne	Beundenweg 36 2503 Biel/ Bienne	Beundenweg 36 2503 Biel/ Bienne	Chemin des Oeuches 36 2503 Bienne	Beundenweg 36 2503 Bienna	Beundenweg 36 2503 Biel/ Bienne

The table indicates that the results for DATABASE, ENGLISH, ALTERNATIVE_1, and PRESERVE_INPUT are in German. The result for ALTERNATIVE_2 is in French.

In the ALTERNATIVE_3 result, you receive the locality information in Italian. The Switzerland reference address database contains only the locality information for the address in Italian. Informatica Address Verification returns the street information in German, which is the database language for the address. In this case, Address Verification returns an extended element result status (EERS) value of E for the street element. An EERS value of E indicates that the output is in the database language because the reference database does not contain the information in the language that you specified.

Process Modes

You can process Switzerland addresses in the following process modes:

- BATCH
- COUNTRYRECOGNITION
- FASTCOMPLETION
- INTERACTIVE
- PARSE

Informatica Address Verification verifies addresses in batch, interactive, and fast completion modes.

Address Enrichments

You can configure Informatica Address Verification to return the following address enrichments for verified Switzerland addresses:

Enrichment	Database	Description
Arrival Point Geocoding	CHE5GCAP.MD	Retrieve the arrival point geocoordinates for valid Switzerland addresses. This is the default geocoding that Address Verification returns for valid Switzerland addresses if you enabled geocoding.
CAMEO	CHE5CA.MD	Retrieve the CAMEO profiles from the Callcredit Information Group as enrichment to valid Switzerland addresses. CAMEO profiles provide consumer classification systems that indicate the socio-economic and geo-demographic profiles of neighborhoods across the world.
Country-Specific Enrichments	CHE5E1.MD	Retrieve additional postal code characters, POCO_EXT, for valid Switzerland addresses.
Parcel Centroid Geocoding	CHE5GCPC.MD	Retrieve the parcel centroid geocoordinates for valid Switzerland addresses.
Standard Geocoding	CHE5GC.MD	Retrieve the standard, interpolated geocoordinates for verified Switzerland addresses.

Address Format and Address Examples

A typical Switzerland address contains the following elements in the given order:

```
RECIPIENT
STREET_NAME HOUSE_NUMBER [[APARTMENT][/][FLOOR]]
POSTAL_CODE LOCALITY
SWITZERLAND
```

The Apartment and Floor elements are optional. Informatica Address Verification verifies Switzerland address elements only up to the premises number.

The following table lists Switzerland address elements and provides examples:

Address Elements	Example 1	Example 2
RECIPIENT	Informatica	-
STREET_NAME HOUSE_NUMBER	Täfernstrasse 4	Rue de Bourgogne 5
[[APARTMENT][/] [FLOOR]]	-	-
POST BOX NUMBER	-	Case Postale 12
POSTAL_CODE	5405	1211
LOCALITY	Dättwil	Genève
COUNTRY	Switzerland	Switzerland

Complete Address	`Informatica`
	`Täfernstrasse 4`
	`5405 Dättwil`
	`SWITZERLAND`
		`Rue de Bourgogne 5`
		`Case Postale 12`
		`1211 Genève`
		`SWITZERLAND`

Key Address Elements

The following elements in a Switzerland address are very important for address verification:

Street Name

House Number

Postal Code

Locality

Informatica Address Verification verifies Switzerland addresses only up to the house number level.

Address Verification Notes

When you verify Switzerland addresses, note the following points:

- Some locality names in Switzerland have numbers at the end. For example, Basel 22 and Bellinzona 2.
  In AddressLines format, Informatica Address Verification removes the number from the locality name. For example, Address Verification returns Basel instead of Basel 22 in AddressLines output.
- Addresses that belong to different localities might share the same postal code. For example, addresses with postal code 3003 could be from Bern 9 or Bern 94. Note that in AddressLines output, Address Verification returns 3003 Bern instead of 3003 Bern 9 or 3003 Bern 94.
- Some of the street names in Switzerland do not contain any descriptors. For example, Hinter der Kirche. Hinter der Kirche translates to Behind the Church in English. Another example is Ausser Glas, which translates to Without Glass in English.
- French street names in Switzerland addresses start with lowercase street descriptors such as chemin, route, rue, sentier, and allée.
  French street names in Switzerland follow the `STREET_TYPE STREET_NAME HOUSE_NUMBER` format. For example, chemin des Molliettes 12.

- German street names in Switzerland follow the `STREET_NAME STREET_TYPE HOUSE_NUMBER` format. For example, Bahnhofstrasse 12.
  Because the ß character is not used in Switzerland, the German street names are written as *Strasse* instead of *Straße*.

Frequently Asked Questions

Is province information available for Switzerland addresses?

Yes, province information is available for Switzerland addresses. Informatica Address Verification returns the two-letter province (canton) ISO code in the result output.

Do all streets in Switzerland have house numbers associated with them?

No, some streets in Switzerland do not have house numbers.

Why is it that some locality names in Switzerland also contain province abbreviations as suffix?

A locality name contains a province (canton) abbreviation as suffix if the locality name is present in multiple provinces. For example, the province abbreviation *SO* in Beinwil SO indicates that the locality Beinwil is part of the Canton of Solothurn. There are two more localities, Beinwil am See and Beinwil (Freiamt), with the same name.

Are Large Volume Receivers present in Switzerland?

Large volume receivers (LVR) are present in Switzerland. LVRs in a locality might share a common postal code. For example, 3005 is the collective postal code for multiple public services in Bern.

Reference Address Databases

Informatica updates the reference address databases for Switzerland every month. You can download the latest database packages from the Informatica Database Download portal.

Informatica Address Verification supports the following reference address databases for Switzerland addresses:

- `CHE5BI.MD`. For batch and interactive modes.
- `CHE5CA.MD`. For CAMEO consumer segmentation.
- `CHE5E1.MD`. For country-specific enrichments.
- `CHE5FC.MD`. For fast completion mode.
- `CHE5GCAP.MD`. For arrival point geocoding.
- `CHE5GC.MD`. For standard geocoding.
- `CHE5GCPC.MD`. For parcel centroid geocoding.

For news about reference address databases and software updates for Address Verification, subscribe to the UpData newsletter from Informatica.

Additional Documentation Resources

For more information about Informatica Address Verification features and configuration, see the latest Address Verification documentation at:

https://network.informatica.com/community/informatica-network/products/data_quality/address-doctor/

Authors

Abhilash Prabhakaran

Bart Honhoff