How-To Library

Informatica

Address Verification 6.x Status Codes

© Copyright Informatica LLC 2023. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

Informatica Address Verification can return status codes for an address as part of the address output. This article describes the types of status codes that Address Verification can return and the possible values for each code.

Supported Versions

- Informatica Address Verification 6.3 and later
- Informatica Address Verification (On-Premises) 6.3.0

Table of Contents

Introduction. . . . 2
Process Status. . . . 2
Address Element Status Codes. . . . 3
Match Status. . . . 3
Result Status. . . . 4
Postal Relevance. . . . 4
Extended Result Status. . . . 5
Certification and Enrichment Data Status Codes. . . . 6
Result Quality. . . . 6
Match Percentage Value. . . . 7
Level of Verification. . . . 7

Introduction

Informatica Address Verification returns status codes to help you understand the results of validation and enrichment operations. Status codes are strings that indicate the actions that Address Verification performed for each address and the outcome of each action.

The status codes provide information about the overall validation outcome as well as the result of the validation process for each address element. You can use the status codes to determine the quality and deliverability of an address.

Process Status

The ProcessStatus property provides a summary of the address verification process for a single address. The process status code indicates the overall quality of the output address.

The following table describes the process status values:

Status Code	Description
V	Address Verification verified all postally relevant elements. The input data matches the reference data for the address.
A	Address Verification added one or more relevant address elements to the address.

Status Code	Description
C	Address Verification corrected one or more input address elements to match the address elements in the reference data.
I	Address Verification cannot correct the address. The address is not valid.
N	Address Verification cannot verify the address because the address is not available in the reference data or the country is not supported.
F	QuickCapture mode. Address Verification returned complete addresses in the suggestion list.
P	QuickCapture mode. Address Verification returned aggregated address suggestions. **Note:** A status of P indicates that the verification process is incomplete and that the available suggestions are not fully extended in the result.

Address Element Status Codes

The MatchStatus, ResultStatus, PostalRelevance, and ExtendedResultStatus properties provide granular, element-level details.

You can use the properties to assess the following aspects of your address records:

- Levels of similarity between each input data element and the reference data.
- Types of change made to the input data values during verification.
- Relevance of the address elements.
- Availability of additional data for the address.

Match Status

The MatchStatus property describes the level of similarity between each data element in the input address and the corresponding element that the reference data files store for the address. Address Verification returns a discrete match status code for every address data element.

The following table describes the match status values:

Value	Description
0	The input element does not contain any data from the user.
1	The reference data does not contain the input address element for the country as a whole or for specific address, locality, and street.
2	The reference data does not contain a match for the input element value, and the input address does not contain enough verifiable elements to permit an estimate of a correct value for the element.
3	The reference data does not contain a match for the input element value, and Address Verification cannot correct the value. Address Verification rejects the address.
4	The input element value partially matches the reference data.
5	The input element value matches the reference data, but Address Verification corrects the data.

Value	Description
6	The input element value matches the reference data within the available range.
7	The input element value matches the reference data, but Address Verification standardizes the data
8	The input element value perfectly matches the reference data without any errors.

Result Status

The ResultStatus property describes any change made to the input data during processing. Address Verification returns a discrete result status code for every address data element.

The following table describes the result status values:

Value	Description
1	The element value is not changed.
2	The element value is standardized.
3	The element value is replaced by a preferred version because the input contains outdated synonyms, archived names, or a combination of languages.
4	Address Verification changed the secondary part of the elements. For example, Address Verification corrected street descriptors, street directionals, or the +4 data in ZIP Codes.
5	Address Verification changed the primary part of the elements. For example, Address Verification corrected street names or five-digit ZIP Codes.
6	Address Verification added the element to the result output.

Postal Relevance

You can use the PostalRelevance property value to identify the address elements that are relevant to an address according to the local postal guidelines. Address Verification returns a discrete postal relevance value for every address data element.

The following table describes the postal relevance values:

Value	Description
2	Element mandatory. The address element is relevant.
1	Element optional. The address might be valid without the element.
0	Element not used in the postal format. Address element is not relevant.

All address elements with an element relevance value of 2 must be present for the local postal authority to consider an address valid. Element relevance value might vary from address to address for countries with different address types, such as rural address and metropolitan addressing. Furthermore, address elements that have actually been validated against reference data might override the default element relevance value defined for that address element.

Note: Element relevance values are available only for addresses with a process status value of C or V in batch and interactive modes or I values in the interactive mode. Other element-level codes such as match status, result status, and extended result status always return a value regardless of the process status.

Extended Result Status

You can use the ExtendedResultStatus property to see whether more information is available for an address element in the reference data. Address Verification can return an extended result status value for every address data element.

The following table describes the values that the property can return for each element in an input address:

Note: Unless otherwise indicated, Address Verification can return ExtendedResultStatus values in batch, interactive, and certified modes.

Extended Result Status Values	Description
FromDBNotUsed	The reference data contains information for the element that the engine did not use to verify the address. This additional information is not required for a valid address, and the engine did not add the information to the address.
WrongFormatMoved	The input address contains the element at an incorrect position in the formatted address, and the engine moved the element to the correct position. For example, the postal code appears after the locality in a country that requires the postal code to appear before the locality.
AlternativeExists	The reference data includes at least one additional alternative for the address element.
UncheckedParts	One or more values in the element are not verified because they do not appear in the reference data. The engine cannot confirm their relevance and therefore did not remove them from the address.
CertificationRule	The output element is determined by a postal certification rule. This may contradict the address job properties that you configured.
DominantMatch	The current element matches the reference data, but two or more elements in the input address contradict each other. For example, the postal code does not match the locality.
Deprecated	The address element matches an outdated or archived name.
LanguageNotAvailable	The requested language is not available in the reference data for the element. The engine returns the element in the default language.
RangeInterpolation	The engine returns the input value, as the value falls within a valid range in the reference data. The reference data contains a range of values for the element in the address rather than individual values.
RangeGuess	Applies in interactive mode when the element in the address suggestion contains a range of values. Indicates that the reference data includes the lower and upper values in the range only.
RangeCovered	Applies in interactive mode when the element in the address suggestion contains a range of values. Indicates that the reference data includes values for every address in the range.

Certification and Enrichment Data Status Codes

Informatica Address Verification returns status codes that describe the successful delivery of enrichment and certification data in the output address.

The status codes describe the completeness of the data that address verification returns for global enrichments, country-specific enrichments, CAMEO data, and the supplementary data returned in certification mode.

Address verification returns the following status codes for enrichment and certification data along with the address output:

- AllValuesAvailable. Verification returns all requested enrichment and certification data in the output address.
- SomeValuesAvailable. Verification returns some but not all of the requested enrichment and certification data in the output address.
- NoValuesAvailable. Verification did not return any of the requested enrichment or certification data.

The status code fields are empty when you did not request the enrichment or certification item concerned. The status code fields are also empty when address verification did not find a match for the input address.

Note: Address Verification does not return the empty fields in the JSON output.

Result Quality

The ResultQuality property provides a general estimate of the likelihood that a mail carrier can deliver mail to an address. Use the result quality value with other status values, such as the process status value, to evaluate the address quality and deliverability.

The following table describes the result quality values:

Value	Summary	Description
6	Completely confident	Indicates that Address Verification verified all postally relevant elements.
5	Very confident	Indicates that Address Verification cannot completely verify the address. For example, Address Verification may be unable to verify secondary delivery information such as sub-building data. Or, the address might be a high-rise default address.
4	Secondary delivery point not verified	Indicates that Address Verification can check the primary delivery identifier but cannot verify the secondary delivery information in the address record.
3	Primary delivery identifier not verified	Indicates that Address Verification cannot check the primary delivery identifiers such as house number and P.O. Box number. In countries where the house number information is not available, the primary delivery identifier might be a building name.
2	Delivery information not verified	Indicates that Address Verification cannot find a match for the input street or delivery service information within the reference data. The address is verified to locality level.
1	Incomplete or contradictory address	Indicates that Address Verification cannot find a match for the address in the reference data. This can occur when locality information is not available in the reference data or the address includes contradictory postal code data.
0	Not an address	Indicates that the input is not a deliverable address.

Note: Address Verification is likely to return a lower score for a poor-quality address in batch mode than in interactive mode. Interactive mode can apply a relatively higher tolerance when calculating the result quality score, as it returns multiple addresses from which you can select the correct address.

Match Percentage Value

The MatchPercentage property describes the degree of similarity between the input data and the reference data as a percentage value. Higher values indicate higher degrees of similarity.

Use the match percentage values to filter out results with extensive corrections. Similarly, use the match percentage values to identify interactive mode suggestions that have the least deviation from the input.

Note: Match percentage values refer explicitly to the similarity between the input and the reference data and not to the similarity between the input and the output address. In most cases, the degrees of similarity will be the same. However, this will not be the case if the output address contains an alternative form of a value, such as MUNICH for MÜNCHEN or PKWY for PARKWAY.

Level of Verification

The UsedVerificationLevel property reports the depth or level to which the input address was verified.

Author

Dishari Dutta