How-To Library

Informatica

Address Verification 6.x Best Practices for Mexico Addresses

© Copyright Informatica LLC 2023, 2024. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

This document tells you how to connect the elements in a Mexico address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in Mexico.

Supported Versions

- Informatica Address Verification (On-Premises) 6.4
- Informatica Address Verification 6.4

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result JSON in Address Verification (On-Premises). . . . 4
Input and Result JSON in Address Verification. . . . 5
Address Format and Address Structure. . . . 8
Address Enrichments. . . . 8
Address Verification Tips and Best Practices. . . . 8
Reference Address Databases. . . . 10
Additional Documentation Resources. . . . 10

Introduction

Informatica Address Verification can validate and enhance addresses in Mexico. This how-to article provides you with configuration information and best practices that you can implement when you verify addresses in Mexico. The best practices include advice on how to select the appropriate JSON elements for Mexico address data.

To verify the quality of input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to identify the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Mexico addresses:

- BATCH
- CERTIFIED
- GEOCODE TO ADDRESS
- INTERACTIVE
- QUICK CAPTURE

Character Set

Informatica Address Verification verifies Mexico address in the Spanish language.

The default character set for Mexico addresses is Latin 1 - Western European.

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how the input address data maps to the Address Verification address elements:

Information Type	Address Information Example	Address Element
Street Type and Street Name	PRIVADA UNIÓN	Street
House Number	10	HouseNumber
Neighborhood, Quarter, or Settlement	COL. AGRÍCOLA PANTITLÁN	Locality_2
Municipality	IZTACALCO	Province_2
Postal Code	08100	PostalCode
City	CIUDAD DE MÉXICO	Locality_1
State	CDMEX	Province_Abbreviation
Country	MEXICO	Country

The following example shows the fielded input format for an address:

```
Street: PRIVADA UNIÓN
House Number: 10
Locality 2: COL. AGRÍCOLA PANTITLÁN
Province 2: IZTACALCO
Postal Code: 08100
Locality 1: CIUDAD DE MÉXICO
Province Abbreviation: CDMEX
Country: MEXICO
```

The following example shows the hybrid or partially-fielded input format for an address:

```
Delivery Address Line (DAL): PRIVADA UNIÓN 10
Locality 2: COL. AGRÍCOLA PANTITLÁN
Province 2: IZTACALCO
Postal Code: 08100
Locality 1: CIUDAD DE MÉXICO
Province Abbreviation: CDMEX
Country: MEXICO
```

Address Elements and State or Federal District Names

Address Verification uses Province elements to identify states within Mexico. Address Verification treats the federal district of Mexico City as a state for verification purposes. You can use a Province or an AdministrativeDivision element in place of a PROVINCE_ABBREVIATION element for the state or federal district name. The province name for CDMEX is `Ciudad de México`.

Address Verification can return the name of a municipality or borough within a state in the PROVINCE_2 element. For example, the locality of `Ciudad de México` is within the borough of `Iztacalco` in Mexico City.

Input and Result JSON in Address Verification (On-Premises)

The following example shows how you can map the address information to the JSON address elements in Address Verification (On-Premises).

You enter the following input address:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
   "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "CALLE JUAREZ" } ],
          "HouseNumber": [ { "Value": "99" } ],
          "Locality": [
            { "Value": "CUAUHTEMOC" }, { "Value": "FRACC. HECTOR VALDEZ" }
          ],
          "PostalCode": [ { "Value": "31543" } ],
          "AdministrativeDivision": [
            { "Value": "CHIH." }, { "Value": "CUAUHTEMOC" }
          ],
          "Country": "MEXICO"
        }
      }
    ]
  }
}
```

Informatica Address Verification (On-Premises) returns the following result:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
  "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "CALLE JUAREZ" } ],
          "HouseNumber": [ { "Value": "99" } ],
          "Locality": [
            { "Value": "CUAUHTEMOC" }, { "Value": "FRACC. HECTOR VALDEZ" }
          ],
          "PostalCode": [ { "Value": "31543" } ],
          "AdministrativeDivision": [
            { "Value": "CHIH." }, { "Value": "CUAUHTEMOC" }
          ],
          "Country": "MEXICO"
        }
      }
    ],
    "Outputs": [
      {
        "ResultInfo": {
          "ProcessStatus": "V",
          "ProcessModeUsed": "Batch",
          "DeliverAdditionalSuggestions": "No",
          "ResultCount": 1,
          "ResultCountOverflow": false,
          "ResultCountries": [ "MEX" ]
        },
        "Results": [
          {
            "Variants": [
```

```
                {
                  "StatusValues": {
                    "AddressType": "S",
                    "LanguageISO3": "SPA",
                    "UsedVerificationLevel": "All",
                    "MatchPercentage": "100.00",
                    "Script": "Native Primary",
                    "AddressCount": "",
                    "ResultQuality": 3
                  },
                  "AddressElements": {
                    "Street": [ { "Value": "CALLE JUÁREZ" } ],
                    "HouseNumber": [ { "Value": "99" } ],
                    "Locality": [
                      { "Value": "CUAUHTÉMOC" }, { "Value": "FRACC. HÉCTOR VALDEZ" }
                    ],
                    "PostalCode": [ { "Value": "31543" } ],
                    "AdministrativeDivision": [
                      { "Value": "CHIH." }, { "Value": "CUAUHTÉMOC" }
                    ],
                    "Country": [ { "Code": "MEX", "Name": "MEXICO" } ]
                  },
                  "PreformattedData": {
                    "PostalDeliveryAddressLines": [
                      { "Value": "CALLE JUÁREZ 99" }
                    ],
                    "PostalFormattedAddressLines": [
                      { "Value": "CALLE JUÁREZ 99" },
                      { "Value": "FRACC. HÉCTOR VALDEZ, CUAUHTÉMOC" }, { "Value": "31543
CUAUHTÉMOC, CHIH." }
                    ],
                    "PostalLocalityLine": { "Value": "31543 CUAUHTÉMOC, CHIH." }
                  }
                }
              ]
            }
          ]
        }
      ]
    }
}
```


Input and Result JSON in Address Verification

The following example shows how you can verify a Mexico address in a REST call to Address Verification.

You submit the following request:


```
{
  "Login": *****,
  "Password": *****,
  "CampaignId": "Campaign222",
  "UseTransactions": "TEST",
  "Request": {
    "Parameters": {
      "Mode": "Batch",
      "CountryDetermination": {},
      "DataSetDetermination": {},
      "CountrySets": [
        {
          "Process": {
            "AlternativeHandling": {
              "OutdatedAddresses": { "Match": "Off", "GetNewAddress": false },
              "AliasAddresses": { "Match": "Off" }
            },
            "VerificationLevel": {
              "PreferredVerificationLevel": "All",
              "MinimumVerificationLevel": "All"
            },
            "Geocode": { "SearchRadius": "50" },
```

```
            "Enrichments": {
              "Geocoding": {
                "Rooftop": false,
                "ArrivalPoint": false,
                "StreetCenter": false,
                "PostalCodeCenter": false,
                "LocalityCenter": false
              },
              "Global": false,
              "CountrySpecific": false,
              "CAMEO": false
            }
          }
        }
      ]
    },
         "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "CALLE JUAREZ" } ],
          "HouseNumber": [ { "Value": "99" } ],
          "Locality": [
            { "Value": "CUAUHTEMOC" }, { "Value": "FRACC. HECTOR VALDEZ" }
          ],
          "PostalCode": [ { "Value": "31543" } ],
          "AdministrativeDivision": [
            { "Value": "CHIH." }, { "Value": "CUAUHTEMOC" }
          ],
          "Country": "MEXICO"
        }
      }
    ]
  }
  }
}
```

Informatica Address Verification returns the following response:

```
{
    "Status": "Ok",
    "StatusDescription": "No error",
    "TransactionInfo": {
        "TotalTransactionsCharged": 1,
        "TransactionPools": [
            {
                "Type": "BATCH",
                "TransactionsCharged": 1
            }
        ]
    },
    "CampaignId": "Campaign222",
    "Response": [
        {
            "ResultInfo": {
                "ProcessStatus": "V",
                "ProcessModeUsed": "Batch",
                "DeliverAdditionalSuggestions": "No",
                "ResultCount": 1,
                "ResultCountOverflow": false,
                "ResultCountries": [
                    "MEX"
                ]
            },
            "Results": [
                {
                    "Variants": [
                        {
                            "StatusValues": {
                                "AddressType": "S",
                                "LanguageISO3": "SPA",
```

```
                    "UsedVerificationLevel": "All",
                    "MatchPercentage": "100.00",
                    "Script": "Native Primary",
                    "AddressCount": "",
                    "ResultQuality": 3
                },
                "AddressElements": {
                    "Street": [
                        {
                            "Value": "CALLE JUÁREZ"
                        }
                    ],
                    "HouseNumber": [
                        {
                            "Value": "99"
                        }
                    ],
                    "Locality": [
                        {
                            "Value": "CUAUHTÉMOC"
                        },
                        {
                            "Value": "FRACC. HÉCTOR VALDEZ"
                        }
                    ],
                    "PostalCode": [
                        {
                            "Value": "31543"
                        }
                    ],
                    "AdministrativeDivision": [
                        {
                            "Value": "CHIH."
                        },
                        {
                            "Value": "CUAUHTÉMOC"
                        }
                    ],
                    "Country": [
                        {
                            "Code": "MEX",
                            "Name": "MEXICO"
                        }
                    ]
                },
                "PreformattedData": {
                    "PostalDeliveryAddressLines": [
                        {
                            "Value": "CALLE JUÁREZ 99"
                        }
                    ],
                    "PostalFormattedAddressLines": [
                        {
                            "Value": "CALLE JUÁREZ 99"
                        },
                        {
                            "Value": "FRACC. HÉCTOR VALDEZ, CUAUHTÉMOC"
                        },
                        {
                            "Value": "31543 CUAUHTÉMOC, CHIH."
                        }
                    ],
                    "PostalLocalityLine": {
                        "Value": "31543 CUAUHTÉMOC, CHIH."
                    }
                }
            }
        ]
    }
]
}
```

```
        ]
    }
```

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The postal service in Mexico recognizes the following structure for a postal address:

```
Line 1: Street type, Street name, House number
Line 2: Neighborhood, Municipality
Line 3: Postal code, City, State
Line 4: Country
```

The sample address has the following format on an envelope or label:

```
PRIVADA UNIÓN 10
COL. AGRÍCOLA PANTITLÁN, IZTACALCO
08100 CIUDAD DE MÉXICO, CDMEX
MEXICO
```

Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Mexico addresses.

The following table lists the types of enrichment that you can add to a Mexico address:

Enrichment Type	Description
CAMEO	You can retrieve CAMEO profiles as enrichments for valid Mexico addresses. CAMEO profiles are consumer classification systems that provide socio-economic and demographic indicators about the residents at the address.
Geocoding	You can perform geocoding for Mexico addresses to the following levels of precision: - ArrivalPoint - Rooftop - Standard

Address Verification Tips and Best Practices

Mexico addresses often contain zonal indicators. Informatica Address Verification maps the zonal indicators to a Locality address element.

The following table lists the zonal indicators:

Zonal Indicators	Description
Ampliación	Extension
Barrio	Neighborhood
Centro	Centre
Ciudad, Cd.	City
Colonia, Col.	Neighborhood or Quarter

Zonal Indicators	Description
Congregación	Assembly, meeting
Conjunto Habitacional, Conjunto Residencial	Housing complex, Residential complex
Ejido	Cooperative
Fraccionamiento, Fracc.	Division, development
Hacienda	Estate, ranch
Parque Industrial	Industrial Park
Pueblo	Village, small town
Rancho, Lechería	Ranch, Dairy
Sección, Secc.	Section
Sector, Sect.	Section
Unidad	Unit
Unidad Habitacional	Housing unit
Villa	Town

Mexico addresses can contain multiple terms and abbreviations. The following table lists a range of terms or abbreviations with the descriptions:

Term or Abbreviation	Description
Estado	State
Municipio	Municipality (major subdivision of estado, similar to a county)
Localidad	City or town within a municipio
Población	A populated place (city, town, or village)
Delegación	Administrative division of a city, such as a borough
Asentamiento	Subdivision of a municipio
Apartado	Apartado Postal, Apartado de Correos, Casilla Postal (Post Office Box)
Calle	Street
CP	Código Postal (postal code)

A Mexico postal code consists of five digits. Each digit corresponds to a geographical area of the country. The first two digits indicate a neighborhood. The third digit indicates an important town or city, a municipality, or one of the ten areas

into which a city is divided. The fourth digit indicates a municipality, a suburb, or an estate within a town. The final digit indicates a group of blocks or the specific street address of a large user.

To parse the input address accurately, enter `Calle` before the street information when you enter the input address.

For optimum results, use the hybrid or partially-fielded input address format for the following address elements:

- Delivery Address Lines
- Locality
- Postal Code
- Province

Reference Address Databases

Informatica updates the Mexico reference address databases every quarter. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Mexico addresses:

- `MEX_ADV_VRF_BIA_000_6_x_0.MD6`. Batch and interactive data.
- `MEX_ADV_VRF_QCP_000_6_x_0.MD6`. QuickCapture data.
- `MEX_ADV_RLK_GTA_000_6_x_0.MD6`. GeocodeToAddress data.
- `MEX_ADV_ENR_GST_000_6_x_0.MD6`. Standard geocoding data.
- `MEX_ADV_ENR_GAP_000_6_x_0.MD6`. ArrivalPoint geocoding data.
- `MEX_ADV_ENR_GRT_000_6_x_0.MD6`. Rooftop geocoding data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, click the following links:

https://docs.informatica.com/data-as-a-service/address-verification-(on-premises)/6-4-0.html

https://docs.informatica.com/data-as-a-service/address-verification/6-4-0.html

Author

Dishari Dutta