How-To Library

Informatica

Address Verification 6.x Best Practices for Palestine

© Copyright Informatica LLC 2023, 2026. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

This document tells you how to connect the elements in a France address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in France.

Supported Versions

- Informatica Address Verification (On-Premises and Cloud) 6.0.and later

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result JSON in Address Verification (On-Premises). . . . 3
Input and Result JSON in Address Verification. . . . 5
Address Enrichments. . . . 7
Reference Address Databases. . . . 8
Additional Documentation Resources. . . . 8

Introduction

Informatica Address Verification can validate and enhance addresses in Palestine. This how-to article provides you with configuration information and best practices that you can implement when you verify addresses in Palestine. The best practices include advice on how to select the appropriate JSON elements for Palestine address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to identify the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Palestine addresses:

- BATCH
- INTERACTIVE
- QUICK CAPTURE

Character Set

Palestine reference address databases store address data in the Latin-1 script. By default, Informatica Address Verification returns the verified Palestine addresses in the Latin-1 script.

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The Palestine postal service recognizes the following structure for a postal address:

```
Line 1: RECIPIENT
Line 2: LOCALITY
Line 2: POST CODE
Line 3: COUNTRY
```

The following sample address illustrates the structure:

```
MAHMOUD AMEER
DEIR GHAZALA
JENIN P237
PSE
```

Key Address Elements

Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Locality
- Post Code
- Country

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information Example	Address Element
City	Dahiyat al Bareed	Locality
Post Code	P6100154	PostCode
Country	Palestine	Country

Input and Result JSON in Address Verification (On-Premises)

The following example shows how you can map the address information to the JSON address elements in Address Verification (On-Premises).

You enter the following input address:

```
{
  "Parameters": {
    "Mode": "Batch",
```

```
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
  "IO": {
    "Inputs": [
      {
          "AddressElements": {
          "DeliveryService": [ { "Value": "P.O. Box 102" } ],
          "Locality": [ { "Value": "Tulkarm" }, { "Value": "Iktaba" } ],
          "PostalCode": [ { "Value": "P327" } ],
          "AdministrativeDivision": [ { "Value": "Tulkarm" } ],
          "Country": "PSE"
        }
      }
    ]
  }
}
```

Informatica Address Verification (On-Premises) returns the following result:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
  "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "DeliveryService": [ { "Value": "P.O. Box 102" } ],
          "Locality": [ { "Value": "Tulkarm" }, { "Value": "Iktaba" } ],
          "PostalCode": [ { "Value": "P327" } ],
          "AdministrativeDivision": [ { "Value": "Tulkarm" } ],
          "Country": "PSE"
        }
      }
    ],
    "Outputs": [
      {
        "ResultInfo": {
          "ProcessStatus": "V",
          "ProcessModeUsed": "Batch",
          "DeliverAdditionalSuggestions": "No",
          "ResultCount": 1,
          "ResultCountOverflow": false,
          "ResultCountries": [ "PSE" ]
        },
        "Results": [
          {
            "Variants": [
              {
                "StatusValues": {
                  "AddressType": "P",
                  "LanguageISO3": "???",
                  "UsedVerificationLevel": "All",
                  "MatchPercentage": "100.00",
                  "Script": "Native Primary",
                  "AddressCount": "",
                  "ResultQuality": 3
                },
                "AddressElements": {
                  "DeliveryService": [ { "Value": "P.O. BOX 102" } ],
                  "Locality": [ { "Value": "Tulkarm" }, { "Value": "Iktaba" } ],
                  "PostalCode": [ { "Value": "P327" } ],
                  "AdministrativeDivision": [ { "Value": "Tulkarm" } ],
                  "Country": [ { "Code": "PSE", "Name": "PALESTINE" } ]
                },
                "PreformattedData": {
                  "PostalDeliveryAddressLines": [ { "Value": "P.O. Box 102" } ],
                  "PostalFormattedAddressLines": [
```

```
                    { "Value": "P.O. Box 102" }, { "Value": "P327 Tulkarm" }
                  ],
                  "PostalLocalityLine": { "Value": "P327 Tulkarm" }
                }
              }
            ]
          }
        ]
      }
    ]
  }
}
```

Input and Result JSON in Address Verification

The following example shows how you can verify a Palestine address in a REST call to Address Verification.

You submit the following request:

```
{
    "Login": *****,
    "Password": *****,
    "CampaignId": "Campaign222",
    "UseTransactions": "TEST",
    "Request": {
        "Parameters": {
            "Mode": "Batch",
            "CountryDetermination": {},
            "DataSetDetermination": {},
            "CountrySets": [
                {
                    "Process": {
                        "AlternativeHandling": {
                            "OutdatedAddresses": {
                                "Match": "Off",
                                "GetNewAddress": false
                            },
                            "AliasAddresses": {
                                "Match": "Off"
                            }
                        },
                        "VerificationLevel": {
                            "PreferredVerificationLevel": "All",
                            "MinimumVerificationLevel": "All"
                        },
                        "Geocode": {
                            "SearchRadius": "50"
                        },
                        "Enrichments": {
                            "Geocoding": {
                                "Rooftop": false,
                                "ArrivalPoint": false,
                                "StreetCenter": false,
                                "PostalCodeCenter": false,
                                "LocalityCenter": false
                            },
                            "Global": false,
                            "CountrySpecific": false,
                            "CAMEO": false
                        }
                    }
                }
            ]
        },
        "IO": {
            "Inputs": [
                {
                    "AddressElements": {
                        "DeliveryService": [
                            {
```

```
                                "Value": "P.O. Box 102"
                            }
                        ],
                        "Locality": [
                            {
                                "Value": "Tulkarm"
                            },
                            {
                                "Value": "Iktaba"
                            }
                        ],
                        "PostalCode": [
                            {
                                "Value": "P327"
                            }
                        ],
                        "AdministrativeDivision": [
                            {
                                "Value": "Tulkarm"
                            }
                        ],
                        "Country": "PSE"
                    }
                }
            ]
        }
    }
}
```

Informatica Address Verification returns the following response:

```
{
    "Status": "Ok",
    "StatusDescription": "No error",
    "TransactionInfo": {
        "TotalTransactionsCharged": 1,
        "TransactionPools": [
            {
                "Type": "BATCH",
                "TransactionsCharged": 1
            }
        ]
    },
    "CampaignId": "Campaign222",
    "Response": [
        {
            "ResultInfo": {
                "ProcessStatus": "V",
                "ProcessModeUsed": "Batch",
                "DeliverAdditionalSuggestions": "No",
                "ResultCount": 1,
                "ResultCountOverflow": false,
                "ResultCountries": [
                    "PSE"
                ]
            },
            "Results": [
                {
                    "Variants": [
                        {
                            "StatusValues": {
                                "AddressType": "P",
                                "LanguageISO3": "???",
                                "UsedVerificationLevel": "All",
                                "MatchPercentage": "100.00",
                                "Script": "Native Primary",
                                "AddressCount": "",
                                "ResultQuality": 3
                            },
                            "AddressElements": {
                                "DeliveryService": [
```

```
                        {
                            "Value": "P.O. Box 102"
                        }
                    ],
                    "Locality": [
                        {
                            "Value": "Tulkarm"
                        },
                        {
                            "Value": "Iktaba"
                        }
                    ],
                    "PostalCode": [
                        {
                            "Value": "P327"
                        }
                    ],
                    "AdministrativeDivision": [
                        {
                            "Value": "Tulkarm"
                        }
                    ],
                    "Country": [
                        {
                            "Code": "PSE",
                            "Name": "PALESTINE"
                        }
                    ]
                },
                "PreformattedData": {
                    "PostalDeliveryAddressLines": [
                        {
                            "Value": "P.O. Box 102"
                        }
                    ],
                    "PostalFormattedAddressLines": [
                        {
                            "Value": "P.O. Box 102"
                        },
                        {
                            "Value": "P327 Tulkarm"
                        }
                    ],
                    "PostalLocalityLine": {
                        "Value": "P327 Tulkarm"
                    }
                }
            }
        ]
    }
]
}
```


Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Palestine addresses.

The following table lists the types of enrichment that you can add to a Palestine address:

Enrichment Type	Description
Standard Geocoding	You can retrieve the standard, interpolated geocoordinates for valid Palestine addresses.

Reference Address Databases

Informatica updates the Palestine reference address databases every year. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Palestine every year:

- `PSE_ADV_VRF_BIA_000_6_x_0_<YYYY>_<MM>.ZIP`. Batch and interactive data.
- `PSE_ADV_VRF_QCP_000_6_x_0_<YYYY>_<MM>.ZIP`. QuickCapture data.
- `PSE_ADV_ENR_GST_000_6_x_0_<YYYY>_<MM>.ZIP`. Standard geocoding data.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, click the following links:

https://docs.informatica.com/data-as-a-service/address-verification-(on-premises)/6-8-0.html

https://docs.informatica.com/data-as-a-service/address-verification-(cloud)/6-8-0.html

Author

Priyanka Bhattacharya