How-To Library

Informatica

How to backup and restore Data Integration Hub repository and Power Center Repository Service

© Copyright Informatica LLC 2020, 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

This article explains the steps to backup and restore the metadata and publication repository of Data Integration Hub and the Power Center Repository Service.

Supported Versions

- Data Integration Hub 10.4.0

Table of Contents

Prerequisites. 2
Backup and Restore Data Integration Hub for Oracle Database. 2
Backup and Restore Data Integration Hub for SQL Server Database. 3
Backup and Restore PowerCenter Repository Service. 4
Post Import or Export, and Restore steps for PowerCenter Repository. 4

Prerequisites

Before you backup and restore data, you must perform the following steps:

1. A working environment of Data Integration Hub and PowerCenter.
2. You must have the following empty database schemas and users for Data Integration Hub:
   - Metadata repository
   - Publication repository
3. You must have an empty database schema and user for PowerCenter Repository Service if you want to use a different PowerCenter set up apart from the default one.

Backup and Restore Data Integration Hub for Oracle Database

Perform the following steps to backup and restore Data Integration Hub on Oracle Databases:

1. Shut down the Data Integration Hub services.
2. Take a backup of the existing Data Integration Hub metadata and publication repository databases using the following commands:
   a. Metadata repository. `expdp REPO_USERNAME/REPO_PWD@connection_identifierschemas=REPO DUMPFILE=REPO_BACKUP_FILE.dmp logfile=REPO_LOG_FILE.log;`

      For example, `expdpDIHREPO/DIHREPO@b2b12cschemas=DIHREPODUMPFILE=DIHREPO.dmp logfile=expdpREPO.log;`

   b. Publication repository. `expdp STAGE_USERNAME/STAGE_PWD@connection_identifierschemas=STAGE dumpfile=STAGE_Backup_file.dmp logfile=expdpStage_Log_file.log`

      For example, `expdp DIHSTAGE/DIHSTAGE@b2b12cschemas=DIHSTAGEdumpfile=DIHSTAGE.dmp logfile=expdpStage.log`

   A dump file with `.dmp` extension is created in the database server location. You can view the exact location in the export logs.

   Note: expdp is bundled with the oracle client. To verify, open the command prompt and type expdp.

3. Manually backup the docstore folder for filestore topics in the Data Integration Hub repository.
    a. Get the docstore location from the system property `dx.system.document.store.folder` from the Data Integration Hub repository that you need to backup.
    b. Keep a backup of this folder to copy it to the new Data Integration Hub instance location.
4. Start the Data Integration Hub services.
5. Copy the `.dmp` file to the new database location.
6. Use the following commands to restore the metadata and publication schemas:
    a. To import metadata repository. `impdp REPO_NEW_USERNAME/ REPO_NEW_PWD@Connection_Identifierremap_schema=REPO:REPO_NEW DIRECTORY=<.dmp file directory>dumpfile=REPO.dmp logfile=impdpREPO_NEW.log;`

    For example, `impdp DIHREPO_NEW/DIHREPO_NEW@b2b12c remap_schema=DIHREPO:DIHREPO_NEWdumpfile=DIHREPO.dmp logfile=impdpREPO_NEW.log;`
    b. To import publication repository. `impdp STAGE_NEW_USERNAME/ STAGE_NEW_PWD@connection_identifierremap_schema=STAGE:STAGE_NEWDIRECTORY=<.dmp file directory>dumpfile=STAGE_Backup_file.dmp logfile=impdpStaging_LogFileName.log;`

    For example, `impdp DIHSTAGE_NEW/DIHSTAGE_NEW@b2b12c remap_schema=DIHSTAGE:DIHSTAGE_NEW dumpfile=DIHSTAGE_NEW.dmp logfile=impdpSTAGING_NEW.log;`

    Note: impdp is bundled with the oracle client. To verify, open the command prompt and type impdp.

Backup and Restore Data Integration Hub for SQL Server Database

Perform the following steps to backup and restore Data Integration Hub metadata and publication repository databases:

1. Shut down the Data Integration Hub services.
2. Perform the following steps after connecting to the appropriate instance of the Microsoft SQL Server Database Engine:
    a. Expand the server tree in **Object Explorer**.
    b. Expand Databases, right-click the database name and select **Tasks** > **Back Up**.
3. In the **Source** section of the **General** page, select the **Copy-only backup** option. Select **Disk** from the **Back up to** menu in the **Destination** section.
4. Click **Add**.

    The **Select Backup Destination** dialog box appears.
5. Enter the file name and a valid directory. Use `.bak` file extension to simplify the classification of this file.
6. Click **OK**.

    The backup process begins.
7. After the backup is complete click **OK** to close the **SQL Server Management Studio** dialog box.
8. Manually backup the docstore folder for filestore topics in the Data Integration Hub repository.
    a. Get the docstore location from the system property `dx.system.document.store.folder` from the Data Integration Hub repository that you need to backup.
    b. Keep a backup of this folder to copy it to the new Data Integration Hub instance location.
9. Perform the following steps to restore the backup of the metadata and publication repository databases to a new database:
    a. In **Object Explorer**, connect to an SQL server database engine instance and expand that instance.

b. Right-click **Databases** and select **Restore Database**.

c. In the **Source** section of the **General** page, enter the source directory of the backup sets to restore.

The following options are available:

- **Database**. The list contains the backed-up databases according to the `msdb` backup history.

  Note: If the backup is taken from a different server, the destination server will not include the backup history information for the specified database. In such a situation, select **Device** to manually enter the file or device to restore.

- **Device**. Click **Browse** and the **Select backup devices** dialog box appears.
  - Select the media type as **File** from the **Backup media type** menu. Click **Add**.
  - Locate the back up file and click **OK**.
  - In the **Destination** section, the **Database** box automatically populates the database name to restore. Change the name of the database to the new Publication and Metadata database name.

d. In the **Options** page, select the following options:

- In the **Restore options** panel, select **Overwrite the existing database (WITH REPLACE)**.
- In the **Server Connections** section, select the **Close existing connections to destination database** check-box.

e. Click **OK**.

The restore process begins.

f. After the restore is complete click **OK** to close the **SQL Server Management Studio** dialog box.

Backup and Restore PowerCenter Repository Service

Refer to the following document to backup and restore the PowerCenter Repository Service.

https://docs.informatica.com/data-integration/metadata-manager/10-2/application-service-guide/powercenter-repository-management/backing-up-and-restoring-the-powercenter-repository.html

Post Import or Export, and Restore steps for PowerCenter Repository

Perform the following steps after you import or export, and restore PowerCenter repository:

1. Start the Data Integration Hub installer and install a fresh Data Integration setup.
   a. Select the **Use existing data integration hub repository** option for **Metadata Repository/Publication Repository**.
   b. Enter the schema users that were used during restore.
   c. Enter the required details and complete the installation.
2. Restore the filestore topics in the Data Integration Hub repository.
   a. If the folder path is the same as the backup path in the new Data Integration Hub instance, copy the folder contents to the new folder.
   b. If the same folder path does not exist, you must update the docstore location using the repoutil.bator repoutil.sh from `<DIH>\dx-tools\repoutil.bat` or `<DIH>\dx-tools\repoutil.sh` using the --docStore option and then copy the folder contents to the new docstore location.
3. Start the Data Integration Hub console after the Data Integration Hub installation is complete.

4. Update the metadata and publication repository connection (*DIH__REPO*, *DIH__STAGING*, and *DIH__STAGING__HADOOP*) details such as password, database name and connection string.

   This is to reflect the same credentials in the PowerCenter repository.
5. Update the following system properties:
   - pwc.domain.name
   - pwc.integration.service.name
   - pwc.repository.host
   - pwc.repository.password
   - pwc.repository.port
   - pwc.repository.service.name
   - pwc.repository.user.name
   - pwc.webservices.url

   Note: You must update the system properties manually as the installer doesn't update the system properties by default.
6. Restart the Data Integration Hub services.
7. Ensure that the DIH__REPO and DIH__STAGING test connection succeeds.
8. Data Integration Hub displays the restored data.

Author

Sindhu K K