

Informatica® Data Replication
9.8.0

Release Notes

Informatica Data Replication Release Notes
9.8.0
December 2018

© Copyright Informatica LLC 2018

Publication Date: 2018-12-14

Table of Contents

Introduction. iv

Chapter 1: Installation and Upgrades. 5

Chapter 2: Closed Enhancements. 6

Chapter 3: Fixes. 8

Chapter 4: Known Limitations. 12

Chapter 5: Informatica Global Customer Support. 17

Introduction

This document contains important information about enhancements, fixes, and known limitations in Informatica Data Replication 9.8.0.

CHAPTER 1

Installation and Upgrades

For information about installing or upgrading Data Replication, see the *Data Replication Installation and Upgrade Guide*.

CHAPTER 2

Closed Enhancements

The following table describes closed enhancement requests:

Enhancement	Description
IDR-3700	You can use the new extract.oracle.rds.fetch_archive_log_list_attempts runtime parameter to specify the maximum number of times that the Oracle Extractor retries its request for the list of archived redo log files from an Amazon RDS for Oracle instance. Use the new extract.oracle.rds.fetch_archive_log_list_timeout runtime parameter to specify the interval that the Extractor waits after a failed attempt before trying the request again.
IDR-3690	The Server Manager can now send the list of processed redo logs to the Extractor.
IDR-3648	When the SQLNET.RECV_TIMEOUT and SQLNET.SEND_TIMEOUT profile parameters are not specified in the sqlnet.ora configuration file, the Oracle Extractor can now use the new extract.oracle.receive_timeout and extract.oracle.send_timeout runtime parameters to determine the timeout intervals for receiving data from the database server and sending data to the database server.
IDR-3627	User activity in the Data Replication Console, in addition to network activity, now resets the timeout interval that is specified in the Server Manager SessionExpirationTimeout advanced property to the beginning of the interval.
IDR-3576	You can now use the Server Manager EnforcePasswordHistory advanced property to specify the number of unique new passwords that a user must define for a user account before an old password can be used again. The default value is 1.
IDR-3491	The Oracle Extractor now stores the headers of the archived redo log files and redo log files from backup sets that the Extractor already read from disk in a SQLite database. The Extractor uses cached headers instead of re-reading backup sets or redo log headers for faster processing. You can set the extract.oracle.use_log_file_header_cache runtime parameter to 0 to disable the caching of headers.
IDR-3370	Data Replication now deletes Avro schema cache files when you clean replication processing information for a configuration that has a Kafka target. The overflow subdirectory that contains Avro schema cache files is now created in the *DataReplication_installation*/output/*replication_configuration* directory.
IDR-3211, IDR-3210	Data Replication now supports MemSQL targets.
IDR-3152	Data Replication can now extract change data from archived redo logs in backup sets that are created by the Recovery Manager (RMAN) utility.
IDR-3120	Data Replication now supports Microsoft SQL Server sources on Linux.

Enhancement	Description
IDR-2860, IDR-2859	On the **Extract Range** tab, if you specify multiple locations of Oracle archived redo logs, the Data Replication Console assigns priorities to the locations based on their order. The Extractor uses the priorities to determine the location from which to read redo logs. To change the priority of a location, drag the location to another position in the list.
IDR-3679	You can set the new show_save_sm_password parameter to false in the default.cfg file if you want to hide the **Save** check box next to the Server Manager **Password** field on the **Server Manager** tab > **Configs** view to make sure that users type their passwords each time they connect to the Server Manager.
IDR-1914	For Microsoft SQL Server sources, Data Replication can now capture data from compressed backups of transaction logs.

CHAPTER 3

Fixes

The following table describes fixed limitations:

Bug	Description
IDR-3916	The Oracle Extractor might end with an error or corrupt a replication configuration when processing ALTER TABLE or ALTER INDEX operations that include objects with non-Latin names.
IDR-3915	The Oracle Extractor might incorrectly process Quick Multi Insert (QMI) records with trailing NULL values. If the mapped target columns have default values, these records might be applied on the target with the default values instead of NULL values.
IDR-3906	The Applier ends with an error when applying data from DB2 TIME columns to Apache Kafka targets.
IDR-3899	After you set the DBPasswordEncryptionEnabled advanced property to 1, the Server Manager ends abnormally and generates a core file when a replication configuration is accessed.
IDR-3894	For configurations that have a single source and multiple targets, the target Server Manager instance deletes intermediate files after you delete a target in the configuration.
IDR-3882	For configurations that have an Oracle source and target and include virtual columns with Tcl scripts, InitialSync ends abnormally and generates a core file if the Tcl scripts use the ::dbs::transaction::user_id и ::dbs::transaction::user_name commands.
IDR-3875, IDR-3837	The Oracle Extractor might extract corrupted data from chained rows. The problem occurs if only some of the source columns use Oracle Transparent Data Encryption (TDE).
IDR-3833	For Microsoft SQL Server source tables that contain binary LOB columns, InitialSync attempts to get more than one row in a single fetch when the initial.lob_prefetch_threshold has the default value of 0.
IDR-3830	The Oracle Extractor might incorrectly process Update operations for rows that contain trailing null values.
IDR-3815	The Applier for Amazon Redshift targets fails if it is missing the Oracle libclntsh.so library.
IDR-3814	The Oracle Extractor does not decrypt QMI records that use Transparent Data Encryption (TDE). Consequently, the Applier ends with an error when applying these records.
IDR-3811	The Oracle Extractor might incorrectly process Update operations on encrypted tables that have primary keys with NO SALT columns.
IDR-3794	The Data Replication Console does not show information about schedules and tasks on the **Server Manager** tab > **Event Viewer** view > **Logs of Schedules** subtab if the console user is not the idradmin user and if the listed objects are owned by other users.

Bug	Description
IDR-3776, IDR-1706	Previously, the Data Replication Console included all source columns, including the unnecessary unmapped columns, in the Avro schema files that it generated for consumers of Apache Kafka target topics. Now, the Data Replication Console includes only the mapped columns.
IDR-3767, IDR-3395	An Oracle Extractor that is running in continuous mode might hang if it encounters an error when trying to read redo logs from an Amazon RDS for Oracle source.
IDR-3748	If multiple scripts that use the Server Manager CLI commands attempt to update the state.dat file simultaneously, the scripts might end with an I/O error.
IDR-3747	The Applier ends with an error when applying DB2 BIGINT data to Apache Kafka targets.
IDR-3739	The Microsoft SQL Server Extractor ends with an error and generates a core file if it cannot find the certificate that is specified in the replication configuration.
IDR-3737	If you drop a Microsoft SQL Server source database and then create it again, the Server Manager might fail to change the CDC setting for a source table. The problem occurs if you changed the setting before the database was dropped.
IDR-3736	The Applier ends with an error when applying data from Microsoft SQL Server TIME columns to Apache Kafka targets.
IDR-3735	For configurations that have a DB2 source and Apache Kafka target, the Applier ends with an error when processing records with DB2 BIGINT values of 10 or more digits.
IDR-3731	After the session between the Data Replication Console and the Server Manager times out, the Console allows users to edit their passwords but does not send the changes to the disconnected Server Manager.
IDR-3730	After the session between the Data Replication Console and the Server Manager times out, the Console allows users to connect to the Server Manager without entering a password, even if the show_save_sm_password parameter is set to false in the default.cfg file. This issue occurs if two instances of the Console are open simultaneously and the show_save_sm_password parameter is set to false in only one of the instances.
IDR-3725	The Oracle Extractor might incorrectly process Updates for chained rows and not write UNDO values to the Update records in the intermediate file. In this case, the Applier ends with an error.
IDR-3710	For configurations that have a Microsoft SQL Server source and target, Data Replication might change the order of columns in a composite, non-unique clustered index on the target database when replicating the CREATE INDEX operation.
IDR-3702	The Microsoft SQL Server Extractor writes misleading warning messages when processing CREATE TABLE operations. This issue occurs if a schema mapping for DDL replication is created but the CREATE TABLE option is not selected.
IDR-3686	If the Server Manager runs as a daemon on Linux or UNIX, it ignores the umask command in the Server Manager startup script. In this case, the Server Manager always creates the logs with the umask(0) default permissions. This setting allows logs to be created as world-writable files, which is not secure.
IDR-3681	If you enter a Server Manager password in the Data Replication Console and then specify show_save_sm_password=false in the default.cfg file, the password is still displayed on the **Server Manager** tab > **Configs** view the next time you log in.

Bug	Description
IDR-3651	The Oracle Extractor might incorrectly parse a redo record for a chained row as a Delete record instead of skipping it. In this case, data loss might occur.
IDR-3635	The Applier for Apache Kafka targets does not ignore the apply.loader_multiple_load_passes runtime parameter. As a result, data loss might occur on the target.
IDR-3632	When a task log window for a running Data Replication task is open in the Data Replication Console, the Server Manager TCP/IP session does not time out and the Data Replication Console does not disconnect from the Server Manager.
IDR-3623	The Kafka Applier ends with an error if the transaction ID value is longer than the maximum length of the Java Long data type.
IDR-3622	If the Applier runs in continuous mode, it might not apply TRUNCATE TABLE operations to the target database. This issue occurs if the replication of TRUNCATE TABLE operations is enabled after the Applier is already running.
IDR-3606	The DB2 Extractor might end with an error when processing compressed UNDO UPDATE, UNDO INSERT, or UNDO DELETE records.
IDR-3601	Upgrading Data Replication might take a long time if existing replication configurations include many records about processed Oracle redo log files.
IDR-3598	The Server Manager does not log sufficient information about SQLite database errors.
IDR-3582	When generating an Avro Schema definition, the Apache Kafka Applier incorrectly identifies the primary key columns if some of the source columns that occur prior to the primary key columns are not mapped to the target.
IDR-3568	The first time the Applier runs, it does not print the error message IDR-070230 if a row count mismatch occurs.
IDR-3558	If you add a source table to a replication configuration while the Applier is running in continuous mode, the Applier might end with an error. The error occurs when the source table has an open transaction.
IDR-3552	The Microsoft SQL Server Extractor ends with an error and generates a core file if the source tables are in a SQL Server Always On availability group and a failover occurs.
IDR-3546	The DB2 Extractor ends with an error and generates a core file when using a database alias to connect to a DB2 source database. This error occurs if the specified alias name is not present in the list of aliases on the system where the Extractor runs.
IDR-3544	The DB2 Extractor ends with an error when processing compressed Delete records that do not have the propagatable flag set in the log record header. This error occurs if the extract.db2.enable_row_compression_support runtime parameter is set to 1 and the extract.db2.filter_option_forced parameter is set to 0.
IDR-3531	The Oracle Extractor might fail to process some of the records in a redo log file if an error occurs when the Extractor is reading the log file from an Amazon Relational Database Service (RDS) for Oracle instance. In this case, data loss might occur.
IDR-3522	After you use InitialSync to resynchronize some but not all mapped source tables in a configuration, the Applier might skip the processing of one or more intermediate files if the files include open transactions or if the Applier starts a recovery cycle.

Bug	Description
IDR-3517	The Oracle Extractor might end with an error and generate a core file when processing a rollback for a CREATE TABLE operation.
IDR-3510	For configurations that have Oracle sources, the Applier does not apply Update operations that change trailing null values. This problem occurs because the Oracle Extractor incorrectly processes redo records for Updates of columns that are part of a supplemental log group but that are not defined in the redo record. The Applier cannot build a where clause for the Update operation.
IDR-3495	The reset_idradmin command-line parameter for the Server Manager does not reset the password for the idradmin account.
IDR-3467	The Oracle Extractor does not process TRUNCATE operations that occurred on the source prior to re-saving the replication configuration.
IDR-3464	If you clean a replication configuration and then add or delete log locations on the **Extract Range** tab, the Extractor ignores the changes to the log locations.
IDR-3439	During the first run of the Applier in Audit Apply mode, the Applier does not use the Sync SCN value to process virtual columns.
IDR-3424	The Oracle Extractor does not process ALTER TABLE *table* SET UNUSED *column* statements correctly. If you delete the unused column from the source table, the Extractor corrupts the configuration SQLite database file.
IDR-3406	The Microsoft SQL Server Extractor might end with an error that reports 'Metadata load failed' when processing a DDL operation. This problem occurs if the DDL operation is preceded by ALTER TABLE operations in the same transaction.
IDR-3388	For configurations that have an Apache Kafka target, Data Replication might fail to delete processed intermediate files. This problem occurs if the Applier encounters two transactions that were opened in the same apply cycle but closed in different apply cycles.
IDR-3377	Error message IDR-030051 does not clearly explain why the Oracle Extractor excluded some redo log files from processing. A specific reason is needed.
IDR-3360	InitialSync and the Applier cannot connect to Amazon Redshift targets that use AWS Signature Version 4.
IDR-3351	If the Oracle Extractor encounters an incorrect redo log poll value, it does not write an error message that contains stack trace information to the Extractor message log.
IDR-3343, IDR-1686	For configurations that have a DB2 source, the Data Replication Console does not reset the db2.initial_lsn runtime parameter after cleaning a replication configuration. Consequently, the Extractor does not process the Extractor Start Point correctly.
IDR-3198	The Data Replication Console displays a warning message about offline redo threads for Oracle RAC sources each time you save a replication configuration. It should display the message only the first time the Extractor is started after an upgrade.
IDR-3185	An Oracle Extractor that runs on a big-endian system might incorrectly determine the SCN value of a redo record from a redo log file that was created on a little-endian system.
IDR-3145	The Data Replication Console deletes information about an Oracle ASM connection from the replication configuration if the Console is not connected to the Oracle ASM instance when you save the edited configuration.

CHAPTER 4

Known Limitations

The following table describes known limitations:

Bug	Description
IDR-3925	An Extractor task that runs in continuous mode and extracts data from a remote MySQL database server fails to create intermediate files that contain the extracted change data. As a result, no change data is sent to the target database. Workaround: Run the MySQL Extractor task on demand or schedule the task to run periodically.
IDR-3157	For Vertica 9 targets, an Applier or InitialSync process that runs on Solaris might hang or end abnormally with a core file. Workaround: Install the DataDirect ODBC driver v.4.1.19 for Vertica targets.
IDR-3056	For configurations that have an Oracle source and target, InitialSync performance becomes degraded when synchronizing tables that include LOB columns. This performance issue does not occur in Data Replication 9.7.0 HotFix 1.
IDR-1843	For configurations that have a MySQL source and an Apache Kafka, Cloudera, Flat File, or Hortonworks target, the Data Replication Console allows you to map source columns that have unsupported data types, such as JSON or spatial data types. Mapped columns with unsupported data types cause the Extractor to end with an error. Workaround: In the Data Replication Console, do not map MySQL source columns with unsupported data types when you create a configuration that has an Apache Kafka, Cloudera, Flat File, or Hortonworks target.
IDR-1680 IDR-1670 IDR-1625 IDR-1611 IDR-589	For all source types, Data Replication does not support the use of non-Latin characters or special characters in source object names. If these characters are used in object names, Data Replication tasks might end abnormally. (424492)
IDR-1633	If you do not use InitialSync to materialize targets, either by choice or because InitialSync is not supported for the target type, Data Replication does not set the Sync Point from which the Applier starts applying change data to the targets. In this case, all of the data extracted from the current source log file that contains the Extractor Start Point is applied to the target, including data earlier than the synchronization point. For Apache Kafka, Cloudera, Flat File, and Hortonworks targets that do not use InitialSync, the Applier always applies all of the data extracted from the current source log file, unless you manually set the Sync Point for apply processing. Workaround: To avoid replicating all data from the beginning of the current source log file to targets for which the Sync Point was not generated during initial synchronization, manually set the Applier Sync Point for each mapped target table before starting the Apply task.

Bug	Description
IDR-1585	Data Replication cannot replicate change data or DDL operations for MySQL source columns with the unsigned FLOAT or DOUBLE data type to Oracle targets. You cannot map these columns in the Data Replication Console. Any DDL operation that adds or alters these columns is ignored. Workaround: For DDL changes, edit the DDL statements to omit the unsigned FLOAT or DOUBLE data types or change them to a supported data type. Then run the DDL statements on the target instead of using Data Replication to replicate the DDL changes.
IDR-1552	For configurations that have Oracle sources and Apache Kafka, Cloudera, Flat File, Hortonworks, or Oracle targets, if a source column contains a TIMESTAMP WITH LOCAL TIMEZONE data type with a value of 0001-01-01, Data Replication might produce an invalid year value in the target column. Workaround: Substitute a virtual column for any date column that could have a value of 0001-01-01. For Apache Kafka, Cloudera, Flat File, or Hortonworks targets, use a Tcl expression to handle the condition. For Oracle targets, you can use a SQL script. For example, add 1 to the day if the column value could produce a year value of 0 in the target column after conversion to UTC, or substitute a null value or a hard-coded constant. Alternatively, filter out all source table rows that contain date values of 0001-01-01.
IDR-1121	The Applier and InitialSync can run the ./support/tcl/dbs_worker_start.tcl and ./support/tcl/dbs_worker_end.tcl scripts only if the replication configuration includes one or more virtual columns with assigned Tcl scripts. Workaround: If your configuration does not include virtual columns with assigned Tcl scripts and you want the Tcl Script Engine to run the dbs_worker_start.tcl or dbs_worker_end.tcl script, perform the following steps: 1. Add a virtual column to any mapped table in the replication configuration. 2. Assign an empty Tcl script to the added virtual column. **Note:** You can leave the added virtual column unmapped. (464743)
IDR-874	Microsoft SQL Server target databases always use the database server collation to interpret character data that the Applier loads to the target tables. If the character set of the source character data does not match the collation of the SQL Server target database server, the replicated character data on the target will be corrupted. Workaround: Ensure that the character set of the source data matches the collation of the target database server. To determine the collation of the SQL Server database server, execute the following SQL statement on the target: `SELECT CONVERT (varchar, SERVERPROPERTY('collation'));`
IDR-807	If you specify a custom connection string that contains a user name and password but do not specify the same user name and password in the **Username** and **Password** fields for the target, the Applier or InitialSync might fail to connect to the target database. This problem occurs when the Applier or InitialSync uses the native database load utility instead of an ODBC driver. InitialSync uses the native database load utility if the initial.enforce_odbc_load runtime parameter is set to 0. The Applier always uses the native database load utility in Merge Apply mode and also uses the utility in Audit Apply mode if the apply.direct_load_for_audit_tables runtime parameter is set to 1. Workaround: If you specify a custom connection string that contains a user name and password, specify the same user name and password in the **Username** and **Password** fields.
IDR-742	For Oracle 12*c* sources, if you clear the **Read from online logs** option on the **Extract Range** tab and select the **Force log switch** option for the database connection on the **Source Database** tab or from the **Server Manager** tab > **Connections** view, the Extractor runs the ALTER SYSTEM ARCHIVE LOG CURRENT command to archive online redo logs. If the Extractor connects to a multitenant pluggable database (PDB), the command ends with an error because the Extractor has insufficient privileges to run the command in this situation. Workaround: Clear the **Force log switch** option in the Data Replication Console. (446765)

Bug	Description
IDR-710	If an InitialSync task ends with an error or in response to the **Abort Task** option when loading source data to a Teradata target, the task might lock the target tables. If the target tables are locked, during subsequent attempts to restart InitialSync, the InitialSync task ends with the following error: `error 2652:Operation not allowed: schema_name.table_name is being Loaded.` Workaround: Before you restart the initial synchronization, resolve any problem that led to the abnormal completion of the task. Then, perform one of the following steps: - Wait until the Teradata target closes the orphaned TPT load session and unlocks the target tables. The default session timeout period is 20 minutes. - Ask your DBA to log off the orphaned TPT load sessions. - Drop the locked tables and re-create the tables on the Teradata target. (444572)
IDR-706	For Oracle 11*g* R2 and later sources, Data Replication does not support LZO lossless compression of source LOB data in SecureFile storage if the compression option is set to LOW. The Extractor replaces each byte of LZO-compressed data with the character "A." Workaround: If an Oracle source includes LOB data in SecureFile storage, either use the Oracle advanced LOB compression option of MEDIUM or HIGH or use the NOCOMPRESS option. (444475)
IDR-667	If you map a source column that has a date or time data type to a target column that has a date or time data type with a longer format, the Applier and InitialSync add random characters to the source values so that the lengths of these values are consistent with the date or time format on the target. The characters that the Applier and IntialSync add might differ. In this situation, if the source date or time columns are part of a primary key or unique index, the Applier does not correctly apply Updates and Deletes to the target. Workaround: Do not add date and time columns to a primary key or unique index in the source database if the corresponding target columns have a longer format. (438629)
IDR-661	For DB2 targets, the Applier might return a row count mismatch when updating or deleting primary key columns that have FLOAT, DOUBLE, or other data types without a specified scale. (437378)
IDR-633	For Netezza, Teradata, and Vertica targets, the Applier cannot replicate an ALTER COLUMN DDL operation that decreases the size of a column in a mapped source table. Workaround: To replicate the ALTER COLUMN operation, manually add a new target column that matches the definition of the altered source column and that contains the data of the altered source column. Then drop the original target column and rename the new column to the original target column name. (432129)
IDR-617	When the Applier or InitialSync loads floating-point numbers from source columns that have data types such as DOUBLE, FLOAT, or REAL, the target database rounds the floating-point numbers. If these source columns are part of a primary key or unique index, the Applier then incorrectly applies Updates and Deletes to the target. Workaround: Do not add source columns that contain floating-point numbers to a primary key or unique index in the source database. (428880)
IDR-507	For configurations with a single source and multiple targets, if you specify multiple filter conditions on the **Routing** tab > **Filters** subtab that affect the same column in the same table, Data Replication does not process all of the filter conditions for the column. Workaround: Do not create multiple filter conditions that affect the same column in a target table. (406425)

Bug	Description

IDR-481	The Tcl Script Engine does not support null values. If you use a Tcl script in a replication configuration and the script processes a record that has a null redo or undo value, the ::dbs::get_redo and ::dbs::get_undo commands return corrupted data instead of a null value. Consequently, the Applier or InitialSync either loads corrupted data to the target or ends with an error.
	Workaround: Use the combination of ::dbs::has_redo and ::dbs::record::redo_is_null commands to determine whether the redo data for a source column is null. Then use the ::dbs::create_stream command to apply the null value to the target column. For example, use the following script to update the O2O_DATE_NULL_T column on the target with a null value:
	`set r_col REAL_COLUMN_NAME`
	`if {[::dbs::has_redo $r_col] == 1 } {`
	`if {[::dbs::record::redo_is_null $r_col] == 1} {`
	`set sql_stmt "update TEST.O2O_DATE_NULL_T set s_date=NULL where s_pk=2"`
	`} else {`
	`set vc [::dbs::get_redo $r_col]`
	`set sql_stmt "update TEST.O2O_DATE_NULL_T set s_date=to_date('$vc','YYYY-MM-DD HH24:MI:SS') where s_pk=2"`
	`}`
	`set stream2 [::dbs::create_stream -dst $sql_stmt]`
	`::dbs::delete_stream $stream2`
	`}`
	(403272)

IDR-386	Data Replication replicates empty strings as null values to Greenplum, Vertica, and Netezza targets. (396010)
IDR-376	On UNIX, the Applier and InitialSync end abnormally and generate a core file when processing a Tcl script that performs mathematical operations with values that have numeric data types. (394900)

IDR-371	After an ADD COLUMN ... DEFAULT NOT NULL operation occurs on an Oracle 11*g* source, Oracle does not update existing table rows with the default value. Instead, Oracle writes the default value to the system dictionary ecol$. Consequently, redo records for subsequent DML operations on the table rows contain NULL undo values for the added column.
	Workarounds: Perform one of the following actions:
	- Run the following SQL statement to update the default value for the table rows:
	`UPDATE source_table SET added_column_name=added_column_name;`
	In this statement, both occurrences of *added_column_name* match the name of the column that you added. Oracle then starts writing actual undo values to the redo records.
	- Run the following command to disable the Oracle optimization before adding columns with the DEFAULT NOT NULL clause:
	`ALTER SESSION SET "_add_col_optim_enabled"=FALSE;`
	(394695)

IDR-360	When deploying a configuration from test to production, if you replace two different schemas in the test environment with one schema in the production environment, you cannot open the deployed configuration in the production environment from the Data Replication Console. The configuration is corrupted. (394197)
IDR-175	If the Oracle source database stops responding because the archive log destination is full, the Extractor task does not end abnormally as expected. Workaround: Use a third-party application to notify the Oracle database administrator of insufficient disk space in the archive log destination directory. (355669)
IDR-162	For Microsoft SQL Server sources and targets, InitialSync incorrectly handles non-Latin object names. If a Microsoft SQL Server source or target uses non-Latin object names, InitialSync does not materialize the target tables from the source tables. (352067)

Bug	Description
IDR-161	For configurations that have an Oracle source and include Tcl scripts, if you set the initial.oracle.parallel_sample_percentage runtime parameter to a value other than 0, InitialSync might end abnormally. (351690)
IDR-141	On Linux and UNIX systems, Data Replication might end abnormally if the ODBCINST environment variable points to an existing directory instead of to the odbcinst.ini file. (346875)
IDR-136	The Applier ends abnormally when processing Updates and Deletes for tables with fixed-length columns that are part of a logical primary key if the source and target column lengths differ. This error occurs because of trailing spaces in these columns. (346407)
IDR-81	For Oracle sources, the Extractor processes the archive log or online redo log that includes the Start SCN value from the beginning of the log. If the Start SCN value that the Data Replication Console calculated or that you manually set in the configuration is located in the middle of the Oracle log, Extractor processing of CREATE TABLE operations incorrectly starts from the beginning of the log that includes the Start SCN value. (334817)
IDR-56	Data Replication does not support Internet Protocol version 6 (IPv6). (330287)
IDR-47	For targets other than Netezza, InitialSync truncates source character data on the first occurrence of a null byte (0x00). (326310)
IDR-28	For configurations with a Microsoft SQL Server source, Data Replication does not replicate LOB values when replicating CREATE TABLE ... AS SELECT operations that create a table based on another table that contains LOB columns. (316579)

CHAPTER 5

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through Online Support on Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
http://www.informatica.com/us/services-and-training/support-services/global-support-centers.

If you are an Informatica Network member, you can use Online Support at http://network.informatica.com.