How-To Library

Informatica

# Best practices for using cloud storage to archive data in Data Archive

© Copyright Informatica LLC 2021, 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

# Abstract

You can use Data Archive to archive your data to cloud storage. This article describes some best practices to follow when you archive data to different cloud storage types.

# Supported Versions

- Data Archive 6.5.1

# Table of Contents

Overview. . . . . 2
EMC Centera and EMC Atmos. . . . . 2
Hitachi Content Platform. . . . . 3
Hadoop Distributed File System. . . . . 4
Amazon S3. . . . . 4
AWS S3. . . . . 5
Microsoft Azure. . . . . 6

# Overview

When you create a target connection to archive data, the connection can point to a database or to the Data Vault.

You can create a Data Vault on an external storage platform and configure the archive store type for the Data Vault target connection. The archive store type indicates the storage platform for the Data Vault. You can choose a cloud storage from the list of cloud storage options.

When you archive data to a cloud storage, depending on your setup, you must ensure that you download the required library files and configure the server for optimal performance.

# EMC Centera and EMC Atmos

You can archive data to EMC Centera and EMC Atmos cloud storage platforms.

When you archive data to EMC Centera or EMC Atmos, employ the following best practices:

- Download Centera SDK version 3.3.718 or later.
- To avoid network latency, use storage buckets that are created or stored in the same region as the client. If you experience communication errors between the Data Vault and external storage, ensure that the network latency is low for Data Vault to perform optimally.
- On RHEL and SUSE Linux Enterprise machines, clear the cache memory periodically and when you perform operations such as running a report or browsing data.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- Increase the ulimit values on RHEL and SUSE Linux Enterprise machines based on the workload. For example, the number of jobs running in parallel, or the number of open files.
- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive

storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
See the *Data Vault Administrator Guide* for information on how to migrate archived data.

- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

## Hitachi Content Platform

When you archive data to Hitachi Content Platform, employ the following best practices:

- Informatica does not ship the cURL library files with Data Archive. To use a secure HTTPS protocol, download a version of the cURL library that supports SSL.
  Download the following library versions:

  openssl-1.1.1k

  libssh2-1.9.0.tar.gz

  curl-7.74.0

  See the Knowledge Base article for more information.
- To avoid network latency, use storage buckets that are created or stored in the same region as the client. If you experience communication errors between the Data Vault and external storage, ensure that the network latency is low for Data Vault to perform optimally.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- Increase the ulimit values on RHEL and SUSE Linux Enterprise machines based on the workload. For example, the number of jobs running in parallel, or the number of open files.
- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
  See the *Data Vault Administrator Guide* for information on how to migrate archived data.
- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

## Hadoop Distributed File System

When you archive data to a Hadoop Distributed File System cloud storage, employ the following best practices:

- The Data Vault service requires the following libhdfs files:

  commons-logging-api-1.0.4.jar

  hadoop-0.20.2-core.jar

  libhdfs.so

- On RHEL and SUSE Linux Enterprise machines, clear the cache memory periodically and when you perform operations such as running a report or browsing data.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- Increase the ulimit values on RHEL machines based on the workload. For example, the number of jobs running in parallel, or the number of open files.
- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
  See the *Data Vault Administrator Guide* for information on how to migrate archived data.
- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

## Amazon S3

When you archive data to Amazon S3 cloud storage, employ the following best practices:

- Informatica does not ship the cURL library files with Data Archive. To use a secure HTTPS protocol, download a version of the cURL library that supports SSL.
  Download the following library versions:

  openssl-1.1.1k

  libssh2-1.9.0.tar.gz

  curl-7.74.0

  See the Knowledge Base article for more information.
- To avoid network latency, use storage buckets that are created or stored in the same region as the client. If you experience communication errors between the Data Vault and external storage, ensure that the network latency is low for Data Vault to perform optimally.
- On RHEL and SUSE Linux Enterprise machines, clear the cache memory periodically and when you perform operations such as running a report or browsing data.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- Increase the ulimit values on RHEL and SUSE Linux Enterprise machines based on the workload. For example, the number of jobs running in parallel, or the number of open files.

- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
  See the *Data Vault Administrator Guide* for information on how to migrate archived data.
- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- To avoid limitations on external storage, ensure that the SCT file size does not exceed 5 GB.
- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations for curl error codes:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

  See the curl error code documentation to understand why the errors occur and what you can do to fix the issue.

## AWS S3

When you archive data to AWS S3 cloud storage, employ the following best practices:

- Informatica does not ship the cURL library files with Data Archive. To use a secure HTTPS protocol, download a version of the cURL library that supports SSL.
  Download the following library versions:

  openssl-1.1.1k

  libssh2-1.9.0.tar.gz

  curl-7.74.0

  See the Knowledge Base article for more information.
- To avoid network latency, use storage buckets that are created or stored in the same region as the client. If you experience communication errors between the Data Vault and external storage, ensure that the network latency is low for Data Vault to perform optimally.
- On RHEL machines, clear the cache memory periodically and when you perform operations such as running a report or browsing data.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- Increase the ulimit values on RHEL and SUSE Linux Enterprise machines based on the workload. For example, the number of jobs running in parallel, or the number of open files.
- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
  See the *Data Vault Administrator Guide* for information on how to migrate archived data.
- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- To avoid limitations on external storage, ensure that the SCT file size does not exceed 5 GB.

- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations for curl error codes:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

  See the curl error code documentation to understand why the errors occur and what you can do to fix the issue.

# Microsoft Azure

When you archive data to Microsoft Azure cloud storage, employ the following best practices:

- Informatica does not ship the cURL library files with Data Archive. To use a secure HTTPS protocol, download a version of the cURL library that supports SSL.
  Download the following library versions:

  openssl-1.1.1k

  libssh2-1.9.0.tar.gz

  curl-7.74.0

  See the Knowledge Base article for more information.
- To avoid network latency, use storage buckets that are created or stored in the same region as the client. If you experience communication errors between the Data Vault and external storage, ensure that the network latency is low for Data Vault to perform optimally.
- Increase the MEMORY and MAXVEM values in the ssa.ini file depending on the size of the sct file on which you run the query. For information, see the Knowledge Base article.
- When you retire an application with a large volume of data that includes LOB columns, perform extractor, loader, integrated validation, and retention policy in one job on a LOCAL/SAN/NAS/DAS/ network drive storage. When the job completes successfully, use the `ssamigrate` utility to migrate the archived data from the LOCAL/SAN/NAS/DAS/network drive storage to the cloud storage.
  See the *Data Vault Administrator Guide* for information on how to migrate archived data.
- You can exclude LOB columns when you run a report. BLOB data appears BLANK and CLOB data is visible to a certain limit in JReports.
- When you perform operations such as running a report query or browsing data for tables that contain huge data or LOB columns, ensure that no other operations are running in parallel.
- For information about why a job fails or stops, see the fas logs and the agent logs in the following locations:
  `<Data Vault installation directory>\fas_logs`

  `<Data Vault installation directory>\fas_agent_logs`

# Author

**Data Archive R&D**