Informatica® Data Privacy Management
10.5.10

REST API Reference

Informatica Data Privacy Management REST API Reference
10.5.10
February 2026

© Copyright Informatica LLC 2016, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica, the Informatica logo, [and any other trademarks appearing in the document] are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Subject to your opt-out rights, the software will automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http://www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http://httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/

Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

See patents at https://www.informatica.com/legal/patents.html.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-02-19

Table of Contents

Preface 5

Informatica Resources 5

- Informatica Network 5
- Informatica Knowledge Base 5
- Informatica Documentation 5
- Informatica Product Availability Matrices 6
- Informatica Velocity 6
- Informatica Marketplace 6
- Informatica Global Customer Support 6

Chapter 1: Data Privacy Management REST API Overview 7

Authentication 7

Request Header and Request Body Configuration 8

- Request Header 8
- Request Body 8

Error Codes 9

Logging In 9

Checking Privileges 10

Auditing REST APIs 13

Chapter 2: Data Subjects 15

Overview of Data Subject REST APIs 15

Get Subject Type Configuration Details 16

Post Subject Search 17

Get Subject Summary 19

Get Subject Data Stores 20

Get Subject Details 23

Get Subject Data Domains 26

Get Subject Data Store Data Domains 29

Get Subject DSAR Report Template 31

Post Subject DSAR PrepareReport 32

Get Subject DSAR Task Status 33

Get Subject DSAR Report 34

Get Subject DSAR Latest Report 35

Get Subject DSAR Error Report 36

Chapter 3: Jobs 38

Get Jobs 38

Preface

Refer to the *Data Privacy Management® REST API Reference* to learn how to use the Data Privacy Management REST API to create a limited set of requests. You can create requests for data stores, jobs, and data subjects.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at http://velocity.informatica.com. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.

CHAPTER 1

Data Privacy Management REST API Overview

You can use the Data Privacy Management REST API to perform the following tasks:

Data subjects

You can search for and view information on data subjects including getting a list of data stores that include subject data.

DSAR reports

You can generate and view DSAR reports for a data subject. You can view the templates available, the status of a task that you run, and error reports for tasks.

Jobs

You can view the status of a job.

To use the Data Privacy Management REST API, you need a Data Privacy Management user account and password. The user must have the privileges for the tasks that you want to perform. To start a session, send the login and privilege requests. The login and privileges are valid for the duration of the session.

Important: The Data Privacy Management REST API is subject to change in future releases. Backward compatibility is not guaranteed.

Authentication

Data Privacy Management REST API uses a token and session ID to authenticate requests. To start a session, send a login request to login to Data Privacy Management. When the user is authenticated, the server returns a token and a cookie with a `JSESSIONID`. Use the token and the `JSESSIONID` in the request header of every subsequent request. The token and `JSESSIONID` are valid for the duration of the session.

By default, session timeout is 30 minutes. If you run a REST API after the session times out, the request generates a `200 OK` response code and is redirected to the login page. The `REDIRECT_TO_LOGIN_PAGE` property value in the response header sets to `TRUE`.

To run APIs after session timeout, login again and use the new token and JSESSIONID in the requests.

Request Header and Request Body Configuration

A REST API request includes a header and a body.

Request Header

A request header consists of an HTTP method, a base URL, and a resource URI. The request header also includes parameters such as the content type and token parameters.

Use the following format to construct the request header:

```
<HTTP method> http(s)://<host>:<<port>/public/v1/<resource URI>
Content-Type: <application/json or multipart/form-data>
infaToken: <token from the login request response>
Cookie:JSESSIONID=<JSESSIONID from the cookie included in the login request response>
```

If the request includes a body, the content-type must be application/json.

The following example shows a header for a request that returns a list of DSAR report templates:

```
GET https://<host>:<port>public/v1/subject/dsar/reportTemplates
Content-Type: application/json
infaToken:"DGEsyLo4aSh8Rm-yiF1mhiE0FzekqthFuO9XdLjVHsM*"
Cookie:JSESSIONID=B9FCB9980F89DE5858DB83FB68BC96AE
```

The header format is valid for all requests. However, the login and privileges requests use a unique base URL.

Request Body

A request body includes required and optional parameters for the request. Not all requests require a body. If you include a body in the request, set the Content-Type parameter in the header to application/json. The Data Privacy Management REST API accepts a request body in the JSON data format.

Pass the request body parameters in name value pairs.

The following example shows a request body in the JSON data format:

```
{
  "dbTypeId":3,
  "repoType":"DB",
  "securityGroups":[
    "Administrator"
  ],
  "repoName":"DS4",
  "appGroupId":1,
  "passwordEncrypted":false,
  "department":"HR",
  "name":"New_Data_Store",
  "locationId":null,
  "connectionDetails":{
    "ldmScannerMemory":"Low",
    "port":"1521",
    "host":"inw00006106",
    "schemaList":"SATS_JT1",
    "connectStr":"orcl1",
    "password":"sats_jt1",
    "user":"sats_jt1",
    "serviceName":"orcl1"
  }
}
```

Error Codes

When a request fails, the server returns an HTTP 4xx or 5xx error and a REST API error object.

The following table lists the error codes that Data Privacy Management returns based on the error:

Error Code	Description
400	Bad Request The server cannot or will not process the request because of an apparent client error. For example, a malformed request syntax, missing input parameters, or invalid request message framing. Do not repeat the request without modifications.
403	Forbidden The request contained valid data and was understood by the server, but the server refuses action. This might be because the user does not have the required permissions for a resource. The code might also appear if the request provided authentication through the infaToken header field, but the server did not accept that authentication. Do not repeat the request.
404	Not Found The requested resource could not be found but might be available in the future. You can repeat the request.
500	Internal Server Error A generic error message that appears when an unexpected condition was encountered and no more specific message is available.
503	Service Unavailable The server cannot handle the request.

Logging In

The login request sends the credentials of a user account to Data Privacy Management for authentication. When you log in, the server authenticates the user and returns a token and a JSESSIONID that are valid for the duration of the session. Add the token and the JSESSIONID to the header of all subsequent requests, except for the privileges request.

After you log in, send the privileges request.

HTTP Request

```
POST http(s)://<host>:<port>/web.isp/login
```

Request Header Parameters

Parameter	Description
Content-Type	Required. Use the following value: `application/json`
Accept	Required. Use the following value: `application/json`

Request Body Parameters

Parameter	Type	Description
user	String	Required. User name.
password	String	Required. Password for the user.
namespace	String	Required. Type of user authentication that the Informatica domain uses. Use one of the following values: - `Native`. Native authentication. - `<LDAP configuration name>`. LDAP authentication.

Sample Request

```
POST https://localhost:port/web.isp/login
Content-Type: application/json
{
  "user":"Administrator",
  "password":"Administrator",
  "namespace":"Native"
}
```

Sample Response

```
{
"message": "You have been successfully authenticated.",
"infaToken": "DGEsyLo4aSh8Rm-yiF1mhiE0FzekqthFuO9XdLjVHsM*"
}
```

The response header also includes a cookie with the JSESSIONID. Check the response header to identify the JSESSIONID.

The following line is a sample ID:

```
JSESSIONID=D445BD57D7186D79A80D40B90F18A6F9;
```

Note: Most SDK programming languages and automation tools implicitly handle passing of the JSESSIONID in the request header. If the tool that you use does not handle cookies, you must add the cookie with the JSESSIONID in each request header.

Checking Privileges

The privileges request authenticates the privileges for the logged in user. Send the privileges request directly after you send the login request. The response includes a list of all privileges that are assigned to the user.

The privileges are valid for the duration of the session. If you do not send the privileges request, all subsequent requests fail.

HTTP Request

`GET http(s)://<host>:<port>/privileges`

Request Header Parameters

There are no parameters for the request header.

Request Body Parameters

There are no parameters for the request body.

Sample Request

```
GET https://<host>:<port>/privileges
```

Sample Response


```
{
  "uiPrivMapping":[
    {
      "Data Stores_List":[
        "Export Data Stores",
        "Export DB Configurations",
        "New",
        "Fix",
        "Open",
        "Edit",
        "Duplicate",
        "Delete",
        "Import Data Stores",
        "Import Data Owners",
        "Import Protection Status",
        "Merge",
        "Download Miti Agent",
        "Export"
      ],
      "Data Stores":true
    },
    {
      "Policies_List":[
        "New",
        "Open",
        "Edit",
        "Duplicate",
        "Delete",
        "Evaluate",
        "Import",
        "Export"
      ],
      "Policies":true
    },
    {
      "Application Group":true,
      "Application Group_List":[
        "New",
        "Edit",
        "Delete",
        "Export"
      ]
    },
    {
      "Data Domains_List":[
        "New",
        "Open",
        "Edit",
        "Duplicate",
        "Delete",
```

```
      "Import",
      "Export"
    ],
    "Data Domains":true
  },
  {
    "Jobs":true,
    "Jobs_List":[
      "Stop",
      "Open",
      "Pause",
      "Resume",
      "Terminate",
      "Export",
      "SkipAndResume"
    ]
  },
  {
    "Location_List":[
      "New",
      "Edit",
      "Duplicate",
      "Delete",
      "Export"
    ],
    "Location":true
  },
  {
    "Scans":true,
    "Scans_List":[
      "New",
      "Open",
      "Edit",
      "Duplicate",
      "Delete",
      "Execute",
      "Export"
    ]
  },
  {
    "Security Groups_List":[
      "Export"
    ],
    "Security Groups":true
  },
  {
    "Dashboard_List":[
      "ModifyProtectionFieldSettings",
      "ModifySensitiveFieldSettings",
      "HeroStats",
      "SensitiveDataVsGroups",
      "UserAccess",
      "TopDepartments",
      "TopDataStores",
      "SensitiveDataProliferation",
      "SensitiveDataByLocation",
      "TopUsers",
      "HeatMaps",
      "Export"
    ],
    "Dashboard":true
  },
  {
    "Settings":true,
    "Settings_List":[
      "CustomizeRiskScoring",
      "CustomizeSeverityLevel",
      "CustomizeDefaultConformanceScore"
    ]
  },
  {
```

```
      "User Management_List":[
        "Export",
        "Import User Group Memberships",
        "Import User Groups",
        "Import Users",
        "Import User Aliases",
        "Import User Access",
        "New",
        "Edit",
        "Duplicate",
        "Delete",
        "Execute"
      ],
      "User Management":true
    },
    {
      "View Data Store":true
    },
    {
      "View Department":true
    },
    {
      "View User Activity":true
    }
  ]
}
```

Auditing REST APIs

All Data Subject REST API calls generate audit logs.

Audit information is stored in the `SATS_PRODUCT_USER_AUDIT` table in the Data Privacy Management repository.

The `SATS_PRODUCT_USER_AUDIT` information for REST APIs includes the following information:

Field	Description
ACTION_TYPE	Lists the method type. For example: POST, GET, or PUT.
ACTION_TIME	Date and time that the API was run.
COMPONENT_TYPE	All Data Subject public REST APIs are audited with the PUBLIC_API component type.
ACTION_DESC	Includes the following information: - user. User name that runs the API. - relativePath. Resource URI path. - queryParams. Includes the query parameters if applicable. - pathParams. Includes path parameters if applicable.

The following code contains sample ACTION_DESC field content:

```
{
   "user":"Administrator",
   "relativePath":"subject/dataStore/dataDomains",
   "queryParams":{
      "q":[
         "{\"startIndex\":1,\"limit\":2}"
   ],
      "selectedDataStores":[
```

```
            "SR_ORCL_HDFC_BANK_HR",
            "SR_ORCL_HDFC_BANK_PAYROLL"
     ],
         "entityName":[
            "BankEmployees"
    ],
         "scope":[
            "SELECTED"
    ],
         "subjectId":[
            "90a1d1ab9fe0d12fa9b0a11a2849586d"
     ]

   },
      "pathParams":{

   }
   }
```

CHAPTER 2

Data Subjects

This chapter includes the following topics:

- Overview of Data Subject REST APIs, 15
- Get Subject Type Configuration Details, 16
- Post Subject Search, 17
- Get Subject Summary, 19
- Get Subject Data Stores, 20
- Get Subject Details, 23
- Get Subject Data Domains, 26
- Get Subject Data Store Data Domains, 29
- Get Subject DSAR Report Template, 31
- Post Subject DSAR PrepareReport, 32
- Get Subject DSAR Task Status, 33
- Get Subject DSAR Report, 34
- Get Subject DSAR Latest Report, 35
- Get Subject DSAR Error Report, 36

Overview of Data Subject REST APIs

You can run Data Privacy Management REST APIs to view information and run Subject Registry tasks on data subjects.

You can view information including attribute values and the search fields available for a data subject. You can view a list of data stores that contain information about a data subject. You can view a list of data domains associated with a subject either by data domain or by data store.

You can run APIs to generate a DSAR report for a data subject, track the task status, and download the report.

Most data subject APIs require the subject ID and specific field values in the request.

Run the `GET subjectTypeConfigurations/{subjectType}/details` API to get a list of attributes and search fields that you can use for a subject.

Run the `POST subject/search` API to get the subject ID of the data subject.

You can then use the values in other data subject REST APIs that you run.

Get Subject Type Configuration Details

The `subjectTypeConfigurations/{subjectType}/details` request returns the attributes available for a subject in a golden data set. The information includes the attributes that appear in a subject details page for the entity and a list of attributes that you can use to search on.

Resource URI

`subjectTypeConfigurations/{subjectType}/details`

HTTP Request

`GET http(s)://<host>:<port>/public/v1/subjectTypeConfigurations/{subjectType}/details`

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Path Parameters

Parameter	Type	Description
subjectType	String	Required. Name of the subject type for which you want to view details. The subject type name is the name of the entity file.

Sample Request

```
https://localhost:port/public/v1/subjectTypeConfigurations/BankEmployees/details
```

Sample Response

```
{
  "entityFields": [
    {
      "fieldName": "EMPLOYEE_ID"
    },
    {
      "fieldName": "SR_FULLNAME"
    },
    {
      "fieldName": "SR_EMAILADDRESS"
    },
    {
      "fieldName": "SR_MOBILENUMBER"
    },
    {
      "fieldName": "SR_DATE_OF_BIRTH"
    },
    {
      "fieldName": "SR_AGE"
    },
```

```
      {
        "fieldName": "SR_GENDER"
      },
      {
        "fieldName": "SR_SSN"
      },
      {
        "fieldName": "SR_MARITALSTATUS"
      },
      {
        "fieldName": "SR_CITY"
      },
      {
        "fieldName": "SR_STATE"
      },
      {
        "fieldName": "SR_COUNTRY"
      },
      {
        "fieldName": "SR_DESIGNATION"
      },
      {
        "fieldName": "SOURCE"
      },
      {
        "fieldName": "Legal Hold"
      },
      {
        "fieldName": "Residency"
      },
      {
        "fieldName": "Score"
      }
    ],
    "searchFields": [
      {
        "fieldName": "SR_FULLNAME",
        "fieldPurpose": "Person_Name",
        "matchType": "Fuzzy",
        "mandatory": "true"
      },
      {
        "fieldName": "SR_CITY",
        "fieldPurpose": "Address_Part2",
        "matchType": "Fuzzy",
        "mandatory": "false"
      },
      {
        "fieldName": "SR_MOBILENUMBER",
        "fieldPurpose": "Telephone_Number",
        "matchType": "Exact",
        "mandatory": "true"
      }
    ]
  }
```

Post Subject Search

The `subject/search` request returns subjects that match search criteria. You can use filters to configure the fields that appear in the results.

Resource URI

`/subject/search`

HTTP Request

```
POST http(s)://<host>:<port>/public/v1/subject/search
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Content-Type	Indicates the media type of the resource. Use the following value: `application/json`
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Body and Query Parameters

Parameter	Type	Description
The request body is a JSON object and contains the following properties: - entityName - searchLayout - returnFields	JSON	Enter values for the following properties: - entityName. The name of the entity file that represents the subject type you want to search. - searchLayout. The attribute that you want to search. Enter the field name and the value that you want to use. - returnFields. You can choose to display only specific fields in the results. Enter field names in quotes and separated by commas.
q	String	You can use the following query parameters: - Sort. For example: `{"sortParam":{"Score":"DESC"}}` - Pagination. For example: `"startIndex":0,"limit":3` Start index indicates the index position from which you want to include data in the response. Begins from 0. Limit indicates the maximum number of results that you want to include in the response.

Sample Request

```
https://localhost:port/public/v1/subject/search
```

Sample Request Body

```
  "entityName": "BankEmployees",
  "searchLayout": {
    "SR_FULLNAME": "Porry"

  },
  "returnFields": ["Subject Id","SR_AGE"

  ]
}
```

Sample Response

```
{
  "totalCount": 1,
```

```
  "searchResults": [
    {
      "Subject Id": "90a1d1ab9fe0d12fa9b0a11a2849586d",
      "SR_AGE": "27"
    }
  ]
}
```

Get Subject Summary

The `subject/subjectSummary` request returns information about a specific data subject. You can choose to specify the attributes that you want to include in the response. If you do not specify attributes, the response includes all attributes.

Resource URI

`subject/subjectSummary`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/subjectSummary?{subjectId}&{entityName}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `/subject/search` API to get the subject ID.
entityName	String	Required. Name of the entity that you want to search.
attributeList	String	Attributes that you want to view in the response.

Sample Request

```
https://localhost:port/public/v1/subject/subjectSummary?
subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&entityName=BankEmployees
```

Sample Response


```
{
  "searchResults": {
    "Subject Type": "BankEmployees",
    "EMPLOYEE_ID": "32",
    "SR_FULLNAME": "John Porry",
    "SR_STATE": "KA",
    "SR_EMAILADDRESS": "JohnPorry@gmail.com",
    "SR_CITY": "Bangalore",
    "SR_AGE": "27",
    "Subject Id": "90a1d1ab9fe0d12fa9b0a11a2849586d",
    "SR_MARITALSTATUS": "Divorced",
    "Legal Hold": "Yes",
    "Residency": "Bangalore, KA, IN",
    "SOURCE": "SR_ORCL_HDFC_BANK_HR",
    "SR_GENDER": "Male",
    "SR_DESIGNATION": "Collectors",
    "SR_COUNTRY": "IN",
    "SR_SSN": "413-66-4353",
    "SR_DATE_OF_BIRTH": "1992-12-31 03:08:18.0",
    "SR_MOBILENUMBER": "8040201000"
  }
}
```


Get Subject Data Stores

The `subject/dataStores` request returns a list of data stores that contain information about a data subject. By default, the response lists data stores alphabetically by name.

Resource URI

`subject/dataStores`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dataStores?{subjectId}&{entityName}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `/subject/search` API to get the subject ID.
entityName	String	Required. Name of the entity that you want to search.
q	String	You can use the following query parameter: - Pagination. For example: `"startIndex":0,"limit":3` Start index indicates the index position from which you want the response to include data. Begins from 0. Limit indicates the maximum number of results that you want to include in the response.

Sample Request

```
https://localhost:port/public/v1/subject/dataStores?
subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&entityName=BankEmployees
```

Sample Response

```
{
  "dataStoreCount": 5,
  "dataStores": [
    {
      "dataStoreID": 5,
      "dataStoreName": "SR_Local_FS_10_4",
      "dataStoreType": "File System",
      "thirdPartyNames": null,
      "dataStoreDescription": "Filesystem with local file Protocol connection For SR",
      "dataOwner": null,
      "location": null,
      "dataStoreDepartment": "UNKNOWN",
      "connectionDetails": {
        "Path": "/mount/nfsshare/Subject_Registry/1a_Nrw",
        "IncludeSubdirectory": "true",
        "FileType": "All",
        "Memory": "High",
        "Port": "1521",
        "Host": "[hostname]",
        "Protocol": "file"
      },
      "category": [
        "FILE_MANAGEMENT"
      ],
      "thirdPartyShared": false
    },
    {
      "dataStoreID": 1,
      "dataStoreName": "SR_ORCL_HDFC_BANK_HR",
      "dataStoreType": "Oracle",
      "thirdPartyNames": "HR",
      "dataStoreDescription": "GOLDEN DS FOR BANK HR IN ORACLE",
      "dataOwner": "Administrator (Administrator)",
      "location": null,
      "dataStoreDepartment": "UNKNOWN",
      "connectionDetails": {
        "includeViews": "true",
        "User": "SR_BANK_HR",
        "Memory": "Low",
        "Port": "1521",
        "Schema": "SR_BANK_HR",
        "ScannerExecutionMode": "normal",
        "Service": "ORA12CR2.INFORMATICA.COM",
```

```
      "Host": "INKR73DSG623.informatica.com",
      "ConnectionString": "INKR73DSG623",
      "ProfileExecutionEngine": "Native",
      "SchemaOption": "SelectFromList"
    },
    "category": [
      "DATABASE_MANAGEMENT"
    ],
    "thirdPartyShared": true
  },
  {
    "dataStoreID": 4,
    "dataStoreName": "SR_ORCL_HDFC_BANK_PAYROLL",
    "dataStoreType": "Oracle",
    "thirdPartyNames": "HR,Payroll",
    "dataStoreDescription": "RAW DS FOR BANK PAYROLL IN ORACLE",
    "dataOwner": "Administrator (Administrator)",
    "location": null,
    "dataStoreDepartment": "UNKNOWN",
    "connectionDetails": {
      "includeViews": "true",
      "User": "SR_BANK_PAYROLL",
      "Memory": "Low",
      "Port": "1521",
      "Schema": "SR_BANK_PAYROLL",
      "ScannerExecutionMode": "normal",
      "Service": "ORA12CR2.INFORMATICA.COM",
      "Host": "INKR73DSG623.informatica.com",
      "ConnectionString": "INKR73DSG623",
      "ProfileExecutionEngine": "Native",
      "SchemaOption": "SelectFromList"
    },
    "category": [
      "DATABASE_MANAGEMENT"
    ],
    "thirdPartyShared": true
  },
  {
    "dataStoreID": 2,
    "dataStoreName": "SR_ORCL_HDFC_CC_HR",
    "dataStoreType": "Oracle",
    "thirdPartyNames": "",
    "dataStoreDescription": "GOLDEN DS FOR CC HR IN ORACLE",
    "dataOwner": "Administrator (Administrator)",
    "location": null,
    "dataStoreDepartment": "UNKNOWN",
    "connectionDetails": {
      "includeViews": "true",
      "User": "SR_CC_HR",
      "Memory": "Low",
      "Port": "1521",
      "Schema": "SR_CC_HR",
      "ScannerExecutionMode": "normal",
      "Service": "ORA12CR2.INFORMATICA.COM",
      "Host": "INKR73DSG623.informatica.com",
      "ConnectionString": "INKR73DSG623",
      "ProfileExecutionEngine": "Native",
      "SchemaOption": "SelectFromList"
    },
    "category": [
      "DATABASE_MANAGEMENT"
    ],
    "thirdPartyShared": true
  },
  {
    "dataStoreID": 3,
    "dataStoreName": "SR_ORCL_HDFC_INSURANCE_HR",
    "dataStoreType": "Oracle",
    "thirdPartyNames": null,
    "dataStoreDescription": "GOLDEN DS FOR INSURANCE HR IN ORACLE",
    "dataOwner": "Administrator (Administrator)",
```

```
      "location": null,
      "dataStoreDepartment": "UNKNOWN",
      "connectionDetails": {
        "includeViews": "true",
        "User": "SR_INSURANCE_HR",
        "Memory": "Low",
        "Port": "1521",
        "Schema": "SR_INSURANCE_HR",
        "ScannerExecutionMode": "normal",
        "Service": "ORA12CR2.INFORMATICA.COM",
        "Host": "INKR73DSG623.informatica.com",
        "ConnectionString": "INKR73DSG623",
        "ProfileExecutionEngine": "Native",
        "SchemaOption": "SelectFromList"
      },
      "category": [
        "DATABASE_MANAGEMENT"
      ],
      "thirdPartyShared": false
    }
  ]
}
```


Get Subject Details

The `subject/subjectDetails` request returns attribute details about a specific subject. The response includes all attributes that you configure for the subject type. By default, the response lists attributes alphabetically by data store name. For each data store, the response lists attributes alphabetically by name.

Resource URI

`subject/subjectDetails`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/subjectDetails?
{subjectId}&{entityName}&{scope}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `/subject/search` API to get the subject ID.
entityName	String	Required. Name of the entity that you want to search.
includeValues	Boolean	Determines whether the response includes values. You can enter the following values: - true. Returns attributes and values. - false. Returns attributes. **Note:** To include values, you must have generated a DSAR report for the subject before you run the API.
includePK	Boolean	Determines whether the response returns the primary key of a table. You can enter the following values: - true. Returns the primary key and value. - false. Does not return the primary key.
scope	String	Determines the scope of the REST API. Choose the required value from the list. You can choose from the following values: - ALL. Includes all data stores. - SELECTED. Includes specific data stores. - FILTERED. Includes data stores that match filter criteria. You can filter based on data store location and department information.
selectedDataStores	String array	Applicable if you limit the scope to specific data stores. Click **Add item** and specify the data store names.
q	String	You can use the following query parameters: - Filter parameters. You can filter based on data store department and location information. For example: `"filterParams":{"department":"<string>"],"locationName":["<string>"]}` - Pagination. For example: `"startIndex":0,"limit":3` Start index indicates the index position from which you want the response to include data. Begins from 0. Limit indicates the maximum number of results that you want to include in the response. If you choose the scope as Filtered and enter a data store name in the `selectedDataStores` field, the command ignores the selected data store.

Sample Request

```
https://localhost:port/public/v1/subject/subjectDetails?
subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&entityName=BankEmployees&includeValues=true&in
cludePK=false&scope=ALL
```

Sample Response

```
{
  "attributeCount": 631,
  "attributes": [
    {
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw.zip|FILE_COMPRESSED",
      "attributeValue": "",
      "dataDomain": "SR_AGE",
```

```
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    },
    {
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw.zip|FILE_COMPRESSED",
      "attributeValue": "Bangalore",
      "dataDomain": "SR_CITY",
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    },
    {
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw.zip|FILE_COMPRESSED",
      "attributeValue": "IN",
      "dataDomain": "SR_COUNTRY",
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    },{
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw_doc.doc.Z|FILE_COMPRESSED",
      "attributeValue": "Bangalore",
      "dataDomain": "SR_CITY",
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    },
    {
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw_doc.doc.Z|FILE_COMPRESSED",
      "attributeValue": "IN",
      "dataDomain": "SR_COUNTRY",
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    },
    {
      "dataStoreName": "SR_Local_FS_10_4",
      "attributePathName": "SR_Local_FS_10_4|/FileServer/mount/nfsshare/
Subject_Registry/1a_Nrw/Compressed|1a_Nrw_doc.doc.Z|FILE_COMPRESSED",
      "attributeValue": "1992-12-31 03:08:18.0",
      "dataDomain": "SR_DATE_OF_BIRTH",
      "purpose": "",
      "category": "",
      "thirdPartyShare": false,
      "thirdPartyNames": ""
    }
  ]
}
```

Get Subject Data Domains

The `subject/dataDomains` request returns a list of unique data domains associated with a data subject, with the category and purpose associated with the data domain, and with data store information. By default, the response lists data domains alphabetically by name.

Resource URI

`/subject/dataDomains`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dataDomains?
{subjectId}&{entityName}&{scope}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `/subject/search` API to get the subject ID.
entityName	String	Required. Name of the entity that you want to search.
scope	String	Determines the scope of the REST API. Choose the required value from the list. You can choose from the following values: - ALL. Includes all data stores. - SELECTED. Includes specific data stores. - FILTERED. Includes data stores that match filter criteria. You can filter on data store location and department information.

Parameter	Type	Description
selectedDataStores	String array	Applicable if you limit the scope to specific data stores. You can enter multiple key values. In Swagger, you can click **Add item** and specify the data store names.
q	String	You can use the following query parameters: - Filter parameters. You can filter on data store location and department information. For example: `"filterParams":{"department":<string>"], "locationName":["<string>"]}` - Pagination. For example: `"startIndex":0,"limit":3` Start index indicates the index position from which you want to include data in the response. Begins from 0. Limit indicates the maximum number of results that you want to include in the response.

Sample Request

```
https://host:port/public/v1/subject/dataDomains?
subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&entityName=BankEmployees&scope=SELECTED&select
edDataStores=SR_ORCL_HDFC_BANK_HR&selectedDataStores=SR_ORCL_HDFC_BANK_PAYROLL
```

Sample Response


```
{
  "totalDataDomainCount": 11,
  "dataDomainDetails": [
    {
      "dataDomain": "SR_CITY",
      "categories": [
        "Demographic_bank_hr",
        "Demographic_bank_payroll"
      ],
      "purposes": [
        "Communication_bank_payroll",
        "Communication_bank_hr"
      ],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    },
    {
      "dataDomain": "SR_COUNTRY",
      "categories": [],
      "purposes": [],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    },
    {
      "dataDomain": "SR_DATE_OF_BIRTH",
      "categories": [
        "Professional"
      ],
      "purposes": [
        "Verification"
      ],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    },
    {
      "dataDomain": "SR_DESIGNATION",
      "categories": [
        "Professional_bank_payroll"
```

```
    ],
    "purposes": [
      "Communication_bank_payroll"
    ],
    "dataStores": [
      "SR_ORCL_HDFC_BANK_PAYROLL"
    ]
  },
  {
    "dataDomain": "SR_EMAILADDRESS",
    "categories": [
      "Professional_bank_hr",
      "Professional_bank_payroll"
    ],
    "purposes": [
      "Communication_bank_payroll",
      "Communication_bank_hr"
    ],
    "dataStores": [
      "SR_ORCL_HDFC_BANK_HR",
      "SR_ORCL_HDFC_BANK_PAYROLL"
    ]
  },
  {
    "dataDomain": "SR_FULLNAME",
    "categories": [
      "Personal_bank_hr",
      "Personal_bank_payroll"
    ],
    "purposes": [
      "Communication_bank_payroll",
      "Communication_bank_hr"
    ],
    "dataStores": [
      "SR_ORCL_HDFC_BANK_HR",
      "SR_ORCL_HDFC_BANK_PAYROLL"
    ]
  },
  {
    "dataDomain": "SR_GENDER",
    "categories": [
      "Personal"
    ],
    "purposes": [
      "Communication"
    ],
    "dataStores": [
      "SR_ORCL_HDFC_BANK_HR"
    ]
  },
  {
    "dataDomain": "SR_MARITALSTATUS",
    "categories": [
      "Personal"
    ],
    "purposes": [
      "Verification"
    ],
    "dataStores": [
      "SR_ORCL_HDFC_BANK_HR"
    ]
  },
  {
    "dataDomain": "SR_MOBILENUMBER",
    "categories": [
      "Professional_bank_hr",
      "Professional_bank_payroll"
    ],
    "purposes": [
      "Communication_bank_payroll",
      "Communication_bank_hr"
```

```
      ],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    },
    {
      "dataDomain": "SR_SSN",
      "categories": [
        "Professional_bank_hr",
        "Professional"
      ],
      "purposes": [
        "Verification",
        "Verification_bank_hr"
      ],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    },
    {
      "dataDomain": "SR_STATE",
      "categories": [],
      "purposes": [],
      "dataStores": [
        "SR_ORCL_HDFC_BANK_HR",
        "SR_ORCL_HDFC_BANK_PAYROLL"
      ]
    }
  ]
}
```


Get Subject Data Store Data Domains

The `subject/dataStore/dataDomains` request returns a list of unique data domains associated with a data subject grouped by data store. The request also includes category and purpose information. By default, the response lists data domains alphabetically by data store name.

Resource URI

`subject/dataStore/dataDomains`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dataStore/dataDomains?
{subjectId}&{entityName}&{scope}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `/subject/search` API to get the subject ID.
entityName	String	Required. Name of the entity that you want to search.
scope	String	Determines the scope of the REST API. Choose the required value from the list. You can choose from the following options: - ALL. Includes all data stores. - SELECTED. Includes specific data stores. - FILTERED. Includes data stores that match filter criteria. You can filter on data store location and department information.
selectedDataStores	String array	Applicable if you limit the scope to specific data stores. Click **Add item** and specify the data store names.
q	String	You can use the following query parameters: - Filter parameters. You can filter on data store location and department information. For example: `"filterParams":{"department":<string>"],"locationName":["<string>"]}` - Pagination. For example: `"startIndex":0,"limit":3` Start index indicates the index position from which you want to include data in the response. Begins from 0. Limit indicates the maximum number of results that you want to include in the response.

Sample Request

```
https://localhost:port/public/v1/subject/dataStore/dataDomains?
subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&entityName=BankEmployees&scope=SELECTED&select
edDataStores=SR_ORCL_HDFC_BANK_PAYROLL
```

Sample Response

```
{
  "totalDataStoreCount": 1,
  "dataStoreDetails": [
    {
      "dataStore": "SR_ORCL_HDFC_BANK_PAYROLL",
      "dataDomains": [
```

```
            "SR_FULLNAME",
            "SR_STATE",
            "SR_EMAILADDRESS",
            "SR_CITY",
            "SR_DESIGNATION",
            "SR_COUNTRY",
            "SR_SSN",
            "SR_DATE_OF_BIRTH",
            "SR_MOBILENUMBER"
          ],
          "categories": [
            "Demographic_bank_payroll",
            "Professional",
            "Personal_bank_payroll",
            "Professional_bank_payroll"
          ],
          "purposes": [
            "Communication_bank_payroll",
            "Verification"
          ]
        }
      ]
    }
```

Get Subject DSAR Report Template

The `subject/dsar/reportTemplates` request returns a list of available report templates.

Resource URI

`subject/dsar/reportTemplates`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dsar/reportTemplates
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Parameters

Does not take any request body or query parameters.

Sample Request

```
https://localhost:port/public/v1/subject/dsar/reportTemplates
```

Sample Response

```
{
  "recordCount": 4,
  "reportTemplates": [
    {
      "reportFileType": "csv",
      "templateName": "Detailed CSV"
    },
    {
      "reportFileType": "csv",
      "templateName": "Summary CSV"
    },
    {
      "reportFileType": "pdf",
      "templateName": "Summary PDF"
    },
    {
      "reportFileType": "pdf",
      "templateName": "Summary PDF Without Personal Data"
    }
  ]
}
```

Post Subject DSAR PrepareReport

The `subject/dsar/prepareReport` request prepares a DSAR report for a data subject.

Resource URI

`subject/dsar/prepareReport`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dsar/prepareReport
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Content-Type	Indicates the media type of the resource. Use the following value: `application/json`
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Body Parameters

The request body is a JSON object and contains the following properties:

Parameter	Type	Description
- entity - subjectId	JSON	Enter values for the following properties: - entity. Required. Name of the subject type that includes the subject. - subjectId. Required. ID of the data subject. To determine the subject ID, run the `GET subjectTypeConfigurations/{subjectType}/details` API and then run the `POST /subject/search` API to get the subject ID.

Sample Request

```
https://localhost:port/public/v1/subject/dsar/prepareReport
```

Sample Request Body

```
  "entityName": "Customer_4a",
  "searchLayout": {
    "subjectId": "a6729061160c1e4c01206a2f9e833f42"
    }
    ]
}
```

Sample Response

```
{
  "generatedTaskIds": [
    "2825"
  ]
}
```

Get Subject DSAR Task Status

The `/subject/dsar/status/{taskId}` request returns the status of a DSAR report creation job that you run.

Resource URI

`/subject/dsar/status/{taskId}`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dsar/status/{taskId}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
dsarTaskId	String	Required. Task ID of the DSAR report creation task. The `subject/dsar/prepareReport` REST API generates the task ID.

Sample Request

```
https://localhost:port/public/v1/subject/dsar/status/2825
```

Sample Response

```
{
  "dsarTaskId": "2825",
  "taskName": "DSAR-1579507573",
  "taskType": "DSAR",
  "taskTypeCategory": "Data Subject Access Request",
  "description": "DSAR task for Customer_4a : a6729061160c1e4c01206a2f9e833f42",
  "lastUpdatedTime": "Mon Jan 20 13:36:13 IST 2020",
  "status": "COMPLETED",
  "completedWithErrors": false,
  "state": "WIP",
  "purged": false,
  "purgeDate": "N/A",
  "errorReportURL": "No error",
  "closed": false
}
```

Get Subject DSAR Report

The `subject/dsar/downloadReport` request returns the DSAR report in detailed CSV format as a downloadable file.

Resource URI

`subject/dsar/downloadReport`

HTTP Request

`GET http(s)://<host>:<port>/public/v1/subject/dsar/downloadReport?{dsarTaskId}`

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
dsarTaskId	String	Required. Task ID of the DSAR report creation task. The `subject/dsar/prepareReport` REST API generates the task ID.

Sample Request

```
https://localhost:port/public/v1//v1/subject/dsar/downloadReport?dsarTaskId=2825
```

Sample Response

The response body includes a link to download the DSAR report in the default CSV format: `DSAR_REPORT.csv`

Get Subject DSAR Latest Report

The `subject/dsar/downloadlatestReport` request returns the latest DSAR report in the specified format as a downloadable file.

Resource URI

`subject/dsar/downloadLatestReport`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dsar/downloadLatestReport?
{entityName}&{subjectId}&{reportTemplateName}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
subjectId	String	Required. ID of the data subject. To determine the subject ID, run the GET `subjectTypeConfigurations/{subjectType}/details` API and then run the POST `subject/search` API to get the subject ID.
entityName	String	Required. Name of the subject type.
reportTemplateName	String	The format of the DSAR report. The `subject/dsar/reportTemplates` API returns a list of report templates.

Sample Request

```
https://localhost:port/public/v1/subject/dsar/downloadLatestReport?
entityName=employee&subjectId=90a1d1ab9fe0d12fa9b0a11a2849586d&reportTemplateName=Summary
 CSV
```

Sample Response

The response body includes a link to download the DSAR report in the specified format:

```
John_Porry_BankEmployees_Summary_CSV.csv
```

Get Subject DSAR Error Report

The `/subject/dsar/downloadErrorReport` request returns the error report for a DSAR report generation job that failed.

Resource URI

```
/subject/dsar/downloadErrorReport
```

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/subject/dsar/downloadErrorReport?{taskId}
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Query Parameters

Parameter	Type	Description
dsarTaskId	String	Required. Task ID of the DSAR report for which you want to view the error report. The `subject/dsar/prepareReport` REST API generates the task ID.

Sample Request

```
https://localhost:port/public/v1/subject/dsar/downloadErrorReport?dsarTaskId=2825
```

Sample Response

The response body includes a link to download the error report: `DSAR_ERROR.csv`

CHAPTER 3

Jobs

This chapter includes the following topic:

- Get Jobs, 38

Get Jobs

The `jobs` request returns the status of a specific job.

Resource URI

`/public/v1/jobs/`

HTTP Request

```
GET http(s)://<host>:<port>/public/v1/jobs/<jobId>
```

Request Header Parameters

The following parameters are required:

Parameter	Description
Content-Type	Indicates the media type of the resource. Use the following value: `application/json`
Accept	Indicates the format of the response body. Use the following value: `application/json`
infaToken	Use the token from the login request response.
JSESSIONID	Use the session ID from the login request response.

Request Body Parameters

Parameter	Type	Description
jobId	Integer	Required. ID of the job.

Sample Request

```
POST https://localhost:9090/public/v1/jobs/27  -H "accept: application/json"
```

Sample Response

```
{
  "jobId": 27,
  "status": "COMPLETED"
}
```