Informatica® Data Privacy Management
10.5.11

Upgrading From Versions 10.5 and Later

Informatica Data Privacy Management Upgrading From Versions 10.5 and Later
10.5.11
August 2026

© Copyright Informatica LLC 2015, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo **[and any other Informatica-owned trademarks appearing in the document]** are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Subject to your opt-out rights, the software will automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-08-18

Table of Contents

Preface 5

Informatica Resources 5

- Informatica Network 5
- Informatica Knowledge Base 5
- Informatica Documentation 5
- Informatica Product Availability Matrices 6
- Informatica Marketplace 6
- Informatica Global Customer Support 6

Chapter 1: Upgrading to Data Privacy Management 10.5.11 7

Data Privacy Management upgrade overview 7

Upgrade Paths 8

Upgrade options 10

Chapter 2: Apply the hotfix 11

Hotfix installation and rollback overview 11

Applying the services hotfix 11

- Before you apply the hotfix 11
- Apply the services hotfix in console mode 13
- Apply the services hotfix in silent mode 14
- After you apply the hotfix 18

Rolling back the services hotfix 20

- Before you roll back the hotfix 20
- Back Up Data Privacy Management 21
- Back up the catalog data 22
- Back up other repositories and content 23
- Roll back the services hotfix in console mode 24
- Roll back the services hotfix in silent mode 25
- After you roll back the hotfix 26

Applying the client hotfix 26

- Apply the client hotfix in graphical mode 26
- Apply the client hotfix in silent mode 27
- Remove the distribution packages from the backup location 29

Rolling back the client hotfix 29

- Rolling back the client hotfix in graphical mode 29
- Rolling back the client hotfix in silent mode 30

Chapter 3: Before You Upgrade 31

Before you Begin 31

- System Prerequisites to Upgrade 31

Verify Required Versions. . . . 33
Verify the Services. . . . 33
Verify the Status of Jobs. . . . 33
Disable Polling. . . . 34
Configure Custom SSL Certificates Overview. . . . 34
Download the Required Informatica Software. . . . 42
Back Up the Informatica Domain. . . . 42
Back Up Data Privacy Management. . . . 43
Back up the catalog data. . . . 45
Back up other repositories and content. . . . 46
Back Up the SSL Configuration. . . . 47
Back Up the Domain Information. . . . 47
Complete Other Pre-Upgrade Tasks. . . . 47

Chapter 4: Upgrade to Version 10.5.11 49

Upgrade. . . . 49
Upgrade in Console Mode. . . . 49
Upgrading in Silent Mode. . . . 51

Chapter 5: After you Upgrade. . . . 55

After you Upgrade Overview. . . . 55
Copy the Third-party Resource Drivers. . . . 56
Complete the Default SSL Configuration. . . . 56
Enable and Upgrade the Services. . . . 56
Migrate the Catalog Data. . . . 57
Upgrade the Data Privacy Management Service 57
Copy Custom SSL Certificates to Data Privacy Management. . . . 58
Upgrade the remote agent. . . . 59
Update 10.4.1 Entity Files. . . . 59
Enable Polling Jobs. . . . 59
Upgrade JARs and Required Informatica Product Versions. . . . 60
Delete temporary files. . . . 61

Appendix A: Managing Distribution Packages. . . . 62

Managing Distribution Packages Overview. . . . 62
Before You Begin. . . . 62
Install or Remove Distribution Packages in Console Mode. . . . 63
Install or Remove Distribution Packages in Silent Mode. . . . 64
After You Install. . . . 64

Index. . . . 66

Preface

Follow the instructions in the *Data Privacy Management® Upgrade Guide* to upgrade Data Privacy Management. The guide also includes steps to perform pre-requisite tasks, perform post-upgrade tasks, and troubleshoot common upgrade errors. Unless otherwise noted, the upgrade path includes hotfixes and service packs.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.

CHAPTER 1

Upgrading to Data Privacy Management 10.5.11

This chapter includes the following topics:

- Data Privacy Management upgrade overview, 7
- Upgrade Paths, 8
- Upgrade options, 10

Data Privacy Management upgrade overview

If you are on version 10.5 including any hotfix, service pack, or cumulative patch, you can apply the 10.5.11 hotfix. If you are on a version earlier than 10.5, you must first upgrade to 10.5 and then apply the 10.5.11 hotfix. You cannot directly upgrade to version 10.5.11 from versions earlier than 10.5.

Note: Effective from version 10.5.6, the installer doesn't include the default Elasticsearch tar file. If you are on 10.5.4.1 or earlier versions and using the default Elasticsearch tar file, you might encounter issues with Elasticsearch if you upgrade to version 10.5.6 or later. To use the correct version of the Elasticsearch tar file, perform one of the following options:

- Upgrade to 10.5.5 and then apply the 10.5.11 hotfix.
- Replace the Elasticsearch tar file in `<INFA_HOME>/ services/InfaClusterService/ServiceBinaries/ES` with an Elasticsearch tar file that you download from the official website. Data Privacy Management 10.5.11 requires Elasticsearch version 8.19.x or higher for compatibility with the Elasticsearch client version. After you replace the Elasticsearch tar file, apply the 10.5.11 hotfix.

Run the Informatica service installer to upgrade Data Privacy Management and services within an Informatica domain. After you run the installer, upgrade the required services and complete post upgrade tasks to complete the upgrade.

Upgrade Paths

The upgrade path that you take depends on the products and versions that you're currently using.

Consider the following rules and guidelines to applying the hotfix or upgrade:

- You can apply the hotfix if you are on any version associated with the major release. For example 10.5 is a major release, so you can apply the hotfix from any version of 10.5.x.
- If you're not currently using a version associated with the major release, you can upgrade to the current release from any supported previous release.
- If you are on a version that doesn't support a direct upgrade, you must first upgrade to a supported version.
- Any supported update also includes hotfixes, service packs, and cumulative patches.

Important: If Data Engineering is in the same domain as any other product supported by the Informatica installer, verify that all products are upgraded to the same supported upgrade version before you upgrade to 10.5.11.

The following table provides details for the rules and guidelines:

Product	Versions
PowerCenter	You can apply the10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5.11 from the following previous versions: - 10.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Informatica Data Quality	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5.11 from the following previous versions: - 10.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Data Engineering Integration Data Engineering Quality	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.2 including any hotfix, service pack, or cumulative patch - 10.2.1 including any hotfix, service pack, or cumulative patch - 10.2.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch **Important:** If Data Engineering is in the same domain as any other product supported by the Informatica installer, verify that all products are upgraded to the same supported upgrade version before you upgrade to 10.5.11.
Data Engineering Streaming	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.2.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch

Product	Versions
Data Privacy Management	You can apply the 10.5.11 hotfix to versions 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Enterprise Data Catalog	You can apply the 10.5.11 to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 (including any service packs or cumulative patches) - 10.4.1 (including any service packs or cumulative patches) **Important:** If Enterprise Data Catalog and Data Engineering are in the same domain of a version 10.4.1, 10.4 or earlier, upgrade them both to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 before you upgrade to 10.5.11.
Enterprise Data Preparation	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. **Note:** You cannot upgrade to version 10.5.11 from Enterprise Data Preparation version 10.5.7. You can upgrade to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Test Data Management	You can apply the 10.5.11 hotfix to versions 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch

Upgrade options

You can run the Informatica installer to apply the hotfix on Data Privacy Management versions 10.5 and later.

The following table describes the upgrade path from different versions:

Data Privacy Management Version	Upgrade Path
10.5 including any hotfix, service pack, or cumulative patch.	Apply the 10.5.11 hotfix. See Chapter 2, "Apply the hotfix" on page 11 for the steps to apply the hotifx.
- 10.4.1 - 10.4	Upgrade to 10.5 and then apply the 10.5.11 hotfix. For information about how to upgrade to version 10.5, see the *Informatica® Data Privacy Management Upgrading From Versions 10.4.0 and Later*. Apply the hotfix after you perform all post upgrade tasks for 10.5.
All earlier versions.	Upgrade to one of the following versions and then upgrade to 10.5: - 10.4.1 - 10.4 Apply the hotfix after you perform all post upgrade tasks for 10.5.

CHAPTER 2

Apply the hotfix

This chapter includes the following topics:

- Hotfix installation and rollback overview, 11
- Applying the services hotfix, 11
- Rolling back the services hotfix, 20
- Applying the client hotfix, 26
- Rolling back the client hotfix, 29

Hotfix installation and rollback overview

If you are currently on Data Privacy Management version 10.5 or later, you must choose the option to apply the hotfix when you run the 10.5.11 installer.

You cannot directly run the installer to apply or roll back the hotfix. Perform the steps listed in "Before you apply the hotfix" on page 11 before you apply the hotfix. Perform the steps listed in "Before you roll back the hotfix" on page 20 before you roll back the hotfix.

Applying the services hotfix

When you apply the hotfix, the installer backs up existing directories, applies the new version of the product, and restores or updates required configuration and run-time files.

You can run the installers to apply hotfixes to Informatica services and clients.

Before you apply the hotfix

Before you run the installer to apply the hotfix, perform the following prerequisite tasks.

Verify distribution package

Verify distribution package requirements

The Informatica domain and client require the distribution packages to process complex files within the Informatica domain, or to connect to Hadoop or Databricks environment when you process within the Informatica domain, or to push processing to Hadoop or Databricks environment.

If you need a distribution package, you can install it through the installer or through Integration Package Manager (the package manager) at any time.

You can use the same distribution package that you used in the previous Informatica version to process complex files within the Informatica domain or to connect to the Hadoop or Databricks environment when you process within the Informatica domain.

For the supported distribution packages when you push processing to Hadoop or Databricks environment, see the Product Availability Matrix.

Download Installer Files

Download and extract the installer files

The installer files are distributed as compressed files. You can get the Informatica installation file and distribution packages from the FTP link contained in your fulfillment email. Download the Informatica installation tar file from the Informatica Electronic Software Download site to a directory on your machine.

To download other compressed files and utilities, raise a shipping request with Informatica Global Customer Support.

Note: Make sure that you download the file to a local directory or a shared network drive that is mapped on your machine. You can then extract the installer files. However, you cannot run the installer from a mapped file. Copy the extracted files to a local drive and then run the installer.

1. Download the hotfix package for your product.
2. Untar the contents of the hotfix package.

   Note: Use the native tar or GNU tar command to extract the installer files. The user that runs the installer must have read and write permissions on the directory that contains the installer files and execute permissions on install.sh.
3. If you want to install distribution packages, download the ZIP files of the distribution packages.
4. Copy the ZIP files of the distribution packages to the location: `<Informatica installer files>/source`

   Note: The installer fails if the ZIP files for distribution packages aren't available in the source directory.

Prepare for hotfix Installation

Perform the following prerequisite tasks:

1. Stop all processes that access the installation directory and subdirectories, including command prompts and command line programs.
2. Close the Informatica clients on all machines where you want to apply the hotfix.
3. Perform this task if you are currently on version 10.5 only. Open the `<Informatica installation directory>/version.txt` file in a text editor.
4. Update the following parameter values and save the file:
   - INTERNAL_CLUSTER=1
   - EXTERNAL_CLUSTER=0
   - LDM_VERSION=10.5
5. Back up the catalog data using the infacmd ldm backupContents command.

   Note: Verify that you take a full backup of the catalog data. If you deployed the Informatica Cluster Service on multiple nodes, verify that you configured the cluster shared file system path for the Informatica Cluster Service. If you do not configure the shared file system, the SEARCH store is not

backed up, and a warning message appears in the console log. If the SEARCH store is not backed up, the backup validation fails when you apply or roll back the hotfix.

6. Back up the repository for the Content Management Service and the Model repository.
   a. Back up the database repository contents for the Content Management Service.
   Example for Oracle:
   ```
   exp system/oracle@ORCL OWNER=CMS_REPO FILE=CMS_REPO.dmp
   ```
   b. To back up the Model repository, log in to the Administrator tool and select the Model Repository Service.
   c. Select **Actions** > **Repository Contents** > **Backup**.
   d. Provide the credentials to log in to the domain.
   e. Provide the name of the output file that will contain the backed up content.

   Tip: View the general properties of the node to determine the path of the backup directory. The default path is: `<Informatica installation directory>/server/infa_shared/Backup`
7. Disable the following Informatica application services:
   a. Data Privacy Management Service
   b. Catalog Service
   c. Content Management Service
   d. Data Integration Service
   e. Model Repository Service
   f. Informatica Cluster Service
8. Shut down the Informatica domain using the infaservice shutdown command. By default, the infaservice executable file is located in the following directory: `<Informatica installation directory>/tomcat/bin`.
9. Download and save the Scanner binaries to the following directory:
   `<extracted directory>/source`

   Verify that the Scanner binaries file name is ScannerBinaries.zip.
10. If the machine uses HTTPS to connect to Informatica Administrator, verify that the keystore file is in the default location and that it uses the default file name. The default location for the keystore file is `<Informatica installation directory>/tomcat/conf`. The default file name for the keystore file is Default.keystore.
11. Set the SKIP_VENDOR_CHECK environment variable to true to remove the sudo prompt from the hotfix installation on UNIX.

    Note: If you don't have sudo privileges, set the environment variable to true before you apply or roll back a hotfix. If you have sudo privileges, you don't need to set the environment variable.

Apply the services hotfix in console mode

Run the 10.5.11 installer to apply the hotfix to version 10.5 or 10.5.x.

When you apply the hotfix in console mode, the words Help, Quit, and Back are reserved words. Do not use them as input text.

1. Run the installer using the ./install.sh command.
2. Press **Y** to confirm that you want to proceed with the installation.
3. Press **5** to select the option to apply the hotfix.
4. At the PowerCenter server location prompt, press **Y** to continue.

5. Press **Y** to continue.
6. Press **1** to apply the hotfix.
7. Press **2** to agree to the terms and conditions and apply the license.
8. Verify that all installation requirements are met before you continue to apply the hotfix.
9. Press **Enter**.
10. Enter the directory where you installed Informatica 10.5 or 10.5.x.
    The directory names in the path must not contain spaces or the following special characters: @|* $ # ! % ( ){ } [ ] , ; '
11. Press **2** to confirm that you configured the Catalog Service on the node.
12. Press **2** to confirm that you backed up the catalog data using the infacmd ldm backupContents command.
13. Enter the location of the backup file. For example, `/data/Informatica/LDM_BACKUP1050SAML12.zip`.
14. Select one of the following options based on the type of installation:
    - Press **1** to set Sandbox environment for a basic environment used for proof of concept with minimal users.
    - Press **2** to set Development environment for the design environment.
    - Press **3** to set Test environment for high volume processing that is closest to a production environment.
    - Press **4** to set Production environment for high volume processing with high levels of concurrency meant for end users. Advanced production environments are typically multi-node setups.

    Default is **1** for Sandbox.
15. Choose whether you want to install distribution packages through the Informatica installer.
    - Press **1** if you don't need distribution packages or if you want to install them later.
    - Press **2** if you want to install distribution packages through the installer.

    Default is 1.
16. If you choose to install distribution packages, select one or more packages from the list that you want to install. Separate multiple packages with a comma.
    Default is 1.
17. Press **Enter**.
18. At the Pre-Installation Summary, review the installation information and press **Enter** to apply the hotfix. The installer copies the Informatica files to the installation directory.
19. At the Post-Installation Summary, verify that the hotfix application completed successfully and press **Enter** to exit the installer.

Apply the services hotfix in silent mode

To apply the hotfix in silent mode, create the SilentInput.properties file and then run the installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.

4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 0 to apply the hotfix.
USER_INSTALL_DIR	Directory for the Informatica installation where you want to apply or roll back the hotfix. To apply the hotfix to Informatica services, enter the absolute path for the directory in which the current version of Informatica services is installed.
ENABLE_USAGE_COLLECTION	Enables the software to automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool. For more information about how to disable sending usage statistics, see the *Informatica Administrator Guide*. You must set the value to 1 to apply the hotfix.
INSTALLATION_ENVIRONMENT	If you apply the hotfix, specify the environment type associated with the Informatica services installation. • Press **1** to set Sandbox environment for a basic environment used for proof of concept with minimal users. • Press **2** to set Development environment for the design environment. • Press **3** to set Test environment for high volume processing that is closest to a production environment. • Press **4** to set Production environment for high volume processing with high levels of concurrency meant for end users. Advanced production environments are typically multi-node setups. Default is 1 for Sandbox.
EDC_CATALOG_INST	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations. Set the property to true if the Catalog Service runs on the node on which you want to apply the hotfix.
EDC_HF_BACKUP	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you have set EDC_CATALOG_INST=true. Set the property to true if you have taken a backup of the catalog.
EDC_BACK_UP_DIR	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you set the EDC_CATALOG_INST and EDC_HF_BACKUP properties to true. Enter the location of the catalog data backup file.
INSTALL_HADOOP_LIBRARIES	Determines whether to install distribution packages through the installer. Set the value to true if you want to install distribution packages through the installer. Set the value to false if you don't need distribution packages or if you want to install them later.

Property Name	Description
SELECTED_HADOOP_LIBRARIES	Determines the distribution packages that you want to install from the supported packages list. Enter the distribution packages that you want to install, separating multiple packages with a comma.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. Go to the root of the services installer directory.
7. Verify that the directory contains the SilentInput.properties file that you edited and saved.
8. To apply the hotfix, on a shell command line, enter the following command to run the silent installer: ./silentInstallHotFix.sh.

   The installer copies the Informatica files to the installation directory.
9. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Sample silent input properties

The following example shows the contents of the SilentInput.properties file when you apply or roll back the hotfix in silent mode.

```
############################################################
# (C) Copyright Informatica LLC 1993, 2026.
# This software and documentation are provided only under a separate license agreement
containing restrictions on use and disclosure.
# This software is protected by patents as detailed at https://www.informatica.com/legal/
patents.html
# A current list of Informatica trademarks is available on the web at https://
www.informatica.com/trademarks.html
# See the Informatica privacy policy at https://www.informatica.com/privacy-policy.html
############################################################

# Use the following guidelines when editing this file
# * Use this file to install without user interaction.
# * After you create the properties file, save the file with the name
SilentInput.properties
# * Any error condition that leads to failure, such as an invalid
# installation directory, generates a log file in the user home
# directory. For example: /home/<user name>/silentErrorLog<time_stamp>.log

############################################################
# Set RESUME_INSTALLATION to true if you want to resume installation
# Set RESUME_INSTALLATION to false and INFA_SERVICES_INSTALLED to true in case of
standalone installation
RESUME_INSTALLATION=false

# Set ENABLE_USAGE_COLLECTION  to 1 to accept the product usage toolkit end user license
agreement.
# You must set the value as 1 to install the Informatica platform.
# The product usage toolkit end user license agreement is available at: http://
www.informatica.com/us/eula/en-support-eula.aspx.
# As further described in the EULA, your use of the Informatica platform will enable the
product usage toolkit
# to collect certain product usage and failure information. You may disable this feature
at any time.
# For more information on how to disable this feature refer the Informatica
Administrator Guide.

ENABLE_USAGE_COLLECTION=0

## *INSTALL_TYPE - Set this value to '0' to apply the hotfix. Set this value to '1' to
roll back the hotfix.
```

```
INSTALL_TYPE=0

# * The USER_INSTALL_DIR variable must point to a valid directory with write
#     permissions enabled.

USER_INSTALL_DIR=/home/Informatica/10.5.11


#The INSTALLATION_ENVIRONMENT property represents the installation environment
# Set the property to one of the following installation environment types: Sandbox,
Development, Test, or Production. Values are case-sensitive.
# Set to Sandbox for a basic environment used for proof of concept with minimal
users.
# Set to Development for the design environment.
# Set to Test for high volume processing that is closest to a production environment.
# Set to Production for high volume processing with high levels of concurrency meant for
end users. Advanced production environments are typically multi-node setups.

INSTALLATION_ENVIRONMENT=

# Required only for EDC installation
# Set EDC_CATALOG_INST=true if the Catalog Service is running on the node on which you
want to apply or roll back the hotfix.
EDC_CATALOG_INST=false

# Required only for EDC installation.
# Set EDC_HF_BACKUP=true if you have set EDC_CATALOG_INST=true and you have taken a
backup of the catalog.
# Run the infacmd ldm backupContents command before you apply the hotfix (INSTALL_TYPE=0)
# Run the infacmd ldm restoreContents command after you rollback the hotfix
(INSTALL_TYPE=1)
EDC_HF_BACKUP=false

# Enter the location of the backup file.
# Required for Enterprise Data Catalog installation when the EDC_CATALOG_INST and
EDC_HF_BACKUP parameters are set to true
EDC_BACK_UP_DIR=

# The INSTALL_HADOOP_LIBRARIES property determines whether to install packages to
integrate the domain with Hadoop or Databricks.
# Set INSTALL_HADOOP_LIBRARIES=true if you want to install the integration packages to
push processing to Hadoop or Databricks, process complex files within the domain, or
connect to Hadoop but process within the domain.
# Set INSTALL_HADOOP_LIBRARIES property only if INSTALL_TYPE=0
# If you don't install the integration packages now, you can install them later through
Integration Package Manager.
INSTALL_HADOOP_LIBRARIES=false

# The SELECTED_HADOOP_LIBRARIES property determines the integration packages that you
want to install.
# Lists the supported integration packages and their versions.
# Set SELECTED_HADOOP_LIBRARIES property only if INSTALL_TYPE=0
# Enter the integration package that you want to install. Separate multiple packages
with a comma.
# You can choose from the following options:
# 1->Azure HDInsight 5.1
# 2->Cloudera 7.1
# 3->Cloudera 7.218
# 4->Databricks 14.3
# 5->Dataproc 2.0
# 6->Elastic MapReduce 7.1
# 7->Elastic MapReduce 7.9
# 8->MapR 7.9
# 9->Select all
SELECTED_HADOOP_LIBRARIES=
```

After you apply the hotfix

After you run the installer to apply the hotfix, start the domain and perform the post requisite tasks to complete the hotfix application.

Remove the distribution packages from the backup location

After you apply the hotfix, remove the distribution packages from the backup folder to mitigate the security vulnerabilities.

When you apply the hotfix, all the existing files in the Informatica installation directory are backed up. You need to remove the distribution packages backup from the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\services\shared\hadoop\<distribution package_version>`

The following example shows the backup location for a distribution package when you apply the hotfix: `C:\Informatica\BACK_FROM_3\services\shared\hadoop\EMR_6.4`

Note: The deletion process doesn't remove all files of the distribution packages from the backup folder. Some files might still exist in the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\services\shared\` You can delete these files manually.

Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Start the domain and services

After you run the installer to apply the hotfix, start the domain and enable the services.

1. Run the ./infaservice.sh startup command to start the Informatica domain. By default, infaservice.sh is located in the following directory: `<Informatica installation directory>/tomcat/bin`
2. Enable the following Informatica application services from the Administrator tool:
   a. Model Repository Service
   b. Data Integration Service
   c. Content Management Service
   d. Informatica Cluster Service
3. Enable and upgrade the Catalog Service.
4. Upgrade the Data Integration Service.

Upgrade the Data Privacy Management Service

Upgrade the Data Privacy Management Service content and then enable the service to complete the upgrade job.

1. Log in to Informatica Administrator and upgrade the Data Privacy Management Service content.
2. On the **Processes** tab, verify that the Keystore and Shared Directory paths point to the 10.5 directory.
3. Enable the Data Privacy Management Service.
4. If you configured user activity monitoring, update the Event File Shared Location property on the User Activity Configuration tab of the Data Privacy Management Service.

   The mount location must be accessible to the domain machine and all cluster machines. The path to the mount location must be the same on all machines with Read, Write, and Execute permissions for the domain user on all machines.

Copy third-party JAR files

To perform scans, the required external third-party JARs must be available in an additional folder location. Ensure that you manually copy the JAR files to the location.

1. Browse to the following location: `<Informatica installation directory>/Informatica/<DPM folder>/externaljdbcjars`
2. Copy the JAR files from the folder.
3. Browse to the following location: `<Informatica installation directory>/services/CatalogService/ScannerJars/externalDependencies`
4. Copy each JAR to the respective sub-folder.

Upgrade the remote agent

If you use a Subject Registry for unstructured sources, upgrade the remote agent. If you want to create an agent for the first time, see the instructions to create the remote agent in the *Installation for Data Privacy Management* documentation.

1. Shut down the existing remote agent.

   Run the following command:

   ```
   cd <current agent directory>/bin
    ./siagent.sh shutdown
   ```

2. Extract the 10.5.11 agent binaries from the following location: `<Informatica installation directory>/SecureAtSourceService/InformaticaDiscoveryAgent/InformaticaDiscoveryAgent.zip`

   Extract the files to a folder. For example: `RemoteAgent`

3. From the current agent folder, copy the `<RemoteAgent>/tomcat/conf/server.xml` file and replace the file in the 10.5.11 agent directory.
4. Ensure that the remote agent keystore and truststore files are outside the remote agent directory or backed up and the location updated in the `server.xml` file.
5. Start the 10.5.11 remote agent.

   Run the following command:

   ```
   cd <10.5.11 remote agent directory>/bin
    ./siagent.sh startup
   ```

Upgrade additional products

You can use other Informatica products with Data Privacy Management. The products must be on versions that work with the Data Privacy Management version.

If you use the following products with Data Privacy Management, upgrade to the corresponding version:

- PowerExchange 10.5.11
- Test Data Management 10.5.11
- Axon Data Governance 7.3.7

Complete the Configuration for Upgrade or Apply Hotfix

If you edit odbc.ini, odbcinst.ini, sapnwrfc.ini, or infaservice.sh files, manually merge the changes from the backup files into the latest installed files. Check with your administrator for any customization to the *.ini files before you applied a hotfix or an upgrade. For instance, if an administrator added some variables or java options to the infaservice.sh script before you applied a hotfix or upgrade, manually merge the changes to the latest install file paths.

Manually merge the latest configuration changes into the following install file paths after applying hotfix or upgrade:

- $INFA_HOME/ODBC7.1/odbc.ini
- $INFA_HOME /ODBC7.1/odbcinst.ini
- $INFA_HOME/server/bin/sapnwrfc.ini
- $INFA_HOME/tomcat/bin/infaservice.sh

Delete temporary files

The upgrade process creates temporary directories and files. Delete the files to clean up files that are not required post upgrade and to allow security patches to take effect.

1. Browse to the following location: `<Informatica installation directory>/logs/<node name>/services/SecureAtSourceService/<Data Privacy Management service name>/`

   Add the relevant node name and service name in the path.
2. Delete the following directories:

   augmenter

   percolator

   retention

   ubamanager

Rolling back the services hotfix

You can roll back the hotfix if required. To roll back the hotfix, run the installer.

Before you roll back the hotfix

Before you roll back the hotfix, you must perform the prerequisite tasks.

1. Back up Data Privacy Management. See "Back Up Data Privacy Management" on page 21 for information about how to perform the back up.
2. Back up the catalog using the infacmd ldm BackupContents command. See "Back up the catalog data" on page 22 for information about the command.
3. Back up the repository for the Content Management Service and the Model repository. See "Back up other repositories and content" on page 23 for information.
4. Disable the following services:
   a. Data Privacy Management Service
   b. Catalog Service
   c. Content Management Service
   d. Data Integration Service
   e. Model Repository Service
5. Shut down the Informatica domain using the infaservice shutdown command.

Back Up Data Privacy Management

Optionally, you can choose to back up Data Privacy Management data including the Subject Registry data and Elasticsearch data.

You might require the data if the roll back of the hotfix fails.

Ensure the following statements are true before you perform the backup:

- The $INFA_HOME variable is set.
- The Subject Registry database is running.
- Elasticsearch is running.
- UBA Manager and Percolator system jobs are running.
- You have created a directory to store the backup created by the utility. For example: mkdir /home/ilmsatsqe/DPMBackup

Use the following tools in this order to back up the data:

Database utilities

Use the database utilities to back up the Data Privacy Management repository data and user activity data.

infacmd sats srBackup

Backs up the Subject Registry data.

dpmbackup.sh utility

Back up repository and user activity Data

Back up the Data Privacy Management repository data. If you configured user activity monitoring, back up the user activity data.

1. Back up the database repository contents for the Data Privacy Management Service.

   Example for Oracle:

   ```
   exp system/oracle@ORCL OWNER=SATS_REPO FILE=DPM_REPO.dmp
   ```

2. If you enabled User Activity and anomalies were generated in Data Privacy Management, back up the `/var/lib/hadoop-yarn/<dpm_ServiceName>_elasticsearch` directory from the Hadoop node.

Back Up Data Privacy Management Data with infacmd

Back up the Data Privacy Management data with the infacmd sats srBackup command.

The infacmd backs up the Subject Registry tables.

1. Verify that the instance contains the `sr_config.json` file in the following location: `<Informatica installation directory>/SecureAtSourceService/config`
2. Browse to the bin folder location:

   ```
   cd $INFA_HOME/isp/bin
   ```

3. If you use custom SSL certificates, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format.

   For example:

   ```
   export INFA_TRUSTSTORE=<Custom SSL directory>

   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

4. Run the following command to back up the Subject Registry tables:

```
./infacmd.sh sats srBackup -dn <domain name> -un <domain user name> -pd <domain user password> -sn <Data Privacy Management Service name> -of <output ZIP file path>
```

The output ZIP file path is the path and file name of the Subject Registry data backup file.

- For example:

```
./infacmd.sh sats srBackup -dn Domain_abc345.cfh.com -un Administrator -pd abc@123 -sn DPM -ll DEBUG -of /data/DPM_BACKUP.zip
```

Back Up Data Privacy Management with the backup utility

Back up the data using the dpmbackup.sh utility. The utility backs up the Subject Registry and Elasticsearch data.

1. If you use custom SSL certificates, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format.

   For example:

   ```
   export INFA_TRUSTSTORE=<Custom SSL directory>

   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

2. Browse to the `dpmbackup.sh` utility location: `cd <Extracted installer binary files location>/properties/utils/upgrade/DPM/`

3. Run the following command:

   ```
   sh dpmbackup.sh -d <domain name> -u <user name> -p <password> -s DPM -f /<Complete path to the backup folder>
   ```

   For example:

   ```
   sh dpmbackup.sh -d Domain_invrhost.inica.com -u Administrator -p abc@123 -s DPM -f /home/ilmsatsqe/DPMBackup
   ```

   Note: If you use `./` to run the command, ensure that you have Execute permission on the utility file.

   The utility creates an `upgrade_10_5_11.prop` files in the `<Informatica installation directory>/SecureAtSourceService/config` folder. The file contains the path to the backed up data.

   Note: The utility disables the Data Privacy Management Service in **STOP** mode.

The utility creates an `ESBackup` folder and `SRBackup` folder in the backup location. If you do not have a Subject Registry, an empty SRBackup folder is created.

Back up the catalog data

Back up the Catalog data. You might require the data if you need to roll back the upgrade.

Ensure the following statements are true before you perform the backup:

- The Catalog Service is running.
- The cluster is running.
- You created a directory to store the backup created by the infacmd. For example: mkdir /home/ilmsatsqe/CSBackup

Use the following tools to back up the data:

infacmd ldm backupContents

You can use the backup data if you need to roll back the upgrade.

export utility

Use the backed up content to restore the data after upgrade.

Both methods back up the same data, but the format differs.

Back up the catalog data with infacmd

Run the infacmd to back up the Catalog data.

The command creates a `.zip` file of the directory in the local machine.

1. Browse to the bin folder location:

   ```
   cd $INFA_HOME/isp/bin
   ```

2. Perform the following steps to back up the data with the infacmd:
3. Run the following command:

   ```
   cd $INFA_HOME/isp/bin
   ```

   For example:

   ```
   sh infacmd.sh ldm backupContents -dn Domain_name.informatica.com -un Administrator -
   pd Administrator -sn CS -mode ONLINE -of /LDM_Backup/LDM.zip
   ```

   If the command fails, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format. For example:

   ```
   export INFA_TRUSTSTORE=$INFA_HOME/services/shared/security/
   ```

   ```
   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

Back up the catalog data with the export utility

Run the export utility to back up the catalog data.

The export utility is available in the following directory where you extracted the installer binary files:
`<Extracted installer binary files location>/properties/utils/upgrade/EDC/export.jar`

1. Copy the `application.properties` file from the following folder to the folder created for the backup:
   `<INFA_HOME>/logs/<NODE_NAME>/services/CatalogService/<SERVICE_NAME>/<SSCNNAME>/spark/application.properties`

   a. Run the following command to back up the data:

      ```
      java -jar export.jar export
      ```

2. If the Catalog Service is enabled for SSL, set the following environment variables:
   - INFA_TRUSTSTORE
   - Encrypted INFA_TRUSTSTORE_PASSWORD

     Note: See the sample command to encrypt password: `$INFA_HOME/server/bin/pmpasswd <password>`

Back up other repositories and content

You can choose to back up other repository content. It is recommended that you back up required repository data.

Back up the repositories and content for the Model Repository Service and the Content Management Service.

1. Back up the database repository contents for the Content Management Service.

   Example for Oracle:

   ```
   exp system/oracle@ORCL OWNER=CMS_REPO FILE=CMS_REPO.dmp
   ```

2. Log in to the Administrator tool.
3. Select the Model Repository Service.

4. Select **Actions** > **Repository Contents** > **Backup**.
5. Provide the credentials to log in to the domain.
6. Provide the name of the output file that will contain the backed up content.

   Tip: View the general properties of the node to determine the path of the backup directory. The default path is: `<Informatica installation directory>/server/infa_shared/Backup`

Roll back the services hotfix in console mode

You can roll back the hotfix that you applied. To roll back the hotfix in console mode, run the installer.

1. Run the installer using the ./install.sh command.
2. Press **Y** to confirm that you want to proceed with the installation.
3. Press **5** to roll back the hotfix.
4. At the PowerCenter server location prompt , press **Y** to continue.
5. Press **Y** to continue.
6. Press **2** to roll back the hotfix.
7. Press **2** to accept the license.
8. Verify the prerequisites and press **Enter**.
9. Enter the directory where you installed Informatica and press **Enter**.
10. Press **2** to confirm that you configured the Catalog Service on the node.

    Note: If you confirm that you configured the Catalog Service on the node where you plan to roll back the hotfix, you must validate the backup on the node. Press **1** to skip the backup validation and proceed to step 11.

    You must skip the validation in the following scenarios:

    - You did not configure the cluster shared file system path for the Informatica Cluster Service on a multi-node setup.
    - You configured multiple nodes for the Catalog Service and you do not want to validate the backup on each node.
    - You enabled the Model Repository Service and the Data Integration Service, but you did not create the Catalog Service and the Informatica Cluster Service.
11. Press **2** to confirm that you backed up the catalog data using the infacmd ldm backupContents command.
12. Enter the location of the backup file. For example, `/data/Informatica/LDM_BACKUP1050SAML12.zip`.

    Note: If the SEARCH store is not included in the backup, the validation fails with an error. You can skip the backup validation if the backup does not include the SEARCH store.
13. Press **Enter** to start the rollback.
14. At the Pre-Installation Summary, press **Enter** to continue.
15. Press **Enter** to exit the installer when the rollback completes successfully.

    Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Roll back the services hotfix in silent mode

To roll back the hotfix in silent mode, update the SilentInput.properties file and then run the silent installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that are required by the installer.

1. Go to the root of the directory that contains the installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. Set the value to 1 to roll back the current hotfix.
USER_INSTALL_DIR	Directory for the Informatica installation where you want to roll back the hotfix.
ENABLE_USAGE_COLLECTION	Enables the software to automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool. For more information about how to disable sending usage statistics, see the *Informatica Administrator Guide*. You must set the value to 1 to roll back the hotfix.
INSTALLATION_ENVIRONMENT	You can ignore the property during rollback.
EDC_CATALOG_INST	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations. Set the property to true if the Catalog Service runs on the node on which you want to apply the hotfix.
EDC_HF_BACKUP	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you have set EDC_CATALOG_INST=true. Set the property to true if you have taken a backup of the catalog.
EDC_BACK_UP_DIR	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you set the EDC_CATALOG_INST and EDC_HF_BACKUP properties to true. Enter the location of the catalog data backup file.

5. Save the properties file with the name SilentInput.properties.
6. Go to root of the Informatica services installer directory.
7. Verify that the directory contains the SilentInput.properties file that you edited and saved.
8. On a shell command line, enter the following command to run the silent installer:

   ./silentInstallHotFix.sh.

   The installer removes the last hotfix and restores the previous version of Informatica.

9. Complete the post rollback tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

After you roll back the hotfix

To complete roll back of the hotfix, perform the post requisite tasks after you run the installer.

1. Start the Informatica domain.
2. Remove the contents of the Model repository. Use the infacmd mrs deleteContents command to remove the Model repository contents.
3. Enable the Model Repository Service.
4. Restore the Model repository content using the Model repository backup of the previous version. Use the infacmd mrs RestoreContents to restore the Model repository content.
5. Enable the Data Integration Service.
6. Enable the Content Management Service.
7. Run the infacmd ihs cleanCluster command to clean the Informatica Cluster Service.
8. Enable the Informatica Cluster Service.
9. Run the infacmd ldm restoreContents command to restore content from the previous version of the catalog.
10. From the Informatica Administrator, remove any custom properties that you configured for the Catalog Service after upgrade.
11. Enable the Catalog Service.
12. Restore Data Privacy Management backup of the previous version.
13. Enable the Data Privacy Management Service.

Applying the client hotfix

When you apply the hotfix, the installer backs up existing directories, applies the new version of the client, and restores or updates required configuration and run-time files.

You can run the client installer to apply a hotfix to Informatica clients that you use. After you apply the hotfix, you can remove the backup files of the distribution packages from the backup folder.

Apply the client hotfix in graphical mode

When you run the installer in graphical mode, a console window opens and runs in the background. If you close this window, the installation stops.

1. Log in to the machine with a system user account. The user account must be the same account used to install the previous version of Informatica services.
2. Close all other applications.
3. To begin the installation, run install.bat from the root directory where you unzipped or untarred the client hotfix installation package.

4. On the Informatica 10.5.11 page, select **Apply hotfix to a version from 10.5 through 10.5.10, or roll back the hotfix**, and then click **Start**.

   The **Installation Type** page appears.
5. Select **Apply the hotfix** to choose to apply the hotfix.
6. Verify that all requirements are met before you continue the hotfix, and then click **Next**.

   The **Installation Directory** page appears.
7. Enter the absolute path for the directory in which the current version of the Informatica client is installed and specify the installation environment.
8. If you want to install distribution packages through the Informatica installer, select the check box.
9. If you choose to install distribution packages, select one or more packages from the list that you want to install.
10. Click **Next**.

    The **Pre-Installation Summary** page appears.
11. Review the installation information, and then click **Install** to apply the hotfix.

    The installer copies the Informatica files to the installation directory.
12. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Apply the client hotfix in silent mode

To apply the hotfix in silent mode, create the SilentInput.properties file and then run the installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the client installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica client installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 0 to apply the hotfix.
USER_INSTALL_DIR	Directory for the Informatica client installation where you want to apply or roll back the hotfix. To apply the hotfix, enter the absolute path for the directory in which the current version of the Informatica clients is installed.

Property Name	Description
INSTALL_HADOOP_LIBRARIES	Determines whether to install distribution packages through the installer. Set the value to true if you want to install distribution packages through the installer. Set the value to false if you don't need distribution packages or if you want to install them later.
SELECTED_HADOOP_LIBRARIES	Determines the distribution packages that you want to install from the supported packages list. Enter the distribution packages that you want to install, separating multiple packages with a comma.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. Double-click the silentInstallHotFix.bat to apply the hotfix.

   The installer copies the Informatica client files to the installation directory.
7. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Sample silent input properties

The following example shows the contents of the `SilentInput.properties` file when you apply or roll back the hotfix client in silent mode.

```
############################################################
# Informatica Installer Build Details
# Copyright (c) 1993-2026 Informatica LLC
# This software contains confidential and proprietary
# information of Informatica LLC.
# All Rights Reserved.
############################################################

# Use the following guidelines when editing this file
# * Use this file to install without user interaction.
# * After you create the properties file, save the file with the name
SilentInput.properties
# * Any error condition that leads to failure, such as an invalid
# installation directory, generates a log file in the user home directory.
# For example:  c:\silentErrorLog<time_stamp>.log

############################################################


#######
## *INSTALL_TYPE - Set this value to '0' to apply the hotfix. Set this value to '1' to
roll back the hotfix.

INSTALL_TYPE=0


# * The USER_INSTALL_DIR variable must point to a valid directory with write
#     permissions enabled.

USER_INSTALL_DIR=c:\Informatica\10.5

#######
# After you create the properties file, save the file with the name
SilentInput.properties and
#     run the silent installer to perform the Informatica client installation.
#######
```

Remove the distribution packages from the backup location

After you apply the hotfix, remove the distribution packages from the backup folder to mitigate the security vulnerabilities.

When you apply the hotfix, all the existing files in the Informatica installation directory are backed up. You need to remove the distribution packages backup from the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\clients\DeveloperClient\hadoop\<distribution package_version>`

The following example shows the backup location for a distribution package when you apply the hotfix: `C:\Informatica\BACK_FROM_3\clients\DeveloperClient\hadoop\EMR_6.4`

Note: The deletion process doesn't remove all files of the distribution packages from the backup folder. Some files might still exist in the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\clients\DeveloperClient\` You can delete these files manually.

Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Rolling back the client hotfix

You can roll back the hotfix if required. To roll back the hotfix, perform the required prerequisite tasks and then run the installer.

Rolling back the client hotfix in graphical mode

When you run the installer in graphical mode, a console window opens and runs in the background. If you close this window, the rollback stops.

1. Log in to the machine with a system user account. The user account must be the same account used to install the previous version of Informatica services.
2. Close all other applications.
3. To begin the installation, run install.bat from the root directory where you unzipped or untarred the client hotfix installation package.
4. On the Informatica 10.5.11 page, select **Apply hotfix to a version from 10.5 through 10.5.10, or roll back the hotfix**, and then click **Start**.

   The **Installation Type** page appears.
5. Select **Roll back the hotfix** to choose to roll back the hotfix.
6. Verify that all requirements are met before you continue the rollback, and then click **Next**.

   The **Installation Directory** page appears.
7. Enter the absolute path for the directory in which the current version of Informatica clients is installed, and then click **Next**.

   The **Pre-Installation Summary** page appears.
8. Review the installation information, and then click **Install** to roll back the hotfix.

   The installer removes the last hotfix and restores Informatica clients to the previous version.

9. Complete the post-installation tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Rolling back the client hotfix in silent mode

To roll back the hotfix in silent mode, create the SilentInput.properties file and then run the installer with the file.
Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the client installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica client installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 1 to roll back the hotfix.
USER_INSTALL_DIR	Directory for the Informatica client installation where you want to roll back the hotfix. Enter the absolute path for the directory in which the current version of the Informatica clients is installed.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. To roll back the hotfix on Windows, double-click the silentInstallHotFix.bat file.

   The installer removes the last hotfix and restores the previous version of Informatica clients.
7. Complete the post-installation tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

CHAPTER 3

Before You Upgrade

This chapter includes the following topic:

- Before you Begin, 31

Before you Begin

Verify the status of services and jobs in Data Privacy Management, and download all required Informatica software before you begin the upgrade.

System Prerequisites to Upgrade

Before you start the upgrade as a non-root user with sudo privileges, validate the following prerequisites:

- At least 100 GB of free disk space on the machine where the Informatica domain runs.
- Java Development Kit (JDK) 17 is installed.
- If you are upgrading from a cluster enabled for Kerberos and SSL, take a backup the Informatica domain truststore and default keystore files.
- Verify that the domain configuration repository is available during the upgrade.
- Verify that ntpd is synchronized between the Informatica domain node and the cluster nodes.
- Install the following applications and packages on all nodes:

  Bash shell

  rsync

  libcurl

  xz-libs

  systemctl

  zip

  unzip

  tar

  wget

  scp

  rpm

  curl

nslookup

md5sum

netstat

ping

ifconfig

cksum

dnsdomainname

libncurses5

OpenSSL version 1.0.1e-30.el6_6.5.x86_64 or later.

Note: Verify that the $PATH variable points to the `/usr/bin` directory to use the correct version of Linux OpenSSL.

- The following default ports must be available:

Service	Default Port
Data Privacy Management web URL	18295
Informatica Domain	8443
TCP Listener	51000

- The following default ports for the Informatica Cluster Service must be available:

Service	Default Port
HTTP/HTTPS	9075
Nomad Serf	4648
Nomad web URL	4646
Nomad RPC	4647
ZooKeeper	2181
ZooKeeper peer	2888
ZooKeeper leader	3888
Solr	8983
MongoDB	27017
PostgreSQL	5432
Elasticsearch	9300
Elasticsearch web URL (optional)	9200

Service	Default Port
Spark	7077
Spark web URL	8080, 8040

Verify Required Versions

Verify that you are on the required version and configuration of all required components.

Data Privacy Management version

You must be on the following versions to upgrade to Data Privacy Management 10.5.11:

Enterprise Data Catalog 10.5.x

Data Privacy Management 10.5.x

Cluster

You must be on an instance that has a Catalog Service on an internal cluster.

You cannot upgrade from an instance that has a Catalog Service on an external cluster.

Verify the Services

Verify that the following services are enabled:

- Data Privacy Management Service
- Catalog Service
- Content Management Service
- Data Integration Service
- Informatica Cluster Service
- Model Repository Service
- Monitoring Model Repository Service
- Data Privacy Management Service

Verify the Status of Jobs

Log in to Data Privacy Management.

- If you enabled User Activity, the following system jobs must be running:
  - TCP Listener
  - Augmentor
  - UBA Manager
  - Percolator
  - Elasticsearch

Go to the **Jobs** workspace and verify that all jobs are in one of the following states:

- Completed
- Warning
- Terminated

If the list includes jobs in failed, paused, or in progress states, perform the following steps:

- Terminate failed jobs.
- Terminate or allow jobs that are paused or in progress to complete.
- Identify failed subject registry scan jobs. Files generated when a subject registry scan job fails remain unencrypted in the following location in HDFS: `Informatica/SecureAtSource/<DPM service name>/SubjectRegistry`
  See the job logs for file names. The upgrade does not handle these files.

Important: Do not begin the upgrade process if a job is in Failed, Paused, or Running state. You cannot restart these jobs after you upgrade.

Disable Polling

Disable polling jobs before you upgrade. Polling jobs are enabled if you have data stores with the **Auto Sync with Catalog** option enabled.

1. Log in to Data Privacy Management.
2. On the **Jobs** workspace, click the **Future Jobs** tab, and verify that the following jobs appear in the list:
   - Polling Scan Results
   - Polling Data Store Updates
3. Disable the polling jobs.

   To disable polling, use the satscurl command line utility.

   a. Download the Data Privacy Management satscurl command line utility from the following location in the Informatica tsftp server: `/updates/ILM/SecureAtSource/Tools/satscurl/10.5.2`

      The following utility files are available for Windows and Linux operating systems:

      - SATScurl_10.5.2_Windows.zip
      - SATScurl_10.5.2_Linux.zip

   b. Extract the file to the required location.

   c. Run the following command: `./satscurl -a https://<host name>:<port number> -u <Data Privacy Management user name> -p <password> disablePolling`

      The host name and port number must be the values that you configure to access Data Privacy Management.

      For example: `./satscurl -a https://abccent7dsgace01.abc.com:18295 -u Administrator -p admin123 disablePolling`

When you disable the Polling jobs, the Polling Scan Results and Polling Data Store Updates jobs disappear from the list of jobs.

Configure Custom SSL Certificates Overview

During an install or an upgrade, you can use SSL certificates of your choice, referred to as custom SSL certificates, to secure components associated with the Informatica Cluster Service. You can choose to use CA-signed custom SSL certificates or self-signed custom SSL certificates as the client and cluster certificates.

If you choose to use CA-signed custom SSL certificates, use the generate_csr.sh and generate_certs.sh scripts to generate the required certificates.

If you choose to use self-signed custom SSL certificates, use the custom SSL utility bundled with the installer to generate the required certificates.

Requirements to Enable Custom SSL Certificates

Before you enable custom SSL for Enterprise Data Catalog, secure the Informatica domain with custom SSL certificates.

Verify the following prerequisites for the Informatica domain:

- The custom truststore and keystore files are placed in a custom directory. The truststore file name must be infa_truststore.jks.
- The directory that stores the keystore and truststore files are accessible to the command line programs.

Important: The installer places the default infa_truststore.jks and keystore files in the `<Informatica installation directory>/services/shared/security` directory on each node. Do not overwrite, delete, or move the default truststore and keystore files. Do not place the custom truststore and keystore files in the directory.

To know about how to convert a non-SSL Informatica domain to an SSL-enabled Informatica domain, see the Knowledge Article Convert a non-SSL Informatica domain to an SSL-enabled Informatica domain.

Generate CA-signed SSL Certificates

You have a custom SSL certificate for the Informatica domain, and plan to configure custom SSL for Data Privacy Management. In this scenario, you must generate CA-signed certificates.

Use the `generate_csr.sh` and `generate_certs.sh` scripts to generate the Certificate Signing Request (CSR) to send to a CA and generate the required custom SSL certificates. You can download the scripts from the Akamai Download Manager.

Perform the following steps to use the scripts to generate the custom SSL certificates:

1. Extract the generate_csr.sh and generate_certs.sh scripts from the following location: `<Location of installer files>/properties/utils/CustomSSLScriptsUtil_ExternalCA`.
2. Set the JAVA_HOME environment variable to point to JDK 17.
3. In the gen_csr.properties file, provide the values for the following parameters:

Parameter	Description
InfaDomainKeystorePassword	The Informatica domain keystore password in plain text. **Note:** You must enter RFC2253 compliant values for these parameters. If the following special characters: `, + " \ < > ;` are present, enclose the values in single quotes and prefix each special character with a backslash (\).
ServerHosts	The Informatica Cluster Service hosts that include the data nodes, processing nodes, and gateway node. Enter a comma-separated list of FQDNs of cluster nodes.
ClientHosts	Comma-separated list of unique host names of domain nodes and cluster nodes.
InfaDomainName	The Informatica domain name.
ICSServiceName	The name of the Informatica Cluster Service.

Parameter	Description
KeysOutputDir	The directory to store the generated keys. Specify the $CUSTOM KEYSTORE LOC directory to avoid the additional steps to copy the generated keys. The $ICS SERVICENAME/client_certs and the $ICS SERVICENAME/cluster_certs directories are created under the $CUSTOM KEYSTORE LOC directory. $CUSTOM KEYSTORE LOC is the directory where the custom keystore for the Informatica domain (infa_keystore.jks) is located. $ICS SERVICENAME is the name of the Informatica Cluster Service.
CertsOutputDir	The $CUSTOM TRUSTSTORE LOC directory to store the generated truststore files. The $ICS SERVICENAME/client_certs and the $ICS SERVICENAME/cluster_certs directories are created under the $CUSTOM TRUSTSTORE LOC directory. The $CUSTOM TRUSTSTORE LOC is the directory where the custom truststore for the Informatica domain (infa_truststore.jks) is located.
DNSDomainName	The DNS domain name for the cluster nodes.
ClusterCert_OrganizationUnit	Optional. The value for the OrganizationUnit for the cluster nodes certificate.
ClusterCert_Organization	The value for the Organization for the cluster nodes certificate. **Note:** Verify that the combination of the Organization (O) and the Organizational Unit (OU) parameters in the certificate subject is distinct for the cluster and client certificates
ClusterCert_Location	The value for the Location for the cluster nodes certificate.
ClusterCert_State	The value for the State for the cluster nodes certificate.
ClusterCert_CountryCode	The value for the Country Code for the cluster nodes certificate.
DomainCert_OrganizationUnit	Optional. The value for the Organization Unit for the domain nodes certificate.
DomainCert_Organization	The value for the Organization for the domain nodes certificate. **Note:** Verify that the combination of the Organization (O) and the Organizational Unit (OU) parameters in the certificate subject is distinct for the cluster and client certificates
DomainCert_Location	Optional. The value for the Location for the domain nodes certificate. Default is the ClusterCert_Location parameter.
DomainCert_State	Optional. The value for the State for the domain nodes certificate. Default is the ClusterCert_State parameter.
DomainCert_CountryCode	Optional. The value for the Country Code for the domain nodes certificate. Default is the ClusterCert_CountryCode parameter.

Parameter	Description
Custom_Server_Certificate_CN	Optional. The value for the Common Name in the cluster nodes certificate that can be used instead of the default $InfaDomainName-$ICSServiceName.$DNSDomainName value. **Note:** You must enter RFC2253 compliant values for these parameters. If the following special characters: , + " \ < > ; are present, enclose the values in single quotes and prefix each special character with a backslash (\).
Custom_Client_Certificate_CN	Optional. The value for the Common Name in the domain nodes certificate that can be used instead of the default $InfaDomainName-$ICSServiceName.$DNSDomainName value. Default is the Custom_Server_Certificate_CN parameter. **Note:** You must enter RFC2253 compliant values for these parameters. If the following special characters: , + " \ < > ; are present, enclose the values in single quotes and prefix each special character with a backslash (\).

Note: If the values contain spaces or special characters, you must enclose the values within double-quotes.

4. Run the generate_csr.sh script using the following command to generate the .csr files to send to an external CA: `./generate_csr.sh gen_csr.properties`
   The following files are generated for the cluster:

   infa_nodecert.csr

   infa_privkey.key

   infa_privkey.pem

   keystore.jks

   The following files are generated for the client:

   infa_nodecert.csr

   infa_privkey.key

   infa_privkey.pem

   keystore.jks

   browser_cert.csr

   browser_keystore.jks

   browser_privkey.key

   browser_privkey.pem
5. Validate the contents of the .csr files. Run the following command to view the contents: `keytool -printcertreq -file $PATH TO CSR`
6. Send the following .csr files to an external CA for signing:
   - <CertsOutputDir>/<ICSServiceName>/client_certs/infa_nodecert.csr
   - <CertsOutputDir>/<ICSServiceName>/cluster_certs/infa_nodecert.csr
   - <CertsOutputDir>/<ICSServiceName>/client_certs/browser_cert.csr

   Note: The browser_cert.csr file is required if you want to create the browser certificates to view the scan job logs on Nomad.

7. After you receive the certificates or certificate chains from the CA in .pem format, "Validate the CA-signed Certificates" on page 39 and store the certificates to a location under the $INFA HOME directory on your machine.

   Note: If you receive the certificates or certificate chains from the CA in .cer format, run the following command to convert the files to pem format: `openssl x509 -inform der -in <certificate file name>.cer -outform pem -out <certificate file name>.pem`.

   If you receive a certificate chain from the CA, you must extract the root certificate, intermediate certificates, and the end user certificate.

8. In the gen_certs.properties file, provide the values for the following parameters:

Parameter	Description
InfaDomainKeystorePassword	The Informatica domain keystore password in plain text.
InfaDomainTruststorePassword	The Informatica domain truststore password in plain text.
ClusterCertificate	The path to the cluster certificate signed by the CA in .pem format. This is an end user certificate.
ClientCertificate	The path to the client certificate signed by the CA in .pem format. This is an end user certificate.
BrowserCertificate	The path to the browser certificate signed by the CA in .pem format.
ICSServiceName	The name of the Informatica Cluster Service.
IsCACertificateChainAvailable	Specify if the CA certificate chain is available as a single .pem file. Enter true or false. **Note:** The certificate chain must contain only the root and intermediate certificates.
SingleCACertificateChain	The path to the CA certificate chain in .pem format.
IndividualCertificatesFromCAChain	Optional. Only required if the IsCACertificateChainAvailable parameter is set to false. Comma-separated paths to the public certificates in the CA certificate chain in .pem format if the complete CA certificate chain is available as individual .pem files.

Parameter	Description
KeysOutputDir	The $CUSTOM KEYSTORE LOC directory store the generated keys. The $ICS SERVICENAME/client_certs and $ICS SERVICENAME/cluster_certs directories are created under the $CUSTOM KEYSTORE LOC directory. $CUSTOM KEYSTORE LOC is the directory where the custom keystore for the Informatica domain (infa_keystore.jks) is located. $ICS SERVICENAME is the name of the Informatica Cluster Service
CertsOutputDir	The $CUSTOM TRUSTSTORE LOC directory to store the generated truststore files. The $ICS SERVICENAME/client_certs and the $ICS SERVICENAME/cluster_certs directories are created under the $CUSTOM TRUSTSTORE LOC directory. The $CUSTOM TRUSTSTORE LOC is the directory where the custom truststore for the Informatica domain (infa_truststore.jks) is located.

9. Run the generate_certs.sh script using the following command to generate the certificates: `./generate_certs.sh gen_certs.properties`
   The keystore.jks keystore and the infa_privkey.pem private keys are stored at $CUSTOM KEYSTORE LOC/$ICSServiceName/client_certs and $CUSTOM KEYSTORE LOC/$ICSServiceName/cluster_certs directories.

   The truststore.jks truststore and the infa_nodecert.pem, infa_nodecertkey.pem, and infa_pubcert.pem public keys are stored at $CUSTOM TRUSTSTORE LOC/$ICSServiceName/client_certs and $CUSTOM TRUSTSTORE LOC/$ICSServiceName/cluster_certs directories.
10. Optional. The directories $CUSTOM KEYSTORE LOC and $CUSTOM TRUSTSTORE LOC are generally the same. If the <KeysOutputDir> location is not the same as $CUSTOM KEYSTORE LOC and <CertsOutputDir> location is not the same as $CUSTOM TRUSTSTORE LOC, move the keys and certificates to the respective directories.

    Note: Verify that the $CUSTOM KEYSTORE LOC and the $CUSTOM TRUSTSTORE LOC directories have the required user privileges. Also, validate that the user has minimum chmod 700 permissions configured for the directories and chmod 600 permissions configured for the files that are copied to the directories.

Validate the CA-signed Certificates

You must use a single CA for the cluster and client certificates. After you receive the signed certificates from the CA, you must verify that each certificate is an X.509 certificate in .pem format.

Run the following command to view the contents of the signed cluster and client certificates: `keytool -printcert -file $PATH TO CERTIFICATE PEM FILE`.

Validate the following requirements for the cluster and client certificates:

Prerequisite	Certificate Requirement
Mandatory fields	For the cluster certificate, consider the following key usage requirements: keyUsage = digitalSignature,keyEncipherment extendedKeyUsage = serverAuth,clientAuth For the client certificate, consider the following key usage requirements: keyUsage = digitalSignature extendedKeyUsage = clientAuth
Subject Alternate Name (SAN)	For the cluster certificate, the SAN must include the list of cluster nodes in the following format: SAN=DNS:$CLUSTER HOST1 FQDN,DNS:$CLUSTER HOST2 FQDN,DNS:$CLUSTER HOST3 FQDN The client certificate must contain the FQDNs for the cluster nodes. For the client certificate, the SAN must include the list of all Informatica nodes in the following format: SAN=DNS:$INFA DOMAIN HOST1 FQDN,DNS:$INFA DOMAIN HOST2 FQDN The client certificate must contain the FQDNs for both the domain and cluster nodes.

CLUSTER HOST FQDN represents the fully qualified domain name for the cluster gateway host, processing nodes, and data nodes in the cluster.

INFA DOMAIN HOST FQDN represents the fully qualified domain name of the Informatica domain gateway host, domain nodes, cluster gateway host, processing nodes, and data nodes in the cluster.

Note: Verify that the custom certificate location for the domain nodes contains the infa_truststore.pem file. Also, verify that all the certificates in the CA certificate chain are present in the truststore.jks and the infa_pubcert.pem files.

Generate Self-signed Custom SSL Certificates

You have a custom SSL certificate for the Informatica domain, and you want to use self-signed custom SSL certificates as the client and cluster certificates for the Informatica Cluster Service.

Use the custom SSL utility bundled with the installer to generate the required SSL certificates.

Perform the following steps to use the custom SSL utility to generate the certificates:

1. Extract `GenerateCustomSslUtility.zip` from the following location: `<Location of installer files>/properties/utils/CustomSslCertsUtility/`.
2. Set the JAVA_HOME environment variable to point to JDK 17.
3. Configure the following parameters in the `input.properties` file that you extracted from the `GenerateCustomSslUtility.zip` file:

Parameter	Description
KeystoreFile	Path to a custom keystore file along with file name. The keystore type must be in JKS. X509 format. The file must contain a single private key entry with the complete certificate chain. Verify that the file has signing capability.
KeystorePassword	Password of the custom keystore file in plain text format.

Parameter	Description
TruststoreFile	Path to a custom truststore file along with file name. the truststore type must be in JKS. X509 format. The file must contain the public certificates corresponding to the private key entry in the keystore file.
TruststorePassword	Password of the custom truststore file in plain text format.
ISPDomainKeystorePassword	Password of Informatica domain keystore in plain text format. The utility uses the password for the cluster and client keystore.jks file.
ISPDomainTruststorePassword	Password of the Informatica domain truststore in plain text format. The utility uses the password for the cluster and client truststore.jks file
KeystoreOutputDir	Represents the location of the Informatica domain custom keystore that you provided when you installed Enterprise Data Catalog.
TruststoreOutputDir	Represents the location of the Informatica domain custom truststore that you provided when you installed Enterprise Data Catalog. **Note:** Verify that the KeystoreOutputDir and TruststoreOutputDir parameters point to the same directory.
ServerNodes	Comma-separated list of fully qualified domain names of nodes that you plan to configure as data nodes, processing nodes, service hosts, and gateway node when you configure the Informatica Cluster Service.
IcsServiceName	Name of the Informatica Cluster Service.
ClientNodes	Comma-separated list of fully qualified domain names of nodes that you plan to configure as Informatica domain hosts, data nodes, processing nodes, service hosts, and gateway node.
IspDomainName	The Informatica domain name.
ClusterNodeDNSDomain	Domain name of the gateway host that you plan to configure for the Informatica Cluster Service.

4. Run the utility using the following command: `java -jar GenerateCustomSslUtility.jar -in input.properties`. The utility generates the following keys and client and cluster certificates:
   - Keys:
     - keystore.jks
     - infa_privkey.pem

     Note: The cluster keys are generated in the following directory: `<Keystore output directory>/<IcsServiceName>/cluster_certs`. The client keys are generated in the following directory: `<Keystore output directory>/<IcsServiceName>/client_certs`
   - Certificates:
     - truststore.jks
     - infa_pubcert.pem
     - infa_nodecert.pem

- infa_nodecertkey.pem

  Note: The cluster certificates are generated in the following directory: `<Truststore output directory>/<IcsServiceName>/cluster_certs`. The client certificates are generated in the following directory: `<Truststore output directory>/<IcsServiceName>/client_certs`

5. Copy the generated certificates to the required folders.
6. Assign the ownership of the following directories to the Informatica domain user:
   - <Keystore output directory>/<IcsServiceName>/cluster_certs
   - <Truststore output directory>/<IcsServiceName>/cluster_certs
   - <Keystore output directory>/<IcsServiceName>/client_certs
   - <Truststore output directory>/<IcsServiceName/client_certs

Note: Verify that all the client certificates are included in a single directory. Similarly, verify that all the cluster certificates are included in a single directory. You must also verify that the directories have the `chmod 700` permission configured and the files under the directories have the `chmod 600` permission configured.

Download the Required Informatica Software

Download the following Informatica software:

- Informatica services installer 10.5.11. Extract the files from the Informatica services 10.5.11 installer.
- Get the new license keys for the Informatica domain and the Informatica Cluster Service.
- Scanner binaries for 10.5.11. Download and save the scanner binaries to the following folder: `<extracted installer directory>/source`
  Verify that the Scanner binaries file name is `ScannerBinaries.zip`.
- If you want to use the Informatica Platform resource binary files from version 10.2 through 10.5.10, download the extended scanner binaries file.
  Verify that the Scanner binaries file name is `ExtendedScannerBinaries.zip`
- If you use PowerExchange with Data Privacy Management, download PowerExchange 10.5.11.
- If you use Axon Data Governance with Data Privacy Management, download Axon Data Governance 7.3.7.

Back Up the Informatica Domain

Before you upgrade the domain, back up the configuration metadata for the Informatica domain.

Complete the following steps to back up the Informatica domain:

- Run the infasetup BackupDomain command to back up the domain configuration database tables to a file.
- Back up the metadata configuration files to any directory accessible by the machines where you install Informatica.

Informatica includes command line programs to back up and restore the domain. infasetup is located in the following directory:

```
<Informatica installation directory>/isp/bin
```

To back up the domain with infasetup, use the following syntax:

```
BackupDomain
<<-DatabaseAddress|-da> database_hostname:database_port|

<-DatabaseConnectionString|-cs> database_connection_string>

<-DatabaseUserName|-du> database_user_name
```

```
<-DatabasePassword|-dp> database_password

<-DatabaseType|-dt> database_type

[<-DatabaseServiceName|-ds> database_service_name]

<-BackupFile|-bf> backup_file_name

[<-Force|-f>]

<-DomainName|-dn> domain_name

[<-Tablespace|-ts> tablespace_name (used for IBM DB2 only)]

[<-SchemaName|-sc> schema_name (used for Microsoft SQL Server only)]

[<-DatabaseTlsEnabled|-dbtls> database_tls_enabled]

[<-DatabaseTruststorePassword|-dbtp> database_truststore_password]

[<-TrustedConnection|-tc> trusted_connection (used for Microsoft SQL Server only)]

[<-EncryptionKeyLocation|-kl> encryption_key_location]
```

The following table describes the metadata files and the locations of the files:

Metadata File	Description	Location
nodemeta.xml	Contains metadata for a node.	Stored in the `isp/config` directory on each node in the domain. If you use the same backup directory name on all the nodes, rename nodemeta.xml before copying it to the backup location. For example, you back up nodemeta.xml to the /nodebak directory on nodeA and nodeB. Rename the configuration files so that on nodeA the file is backed up to /nodebak/nodemeta_A.xml, and on nodeB the file is backed up to /nodebak/nodemeta_B.xml.
domains.infa	Contains connectivity information for the gateway nodes.	Stored in one of the following locations: - The Informatica installation directory. - The location configured through the INFA_DOMAINS_FILE environment variable.

Back Up Data Privacy Management

Optionally, you can choose to back up Data Privacy Management data including the Subject Registry data and Elasticsearch data.

You might require the data if the roll back of the hotfix fails.

Ensure the following statements are true before you perform the backup:

- The $INFA_HOME variable is set.
- The Subject Registry database is running.
- Elasticsearch is running.
- UBA Manager and Percolator system jobs are running.
- You have created a directory to store the backup created by the utility. For example: mkdir /home/ilmsatsqe/DPMBackup

Use the following tools in this order to back up the data:

Database utilities

Use the database utilities to back up the Data Privacy Management repository data and user activity data.

infacmd sats srBackup

Backs up the Subject Registry data.

dpmbackup.sh utility

Back up repository and user activity Data

Back up the Data Privacy Management repository data. If you configured user activity monitoring, back up the user activity data.

1. Back up the database repository contents for the Data Privacy Management Service.

   Example for Oracle:

   ```
   exp system/oracle@ORCL OWNER=SATS_REPO FILE=DPM_REPO.dmp
   ```

2. If you enabled User Activity and anomalies were generated in Data Privacy Management, back up the `/var/lib/hadoop-yarn/<dpm_ServiceName>_elasticsearch` directory from the Hadoop node.

Back Up Data Privacy Management Data with infacmd

Back up the Data Privacy Management data with the infacmd sats srBackup command.

The infacmd backs up the Subject Registry tables.

1. Verify that the instance contains the `sr_config.json` file in the following location: `<Informatica installation directory>/SecureAtSourceService/config`
2. Browse to the bin folder location:

   ```
   cd $INFA_HOME/isp/bin
   ```

3. If you use custom SSL certificates, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format.

   For example:

   ```
   export INFA_TRUSTSTORE=<Custom SSL directory>

   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

4. Run the following command to back up the Subject Registry tables:

   ```
   ./infacmd.sh sats srBackup -dn <domain name> -un <domain user name> -pd <domain user password> -sn <Data Privacy Management Service name> -of <output ZIP file path>
   ```

   The output ZIP file path is the path and file name of the Subject Registry data backup file.

   - For example:

     ```
     ./infacmd.sh sats srBackup -dn Domain_abc345.cfh.com -un Administrator -pd abc@123 -sn DPM -ll DEBUG -of /data/DPM_BACKUP.zip
     ```

Back Up Data Privacy Management with the backup utility

Back up the data using the dpmbackup.sh utility. The utility backs up the Subject Registry and Elasticsearch data.

1. If you use custom SSL certificates, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format.

   For example:

   ```
   export INFA_TRUSTSTORE=<Custom SSL directory>

   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

2. Browse to the `dpmbackup.sh` utility location: `cd <Extracted installer binary files location>/properties/utils/upgrade/DPM/`

3. Run the following command:

   ```
   sh dpmbackup.sh -d <domain name> -u <user name> -p <password> -s DPM -f /<Complete path to the backup folder>
   ```

   For example:

   ```
   sh dpmbackup.sh -d Domain_invrhost.inica.com -u Administrator -p abc@123 -s DPM -f /home/ilmsatsqe/DPMBackup
   ```

   Note: If you use `./` to run the command, ensure that you have Execute permission on the utility file.

   The utility creates an `upgrade_10_5_11.prop` files in the `<Informatica installation directory>/SecureAtSourceService/config` folder. The file contains the path to the backed up data.

   Note: The utility disables the Data Privacy Management Service in **STOP** mode.

The utility creates an `ESBackup` folder and `SRBackup` folder in the backup location. If you do not have a Subject Registry, an empty SRBackup folder is created.

Back up the catalog data

Back up the Catalog data. You might require the data if you need to roll back the upgrade.

Ensure the following statements are true before you perform the backup:

- The Catalog Service is running.
- The cluster is running.
- You created a directory to store the backup created by the infacmd. For example: mkdir /home/ilmsatsqe/CSBackup

Use the following tools to back up the data:

infacmd ldm backupContents

You can use the backup data if you need to roll back the upgrade.

export utility

Use the backed up content to restore the data after upgrade.

Both methods back up the same data, but the format differs.

Back up the catalog data with infacmd

Run the infacmd to back up the Catalog data.

The command creates a `.zip` file of the directory in the local machine.

1. Browse to the bin folder location:

   ```
   cd $INFA_HOME/isp/bin
   ```

2. Perform the following steps to back up the data with the infacmd:
3. Run the following command:

   ```
   cd $INFA_HOME/isp/bin
   ```

   For example:

   ```
   sh infacmd.sh ldm backupContents -dn Domain_name.informatica.com -un Administrator -
   pd Administrator -sn CS -mode ONLINE -of /LDM_Backup/LDM.zip
   ```

   If the command fails, set the `INFA_TRUSTORE` and `INFA_TRUSTSTORE_PASSWORD` in encrypted format. For example:

   ```
   export INFA_TRUSTSTORE=$INFA_HOME/services/shared/security/
   ```

   ```
   export INFA_TRUSTSTORE_PASSWORD=hx/nRWisSjnQ0zEGV3N7j1FCGFOm5RfisQxKTdf5f8Y=
   ```

Back up the catalog data with the export utility

Run the export utility to back up the catalog data.

The export utility is available in the following directory where you extracted the installer binary files:
`<Extracted installer binary files location>/properties/utils/upgrade/EDC/export.jar`

1. Copy the `application.properties` file from the following folder to the folder created for the backup:
   `<INFA_HOME>/logs/<NODE_NAME>/services/CatalogService/<SERVICE_NAME>/<SSCNNAME>/spark/application.properties`

   a. Run the following command to back up the data:

      ```
      java -jar export.jar export
      ```

2. If the Catalog Service is enabled for SSL, set the following environment variables:
   - INFA_TRUSTSTORE
   - Encrypted INFA_TRUSTSTORE_PASSWORD

     Note: See the sample command to encrypt password: `$INFA_HOME/server/bin/pmpasswd <password>`

Back up other repositories and content

You can choose to back up other repository content. It is recommended that you back up required repository data.

Back up the repositories and content for the Model Repository Service and the Content Management Service.

1. Back up the database repository contents for the Content Management Service.

   Example for Oracle:

   ```
   exp system/oracle@ORCL OWNER=CMS_REPO FILE=CMS_REPO.dmp
   ```

2. Log in to the Administrator tool.
3. Select the Model Repository Service.
4. Select **Actions** > **Repository Contents** > **Backup**.
5. Provide the credentials to log in to the domain.

6. Provide the name of the output file that will contain the backed up content.

   Tip: View the general properties of the node to determine the path of the backup directory. The default path is: `<Informatica installation directory>/server/infa_shared/Backup`

Back Up the SSL Configuration

Back up the following SSL configuration files from the default location: `<Informatica installation directory>/services/shared/security`.

- Back up the domain truststore and keystore files.
- Back up the default keystore files.
- Back up all the keystore and truststore files that the application services use.

Back Up the Domain Information

Back up the following files:

- `<Informatica installation directory>/isp/config/keys/siteKey`
- `<Informatica installation directory>/domains.infa`
- `<Informatica installation directory>/tomcat/conf/server.xml`
- `<Informatica installation directory>/isp/config/nodemeta.xml`

Note: You must back up the binaries from the Informatica installation directory.

Complete Other Pre-Upgrade Tasks

Perform other pre-upgrade tasks and shut down the domain before you upgrade.

1. If the domain is enabled for Secure Sockets Layer (SSL), clear the configured values for the INFA_TRUSTSTORE and INFA_TRUSTSTORE_PASSWORD environment variables.
2. Disable the Informatica Cluster Service.
3. Run the following infacmd ihs cleancluster command from the `<Informatica installation directory>\isp\bin` folder:

   ```
   ./IHS cleancluster -dn <domain name> -un <domain user name> -pd <domain password> -sn <Informatica Cluster Service name>
   ```

   For example:

   ```
   ./infacmd.sh IHS cleancluster -dn Domain_domain1.xyz.com -un Administrator -pd abc@123 -sn IHS
   ```

   The command removes contents of the cluster.
4. Check the status of the Postgres service, and end any processes that might still be running.

   There must be no process running on the 5432 port.
5. Disable the following services:
   - Catalog Service
   - Content Management Service
   - Data Integration Service
   - Model Repository Service

- Monitoring Model Repository Service

6. Run the following command to shut down the Informatica domain:

```
cd $INFA_HOME/tomcat/bin
./infaservice.sh shutdown
```

CHAPTER 4

Upgrade to Version 10.5.11

Upgrade

You can upgrade to Data Privacy Management version 10.5.11 from version 10.5.

You can upgrade in console mode or silent mode.

Upgrade in Console Mode

You can upgrade in console mode on UNIX or Linux.

When you run the installer in console mode, the words quit, back, and help are reserved words. Do not use them as input text.

1. Log in to the machine with the same user account that you used to install the previous version.
2. Stop all processes that access the directory and subdirectories of the Informatica product to upgrade, including command prompts and tail logs.
3. On a shell command line, run the install file.

   The installer displays the message to verify that the locale environment variables are set.
4. If the environment variables are not set, press **n** to exit the installer and set them as required.

   If the environment variables are set, press **y** to continue.
5. Press **2** to upgrade Informatica.
6. Enter **Y** and press **Enter**.
7. Enter **Y** and press **Enter** to continue.
8. Press **2** to skip running the Informatica Upgrade Advisor.

   Informatica provides utilities to facilitate the Informatica services installation process. You can run the utility before you upgrade Informatica services. The Informatica Upgrade Advisor helps to validate the services and checks for obsolete services in the domain before you perform an upgrade.

   The installer displays a warning to shut down the Informatica domain that you want to upgrade before you continue the upgrade.
9. Read the terms and conditions of Informatica product usage toolkit and press **2** to continue the upgrade.

   Subject to your opt-out rights described below, the software will automatically transmit to Informatica in the USA the information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part

of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You can disable usage collection in the Administrator tool.

10. The **Upgrade Prerequisites** page displays the upgrade system requirements.

    Verify the requirements before you continue the upgrade.

11. Review the upgrade information and press **Enter** to continue.

    The **Upgrade Directory** panel appears.

12. At the prompt, enter the directory of the Informatica version you want to upgrade and the directory in which you want to upgrade to Informatica 10.5.11.

    The following table describes the directories you must specify:

Directory	Description
Directory of the Informatica product to upgrade	Directory that contains the version of Informatica services that you want to upgrade.
Directory for Informatica 10.5.11	Directory in which to install Informatica 10.5.11. Enter the absolute path for the installation directory. The directory cannot be the same as the directory that contains the previous version of Informatica services.The directory names in the path must not contain spaces or the following special characters: @|* $ # ! % ( ) { } [ ] , ; ' **Note:** If you use a special character such as á or €, unexpected results might occur at run time.

13. From the following installation options, select the upgrade environment based on your requirement:
    - Sandbox. Used for proof of concepts or as a sandbox with minimal users.
    - Development. Used for a design environment.
    - Test. Used for high-volume processing environment that resembles a production environment.
    - Production. Used for production environments with high-volume processing and high levels of concurrency meant for end users.
14. Select if you want to change the node host name, port numbers, or domain configuration repository. Press **1** to use the same node configuration as the previous version. Press **2** to change the node configuration.

    The **Component Selection** panel appears.

15. If you created a Catalog Service on the node, you must validate the Catalog backup before you upgrade. Press **1** if the node does not have a Catalog Service or press **2** if the node has a Catalog Service and press **Enter** to continue.
16. Press **2** to confirm that you backed up the catalog using both the export utility and the infacmd LDM backupContents command.
17. Specify the location of the directory containing the catalog backup.

    The catalog backup is validated.

18. Choose whether you want to install distribution packages through the Informatica installer.
    - Press **1** if you don't need distribution packages or if you want to install them later.
    - Press **2** if you want to install distribution packages through the installer.

    Default is 1.

19. If you choose to install distribution packages, select one or more packages from the list that you want to install. Separate multiple packages with a comma.

    Default is 1.

20. Press **Enter**.

    The **Domain Security Encryption Key** panel appears.

21. If you created a Data Privacy Management Service on the node, you must run the `dpmbackup.sh` utility before you upgrade. Press **1** if the node does not have a Data Privacy Management Service or press **2** if the node has a Data Privacy Management Service and press **Enter** to continue.

22. If the node has a Data Privacy Management Service, enter the directory where you have backed up the data.

23. At the prompt to configure a repository for Advanced Scanners, press **2** and press **Enter** to continue.

    The **Domain Security Encryption Key** panel appears.

24. Enter the user name and password for the Informatica domain.

    The **Pre-installation Summary** page appears.

25. Review the upgrade information and press **Enter** to continue.

    After the domain upgrade completes, the **Domain Configuration Repository** panel appears.

26. Press **Enter** to continue the upgrade.

    The installer copies the server files to the Informatica 10.5.11 installation directory.

    The installer displays the database and user account information for the domain configuration repository to upgrade. It displays the database connection string for the domain configuration repository based on how the connection string of the previous version was created at installation:

    - If the previous version used a JDBC URL at installation, the installer displays the JDBC connection properties, including the database address and service name.
    - If the previous version used a custom JDBC connection string at installation, the installer displays the custom connection string.

27. If you use a JDBC URL, you can specify additional parameters to include in the connection string.

    If you use a custom connection string, you cannot specify additional parameters.

28. Review the information and press **Enter**.

    The upgrade completes and the **Post-installation Summary** panel appears.

29. Press **Enter** to complete the installation procedure and exit the installer.

Review the upgrade.log file to get more information about the tasks performed by the upgrade wizard and to view the configuration of installed components.

Upgrading in Silent Mode

To upgrade the Data Privacy Management without user interaction, upgrade in silent mode. Use a properties file to specify the upgrade options. The installer reads the file to determine the upgrade options. You can use silent mode upgrade to upgrade Data Privacy Management on multiple machines on the network or to standardize the upgrade process across machines.

Copy the installation files to the machine that hosts the Data Privacy Management instance you plan to upgrade.

To upgrade in silent mode, complete the following tasks:

1. Create the upgrade properties file and specify the upgrade options.

2. Run the installer with the upgrade properties file.
3. Secure the passwords in the upgrade properties file.

Encrypting Passwords in the Properties File

The installer includes a utility that you can use to encrypt passwords you set in the properties file you use to specify options when you run the installer in silent mode. Informatica uses AES encryption with multiple 256-bit keys to encrypt passwords.

You run the utility for each password you want to encrypt. When you run the utility, you specify the value of the password in plain text at the command prompt. The utility generates the password in encrypted format as output. The output includes the following prefix: `=INSTALLER:CIPHER:AES:256=`

Copy the complete output string, including the prefix, and then paste it into the properties file as the value for the password property. When you run the installer in silent mode, the installation framework decrypts the password.

1. Go to the utility directory:

   ```
   <Installer directory>/properties/utils/passwd_encryption
   ```

2. Run the utility. Specify the plain text password you want to encrypt as the value for <password>.
   - On Linux and UNIX, run the following command:

     ```
     sh install.sh <password>
     ```

   - On Windows, run the following command:

     ```
     install.bat <password>
     ```

3. Copy the encrypted password string from the output, and then paste the string into the .properties file as the value for the corresponding password.

   The following example shows the encrypted password set as the value for the DOMAIN_PSSWD property:

   ```
   DOMAIN_PSSWD==INSTALLER:CIPHER:AES:256=mjkjmDR2kzFJiizfRWIOPg==
   ```

Creating the Properties File

Informatica provides two versions of the properties file. Use either file to specify options for your installation.

Silent input upgrade new config properties file

Use the silent input upgrade new configuration properties file to upgrade Informatica domain services with changes to the node configuration and without user interaction.

The silent input upgrade new configuration properties file contains the configuration properties required to upgrade the Informatica domain services in silent mode. Use the file if you want to consider the appropriate value to set for each property in the file.

Default silent input upgrade properties file

Use the silent input upgrade properties file to upgrade Informatica domain services without user interaction.

The default silent input properties file contains default values for many configuration properties. Use the file if you plan to upgrade the Informatica domain services using the default property values.

Informatica provides a sample properties file that includes the upgrade parameters that are required by the installer. You can customize the sample properties file to specify the options for your upgrade.

The sample upgrade properties file is named SilentInput_upgrade.properties and is located in the installer download location. After you customize the file, save it with the file name SilentInput.properties.

1. Go to the root of the directory that contains the installation files.
2. Find the file named SilentInput_upgrade.properties.

   Back up the file before you modify it.
3. Use a text editor to open the file and modify the values of the upgrade parameters.

   The following table describes the upgrade parameters that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to install or upgrade Informatica. If the value is 0, the installer performs a fresh installation of Informatica. If the value is 1, the installer upgrades a previous version of Informatica.
USER_INSTALL_DIR	Directory in which to install the new version of Informatica services. The directory cannot be the same as the directory that contains the previous version of Informatica services.
UPG_BACKUP_DIR	Directory that contains the previous version of Informatica services that you want to upgrade.
INSTALL_HADOOP_LIBRARIES	Determines whether to install distribution packages through the installer. Set the value to true if you want to install distribution packages through the installer. Set the value to false if you don't need distribution packages or if you want to install them later.
SELECTED_HADOOP_LIBRARIES	Determines the distribution packages that you want to install from the supported packages list. Enter the distribution packages that you want to install, separating multiple packages with a comma.
KEY_DEST_LOCATION	Directory in which to store the encryption key for the node created during the installation.
DOMAIN_USER	User name for the Informatica domain.
DOMAIN_PSSWD	Password for the Informatica domain.
ENABLE_USAGE_COLLECTION	Enables Informatica DiscoveryIQ, a product usage tool that sends routine reports on data usage and system statistics to Informatica. Informatica DiscoveryIQ uploads data to Informatica 15 minutes after you install and configure Informatica domain. Thereafter, the domain sends the data every 30 days. You can choose to not send any usage statistics to Informatica. For more information on how to disable sending usage statistics, see the *Informatica Administrator Guide*. You must set the value to 1 to upgrade.

4. Save the properties file with the name SilentInput.properties.

Data Privacy Management Properties in the Silent Upgrade Files

You can use the silent input upgrade properties files to configure Data Privacy Management properties along with the domain properties.

The following properties in the file are specific to Data Privacy Management.

Property	Description
INSTALL_DPM	Indicates whether you want to upgrade Data Privacy Management along with the domain and Enterprise Data Catalog. Set the value to upgrade Data Privacy Management.
DPM_SERVICE_INST	Indicates whether the node on which you run the upgrade has a Data Privacy Management Service. Set the value to true if the node has a Data Privacy Management Service, or set to false if the node does not have the service.
DPM_BACKUP_DIR	You must run the dpmbackup.sh utility on nodes that have a Data Privacy Management Service. If you set `DPM_SERVICE_INST=true`, provide the backup directory location.

To perform a silent upgrade, you must configure all properties in the properties file. Read the descriptions in the properties file carefully before you update and use the file to upgrade Data Privacy Management.

Running the Silent Installer

After you create the properties file, open a command prompt to start the silent upgrade.

1. Open a command prompt.
2. Go to the root of the server installer directory.
3. Verify that the directory contains the file SilentInput.properties with the upgrade options.
4. Run the silentInstall executable.

The silent upgrade runs in the background. The process can take a while. The silent upgrade process is complete when the Informatica_<Version>_Services_InstallLog<timestamp>.log is created in the installation directory.

The silent upgrade fails if you incorrectly configure the properties file or if the installation directory is not accessible. If the upgrade fails, view the silent upgrade log file and correct the errors. Then run the silent installer again. The silent upgrade log file name is silentErrorLog.log.

The installer creates the log file in the user home directory.

CHAPTER 5

After you Upgrade

This chapter includes the following topics:

- After you Upgrade Overview, 55
- Copy the Third-party Resource Drivers, 56
- Complete the Default SSL Configuration, 56
- Enable and Upgrade the Services, 56
- Migrate the Catalog Data, 57
- Upgrade the Data Privacy Management Service , 57
- Copy Custom SSL Certificates to Data Privacy Management, 58
- Upgrade the remote agent, 59
- Update 10.4.1 Entity Files, 59
- Enable Polling Jobs, 59
- Upgrade JARs and Required Informatica Product Versions, 60
- Delete temporary files, 61

After you Upgrade Overview

After you run the Informatica service installer to upgrade, you must perform a few tasks to complete the Data Privacy Management upgrade.

Perform the following tasks to complete the upgrade:

- Copy third-party resource drivers.
- Complete the default SSL Configuration.
- Enable and upgrade the services.
- Migrate the Catalog Service data.
- If you use a Subject Registry, upgrade the remote agent.
- If you use PowerExchange, upgrade the version.
- If you use Test Data Management, upgrade the Test Data Manager Service.
- If you use Axon Data Governance, upgrade the version.

Copy the Third-party Resource Drivers

Complete the following post requisite after you upgrade the Informatica domain:

- Copy the third-party JAR or ZIP files that you had configured for resources such as Teradata, JDBC, and IBM Netezza from the following location `<Informatica installation directory>services/CatalogService/ScannerBinaries` to the same location in the machine that hosts the upgraded Informatica domain.

Complete the Default SSL Configuration

If the Informatica domain is enabled for SSL using the default SSL certificates, you can configure the Informatica Cluster Service and Catalog Service to use the new keystore.
To configure the services to use the 10.5.11 keystore, perform the following steps:

1. Disable the Informatica Cluster Service and the Catalog Service.
2. Edit the process options for the Informatica Cluster Service and Catalog Service and provide the location of the 10.5.11 `Default.keystore` file. Default path to the file is `$INFA_HOME/tomcat/conf/Default.keystore`.
3. From the 10.5.11 `$INFA_HOME/services/shared/security/infa_truststore.jks` file, remove the existing value configured for the *infa_dflt* alias and import the `$INFA_HOME/tomcat/conf/Default.keystore` file.
4. Enable the Informatica Cluster Service and Catalog Service.

Enable and Upgrade the Services

Enable and upgrade the services from the Administrator tool.

To manage services, go to the **Manage** > **Services and Nodes** tab.

- To enable a service, select the service and click the **Actions** menu on the **Properties** pane and select **Enable Service**.
- To upgrade a service, select the service and click the **Actions** menu on the **Properties** pane and select **Upgrade**.

1. Enable and upgrade the Model Repository Service.
2. Enable and upgrade the monitoring Model Repository Service.
3. Enable and upgrade the Data Integration Service.
4. Enable the Content Management Service.
5. Update the Informatica Cluster Service license.

   Before you can enable the Informatica Cluster Service, import the updated license and reassign the updated license to the Informatica Cluster Service.

   a. Click **Domain**.

   b. Click **Actions** > **New** > **License**.

c. Add the license file and click **OK**.

d. Select the old license in the **Navigator** panel and click **Assigned Services** and click **Edit**.

e. Remove the Informatica Cluster Service from the list of assigned services and click **OK**.

f. Select the new license in the **Navigator** panel and click **Assigned Services** and click **Edit**.

g. Add the Informatica Cluster Service to the list of assigned services and click **OK**.

6. Enable the Informatica Cluster Service.

Migrate the Catalog Data

Enable the Catalog Service and migrate the data and after you upgrade.

Before you restore the Catalog Service, all services such as MongoDB, Solr, and ZooKeeper must be running. There must be sufficient disk space available on the MongoDB host.

Set *INFA_HOME* to the current version in the `bash_profile`.

1. To enable the Catalog Service, select the service and click the **Actions** menu on the **Properties** pane and select **Enable Service**.

   The service prompts you to upgrade the contents.

2. Upgrade the Catalog Service contents.

   Verify that the service restarts after the upgrade. If the service does not restart, manually restart it.

3. If the Catalog Service is SSL enabled, set the encrypted *INFA_TRUSTSTORE_PASSWORD* and *INFA_KEYSTORE_PASSWORD*.

4. Set the *INFA_TRUSTSTORE* and *INFA_KEYSTORE* environment variables.

5. Run the migrateContents command.

   ```
   ./infacmd.sh LDM migrateContents -un <DomainUserName> -pd <DomainPassword> -dn
   <DomainName> -sn <CatalogServiceName> -id <ExportDir>
   ```

   For example:

   ```
   ./infacmd.sh LDM migrateContents -un Administrator -pd infa@123 -dn Domain_abcdef.xyz.com
   -sn CS -id /home/satsqe/CSBackup/export
   ```

Upgrade the Data Privacy Management Service

Upgrade the Data Privacy Management Service content and then enable the service to complete the upgrade job.

1. If you enabled User Activity, perform the following tasks:

   a. Uninstall the existing Data Privacy Management UBA core on the Hadoop cluster nodes.

      Use the following command: `sudo rpm -e sats_analytics`

   b. Navigate to the `/tmp` folder on each node and delete the `com.infa.sats.uba.core_*.rpm` file in the folder.

c. Copy the Data Privacy Management UBA core rpms from `<Informatica installation directory/SecureAtSourceService/spark-components/com.infa.sats.uba.core_10.5-SNAPSHOT-x86_64.rpm` to the `/tmp` folder on all Spark nodes.

d. Install Data Privacy Management 10.5.2 UBA core rpms on the Spark nodes.

Use the following command: `sudo rpm -ivh /tmp/com.infa.sats.uba.core_*.rpm`

2. Browse to the following location and verify that the `sr_config` file exists: `<Informatica installation directory>/SecureAtSourceService/config/sr_config.json`

If the file exists, update the path in the *SSAControls* property path to reflect the correct Data Privacy Management version.

If the file does not exist, perform the following steps:

a. Open the file from the following location: `<Informatica installation directory>/SecureAtSourceService/config/samples/sr_config.json`

b. Enter the required property values and save the file to the following location: `<Informatica installation directory>/SecureAtSourceService/config/sr_config.json`

3. Log in to Informatica Administrator and upgrade the Data Privacy Management Service content.
4. On the **Processes** tab, change the Keystore and Shared Directory path to the upgraded directory.
5. Enable the Data Privacy Management Service.
6. If you configured user activity monitoring, update the Event File Shared Location property on the User Activity Configuration tab of the Data Privacy Management Service.

The mount location must be accessible to the domain machine and all cluster machines. The path to the mount location must be the same on all machines with Read, Write, and Execute permissions for the domain user on all machines.

7. Log in to the Data Privacy Management UI and click **Manage** > **Jobs**.

The **Jobs** workspace appears.

8. Verify that the Master Upgrade job is running.
9. Click the Master Upgrade job to view details of each job step.

Wait until the Master Upgrade job finishes before you perform any other task in Data Privacy Management.

If the Master Upgrade job fails, enable the `debug` log level for the Data Privacy Management Service in Informatica Administrator. Resume the job in Data Privacy Management . This generates error logs that you can use to troubleshoot.

Copy Custom SSL Certificates to Data Privacy Management

Required if you use custom SSL certificates with the Certificate Authority (CA) set to False.

Perform the prerequisite tasks described in "Configure Custom SSL Certificates Overview" on page 34 and copy the certificates to the Informatica Cluster Service folder.

1. Disable the Data Privacy Management Service.
2. Copy the `client_certs` folder that the utility generates to the following location: `<Previous custom SSL certificates folder>/`

3. Rename the `client_certs` folder to `certs`.
4. Enable the Data Privacy Management Service.

Upgrade the remote agent

If you use a Subject Registry for unstructured sources, upgrade the remote agent. If you want to create an agent for the first time, see the instructions to create the remote agent in the *Installation for Data Privacy Management* documentation.

1. Shut down the existing remote agent.

   Run the following command:

   ```
   cd <current agent directory>/bin
    ./siagent.sh shutdown
   ```

2. Extract the 10.5.11 agent binaries from the following location: `<Informatica installation directory>/SecureAtSourceService/InformaticaDiscoveryAgent/InformaticaDiscoveryAgent.zip`

   Extract the files to a folder. For example: `RemoteAgent`

3. From the current agent folder, copy the `<RemoteAgent>/tomcat/conf/server.xml` file and replace the file in the 10.5.11 agent directory.
4. Ensure that the remote agent keystore and truststore files are outside the remote agent directory or backed up and the location updated in the `server.xml` file.
5. Start the 10.5.11 remote agent.

   Run the following command:

   ```
   cd <10.5.11 remote agent directory>/bin
    ./siagent.sh startup
   ```

Update 10.4.1 Entity Files

Required if you upgraded from version 10.4.1.x and created entity files that use Exact matching for index and search configurations in version 10.4.1.

Delete the Subject Registry database tables for the entity and run the scans again. This is required because of changes to Match configurations.

Enable Polling Jobs

Required if you disabled polling jobs before upgrade. You must enable Polling jobs after you upgrade.

To enable polling jobs, you can use the satscurl command line utility or update and save a data store with the **Auto Sync with Catalog** option.

To use the satscurl command line utility, you must have downloaded the utility files. For information about how to download the files, see "Disable Polling" on page 34.

1. Enable polling jobs.
   - Run the following command: `./satscurl -a https://<host name>:<port number> -u <Data Privacy Management user name> -p <password> enablePolling`
     The host name and port number must be the values that you configure to access Data Privacy Management.

     For example: `./satscurl -a https://abccent7dsgace01.abc.com:18295 -u Administrator -p admin123 enablePolling`
   - To enable polling jobs from Data Privacy Management, perform the following tasks:
     1. Log in to Data Privacy Management.
     2. On the **Data Stores** workspace, click a data store that has the **Auto Sync with Catalog** option selected.
     3. Click **Edit** and then click **Save**.
2. On the **Jobs** workspace, click the **Future Jobs** tab and verify that the following jobs appear in the list:
   - Polling Scan Results
   - Polling Data Store Updates

Upgrade JARs and Required Informatica Product Versions

Before using Data Privacy Management, perform the following steps:

1. If you plan to scan IBM DB2/zOS and IBM DB2/i5 OS sources, and you already have PowerExchange, upgrade to PowerExchange 10.5.11.

   For information, see the *Informatica PowerExchange Installation and Upgrade Guide*.
2. Verify whether you added any JARs for Data Engineering Integration scans in the previous version to the following directory: `<Informatica install directory>/services/SecureAtSourceService/ROOT/WEB-INF/eclipse/plugins`

   Copy the `.jar` files to the same directory in Data Privacy Management 10.5.11 and restart the Data Privacy Management Service.
3. If you use Remote PDM with Data Privacy Management, upgrade the domain and Test Data Manager Service to 10.5.11.

   For information, see the *Informatica Test Data Management Upgrade Guide*.
4. If you use Axon Data Governance, update to version 7.3.7.

   For information, see the *Axon Data Governance Upgrade Guide*.
5. If you plan to run Data Engineering scans on versions earlier than 10.5.11, download the `ExtendedScannerBinaries.zip` file.

   Extract the file to the following location: `<Informatica install directory>/services/CatalogService/ScannerBinaries`.

Delete temporary files

The upgrade process creates temporary directories and files. Delete the files to clean up files that are not required post upgrade and to allow security patches to take effect.

1. Browse to the following location: `<Informatica installation directory>/logs/<node name>/services/SecureAtSourceService/<Data Privacy Management service name>/`

   Add the relevant node name and service name in the path.
2. Delete the following directories:

   augmenter

   percolator

   retention

   ubamanager

APPENDIX A

Managing Distribution Packages

This appendix includes the following topics:

- Managing Distribution Packages Overview, 62
- Before You Begin, 62
- Install or Remove Distribution Packages in Console Mode, 63
- Install or Remove Distribution Packages in Silent Mode, 64
- After You Install, 64

Managing Distribution Packages Overview

You can use Integration Package Manager (the package manager) to install and remove distribution packages from the Informatica service and client machines.

A distribution package is a set of distribution binaries that you install within the domain for the following processing requirements:

- To push processing to the Hadoop or Databricks environment.
- To process complex files within the Informatica domain.
- To connect to the Hadoop or Databricks environment when you process within the Informatica domain.

You can install distribution packages if you didn't do so during the upgrade or install process or if you want to add a distribution package. You can remove a distribution package if you want to use a different package or if you installed a package that you don't use.

When you install or remove distribution packages, verify that you perform the operation on all service and client machines.

Before You Begin

Before you run the package manager, perform tasks such as setting environment variables and downloading files.

1. Shut down the Informatica services.

2. Set one of the following environment variables:

Variable	Description
INFA_JDK_HOME	Location of the folder containing the supported Java Development Kit (JDK). Set the INFA_JDK_HOME environment variable in the following scenarios: - Informatica domain is on Windows or Linux - Informatica client
INFA_JRE_HOME	Location of the folder containing the supported Java Runtime Environment (JRE). If the Informatica domain is on AIX, set the INFA_JRE_HOME environment variable.

3. Verify that the user that runs the package manager has read and write permissions on the Informatica installation directory and execute permissions on the executable file.
4. Download the following files from the Informatica Electronic Software Download site:
   - Integration Package Manager
   - Distribution packages
5. Extract the Integration Package Manager ZIP files to a local drive.
6. Copy the ZIP files of distribution packages that you need to the following location: `<Integration Package Manager directory>/source`

   Note: The package manager fails if the ZIP files for distribution packages aren't available in the source directory.

Install or Remove Distribution Packages in Console Mode

You can run the package manager in console mode to install or remove distribution packages.

1. From the package manager directory, run one of the following commands:
   - `./Server.sh console` for Linux or UNIX
   - `Server.bat console` for Windows
   - `Client.bat console` for client

   Note: To run the command on Windows, use the administrator command prompt.
2. Enter the installation directory of the services or client and press **Enter**.
3. Choose the operation type and press **Enter**.
   - Select 1 to remove existing distribution packages.
   - Select 2 to install one or more distribution packages.

   The console lists the distribution packages that you can install or remove.
4. Enter the distribution packages that you want to install or remove, separating multiple packages with a comma, and press **Enter**.
5. Verify the installation or removal status in the package manager log file.

   You can find the log file in the following location: `<Integration Package Manager directory>/IntegrationPackageManager_<date and timestamp>.log`

Install or Remove Distribution Packages in Silent Mode

You can run the package manager in silent mode to install or remove distribution packages. The silent input properties file contains the properties for the package manager to run in silent mode for service and clients. Set the appropriate value for each property in the file.

1. Find the IntegrationPackageManager.properties file in the following location: `<Integration Package Manager directory>/`
2. Edit the properties file in a text editor.

   The following table describes the properties that you can modify:

Property Name	Description
USER_INSTALL_DIR	The installation directory of the service or client.
OPERATION_TYPE	The operation that you want to perform: - Set to DELETE to remove existing distribution packages. - Set to EXTRACT to install one or more distribution packages.
SELECTED_HADOOP_LIBRARIES	Lists the distribution packages and versions. Enter the distribution packages that you want to install or remove. Separate multiple packages with a comma.

3. Save the properties file.
4. From the package manager directory, run one of the following commands:
   - `./Server.sh silent` for Linux or UNIX
   - `Server.bat silent` for Windows
   - `Client.bat silent` for client

   Note: To run the command on Windows, use the administrator command prompt.
5. Verify the installation or removal status in the package manager log file.

   You can find the log file in the following location: `<Integration Package Manager directory>/IntegrationPackageManager_<date and timestamp>.log`

After You Install

To use the distribution packages that are installed using the package manager, configure the property or environment variable in service and client machines.

Configure the Developer Tool

After you install the distribution packages in the Developer tool, update the developerCore.ini file with the installed distribution package.

1. Find the developerCore.ini file in the following location: `<Informatica installation directory>\clients\DeveloperClient`

2. Edit the file to update the following property:

   ```
   -DINFA_HADOOP_DIST_DIR=hadoop\<Hadoop distribution name>_<version>
   ```

   For example,

   ```
   -DINFA_HADOOP_DIST_DIR=hadoop\CDH_7.1
   ```

3. Restart the Developer tool.

Configure Environment Variables

Some adapters require environment variables for the Data Integration Service and Metadata Access Service to access the distribution packages. For more information, see Configure environment variables to process complex files.

INDEX

C

console mode
  upgrading Informatica services 49

I

Informatica services
  upgrading in console mode 49

U

UNIX
  upgrading Informatica services in console mode 49