How-To Library

Informatica

Secure@Source Backup and Restore Guidelines

© Copyright Informatica LLC 2015, 2021. Informatica LLC. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. All other company and product names may be trade names or trademarks of their respective owners and/or copyrighted materials of such owners.

Abstract

This article explains how to back up and restore Secure@Source.

Supported Versions

- Secure@Source 2.0

Table of Contents

Backup and Restore Overview. 2
Backup. 2
Restore. 2

Backup and Restore Overview

Regularly back up the Secure@Source repository to prevent data loss due to hardware or software problems. In the event that you need to restore Secure@Source, follow the guidelines outlined in this article.

Backup

1. Regularly back up the Informatica repositories along with your other production databases.
2. Back up the `$INFA_HOME` directory and its subdirectories.
3. Create a cron job to take snapshots of HDFS and to back up these snapshots.
   Example:

   ```
   - hdfs dfsadmin -allowSnapshot /
   - hdfs dfs -createSnapshot / snapshot.02042016
   - hadoop fs -get /.snapshot/snapshot.02042016 /home/backup
   - zip -r snapshot.02042016.zip /home/backup/snapshot.02042016
   - scp snapshot.02042016.zip root@backup-host:~
   ```

   The frequency of the cron job depends on your scan schedule. Informatica recommends that you take and back up HDFS snapshots daily.

Restore

1. Restore the Informatica repositories from the backup.
2. Restore the `$INFA_HOME` directory and its sub-directories.

   The hostname and the IP address must be the same as before.
3. Start the domain.
4. Shut down the Catalog Service.
5. Apply the HDFS snapshot on the Hadoop cluster.
   Example:

   ```
   - unzip snapshot.02042016.zip
   - hadoop fs -put snapshot.02042016/ /tmp
   - hdfs dfs -cp  /tmp/snapshot.02042016/* /
   ```

6. Start the Catalog Service.
7. Start the Secure@Source Service.
8. Shut down all the Vibe Data Stream nodes.
9. For each transform, update the HDFS URI in the Vibe Data Stream dataflow.
10. Start the Vibe Data Stream nodes.
11. From the Secure@Source UI, run the Evaluate Policies job.

Author