How-To Library

Informatica

Connection Details for Secure@Source Scan Jobs

© Copyright Informatica LLC 2018, 2021. Informatica, the Informatica logo, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

Based on the scan definition and source, Secure@Source uses specific applications and services to connect to and scan sources. This article explains the connection details for the Load Catalog, Profiling, and Collect Row Count scan job steps.

Supported Versions

- Secure@Source 4.5

Table of Contents

Connection Details for Scan Jobs Overview. 2
Load Catalog Job Step. 2
Profiling Job Step. 3
Collect Row Count Job Step. 4

Connection Details for Scan Jobs Overview

A scan defines how to discover and classify sensitive data in data stores. When you create a scan, you specify the data stores, classification policies, and scan options. Scan options are based on the type of data store you include in the scan. When you run a scan, the Secure@Source Service creates one or more scan jobs. Each scan job includes job steps based on the scan options you selected.

The following table shows the scan options and the corresponding job step in scan job:

Scan Option	Job Step
Include Catalog Information	Load Catalog
Run Profiling	Profiling
Include Row Count	Collect Row Count

For example, you scan an Oracle data store with the Include Catalog Information and Run Profiling scan options. Secure@Source creates a database scan job that includes the Load Catalog and Profiling job steps.

Load Catalog Job Step

The scan job includes the Load Catalog job step if the scan is configured to include catalog information. Secure@Source extracts a metadata catalog from the source during the job step.

The following list provides information on the Load Catalog job step for an administrator:

Tasks

The Load Catalog job step performs the following tasks:

- Tests the connection and connects to the source.
- Extracts the metadata catalog from the source.
- Saves the metadata information in the staging area.

- Loads the metadata information in Apache Solr.

Connectivity

For non IBM mainframe sources, Secure@Source uses JDBC to test and access the source and retrieve, save, and scan the metadata catalog.

For IBM Db2 on z/OS and IBM Db2 on AS/400 sources, Secure@Source uses the Informatica PowerExchange Connector to test and access the source and retrieve, save, and scan the metadata catalog.

Note: You must install the PowerExchange Connector on the domain node before you can scan IBM Db2 on z/OS and IBM Db2 on AS/400 sources.

For data store specific connectivity information, see the *Informatica Secure@Source v4.5 Administrator Guide*.

Ports

Secure@Source uses the JDBC port to connect to the source. For example, Secure@Source uses port 1521 to connect to Oracle sources.

Services Involved

Secure@Source uses the following agents during the Load Catalog job step:

- Enterprise Data Catalog (EDC).
- For non IBM mainframe sources, a MITI connector to extract the data.
- For IBM Db2 on z/OS and IBM Db2 on AS/400 sources, JDBC to connect to the source.

Troubleshooting

If the scan fails at the Load Catalog job step, check the following logs:

- The `LDM.log` located at `$INFA_HOME/logs/node01/services/CatalogService/<Catalog_Service_Name>/`
- If there is not enough information in the `LDM.log` log, then browse the Yarn Resource Manager for the Yarn logs.
- The logs in the scanner application.
- If the job fails during loading, then check the logs in Apache Solr.
- The logs located at `$INFA_HOME/logs/node01`

Profiling Job Step

The scan job includes the Profiling job step if the scan is configured to run profiling. Secure@Source creates and runs a profile to perform data domain discovery. The scan options determine if the data domain discovery runs on the source metadata, data, or both. The scan job uses the profile results to determine the sensitivity status.

The following list provides information on the Profiling job step for an administrator:

Tasks

The Profiling job step performs the following tasks:

- Tests the connection and connects to the source.
- Profiles the source data based on the data domains in the scan.

Connectivity

Secure@Source uses the native client or ODBC to test and access the source data. Install the specific native client for the source. For example, to profile an Oracle source, you must install Oracle Client on all the Data Integration Service nodes.

For data store specific connectivity information, see the *Informatica Secure@Source v4.5 Administrator Guide*.

Ports

Secure@Source uses the JDBC port to connect to the source. For example, Secure@Source uses port 1521 to connect to Oracle sources.

Services Involved

Secure@Source uses the following services during the Profiling job step:

- Content Management Service
- Data Integration Service
- Model Repository Service

Troubleshooting

If the scan fails at the Profiling job step, check the following logs:

- The logs in the scanner application.
- The Data Integration Service logs located in the following locations:
  - `<INFA_HOME>/logs/node01/services/DataIntegrationService/disLogs/dis_Data_Integration_Service_node01.log.0`
  - The mapping logs which contain detailed profiling information. `<INFA_HOME>/logs/node01/services/DataIntegrationService/disLogs/profiling/`
- The logs located at `$INFA_HOME/logs/node01`

Collect Row Count Job Step

The scan job includes the Collect Row Count job step if the scan is configured to include a row count. Secure@Source calculates the row count for each table that contains sensitive data.

The following list provides information on the Collect Row Count job step for an administrator:

Tasks

The Collect Row Count job step performs the following tasks:

- Connects to the source.
- Calculates the distinct row count from every sensitive field.

Connectivity

Secure@Source uses JDBC to access the source data. To connect to Salesforce, Secure@Source uses an Informatica API.

For data store specific connectivity information, see the *Informatica Secure@Source v4.5 Administrator Guide*.

Ports

Secure@Source uses the JDBC port to connect to the source. For example, Secure@Source uses port 1521 to connect to Oracle sources.

Services Involved

Secure@Source uses the Secure@Source Service for row count.

Troubleshooting

If the scan fails at the Collect Row Count job step, check the Secure@Source log located at `<INFA_HOME>/logs/node01/services/SecureAtSourceService/SecureAtSource_Service/SecureAtSourceService.log`

Author