How-To Library

Informatica

Configuring Incremental Subject Registry Scans in Data Privacy Management

© Copyright Informatica LLC 2020, 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This article explains the behavior of incremental Subject Registry scans and the steps to configure the scans. It also includes rules and guidelines to consider when you choose to configure incremental Subject Registry scans.

Supported Versions

- Data Privacy Management 10.4.1.1

Table of Contents

Overview. 2
Example. 2
Rules and Guidelines for Incremental Subject Registry Scans. 3
Configure Incremental Subject Registry Scans. 3
Step 1. Configure the Entity File for Incremental Scans. 3
Step 2. Create and Run the Subject Registry Scan. 4
Update a Scan Definition 5

Overview

You can create a Subject Registry to quickly find subject information across your structured and unstructured data sources.

To create a Subject Registry, you scan the data stores that you want to include in the Subject Registry. After you complete the first full scan of the data stores, you can then run incremental scans to scan the delta of records updated since the previous scan instead of the entire data store.

Incremental scans apply to structured sources.

Example

You work for an organization that uses a Data Privacy Management Subject Registry to maintain and manage the huge volumes of subject data that it collects and stores. The organization has a Data Privacy team that handles subject requests related to personal data.

You are part of the team that set up the Subject Registry and ensures that the Subject Registry data is up to date. During the initial setup, the first scan of some entities included millions of records.

Given the updates to the data, you need to run regular repeat scans to ensure that the Subject Registry data is up to date. You configure recurrent scans for entities that are updated frequently. You run manual repeat scans for entities that are updated less often. A scan of millions of records can take considerable time and uses more resources during processing of records.

The initial scan is a complete scan that includes all records. The subsequent scans that you run update any changes to the data. Because you need to include only the changes since the last scan, you configure repeat scans to be incremental. The configuration ensures the scan takes less time.

To configure incremental repeat scans, you perform the following tasks:

1. Add the required properties to the entity file.
2. Create the scan definition or update an existing scan definition to configure incremental scans.

Rules and Guidelines for Incremental Subject Registry Scans

Consider the following rules and guidelines before you configure incremental Subject Registry scans.

- The first scan for an entity is always a complete scan. If the scan is configured for incremental scans, the scans are incremental from the second scan run.
- To enable incremental scans, you must include a field with the *IncrementalScanField* property set to true in the entity file.
- A scan fails with errors if you configure an incremental scan on the scan UI but do not configure the property in the entity file.
- The field with the *IncrementalScanField* property set to true must contain a time stamp value. The scan uses the value to verify if the data was added or updated after the last scan. It adds records that have a last updated time greater than the time of the last scan.
- If you set the *IncrementalScanField* value to true for more than one field, only the first field is considered.
- The scan does not consider the last updated time on records that you delete after the last scan. So an incremental scan does not remove records that you delete after the last scan from the golden record table. You must run a full scan to remove deleted records.
- Search results on the UI and DSAR reports that you generate after an incremental scan might therefore include incorrect data for deleted records or fail.
- If you update a record such that it does not match with a subject, an incremental scan does not delete the link to the subject. This can result in incorrect data included in search results and in DSAR reports.

Configure Incremental Subject Registry Scans

You can choose to configure repeat Subject Registry scans as incremental scans.

Before you can configure an incremental Subject Registry scan in Data Privacy Management, you must update the entity JSON file with the required flag and value.

On the Data Privacy Management UI, you can configure a Subject Registry scan as incremental when you create the scan. The scan is incremental from the second scan run.

Alternatively, you can edit an existing scan definition to make subsequent scans incremental. If the scan has completed the first run, all subsequent scan runs are incremental. If the first run is not done, the first scan is a complete scan and subsequent scans are incremental.

The incremental scan option applies to structured data sources both in manual repeat scans and repeat scans that run as part of a recurrence.

Step 1. Configure the Entity File for Incremental Scans

Before you configure an incremental Subject Registry scan, you must add the required field to the entity file.

1. Browse to the following location and open the required entity JSON file in edit mode: `<Informatica installation directory>/SecureAtSourceService/config`
2. In the `EntityFields` section, add a field that the scan can use to determine the last updated time. The field must point to a column that contains a time stamp value.

   Alternatively, if the entity includes a field that you want to use, update the field properties.
3. Add the `IncrementalScanField` flag and set the value to `true`. For example:

```
{
            "FieldName": "LastUpdatedTime",
```

```
            "FieldLength": "00",
            "DisplayCode": "00",
            "IsPrimaryKey": "false",
            "IncrementalScanField":"true"
        }
```

Note: Set the flag to true for one field in the entity.

The column that the field points to must contain data in the `yyyy-MM-dd HH24:mm:ss` format.

4. If you do not want to include the field in scans and searches, set the FieldLength to 0.
5. To exclude the field from DSAR reports, ensure that you do not use a field name that is a data domain in Data Privacy Management.
6. Save and close the file.

Step 2. Create and Run the Subject Registry Scan

You can configure a Subject Registry scan as incremental when you create the scan. The scan is incremental from the second scan.

Before you configure an incremental scan on the **Scans** workspace, update the required field in the entity file.

1. Log in to Data Privacy Management.
2. Click **Manage** > **Scans**.

   The **Scans** workspace appears.
3. Click **New**.

   The **Define & Connect** panel appears.
4. Enter the scan name and description.
5. Select the required scan type.

   The following table lists the scan types with descriptions:

Option	Description
Domain Discovery	Maps columns to data domains. Include this type if you have not already run Domain Discovery scans on all data stores, or if you want to update the scan results.
Discover Subjects	Scans golden data stores to identify data subjects.
Link Subjects	Scans transaction data stores to link subjects with data subjects discovered in golden data stores. **Note:** You cannot run a scan to link subjects in transaction data stores before you discover subjects in golden data stores. If you have not run a Discover Subjects scan to identify subjects, include a Discover Subjects scan with the Link Subjects scan.

   You can first run the scan to identify subjects in golden data stores, and then run the scan to link subjects in transaction data stores. You can choose to run both scans in a single Subject Registry scan.
6. Choose the subject type.

   Select the required entity file.
7. In the **Subject Scan Options** section, uncheck the **Full Subject Scans** check box to configure repeat scans as incremental.

   Applies to structured data stores. Unstructured data stores always have complete scans.

8. Select the category, data store type, and the data stores to include in the scan. If the scan includes the Link Subjects scan type, choose data stores that you want to scan for subject linking from the list of data stores. The Subject Discovery scan uses data stores mentioned in the Subject Type.

   After you select the data store type, the scan options appear. Enter the required scan options and click **Next**.

9. If applicable, assign classification policies.

   You can assign classification policies if the scan includes domain discovery.

10. Click **Next** to save and schedule or run the scan.

    If you choose to set a recurrence, all recurrent scans of structured sources are incremental.

    The Data Privacy Management Service creates a Scan job. The job runs according to the schedule that you configure. The first scan is a complete scan and all subsequent scans are incremental.

On the **Jobs** workspace, you can monitor the status of the Subject Registry master job and child jobs.

Update a Scan Definition

You can update an existing Subject Registry scan to configure it for incremental scans.

Before you update the scan definition, ensure that the entity file includes the required field and property.

1. Log in to Data Privacy Management.
2. Click **Manage** > **Scans**.

   The **Scans** workspace appears.

3. From the list of scans, click the required Subject Registry scan to open the scan page.
4. Click **Edit**.

   The **Edit** scan page opens on the **Define & Connect** panel.

5. In the **Subject Scan Options** section, uncheck the **Full Subject Scan** check box.

   If you do not select the **Full Subject Scan** option, repeat scans are incremental instead of full.

6. Click **Save** to save the changes to the scan definition.

   If the first scan run is complete, all subsequent scans will be incremental. If the first scan is not complete, the first scan is a complete scan and all subsequent scans are incremental.

On the **Jobs** workspace, you can monitor the status of the Subject Registry master job and child jobs.

Author

Sadhana Kamath