Informatica® Application Integration
October 2026

DaaS Service Connector Guide

Informatica Application Integration DaaS Service Connector Guide
October 2026

© Copyright Informatica LLC 1993, 2026

Publication Date: 2026-10-28

Table of Contents

Preface 4

Chapter 1: Introduction to DaaS Service Connector 5

DaaS Service Connector Overview 5

Chapter 2: DaaS Service Connections 6

DaaS Service Connections Overview 6

Basic Connection Properties 6

DaaS Service Connection Properties 7

Chapter 3: DaaS Service Connector Processes 8

Services in DaaS Service Connector 8

- Validate Email 8
- Validate Phone 9

Process with DaaS Service Connector Example 9

Index 10

Preface

Read the *DaaS Service Connector Guide* to learn how to set up and use DaaS Service connections.

This guide assumes that you have an understanding of the DaaS API web service and how to define service calls using Application Integration.

CHAPTER 1

Introduction to DaaS Service Connector

This chapter includes the following topic:

- DaaS Service Connector Overview, 5

DaaS Service Connector Overview

Application Integration allows you to interact with programs and services that are in DaaS Service Connector.

To access an exposed API, you can create a Service Connector in Process Designer. You can then use the Service Connector to specify the parameters and actions associated with any service that you want to use in a process.

DaaS Service Connector is a Service Connector that allows you to access the parameters and actions associated with the DaaS Service API. You can create a DaaS Service connection and configure a service call in a process to access the services exposed by the API. You can perform the following actions:

- Email address, phone, and address validation
- U.S. sales tax retrieval
- U.S. and Canadian latitude and longitude retrieval

Informatica DaaS Service Connector is already licensed for use by customers. You do not need to buy a license to use it.

CHAPTER 2

DaaS Service Connections

This chapter includes the following topics:

- DaaS Service Connections Overview, 6
- Basic Connection Properties, 6
- DaaS Service Connection Properties, 7

DaaS Service Connections Overview

You can create a DaaS Service connection to create and access the services that have actions associated with the process.

After you create a DaaS Service connection, you can validate and save the connection.

You can then publish the DaaS Service connection and click the **Metadata** tab to view the generated process objects for the connection.

Basic Connection Properties

The following table describes the basic properties available on the **Properties** tab of the connection creation page:

Properties	Description
Name	Required. Unique name for the DaaS Service connection that identifies it in the Process Designer. The name must start with an alphabet and can contain only alphabets, numbers, or hyphens (-).
Location	Optional. The location of the project or folder where you want to save the connection. Click **Browse** to select a location. If the **Explore** page is currently active and a project or folder is selected, the default location for the connection is the selected project or folder. Otherwise, the default location is the location of the most recently saved asset.
Description	Optional. Description of the connection.

Properties	Description
Type	Required. The type of connection you want to use for the connector or service connector. Select **Informatica DaaS Service (Licensed for use)**.
Runtime Environment	Required. The runtime environment for the connection. You can run the connection on the Cloud Server, a Secure Agent group, or a Secure Agent machine.
Connection Test	Not supported for DaaS Service Connector.
OData-Enabled	Specifies whether OData feeds are enabled for the connection. Select **Yes** to enable OData feeds. If you select **Yes**, you must specify the users or groups that can use the OData endpoint at run time. Default is **No**. Note: If you change the database structure (for example, add or remove tables or views), republish the connection to refresh the cached list and reflect the changes.

Along with these basic properties, you must define the properties applicable to the DaaS Service connection type.

DaaS Service Connection Properties

The following table defines the DaaS Service connection properties that you must configure in the **Connection Properties** section:

Connection Property	Description
UserID	Required. The User ID, which is an email address, that is associated with your DaaS API account. Or, you can also specify the API license key obtained from your DaaS API account.
Password	The password associated with the User ID. Leave this field blank if you specify the API license key as the User ID.
EndPointUrl	Optional. The service endpoint URL to access the DaaS API service. For example, enter `https://ws.strikeiron.com/StrikeIron`. Default is `https://ws.strikeiron.com/StrikeIron`.

CHAPTER 3

DaaS Service Connector Processes

This chapter includes the following topics:

- Services in DaaS Service Connector, 8
- Process with DaaS Service Connector Example, 9

Services in DaaS Service Connector

DaaS Service Connector uses the DaaS Service API to perform various tasks.

Activities that you can perform in DaaS Service Connector are listed as services that you can configure in a Service step in a process.

To configure a service, you need to identify and pass the input fields required for the service. You can also use the service output to perform other steps in the process.

Validate Email

Application Integration verifies if the email address that you specify is valid, invalid, or malicious.

Input Fields

- The email address
- The duration, in milliseconds, after which the DaaS service stops the email verification process. Specify a value between 1 and 90.

Output Fields

- The result of the DaaS email verification process.
- The result of the DaaS email Hygiene process.
- The domain protected by a third party that might be associated with the email address.

Note: In output fields, if the status code is **200** and the status description is **Email Valid**, the **Email Result** field displays **OK**. For all other status codes, the **Email Result** field displays **NOT OK**.

Validate Phone

Application Integration verifies the validity of the phone number that you specify.

Input Field

The phone number including the country code. Country phone codes must follow the conventions defined by the ITU-T recommendations E.164

Output Fields

- The status code and description of the phone validation process.
- The results of the phone validation process.
- Mobile and phone action result process object, which contains the national and international prefix of the phone number; region code and name; latitude and longitude; and time zone.

Process with DaaS Service Connector Example

You can create a process in Process Designer and configure a service call using a DaaS Service connection and validate an email address.

In this example to validate an email address, perform the following steps:

1. Create a DaaS Service connection.
2. Create a process and configure a Service step using the services in a DaaS Service connection.
3. Select the ValidateEmail service and specify the email address that you want to validate.
4. Configure an Assignment step to capture the email result and the hygiene result.
5. Save, publish, and run the process. Application Integration runs the email validation process and validates the email address.

INDEX

B

Basic connection properties
  DaaS Service 6

D

DaaS Service connection
  properties 7
DaaS Service Connector
  example 9
  overview 5

S

services
  overview 8
  Validate Email 8
  Validate Phone 9

V

Validate Email
  services 8
Validate Phone
  services 9