Informatica® Cloud Data Governance and Catalog

2026 October

Understanding Technical Assets

Informatica Cloud Data Governance and Catalog Understanding Technical Assets
2026 October

© Copyright Informatica LLC 2021, 2026

Publication Date: 2026-10-29

Table of Contents

Preface 5

Chapter 1: Technical asset types 6

Amazon Athena 6
Amazon Redshift 8
Amazon S3 9
dbt 15
Databricks 16
File System 20
Google BigQuery 22
Google Vertex AI 23
Greenplum 24
IBM Db2 for LUW 24
IBM Db2 for z/OS 25
IBM Mainframe Job Control Language (Accelerator) 26
IBM Netezza 27
Informatica PowerCenter 27
JDBC 28
Microsoft Azure Data Lake Storage Gen2 29
Microsoft Azure SQL Server 32
Microsoft Azure Synapse Data Warehouse 33
Microsoft Fabric Data Warehouse 35
Microsoft SQL Server 36
Microsoft SQL Server Analysis Services 37
Microsoft SQL Server Integration Services 38
Microsoft SQL Server Reporting Services 39
Microsoft SQL Server Script 40
MicroStrategy 40
MySQL 42
Oracle 43
Oracle Business Intelligence 45
Oracle PL/SQL Script 47
Oracle SQL Loader 48
PostgreSQL 48
Qlik Sense 49
Qlik Sense Cloud 50
QlikView 51
SAP BusinessObjects 52
SAP BusinessObjects Data Services 55
SAP HANA 55

SAP S/4HANA Cloud. 56
Snowflake. 57
Snowflake SQL Script. 59
Tableau. 60
TIBCO Spotfire. 61
Talend Data Integration. 63
Teradata BTEQ Script. 64
Workday. 64

Index. 66

Preface

Read *Understanding Technical Assets* to familiarize yourself with the assets from various source systems for which you can extract metadata to Data Governance and Catalog.

CHAPTER 1

Technical asset types

Data Governance and Catalog displays several types of technical assets that are retrieved by Metadata Command Center.

Amazon Athena

Amazon Athena is an interactive query service to query and analyze big data in Amazon S3 using standard SQL.

Objects extracted

Metadata Command Center extracts the following objects from an Amazon Athena source system:

- Database
- Schema
- View
- ViewColumn
- External Table
- External Column
- Calculation
- Resource
- Nested Field

You can extract objects with the following complex data types and their nested fields from an Amazon Athena source system:

- Array
- Map
- Struct

Data Governance and Catalog displays objects with complex data types as external columns. The nested fields within arrays appear as elements, while those within maps appear as keys and values.

Data profiling for Amazon Athena

Configure data profiling to run profiles on the metadata extracted from an Amazon Athena source system. You can run data profiles on the following Amazon Athena objects:

- External tables created in the following file formats:
  - Avro
  - CSV
  - Delta
  - JSON
  - Parquet
- External columns

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Amazon Athena objects:

- Bigint
- Boolean
- Char
- Date
- Decimal
- Double
- Float
- Int
- Smallint
- String
- Timestamp
- Tinyint
- Varchar

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for an Amazon Athena catalog source:

- All Rows
- Limit N Rows
- Custom Query. Enter the sampling method to specify a percentage of rows on which you want to run the data profiling task. For example, `TABLESAMPLE BERNOULLI(10)` or `TABLESAMPLE SYSTEM(10)`

Note: You can run data quality only on views and external tables that are created in Amazon Athena.

Data lineage

The following lineage data is available for Amazon Athena assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

Amazon Redshift

Amazon Redshift is a cloud-based data warehousing service that you can use to analyze and store data.

Objects extracted

Metadata Command Center extracts the following metadata from an Amazon Redshift source system:

- Database
- Schema
- External Schema
- Table
- External Table
- View
- Materialized View

  Note: Objects of the Materialized View type appear as View in Data Governance and Catalog.
- Function
- Procedure
- Column

Data profiling for Amazon Redshift objects

Configure data profiling to run profiles on the metadata extracted from an Amazon Redshift source system.

You can run data profiles on the following objects:

- Table
- View
- Spectrum External Table

You can run profiles on Spectrum external tables that are created using the following file formats:

- PARQUET
- AVRO
- TEXT
- RC
- SEQUENCE
- ORC

Note: If the Spectrum external tables include columns with string data types, those columns are skipped and are not considered for data profiling and data quality.

The data profiling task runs profiles on the following data types:

- SMALLINT
- INTEGER
- BIGINT
- DECIMAL
- REAL
- DOUBLE PRECISION

- BOOLEAN
- CHAR
- VARCHAR
- DATE
- TIMESTAMP
- STRING
- SUPER

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types:

- All Rows
- Limit N Rows
- Random N Rows

Data lineage

The following lineage data is available for Amazon Redshift assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Amazon S3

Amazon Simple Storage Service (Amazon S3) is an object storage service offered by Amazon Web Services (AWS).

Objects extracted

Metadata Command Center extracts the following metadata from an Amazon S3 source system:

- File
- Folder
- Bucket
- Iceberg Table
- Iceberg Field

You can extract metadata from S3 data sources. By default, you extract metadata from the Amazon S3 Storage, but you can also extract metadata from the S3 Scality Storage or MinIO.

File types

You can extract metadata from the following file types:

- AVRO
- Compressed files
  - TAR
  - ZIP
- Delimited files
  - CSV
  - TSV
- E-mail files
  - EML
  - EMLX
  - MSG
- JSON
- JSONL
- Markdown
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- ORC
- Presentation files
  - PPT
  - PPTX
- Parquet
- PDF
- Rich Text Format (RTF)
- TXT
- XML
- XSD

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
AVRO	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

You can extract workbooks, worksheets, and columns from Microsoft Excel files.

You can extract metadata from XML and XSD file formats as XML file objects. Metadata Command Center extracts only elements and attributes from XML and XSD files. If the size of the XML file exceeds 100 KB, Metadata Command Center extracts metadata from the initial 100 KB of the file. However, for XSD file types, Metadata Command Center extracts complete metadata.

Prerequisites for configuring the Amazon S3 catalog source

Use the Amazon S3 v2 connector to connect to the Amazon S3 source system. For information about configuring a connection in Administrator, see *Connections* in the Cloud Common Services help.

Configure permissions

To extract metadata and run profiles, you need account access and permissions on the Amazon S3 source system.

Permissions to extract metadata

Configure the following permissions on the Amazon S3 catalog source:

- Read permission for the user account that you use to access the catalog source.
- Access permission. Required if the user account is different from the user account that you used to create the Amazon S3 catalog source.

Permissions to run data profiles

To perform data profiling, grant the following permissions to the user:

- PutObject. Required to process the staging data for Avro and Parquet files.
- GetObject. Required to read the objects from Amazon S3 buckets.
- DeleteObject. Required to delete the staging data of Avro and Parquet files.
- ListBucket. Required to view the objects from Amazon S3 buckets.
- ListBucketMultipartUploads. Applicable only for mappings in advanced mode.

Data profiling for Amazon S3 objects

Configure data profiling to run profiles on the metadata extracted from an Amazon S3 source system. You can run data profiles on the following Amazon S3 objects:

- AVRO
- CSV

- Parquet

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for AVRO, CSV, and Parquet file formats:

File format	Data type
Avro	- INT - STRING
CSV	- STRING
Parquet	- BOOLEAN - INT32 - INT64 - FLOAT - DOUBLE - DATE - DECIMAL - STRING

Sampling type

You can run the data profiling task on all rows for an Amazon S3 source system.

Note: To run a profile on an Avro or Parquet file, connect to an advanced cluster. For more information about advanced clusters, see Advanced Clusters help.

Data classification for Amazon S3 objects

Configure data classification for Amazon S3 catalog sources to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Connection properties

When you configure a connection to the Amazon S3 source system in Administrator, you can view the connection properties for that connection on the **Registration** page in Metadata Command Center.

The following table describes the Amazon S3 connection properties:

Property	Description
Runtime Environment	The execution platform that runs tasks. The runtime environment is either a Secure Agent or a serverless runtime environment.
Access Key	Amazon Web Services access key ID to sign requests that you send to Amazon Web Services.
Secret Key	Amazon Web Services secret access key to sign requests that you send to Amazon Web Services.
Bucket Name	Amazon Web Services bucket name that needs to be scanned.
Region	A named set of Amazon resources in the same geographical area.

Note: To authenticate to Amazon S3 source systems, you can create and use an access key and a secret key. Optionally, you can configure Identity and Access Management (IAM) authentication in your AWS user account. If you use IAM authentication, you do not need to provide access key ID and secret access key

explicitly in the Amazon S3 connection. For more information about managing IAM authentication for Amazon S3, see *Amazon S3 Connector* in the Connectors help.

Configuration parameters for metadata extraction

Expand the **Catalog Source Configuration Options** in the **Metadata Extraction** tab of the **Configuration** page. Configure the following parameters for extracting metadata from an Amazon S3 source system:

Parameter	Description
Extract Group Elements from Hierarchical Files	Select one of the following options to extract group or leaf elements from hierarchical files: - Yes. Extracts group elements from hierarchical files with the complete hierarchy of hierarchical fields. You can view the hierarchy of hierarchical files in the **Hierarchy** tab of assets in Data Governance and Catalog. - No. Extracts only leaf elements from hierarchical files without the complete hierarchy of hierarchical fields. You can extract group elements from hierarchical files for the following file types: - AVRO. Extracts and groups hierarchical files and hierarchical fields. - Parquet. Extracts and groups hierarchical files and hierarchical fields. - JSON. Extracts and groups hierarchical files and hierarchical fields. - XML. Extracts and groups elements and attributes. For XML file types, a maximum depth of 1000 elements is permitted within a single element in the hierarchy. - XSD. Extracts and groups elements and attributes. **Attention:** If you modify the **Extract Group Elements from Hierarchical Files** field and run the catalog source again, the asset page doesn't display the hierarchical elements in the correct hierarchy groups. If you modify the property value, purge the catalog source before you run it again.
Enable Extension-Based File Type Detection	Select one of the following options to detect file types by file extensions or by parsing the file contents: - Yes. Detects file types by file extensions. - No. Parses the file contents to detect file types. **Note:** You can detect file types by file extensions for the following file types: - CSV - TSV - TXT - XML
Use First Row as Header of Delimited Files	Select one of the following options to use the first row as the header or detect headers automatically for delimited files: - Yes. Detects column headers based on the following rules: - Duplicate headers get suffixed with '#' followed by a number, for example, ABC#1, ABC#2. The detection is not case-sensitive. - Empty column header values appear as UnknownColumn<position>, for example UnknownColumn2. - The header row in the file is detected even if it has a different number of columns than the data rows. - No. Detects headers automatically for delimited files.
Headers of Delimited Files	Specify values to determine headers of delimited files. Separate multiple values by commas. If any value from the list is found in the first row of the delimited file, then the first row is used as the header. **Note:** This parameter appears only if you choose No for the **Use First Row as Header of Delimited Files** parameter.

Parameter	Description
Treat Files Without Extension As	Select one of the following options to identify files without an extension: - Parquet - Avro - JSON
Enter File Delimiter	Specify the file delimiter if the file from which you extract metadata uses a delimiter other than the following list of delimiters: - Comma(,) - Horizontal tab (\t) - Semicolon (;) - Colon (:) - Pipe symbol (|) Enclose the delimiter in single quotes. For example, '$'. Use a comma to separate multiple delimiters.
Files to be excluded during partition discovery	Specify the regular expression of the files that you want to exclude during partition discovery. Enclose each regular expression in double quotes. For example, ".*json","Customer.csv","Parquet.*". Use a comma to separate multiple regular expressions.

Expand the **Partitioned File Configuration** section in the **Metadata Extraction** tab of the **Configuration** page. The following table shows the parameters that you can configure for custom partition detection and partition pruning:

Parameter	Description
Custom Partition Detection Configuration File	Upload a configuration file in the JSON format to specify the pattern of the non-hive style custom partitions in the source system. Metadata Command Center detects only those partitions that have non-hive style date patterns.
Partitioned Pruning Configuration File	Upload a configuration file in the JSON format. In the file, specify additional information to identify partitions for determining the relevant schema in the source system.
Partition Detection	Select one of the following options: - Yes. Enables partition detection. - No. Disables partition detection.
Partition Pruning	Applicable if you enable partition detection. Select one of the following options: - Yes. Enables partition pruning. - No. Disables partition pruning. Default is Yes.

The following code shows a sample pruned partition configuration file in the JSON format:

```
{
  "SortablePartitionKeys": [
    {
      "Key": "Region",
      "PrunedValues": [
        "USA",
        "IND"
      ]
    }
  ]
}
```

In this example, the partitions `USA` and `IND` are used for determining the schema.

Data lineage

Lineage data is available for Amazon S3 assets that connect to the following source systems:

- Databricks Notebook
- Informatica products, services, and tools
- Microsoft Azure Data Factory
- Microsoft Power BI
- Tableau

For more information about data lineage, see the *Asset Discovery* help.

dbt

dbt is a data transformation tool that enables data analysts and engineers to transform data in a cloud data analytics warehouse.

Objects extracted

Metadata Command Center extracts the following metadata from a dbt source system:

- DbtCalculation
- DbtFolder
- DbtModel
  - DbtModel Instance
- DbtPackage
- DbtSeed
- DbtTest
- DbtProject
- Snapshot
  - Snapshot Instance

Note: Metadata Command Center only extracts metadata from models, seeds, and tests.

Data lineage

The following lineage data is available for dbt assets:

- Data set level is available for DbtModel and DbtSeed
- Data element level is available for DbtCalculation

Note: You cannot drill down to view the data element level lineage for the DbtModel and DbtSeed assets. Select a data element and open the **Lineage** tab to view the data element level lineage.

For more information about data lineage, see the *Asset Discovery* help.

Databricks

Databricks combines data warehouses and data lakes into an AI-driven Databricks Lakehouse platform.

You can run connection-aware scans on Databricks sources.

You can use SQL warehouse or all-purpose clusters to extract metadata.

Note: To improve wildcard lineage at the directory or file level for Databricks assets, perform connection assignment, and run the Databricks catalog source again. These wildcards can refer to files in Amazon S3 and Microsoft Azure Data Lake Storage Gen2.

Objects extracted

You can extract AI Model Core and AI Model Core Version metadata from Databricks Unity Catalog source systems. Additionally, you can retrieve lineage captured by Databricks Unity Catalog.

Note: Databricks Unity Catalog retains lineage data for 90 days.

You can extract metadata from Databricks notebooks if they use the following technologies:

- Markdown
- Python
- SQL

You can extract metadata of the following objects from a Databricks workspace:

- Calculation
- Command
- Experiment
  - Experiment Run
- Folder
- Genie Space
- Job Parameter
- Knowledge Assistant
- Live View
- Materialized View
- MCP Server
- MCP Server Tool
- Notebook Definition
- Notebook Instance
- Notebook Parameter
- Notebook Task
- Pipeline Definition (SQL based)
  - Live View
  - Materialized View
  - Streaming Table
  - Streaming View
- Result

- Run Job Task
- Serving Endpoint
- Streaming Table
- Streaming View
- Supervisor Agent
- Supervisor Agent Tool
- Task Parameter
- Workflow Job Definition
- Workflow Job Instance

You can extract metadata of the following objects from Databricks Unity Catalog:

- AI Search Index
- AI Search Index Column
- Column
  - Primary Key
  - Foreign Key
- Dashboard
- Database
- External Column
- External Table
- File
- File System
- Function
- Metric View
- Schema
- Stored Procedure
- Table
- View
- Volume

You can extract metadata from foreign catalogs in Databricks Unity Catalog that connect to the following source systems:

- Amazon Redshift
- Databricks
- Google BigQuery
- Microsoft Azure Synapse Data Warehouse
- Microsoft SQL Server
- Salesforce
- Snowflake

You can extract the following complex data type columns along with their nested fields from Databricks source systems:

- Map
- Struct
- Array

You can extract metadata of the following file types from a Databricks volume:

- AVRO
- Compressed files
  - TAR
  - ZIP
- Delimited files
  - CSV
  - TSV
- E-mail files
  - EML
  - EMLX
  - MSG
- JSON
- JSONL
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- ORC
- Parquet
- PDF
- Presentation files
  - PPT
  - PPTX
- Rich Text Format (RTF)
- Text
  - TXT
  - Markdown
- XML
- XSD

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
AVRO	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

Data profiling for Databricks objects

Configure data profiling to run profiles on the metadata extracted from Databricks Delta Lake source systems. You can run profiles on Databricks Delta tables created in all-purpose clusters or SQL warehouse. You can also run profiles on Databricks Unity Catalog objects.

You can run profiles on the following Databricks Delta Lake objects:

- Delta Table
- External Table in Delta format.
- View

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Databricks Delta Lake objects:

- Bigint
- Boolean
- Date
- Decimal
- Double
- Float
- Int
- Smallint
- String
- Tinyint
- Timestamp

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for a Databricks catalog source:

- All Rows
- Custom Query. Sampling method to specify a percentage of rows on which you want to run the data profiling task. For example, **TABLESAMPLE (BUCKET 10 OUT OF 50)**, **TABLESAMPLE (5 PERCENT)**, **LIMIT 2**, or **TABLESAMPLE (5000 ROWS)**.

Data lineage

The following lineage data is available for Databricks assets:

- Data set level
- Data element level

You can extract lineage information from the following source systems:

- Databricks Delta Lake
- Amazon S3
- Oracle
- Microsoft Azure Data Lake Storage Gen2

You can extract lineage information from the following technologies, if available in Unity Catalog:

- Python
- SQL
- Scala
- R

For more information about data lineage, see the *Asset Discovery* help.

File System

Use the File System catalog source to extract metadata from files located on a Windows or a Linux machine into the catalog. You can use either the Local File System protocol to import metadata from the files located on a local machine or use the Remote File System protocol to import metadata from the files located on a remote Windows machine.

Note: To extract metadata from files located on a remote Linux machine, configure the SFTP File System catalog source in Metadata Command Center.

For more information, see the *SFTP File System* catalog source help.

Objects extracted

Metadata Command Center extracts files and folders from a Windows or a Linux file system.

Supported file types

You can extract metadata from the following file types:

- AVRO
- Compressed files
  - TAR
  - ZIP
- Delimited files
  - CSV
  - TSV

- E-mail files
  - EML
  - EMLX
  - MSG
- JSON
- JSONL
- Markdown
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- Parquet
- PDF
- Presentation files
  - PPT
  - PPTX
- Rich Text Format (RTF)
- TXT
- XML
- XSD

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
Avro	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

Note: File System catalog sources can only extract input files encoded in UTF-8.

You can extract workbooks, worksheets, and columns from Microsoft Excel files.

You can extract metadata from XML and XSD file formats as XML file objects. Metadata Command Center extracts only elements and attributes from XML and XSD files. If the size of the XML file exceeds 100 KB,

Metadata Command Center extracts metadata from the initial 100 KB of the file. However, for XSD file types, Metadata Command Center extracts complete metadata.

Data lineage

Lineage data is available for File System assets that connect to the following source systems:

- Informatica PowerCenter
- Informatica Cloud Data Integration
- Microsoft SQL Server Integration Services (SSIS)

For more information about data lineage, see the *Asset Discovery* help.

Google BigQuery

Google BigQuery is a serverless data warehouse that performs scalable analysis over petabytes of data. Use a Google BigQuery catalog source to collect metadata from the assets in a Google BigQuery source system.

Objects extracted

Metadata Command Center extracts the following metadata from a Google BigQuery source system:

- Database
- Schema
- Table
- External Table
- Column
- View
- View Column
- Materialized View

  Note: Objects of the Materialized View type appear as View in Data Governance and Catalog.
- Nested Field
- Stored procedure
- SQL User-defined functions (UDF)

You can extract metadata from columns with the following complex data types, along with their nested fields, from Google BigQuery source systems:

- Array
- Range
- Struct

Data Governance and Catalog displays columns with their complex data types and nested fields, including data types of those nested fields. The nested fields within Array and Range column data types appear under element.

Note: Each time Metadata Command Center runs a scan on a Google BigQuery catalog source, Data Governance and Catalog displays the extracted objects along with the objects from the previous scans. This means that if you modify the filters in Metadata Command Center and run a scan, Data Governance and Catalog does not replace the objects from the previous scan. Instead, Data Governance and Catalog adds the

newly extracted objects to the existing scanned objects. To see the results of only the latest scan, choose Delete as the Metadata Change Option before you run the scan.

Data profiling for Google BigQuery objects

Configure data profiling to run profiles on the metadata extracted from a Google BigQuery source system. You can run data profiles on the following objects:

- Table
- External Table
- Partitioned Table
- Views
- Materialized Views

The data profiling task runs profiles on the following data types:

- BOOLEAN
- DATE
- DATETIME
- FLOAT
- INTEGER
- NUMERIC
- STRING
- TIME
- TIMESTAMP

Data lineage

The following lineage data is available for Google BigQuery assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

Google Vertex AI

Google Gemini Enterprise Agent Platform is a managed platform that you can use to build, train, deploy, and monitor machine learning and generative AI models.

Objects extracted

Metadata Command Center extracts the following metadata from a Google Gemini Enterprise Agent Platform source system:

- Agent
- AI Application
- AI Model Core
- AI Model Core Version
- AI Model Evaluation

- Data Connector
- Data Store
- Evaluation Metric
- Model Endpoint
- Project
- Subagent

Data lineage

The following lineage data is available for Google Gemini Enterprise Agent Platform assets:

- From dataset to model version

For more information about data lineage, see the *Asset Discovery* help.

Greenplum

Greenplum is a massively parallel processing SQL database based on PostgreSQL open source database technology.

Objects extracted

Metadata Command Center extracts the following metadata from a Greenplum source system:

- Column
  - Primary key
  - Foreign key
- Database
- Schema
- Stored Procedure
- Table
- View
- View Column

Data lineage

The following lineage data is available for Greenplum assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

IBM Db2 for LUW

IBM Db2 for LUW is a relational database management system (RDBMS) designed by IBM to store, analyze, and retrieve data from for Windows, Linux and Unix operating systems.

Configure an IBM Db2 for LUW catalog source to extract metadata from an IBM Db2 for LUW database hosted on a dedicated server, or from an Amazon RDS for Db2 database.

Objects extracted

Metadata Command Center extracts the following objects from an IBM Db2 for LUW source system:

- Database
- Schema
- Table
- View
- Column
- Materialized Query Table
- Stored Procedure

Note: To extract the following schemas, you need to define include filters:

- NULLID
- SQLJ
- SYSFUN
- SYSIBMINTERNAL
- SYSIBMTS
- SYSPROC
- SYSPUBLIC
- SYSCAT
- SYSIBM
- SYSIBMADM
- SYSSTAT
- SYSTOOLS

Data lineage

The following lineage data is available for IBM Db2 for LUW assets:

- From table and columns to view

For more information about data lineage, see the *Asset Discovery* help.

IBM Db2 for z/OS

IBM Db2 for z/OS is an IBM relational database management system (RDBMS) for IBM Z mainframes to manage core business data. IBM Db2 for z/OS is the main operating system for the IBM hardware platform and IBM zSystems.

Objects extracted

Metadata Command Center extracts the following metadata from the IBM Db2 for z/OS source system:

- Database

- Schema
- Table
- Column
- View
- View column
- Primary key
- Foreign key

Data lineage

Data lineage is available for the following IBM DB2 for z/OS assets at the data set and data element levels:

- Table
- View
- View Column

For more information about data lineage, see the *Asset Discovery* help.

IBM Mainframe Job Control Language (Accelerator)

Job Control Language (JCL) is a scripting language used on IBM mainframe operating systems to instruct the systems on how to run a batch job or start a subsystem. The use of JCL involves the specification of job parameters through the JOB, EXEC, and DD statements to manage input, processing, and output tasks in a structured manner.

Objects extracted

You can use the IBM Mainframe Job Control Language (Accelerator) catalog source to extract metadata from the following objects in the IBM Mainframe Job Control Language source system:

- JCL Job
- JCL Step
- Calculation
- COBOL Program
- COBOL Program Instance
- JCL Procedure
- JCL Procedure Instance
- Partitioned Dataset
- Mainframe File Field
- Mainframe File Format

Data lineage

Data lineage is available for the following IBM Mainframe Job Control Language (Accelerator) assets:

- JCL Step
- COBOL Program Instance
- Mainframe File Field

- Mainframe File Format

For more information about data lineage, see the *Asset Discovery* help.

IBM Netezza

IBM Netezza is a data warehouse system that integrates the database, server, and storage to run and manage complex data warehouse tasks. You can create and configure an IBM Netezza catalog source to extract metadata from an IBM Netezza database.

Objects extracted

Metadata Command Center extracts the following metadata from an IBM Netezza source system:

- Database
- Data Type
- Foreign Key
- Materialized View
- Primary Key
- Schema
- Table
- Unique Key Constraint
- View
- Stored Procedure

Data lineage

The following lineage data is available for IBM Netezza assets:

- From table to view
- From view to view
- From view to table

For more information about data lineage, see the *Asset Discovery* help.

Informatica PowerCenter

Informatica PowerCenter is an Informatica product that extracts data from multiple sources, transforms the data according to business logic, and loads the transformed data into different target databases.

Objects extracted

Metadata Command Center extracts the following objects from an Informatica PowerCenter source system:

- Folder
- Repository
- Workflow

- Workflow Instance
- Calculation
- Mapping
- Session
- Session Instance

Data lineage

The following lineage data is available for PowerCenter assets:

- Summary lineage
- Data set level
- Data element level
- SQL override
- Pre- and post-SQL session
- Default column

For more information about data lineage, see the *Asset Discovery* help.

JDBC

JDBC is a Java API to connect and interact with databases. You can use a JDBC connection to extract metadata from any source system for which a JDBC driver is available. Metadata Command Center certifies the following source systems from which you can extract metadata using the JDBC catalog source:

- Amazon DynamoDB
- Microsoft Azure Cosmos DB
- Marketo
- Microsoft Dynamics CRM
- MongoDB
- IBM Netezza
- Sybase ASE (Adaptive Server Enterprise)
- Sybase IQ (Intelligent Query)
- Workday
- Apache Cassandra
- SAP SuccessFactors
- NetSuite
- SingleStore
- IBM Db2 for z/OS

To extract metadata from these source systems, download the source-specific JDBC drivers and procure appropriate licenses. For information about using the JDBC drivers and licenses to extract metadata, see the HOW TO: Use the JDBC drivers to extract metadata in Metadata Command Center Knowledge article.

Note: MongoDB and Amazon DynamoDB are NoSQL databases that do not contain views and view columns.

Objects extracted

Metadata Command Center extracts the following metadata from source systems that you connect to with the JDBC catalog source:

- Database
- Schema
- View
- Table
- Column
- View Column

Data lineage

The following lineage data is available for JDBC assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

Microsoft Azure Data Lake Storage Gen2

Microsoft Azure Data Lake is a scalable data storage and analytics service that is hosted on Azure. Configure an Azure Data Lake Store (ADLS) catalog source to extract metadata from the data lake store.

Objects extracted

Metadata Command Center extracts the following metadata from an Azure Data Lake Storage Gen2 source system:

- File
- Folder
- Container
- Iceberg Table
- Iceberg Field

File types

You can extract metadata from the following file types:

- AVRO
- Compressed files
  - TAR
  - ZIP
- Delimited files
  - CSV
  - TSV

- E-mail files
  - EML
  - EMLX
  - MSG
- JSON
- JSONL
- Markdown
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- Parquet
- PDF
- Presentation files
  - PPT
  - PPTX
- Rich Text Format (RTF)
- TXT
- XML
- XSD

Note: Catalog source jobs can extract metadata from protected unstructured files. However, some metadata attributes of such files might not get extracted or displayed in Data Governance and Catalog.

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
Avro	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

You can extract workbooks, worksheets, and columns from Microsoft Excel files.

You can extract metadata from XML and XSD file formats as XML file objects. Metadata Command Center extracts only elements and attributes from XML and XSD files. If the size of the XML file exceeds 100 KB,

Metadata Command Center extracts metadata from the initial 100 KB of the file. However, for XSD file types, Metadata Command Center extracts complete metadata.

Data profiling for Microsoft Azure Data Lake Storage Gen2 objects

Configure data profiling to run profiles on the metadata extracted from a Microsoft Azure Data Lake Storage Gen2 source system. You can run data profiles on the following Microsoft Azure Data Lake Storage Gen2 objects:

- Avro
- CSV
- JSON
- Parquet

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for AVRO, CSV, JSON, and Parquet file formats:

File format	Supported data type
AVRO	- INT - STRING
CSV	- STRING
JSON	- ARRAY - BOOLEAN - NUMBER (double) - NUMBER (float) - NUMBER (int) - NUMBER (long) - OBJECT - STRING
Parquet	- BOOLEAN - INT32 - INT64 - FLOAT - DOUBLE - DATE - DECIMAL - STRING

Sampling type

You can run the data profiling task on all rows for a Microsoft Azure Data Lake Storage Gen2 catalog source.

Note: To run a profile on an Avro or Parquet files, use a secure agent configured with an advanced cluster. The same agent can also process delimited files. If the agent has no advanced cluster capabilities, the data profiling task runs profiles only on delimited files. For more information about advanced clusters, see Advanced Clusters help.

Data classification for Microsoft Azure Data Lake Storage Gen2 objects

Configure data classification for Microsoft Azure Data Lake Storage Gen2 catalog sources to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Data lineage

Lineage data is available for Microsoft Azure Data Lake Storage Gen2 assets that connect to the following source systems:

- Databricks Notebook
- Informatica products, services, and tools
- Microsoft Azure Data Factory
- Microsoft Power BI
- Snowflake
- Tableau

For more information about data lineage, see the *Asset Discovery* help.

Microsoft Azure SQL Server

Microsoft Azure SQL Server is a managed cloud database.

Objects extracted

Metadata Command Center extracts the following metadata from a Microsoft Azure SQL Server source system:

- Database
- Schema
- Table
- View
- Synonym (local, public)
- Function
- Procedure
- Package
- Trigger
- Column
  - Primary Key
  - Foreign Key
  - Unique
- External Table
- External Column

Data lineage

The following lineage data is available for Microsoft Azure SQL Server assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views

- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Microsoft Azure Synapse Data Warehouse

Microsoft Azure Synapse Data Warehouse, formerly known as Azure SQL Data Warehouse, is a big data analytic service that queries and analyzes your data. Create a Microsoft Azure Synapse Data Warehouse catalog source to access data from Microsoft Azure SQL Data Warehouse.

Objects extracted

The metadata extraction capability extracts the following objects from a Microsoft Azure Synapse Data Warehouse catalog source:

- Database
- Table
- Schema
- View
- Materialized View
- Function
- Stored Procedure
- Column
- External Table
- External Column

Note: If an incremental metadata extraction job includes a view, it extracts the corresponding tables even if the tables were extracted in previous runs.

Note: Effective in the November 2023 release, Metadata Command Center retrieves the database name from the source system instead of the Azure DW JDBC URL. If you extracted database objects before the November 2023 release, and the name of a database that you entered in the Azure DW JDBC URL uses a different case than the original database name, you might extract duplicate assets when you run the catalog source job again. To ensure that you extract the correct database structure, select **Delete** in the Metadata Change Option and rerun the catalog source job.

Data profiling for Microsoft Azure Synapse Data Warehouse objects

Configure data profiling to run profiles on the metadata extracted from a Microsoft Azure Synapse Data Warehouse source system.

You can run data profiles on the following Microsoft Azure Synapse Data Warehouse objects:

- Tables
- External Tables created in the following file formats on the Microsoft Azure Serverless SQL pool:
  - Delimited text
  - Parquet
- Views

Configure the following data profiling properties in the **Data Profiling** tab of the **Configuration** page in Metadata Command Center:

Property	Description
Azure Blob Container	Name of the Blob container that is used to stage profiled data. Applies to the Azure Blob storage type.
ADLS FileSystem Name	Name of the file system that is used to stage profiled data. Applies to the ADLS Gen2 storage type.
Staging File Format	File format to use when you stage the profiled data. Select one of the following formats: - Delimited Text. Select if the external table is created in the Delimited text file format. - Parquet. Select if the external table is created in the Parquet file format. Applies to external tables created on the Microsoft Azure Serverless SQL pool.
Field Delimiter	Character used to separate fields in a file. Default is `0x1e`. Non-printable characters must be specified as hexadecimal characters. **Note:** Use the field delimiter that you used while creating the external table in the Delimited text file format.
Quote Character	Specifies the quote character to skip when you read data from Microsoft Azure Synapse SQL. The quote character that you specify must not exist in the source table. If it exists, enter a different quote character value. Default is `0x1f`. **Note:** Use the quote character that you used while creating the external table in the Delimited text file format.

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Microsoft Azure Synapse Data Warehouse objects:

- Bigint
- Bit
- Char
- Date
- Datetime
- Datetime2
- Decimal
- Float
- Int
- Nchar
- Nvarchar
- Real
- Smalldatetime
- Smallint
- Time
- Tinyint
- Uniqueidentifier
- Varchar

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for a Microsoft Azure Synapse Data Warehouse catalog source:

- All Rows
- Limit N Rows
- Random N Rows

Data classification for Microsoft Azure Synapse Data Warehouse objects

Configure data classification for Microsoft Azure Synapse Data Warehouse catalog sources to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Data Lineage

The following lineage data is available for Microsoft Azure Synapse Data Warehouse assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Microsoft Fabric Data Warehouse

Microsoft Fabric Data Warehouse is a data warehouse for large-scale enterprise analytics available on the Microsoft Fabric platform.

Objects extracted

Metadata Command Center extracts the following metadata from a Microsoft Fabric Data Warehouse source system:

- Column
- Database
- Function
- Primary Key
- Schema
- Stored procedure
- Table
- View

Data lineage

The following lineage data is available for Microsoft Fabric Data Warehouse assets at the data set level and data element level:

- From table to view

- Stored procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Microsoft SQL Server

Microsoft SQL Server is a Relational Database Management System (RDBMS) solution for storing and retrieving data.

Objects extracted

Metadata Command Center extracts the following metadata from a Microsoft SQL Server source system:

- Database
- Schema
- Table
- View
- Column
  - Primary Key
  - Foreign Key
- Stored Procedure
- Function
- Trigger
- External Table
- External Column
- Objects created using an SQL Server linked server

Data profiling for Microsoft SQL Server objects

Configure data profiling to run profiles on the metadata extracted from a Microsoft SQL Server source system. You can run data profiles on the following Microsoft SQL Server objects:

- Table
- View

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Microsoft SQL Server objects:

- BIGINT
- NUMERIC
- BIT
- DECIMAL
- INT

- SMALLINT
- TINYINT
- FLOAT
- REAL
- DATE
- DATETIME2
- SMALLDATETIME
- DATETIME
- TIME
- CHAR
- VARCHAR
- TEXT
- NCHAR
- NVARCHAR
- NTEXT

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for a Microsoft SQL Server catalog source:

- All Rows
- Limit N Rows

Data classification for Microsoft SQL Server objects

Configure data classification for Microsoft SQL Server catalog sources to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Data lineage

The following lineage data is available for Microsoft SQL Server assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Microsoft SQL Server Analysis Services

Microsoft SQL Server Analysis Services is an online analytical processing and data mining tool. It allows you to mine and process data to facilitate decision-making and business analytics.

Objects extracted

Metadata Command Center extracts the following metadata from the SSAS source system:

SSAS model	Extracted assets
Tabular	- Project - Table - Calculation - Measure Group - KPI - Perspective - Perspective Table
Multidimensional	- Project - Data Source View - Data Source View Table - Dimension - Dimension Hierarchy - Cube - Cube Dimension - Cube Dimension Hierarchy - Cube Measure Group - Cube KPI - Cube Partition - Cube Perspective - Cube Calculation

Data lineage

Tabular

The following lineage data is available for Measure Group, KPI, Table, Perspective Table, and Calculation assets:

- Data set level
- Data element level

Multidimensional

The following lineage data is available for Cube Calculation, Cube Dimension, Cube KPI, Cube Measuring Group, Cube Perspective, Data Source View Table, Dimension, Dimension Hierarchy, and Calculation assets:

- Data set level
- Data element level

For more information about data lineage, see the *Asset Discovery* help.

Microsoft SQL Server Integration Services

Microsoft SQL Server Integration Services (SSIS) is an ETL (Extract, Transform, Load) tool that extracts data from multiple sources, transforms, and loads them into different target databases. SSIS is a component of the Microsoft SQL Server database.

Objects extracted

Metadata Command Center extracts the following objects from a Microsoft SQL Server Integration Services source system:

- Calculation
- Data Task
- Database
- Folder
- Package
- Parameter
- Parameter Container
- Procedure Definition
- Procedure Instance
- Result Set
- Result Set Calculation
- Schema
- Script
- Statement

Data lineage

The following lineage data is available for Microsoft SQL Server Integration Services assets:

- Data set level
- Data element level
- Embedded SQL
- SQL Task
- Stored Procedure calls

For more information about data lineage, see the *Asset Discovery* help.

Microsoft SQL Server Reporting Services

Microsoft SQL Server Reporting Services (SSRS) is a server-based report generating software system. It is part of a suite of Microsoft SQL Server services. You can use SSRS to prepare interactive and printed reports. SQL administrators can connect to SQL databases and use SSRS tools to format SQL reports.

Objects extracted

Metadata Command Center extracts the following objects from a Microsoft SQL Server Reporting Services source system:

- Folders
- Projects
- DataSets

- Fields
- Reports
- PlSql DataSet Statements
- Calculations

Note: If you run catalog sources created prior to the July 2023 release with Retain as the **Metadata Change Option**, duplicate calculations appear in Data Governance and Catalog. To avoid duplicate calculations and to view complete lineage information, run catalog sources created prior to the July 2023 release with Delete as the **Metadata Change Option**.

Data lineage

Lineage data is available for Microsoft SQL Server Reporting Services (SSRS) assets that connect to the following source systems:

- Microsoft SQL Server
- Oracle

For more information about data lineage, see the *Asset Discovery* help.

Microsoft SQL Server Script

Metadata Command Center extracts the following metadata from the Microsoft SQL Server Script source system:

- Calculation
- Folder
- Script
- Statement

Data lineage

The following lineage data is available for Statements and Calculation assets:

- Data set level
- Data element level

Note: You cannot drill down to view the data element level lineage for the Statement assets. Select a data element and open the **Lineage** tab to view the data element level lineage.

For more information about data lineage, see the *Asset Discovery* help.

MicroStrategy

Strategy is an enterprise business intelligence application software and a source system from which you can extract metadata about Strategy business intelligence objects, such as dashboards, scorecards, highly formatted reports.
Strategy was previously known as MicroStrategy. In February 2025, the company including its business intelligence products, was rebranded as Strategy.

Objects extracted

Metadata Command Center extracts the following metadata from the Strategy source system:

- Attribute
- AttributeForm
- CalculatedReportField
- Column
- Consolidation
- ConsolidationElement
- ConsolidationModel
- CustomGroup
- CustomGroupModel
- DatabaseInstance
- DatabaseSchema
- Dataset
- Document
- DocumentReport
- Expression
- Fact
- FactMeasure
- Filter
- FilterModel
- Folder
- HTMLDocument
- HTMLDocumentReport
- HiddenFolder
- Hierarchy
- IntelligentCube
- IntelligentCubeReport
- LogicalQueryTable
- LogicalTable
- Lookup
- Metric
- MetricMeasure
- MetricModel
- Project
- ProjectSource
- Prompt
- PromptAnswer
- PromptModel

- QueryBuilderDefinition
- Report
- ReportMetric
- SQLAttributeForm
- SQLColumn
- SQLMetric
- Schema
- SecurityFilter
- SecurityFilterModel
- Subtotal
- SubtotalMeasure
- SubtotalModel
- Threshold
- WarehouseTable

Data lineage

The following lineage data is available for DocumentReport, HTMLDocumentReport, IntelligentCubeReport, and Report assets:

- Data set level
- Data element level

For more information about data lineage, see the *Asset Discovery* help.

MySQL

MySQL is an open-source relational database management system (RDBMS) to store and structure data.

Objects extracted

Metadata Command Center extracts the following objects from a MySQL source system:

- Database
- Schema
- Table
- View
- Materialized view

Data lineage

The following lineage data is available for MySQL assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

Oracle

Configure an Oracle catalog source to extract metadata from an Oracle database hosted on a dedicated server, an AWS RDS Oracle instance, or Oracle Autonomous Database.
Oracle Autonomous Database is a SaaS implementation of Oracle Database on the Oracle Cloud Infrastructure.

Objects extracted

Metadata Command Center extracts the following objects from an Oracle source system:

- Database
- Schema
- Table
- View
- Materialized View

  Note: Objects of the Materialized View type appear as View in Data Governance and Catalog.
- Column
  - Primary Key
  - Foreign Key
- Stored Procedure
- Function
- Package
- External Table

  Note:
  - For Oracle On-premise you can extract data from external tables created in File System and Hadoop Distributed File System source systems.
  - For Oracle ADB you can extract data from external tables created in Amazon S3, Microsoft Azure Data Lake, and Oracle Cloud Object Storage source systems.

    You can extract data from the external tables created with DBMS_CLOUD.CREATE_EXTERNAL_TABLE and DBMS_CLOUD.CREATE_EXTERNAL_PART_TABLE procedures.
- Sequence
- Trigger
- Objects created using Oracle database link

You can also use the following SQL functionalities:

- Static SQL
- PL/SQL
- Procedure calls with parameters tracing
- Dynamic SQL with metatables
- COPY_DATA
- EXPORT_DATA

Data profiling for Oracle objects

Configure data profiling to run profiles on the metadata extracted from an Oracle source system. You can either use the Oracle connector to establish a connection to Oracle for profiling data, or use the JDBC V2 connector to enable Secure Agent-based data profiling for Oracle. You can run data profiles on the following Oracle objects:

- Table
- View

After running the data profiling capability on an Oracle catalog source, you can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Oracle objects:

- CHAR
- DATE
- NUMBER
- NUMBER (p,s)
- TIMESTAMP
- VARCHAR
- VARCHAR2
- NCHAR
- NVARCHAR2
- FLOAT (126)
- TIMESTAMP WITH TIMEZONE
- TIMESTAMP WITH LOCAL TIMEZONE
- INTERVAL DAY TO SECOND
- INTERVAL YEAR TO MONTH
- BINARY FLOAT
- BINARY DOUBLE
- FLOAT
- UROWID
- ROWID

Note: Oracle supports the maximum precision value of 38 for the NUMBER data type for data profiling.

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for an Oracle catalog source:

- All Rows
- Limit N Rows

Data classification for Oracle objects

Configure data classification for an Oracle catalog source to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Data lineage

The following lineage data is available for Oracle assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function

For more information about data lineage, see the *Asset Discovery* help.

Oracle Business Intelligence

Oracle Business Intelligence is a business intelligence tool to gather, store, and visualize enterprise data. You can create and configure an Oracle Business Intelligence catalog source to extract metadata from the Oracle Business Intelligence Enterprise Edition Presentation Server. Metadata Command Center extracts report objects that include presentations, business, and physical models.

Objects extracted

Metadata Command Center extracts the following metadata from an Oracle Business Intelligence source system:

- Alias
- Alias Column
- Alias Key Column
- Alias Table
- Answers Report
- Business Model
- Business Model and Mapping
- Catalog
- Column
- Condition
- Criteria
- Criteria Column
- Criteria Hierarchical Column
- Dashboard
- Dashboard Page
- Dashboard Prompt
- Database
- Data Set
- Data Source
- Derived Logical Column

- Derived Presentation Column
- Element
- External Schema
- Folder
- Group
- Hierarchy
- Key
- KPI
- Link
- List of Values
- Logical Column
- Logical Dimension
- Logical Fact Table
- Logical Key Column
- Logical Level
- Logical Table
- Measure
- Parameter
- Parameter Answer
- Parameter Value
- Physical Column
- Physical Key Column
- Physical Table
- Presentation Column
- Presentation Fact Table
- Presentation Hierarchy
- Presentation Level
- Presentation Table
- Presentation Variable
- Prompt
- Prompt Answer
- Publisher Data Model
- Publisher Report
- Report
- Report Field
- Repository
- Repository Variable
- Session Initialization Block
- Session Variable

- Static Variable
- Subject Area
- Value
- Variable

Data lineage

Data lineage is available for the following Oracle Business Intelligence assets at the data set and data element levels:

- Alias Column
- Alias Key Column
- Alias Table
- Answers Report
- Criteria
- Criteria Column
- Logical Column
- Logical Dimension
- Logical Fact Table
- Logical Key Column
- Logical Table
- Measure
- Physical Key Column
- Physical Table
- Presentation Column
- Presentation Fact Table
- Presentation Hierarchy
- Presentation Level
- Presentation Table
- Presentation Variable
- Presentation Variables
- Prompt Answer
- Report
- Report Field

For more information about data lineage, see the *Asset Discovery* help.

Oracle PL/SQL Script

Oracle PL/SQL Script is a set of Oracle SQL statements stored in a file which you can use to run sequential scripts.

Objects extracted

Metadata Command Center extracts the following metadata from the Oracle Database source system:

- Calculation
- Folder
- Script
- Statements

Data lineage

The following lineage data is available for Calculation assets:

- Data set level

Note: You cannot drill down to view the data element level lineage for the Statement assets. Select a data element and open the **Lineage** tab to view the data element level lineage.

For more information about data lineage, see the *Asset Discovery* help.

Oracle SQL Loader

Oracle SQL Loader is a utility that you can use to bulk load data from external files into Oracle database tables.

Objects extracted

Metadata Command Center extracts the following metadata from an Oracle SQL Loader source system:

- Calculation
- Script
- Statement

Data lineage

The following lineage data is available for Oracle SQL Loader assets:

- Oracle to Oracle
- File to Oracle

For more information about data lineage, see the *Asset Discovery* help.

PostgreSQL

PostgreSQL is an open-source relational database management system (RDBMS) used as a data store or data warehouse for applications.

Objects extracted

Metadata Command Center extracts the following objects from a PostgreSQL source system:

- Database

- Foreign Table

  Note: Objects of the Foreign Table type appear as Table in Data Governance and Catalog.
- Schema
- Table
- View
- Materialized View

  Note: Objects of the Materialized View type appear as View in Data Governance and Catalog.
- Stored Procedure

Data lineage

The following lineage data is available for PostgreSQL assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

Qlik Sense

Qlik Sense is a business intelligence and visual analytics platform that supports a range of use cases including centrally deployed analytic applications, dashboards, and embedded analytics within a scalable framework.

Objects extracted

Metadata Command Center extracts the following objects from a Qlik Sense source system:

- Application
- Application Model
- Column
- Condition
- Connection
- Connection Schema
- Database Schema
- Dimension
- Dimension Attribute
- Document
- Expression
- Field
- File
- File Directory
- Folder
- Hub
- Measure

- Measure Attribute
- QVD
- QVD Model
- Source Column
- Source Table
- Story
- Stream
- System Field
- Table

Relationships

The relationships between the following Qlik Sense assets are derived and displayed:

- Hub to Stream
- Stream to Document

Data lineage

Data lineage is available for the following Qlik Sense assets:

- Document
- Table and its child assets

For more information about data lineage, see the *Asset Discovery* help.

Qlik Sense Cloud

Qlik Sense Cloud is a cloud-based business intelligence tool to connect to data and create reports. It offers modern analytics that enables you to uncover insights and initiate actions.

Objects extracted

Metadata Command Center extracts the following metadata from a Qlik Sense Cloud source system:

- Application
- Application Model
- Column
- Condition
- Dimension
- Dimension Attribute
- Document
- Expression
- Field
- File
- File Directory
- Folder

- Hub
- Measure
- Measure Attribute
- QVD
- QVD Model
- Source Column
- Source Table
- Space
- Story
- System Field
- Table
- Variable
- Variables

Data lineage

Data lineage is available for the following Qlik Sense Cloud assets at the data set and data element levels:

- Document
- Table and its child assets

For more information about data lineage, see the *Asset Discovery* help.

QlikView

QlikView is flexible business intelligence tool to connect to data and create reports. Create a QlikView catalog source to extract metadata from the QlikView source system.

Objects extracted

Metadata Command Center extracts the following objects from a QlikView source system:

- Application
- Button Field
- Column
- Condition
- Connection
- Connection Model
- Connection Schema
- Database Schema
- Document
- Expression
- Field
- File

- File Directory
- Folder
- Group
- Measure
- QVD
- QVD Model
- QVW
- QVW Model
- Source Column
- Source File
- Source Table
- System Field
- System Variable
- Table
- Text Field
- Variable

Data lineage

The following lineage data is available for QlikView assets:

- Report level
- Report element level

For more information about data lineage, see the *Asset Discovery* help.

SAP BusinessObjects

SAP BusinessObjects is a business intelligence tool to connect to data for data reporting, visualization, and sharing. Configure an SAP BusinessObjects catalog source to extract metadata from SAP BusinessObjects.

Objects extracted

Metadata Command Center extracts the following objects from an SAP BusinessObjects source system:

- Alias Column
- Alias Table
- Analytic Model
- Analytic Report
- Business Layer View
- Category
- Cell
- Class
- Column

- Connection
- Connection Classifier
- Connection Feature
- Connection Folder
- Connection Model
- Constants
- Context
- Contexts
- Crystal Report
- Crystal Report Model
- Custom Hierarchies
- Dashboard
- Data Provider
- Data Providers
- Database Connection
- Default Hierarchies
- Derived Table
- Desktop Intelligence Document
- Desktop Intelligence Model
- Detail
- Detail Result
- Detail Variable
- Dimension
- Dimension Result
- Dimension Variable
- Discovered Tables
- Enterprise Folder
- Favorite Folder
- Field
- File
- File Connection
- Filter
- Folder
- Formula Fields
- Formulas
- Group Name Fields
- Hierarchy
- Inbox
- Join

- Key
- List of Values
- Logical Column
- Measure
- Measure Result
- Measure Variable
- Merged Dimensions
- Object Package
- Olap Connection
- Olap Dimension
- Parameter
- Parameter Answer
- Parameter Prompt
- Personal Category
- Procedure Query
- Procedure Table
- Query
- Query Filter
- Report Field
- Report Filter
- Report Folder
- Repository
- Running Total Fields
- SQL Expression Fields
- SQL Query
- Schema
- Special Fields
- Summary Fields
- Table
- Universe
- Universe Connection
- Universe Folder
- Universe Model
- Universe Query
- Value
- Variables
- View
- Web Intelligence Document
- Web Intelligence Model

- XML Query

Data lineage

Data lineage is available for the following SAP BusinessObjects assets:

- Analytic Report
- Crystal Reports
- Desktop Intelligence Document
- Web Intelligence Document

For more information about data lineage, see the *Asset Discovery* help.

SAP BusinessObjects Data Services

SAP BusinessObjects Data Services is an ETL tool used for data integration, data quality, data profiling and data processing. It enables you to integrate and transform reliable data into a data warehouse system for analytical reporting.

Objects extracted

Metadata Command Center extracts the following metadata from an SAP BusinessObjects Data Services source system:

- Project
- Job
- Workflow
- Dataflow
- Dataflow Instance
- Script
- Script Instance
- Calculation

Data lineage

Data lineage is available for the following SAP BusinessObjects Data Services assets at the data set and data element levels:

- DataflowInstance
- ScriptInstance
- Calculation

For more information about data lineage, see the *Asset Discovery* help.

SAP HANA

SAP HANA Database is a multi-model database system that stores data in its memory and performs high-speed processing and analytics of data.

Objects extracted

Metadata Command Center extracts the following objects from an SAP HANA Database source system:

- Table
- Column
- View
  - Plain SQL Database View (Views created using the CREATE VIEW syntax)
  - Column View
- View Column
- Schema
- Calculation View
  Includes calculation views created in the HANA Deployment Infrastructure (HDI).

  Includes graphical and SQL script calculation views.
- Attribute
- Constraints (Primary Key and Foreign Key)
- Sequence

Data classification for SAP HANA Database objects

Configure data classification for SAP HANA Database catalog sources to classify and organize data in your organization. You can view the data classification results in Data Governance and Catalog.

Data lineage

The following lineage data is available for SAP HANA Database assets:

- From table to view

For more information about data lineage, see the *Asset Discovery* help.

SAP S/4HANA Cloud

SAP S/4HANA Cloud is a software-as-a-service (SaaS) version of the SAP S/4HANA ERP source system. It runs on the SAP S/4HANA in-memory database and provides a single place to access, process, and store enterprise data in real time. The SAP S/4HANA Cloud catalog source connects to SAP S/4HANA Cloud Public Edition sources.

Objects extracted

Metadata Command Center extracts the following metadata from an SAP S/4HANA Cloud Public Edition source system:

- Table
- CDS View
  - View Entity
  - View
  - Custom Entity
- Data Element

- Domain

Data lineage

The following lineage data is available for SAP S/4HANA Cloud assets:

- From table to view
- From view to view
- From unreleased dictionary object to view

For more information about data lineage, see the *Asset Discovery* help.

Snowflake

Snowflake is an analytic data warehouse provided as Software-as-a-Service (SaaS). The Snowflake data warehouse uses an SQL database engine with a unique architecture designed for cloud services.

Snowflake tags

In Snowflake, you can assign a tag to a database object. When a tag is assigned to an object, the tag is assigned a string value. Snowflake stores the tag and its string value as a key-value pair. For example, `cost_center = 'sales'`. When you run the metadata extraction task for a Snowflake catalog source, the catalog source job extracts Snowflake tags by default. In Data Governance and Catalog, you can view Snowflake tags for data elements and entities in a catalog source and also search assets by Snowflake tags.

For more information about Snowflake tags, see the Snowflake documentation.

Objects extracted

The metadata extraction service extracts the following objects from a Snowflake source system:

- Column

  Note: For certain column types, such as DATE, the column length in bytes is not applicable because the column type has a fixed length.
- Database
- External Table
  - Iceberg Table
- Function

  Note: Objects of the Function type appear as Stored Procedure in Data Governance and Catalog.
- Materialized View

  Note: Objects of the Materialized View type appear as View in Data Governance and Catalog.
- Pipe
- Schema
- Semantic View
- Stage
- Stored Procedure

Note: To extract Data Definition Language (DDL) statements from a stored procedure, you need owner privileges on the stored procedure. Alternatively, you can re-create the stored procedure with the `EXECUTE AS CALLER` clause.

Note: You can extract lineage from procedures and functions in the JavaScript language.

- Table
- Tag
- View

You can extract metadata from stored procedures that use the following languages:

- JavaScript
- Snowflake SQL scripting
- Snowpark Python

Note: Effective in the 2024.11.S release, extracting metadata from stored procedures that use Snowpark Python is available for preview.

Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

Secure Data Sharing in Snowflake allows you to share selected database assets with other Snowflake accounts without copying or transferring any actual data. To share data, providers create a share of their database, select specific objects to include, and then add consumer accounts to this share.

You can extract metadata from the following database assets shared through Snowflake Secure Data Sharing:

- Database
- Table
- External table
- Secure view
- Secure materialized view

To view the complete data lineage and all the metadata extracted for the consumer account, including shared assets, perform a connection assignment between catalog sources created for the provider and consumer Snowflake accounts.

Data profiling for Snowflake objects

Configure data profiling to run profiles on the metadata extracted from a Snowflake source system. You can run data profiles on the following Snowflake objects:

- Table
- View

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types for Snowflake objects:

- NUMBER
- FLOAT
- DOUBLE

- VARCHAR
- BOOLEAN
- DATE
- TIME
- TIMESTAMP_LTZ
- TIMESTAMP_NTZ
- TIMESTAMP_TZ
- OBJECT
- ARRAY
- VARIANT

Sampling type

Determine the sample rows on which you want to run the data profiling task. You can choose one of the following sampling types for a Snowflake catalog source:

- All Rows
- Limit N Rows
- Custom Query

Data classification for Snowflake objects

You can run the data classification capability on Snowflake catalog sources to identify and organize data into relevant categories. For more information about data classification, see the *Administration* help.

Data lineage

The following lineage data is available for Snowflake assets:

- From table to view
- Stored Procedures linked to tables or views
- Functions linked to tables or views
- Procedure calling a procedure
- Procedure calling a function
- Pipe linked to stages
- Pipe linked to table or views

For more information about data lineage, see the *Asset Discovery* help.

Snowflake SQL Script

{Varref: Snowflake SQL Script}Snowflake SQL Script
is a set of Snowflake SQL statements stored in files that you can use for sequential execution.

Objects extracted

Metadata Command Center extracts the following metadata from the Snowflake SQL Script source system:

- Calculation

- Folder
- Script
- Statements

Data lineage

The following lineage data is available for Statements and Calculation assets:

- Data set level
- Data element level

Note: You cannot drill down to view the data element level lineage for the Statement assets. Select a data element and open the **Lineage** tab to view the data element level lineage.

For more information about data lineage, see the *Asset Discovery* help.

Tableau

Tableau is a business intelligence tool that connects to data and create dashboards that can be shared.

Objects extracted

Metadata Command Center extracts the following objects from a Tableau source system:

- Calculation
- Dashboard
- Data Source
  - Data Source Table
  - Custom SQL Query
  - Data Source Stored Procedure
- Project
- Published Data Source
  - Data Source Table
  - Custom SQL Query
  - Data Source Stored Procedure
- Server
- Site
- Stored Procedure
- Tags
- Workbook
- Worksheet
  - Dimension
  - Measure Names

    Note: Objects of the measure name type appear as calculations nested under worksheets in Data Governance and Catalog.

Data lineage

Lineage data is available for Tableau assets that connect to the following source systems:

- Amazon S3
- Microsoft Azure Data Lake Storage Gen2
- Microsoft Azure SQL Server
- Oracle
- Snowflake
- IBM Netezza using JDBC
- Microsoft SQL Server
- IBM DB2
- Teradata Database
- Amazon Redshift
- Snowflake
- Apache Hive
- Google BigQuery

The following lineage data is available for Data Source and Worksheet assets:

- Data set level
- Data element level

The data set level lineage is available for Dashboard asset and data element level lineage is available for data element level.

For more information about data lineage, see the *Asset Discovery* help.

TIBCO Spotfire

TIBCO Spotfire is a business intelligence tool that you can use to explore data through dashboards and advanced analytics.

Objects extracted

Metadata Command Center extracts the following metadata from the TIBCO Spotfire source system:

- AnalysisDocument
- Annotation
- Column
- ColumnMatch
- ConnectionClassifier
- ConnectionDataSource
- ConnectionFeature
- CustomQuery
- DataColumn

- DataFunction
- DataProducer
- DataTable
- DataTransformation
- Database
- Document
- DocumentProperty
- ESRIShapeFile
- ExcelWorkbook
- ExcelWorksheet
- Expression
- Field
- File
- Filter
- Folder
- InformationLink
- LocalConnection
- Parameter
- Property
- Relation
- Report
- ResultAttribute
- SBDFFile
- STDFFile
- Schema
- Server
- StoredProcedure
- Table
- TextFile
- View

Data lineage

Data lineage is available for the following TIBCO Spotfire assets:

- Column
- Data Column
- Data Producer
- Data Table
- Field
- Report
- Schema

- Table
- View

For more information about data lineage, see the *Asset Discovery* help.

Talend Data Integration

Talend Data Integration is an ETL data integration platform that you can use to gain business insights from data.

Objects extracted

Metadata Command Center extracts the following metadata from the source system:

- Project
- Folder
- Job
- Subjob
- Calculation

Metadata Command Center extracts the following metadata if the source system uses stored procedures for connection-aware scans:

- Project
- Folder
- Job
- Subjob
- Calculation
- Database
- Procedure Definition
- Procedure Instance
- Parameter
- Parameter Container
- Schema
- Statement

Data lineage

The following lineage data is available for Calculation and Subjob assets:

- Data set level
- Data element level

For more information about data lineage, see the *Asset Discovery* help.

Teradata BTEQ Script

Teradata BTEQ Script is a set of commands and Teradata SQL statements stored in files that you can use to run sequential scripts.

Objects extracted

Metadata Command Center extracts the following metadata from the Teradata database source system:

- Calculation
- Folder
- Script
- Statements

Data lineage

The following lineage data is available for Statements and Calculation assets:

- Data set level
- Data element level

Note: You cannot drill down to view the data element level lineage for the Statement assets. Select a data element and open the **Lineage** tab to view the data element level lineage.

For more information about data lineage, see the *Asset Discovery* help.

Workday

Workday is a cloud-based financial management, enterprise resource planning, and human capital management platform.

Extracted objects

Metadata Command Center extracts the following metadata from a Workday source system:

- Business Object
- Data Source
- Operation
- Operation Entity
- Operation Entity Property
- Report
- Report Entity
- Report Entity Property
- Report Property
- Service

Data lineage

The following lineage data is available for Workday assets at the data set level:

- From Business Object to Data Source

- From Data Source to Report

For more information about data lineage, see the *Asset Discovery* help.

INDEX

A

Amazon Athena 6
Amazon Redshift 8
Amazon S3 9
asset types
  Amazon Athena 6
  Amazon Redshift 8
  Amazon S3 9
  Databricks Notebook 16
  File System 20
  Google BigQuery 22
  IBM DB2 24
  Informatica PowerCenter 27
  JDBC 28
  Microsoft Azure Data Lake Storage Gen2 29
  Microsoft Azure SQL Server 32
  Microsoft Azure Synapse 33
  Microsoft SQL Server 36
  Microsoft SQL Server Integration Services 38
  Microsoft SQL Server Reporting Services 39
  MySQL 42
  Oracle 43
  Oracle Business Intelligence 45
  PostgreSQL 48
  Qlik Sense 49
  Qlik Sense Cloud 50
  QlikView 51
  SAP BusinessObjects 52
  SAP HANA 55
  Snowflake 57
  Tableau 60
  TIBCO Spotfire 61

D

Databricks Notebook 16

F

File System 20

G

Google BigQuery 22

I

IBM DB2 24
Informatica PowerCenter 27

J

JDBC 28

M

Microsoft Azure Data Lake Storage Gen2 29
Microsoft Azure SQL Server 32
Microsoft Azure Synapse 33
Microsoft SQL Server 36
Microsoft SQL Server Integration Services 38
Microsoft SQL Server Reporting Services 39
MySQL 42

O

Oracle 43
Oracle Business Intelligence 45

P

PostgreSQL 48

Q

Qlik Sense 49
Qlik Sense Cloud 50
QlikView 51

S

SAP BusinessObjects 52
SAP HANA 55
Snowflake 57

T

Tableau 60
technical asset types
  Amazon Athena 6
  Amazon Redshift 8
  Amazon S3 9
  Databricks Notebook 16
  File System 20
  Google BigQuery 22
  IBM DB2 24
  Informatica PowerCenter 27
  JDBC 28
  Microsoft Azure Data Lake Storage Gen2 29
  Microsoft Azure SQL Server 32

technical asset types *(continued)*
Microsoft Azure Synapse 33
Microsoft SQL Server 36
Microsoft SQL Server Integration Services 38
Microsoft SQL Server Reporting Services 39
MySQL 42
Oracle 43
Oracle Business Intelligence 45
PostgreSQL 48
Qlik Sense 49
technical asset types *(continued)*
Qlik Sense Cloud 50
QlikView 51
SAP BusinessObjects 52
SAP HANA 55
Snowflake 57
Tableau 60
TIBCO Spotfire 61
TIBCO Spotfire 61