Informatica® Metadata Command Center
October 2026

SFTP File System Sources

Informatica Metadata Command Center SFTP File System Sources
October 2026

© Copyright Informatica LLC 2022, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-11-02

Table of Contents

Preface 5

Chapter 1: Introduction to SFTP File System catalog sources 6

Extraction and view process 6

About the SFTP File System catalog source 7

Extracted metadata 7

Compatible connectors 9

Chapter 2: Before you begin 10

Verify permissions 10

Permissions to extract metadata 10

Permissions to run data classification 10

Permissions to run glossary association 10

Create a connection 11

Configure runtime environment for document classification 12

Enable document classification 13

Chapter 3: Create catalog sources in Metadata Command Center 14

Step 1. Register a catalog source 14

Step 2. Configure capabilities 16

Configure metadata extraction 16

Filter guidelines and examples 20

Configure data classification 22

Configure glossary association 23

Configure automation 24

Step 3. Associate stakeholders and asset groups 25

Step 4. Run or schedule the job 27

Step 5. Assign reference catalog source connections to endpoint catalog source objects 28

Chapter 4: View results in Data Governance and Catalog 30

View metadata extraction results 30

View data lineage 32

View lineage at the catalog source level 32

View lineage at the data set level 32

View lineage at the data element level 33

View classified data 34

View glossary associations 34

Appendix A: Managing catalog sources 36

Cloning a catalog source configuration 36

Deleting or purging a catalog source. 37
Purging obsolete objects from a catalog source. 37
Curating CLAIRE recommendations. 38
Managing configuration permissions for catalog sources. 38

Preface

Read *SFTP File System Sources* to learn how to register and configure SFTP File System sources as catalog sources in Metadata Command Center. After you configure a catalog source, you extract metadata and then view the results in Data Governance and Catalog.

CHAPTER 1

Introduction to SFTP File System catalog sources

You can use Metadata Command Center to extract metadata from a source system.

A source system is any system that contains data or metadata. For example, SFTP File System is a source from which you can extract metadata through an SFTP File System catalog source with Metadata Command Center. A catalog source is an object that represents and contains metadata from the source system.

Before you extract metadata from a source system, you first create and register a catalog source that represents the source system. Then you configure capabilities for the catalog source. A capability is a task that Metadata Command Center can perform, such as metadata extraction, lineage discovery, autonomous enrichment, data profiling, data classification, or glossary association.

When Metadata Command Center extracts metadata, Data Governance and Catalog displays the extracted metadata and its attributes as technical assets. You can then perform tasks such as analyzing the assets, viewing lineage, and creating links between those assets and their business context.


The following table describes the capabilities of the catalog source:

Capability	Description
Data Classification	Data classification is the process of identifying and organizing data into relevant categories based on the functional meaning of the data. Classifying data can help your organization manage risks, compliance, and data security.
Glossary Association	You can associate terms that are in the glossary with technical assets to provide user-friendly business names to technical assets. Glossary Association automatically associates glossary terms with technical assets or recommends glossary terms that you can manually associate with technical assets in Data Governance and Catalog.
Autonomous Enrichment	Automatically propagates classification, description, business name, and glossary enrichments from an asset to related assets based on the lineage between assets. Autonomous enrichment reduces manual curation effort by extending the enrichments that you apply to one asset across assets that are connected to it through lineage.

Extraction and view process

To extract metadata from a source system, configure the catalog source and run the extraction job in Metadata Command Center. Then view the results in Data Governance and Catalog.

The following image shows the process to extract metadata from a source system:



After you verify prerequisites, perform the following tasks to extract metadata from SFTP File System:

1. Register a catalog source. Create a catalog source object, select SFTP File System, and then select and test the connection.
2. Configure the catalog source. Specify the runtime environment and configure parameters for metadata extraction. Optionally, add filters to include or exclude source system assets from metadata extraction. You can also configure other capabilities such as lineage discovery, autonomous enrichment, data profiling and quality, data classification, or glossary association.
3. Optionally, associate stakeholders. Associate users with technical assets, giving the users permission to perform actions determined by their roles.
4. Run or schedule the catalog source job.
5. Optionally, if the catalog source job generates referenced asset objects, you can assign a connection to referenced source system assets.
   You can view the lineage with object references without performing connection assignment. After connection assignment, you can view the objects.

After you run the catalog source job, you view the results in Data Governance and Catalog.

About the SFTP File System catalog source

You can use the SFTP File System catalog source to extract metadata from the SFTP File System source.

SFTP is a secure file transfer protocol that enables you to transfer files over SSH, also known as Secure Shell protocol.

Extracted metadata

You can extract specific metadata from an SFTP File System with an SFTP File System catalog source.

Metadata Command Center extracts metadata from the following objects:

- File Systems
- Flat Fields
- Flat Files

- Folders from an SFTP File System source

Supported file types

You can extract metadata from the following file types:

- Attribute
- AVRO
- CSV
- E-mail files
  - EML
  - EMLX
  - MSG
- Element
- JSON
- JSONL
- Markdown
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- Parquet files based on the partition structure
- PDF
- Presentation files
  - PPT
  - PPTX
- Rich Text Format (RTF)
- TSV
- TXT
- XML File
- XSD File

Note: Catalog source jobs can extract metadata from protected unstructured files. However, some metadata attributes of such files might not get extracted or displayed in Data Governance and Catalog.

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
AVRO	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge

File Type	Partition structure
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

You can extract workbooks, worksheets, and columns from Microsoft Excel files.

You can extract metadata from XML and XSD file formats as XML file objects. Metadata Command Center extracts only elements and attributes from XML and XSD files. If the size of the XML file exceeds 100 KB, Metadata Command Center extracts metadata from the initial 100 KB of the file. However, for XSD file types, Metadata Command Center extracts complete metadata.

Compatible connectors

Before you configure a catalog source, you must connect to the SFTP File System source system.

Use the Advanced SFTP V2 connector to connect to the SFTP File System source system.

For information about configuring a connection, see *Connections* in the Administrator help.

CHAPTER 2

Before you begin

Before you can extract catalog source metadata, get information from the SFTP File System administrator.

Ensure that the following prerequisites are met:

- Configure SFTP on the Windows or Linux machine from which you want to extract metadata.
- Verify permissions.
- Create a connection.

Verify permissions

To extract metadata and to configure other capabilities that a catalog source might include, you need account access and permissions on the source system. The permissions required might vary depending on the capability.

Permissions to extract metadata

To extract SFTP File System metadata, you need account access to the SFTP File System source.

Verify that the administrator performs the following tasks:

- Creates a user account to access the source system.
- Grants read permissions to the directory on the Windows or Linux machine from which you want to extract metadata.

Permissions to run data classification

You can perform data classification with the permissions required on the source system to perform metadata extraction.

Permissions to run glossary association

You can perform glossary association with the permissions required on the source system to perform metadata extraction.

Create a connection

Before you configure the SFTP File System catalog source, create an Advanced SFTP V2 connection object in Administrator.

If you want to test the connection before you save it, verify that Mass Ingestion is running on the Secure Agent.

1. In Administrator, select **Connections**.
2. Click **Add Connection**.
3. Search for and select **Advanced SFTP V2** and then click **Next**.
4. Enter the following connection details:

Property	Description
Connection Name	The name of the connection. The name is not case sensitive and must be unique within the domain. You can change this property after you create the connection. The name cannot exceed 128 characters, contain spaces, or contain the following special characters:~ ` ! $ % ^ & * ( ) - + = { [}] | \ : ; " ' < , > . ? /
Description	Optional. The description of the connection. The description cannot exceed 4,000 characters.
Runtime Environment	The name of the runtime environment that contains the Secure Agent that you want to run the tasks.
Host	The host name or IP address of the server. The host name is case insensitive and must be unique within the domain. The name cannot exceed 24 characters. It can contain letters (A to Z), digits (0 to 9), period (.) special character, and minus (-) sign.
Port	The port number to use to connect to the server. Default is 22.
Username	User name to connect to the SFTP server.
Password	Password to connect to the SFTP server.
Folder Path	The directory to use after connecting to the server.
Private Key File	The name of the SSH private key file along with the path where the file is stored. Ensure that the file path is on the machine that hosts the Secure Agent. For example, `C:/SSH/my_keys/key.ppk`
Private Key Passphrase	Specify the passphrase to encrypt the SSH private key.

5. Click **Test** to test your connection to the source system.
6. Click **Save**.

Configure runtime environment for document classification

To enable the document classification capability for the catalog source, you must configure an elastic runtime environment and configure at least one GPU node on the runtime environment.

A GPU node is a prerequisite to train the classification engine and run the document classification capability. For better performance during classification training and inference, you can install more than one GPU node.

1. Configure an elastic runtime environment in Administrator.

   For information about how to configure and use the elastic runtime environment, see *Elastic Runtime Environments* in the Administrator help.

2. Download the `gpu_setup.zip` file.

   The ZIP file is available in the following location:

   ```
   <Informatica Secure Agent installation directory>/downloads/package-
   MetadataPlatformService.<version>/package/scripts/gpu_setup.zip
   ```

3. Extract the ZIP file on the master node of your elastic runtime environment installation.

   Run the following command:

   ```
   unzip gpu_setup.zip -d gpu_setup && cd gpu_setup
   ```

4. From the extracted folder, open the `gpu_node.txt` file and configure the following key-value pairs:

Key	Value
JOB_NODE_ASG_NAME	Name of the existing job-node Auto Scaling Group for your elastic runtime environment cluster.
SSH_KEY_PATH	The absolute path to the PEM key that was generated during the elastic runtime cluster installation.
SSH_USER	The SSH user name for connecting to the cluster nodes. Default is cloud-user.
GPU_WORKER_INSTANCE_TYPE	The EC2 instance type for GPU nodes. Default is g5.xlarge. The minimum requirement is g4dn.xlarge.

5. Run the preflight check.

   Use the following command:

   ```
   ./gpu-setup-preflight.sh
   ```

   Ensure that there are no failures in the summary. Review the warnings.

6. Run the installer to install the GPU node on the runtime environment.

   Use the following command:

   ```
   ./gpu-setup-master-multi.sh
   ```

   Optionally, add the `--count=N` parameter where `N` indicates the desired number of GPU nodes to provision.

After you configure an elastic runtime environment with GPU nodes, select this runtime environment to run the classification engine training jobs in Metadata Command Center. For more information, see "Enable document classification" on page 13.

Enable document classification

After configuring an elastic runtime environment in Administrator, you must enable document classification and select the runtime environment to run the document classification training jobs in Metadata Command Center.

To enable document classification in your organization, perform the following steps:

1. In Metadata Command Center, go to the **Configure** page.
2. Click the **Document Classification** tab.
3. Select **Enable Document Classification**.
4. Select the elastic runtime environment that you configured with GPU nodes in Administrator.
5. Click **Save**.

You can now enable the document classification capability for the catalog source to automatically identify and classify unstructured documents, such as PDFs and text files.

CHAPTER 3

Create catalog sources in Metadata Command Center

Use Metadata Command Center to configure a catalog source for SFTP File System and run the catalog source job.

When you configure a catalog source, you define the source system that you want to extract metadata from. Configure filters to include or exclude source system metadata before you run the job. Optionally, configure other capabilities, such as lineage discovery, autonomous enrichment, data profiling and quality, data classification, relationship discovery, and glossary association.

To provide stakeholders access to technical assets, you can assign access through stakeholder roles. You can also associate technical assets extracted from the catalog source to asset groups. If your catalog source references other source systems, you can create a connection assignment to the endpoint catalog source to view complete lineage.

Step 1. Register a catalog source


When you register a catalog source, provide general information and connection values.

Verify that Mass Ingestion is running on the Secure Agent before you test the connection.

1. Log in to Intelligent Data Management Cloud.


   The **My Services** page appears.
2. Click **Metadata Command Center**.

   The **Metadata Command Center** box appears on the **My Services** page.



The Metadata Command Center home page appears.

3. Click **New**.
4. Select **Catalog Source** from the list of asset types.
5. Select SFTP File System from the list of source systems.



6. Click **Create**.

   The **New Catalog Source** page opens.

7. In the **General Information** section, enter a name and an optional description for the catalog source.

   Note: You can rename a catalog source after you create it, but to apply the change to all associated objects you must rerun the metadata extraction job.

   After you save the catalog source, you can update the description in Metadata Command Center and Data Governance and Catalog. The update appears only in the service in which you update it.

8. In the **Connection Information** area, select the connection that you created in Administrator.

Note: To create or edit a catalog source, you need permissions on the connection to the source system. Select a connection that you have access to, or ask the administrator to grant the necessary permissions to the connection that you want to use.

9. Click **Connection Properties** to expand and view the connection properties for the selected connection.
10. Click **Test Connection** to test your connection to the source system.
11. Click **Next**.

The **Configuration** page appears.

Step 2. Configure capabilities

When you configure the SFTP File System catalog source, you define the settings for the metadata extraction capability and other optional capabilities.

The metadata extraction capability extracts source metadata from external source systems. You can also configure other capabilities that the catalog source includes.

You can save the catalog source configuration at any point after you enter the connection information. After you save the catalog source, you can choose to run the catalog source job. To run the job once, click **Run**. To run metadata extraction and other capabilities on a recurring schedule, configure schedules on the **Schedule** tab.

Configure metadata extraction

When you configure the SFTP File System catalog source, you choose a runtime environment, define filters, and enter configuration parameters for metadata extraction.


1. In the **Connection and Runtime** area, choose a serverless runtime environment or the Secure Agent group where you want to run catalog source jobs.

   Note: Serverless runtime environment options are available if the catalog source works with a serverless runtime environment.
2. Choose to retain, delete, or deprecate objects that are deleted from the source system in the catalog with the **Metadata Change Option**.
   - **Retain**. Retains objects that are deleted from the source system in the catalog. If you update or add a filter, the catalog retains objects extracted from the previous job and extracts additional objects that match the current filter. Objects deleted from the source system are not deleted from the catalog. Enrichments added on deleted objects and relationships are retained.
   - **Delete**. Deletes metadata from the catalog based on objects deleted from the source system and changes you make to the filter. Enrichments added on deleted objects and relationships are also permanently lost. Objects renamed in the source system are removed and recreated in the catalog.

- **Deprecate**. When objects are deleted from the source system, the catalog changes the lifecycle of the imported objects to Obsolete. The lifecycle of objects also changes to Obsolete when you add exclusion filters or reduce the scope so that objects extracted in earlier jobs are no longer included. For example, the first job includes the sales schema. The second job also includes the sales schema, but excludes the sales.transactions table. In this case, the second job marks the sales.transactions object as Obsolete, even though the first job includes it. This does not impact enrichments applied to deprecated objects and relationships. Objects renamed in the source system are removed and recreated in the catalog. When you run the catalog source job again for other capabilities such as data classification, relationship discovery, or glossary association, the job doesn't consider obsolete objects. Obsolete objects remain in the catalog until they are purged when you run a **Purge Obsolete Objects** job on the **Explore** page.

Note: You can also change the configured metadata change option when you run a catalog source.

3. In the **Filters** area, define one or more filter conditions to apply for metadata extraction:
   a. Select **Yes** to view filter options.
   b. From the Include/Exclude list, choose to include or exclude metadata based on the filter parameters.
   c. From the Object type list, select an object type, depending on the object that you want to extract metadata from.
   d. Enter the path to the object as the filter value.



   e. To define an additional filter with an OR condition, click the **Add** icon.
4. In the **Configuration Parameters** area, enter the configuration parameters.

The following table describes the properties that you can enter in the **Catalog Source Configuration Options** section:

Property	Description
Extract Group Elements from Hierarchical Files	Select one of the following options to extract group or leaf elements from hierarchical files: - Yes. Extracts group elements from hierarchical files with the complete hierarchy of hierarchical fields. You can view the hierarchy of hierarchical files in the **Hierarchy** tab of assets in Data Governance and Catalog. - No. Extracts only leaf elements from hierarchical files without the complete hierarchy of hierarchical fields. You can extract group elements from hierarchical files for the following file types: - AVRO. Extracts and groups hierarchical files and hierarchical fields. - Parquet. Extracts and groups hierarchical files and hierarchical fields. - JSON. Extracts and groups hierarchical files and hierarchical fields. - XML. Extracts and groups elements and attributes. For XML file types, a maximum depth of 1000 elements is permitted within a single element in the hierarchy. - XSD. Extracts and groups elements and attributes. **Attention:** If you modify the **Extract Group Elements from Hierarchical Files** field and run the catalog source again, the asset page doesn't display the hierarchical elements in the correct hierarchy groups. If you modify the property value, purge the catalog source before you run it again.
Enable Extension-Based File Type Detection	Select one of the following options to detect file types by file extensions or by parsing the file contents: - Yes. Detects file types by file extensions. - No. Parses the file contents to detect file types. **Note:** You can detect file types by file extensions for the following file types: - CSV - TSV - TXT - XML
Use First Row as Header of Delimited Files	Select one of the following options to use the first row as the header or detect headers automatically for delimited files: - Yes. Detects column headers based on the following rules: - Duplicate headers get suffixed with '#' followed by a number, for example, ABC#1, ABC#2. The detection is not case-sensitive. - Empty column header values appear as UnknownColumn<position>, for example UnknownColumn2. - The header row in the file is detected even if it has a different number of columns than the data rows. - No. Detects headers automatically for delimited files.
Headers of Delimited Files	Specify values to determine headers of delimited files. Separate multiple values by commas. If any value from the list is found in the first row of the delimited file, then the first row is used as the header. **Note:** This parameter appears only if you choose No for the **Use First Row as Header of Delimited Files** parameter.

Property	Description
Treat Files Without Extension As	The default file extension to identify files without an extension. Select one of the following options: - Parquet - Avro - JSON
Enter File Delimiter	Specify the file delimiter if the file from which you extract metadata uses a delimiter other than the following list of delimiters: - Comma (,) - Horizontal tab (\t) - Semicolon (;) - Colon (:) - Pipe symbol (|) Enclose the delimiter in single quotes. For example, enter '$'. Use a comma to separate multiple delimiters. **Note:** Adding a custom delimiter overrides the default list of delimiters. If you specify a delimiter, characters from the default list are not considered as delimiters.
Files to be excluded during partition discovery	Specify the regular expression of the files that you want to exclude during partition discovery. Enclose each regular expression in double quotes. For example, enter ".*json","Customer.csv","Parquet.*". Use a comma to separate multiple regular expressions.
Treat Unrecognized Files As	Choose how to handle files with unrecognized formats during metadata extraction. Select one of the following options: - Structured files. Treats all files with unrecognized formats as structured files. - Unstructured files. Treats all files with unrecognized formats as unstructured files.
Unrecognized Files Override	Enter one or more file paths as exceptions to override whether the specific unrecognized files should be treated as structured or unstructured files. You can use the path-based overrides to apply different treatment rules to different files within the same catalog source.

The following table describes the properties that you can enter in the **Partitioned File Configuration** section:

Property	Description

Custom Partition Detection Configuration File	The configuration file in JSON format to detect custom partitions in the source system. The configuration file defines the pattern of the non-Hive style custom partitions.
	Note: The system automatically detects partitions if the date format of the partition key is in any of the following formats:
	- dd-MM-yy
	- dd-MM-yyyy
	- dd-MMM-yyyy
	For example, the system interprets dd-MM-yyyy as the partition format and extracts `Customer` as a hierarchical file instead of a folder in the following partition pattern:
	`Customer`
	`|__01-01-2022`
	`|  |  |__ dataFile1.parquet`
	`|  |  |__ dataFile2.parquet`
	`|  |  |__ ...`
	`|__02-02-2022`
	`|__...`
	The system doesn't automatically detect partitions with other patterns, such as MM-dd-yyyy. If the pattern is different, you need to define it in JSON format. For example, `{"CustomPartitionPatterns": ["MM-dd-yyyy"]}`
	To detect the epoch time format, define it in JSON format as: `{"CustomPartitionPatterns": ["@"]}`

Partitioned Pruning Configuration Options	The configuration file in JSON format for partition pruning that contains additional information to identify partitions and determine the relevant schema in the source system.
Partition Detection	Specify if you want to enable partition detection.
Partition Pruning	Applicable if you enable partition detection. Specify if you want to enable partition pruning. Default is Yes.

5. Configure additional capabilities for the catalog source by clicking on the tabs.

Filter guidelines and examples

You can add metadata extraction filters when you configure the catalog source. To create a filter, you can use choose from file names, folder names, or paths.

Consider the following rules and guidelines when you enter filter values:

- Filters are case-sensitive.
- Use an asterisk to represent multiple characters in a folder name, file name, and a single folder level in a folder hierarchy. For example, A* matches A, Ab, ABC.
- For file filters, specify only the file name.
- If a file name contains an asterisk, the filter considers it as a wildcard and not a special character. To ignore an asterisk as a wildcard, enclose it in double quotes (“) in the filter.
- Use a forward slash as a separator in path hierarchies. You can add a path in folder and path filters.

- Use an asterisk as a path placeholder in folder and path filters. For example, folder1/*/folder3. Here, the filter includes all folders under folder1.
- Use two asterisks to indicate zero or more levels of folders in folder and path filters. The pattern with two asterisks is recursive. The processing time is longer as the data volume increases.

Important: It is recommended that you either use only a path filter or use a combination of a folder and a file filter.

Examples

You can include or exclude metadata from folders, files, or paths.

Folder filters

Folder filters apply to folders included in the source system.

For example:

- To include or exclude metadata from 'Folder2' located inside 'Folder1', select **Folder** as the object type and enter `Folder1/Folder2` in the value field.
- To include or exclude metadata from 'Folder2' located in any folder under 'Folder1', select **Folder** as the object type and enter `Folder1/*/Folder2` in the value field.
- To include or exclude metadata from 'Folder2' located two levels under 'Folder1', select **Folder** as the object type and enter `Folder1/*/*/Folder2` in the value field.
- To include or exclude metadata from 'Folder2' located at any level under 'Folder1', select **Folder** as the object type and enter `Folder1/**/Folder2` in the value field. This is a recursive search, and therefore the processing time can be longer.

File filters

File filters apply to the files included in folders that you filter. The file filter is recursive. If you don't provide any folder filters, the file filters apply to the entire folder hierarchy.

For example:

- To include or exclude metadata from all files with the name 'File1.csv' located in the source directory, select **File** as the object type and enter `File1.csv` in the value field. Metadata Command Center recursively searches for files that match the filter criteria in all folders in the source directory.
- To include or exclude metadata from all files with names that start with 'File' and end with 'ame.csv', select **File** as the object type and enter `File*ame.csv` in the value field.
- To include or exclude metadata from all files with names that end with 'File.csv', select **File** as the object type and enter `*File.csv` in the value field.
- To include or exclude metadata from all files with the name 'File' and files that start with the name 'File' followed by one or more characters, select **File** as the object type and enter `File*` in the value field.
- To include or exclude metadata from all files with names that contain the word 'File', select **File** as the object type and enter `*File*` in the value field.
- To include or exclude metadata from all files with the name 'Fi*le.csv', select **File** as the object type and enter `Fi"*"le.csv` in the value field.

Path filters

Path filters apply to the files and folders in the path that you filter. The path filter is non-recursive. If you provide only the file or folder names, the path filters apply to the first level files or directories.

For example:

- To include or exclude metadata from files and folders with names that start with 'Item1' in the first level directory, select **Path** as the object type and enter `Item1*` in the value field.
- To include or exclude metadata from the 'File1' file in the 'Folder1' folder, select **Path** as the object type and enter `Folder1/File1` in the value field.
- To include or exclude metadata from files or folders with names that contain the word ‘Subfolder’ in the ‘Folder1’ folder, select **Path** as the object type and enter `Folder1/*Subfolder*` in the value field.
- To include or exclude metadata from files or folders with the name 'File1' in any subfolder of the 'Folder1' folder, select **Path** as the object type and enter `Folder1/*/File1` in the value field.
- To include or exclude metadata from all files and subfolders in the 'Folder1' folder, select **Path** as the object type and enter `Folder1/*` in the value field.
- To include or exclude metadata from files or folders with the name ‘File1’ located at any level in the ‘Folder1’ folder, select **Path** as the object type and enter `Folder1/**/File1` in the value field. This is a recursive search, and therefore the processing time can be longer.


Configure data classification

Enable the data classification capability to identify and organize data into relevant categories based on the functional meaning of the data.

Before you enable document classification for the catalog source, perform the following tasks:


- Configure an elastic runtime environment with GPU nodes. For more information, see “Configure runtime environment for document classification” on page 12.
- Select the runtime environment to run the document classification training jobs. For more information, see “Enable document classification” on page 13.

1. Click the **Data Classification** tab.
2. Select **Enable Data Classification**.
3. Choose one or both of the following options:
   - **Generated Data Classifications**. CLAIRE automatically generates data classifications for the data elements.
   - **Data Classification Rules**. Choose from predefined or custom data classifications.
     1. Click **Add Data Classification**. The **Select Data Classifications** dialog box appears.



2. Select the data classifications that you want to use.
3. Click **OK**.

4. Optionally, select **Enable Document Classification** to automatically identify and classify unstructured documents, such as PDFs and text files, for enhanced search and discovery.
   a. Click **Select Document Classifications**. The **Document Classifications** dialog box appears.



   b. Choose one or more document classifications that you created for your organization.
   c. Click **OK**.

Configure glossary association

Enable the glossary association capability to associate glossary terms with technical assets, or to get recommendations for glossary terms that you can manually associate with technical assets in Data Governance and Catalog.

Metadata Command Center considers all published business terms in the glossary while making recommendations to associate your technical assets.

1. Click the **Glossary Association** tab.
2. Select **Enable Glossary Association**.
3. Select **Enable auto-acceptance** to automatically accept glossary association recommendations.
4. Specify the **Confidence Score Threshold for Auto-Acceptance** to set a threshold limit based on which the glossary association capability automatically accepts the recommended glossary terms.

   Note: Specify a percentage from 80 to 100. If the score is higher than the specified limit, the glossary association capability automatically assigns a matching glossary term to the data element.
5. Select **Enable Below-threshold Recommendations** to receive glossary association recommendations below the auto-acceptance threshold. If you enable auto-acceptance, you can enable below-threshold recommendations to receive glossary recommendations below the auto-acceptance threshold.
6. Specify the **Confidence Score Threshold for Recommendations** to set a threshold based on which the glossary association capability makes recommendations

If you enable auto-acceptance, specify a percentage from 80 to the selected auto-acceptance threshold. You can accept or reject the recommended glossary terms that fall within this range in Data Governance and Catalog.

If you disable auto-acceptance, specify a percentage from 80 to 100 inclusive.

7. Choose to automatically assign business names and descriptions to technical assets. You can then choose to retain existing assignments and only assign business names and descriptions to assets that don't have assignments, or allow overwrite of existing assignments.

   By default, existing assignments are retained.

8. Optional. Choose to ignore specific parts of data elements when making recommendations. Select **Yes** and enter prefix and suffix keyword values as needed.

   Click **Select** to enter a keyword. You can enter multiple unique prefix and suffix keywords. Keyword values are case insensitive.

9. Optional. Choose specific top-level business glossary assets to associate with technical assets. Selecting a top-level asset selects its child assets as well. Select **Top-level Glossary Assets** and specify the assets on the **Select Assets** page.

10. Optional. Choose to use abbreviations and synonym definitions from lookup tables for accurate glossary association. Select **Yes** to enable, and then click **Select** to upload a lookup table.

11. Click **Next**.

    The **Associations** page appears.

Configure automation

Enable lineage-based propagation to receive enrichments propagated from catalog sources connected through lineage.

Enable Lineage-based Propagation on the Autonomous Enrichment tab of the Configure page before you configure this catalog source to receive enrichments. For more information, see *Administration*.

With the lineage-based propagation settings on this tab, you configure how this catalog source receives enrichments propagated from connected catalog sources. Enrichments propagate only to assets that don't already have enrichments.

1. Click the **Automation** tab.
2. In the **Autonomous Enrichment** section, select **Enable Lineage-based Propagation**.

   The lineage-based propagation settings appear.

3. Select the enrichment types to receive from connected catalog sources.

   You can select Classification, Description, Business Name, and Glossary Term.

4. Choose how to apply received enrichments.
   - Select **Auto-accepted** to apply received enrichments automatically.
   - Select **Recommended** to list them as suggestions that you can curate in Data Governance and Catalog.
5. Choose whether to receive enrichments only from certified assets.

   Assets are certified in Data Governance and Catalog. This option is selected by default. If you clear it, this catalog source also receives enrichments from assets that are not certified, which might be less reliable.

6. Choose where this catalog source receives enrichments from.

- Select **Catalog Source** to receive enrichments from a specific catalog source.
- Select **Nearest Neighbor** to receive enrichments from the closest connected catalog source based on lineage.

7. If you select **Catalog Source**, select a catalog source from the list.

   Ensure that the catalog source you select is within 15 lineage hops. Enrichments don't propagate from a catalog source beyond that distance.

8. If you select **Nearest Neighbor**, configure the lineage settings:

   a. Set **Lineage Direction** to search upstream, downstream, or in both directions.

      Upstream catalog sources feed data into this catalog source. Downstream catalog sources receive data from this catalog source. Select both directions to search upstream and downstream at the same time.

   b. Set **Number of Hops** to define how far along lineage to search.

      The search stops at the first connected catalog source that has enrichments, up to a maximum of 15 hops.

9. Click **Save**.

When you save, the catalog source begins receiving enrichments created from that point onward. Saving doesn't retrieve enrichments created prior to this date and time. To receive such enrichments, run the catalog source job manually and include the Autonomous Enrichment capability.

Step 3. Associate stakeholders and asset groups

Associate users or user groups within a stakeholder role as stakeholders for technical assets in Data Governance and Catalog. Also, you can choose to assign technical assets extracted from the catalog source to asset groups. You can then use access policies to control permissions on assets that are assigned to asset groups.

Verify that the administrator assigned users and user groups to the stakeholder role that you want to associate with technical assets.

1. To associate users or user groups as stakeholders with technical assets extracted from the catalog source, perform the following steps:

   a. On the **Associations** page, click **Stakeholders**.

   b. Select **Assign Stakeholders**.

   c. Select **Propagate to Child Assets** to propagate stakeholders of a parent asset to child assets without stakeholders.

   d. Select **Append Stakeholders** to propagate stakeholders of a parent asset to all child assets including assets with stakeholders assigned.


      Note: To enable **Append Stakeholders**, you must enable **Propagate to Child Assets**.

      You can also override the propagation settings from the catalog source page in Data Governance and Catalog. For more information about stakeholder propagation, see *Stakeholder Propagation* in *Administration*.

   e. Select a stakeholder role.

f. Click **Select** to add users and user groups from the stakeholder role as stakeholders for the technical assets.

The **Add Users & User Groups** dialog box displays a list of users and user groups assigned to the selected stakeholder role.



g. Select one or more users or user groups to assign as stakeholders for the technical assets, and click **OK**.

Only the selected users and user groups belonging to the specified stakeholder role are granted the permissions to technical assets.

h. To assign users or user groups from another stakeholder role, click **Add** and then repeat the steps.

2. To assign asset groups to technical assets extracted from the catalog source, perform the following steps:

a. On the **Associations** page, click **Asset Groups**.


b. Select **Assign Asset Groups**.

c. Click **Select**.

The **Select Asset Groups** dialog box displays the list of asset groups.

If you enabled an access policy that includes an asset group, you can only view assets that belong to that asset group.

3. Select the asset groups to which you want to assign technical assets extracted from the catalog source, and click **OK**.



4. Choose to save and run the job or to schedule a recurring job.
   - To save and run the job, click **Save** and then **Run**.
   - To schedule a recurring job, click **Next** to open the **Schedule** page.

Step 4. Run or schedule the job

Choose to run a catalog source job manually, or configure it to run on schedule.

Note: You can't run multiple jobs simultaneously.

You can choose to perform a full or an incremental metadata extraction. A full metadata extraction extracts all objects from the source to the catalog. An incremental metadata extraction extracts only the changed and new objects since the last successful catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable.

When you run an incremental metadata extraction job with a filter to include metadata from objects, the job extracts only the objects that have the latest timestamp since the last successful job.

Note: If incremental metadata extraction is available for the catalog source, the option is always visible, but incremental metadata extraction jobs can run only after a scheduled full metadata extraction job. Manual jobs do not enable the incremental metadata extraction option.

Run the job manually

Click **Save** to save the catalog source and click **Run**. On the **Run Catalog Source Job** window, click **Run** to run the job.

You can override the capabilities that you selected while configuring your catalog source on the **Configuration** page. The first time you run the catalog source job, the metadata extraction capability is mandatory. From the second run onwards, you can choose to override the configured metadata change option. You can retain, delete, or deprecate objects that are deleted from the source in the catalog. For subsequent runs of the catalog source job, the metadata extraction capability is optional.

Note: You can choose incremental metadata extraction for subsequent runs only after one full metadata extraction job completes successfully. Incremental metadata extraction jobs run with the **Retain** metadata change option even if you set the option to **Delete** or **Deprecate** in the catalog source.

Note: To run a catalog source job, you need permissions on the connection to the source system. To run a catalog source job for catalog sources that reference other source systems, you need permissions on the connections for all the reference source systems.

Run the job on a schedule

You can choose to run metadata extraction and other capabilities on a recurring schedule. You can't choose incremental metadata extraction and full metadata extraction in the same schedule. To create a schedule for incremental metadata extraction, you must have completed at least one full metadata extraction job successfully. If not, first create a schedule for a full metadata extraction.

If an incremental metadata extraction is scheduled to run when the last run details aren't available, the job first performs a full metadata extraction, followed by incremental metadata extraction on subsequent runs.

For example, this can happen in the following scenarios:

- You create schedules for both incremental metadata extraction and full metadata extraction, but schedule the incremental extraction to run before the first full metadata extraction job.
- You create schedules for both incremental metadata extraction and full metadata extraction, but delete the full metadata extraction schedule before its first run.

1. On the **Schedule** tab, select **Run on Schedule**.
   The **Schedule** configuration page opens.
2. Click the checkbox corresponding to each capability that you want to include in the schedule.
3. Enter the start date, time zone, and the interval at which you want to run the job.
4. You can manage additional schedules using the following options:
   - To create a new schedule, click the **Add** button.
   - To delete a schedule, click the **Delete** button.
   - To enable or disable a schedule, click the **Enable Schedule** toggle button.

   Note: You can create a maximum of one schedule per capability that you enable. If you purged a catalog source or did not run the metadata extraction job, the catalog source job runs metadata extraction before running other scheduled capabilities.

   Note: To create a schedule, you need permissions on the connection to the source system. If you lose permissions on the connection after you create a schedule, the scheduled jobs continue to run.
5. Click **Save** to save the schedule.

Monitor job status

After the job runs, you can monitor the status of the job on the **Overview** page of the job.

For more information about job monitoring, see *Administration*.

Step 5. Assign reference catalog source connections to endpoint catalog source objects

When you run the catalog source job, if the catalog source references another source system, a reference catalog source and connection get created that point to the reference source system. To view the complete

lineage for your catalog source, you can perform connection assignment from the reference catalog source connection to the objects in the reference source system. A reference source system might be a cloud service, such as Informatica Intelligent Cloud Services. You must first create and run an endpoint catalog source that connects to the reference source system.

Before you assign a connection, ensure that you have created and run an endpoint catalog source for each reference source system.
Note: If the source schema contains case-sensitive tables or if the reference objects contain multiple objects with the same name in different cases, perform case-sensitive connection assignment to get correct lineage.

If you enabled the lineage discovery capability for your catalog source, you can either curate the CLAIRE recommended endpoint objects on the **Related Catalog Sources** tab or assign connections manually.

For more information about related catalog sources and lineage discovery, see *Lineage discovery* in the *Administration* help.

1. On the **Configure** page, select the **Lineage** tab, and then select the **Lineage Discovery** tab. On the **Catalog Sources** panel, select the required catalog source and click the **Assign Connections** tab.

   The **Assign Connections** tab displays a list of assigned and unassigned connections along with details for each connection. Use filters to view the connections based on the connection names. Click the **Add Filter** menu to add filters.

2. Select the connection to the reference source system and click **Assign**.

   The connection name appears prefixed to the reference catalog source name on the **Hierarchy** tab of your catalog source in Data Governance and Catalog.

   The **Assign Connection** dialog box appears with a list of recommended objects from the endpoint catalog sources. Click **All** to view all endpoint catalog source objects.

3. In the **Assign Connection** dialog box, select one or more objects from the endpoint catalog sources and click **Assign**.

   You can filter the list in the Assign Connection dialog box by name, type, or endpoint.

   You can connect to the following referenced source systems:

   - Informatica Intelligent Cloud Services
   - IBM InfoSphere DataStage

When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the lineage that you view in Data Governance and Catalog.

CHAPTER 4

View results in Data Governance and Catalog

After Metadata Command Center runs a job, you can view the results in Data Governance and Catalog where the catalog source and its elements are called technical assets. You can view a catalog source as a hierarchy. Expand each technical asset to see its components.

When referenced source systems are connected to a catalog source, you can expand the hierarchy to see details about the technical asset's component elements.

You can view the data lineage of an asset contained within a catalog source to see individual elements such as data sources, calculations, and filters. When you view data lineage, you can see the individual upstream elements that contribute data or expressions to each component of a data flow or catalog source.

View metadata extraction results


After a job runs in Metadata Command Center, view the results in Data Governance and Catalog. You can view details about source system contents in a hierarchical structure and trace data lineage.

1. Log in to Intelligent Data Management Cloud.

   The **My Services** page appears.

2. Click Data Governance and Catalog.

   The Data Governance and Catalog box appears on the **My Services** page.



3. On the Data Governance and Catalog home page, click the number in the **Technical Assets** panel.


   The **Technical Assets** page opens.

4. Select **Catalog Source** in the **Filter** list.

   The list of catalog sources opens.

5. Search for the catalog source from which you extracted metadata, and click the name.

   The **Overview** tab of the asset opens.



6. View the asset from different perspectives by clicking on the tabs.

For more information about working with assets, see Working with Assets in *Data Governance and Catalog* help.

View data lineage

Data lineage is a visual representation of the flow of data across the systems in your organization. Lineage depicts how the data flows from the system of its origin to the system of its destination.

Data lineage views are available for technical assets in the catalog source. You can view lineage at the catalog source, data set, or data element level.

The lineage at the catalog source level shows how data flows from one catalog source to another. The lineage at the data set and the data element levels show how other technical assets such as files or tables contribute to the selected asset.

If linking catalog sources is available for your catalog source, you can use Metadata Command Center to generate data lineage based on rules or by generating automated lineage with CLAIRE. You can choose source and target catalog sources and objects to link and generate lineage.

To determine whether linking catalog sources is available for your catalog source, navigate to the **Configuration** tab of the **Link Catalog Sources** page. The catalog source must appear in the list of source and target catalog sources.

For information about linking catalog sources, see *Link catalog sources* in the Administration help.

View lineage at the catalog source level

The catalog source level shows how data flows from one catalog source to another with the lineage aggregating data from the data set and data element levels.


To view data lineage at the catalog source level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Catalog Source Level**.

View lineage at the data set level


The data set level displays individual sets of data in the data flow.

To view lineage at the data set level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Set Level**.

The following image shows data set level lineage where the tgtfile1.csv reference data set gets data from the srcfile1.csv reference data set using the MT_File mapping task instance before connection assignment:



The following image shows data set level lineage where the tgtfile1.csv flat file gets data from the srcfile1.csv flat file using the MT_File mapping task instance after connection assignment:




View lineage at the data element level


The data element level displays details of the data set level. At the data element level, you can see the input sources for expressions or commands and calculations or transformations on the data.

To view data lineage at the data element level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Element Level**.

The following image shows data element level lineage where the Fld1 reference data element of the tgtfile1.csv reference data set gets data from the Fld1 reference data element of the srcfile1.csv reference data set using the Fld1 calculation before connection assignment:




The following image shows data element level lineage where the Fld1 flat field of the tgtfile1.csv flat file gets data from the Fld1 flat field of the srcfile1.csv flat file using the Fld1 calculation after connection assignment:



View classified data

When you add data classification rules to a catalog source in Metadata Command Center, the system identifies the columns and tables that match the rules and displays one or more matched data classifications on the column or table asset pages in Data Governance and Catalog.

The following image shows a column asset page with the inferred data element classifications that match the column data and metadata:



For more information about data classification assets, see *Asset Details* in the Data Governance and Catalog help.


View glossary associations

When you enable the glossary association capability for a catalog source in Metadata Command Center, you can view the accepted glossary assets in Data Governance and Catalog.

The **Overview** tab for a technical asset in the catalog source displays glossary assets in the Accepted and CLAIRE Recommendations sections.

The **Glossaries** panel shows the automatically accepted and CLAIRE® recommended terms.

The following image shows a sample asset page:



APPENDIX A

Managing catalog sources

You can update, copy, delete, purge, and run a catalog source. You can also grant configuration permissions for catalog sources to different roles in your organization.

On the **Catalog Sources** page of the **Explore** page, you can select a catalog source to see its overview and related catalog sources. The **Overview** tab displays the capabilities, filters, stakeholders, asset groups, and schedules enabled for a catalog source. The **Related Catalog Sources** tab displays a list of related catalog sources that are either assigned manually using connection assignment or are curated based on CLAIRE recommendations using the lineage discovery capability. You can view related catalog sources and accept or reject CLAIRE recommendations for catalog sources that are run with the lineage discovery capability.

Cloning a catalog source configuration

You can clone the configuration of a catalog source to create another catalog source with the same configuration.

Note: Cloning doesn't copy the content of the catalog source.

1. In Metadata Command Center, go to the **Explore** page.
2. Select **Catalog Sources** from the menu.
3. You can clone a catalog source in one of the following ways:
   - Hover your mouse over the catalog source that you want to clone and click **Clone** from the **Action** menu.
   - Open the catalog source that you want to clone and click **Clone**.

   Note: By default, the cloned catalog source has the same name suffixed with _Clone. You can change the name if needed.
4. If needed, modify the configuration of the catalog source by updating the parameters on each tab.

   Cloning doesn't copy the content of sensitive fields. If the catalog source contains sensitive fields such as Client Secret, enter the values.
5. Click **Save**.

Deleting or purging a catalog source

Delete or purge a catalog source based on your business requirements.

When you delete a catalog source, you delete all the configuration specific to that catalog source, along with all the metadata that was extracted and any enrichment made to the associated metadata. Purging a catalog source deletes all the metadata that was extracted, along with any enrichment made to the associated metadata.

Note: Before you delete or purge a catalog source, manually unassign the connections that are assigned to that catalog source.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source that you want to delete or purge.
4. Click the **Action** menu, and select **Delete** or **Purge**.

   Note: You can't delete or purge a catalog source if the catalog source job is in the running state.
5. To confirm delete or purge, click **OK**.

   The catalog source is triggered to delete or purge. You can monitor the status of the job on the **Monitor** page.

   Note: If the deletion job succeeds, the catalog source disappears from Metadata Command Center. If it fails, some associated objects might still be present in Data Governance and Catalog. Such catalog sources continue to appear in the list of catalog sources in Metadata Command Center, but are marked as **Deleted**. Delete the catalog sources to remove them along with any remaining objects present in Data Governance and Catalog.

Purging obsolete objects from a catalog source

You can purge obsolete objects from a catalog source.

When you configure or run a catalog source, you can choose to deprecate objects that are deleted from a source system. If you delete objects from the source system or make changes to the filter, the objects imported into the catalog before the change move to the Obsolete lifecycle in the catalog. You can purge obsolete objects from a catalog source. This permanently deletes all objects with the Obsolete lifecycle status, along with associated enrichments, from the catalog.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source from which you want to purge obsolete objects.
4. Click the **Action** menu, and select **Purge Obsolete Objects**.

   A warning message appears on the page.
5. Click **Yes** to confirm.

   A confirmation message appears on the page and the purge job starts. You can monitor the status of the job on the **Monitor** page. If the job succeeds, all obsolete objects present in the catalog source disappear from the catalog.

   Note: If the job fails, some obsolete objects might remain in the catalog. To remove the remaining obsolete objects, run the purge job again.

Curating CLAIRE recommendations

You can view related catalog sources and accept or reject CLAIRE recommendations for a catalog source.

Applicable to catalog sources that generate lineage.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source for which you want to curate CLAIRE recommendations.
4. Hover your mouse over the catalog source and click **View Lineage Discovery** from the **Action** menu.

   Note: The **View Lineage Discovery** option is available for catalog sources that are run with the lineage discovery capability.

   The **Configure** page appears with the catalog source filtered on the **Lineage Discovery** tab of the **Lineage** tab.
   The **Related Catalog Sources** tab displays a list of related catalog sources.
5. Hover your mouse over a related catalog source and click **Accept** or **Reject** from the **Action** menu.

   For more information about lineage discovery and curating CLAIRE recommendations, see *Lineage discovery* in the *Administration* help.

Managing configuration permissions for catalog sources

As a service administrator, you can grant configuration permissions for catalog sources to different roles in your organization, and add specific users and user groups to those roles so that they can perform operational activities on a catalog source.

To manage permissions for catalog source configuration, verify that at least one role has the catalog source configuration **Set Permissions** functionality enabled for Metadata Command Center in Administrator. In Administrator, create the required roles, assign users and user groups to the roles, and specify appropriate permissions to the roles.

You can select roles and add specific users or user groups to those roles to grant the following levels of permission for catalog source configuration:


- Create
- Read
- Update
- Run
- Set Permissions

Based on the permissions granted to the roles, the selected users and user groups belonging to that role can perform appropriate operations for configuring catalog sources.

1. Go to the **Explore** page in Metadata Command Center.
2. From the list of catalog sources, search for the catalog source for which you want to manage permissions.


3. Click the **Action** menu, and select **Permissions**.

   The **Catalog Source Permissions** dialog box appears.




4. In the **Roles** panel, click **Add Roles**.

   The **Add Roles** dialog box appears.



5. Select one or more roles, and click **OK** to add the roles.
6. In the **Add Users & User Groups** panel, by default, all users and user groups that belong to the selected role are granted the role-defined permissions for the catalog source configuration.

To assign permissions only to the selected users and user groups that belong to this role, choose **Specific Users and User Groups**.



7. Select **Add Specific Users and User Groups**.

   The **Add Users & User Groups** dialog box displays the list of users and user groups that the administrator has assigned to the selected role.

8. Select one or more users or user groups to assign to the selected role, and click **OK**.

   Only the selected users and user groups belonging to the specified role will be granted the role-defined permissions for catalog source configuration.

9. View the assigned permissions for each user and or group, and click **Save**.