Informatica® Metadata Command Center
October 2026

Databricks Sources

Informatica Metadata Command Center Databricks Sources
October 2026

© Copyright Informatica LLC 2023, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-30

Table of Contents

Preface. 5

Chapter 1: Introduction to Databricks catalog sources. 6

Extraction and view process. 7

About the Databricks catalog source. 8

- Extracted metadata. 8
- Compatible functionalities. 11
- Data profiling for Databricks objects. 14
- Compatible connectors. 15

Chapter 2: Before you begin. 16

Verify permissions. 16

- Permissions to extract metadata. 16
- Permissions to run data profiles. 17
- Permissions to perform data classification. 17
- Permissions to perform relationship discovery. 18
- Permissions to perform glossary association. 18

Create a connection. 18

- Personal access token authentication. 19
- OAuth machine-to-machine authentication. 20
- Advanced connection properties. 20
- Analytics and job cluster properties. 21

Import a relationship inference model. 21

Chapter 3: Create catalog sources in Metadata Command Center. 23

Step 1. Register a catalog source. 23

Step 2. Configure capabilities. 25

- Configure metadata extraction. 25
- Configure data profiling and quality. 36
- Configure data observability. 39
- Configure data classification. 40
- Configure relationship discovery. 41
- Configure glossary association. 42
- Configure automation. 42

Step 3. Associate stakeholders and asset groups. 44

Step 4. Run or schedule the job. 46

Step 5. Assign reference catalog source connections to endpoint catalog source objects. 47

Chapter 4: View results in Data Governance and Catalog. 49

View metadata extraction results. 49

View referenced source systems. . . . 51
View data lineage. . . . 51
View lineage at the catalog source level. . . . 52
View lineage at the data set level. . . . 52
View lineage at the data element level. . . . 53
View data profiling results 53
View data observability results 54
View classified data. . . . 55
View glossary associations. . . . 55

Appendix A: Managing catalog sources. . . . 57

Cloning a catalog source configuration. . . . 57
Deleting or purging a catalog source. . . . 58
Purging obsolete objects from a catalog source. . . . 58
Curating CLAIRE recommendations. . . . 59
Managing configuration permissions for catalog sources. . . . 59

Preface

Read *Databricks Sources* to learn how to register and configure Databricks source systems as catalog sources in Metadata Command Center. After you configure a catalog source, you extract metadata and then view the results in Data Governance and Catalog.

CHAPTER 1

Introduction to Databricks catalog sources

You can use Metadata Command Center to extract metadata from a source system.

A source system is any system that contains data or metadata. For example, Databricks is a source system from which you can extract metadata through a Databricks catalog source. A catalog source is an object that represents and contains metadata from the source system.

Before you extract metadata from a source system, you first create and register a catalog source that represents the source system. Then you configure capabilities for the catalog source. A capability is a task that Metadata Command Center can perform, such as metadata extraction, lineage discovery, autonomous enrichment, data profiling, data classification, or glossary association.

When Metadata Command Center extracts metadata, Data Governance and Catalog displays the extracted metadata and its attributes as technical assets. You can then perform tasks such as analyzing the assets, viewing lineage, and creating links between those assets and their business context.

The following table describes the capabilities of the catalog source:


Capability	Description
Incremental metadata extraction	An incremental metadata extraction extracts only the changed and new objects since the last catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable. Applicable only to Databricks Unity Catalog. Applies to the following Databricks Unity Catalog objects: - Table - View
Advanced Programming Language Parsing	Advanced Programming Language Parsing parses the source system code in addition to extracting objects from the source system.
Lineage Discovery	Builds the complete lineage of a catalog source by recommending endpoint catalog source objects to assign to reference catalog source connections. When you run the catalog source job, Metadata Command Center assigns the reference catalog source connections to CLAIRE recommended endpoint catalog source objects. You can then view the list of CLAIRE recommendations and accept or reject them.
Data Profiling and Quality	- **Data Profiling**. Assesses source metadata and analyzes the collected statistics to discover content and structure, such as value distribution, patterns, and data types. - **Data Quality**. Measures the reliability of the data and enables data usage.
Data Observability	Identifies anomalies in the characteristics of the data that you profile.

Capability	Description
Data Classification	Data classification is the process of identifying and organizing data into relevant categories based on the functional meaning of the data. Classifying data can help your organization manage risks, compliance, and data security.
Glossary Association	You can associate terms that are in the glossary with technical assets to provide user-friendly business names to technical assets. Glossary Association automatically associates glossary terms with technical assets or recommends glossary terms that you can manually associate with technical assets in Data Governance and Catalog.
Autonomous Enrichment	Automatically propagates classification, description, business name, and glossary enrichments from an asset to related assets based on the lineage between assets. Autonomous enrichment reduces manual curation effort by extending the enrichments that you apply to one asset across assets that are connected to it through lineage.

Extraction and view process

To extract metadata from a source system, configure the catalog source and run the catalog source job in Metadata Command Center. Then view the results in Data Governance and Catalog.

The following image shows the process to extract metadata from a source system:



After you verify prerequisites, perform the following tasks to extract metadata from Databricks:

1. Register a catalog source. Create a catalog source object, select the source system, and select the connection.
2. Configure the catalog source. Specify the runtime environment and configure parameters for metadata extraction. Optionally, add filters to include or exclude source system assets from metadata extraction. You can also configure other capabilities such as data profiling and quality.
3. Optionally, associate stakeholders. Associate users with technical assets, giving the users permission to perform actions determined by their roles.
4. Run or schedule the catalog source job.

5. Optionally, if the catalog source job generates referenced asset objects, you can assign a connection to referenced source system assets.
   You can view the lineage with object references without performing connection assignment. After connection assignment, you can view the objects.

   Run the catalog source again after you assign connections to referenced source system assets.

After you run the catalog source job, you view the results in Data Governance and Catalog.

About the Databricks catalog source

You can use the Databricks catalog source to extract metadata from Databricks source system.

Databricks combines data warehouses and data lakes into an AI-driven Databricks Lakehouse platform.

You can run connection-aware scans on Databricks sources.

You can use SQL warehouse or all-purpose clusters to extract metadata.

Extracted metadata

You can extract specific metadata from a Databricks source system with a Databricks catalog source.

You can extract AI Model Core and AI Model Core Version metadata from Databricks Unity Catalog source systems. Additionally, you can retrieve lineage captured by Databricks Unity Catalog.

Note: Databricks Unity Catalog retains lineage data for 90 days.

You can extract metadata from Databricks notebooks if they use the following technologies:

- Markdown
- Python
- SQL

You can extract metadata of the following objects from a Databricks workspace:

- Calculation
- Command
- Experiment
  - Experiment Run
- Folder
- Genie Space
- Job Parameter
- Knowledge Assistant
- Live View
- Materialized View
- MCP Server
- MCP Server Tool
- Notebook Definition

- Notebook Instance
- Notebook Parameter
- Notebook Task
- Pipeline Definition (SQL based)
  - Live View
  - Materialized View
  - Streaming Table
  - Streaming View
- Result
- Run Job Task
- Serving Endpoint
- Streaming Table
- Streaming View
- Supervisor Agent
- Supervisor Agent Tool
- Task Parameter
- Workflow Job Definition
- Workflow Job Instance

You can extract metadata of the following objects from Databricks Unity Catalog:

- AI Search Index
- AI Search Index Column
- Column
  - Primary Key
  - Foreign Key
- Dashboard
- Database
- External Column
- External Table
- File
- File System
- Function
- Metric View
- Schema
- Stored Procedure
- Table
- View
- Volume

You can extract metadata from foreign catalogs in Databricks Unity Catalog that connect to the following source systems:

- Amazon Redshift
- Databricks
- Google BigQuery
- Microsoft Azure Synapse Data Warehouse
- Microsoft SQL Server
- Salesforce
- Snowflake

You can extract the following complex data type columns along with their nested fields from Databricks source systems:

- Map
- Struct
- Array

You can extract metadata of the following file types from a Databricks volume:

- AVRO
- Compressed files
  - TAR
  - ZIP
- Delimited files
  - CSV
  - TSV
- E-mail files
  - EML
  - EMLX
  - MSG
- JSON
- JSONL
- Microsoft Excel files
  - Excel 97-2003 Workbook with XLS extension
  - Excel Workbook with XLSX extension
  - Excel Macro-Enabled Workbook with XLSM extension
- Microsoft Word files
  - DOC
  - DOCX
- ORC
- Parquet
- PDF

- Presentation files
  - PPT
  - PPTX
- Rich Text Format (RTF)
- Text
  - TXT
  - Markdown
- XML
- XSD

Note: Catalog source jobs can extract metadata from protected unstructured files. However, some metadata attributes of such files might not get extracted or displayed in Data Governance and Catalog.

The following table lists the structures associated with the file types that you can extract metadata from:

File Type	Partition structure
AVRO	Single partition, multiple partitions, schema merge
CSV	Single partition, multiple partitions, schema merge
JSON	Single partition, multiple partitions, schema merge
JSONL	Single partition, multiple partitions, schema merge
Parquet	Single partition, multiple partitions, schema merge
XML	Single partition, multiple partitions, schema merge

You can extract workbooks, worksheets, and columns from Microsoft Excel files.

You can extract metadata from XML and XSD file formats as XML file objects. Metadata Command Center extracts only elements and attributes from XML and XSD files. If the size of the XML file exceeds 100 KB, Metadata Command Center extracts metadata from the initial 100 KB of the file. However, for XSD file types, Metadata Command Center extracts complete metadata.

Compatible functionalities

Databricks offers integration with a diverse range of modules and programming languages.

You can use Databricks with the following programming languages:

- Python
- SQL
- Markdown

You can use Databricks with the following Python functionalities:

- Standard language constructions
- Standard built-in functions
- Partially-compatible modules:

Note: Data Governance and Catalog processes only a subset of library functions of partially-compatible modules.

- abs
- adal
- argparse
- array
- ast
- azure
- base64
- binascii
- calendar
- codecs
- collections
- concurrent
- contextlib
- contextvars
- copy
- copyreg
- csv
- dataclasses
- datetime
- dbutils
- decimal
- delta
- difflib
- distutils
- email
- enum
- errno
- fnmatch
- fractions
- functools
- gc
- genericpath
- gettext
- glob
- graphframes
- hashlib
- heapq

- hmac
- importlib
- inspect
- io
- itertools
- json
- keyword
- locale
- logging
- math
- matplotlib
- nt
- numbers
- numpy
- operator
- os
- pandas
- pathlib
- pickle
- pkgutil
- posix
- posixpath
- pprint
- py4j
- pyodbc
- pyspark
- pytz
- random
- re
- reprlib
- requests
- seaborn
- secrets
- shutil
- simplejson
- six
- sklearn
- smtplib
- socket

- ssl
- stat
- string
- struct
- subprocess
- sys
- teradatasql
- textwrap
- threading
- time
- traceback
- types
- typing
- urllib
- urllib3
- uuid
- warnings
- weakref
- xml
- yaml
- zipfile
- zlib

- Custom libraries

  Note: Custom libraries are libraries created by a user.

Note: If Databricks catalog source detects an incompatible function or library, it can't process the statement. It skips the statement and continues to process the next one.

You can also use DeltaLake SQL in SQL commands and PySpark calls.

Data profiling for Databricks objects

Configure data profiling to run profiles on the metadata extracted from a Databricks source system. You can use all-purpose clusters or SQL warehouse to run profiles. You can also run profiles on Databricks Unity Catalog objects. You can view the profiling statistics in Data Governance and Catalog.

You can run profiles on the following Databricks Unity Catalog objects:

- Delta Table
- External Table in Delta, Parquet, and CSV formats
- View

You can view the profiling statistics in Data Governance and Catalog. The data profiling task runs profiles on the following data types:

- Bigint
- Boolean

- Date
- Decimal
- Double
- Float
- Int
- Smallint
- String
- Tinyint
- Timestamp

Compatible connectors

Before you configure a Databricks catalog source, you must connect to Databricks source system.

Use the Databricks connector to connect to Databricks source system.

Note: To enable profiling, perform the following prerequisite steps before you configure a Databricks connector in Administrator:

1. Create a folder with the name `informatica.databricksdelta` in the `<Secure Agent installation directory>/ext/connectors/thirdparty/` folder.
2. Copy the `SparkJDBC42.jar` file to the `informatica.databricksdelta` folder. The minimum version of the Spark server must be 3.x.
3. Run the `./infaagent.sh startup` script located in the `<Secure Agent installation directory>/apps/agentcore` folder to restart the Secure Agent.

CHAPTER 2

Before you begin

Before you create a catalog source, ensure that you have the information required to connect to the source system.

Perform the following tasks:

- Assign the required permissions.
- Configure a connection to the Databricks source system.
- Optionally, if you want to identify pairs of similar columns and relationships between tables within a catalog source, import a relationship inference model.

Verify permissions

To extract metadata and to configure other capabilities that a catalog source might include, you need account access and permissions on the source system. The permissions required might vary depending on the capability.

Permissions to extract metadata

Ensure that you have the required permissions to enable metadata extraction.

- Grant the following permissions for non-unity catalog sources:
  - show tables
  - show schemas
  - describe table extended
  - describe schema extended
  - show catalogs
- To extract metadata of MCP servers, ensure that the MCP server is registered as a metastore-level connection in the Databricks source system with the `is_mcp_connection` flag set to `true`.
- To extract metadata from AI models, grant the following permissions:
  - EXECUTE permission on AI models
  - USE CATALOG permission on the Databricks Unity Catalog
  - USE SCHEMA permission on schemas
- To extract metadata of Databricks Unity Catalog volumes, you need the BROWSE privilege on the Databricks Unity Catalog and the READ VOLUME privilege on the volumes.

- To extract Databricks Unity Catalog lineage with system tables, grant access permissions on the following system tables:

  - system.access.column_lineage

  - system.access.table_lineage

  Note: If you don't have access to system tables, the metadata extraction job uses REST APIs to extract lineage data.

- To extract Databricks Unity Catalog stored procedure and table metadata with system tables, grant the following permissions on the Databricks Unity Catalog and the `system` catalog:

  - USE CATALOG

  - SELECT and USE SCHEMA permissions on the INFORMATION_SCHEMA schema

    Note: To extract metadata of stored procedures, you need permissions on both `system.information_schema` and `catalog.information_schema`.

  - BROWSE privilege on Databricks Unity Catalog. Required if you don't have the SELECT permission on the Databricks Unity Catalog tables.

  When you need to extract metadata from a view associated with a table in a different schema, you must grant the USE SCHEMA permission for the schema that contains the table in Databricks Unity Catalog.

  The metadata extraction job uses the following INFORMATION_SCHEMA schema tables to extract metadata:

  - TABLES
  - COLUMNS
  - SCHEMATA
  - VIEWS
  - KEY_COLUMN_USAGE
  - REFERENTIAL_CONSTRAINTS
  - CATALOGS

Note: If you don't have access to the INFORMATION_SCHEMA tables, the metadata extraction job uses the `Show` and `Describe` commands to extract metadata.

Permissions to run data profiles

Ensure that you have the required permissions to run profiles.

Grant the following permissions:

- Read permission for Databricks tables in the Databricks source system.
- Access to Databricks workspace and Databricks SQL in the Databricks source system.

Note: Databricks Unity Catalog governs access to the INFORMATION_SCHEMA schema. To profile the INFORMATION_SCHEMA schema, use a Databricks SQL endpoint and verify that you have the USE and SELECT permissions on the `system` schemas.

Permissions to perform data classification

You don't need any additional permissions to run data classification.

Permissions to perform relationship discovery

You don't need any additional permissions to run relationship discovery.

Permissions to perform glossary association

You don't need any additional permissions to run glossary association.

Create a connection

Before you configure the Databricks catalog source, create a connection object in Administrator.

To use an external secrets manager to connect to the source system, use one of the following authentication tools:

- AWS Secrets Manager
- Azure Key Vault

1. In Administrator, select **Connections**.
2. Click **Add Connection**.
3. Search for and select Databricks and then click **Next**.
4. Enter the connection details.

   The following table describes the basic connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select the credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.

Property	Description
Runtime Environment	The name of the runtime environment where you want to run tasks. For more information about runtime environments, see *Runtime Environments* in the Administrator help.

SQL Warehouse JDBC URL	Databricks SQL Warehouse JDBC connection URL. Required to connect to a Databricks SQL warehouse. Also applies to Databricks clusters.
	Note: Databricks SQL Serverless is the recommended Databricks cluster type.
	To get the SQL Warehouse JDBC URL, go to the Databricks console and select the JDBC driver version from the JDBC URL menu.
	If you use the personal access token authentication type and select JDBC URL version 2.6.22 or earlier, use the following syntax:
	`jdbc:spark://<Databricks Host>:443/default;transportMode=http;ssl=1;AuthMech=3;httpPath=/sql/1.0/endpoints/<SQL endpoint cluster ID>;`
	If you use the personal access token authentication type and select JDBC URL version 2.6.25 or later, use the following syntax:
	`jdbc:databricks://<Databricks Host>:443/default;transportMode=http;ssl=1;AuthMech=3;httpPath=/sql/1.0/endpoints/<SQL endpoint cluster ID>;`Application ingestion and replication and database ingestion and replication tasks can use JDBC URL version 2.6.25 or later or 2.6.22 or earlier. The URLs must begin with the prefix `jdbc:databricks://`, as follows:
	`jdbc:databricks://<Databricks Host>:443/default;transportMode=http;ssl=1;AuthMech=3;httpPath=/sql/1.0/endpoints/<SQL endpoint cluster ID>;`
	If you use the OAuth machine-to-machine authentication type and select JDBC URL version 2.6.36 or later, use the following syntax: `jdbc:databricks://<Databricks Host>:443/default;transportMode=http;ssl=1;AuthMech=11;Auth_Flow=1;httpPath=/sql/1.0/endpoints/<SQL endpoint cluster ID>;`
	Ensure that you set the required environment variables in the Secure Agent. Also specify the correct JDBC Driver Class Name under advanced connection settings.
	Note: Specify the database name in the Database Name connection property. If you specify the database name in the JDBC URL, it is not considered. The Databricks Host, Organization ID, and Cluster ID properties are not considered if you configure the SQL warehouse JDBC URL property.

5. Select the authentication type to connect to Databricks and enter the required properties.

   You can use the following authentication types:

   - Personal Access Token
   - OAuth Machine-to-Machine
6. Click **Test** to test your connection to the source system.
7. Click **Save**.

Personal access token authentication

The following table describes the connection properties for personal access token authentication:

Property	Description
Databricks Token	Personal access token to access Databricks. This property is required for SQL warehouse, all-purpose cluster, and job cluster.

OAuth machine-to-machine authentication

The following table describes the connection properties for OAuth machine-to-machine authentication:

Property	Description
Client ID	The client ID of the service principal.
Client Secret	The client secret associated with the Client ID of the service principal. Log in to your Databricks account to generate the client secret.

Advanced connection properties

The following table describes the advanced connection properties:

Property	Description
JDBC Driver Class Name	The name of the JDBC driver class. Optional for SQL warehouse and Databricks cluster. For JDBC URL versions 2.6.22 or earlier, specify the driver class name as `com.simba.spark.jdbc.Driver`. For JDBC URL versions 2.6.25 or later, specify the driver class name as `com.databricks.client.jdbc.Driver`.

Analytics and job cluster properties


The following table describes the analytics and job cluster properties:

Property	Description
Databricks Host	The host name of the endpoint the Databricks account belongs to. Required for Databricks cluster. Doesn't apply to SQL warehouse. You can get the Databicks Host from the JDBC URL. The URL is available in the Advanced Options of JDBC or ODBC in the Databricks all-purpose cluster. The following example shows the Databicks Host in JDBC URL: `jdbc:spark:// <Databricks Host> :443/ default;transportMode=http; ssl=1;httpPath=sql/ protocolv1/o/ <Org Id>/<Cluster ID>; AuthMech=3; UID=token; PWD=<personal-access-token>` `The value of PWD in Databricks Host, Organization Id, and Cluster ID is always <personal-access-token>.`
Cluster ID	The ID of the cluster. Required for Databricks cluster. Doesn't apply to SQL warehouse. You can get the cluster ID from the JDBC URL. The URL is available in the Advanced Options of JDBC or ODBC in the Databricks all-purpose cluster. The following example shows the Cluster ID in JDBC URL: `jdbc:spark://<Databricks Host>:443/ default;transportMode=http; ssl=1;httpPath=sql/ protocolv1/o/<Org Id>/ <Cluster ID>; AuthMech=3;UID=token; PWD=<personal-access-token>`
Organization ID	The unique organization ID for the workspace in Databricks. Required for Databricks cluster. Doesn't apply to SQL warehouse. You can get the Organization ID from the JDBC URL. The URL is available in the Advanced Options of JDBC or ODBC in the Databricks all-purpose cluster. The following example shows the Organization ID in JDBC URL: `jdbc:spark://<Databricks Host>:443/ default;transportMode=http; ssl=1;httpPath=sql/ protocolv1/o/ <Organization ID> / <Cluster ID>;AuthMech=3;UID=token; PWD=<personal-access-token>`

Import a relationship inference model

Import a relationship inference model if you want to configure the relationship discovery capability. You can either import a predefined relationship inference model, or import a model file from your local machine.

1. In Metadata Command Center, click **Explore** on the navigation panel.
2. Expand the menu and select **Relationship Inference Model**. The **Explore** page opens with the **Relationship Inference Model** menu.



3. Select one of the following options:
   - **Import Predefined Content**. Imports a predefined relationship inference model called Column Similarity Model v1.0.

- **Import**. Imports the predefined relationship inference model from your local machine. Select this if you previously imported predefined content into your local machine and the inference model is stored on the machine.
  To import a file, click **Choose File** in the **Import Relationship Inference Model** window and navigate to the model file on your local machine. You can also drag and drop the file.

The imported models appear in the list of relationship inference models on the **Relationship Discovery** tab.

CHAPTER 3

Create catalog sources in Metadata Command Center

Use Metadata Command Center to configure a catalog source for Databricks and run the catalog source job.

When you configure a catalog source, you define the source system that you want to extract metadata from. Configure filters to include or exclude source system metadata before you run the job. Optionally, configure other capabilities, such as data profiling and quality, data classification, relationship discovery, and glossary association.

To provide stakeholders access to technical assets, you can assign access through roles. If your catalog source references other source systems, you can create a connection assignment to the endpoint catalog source to view complete lineage.


Step 1. Register a catalog source

When you register a catalog source, provide general information and connection values.

1. Log in to Intelligent Data Management Cloud.


   The **My Services** page appears.
2. Click **Metadata Command Center**.

   The **Metadata Command Center** box appears on the **My Services** page.



The Metadata Command Center home page appears.

3. Click **New**.
4. Select **Catalog Source** from the list of asset types.
5. Select Databricks from the list of catalog source types.



6. Click **Create**.

   The **New Catalog Source** page opens.
7. In the **General Information** section, enter a name and an optional description for the catalog source.

   Note: You can rename a catalog source after you create it, but to apply the change to all associated objects you must rerun the metadata extraction job.

   After you save the catalog source, you can update the description in Metadata Command Center and Data Governance and Catalog. The update appears only in the service in which you update it.
8. In the **Connection Information** area, select the connection that you created in Administrator.

   Note: To create or edit a catalog source, you need permissions on the connection to the source system. Select a connection that you have access to, or ask the administrator to grant the necessary permissions to the connection that you want to use.

9. Click **Connection Properties** to expand and view the connection properties for the selected connection.
10. Click **Test Connection** to test your connection to the source system.
11. Click **Next**.

The **Configuration** page appears.

Step 2. Configure capabilities

When you configure the Databricks catalog source, you define the settings for the metadata extraction capability and other optional capabilities.

The metadata extraction capability extracts source metadata from external source systems. You can also configure other capabilities that the catalog source includes.

You can save the catalog source configuration at any point after you enter the connection information. After you save the catalog source, you can choose to run the catalog source job. To run the job once, click **Run**. To run metadata extraction and other capabilities on a recurring schedule, configure schedules on the **Schedule** tab.

Configure metadata extraction

When you configure the Databricks catalog source, you choose a runtime environment, define filters, and enter configuration parameters for metadata extraction.

Before you configure metadata extraction, configure runtime environments in the IDMC Administrator.

1. In the **Connection and Runtime** area, choose a serverless runtime environment or the Secure Agent group where you want to run catalog source jobs.

   Note: Serverless runtime environment options are available if the catalog source works with a serverless runtime environment.
2. Choose to retain, delete, or deprecate objects that are deleted from the source system in the catalog with the **Metadata Change Option**.
   - **Retain**. Retains objects that are deleted from the source system in the catalog. If you update or add a filter, the catalog retains objects extracted from the previous job and extracts additional objects that match the current filter. Objects deleted from the source system are not deleted from the catalog. Enrichments added on deleted objects and relationships are retained.
   - **Delete**. Deletes metadata from the catalog based on objects deleted from the source system and changes you make to the filter. Enrichments added on deleted objects and relationships are also permanently lost. Objects renamed in the source system are removed and recreated in the catalog.

- **Deprecate**. When objects are deleted from the source system, the catalog changes the lifecycle of the imported objects to Obsolete. The lifecycle of objects also changes to Obsolete when you add exclusion filters or reduce the scope so that objects extracted in earlier jobs are no longer included. For example, the first job includes the sales schema. The second job also includes the sales schema, but excludes the sales.transactions table. In this case, the second job marks the sales.transactions object as Obsolete, even though the first job includes it. This does not impact enrichments applied to deprecated objects and relationships. Objects renamed in the source system are removed and recreated in the catalog. When you run the catalog source job again for other capabilities such as data classification, relationship discovery, or glossary association, the job doesn't consider obsolete objects. Obsolete objects remain in the catalog until they are purged when you run a **Purge Obsolete Objects** job on the **Explore** page.


Note: You can also change the configured metadata change option when you run a catalog source.

3. In the **Filters** area, define one or more filter conditions to apply for metadata extraction:
   a. Select **Yes** to view filter options.
   b. From the Include/Exclude list, choose to include or exclude metadata based on the filter parameters.
   c. From the Object type list, select an object type, depending on the object that you want to extract metadata from.

      You can select the following object types:

      - **Notebooks Path**
      - **Table**
      - **Stored Procedure**
      - **Metric View**
      - **AI Model**
      - **Workflow Job**
      - **Pipeline**
      - **Volume**
      - **Dashboard Path**
      - **Supervisor Agent**
      - **Knowledge Assistant**
      - **Genie Space**
      - **MCP Server**
      - **AI Search Index**

      The following image shows the filter condition options:



d. From the Filter criteria list, select **Pattern**.

e. Click **Select**.

f. In the **Select values** dialog box, enter the path and click **OK**.

Each pattern can contain wildcards. Use a question mark to represent a single character. For example, A? matches A1, Ab. Use an asterisk to represent multiple characters or empty text. For example, A* matches A, Ab, ABC. For object hierarchies, use relevant separators, such as a dot for Table object type and '/' for Notebooks Paths object type. When you enter values for filters, enclose them in double quotes if you include spaces before or after a string value.
The Notebooks Path that you enter in the value field is relative to the Notebook Workspace Path that you enter in the Databricks parameters.

Filters are case-insensitive.

Examples:

- To include or exclude metadata from the 'customers' table located in the 'db_schema' schema that belongs to the 'catalog_dept' catalog, select **Table** as the object type and enter `catalog_dept.db_schema.customers` in the value field.
- To include or exclude metadata from tables with names that start with 'cust' located in schemas with names that start with 'db_sch' and belong to catalogs with names that start with 'catalog_dep', select **Table** as the object type and enter `catalog_dep*.db_sch*.cust*` in the value field.
- To include or exclude metadata from all stored procedures with names that end with '_etl' located in the 'db_schema' schema that belongs to the 'catalog_dept' catalog, select **Stored Procedure** as the object type and enter `catalog_dept.db_schema.*_etl` in the value field.
- To include or exclude metadata from the 'sales_metrics' metric view located in the 'db_schema' schema that belongs to the 'catalog_dept' catalog, select **Metric View** as the object type and enter `catalog_dept.db_schema.sales_metrics` in the value field.
- To include or exclude all metadata from all notebooks located in the workspace path, select **Notebooks Path** as the object type and enter `*` in the value field.
- To include or exclude all metadata from notebooks with names that start with 'Cust' followed by a single character located in the workspace path '/Users/username@domain.com/Deltalake_Notebooks', select **Notebooks Path** as the object type and enter `Users/username@domain.com/Deltalake_Notebooks/Cust?` in the value field.
- To include or exclude the notebook named Cust_Notebook located in the workspace path '/Users/username@domain.com/Deltalake_Notebooks', select **Notebooks Path** as the object type and enter `/username@domain.com/Deltalake_Notebooks/Cust_Notebook` in the value field.
- To include or exclude all the jobs with names that start with 'Job1' followed by a single character, select **Workflow Job** as the object type and enter `Job1?` in the value field.
- To include or exclude all the jobs with names that start with 'Job1', select **Workflow Job** as the object type and enter `Job1*` in the value field.
- To include or exclude all pipelines with names that start with 'Pipeline1' followed by a single character, select **Pipeline** as the object type and enter `Pipeline1?` in the value field.
- To include or exclude metadata from all AI Models in the 'db_schema' schema in the 'catalog_dept' catalog source, select **AI Model** as the object type and enter `catalog_dept.db_schema.*` in the value field.

- To include or exclude metadata from the 'iris_classifier_model' AI Model in the 'db_schema' schema in the 'catalog_dept' catalog source, select **AI Model** as the object type and enter `catalog_dept.db_schema.iris_classifier_model` in the value field.
- To include or exclude all volumes from 'hawk_qe_schema' schema that belongs to 'hawk_qe_catalog' catalog, select **Volume** as the object type and enter `/Volumes/hawk_qe_catalog/hawk_qe_schema/*` in the value field.
- To include or exclude all volumes named 'hawk_external_volume' located in 'hawk_qe_schema' schema that belongs to 'hawk_qe_catalog' catalog, select **Volume** as the object type and enter `/Volumes/hawk_qe_catalog/hawk_qe_schema/hawk_external_volume` in the value field.
- To include or exclude all volumes with names that start with 'hawk_' located in 'hawk_qe_schema' schema that belongs to 'hawk_qe_catalog' catalog, select **Volume** as the object type and enter `/Volumes/hawk_qe_catalog/hawk_qe_schema/hawk_*` in the value field.
- To include or exclude volumes from 'files1' folder located in the 'hawk_external_volume' volume inside the 'hawk_qe_schema' schema that belongs to 'hawk_qe_schema' catalog, select **Volume** as the object type and enter `/Volumes/hawk_qe_catalog/hawk_qe_schema/hawk_external_volume/files1` in the value field.
- To include or exclude metadata from all dashboards located in the workspace path, select **Dashboard Path** as the object type and enter `*` in the value field.
- To include or exclude metadata from all dashboards located in the Users directory, select **Dashboard Path** as the object type and enter `/Users/*` in the value field.
- To include or exclude metadata from all dashboards with names that start with 'Dashboard1' followed by a single character located in the `/Users/username@domain.com` workspace path, select **Dashboard Path** as the object type and enter `/Users/username@domain.com/Dashboard1?` in the value field.
- To include or exclude metadata from 'Dashboard1' dashboard located in the `/Users/username@domain.com` workspace path, select **Dashboard Path** as the object type and enter `/Users/username@domain.com/Dashboard1` in the value field.
- To include or exclude metadata from AI search indexes with names that start with 'search_index' located in schemas with names that start with 'db_sch' and belong to catalogs with names that start with 'catalog_dep', select **AI Search Index** as the object type and enter `catalog_dep*.db_sch*.search_index*` in the value field.

g. Optionally, to define an additional filter with an OR condition, click the **Add** icon.

4. Optional. In the **Configuration Parameters** area, enter properties to override default content values and job parameters.

   Note: Click **Show Advanced** to view all configuration parameters.

The following table describes the properties that you can enter for Databricks Parameters:

Parameter	Description
Lineage from Unity	Select one of the following metadata extraction options for Databricks Unity Catalog: - Disabled. Default option. Doesn't extract lineage from Unity Catalog. - Enabled for filtered assets. Extracts lineage from assets selected in filter conditions. For external tables included in the input filter, the lineage extends to or from the source file on which the external table was created. For assets not selected in the filter conditions, reference assets are created. - Enabled for all assets. Extracts complete lineage including referenced resources. As Databricks Unity Catalog provides lineage details one step at a time, you can only retrieve a single step for each asset. To show the full end-to-end flow, you must include every technical asset in the lineage path.
Notebooks Workspace Path	Absolute path to the Databricks Notebooks that you want to extract on the remote workspace host.
Extract Tags	Specify whether you want to include tags assigned to the objects that you extract.
Notebooks Python Modules Path	Advanced parameter. The absolute path to the Python user modules of Databricks Notebooks located on the Secure Agent machine.
Databricks Environment Initialization File Path	Advanced parameter. The absolute path to the Python code file that defines the mount points and other environment properties related to the Databricks source. Specify the file path to resolve mount points when you extract metadata from the Databricks source.
Python Default Variables Values	Python default variable values for Databricks notebooks. Use `[VARIABLES]`, `[FUNCTIONS]`, or `[GLOBAL]` sections in the form of [SECTION NAME] before you specify a variable.
Notebooks Preload Paths	Advanced parameter. The paths to the Databricks workspace folders with the notebooks that you want to preload. The paths are relative to the Notebooks Workspace Path. If you don’t enter any paths, all the notebooks added in **Notebook Workspace Path** parameter get preloaded.

The following table describes the properties that you can enter for Databricks Volumes Parameters:

Property	Description
Extract Group Elements from Hierarchical Files	Select one of the following options to extract group or leaf elements from hierarchical files: - Yes. Extracts group elements from hierarchical files with the complete hierarchy of hierarchical fields. You can view the hierarchy of hierarchical files in the **Hierarchy** tab of assets in Data Governance and Catalog. - No. Extracts only leaf elements from hierarchical files without the complete hierarchy of hierarchical fields. You can extract group elements from hierarchical files for the following file types: - AVRO. Extracts and groups hierarchical files and hierarchical fields. - Parquet. Extracts and groups hierarchical files and hierarchical fields. - JSON. Extracts and groups hierarchical files and hierarchical fields. - XML. Extracts and groups elements and attributes. For XML file types, a maximum depth of 1000 elements is permitted within a single element in the hierarchy. - XSD. Extracts and groups elements and attributes. **Attention:** If you modify the **Extract Group Elements from Hierarchical Files** field and run the catalog source again, the asset page doesn't display the hierarchical elements in the correct hierarchy groups. If you modify the property value, purge the catalog source before you run it again.
Enable Extension-Based File Type Detection	Select one of the following options to detect file types by file extensions or by parsing the file contents: - Yes. Detects file types by file extensions. - No. Parses the file contents to detect file types. **Note:** You can detect file types by file extensions for the following file types: - CSV - TSV - TXT - XML
Use First Row as Header of Delimited Files	Select one of the following options to use the first row as the header or detect headers automatically for delimited files: - Yes. Detects column headers based on the following rules: - Duplicate headers get suffixed with '#' followed by a number, for example, ABC#1, ABC#2. The detection is not case-sensitive. - Empty column header values appear as UnknownColumn<position>, for example UnknownColumn2. - The header row in the file is detected even if it has a different number of columns than the data rows. - No. Detects headers automatically for delimited files.
Headers of Delimited Files	Specify values to determine headers of delimited files. Separate multiple values by commas. If any value from the list is found in the first row of the delimited file, then the first row is used as the header. **Note:** This parameter appears only if you choose No for the **Use First Row as Header of Delimited Files** parameter.
Treat Files Without Extension As	Select one of the following options to identify files without an extension: - Parquet - Avro - JSON

Property	Description
Enter File Delimiter	Specify the file delimiter if the file from which you extract metadata uses a delimiter other than the following list of delimiters: - Comma(,) - Horizontal tab (\t) - Semicolon (;) - Colon (:) - Pipe symbol (|) Enclose the delimiter in single quotes, such as '$'. Use a comma to separate multiple delimiters. **Note:** Adding a custom delimiter overrides the default list of delimiters. If you specify a delimiter, characters from the default list are not considered as delimiters.
Files to be excluded during partition discovery	Specify the regular expression of the files that you want to exclude during partition discovery. Enclose each regular expression in double quotes such as, ".*json","Customer.csv","Parquet.*". Use a comma to separate multiple regular expressions.
Treat Unrecognized Files As	Choose how to handle files with unrecognized formats during metadata extraction. Select one of the following options: - Structured files. Treats all files with unrecognized formats as structured files. - Unstructured files. Treats all files with unrecognized formats as unstructured files.
Unrecognized Files Override	Enter one or more file paths as exceptions to override whether the specific unrecognized files should be treated as structured or unstructured files. You can use the path-based overrides to apply different treatment rules to different files within the same catalog source.

The following table describes the properties that you can enter for Databricks Volumes Partitioned File Configuration:

Property	Description

Custom Partition Detection Configuration File	Select a configuration file in the JSON format to specify the pattern of the non-hive style custom partitions in your source system.
	Note: The system automatically detects partitions if the date format of the partition key is in any of the following formats:
	- dd-MM-yy
	- dd-MM-yyyy
	- dd-MMM-yyyy
	For example, the system interprets dd-MM-yyyy as the partition format and extracts `Customer` as a hierarchical file instead of a folder in the following partition pattern:
	`Customer`
	`|__01-01-2022`
	`|  |  |__ dataFile1.parquet`
	`|  |  |__ dataFile2.parquet`
	`|  |  |__ ...`
	`|__02-02-2022`
	`|__...`
	The system doesn't automatically detect partitions with other patterns, such as MM-dd-yyyy. If the pattern is different, you need to define it in JSON format. For example, `{"CustomPartitionPatterns": ["MM-dd-yyyy"]}`
	To detect the epoch time format, define it in JSON format as:
	`{"CustomPartitionPatterns": ["@"]}`

Partitioned Pruning Configuration Options	Select a configuration file in the JSON format. In the file, specify additional information to identify partitions for determining the relevant schema in your source system.
Enable Partition Detection	Select **Yes** or **No**.
Enable Partition Pruning	Select **Yes** or **No**.

The following table describes the property that you can enter for additional settings:

Note: The **Additional Settings** section appears when you click **Show Advanced**.

Property	Description
Expert Parameters	Enter additional configuration options to be passed at runtime. Required if you need to troubleshoot the catalog source job. **Caution:** Use expert parameters when it is recommended by Informatica Global Customer Support.

5. Click each tab to enable and configure additional capabilities for the catalog source.

Python default variables values

Provide Python default variables values when your script uses values that are not defined in the code.

Ensure that the Python default variables values include either both `VARIABLES` and `FUNCTIONS` sections or a `GLOBAL` section.

To escape special characters such as `\n` or `\t`, use the backslash (\). For example, to define `E:\file\tgtParameterized.csv`, enter `E:\\file\\tgtParameterized.csv`

Variables

Use the following syntax: `<VariableName>=<VariableExpression>`

Note: A variable name doesn't require quotes if it contains only standard alphanumeric characters. If a variable name contains special characters, use double quotes.

A sample variable section can have the following structure:

```
[VARIABLES]
a = 42
b = 7
c = a < b ? a + 7 : b - 7 // It's 49
d = e(1,2) + 1 // Expression use call to function.
"User::table" = 'table' || "User::tableSuffix" // It's a string table concatenated with
the value of User::tableSuffix variable
```

Functions

Use the following syntax: `<FunctionCallSignature>=<FunctionExpression>`

Consider the following rules and guidelines when you define functions:

- A function name doesn't require quotes if it contains only standard alphanumeric characters.
- Enclose a function name in double quotes if it contains special characters.
- Define the list of arguments within parentheses.
- Use a question mark for each function argument.
- Ensure that arguments consist of question marks separated by commas.

A sample function section can have the following structure:

```
[FUNCTIONS]
a(?) = 1
a(?,?) = 2
b(?) = a(1) + 1 // Expression use call to another function.
c(?,?) = d + 2 // Expression use reference to variable.
```

You can provide additional sections to match functions. To match an overloaded function, provide placeholders for its arguments. You can also reference matched function arguments inside the matched section.

A sample custom function section can have the following structure:

```
[host.db.schema.func(x)]
z=x
[host.db.schema.func(x,y)]
z=x+y
```

The following table describes the functions that you can use:

Function	Description
Hash(str, maxOutputLen)	Applies the Message Digest Algorithm 5 (MD5) to an input string and produces a hash value. You can specify the length of the hash value. For example: `Hash('abcdefgh', 4) -> 'E8DC'` 'E8DC' is the result that you get in MD5 hashing algorithm application for the input string 'abcdefgh' with a specified hash length of 4 characters.
Replace(str, from, to)	Replaces a string with another string. For example: `Replace('abc', 'b', 'D') -> 'aDc'` The function replaces the single occurrence of the substring 'b' in the input string 'abc' with the string 'D' and creates the modified string 'aDc'.

ReplaceRegexp(str, regex, replacement)	Replaces the strings that you specify with Java regular expressions. For example:
	`- ReplaceRegexp('abcde', 'b.*', 'f') -> 'af'`
	`- ReplaceRegexp('graph_id20', 'id(\d+)', '$1') -> 'graph_20'`
	In the first example, the substring 'bcde' matches the regular expression pattern 'b.*'. The function replaces the matched substring with the replacement string 'f'. As a result, the modified string returned by the function is 'af'.
	In the second example the substring 'id20' matches the regular expression pattern 'id(\d+)'. The function replaces the entire matched substring with the captured digits '20'. As a result, the modified string returned by the function is 'graph_20'.

StringLengthLimit(str, limit, hashSize)	Limits the length of the input string based on a specified limit. If the length of the string exceeds the limit, the function appends a hash of the remaining characters using the Hash function, where 'hashSize' specifies the size of the hash.
	For example:
	`- StringLengthLimit('abcc', 3, 2) -> 'a26'`
	`- StringLengthLimit('abcc', 4, 2) -> 'abcc'`
	In the first example, the input string 'abcc' is longer than the specified limit of 3 characters and it is truncated to 'a'. The remaining characters are replaced with the hash value '26'.
	In the second example, the function does not modify or truncate the input string because its length matches the specified limit of 4 characters. The function returns the original string 'abcc'.

StringLengthLimit(str, limit)	Limits the length of the input string based on the specified limit. If the length of the string exceeds the limit, the function appends a hash of the remaining characters using the Hash function with a default hash size of 8 characters. For example: `StringLengthLimit('abcdabcdabcd', 10) -> 'abE340600C'` In this example, the function limits the length of the input string 'abcdabcdabcd' based on the specified limit of 10 characters.
RegexpMatch(pattern, str)	Tests whether the input string matches a specified pattern. For example: `RegexpMatch('[A-Za-z]+','Abcd') -> TRUE` In this example, the function returns 'TRUE' because the input string 'Abcd' contains alphabetic characters that satisfy the pattern of one or more occurrences of alphabetic characters specified by [A-Za-z]+.
Upper(str)	Converts the characters in a given input string to uppercase. For example: `Upper('Abc') -> 'ABC'`
Lower(str)	Converts the characters in a given input string to lowercase. For example: `Lower('aBC') -> 'abc'`

Function	Description
Date(text,format)	Returns objects that represent a date in a specified format. For example: `Date('2017-10-31', 'yyyy-MM-dd')` **Note:** The function follows the conventions and patterns provided by the SimpleDateFormat class in Java 8.
Contains/ ContainsIgnoreCase(stack, needle)	Checks if a given "needle" string is present within a "stack" string. Examples: - Contains('abc', 'ab') -> TRUE - Contains(' abc', 'AB') -> FALSE - ContainsIgnoreCase(' abc', 'AB') -> TRUE - Contains('stack', 'needle') -> FALSE In the examples, `TRUE` means that the function contains a given substring and `FALSE` means that it doesn't.

Global

You can use a `GLOBAL` section. It contains both variables and function definitions. If you use a `GLOBAL` section, don't add the `VARIABLES` or `FUNCTIONS` sections.

Use the following syntax: `DefaultVariable = 'DefaultValue'`

Note: A sample global section can have the following structure:

```
[GLOBAL]
Table = 'DefaultTable'
a = 42
b = 7
c = a < b ? a + 7 : b - 7
d = e(1,2) + 1a(?) = 1
```

Note: A variable name doesn't require quotes if it contains only standard alphanumeric characters. If a variable name contains special characters, use double quotes.

Simple expression

Use the Simple Expression Language to define a value for a variable or a function call. The Simple Expression Language allows you to use values from already defined variables and functions, as well as variables from the current job context.

You can use the following case-sensitive literals:

- Integer: `42`
- String: `'str'`
- String with quoted single quote: `'str\''`
- Boolean: `true`, `false`

You can use the following features and functionalities of the Simple Expression Language:

- Equals: `42 == 7 -> FALSE`
- Non equals: `42 != 7 -> TRUE`
- Concatenations: `'str1' + 'str2' -> 'str1str2'`
- Function calls: `Replace('abc', 'b', 'd') -> 'adc'`

- Ternary operators:

```
- 42 == 7 ?'a ' :'b' -> 'b'
- 42 != 7 ?'a ' :'b' -> 'a'
```

Supported comment types

Use comments to provide additional information about Python default variables values. You can use the following comment types:

- `Single line: // comment`
- `Multi line: /* comment */`

Note: Comments don't affect the job.

Configure data profiling and quality

Enable the data profiling capability to evaluate the quality of metadata extracted from the Databricks source system.

1. Click the **Data Profiling and Quality** tab.
2. Expand **Data Profiling** and select **Enable Data Profiling**.

   Note: Ensure that you have permissions on all the staging connections that you use in your data profiling configuration. You can't run the job if you don't have permissions on the connections that you use. Select connections that you have access to, or ask the administrator to grant the necessary permissions on the connections that you want to use.
3. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
4. Optionally, in the **Filters** area, specify additional filters in addition to metadata filters:
   a. Select **Yes**.
   b. From the Include/Exclude list, choose to include or exclude metadata based on the filter parameters.
   c. From the Object type list, select **Catalog.Schema**.
   d. Enter the path to the object as the filter value.

      Examples:

      - You extracted metadata from all objects from the 'Schema1' schema in the 'Catalog1' catalog and now you want to run a profile on the 'Table1' table in the schema. Select Table from the Object type list and then enter the catalog name followed by the schema name and the table name in the input field. For example, Catalog1.Schema1.Table1
      - You extracted metadata from all objects from a schema and now you want to run a profile on multiple tables in the schema. Select Table from the Object type list. Click Select and then enter the catalog name, schema name and table name separated by dots. Click Add to enter additional tables.

      To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.
5. In the **Parameters** area, configure the parameters.

The following table describes the parameters that you can enter:

Parameter	Description
Modes of Run	Determine the type of data that you want the data profiling task to collect. Choose one of the following options: • Keep signatures only. Collects only aggregate information such as data types, average, standard deviation, and patterns. • Keep signatures and values. Collects both signatures and data values.
Profiling Scope	Determine whether you want to run data profiling only on the changes made to the source system since the last profile run or on the entire source system. Choose one of the following options: • Incremental. Runs the profile only on the changed or updated metadata in the source system since the last profile. • Full. Runs the profile on the entire metadata that is extracted based on the filters applied for extraction.
Sampling Type	All Rows. Runs the profile on all rows in the metadata. Custom Query. Runs the profile on a specified percentage of rows. For example, **TABLESAMPLE (BUCKET 10 OUT OF 50)**, **TABLESAMPLE (5 PERCENT)**, **LIMIT 2**, or **TABLESAMPLE (5000 ROWS)**.
Maximum Precision of String Fields	The maximum precision value for profiles on string data type.
Text Qualifier	The character that defines string boundaries. If you select a quote character, profiling ignores delimiters within the quotes. Select a qualifier from the list. Default is **Double Quote**.

6. Optionally, enter additional settings.

   The following table describes the property that you enter for additional settings:

Property	Description
Expert Parameters	Enter additional configuration options to be passed at runtime. Required if you need to troubleshoot the catalog source job. **Caution:** Use expert parameters when it is recommended by Informatica Global Customer Support.

7. Expand **Data Quality** and select **Enable Data Quality**.

   Note: You can click **Use Data Profiling Parameters** to use the same parameters as in the **Data Profiling** section.

   Note: Ensure that you have permissions on all the staging and flat file connections that you use in your data quality configuration. You can't run the job if you don't have permissions on the connections that you use. Select connections that you have access to, or ask the administrator to grant the necessary permissions on the connections that you want to use.

8. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
9. In the **Parameters** area, configure the parameters.

   The following table describes the parameters that you can enter:

Parameter	Description
Data Quality Rule Automation	Enable the option to automatically create or update rule occurrences for data elements in the catalog source. Choose one of the following options: • Apply on Data Elements linked with Business Dataset. Creates rule occurrences for all data elements that are linked with business data sets in the catalog source. • Apply on all Data Elements. Creates rule occurrences for all data elements in the catalog source.
Data Quality Remediation	Enable the option to specify a flat file connection to store the list of failed rows so that users can remediate poor data quality scores. Choose one of the following options: • **No**. Doesn't enable the **Create Data Quality Failure Ticket** option. • **Yes**. Shows a list of flat file connections where you write failed rows to customer-managed locations.
Data Quality Failure Ticket	Specify whether you want to create data quality failure tickets for poor data quality scores based on the threshold defined for the rule occurrence in Data Governance and Catalog. Choose one of the following options: • **No**. Doesn't automatically create data quality failure tickets when the data quality scores are poor. • **Yes**. Automatically creates data quality failure tickets based on the data quality threshold values you define in Data Governance and Catalog, and notifies you when a data quality score is below the threshold. **Note:** You must configure a workflow event for the data quality failure and enable the event in Metadata Command Center.
Cache Result	Specify how you want to preview the rule occurrence results. Select **Agent Cache** if you want to generate a cache file in the runtime environment and to preview the cached results faster in subsequent data preview runs. The results are cached for seven days by default after the first run in the runtime environment. Select **No Cache** if you don't want to cache the preview results and view the live results.
Run Rule Occurrence Frequency	Specify whether you want to run data quality rules based on the frequency defined for the rule occurrence in Data Governance and Catalog.
Sampling Type	All Rows. Runs the data quality task on all rows in the metadata. Custom Query. Runs the data quality task on a specified percentage of rows. For example, **TABLESAMPLE (BUCKET 10 OUT OF 50)**, **TABLESAMPLE (5 PERCENT)**, **LIMIT 2**, or **TABLESAMPLE (5000 ROWS)**.

Parameter	Description
Maximum Precision of String Fields	The maximum precision value for profiles on string data type.
Text Qualifier	The character that defines string boundaries. If you select a quote character, the data quality task ignores delimiters within the quotes. Select a qualifier from the list. Default is **Double Quote**.

10. Optionally, enter additional settings.

    The following table describes the property that you enter for additional settings:

Property	Description
Expert Parameters	Enter additional configuration options to be passed at runtime. Required if you need to troubleshoot the catalog source job. **Caution:** Use expert parameters when it is recommended by Informatica Global Customer Support.

Configure data observability

Enable the data observability capability to receive anomaly notifications for metadata extracted from the source system.

To include profiling anomalies, enable data profiling for the catalog source. For accurate results, set the **Profiling Scope** option to **Full** in the **Data Profiling and Quality** configuration.

1. Click the **Data Observability** tab.
2. Select **Enable Data Observability**.
3. In the **Parameters** area, enter a value to specify the minimum number of catalog source job runs required to start detecting anomalies. For example, if you enter a value of 5, then the job starts to detect anomalies from the sixth run.

   Note: This option does not apply to anomalies that require a minimum of two runs to generate.
4. Specify the maximum number of anomaly events to generate for each catalog source run. Default is 1000.
5. Optionally, in the **Asset Filters** area, enable filters to run data observability on specific assets.

   Specify data profiling filters if you want to override the data profiling filter and extract profiling anomalies for assets based on a different filter.
6. To add a data profiling filter, perform the following steps:
   a. Select **Yes** to view filter options.
   b. From the **Include/Exclude** list, choose to include or exclude metadata.
   c. From the **Specify data profiling filters** list, select an object type.
   d. Enter a value to specify the object location.

      For example, you ran a profile on multiple schemas, and now you want to generate profiling anomalies on a specific schema. Enter the schema name in the input field.
   e. To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.

7. Optionally, in the **Metric Filter** area, specify filters to generate events based on specific metrics. If you don't include a filter, the job detects both profiling and other anomalies applicable to the catalog source.
   a. Select **Filter conditions**.
   b. From the **Include Metric** list, choose to include or exclude a metric.
   c. From the **All Metrics** list, select a metric for which you want to generate events.
   d. From the **Sensitivity** list, select the sensitivity of the anomaly.
   e. From the **Select detection rules** list, select rules that you apply to detect anomalies.

      The following table describes the detection rules that you can select:


Option	Description
Static Data	Detects the following anomalies: - Percentage variation. If percentage values other than 0% or 100% remain constant for three or more profile runs, any subsequent change generates a Percentage Variation anomaly. - Count variation. A change in a value that is usually constant indicates that there is an anomaly.
100% or 0% Change Detection	Detects the following anomalies: - Drop from maximum. A drop from 100% to a lower value generates a Drop from Maximum anomaly. - Surge from minimum. A spike from 0% to any higher value generates a Surge from Minimum anomaly.
Standard Deviation	Detects the following anomalies: - Drop in transition. A drop from a value that has been decreasing at a constant rate to a significantly lower value generates a Drop in Transition anomaly. - Surge in transition. A spike from a value that has been increasing at a constant rate to a significantly higher value generates a Surge in Transition anomaly. - Deviation. If the percentage values of a record change with each profile run, the algorithm calculates an expected range based on the changes observed in each profile run. A new value that falls outside of this expected range generates a Deviation anomaly.
Breaking Trends	Detect the following types of count-based anomalies: - Drop. A drop in a value that has been increasing to a lower value generates a Drop anomaly. - Surge. A spike in a value that has been decreasing to a higher value generates a Surge anomaly.

Configure data classification

Enable the data classification capability to identify and organize data into relevant categories based on the functional meaning of the data.

1. Click the **Data Classification** tab.
2. Select **Enable Data Classification**.
3. Choose one of the following options:
   - **Generated Data Classifications**. CLAIRE automatically generates data classifications for the data elements.

- **Data Classification Rules**. Choose from predefined or custom data classifications.
  1. Click **Add Data Classification**. The **Select Data Classifications** dialog box appears.



  2. Select the data classifications that you want to use.
  3. Click **OK**.

Configure relationship discovery

Enable the relationship discovery capability to identify pairs of similar columns and relationships between tables within a catalog source.

Before you configure relationship discovery, you need to import a relationship inference model. For more information about importing a relationship inference model, see " Import a relationship inference model" on page 21.

1. Click the **Relationship Discovery** tab.
2. Select **Enable Relationship Discovery**.
3. In the **Column Similarity** area, select the **Relationship Inference Model**.

   The relationship inference models that you imported appear in the **Relationship Inference Model** field.
4. Specify the **Confidence Score Threshold** that indicates whether the predictions made by the model for column similarity are acceptable. Specify a score from 0 to 1 to set a threshold limit. If the score is higher than the specified limit, Metadata Command Center automatically assigns a matching glossary term to the data element.

   Note: A **Confidence Score Threshold** lower than 0.4 might result in a large number of false positives.
5. In the **Joinable Tables Relationship** area, specify the **Containment Score Threshold** to identify joinable table relationships within the catalog source. This score is an indicator of the data overlap between any two given columns which determines whether the tables are joinable.

   A higher score means that the data in the objects is more similar and a lower score means lesser overlapping data between the two objects. A **Containment Score Threshold** lower than 0.4 might result in a large number of false positives.

Configure glossary association

Enable the glossary association capability to associate glossary terms with technical assets, or to get recommendations for glossary terms that you can manually associate with technical assets in Data Governance and Catalog.

Metadata Command Center considers all published business terms in the glossary while making recommendations to associate your technical assets.

1. Click the **Glossary Association** tab.
2. Select **Enable Glossary Association**.
3. Select **Enable auto-acceptance** to automatically accept glossary association recommendations.
4. Specify the **Confidence Score Threshold for Auto-Acceptance** to set a threshold limit based on which the glossary association capability automatically accepts the recommended glossary terms.

   Note: Specify a percentage from 80 to 100. If the score is higher than the specified limit, the glossary association capability automatically assigns a matching glossary term to the data element.
5. Select **Enable Below-threshold Recommendations** to receive glossary association recommendations below the auto-acceptance threshold. If you enable auto-acceptance, you can enable below-threshold recommendations to receive glossary recommendations below the auto-acceptance threshold.
6. Specify the **Confidence Score Threshold for Recommendations** to set a threshold based on which the glossary association capability makes recommendations

   If you enable auto-acceptance, specify a percentage from 80 to the selected auto-acceptance threshold. You can accept or reject the recommended glossary terms that fall within this range in Data Governance and Catalog.

   If you disable auto-acceptance, specify a percentage from 80 to 100 inclusive.
7. Choose to automatically assign business names and descriptions to technical assets. You can then choose to retain existing assignments and only assign business names and descriptions to assets that don't have assignments, or allow overwrite of existing assignments.

   By default, existing assignments are retained.
8. Optional. Choose to ignore specific parts of data elements when making recommendations. Select **Yes** and enter prefix and suffix keyword values as needed.

   Click **Select** to enter a keyword. You can enter multiple unique prefix and suffix keywords. Keyword values are case insensitive.
9. Optional. Choose specific top-level business glossary assets to associate with technical assets. Selecting a top-level asset selects its child assets as well. Select **Top-level Glossary Assets** and specify the assets on the **Select Assets** page.
10. Optional. Choose to use abbreviations and synonym definitions from lookup tables for accurate glossary association. Select **Yes** to enable, and then click **Select** to upload a lookup table.
11. Click **Next**.

    The **Associations** page appears.

Configure automation

Enable the lineage discovery and autonomous enrichment capabilities to build complete lineage using CLAIRE and to receive enrichments propagated from catalog sources connected through lineage.

Enable Lineage-based Propagation on the Autonomous Enrichment tab of the Configure page before you configure this catalog source to receive enrichments. For more information, see *Administration*.

With the lineage-based propagation settings on this tab, you configure how this catalog source receives enrichments propagated from connected catalog sources. Enrichments propagate only to assets that don't already have enrichments.

1. Click the **Automation** tab.
2. In the **Lineage Discovery** section, select **Enable Lineage Discovery**.
3. In the **Filters** area, define one or more filter conditions to apply for lineage discovery.

   To define filters, you can choose to select catalog source types, asset groups, or enter a catalog source name or search from a list of catalog sources.

   a. Select **Yes** to view filter options.


   b. From the Include/Exclude list, choose to include or exclude catalog sources for lineage discovery based on the filter parameters.

   c. From the filter type list, select catalog source type, catalog source name, or asset group.

   d. In the filter value field, select the required catalog source types, or click the Search button and select catalog sources or asset groups.

      Filters can contain the asterisk wildcard to represent multiple characters or empty text.

      The filter options appear.



      Examples:

      - To include or exclude all Oracle catalog sources, select **Catalog Source Type** as the filter type and select `Oracle` in the filter value field.
      - To include or exclude the 'Oracle_Retail' catalog source, select **Catalog Source Name** as the filter type and search for the catalog source or enter `Oracle_Retail` in the filter value field.
      - To include or exclude all catalog sources with names that start with 'Oracle', select **Catalog Source Name** as the filter type and search for the catalog source or enter `Oracle*` in the filter value field.
      - To include or exclude all catalog sources with names that end with 'Retail', select **Catalog Source Name** as the filter type and search for the catalog source or enter `*Retail` in the filter value field.
      - To include or exclude all catalog sources with names that contain 'Ret', select **Catalog Source Name** as the filter type and search for the catalog source or enter `*Ret*` in the filter value field.
      - To include or exclude all catalog sources that are part of the 'Financial Group' asset group, select **Asset Group** as the filter type and search `Financial Group` in the filter value field.

      Note: You can't add more than one include or exclude filter for the same filter type.

   e. Optionally, to define an additional filter with an AND condition, click the **Add** icon.

4. In the **Autonomous Enrichment** section, select **Enable Lineage-based Propagation**.

   The lineage-based propagation settings appear.

5. Select the enrichment types to receive from connected catalog sources.

   You can select Classification, Description, Business Name, and Glossary Term.

6. Choose how to apply received enrichments.
   - Select **Auto-accepted** to apply received enrichments automatically.
   - Select **Recommended** to list them as suggestions that you can curate in Data Governance and Catalog.
7. Choose whether to receive enrichments only from certified assets.

   Assets are certified in Data Governance and Catalog. This option is selected by default. If you clear it, this catalog source also receives enrichments from assets that are not certified, which might be less reliable.
8. Choose where this catalog source receives enrichments from.
   - Select **Catalog Source** to receive enrichments from a specific catalog source.
   - Select **Nearest Neighbor** to receive enrichments from the closest connected catalog source based on lineage.
9. If you select **Catalog Source**, select a catalog source from the list.

   Ensure that the catalog source you select is within 15 lineage hops. Enrichments don't propagate from a catalog source beyond that distance.
10. If you select **Nearest Neighbor**, configure the lineage settings:
    a. Set **Lineage Direction** to search upstream, downstream, or in both directions.

       Upstream catalog sources feed data into this catalog source. Downstream catalog sources receive data from this catalog source. Select both directions to search upstream and downstream at the same time.

    b. Set **Number of Hops** to define how far along lineage to search.

       The search stops at the first connected catalog source that has enrichments, up to a maximum of 15 hops.
11. Click **Save**.

When you save, the catalog source begins receiving enrichments created from that point onward. Saving doesn't retrieve enrichments created prior to this date and time. To receive such enrichments, run the catalog source job manually and include the Autonomous Enrichment capability.

Step 3. Associate stakeholders and asset groups

Associate users or user groups within a stakeholder role as stakeholders for technical assets in Data Governance and Catalog. Also, you can choose to assign technical assets extracted from the catalog source to asset groups. You can then use access policies to control permissions on assets that are assigned to asset groups.

Verify that the administrator assigned users and user groups to the stakeholder role that you want to associate with technical assets.

1. To associate users or user groups as stakeholders with technical assets extracted from the catalog source, perform the following steps:
   a. On the **Associations** page, click **Stakeholders**.
   b. Select **Assign Stakeholders**.

c. Select **Propagate to Child Assets** to propagate stakeholders of a parent asset to child assets without stakeholders.

d. Select **Append Stakeholders** to propagate stakeholders of a parent asset to all child assets including assets with stakeholders assigned.


Note: To enable **Append Stakeholders**, you must enable **Propagate to Child Assets**.

You can also override the propagation settings from the catalog source page in Data Governance and Catalog. For more information about stakeholder propagation, see *Stakeholder Propagation* in *Administration*.

e. Select a stakeholder role.

f. Click **Select** to add users and user groups from the stakeholder role as stakeholders for the technical assets.

The **Add Users & User Groups** dialog box displays a list of users and user groups assigned to the selected stakeholder role.



g. Select one or more users or user groups to assign as stakeholders for the technical assets, and click **OK**.

Only the selected users and user groups belonging to the specified stakeholder role are granted the permissions to technical assets.

h. To assign users or user groups from another stakeholder role, click **Add** and then repeat the steps.

2. To assign asset groups to technical assets extracted from the catalog source, perform the following steps:

a. On the **Associations** page, click **Asset Groups**.


b. Select **Assign Asset Groups**.

c. Click **Select**.

The **Select Asset Groups** dialog box displays the list of asset groups.

If you enabled an access policy that includes an asset group, you can only view assets that belong to that asset group.

3. Select the asset groups to which you want to assign technical assets extracted from the catalog source, and click **OK**.



4. Choose to save and run the job or to schedule a recurring job.
   - To save and run the job, click **Save** and then **Run**.
   - To schedule a recurring job, click **Next** to open the **Schedule** page.

Step 4. Run or schedule the job

Choose to run a catalog source job manually, or configure it to run on schedule.

Note: You can't run multiple jobs simultaneously.

You can choose to perform a full or an incremental metadata extraction. A full metadata extraction extracts all objects from the source to the catalog. An incremental metadata extraction extracts only the changed and new objects since the last successful catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable.

When you run an incremental metadata extraction job with a filter to include metadata from objects, the job extracts only the objects that have the latest timestamp since the last successful job.

Note: If incremental metadata extraction is available for the catalog source, the option is always visible, but incremental metadata extraction jobs can run only after a scheduled full metadata extraction job. Manual jobs do not enable the incremental metadata extraction option.

Run the job manually

Click **Save** to save the catalog source and click **Run**. On the **Run Catalog Source Job** window, click **Run** to run the job.

You can override the capabilities that you selected while configuring your catalog source on the **Configuration** page. The first time you run the catalog source job, the metadata extraction capability is mandatory. From the second run onwards, you can choose to override the configured metadata change option. You can retain, delete, or deprecate objects that are deleted from the source in the catalog. For subsequent runs of the catalog source job, the metadata extraction capability is optional.

Note: You can choose incremental metadata extraction for subsequent runs only after one full metadata extraction job completes successfully. Incremental metadata extraction jobs run with the **Retain** metadata change option even if you set the option to **Delete** or **Deprecate** in the catalog source.

Note: To run a catalog source job, you need permissions on the connection to the source system. To run a catalog source job for catalog sources that reference other source systems, you need permissions on the connections for all the reference source systems.

Run the job on a schedule

You can choose to run metadata extraction and other capabilities on a recurring schedule. You can't choose incremental metadata extraction and full metadata extraction in the same schedule. To create a schedule for incremental metadata extraction, you must have completed at least one full metadata extraction job successfully. If not, first create a schedule for a full metadata extraction.

If an incremental metadata extraction is scheduled to run when the last run details aren't available, the job first performs a full metadata extraction, followed by incremental metadata extraction on subsequent runs.

For example, this can happen in the following scenarios:

- You create schedules for both incremental metadata extraction and full metadata extraction, but schedule the incremental extraction to run before the first full metadata extraction job.
- You create schedules for both incremental metadata extraction and full metadata extraction, but delete the full metadata extraction schedule before its first run.

1. On the **Schedule** tab, select **Run on Schedule**.
   The **Schedule** configuration page opens.
2. Click the checkbox corresponding to each capability that you want to include in the schedule.
3. Enter the start date, time zone, and the interval at which you want to run the job.
4. You can manage additional schedules using the following options:
   - To create a new schedule, click the **Add** button.
   - To delete a schedule, click the **Delete** button.
   - To enable or disable a schedule, click the **Enable Schedule** toggle button.

   Note: You can create a maximum of one schedule per capability that you enable. If you purged a catalog source or did not run the metadata extraction job, the catalog source job runs metadata extraction before running other scheduled capabilities.

   Note: To create a schedule, you need permissions on the connection to the source system. If you lose permissions on the connection after you create a schedule, the scheduled jobs continue to run.
5. Click **Save** to save the schedule.

Monitor job status

After the job runs, you can monitor the status of the job on the **Overview** page of the job.

For more information about job monitoring, see *Administration*.

Step 5. Assign reference catalog source connections to endpoint catalog source objects

When you run the catalog source job, if the catalog source references another source system, a reference catalog source and connection get created that point to the reference source system. To view the complete

lineage for your catalog source, you can perform connection assignment from the reference catalog source connection to the objects in the reference source system. A reference source system might be a database, such as Databricks.

Before you assign a connection, ensure that you have created and run an endpoint catalog source for each reference source system.
Note: If the source schema contains case-sensitive tables or if the reference objects contain multiple objects with the same name in different cases, perform case-sensitive connection assignment to get correct lineage.

If you enabled the lineage discovery capability for your catalog source, you can either curate the CLAIRE recommended endpoint objects on the **Related Catalog Sources** tab or assign connections manually.

For more information about related catalog sources and lineage discovery, see *Lineage discovery* in the *Administration* help.

1. On the **Configure** page, select the **Lineage** tab, and then select the **Lineage Discovery** tab. On the **Catalog Sources** panel, select the required catalog source and click the **Assign Connections** tab.

   The **Assign Connections** tab displays a list of assigned and unassigned connections along with details for each connection. Use filters to view the connections based on the connection names. Click the **Add Filter** menu to add filters.

2. Select the connection to the reference source system and click **Assign**.

   The connection name appears prefixed to the reference catalog source name on the **Hierarchy** tab of your catalog source in Data Governance and Catalog.

   The **Assign Connection** dialog box appears with a list of recommended objects from the endpoint catalog sources. Click **All** to view all endpoint catalog source objects.

3. In the **Assign Connections** dialog box, select one or more objects from the endpoint catalog sources and click **Assign**.

   You can filter the list in the **Assign Connections** dialog box by name, type, or endpoint.

   When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the lineage that you view in Data Governance and Catalog.

   You can connect to the following source system:

   - Amazon S3
   - Microsoft Azure Data Lake Storage Gen2
   - Databricks
   - Microsoft Azure Synapse Data Warehouse
   - Oracle

   To assign connections to a catalog source, the target catalog source must belong to the Database class type.

4. Run the catalog source job again. If you configured the catalog source job to run on a regular schedule, the next scheduled run picks up the updated details. If you didn't configure a schedule, run the catalog source job again to view complete lineage.

When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the lineage that you view in Data Governance and Catalog.

CHAPTER 4

View results in Data Governance and Catalog

After Metadata Command Center runs a job, you can view the results in Data Governance and Catalog where the catalog source and its elements are called technical assets. You can view a catalog source as a hierarchy. Expand each technical asset to see its components.

When referenced source systems are connected to a catalog source, you can expand the hierarchy to see details about the technical asset's component elements.

You can view the data lineage of an asset contained within a catalog source to see individual elements such as data sources, calculations, and filters. When you view data lineage, you can see the individual upstream elements that contribute data or expressions to each component of a data flow or catalog source.

View metadata extraction results


After a job runs in Metadata Command Center, view the results in Data Governance and Catalog. You can view details about source system contents in a hierarchical structure and trace data lineage.

1. Log in to Intelligent Data Management Cloud.

   The **My Services** page appears.

2. Click Data Governance and Catalog.

   The Data Governance and Catalog box appears on the **My Services** page.



3. On the Data Governance and Catalog home page, click the number in the **Technical Assets** panel.


   The **Technical Assets** page opens.

4. Select **Catalog Source** in the **Filter** list.

   The list of catalog sources opens.

5. Search for the catalog source from which you extracted metadata, and click the name.

   The **Overview** tab of the asset opens.



6. View the asset from different perspectives by clicking on the tabs.

   Note: You can view the calculation properties such as expression, control conditions, and calculation complexity on the **Overview** tab of a calculation asset.

   Note: If a new record is added to the source system and you run an incremental metadata extraction job, no objects are extracted because the metadata has not changed. If an incremental metadata extraction job includes a view, the job extracts the corresponding tables even if the tables were extracted in previous runs.


For more information about working with assets, see Working with Assets in *Data Governance and Catalog* help.

View referenced source systems

Drill down into the source systems that are referenced by catalog sources.

1. Browse to the catalog source that you want to view.
2. Click the **Hierarchy** tab to view the catalog source as a hierarchy.
3. Find an asset with the type **Reference Catalog Source**.

   The following image shows an expanded view of a referenced catalog source:



4. Click to expand the referenced source to see its components.

View data lineage

Data lineage is a visual representation of the flow of data across the systems in your organization. Lineage depicts how the data flows from the system of its origin to the system of its destination.

Data lineage views are available for technical assets in the catalog source. You can view lineage at the catalog source, data set, or data element level.

The lineage at the catalog source level shows how data flows from one catalog source to another. The lineage at the data set and the data element levels show how other technical assets such as files or tables contribute to the selected asset.

If linking catalog sources is available for your catalog source, you can use Metadata Command Center to generate data lineage based on rules or by generating automated lineage with CLAIRE. You can choose source and target catalog sources and objects to link and generate lineage.

To determine whether linking catalog sources is available for your catalog source, navigate to the **Configuration** tab of the **Link Catalog Sources** page. The catalog source must appear in the list of source and target catalog sources.

For information about linking catalog sources, see *Link catalog sources* in the Administration help.

View lineage at the catalog source level

The catalog source level shows how data flows from one catalog source to another with the lineage aggregating data from the data set and data element levels.

To view data lineage at the catalog source level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Catalog Source Level**.


View lineage at the data set level

The data set level is a view that shows individual sets of data in the data flow.


To view lineage at the data set level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Set Level**.

Note: To improve wildcard lineage at the directory or file level for Databricks assets, perform connection assignment, and run the Databricks catalog source again. These wildcards can refer to files in Amazon S3 and Microsoft Azure Data Lake Storage Gen2.

The following image shows how the target author_details.parquet file gets data from a Parquet file stored in the Databricks source system before connection assignment:



The following image shows how the target author_details.parquet file gets data from a Parquet file stored in the Databricks source system after connection assignment:




View lineage at the data element level


The data element level displays details of the data set level. At the data element level, you can see the input sources for expressions or commands and calculations or transformations on the data.

To view data lineage at the data element level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Element Level**.

The following image shows how the target AuthorDetails column gets data from the AuthorDetails column of a Parquet file stored in Databricks source system before connection assignment:



The following image shows how the target AuthorDetails column gets data from the AuthorDetails column of a Parquet file stored in Databricks source system after connection assignment:




View data profiling results

When you enable the data profiling task for a catalog source in Metadata Command Center, the system runs a profile to evaluate the quality of the metadata extracted from the source system. The profiling statistics appear in Data Governance and Catalog when you open the technical assets.

The scope of profiling statistics that Data Governance and Catalog displays depends on the data profiling configuration parameters that you set when you configured the catalog source in Metadata Command Center.

The following image shows the data profiling statistics that appear on a column asset page in Data Governance and Catalog:




For more information about data profiling results, see *Asset Details* in the Data Governance and Catalog help.

View data observability results

When you enable data observability for a catalog source in Metadata Command Center, you can view and evaluate the events that it generates in Data Governance and Catalog. These events indicate anomalies identified in the characteristics of the profiled data in your source system.

You can view the events that data observability generates for anomalies identified for catalog sources, technical data sets, and data elements. You can then take appropriate actions for the generated events.
Note: The administrator of the catalog source might have applied filters to the data to narrow down the data elements that are applicable for business users in Data Governance and Catalog. The data for which users receive anomaly notifications depend on the filters that are configured for the catalog source.

The following image shows the open events for a column asset in Data Governance and Catalog:




For more information about data observability results, see *Working With Assets* in the Data Governance and Catalog help.

View classified data

When you add data classification rules to a catalog source in Metadata Command Center, the system identifies the columns and tables that match the rules and displays one or more matched data classifications on the column or table asset pages in Data Governance and Catalog.

The following image shows a column asset page with the inferred data element classifications that match the column data and metadata:



For more information about data classification assets, see *Asset Details* in the Data Governance and Catalog help.


View glossary associations

When you enable the glossary association capability for a catalog source in Metadata Command Center, you can view the accepted glossary assets in Data Governance and Catalog.

The **Overview** tab for a technical asset in the catalog source displays glossary assets in the Accepted and CLAIRE Recommendations sections.

The **Glossaries** panel shows the automatically accepted and CLAIRE® recommended terms.

The following image shows a sample asset page:



APPENDIX A

Managing catalog sources

You can update, copy, delete, purge, and run a catalog source. You can also grant configuration permissions for catalog sources to different roles in your organization.

On the **Catalog Sources** page of the **Explore** page, you can select a catalog source to see its overview and related catalog sources. The **Overview** tab displays the capabilities, filters, stakeholders, asset groups, and schedules enabled for a catalog source. The **Related Catalog Sources** tab displays a list of related catalog sources that are either assigned manually using connection assignment or are curated based on CLAIRE recommendations using the lineage discovery capability. You can view related catalog sources and accept or reject CLAIRE recommendations for catalog sources that are run with the lineage discovery capability.

Cloning a catalog source configuration

You can clone the configuration of a catalog source to create another catalog source with the same configuration.

Note: Cloning doesn't copy the content of the catalog source.

1. In Metadata Command Center, go to the **Explore** page.
2. Select **Catalog Sources** from the menu.
3. You can clone a catalog source in one of the following ways:
   - Hover your mouse over the catalog source that you want to clone and click **Clone** from the **Action** menu.
   - Open the catalog source that you want to clone and click **Clone**.

   Note: By default, the cloned catalog source has the same name suffixed with _Clone. You can change the name if needed.
4. If needed, modify the configuration of the catalog source by updating the parameters on each tab.

   Cloning doesn't copy the content of sensitive fields. If the catalog source contains sensitive fields such as Client Secret, enter the values.
5. Click **Save**.

Deleting or purging a catalog source

Delete or purge a catalog source based on your business requirements.

When you delete a catalog source, you delete all the configuration specific to that catalog source, along with all the metadata that was extracted and any enrichment made to the associated metadata. Purging a catalog source deletes all the metadata that was extracted, along with any enrichment made to the associated metadata.

Note: Before you delete or purge a catalog source, manually unassign the connections that are assigned to that catalog source.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source that you want to delete or purge.
4. Click the **Action** menu, and select **Delete** or **Purge**.

   Note: You can't delete or purge a catalog source if the catalog source job is in the running state.
5. To confirm delete or purge, click **OK**.

   The catalog source is triggered to delete or purge. You can monitor the status of the job on the **Monitor** page.

   Note: If the deletion job succeeds, the catalog source disappears from Metadata Command Center. If it fails, some associated objects might still be present in Data Governance and Catalog. Such catalog sources continue to appear in the list of catalog sources in Metadata Command Center, but are marked as **Deleted**. Delete the catalog sources to remove them along with any remaining objects present in Data Governance and Catalog.

Purging obsolete objects from a catalog source

You can purge obsolete objects from a catalog source.

When you configure or run a catalog source, you can choose to deprecate objects that are deleted from a source system. If you delete objects from the source system or make changes to the filter, the objects imported into the catalog before the change move to the Obsolete lifecycle in the catalog. You can purge obsolete objects from a catalog source. This permanently deletes all objects with the Obsolete lifecycle status, along with associated enrichments, from the catalog.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source from which you want to purge obsolete objects.
4. Click the **Action** menu, and select **Purge Obsolete Objects**.

   A warning message appears on the page.
5. Click **Yes** to confirm.

   A confirmation message appears on the page and the purge job starts. You can monitor the status of the job on the **Monitor** page. If the job succeeds, all obsolete objects present in the catalog source disappear from the catalog.

   Note: If the job fails, some obsolete objects might remain in the catalog. To remove the remaining obsolete objects, run the purge job again.

Curating CLAIRE recommendations

You can view related catalog sources and accept or reject CLAIRE recommendations for a catalog source.

Applicable to catalog sources that generate lineage.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source for which you want to curate CLAIRE recommendations.
4. Hover your mouse over the catalog source and click **View Lineage Discovery** from the **Action** menu.

   Note: The **View Lineage Discovery** option is available for catalog sources that are run with the lineage discovery capability.

   The **Configure** page appears with the catalog source filtered on the **Lineage Discovery** tab of the **Lineage** tab.
   The **Related Catalog Sources** tab displays a list of related catalog sources.
5. Hover your mouse over a related catalog source and click **Accept** or **Reject** from the **Action** menu.

   For more information about lineage discovery and curating CLAIRE recommendations, see *Lineage discovery* in the *Administration* help.

Managing configuration permissions for catalog sources

As a service administrator, you can grant configuration permissions for catalog sources to different roles in your organization, and add specific users and user groups to those roles so that they can perform operational activities on a catalog source.

To manage permissions for catalog source configuration, verify that at least one role has the catalog source configuration **Set Permissions** functionality enabled for Metadata Command Center in Administrator. In Administrator, create the required roles, assign users and user groups to the roles, and specify appropriate permissions to the roles.

You can select roles and add specific users or user groups to those roles to grant the following levels of permission for catalog source configuration:


- Create
- Read
- Update
- Run
- Set Permissions

Based on the permissions granted to the roles, the selected users and user groups belonging to that role can perform appropriate operations for configuring catalog sources.

1. Go to the **Explore** page in Metadata Command Center.
2. From the list of catalog sources, search for the catalog source for which you want to manage permissions.


3. Click the **Action** menu, and select **Permissions**.

   The **Catalog Source Permissions** dialog box appears.




4. In the **Roles** panel, click **Add Roles**.

   The **Add Roles** dialog box appears.



5. Select one or more roles, and click **OK** to add the roles.
6. In the **Add Users & User Groups** panel, by default, all users and user groups that belong to the selected role are granted the role-defined permissions for the catalog source configuration.

To assign permissions only to the selected users and user groups that belong to this role, choose **Specific Users and User Groups**.



7. Select **Add Specific Users and User Groups**.

   The **Add Users & User Groups** dialog box displays the list of users and user groups that the administrator has assigned to the selected role.

8. Select one or more users or user groups to assign to the selected role, and click **OK**.

   Only the selected users and user groups belonging to the specified role will be granted the role-defined permissions for catalog source configuration.

9. View the assigned permissions for each user and or group, and click **Save**.