Informatica® Metadata Command Center
October 2026

erwin Data Modeler File Sources

Informatica Metadata Command Center erwin Data Modeler File Sources
October 2026

© Copyright Informatica LLC 2023, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-30

Table of Contents

Preface. 4

Chapter 1: Introduction to erwin Data Modeler File catalog sources. 5

Extraction and view process. 6

About the erwin Data Modeler File catalog source. 6

Extracted metadata. 7

Chapter 2: Before you begin. 9

Chapter 3: Create catalog sources in Metadata Command Center. 10

Step 1. Register a catalog source. 10

Step 2. Configure capabilities. 12

Configure metadata extraction. 12

Step 3. Associate stakeholders and asset groups. 13

Step 4. Run or schedule the job. 15

Step 5. Assign reference catalog source connections to endpoint catalog source objects. 16

Chapter 4: View results in Data Governance and Catalog. 18

View metadata extraction results. 18

View relationships. 20

View relationships at catalog source level. 20

View relationships at data set level and data element level. 20

Appendix A: Managing catalog sources. 23

Cloning a catalog source configuration. 23

Deleting or purging a catalog source. 24

Purging obsolete objects from a catalog source. 24

Curating CLAIRE recommendations. 25

Managing configuration permissions for catalog sources. 25

Preface

Read *erwin Data Modeler File Sources* to learn how to register and configure erwin Data Modeler File sources in Metadata Command Center as catalog sources. After you configure a catalog source, you extract metadata and then view the results in Data Governance and Catalog.

CHAPTER 1

Introduction to erwin Data Modeler File catalog sources

You can use Metadata Command Center to extract metadata from a source system.

A source system is any system that contains data or metadata. For example, erwin Data Modeler File is a source system from which you can extract metadata through an erwin Data Modeler File catalog source with Metadata Command Center. A catalog source is an object that represents and contains metadata from the source system.

Before you extract metadata from a source system, you first create and register a catalog source that represents the source system.


When Metadata Command Center extracts metadata, Data Governance and Catalog displays the extracted metadata and its attributes as technical assets. You can then perform tasks such as analyzing the assets, viewing relationships, and creating links between those assets and their business context.

You can only extract metadata using this catalog source.

Extraction and view process

To extract metadata from a source system, configure the catalog source and run the catalog source job in Metadata Command Center. Then view the results in Data Governance and Catalog.

The following image shows the process to extract metadata from a source system:



After you verify prerequisites, perform the following tasks to extract metadata from erwin Data Modeler File:

1. Register a catalog source. Create a catalog source object, select erwin Data Modeler File, and specify values for connection properties.
2. Configure the catalog source. Specify the runtime environment and configure the metadata extraction capability.
3. Optionally, associate stakeholders. Associate users with technical assets, giving the users permission to perform actions determined by their roles.
4. Run or schedule the catalog source job.
5. Assign a connection to referenced source system assets.

About the erwin Data Modeler File catalog source

You can use the erwin Data Modeler File catalog source to extract metadata from the erwin Data Modeler source system.

erwin Data Modeler is a data modeling tool used to find, visualize, design, deploy and standardize data assets.

Extracted metadata

You can extract specific metadata from an erwin Data Modeler source system with an erwin Data Modeler File catalog source.

Metadata Command Center extracts the following metadata from an erwin Data Modeler source system:

- Argument
- Attribute
- CandidateKeyGroup
- Column
- ColumnAttribute
- Condition
- Db2Database
- DataSource
- DataSourceFile
- DataSourceSchema
- DataSourceTable
- DatabaseSchema
- DefaultValue
- Directory
- Domain
- ERDiagram
- Entity
- File
- FileGroup
- Folder
- ForeignKeyGroup
- Identity
- Index
- IndexMember
- Library
- Mart
- MinMax
- Model
- ModelSource
- NamedRelationshipEnd
- Note
- OracleDatabase
- PrimaryKeyAttribute
- PrimaryKeyColumn
- PrimaryKeyColumnAttribute

- Relationship
- SQLServerDatabase
- Sequence
- StorageGroup
- StoredProcedure
- SubjectArea
- SubtypeRelationship
- SubtypeRelationshipRole
- Synonym
- Table
- TableEntity
- Template
- Trigger
- TypeValue
- UDP
- UDPs
- UnnamedRelationshipEnd,UserDefined
- ValidValuesList
- View
- ViewColumn

Input files

erwin Data Modeler File catalog source extracts model metadata from XML and erwin files saved with the use of the erwin Data Modeler tool. Ensure that the input files are located on the Secure Agent machine. Use erwin input files when the Secure Agent is installed on a Windows machine and the erwin Data Modeler File tool is installed on the Secure Agent. Use XML input files with the Secure Agent installed on Linux machines.

CHAPTER 2

Before you begin

Before you create a catalog source, ensure that you have the information required to connect to the source system.

Perform the following tasks:

- Install a Secure Agent on the Windows machine where you installed the erwin Data Modeler File software. Ensure the license is validated. For more information about Secure Agent installation, see *Runtime Environments* in *Administrator*.
- Get the erwin Data Modeler File source information.
- Ensure you have access to the erwin Data Modeler File software when you install Secure Agent.

Note: You don't need to create a connection object for erwin Data Modeler File. You provide this information when you configure the catalog source.

CHAPTER 3

Create catalog sources in Metadata Command Center

Use Metadata Command Center to configure a catalog source for erwin Data Modeler and run the catalog source job.

When you configure a catalog source, you define the source system that you want to extract metadata from.

To provide stakeholders access to technical assets, you can assign access through roles. To view relationships for any system that the source system references, create a catalog source and a connection associated with the referenced source system after you run the job.


Step 1. Register a catalog source

When you register a catalog source, provide general information and connection values.

1. Log in to Intelligent Data Management Cloud.

   The **My Services** page appears.
2. Click **Metadata Command Center**.


   The **Metadata Command Center** box appears on the **My Services** page.



The Metadata Command Center home page appears.

3. Click **New**.
4. Select **Catalog Source** from the list of asset types.
5. Select erwin Data Modeler File from the list of catalog source types.
6. Click **Create**.

   The **New Catalog Source** page opens.



7. Click **Create**.

   The **New Catalog Source** page opens.

8. In the **General Information** section, enter a name and an optional description for the catalog source.

   Note: You can rename a catalog source after you create it, but to apply the change to all associated objects you must rerun the metadata extraction job.

   After you save the catalog source, you can update the description in Metadata Command Center and Data Governance and Catalog. The update appears only in the service in which you update it.

9. In the **Connection Information** panel, enter an absolute path to an erwin or XML input file.

   Use the XML file path on Windows and Linux machines. Use the erwin path on Windows machines only.

10. Click **Next**.

The **Configuration** page appears.

Step 2. Configure capabilities

When you configure the erwin Data Modeler File catalog source, you define the settings for the metadata extraction capability.

The metadata extraction capability extracts source metadata from external source systems.

You can save the catalog source configuration at any point after you enter the connection information. After you save the catalog source, you can choose to run the catalog source job. To run the job once, click **Run**. To run metadata extraction and other capabilities on a recurring schedule, configure schedules on the **Schedule** tab.

Configure metadata extraction

When you configure the erwin Data Modeler File catalog source, you choose a runtime environment and enter configuration parameters for metadata extraction.

Before you configure metadata extraction, install the Secure Agent on the same Windows machine where you installed the erwin Data Modeler File software.

1. In the **Connection and Runtime** area, choose a serverless runtime environment or the Secure Agent group where you want to run catalog source jobs.

   Note: Serverless runtime environment options are available if the catalog source works with a serverless runtime environment.

2. Choose to retain, delete, or deprecate objects that are deleted from the source system in the catalog with the **Metadata Change Option**.

   - **Retain**. Retains objects that are deleted from the source system in the catalog. If you update or add a filter, the catalog retains objects extracted from the previous job and extracts additional objects that match the current filter. Objects deleted from the source system are not deleted from the catalog. Enrichments added on deleted objects and relationships are retained.
   - **Delete**. Deletes metadata from the catalog based on objects deleted from the source system and changes you make to the filter. Enrichments added on deleted objects and relationships are also permanently lost. Objects renamed in the source system are removed and recreated in the catalog.
   - **Deprecate**. When objects are deleted from the source system, the catalog changes the lifecycle of the imported objects to Obsolete. The lifecycle of objects also changes to Obsolete when you add exclusion filters or reduce the scope so that objects extracted in earlier jobs are no longer included. For example, the first job includes the sales schema. The second job also includes the sales schema, but excludes the sales.transactions table. In this case, the second job marks the sales.transactions object as Obsolete, even though the first job includes it. This does not impact enrichments applied to deprecated objects and relationships. Objects renamed in the source system are removed and recreated in the catalog. When you run the catalog source job again for other capabilities such as data classification, relationship discovery, or glossary association, the job doesn't consider obsolete objects. Obsolete objects remain in the catalog until they are purged when you run a **Purge Obsolete Objects** job on the **Explore** page.

   Note: You can also change the configured metadata change option when you run a catalog source.

3. In the **Configuration Parameters** area, enter configuration parameters.

   The following table describes the properties that you need to enter:

Property	Description
Import UDPs	Specify how to import property definitions and values. A user-defined property (UDP) is usually defined with a property definition object that has a default value.
Import Relationship Name	Specifies how to import relationship names from erwin Data Modeler. Choose one of the following options: - From relationship name - From derived name
Import Column Order From	Specifies how to import the position of columns in tables. Choose one of the following options: - Physical order - Column order
Import Owner Schemas	Determines whether to import owner schemas. Import owner schemas to preserve the original ownership information from the source database in the data analysis. Select 'True' to import owner schemas. Select 'False' if you don't want to import owner schemas.
Move Entities to Subject Areas	Select 'True' if you want subject areas to be used as conventional UML design packages with corresponding namespaces. If entities belong to a single subject area, they are placed in the corresponding package. Other entities are placed in the model. Select 'False' if you don't want to move the entities to the subject areas .
Miscellaneous Options	Enter a value for additional extraction runtime options. For example: - To allocate 4 GB of memory to the metadata extraction process, enter: `–java.memory 4G` - To clear the cache before metadata extraction, enter: `-cache.clear`

4. Click **Next**.

   The **Associations** page appears.

Step 3. Associate stakeholders and asset groups

Associate users or user groups within a stakeholder role as stakeholders for technical assets in Data Governance and Catalog. Also, you can choose to assign technical assets extracted from the catalog source to asset groups. You can then use access policies to control permissions on assets that are assigned to asset groups.

Verify that the administrator assigned users and user groups to the stakeholder role that you want to associate with technical assets.

1. To associate users or user groups as stakeholders with technical assets extracted from the catalog source, perform the following steps:
   a. On the **Associations** page, click **Stakeholders**.
   b. Select **Assign Stakeholders**.

c. Select **Propagate to Child Assets** to propagate stakeholders of a parent asset to child assets without stakeholders.

d. Select **Append Stakeholders** to propagate stakeholders of a parent asset to all child assets including assets with stakeholders assigned.


Note: To enable **Append Stakeholders**, you must enable **Propagate to Child Assets**.

You can also override the propagation settings from the catalog source page in Data Governance and Catalog. For more information about stakeholder propagation, see *Stakeholder Propagation* in *Administration*.

e. Select a stakeholder role.

f. Click **Select** to add users and user groups from the stakeholder role as stakeholders for the technical assets.

The **Add Users & User Groups** dialog box displays a list of users and user groups assigned to the selected stakeholder role.



g. Select one or more users or user groups to assign as stakeholders for the technical assets, and click **OK**.

Only the selected users and user groups belonging to the specified stakeholder role are granted the permissions to technical assets.

h. To assign users or user groups from another stakeholder role, click **Add** and then repeat the steps.

2. To assign asset groups to technical assets extracted from the catalog source, perform the following steps:

a. On the **Associations** page, click **Asset Groups**.


b. Select **Assign Asset Groups**.

c. Click **Select**.

The **Select Asset Groups** dialog box displays the list of asset groups.

If you enabled an access policy that includes an asset group, you can only view assets that belong to that asset group.

3. Select the asset groups to which you want to assign technical assets extracted from the catalog source, and click **OK**.



4. Choose to save and run the job or to schedule a recurring job.
   - To save and run the job, click **Save** and then **Run**.
   - To schedule a recurring job, click **Next** to open the **Schedule** page.

Step 4. Run or schedule the job

Choose to run a catalog source job manually, or configure it to run on schedule.

Note: You can't run multiple jobs simultaneously.

You can choose to perform a full or an incremental metadata extraction. A full metadata extraction extracts all objects from the source to the catalog. An incremental metadata extraction extracts only the changed and new objects since the last successful catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable.

When you run an incremental metadata extraction job with a filter to include metadata from objects, the job extracts only the objects that have the latest timestamp since the last successful job.

Note: If incremental metadata extraction is available for the catalog source, the option is always visible, but incremental metadata extraction jobs can run only after a scheduled full metadata extraction job. Manual jobs do not enable the incremental metadata extraction option.

Run the job manually

Click **Save** to save the catalog source and click **Run**. On the **Run Catalog Source Job** window, click **Run** to run the job.

You can override the capabilities that you selected while configuring your catalog source on the **Configuration** page. The first time you run the catalog source job, the metadata extraction capability is mandatory. From the second run onwards, you can choose to override the configured metadata change option. You can retain, delete, or deprecate objects that are deleted from the source in the catalog. For subsequent runs of the catalog source job, the metadata extraction capability is optional.

Note: You can choose incremental metadata extraction for subsequent runs only after one full metadata extraction job completes successfully. Incremental metadata extraction jobs run with the **Retain** metadata change option even if you set the option to **Delete** or **Deprecate** in the catalog source.

Note: To run a catalog source job, you need permissions on the connection to the source system. To run a catalog source job for catalog sources that reference other source systems, you need permissions on the connections for all the reference source systems.

Run the job on a schedule

You can choose to run metadata extraction and other capabilities on a recurring schedule. You can't choose incremental metadata extraction and full metadata extraction in the same schedule. To create a schedule for incremental metadata extraction, you must have completed at least one full metadata extraction job successfully. If not, first create a schedule for a full metadata extraction.

If an incremental metadata extraction is scheduled to run when the last run details aren't available, the job first performs a full metadata extraction, followed by incremental metadata extraction on subsequent runs.

For example, this can happen in the following scenarios:

- You create schedules for both incremental metadata extraction and full metadata extraction, but schedule the incremental extraction to run before the first full metadata extraction job.
- You create schedules for both incremental metadata extraction and full metadata extraction, but delete the full metadata extraction schedule before its first run.

1. On the **Schedule** tab, select **Run on Schedule**.
   The **Schedule** configuration page opens.
2. Click the checkbox corresponding to each capability that you want to include in the schedule.
3. Enter the start date, time zone, and the interval at which you want to run the job.
4. You can manage additional schedules using the following options:
   - To create a new schedule, click the **Add** button.
   - To delete a schedule, click the **Delete** button.
   - To enable or disable a schedule, click the **Enable Schedule** toggle button.

   Note: You can create a maximum of one schedule per capability that you enable. If you purged a catalog source or did not run the metadata extraction job, the catalog source job runs metadata extraction before running other scheduled capabilities.

   Note: To create a schedule, you need permissions on the connection to the source system. If you lose permissions on the connection after you create a schedule, the scheduled jobs continue to run.
5. Click **Save** to save the schedule.

Monitor job status

After the job runs, you can monitor the status of the job on the **Overview** page of the job.

For more information about job monitoring, see *Administration*.

Step 5. Assign reference catalog source connections to endpoint catalog source objects

If the source system references another source system, perform connection assignment in Metadata Command Center to view relationships with actual source objects. To perform a connection assignment,

create a connection for the source in IDMC Administrator, and then create endpoint catalog sources using the connections. A referenced source system might be a relational database, such as Oracle.

Before you can connect to a referenced source system, create a connection to the referenced source system in Administrator.

You can't create a connection assignment based on a File System when you extract report metadata from an erwin Data Modeler File source system.

1. On the **Configure** page, select the **Lineage** tab, and then select the **Lineage Discovery** tab. On the **Catalog Sources** panel, select the required catalog source and click the **Assign Connections** tab.

   The **Assign Connections** tab displays a list of assigned and unassigned connections along with details for each connection. Use filters to view the connections based on the connection names. Click the **Add Filter** menu to add filters.

2. Select the connection to the reference source system and click **Assign**.

   The connection name appears prefixed to the reference catalog source name on the **Hierarchy** tab of your catalog source in Data Governance and Catalog.

   The **Assign Connection** dialog box appears with a list of recommended objects from the endpoint catalog sources. Click **All** to view all endpoint catalog source objects.

3. In the **Assign Connection** dialog box, select one or more catalog sources to assign to the selected connection and click **Assign**.

   You can filter the list of catalog sources by name, type, or endpoint.

   You can create a connection assignment to Oracle catalog sources. The catalog sources must belong to the **Schema** class type.

When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the relationships with database assets that you view in Data Governance and Catalog.

CHAPTER 4

View results in Data Governance and Catalog

After Metadata Command Center runs a job, you can view the results in Data Governance and Catalog where the catalog source and its elements are called technical assets. You can view the catalog source and the included technical assets in a hierarchical structure.

When referenced source systems are connected to a catalog source, you can expand the hierarchy to see details about the technical asset's component elements.

You can view the relationship information of an asset in a catalog source to see individual elements such as data sources, calculations, and filters. When you view the relationship information of an asset, you can see how the assets relate to one another.

View metadata extraction results


After a job runs in Metadata Command Center, view the results in Data Governance and Catalog. You can view details about source system contents as hierarchical displays and view relationships with database assets.

1. Log in to IDMC.

   The **My Services** page appears.

2. Click Data Governance and Catalog.

   The following image shows the Data Governance and Catalog box on the **My Services** page:



3. On the Data Governance and Catalog home page, click the number in the **Technical Assets** panel.

   The **Technical Assets** page opens.


4. Select **Catalog Source** in the **Filter** list.

   The list of catalog sources opens.

5. Search for the catalog source from which you extracted metadata, and click the name.

   The **Overview** tab of the asset opens.

   The following image shows a sample erwin Data Modeler File catalog source asset page:



6. View the asset from different perspectives by clicking on the tabs.

For more information about working with assets, see "Working with Assets" in *Cloud Data Governance and Catalog* online help.

View relationships

Relationship views are available for technical assets in the catalog source. You can connect assets to each other using different types of relationships.

A relationship between assets shows how the assets relate to one another. When data from a source system is ingested into the catalog, Data Governance and Catalog can automatically create relationships among the technical assets of that source system.

For more information about viewing relationships, see *Relationships* in the Data Governance and Catalog help.


View relationships at catalog source level

The **Relationships** tab of an asset page displays the relationships between the selected asset and other business and technical assets in Data Governance and Catalog.

The erwin Data Modeler File catalog source reads metadata from the input data model and creates reference assets in the model. You can view the relationship with reference objects without performing connection assignment. After connection assignment, you can view the relationship between the actual objects extracted by the erwin Data Modeler File catalog source.

To view relationships at the catalog source level, search for and open an erwin Data Modeler File catalog source, click the **Relationships** tab and expand the catalog source.

The following image shows the relationship between the erwinFile_Erwin_134 catalog source and the erwin Data Modeler File reference catalog source:



View relationships at data set level and data element level


The relationships at the data set level and the data element level show how technical assets such as tables and columns are related to the selected asset.

Data sets are technical assets that contain sets of data. For example, a table in a source object. Data elements are objects upstream or downstream of a data set. For example, a column in a source object.


View relationships at the data set level

The relationships at the data set level show how the technical assets such as tables are related to the selected asset. To view relationships at the data set level, open a technical asset such as a table, click the **Relationships** tab, and then expand the data set.

The following image shows the table-to-table relationship between the erwin Data Modeler File Department asset and the referenced Department data set before the connection assignment:




The following image shows the table-to-table relationship between the erwin Data Modeler File Department asset and the Oracle table after connection assignment:




View relationships at the data element level

The data element level displays details of the data set level. The relationships at the data element level show how the technical assets such as columns are related to the selected asset. To view relationships at the data element level, open a technical asset, click the **Relationships** tab, and then expand the data element.

The following image shows a table to column relationship between the erwin Data Modeler File Dept_name asset and the referenced Dept_name data element before connection assignment:



The following image shows a table to column relationship between the erwin Data Modeler File Dept_name asset and the DEPT_NAME column after connection assignment:



APPENDIX A

Managing catalog sources

You can update, copy, delete, purge, and run a catalog source. You can also grant configuration permissions for catalog sources to different roles in your organization.

On the **Catalog Sources** page of the **Explore** page, you can select a catalog source to see its overview and related catalog sources. The **Overview** tab displays the capabilities, filters, stakeholders, asset groups, and schedules enabled for a catalog source. The **Related Catalog Sources** tab displays a list of related catalog sources that are either assigned manually using connection assignment or are curated based on CLAIRE recommendations using the lineage discovery capability. You can view related catalog sources and accept or reject CLAIRE recommendations for catalog sources that are run with the lineage discovery capability.

Cloning a catalog source configuration

You can clone the configuration of a catalog source to create another catalog source with the same configuration.

Note: Cloning doesn't copy the content of the catalog source.

1. In Metadata Command Center, go to the **Explore** page.
2. Select **Catalog Sources** from the menu.
3. You can clone a catalog source in one of the following ways:
   - Hover your mouse over the catalog source that you want to clone and click **Clone** from the **Action** menu.
   - Open the catalog source that you want to clone and click **Clone**.

   Note: By default, the cloned catalog source has the same name suffixed with _Clone. You can change the name if needed.
4. If needed, modify the configuration of the catalog source by updating the parameters on each tab.

   Cloning doesn't copy the content of sensitive fields. If the catalog source contains sensitive fields such as Client Secret, enter the values.
5. Click **Save**.

Deleting or purging a catalog source

Delete or purge a catalog source based on your business requirements.

When you delete a catalog source, you delete all the configuration specific to that catalog source, along with all the metadata that was extracted and any enrichment made to the associated metadata. Purging a catalog source deletes all the metadata that was extracted, along with any enrichment made to the associated metadata.

Note: Before you delete or purge a catalog source, manually unassign the connections that are assigned to that catalog source.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source that you want to delete or purge.
4. Click the **Action** menu, and select **Delete** or **Purge**.

   Note: You can't delete or purge a catalog source if the catalog source job is in the running state.
5. To confirm delete or purge, click **OK**.

   The catalog source is triggered to delete or purge. You can monitor the status of the job on the **Monitor** page.

   Note: If the deletion job succeeds, the catalog source disappears from Metadata Command Center. If it fails, some associated objects might still be present in Data Governance and Catalog. Such catalog sources continue to appear in the list of catalog sources in Metadata Command Center, but are marked as **Deleted**. Delete the catalog sources to remove them along with any remaining objects present in Data Governance and Catalog.

Purging obsolete objects from a catalog source

You can purge obsolete objects from a catalog source.

When you configure or run a catalog source, you can choose to deprecate objects that are deleted from a source system. If you delete objects from the source system or make changes to the filter, the objects imported into the catalog before the change move to the Obsolete lifecycle in the catalog. You can purge obsolete objects from a catalog source. This permanently deletes all objects with the Obsolete lifecycle status, along with associated enrichments, from the catalog.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source from which you want to purge obsolete objects.
4. Click the **Action** menu, and select **Purge Obsolete Objects**.

   A warning message appears on the page.
5. Click **Yes** to confirm.

   A confirmation message appears on the page and the purge job starts. You can monitor the status of the job on the **Monitor** page. If the job succeeds, all obsolete objects present in the catalog source disappear from the catalog.

   Note: If the job fails, some obsolete objects might remain in the catalog. To remove the remaining obsolete objects, run the purge job again.

Curating CLAIRE recommendations

You can view related catalog sources and accept or reject CLAIRE recommendations for a catalog source.

Applicable to catalog sources that generate lineage.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source for which you want to curate CLAIRE recommendations.
4. Hover your mouse over the catalog source and click **View Lineage Discovery** from the **Action** menu.

   Note: The **View Lineage Discovery** option is available for catalog sources that are run with the lineage discovery capability.

   The **Configure** page appears with the catalog source filtered on the **Lineage Discovery** tab of the **Lineage** tab.
   The **Related Catalog Sources** tab displays a list of related catalog sources.
5. Hover your mouse over a related catalog source and click **Accept** or **Reject** from the **Action** menu.

   For more information about lineage discovery and curating CLAIRE recommendations, see *Lineage discovery* in the *Administration* help.

Managing configuration permissions for catalog sources

As a service administrator, you can grant configuration permissions for catalog sources to different roles in your organization, and add specific users and user groups to those roles so that they can perform operational activities on a catalog source.

To manage permissions for catalog source configuration, verify that at least one role has the catalog source configuration **Set Permissions** functionality enabled for Metadata Command Center in Administrator. In Administrator, create the required roles, assign users and user groups to the roles, and specify appropriate permissions to the roles.

You can select roles and add specific users or user groups to those roles to grant the following levels of permission for catalog source configuration:


- Create
- Read
- Update
- Run
- Set Permissions

Based on the permissions granted to the roles, the selected users and user groups belonging to that role can perform appropriate operations for configuring catalog sources.

1. Go to the **Explore** page in Metadata Command Center.
2. From the list of catalog sources, search for the catalog source for which you want to manage permissions.


3. Click the **Action** menu, and select **Permissions**.

   The **Catalog Source Permissions** dialog box appears.




4. In the **Roles** panel, click **Add Roles**.

   The **Add Roles** dialog box appears.



5. Select one or more roles, and click **OK** to add the roles.
6. In the **Add Users & User Groups** panel, by default, all users and user groups that belong to the selected role are granted the role-defined permissions for the catalog source configuration.

To assign permissions only to the selected users and user groups that belong to this role, choose **Specific Users and User Groups**.



7. Select **Add Specific Users and User Groups**.

   The **Add Users & User Groups** dialog box displays the list of users and user groups that the administrator has assigned to the selected role.

8. Select one or more users or user groups to assign to the selected role, and click **OK**.

   Only the selected users and user groups belonging to the specified role will be granted the role-defined permissions for catalog source configuration.

9. View the assigned permissions for each user and or group, and click **Save**.