Informatica® Cloud Business 360 Console
October 2026

Define Jobs

Informatica Cloud Business 360 Console Define Jobs
October 2026

© Copyright Informatica LLC 2020, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices and AI assistant acknowledgements are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-30

Table of Contents

Preface 5

Chapter 1: Introduction to jobs 6

Chapter 2: Defining ingress jobs 7

Key concepts 8

Supported assets 8

Ingress process 9

Prerequisites for data ingress 9

Rules and guidelines for importing data 10

Automapping source and target transformations 12

Considerations for excluding source records from the match process 13

Ingress data 13

Ingress data with business ID 14

Chapter 3: Defining egress jobs 19

Key concepts 19

Supported Assets 20

Egress Process 20

Prerequisites 20

Export job types 21

Rules and guidelines for exporting data 21

Egress data 22

Exported data 23

Parent IDs of field groups in the exported data 23

Business IDs of records in the exported data 24

Match pairs 24

Chapter 4: Defining match and merge jobs 25

Define and run a match and merge job 26

Chapter 5: Defining generate merge tasks jobs 28

Define and run a generate merge tasks job 28

Chapter 6: Defining recover a failed job 30

Define and run a recover failed job 30

Chapter 7: Defining generate search indexes or match keys job 31

Define and run the generate search indexes or match keys job 32

Chapter 8: Defining publish business events jobs. 33

Prerequisites for a publish business events job. 33

Define and run a publish business events job. 34

Chapter 9: Defining process hierarchies jobs. 35

Define and run a process hierarchies job. 35

Chapter 10: Defining reprocess master data jobs. 36

Define and run a reprocess master data job. 36

Index. 38

Preface

Use the Business 360 REST APIs to interact with your Informatica Intelligent Cloud Services organization through API calls. You can use the REST APIs to perform tasks and get data from your organization.

CHAPTER 1

Introduction to jobs

A job is an executable instance of a task or process that uses one or more steps. Some jobs can perform different processes, and you can select the process that you want to perform.

You can define the following jobs in Business 360 Console:

- Ingress
- Egress
- Generate search indexes or match keys
- Match and merge
- Generate merge tasks
- Recover a failed job
- Publish business events
- Process hierarchies
- Publish report data
- Reprocess master data

CHAPTER 2

Defining ingress jobs

Ingress is a process that imports data from external source systems, masters the data, and stores it in MDM SaaS assets. When you get started with MDM SaaS for the first time, to onboard your initial data, you must ingress it. You can continue to ingress data incrementally to be in sync with the source systems.

For example, you work for an enterprise that manages customer data in Salesforce. You subscribe to MDM SaaS to master the customer data in Salesforce. To get started with MDM SaaS, ingress the initial data from Salesforce. You can then continue to ingress data incrementally into MDM SaaS so that the data in MDM SaaS is in sync with the Salesforce data.

You can import new records and update field values, delete field group entries in record sections, delete source records, or delete relationships and hierarchies. For example, you can import a new record, update only the home address, or delete the billing address of existing records.

Note: You can't update patch records through ingress.

You can choose to update only the fields that contain values in the source system, without overwriting the entire record. The update applies only to the fields that are present in the source system and mapped to target fields. Other fields remain unchanged. You can control how the update handles empty fields in the source system. By default, the update ignores these values and leaves the corresponding target fields unchanged. You can choose to overwrite these target fields with null instead.

Note: After migrating your rule associations to use Enrichment and Validation Orchestrator in organizations created before the October 2025 release, you can update only fields that contain values and set empty fields to null.

When you set empty fields to null, the update determines each field value using the following precedence:

- If the source system contains a value, the update sets the mapped field to that value.
- If the source system doesn't contain a value and the field has a default value, the update sets the mapped field to the default value.
- If the source system doesn't contain a value and the field has no default value, the update sets the mapped field to null.

Note: When you update records through ingress, the NotReadyForMatch field remains unchanged, even when you overwrite empty fields.

You can also ingress records with validation errors. However, ensure that you purge the existing data before data validation is enabled and then ingress records that have validation errors.

You can use business IDs, which are unique identifiers that MDM SaaS uses to identify records, to ingress data. When the ingress data contains business IDs, the records merge directly with the master records, and they don't go through the match and merge process. For example, if you specify the business IDs of existing source records, the records merge with the master records to which the source records contribute. The records are added as source records and are assigned new business IDs. If you specify the business IDs of existing master records, the records become source records for the master records, and they merge directly

with the master records. For more information about using business IDs to ingress data, see "Ingress data with business ID" on page 14.

You can exclude source records from participating in the match process by specifying them as not ready for match during the ingress process. You might want to exclude records that belong to a specific source system or records that contain incomplete data.

Key concepts

To effectively ingress data, you need a basic understanding of the following concepts:

Source System

An external data source from where you can extract data. For example, Salesforce.

Note: If the source system includes date and time data without time zone details, the system considers it to be UTC date and time, and converts the values as per its current time zone.

Process

A Cloud Application Integration asset that provides a set of instructions to automate a business requirement. For more information about process, see *Informatica Cloud Application Integration Design*.

Taskflow

A Cloud Data Integration workflow that consists of multiple tasks linked together. You can use a taskflow to run multiple tasks in a sequential order or in parallel. Use Cloud Data Integration to create taskflows that map source systems to target systems. For example, if you want to ingress customer data from a flat file and a MySQL database, create a mapping task that maps the flat file to your target asset, and another mapping task that maps the MySQL database to your target asset. Add the mapping tasks to a taskflow that you can use to ingress data. For more information about taskflows, see *Informatica Cloud Data Integration Taskflows*.

To add new records and update field values or delete field group entries in record sections, create a mapping with different data flows for each field group and for root fields with Business 360 FEP Connector. You can specify the operation that you want to perform on the field values in record sections.

For more information about the different supported operations, see *Target transformation in mappings* in the Data Integration help.

Note: Ensure that you do not include disabled fields in mappings. When you run a taskflow related to mappings that include disabled fields, the imported data does not include the data in disabled fields.

Asset

A target system that stores the data extracted from the source systems. For example, Business 360 can store data in the Person or Organization business entities. For more information about business entities, see the *Model Master Data* section.

Supported assets

You can ingress data to the following types of assets:

- Predefined and custom business entities
- Predefined and custom relationships

- Hierarchies

Ingress process

The process available to ingress data is MDMIngress.

The ingress process includes the following steps:

1. Extract data from a source and load to a staging area.
2. Cleanse and transform the staged data.
3. Load the cleansed data to MDM SaaS data store.
4. Index records for search.
5. Generate match keys.

For more details about these steps, see *Monitor MDM SaaS*.

Prerequisites for data ingress

Before you ingress data, ensure that you have defined the following assets and objects:

1. In Administrator, create a source connection to read data from source and a Business 360 connection to write to the Business 360 assets. For more information about creating connections, see Configuring a connection in the Administrator help.
2. In Administrator, specify a Secure Agent that is up and running as a runtime environment to run a mapping task.

   Note: Ensure that you don't share runtime environments between parent and sub-organizations. If you use a runtime environment of the parent organization in the sub-organizations, MDM SaaS can't retrieve the data from the parent organization.

   For more information about Secure Agent, see Runtime environments in the Administrator help.
3. Create a mapping in one of the following ways:
   - Manual mapping. In Cloud Data Integration, create a mapping with the source connection as the source transformation and the Business 360 connection as the target transformation. Manually map the fields between the source and target transformations. For more information about manually creating a mapping, see Mapping configuration in the Data Integration help.
   - Automapping. Start the mapping creation process from a business entity in Business 360 Console. In Cloud Data Integration, the business entity becomes the target for the mapping. After you select a source, Cloud Data Integration automatically maps the fields between the source and the target.

   Ensure that you create an in-out parameter `jobInstanceId` in the Parameters panel.

   Note: The name of the in-out parameter is case sensitive.
4. In Cloud Data Integration, create a mapping task by selecting the runtime environment and adding the mapping that you create. For more information about configuring a mapping task, see Mapping task configuration in the Data Integration help.

5. In Cloud Data Integration, create the required taskflows. Publish the taskflows to use in your ingress job. For more information about creating taskflows, see Taskflows in the Data Integration help.

   Note: Ensure that you don't add a Command Task step to the taskflows that you create. If the taskflows contain the Command Task step, the ingress jobs fail.
6. Consider the data source for the ingress jobs because not all the connectors available in IDMC can be used in the mapping for ingress jobs.
   For example, you can't use the Databricks Delta connector with custom queries in an ingress mapping for MDM SaaS. Before you define an ingress job, identify the source systems and validate the connectivity.
7. Validate the connectivity with the MongoDB Atlas instance and Business 360 Connector.
8. To load a multibyte data set, meet the following requirements:
   - Define JVM options in the Secure Agent.
     For more information, see Rules and Guidelines for Business 360 FEP Connector.
   - Ensure that the sourcePkey field name contains only alphanumeric characters and the following special characters without exceeding 255 characters:
     ~!'={}|:@#$^&*()-_+,<>?`

     For more information about loading a multibyte data set with ingress, see the

     Multibyte characters not loading properly with Ingress when using Business 360 connector Knowledge article.
9. Ensure that a match model is defined for the business entity.
10. Without a match model, an ingress job can't generate match keys for source and master records.
11. If you configure data quality rule associations for crosswalk standardization, Informatica recommends that you use the Business 360 FEP Connector to run ingress jobs.
    For more information about configuring rule associations for crosswalk standardization, see *Configure Data Quality*.

    MDM SaaS allocates fixed memory to store field mappings for crosswalk standardization. When you run an ingress job that processes large volumes of data with crosswalk rule associations in business entities through the Business 360 Connector, you might exceed the allocated memory. The ingress job fails because of insufficient memory.
12. To insert, update, or upsert records, use the Business 360 FEP Connector in Cloud Data Integration

    Note: You can't use Business 360 FEP Connector with reference data assets.

Rules and guidelines for importing data

Consider the following rules and guidelines when you create and run an ingress job to import data:

- Identify the differences between Business 360 Connector and Business 360 FEP Connector.
  For more information about the differences between the Business 360 and Business 360 FEP Connectors, see the FAQ: Difference between Business 360 Connector & Business 360 FEP Connector Knowledge article.
- When you ingress a large volume of data, use the chunking strategy to load a maximum of 25 to 50 million records per ingress job. To optimize the load time and help with the recovery time in case of any job failures, logically divide large source data into multiple jobs.
- If you rename or delete a business entity in Business 360 Console, the existing mappings that reference the business entity fail when you run the mappings. Ingress jobs that use these mappings also fail.
- Ensure that the you don't create mappings in the advanced mode in Cloud Data Integration.

If you create mappings in the advanced mode with the Business 360 Connector or the Business 360 FEP Connector in the Target Transformation, you can't ingress data into MDM SaaS.

- Use Business 360 FEP Connector instead of Business 360 Connector for parallel execution and enhanced performance.
- In Data Integration, create separate mappings for hierarchy instances, root relationships, and relationships. Add each mapping to its own mapping task, and then add all the mapping tasks to a common taskflow.
- Ensure that the primary key of each relationship in a hierarchy is unique.
- If you want to insert, update, upsert, or delete field values of records in a single mapping, ensure that you add separate target transformations for each operation in Data Integration.
- Ingress jobs process records based on the operation type of the root field in Data Integration mappings, regardless of the operations specified for field groups. When you specify an update operation for any field group of records without a root field in Data Integration mappings, ingress jobs perform the update operation on the records.
- If you specify the update operation to update field values of existing records, the load step rejects records with field values that are identical to the field values of existing records.
- Ensure that you don't run ingress jobs that include taskflows associated with reference data assets to import the reference data assets into Reference 360.
  To import reference data assets into Reference 360, ensure that you run a reference data import job in Reference 360.

  For more information about reference data import jobs, see *Defining reference data import jobs* in the Reference 360 help.
- When an ingress job processes records that contain blank values in all fields of the root or field groups, MDM SaaS skips these records in the transform step even if source primary keys of the records are valid. If records aren't skipped and come from a high-rank source system, the merge process might overwrite the existing master record values with blank values.
- When you configure an ingress job, ensure that the taskflows associated with the job don't contain mappings with different operations, such as update and delete, for the same set of records. If a taskflow contains mappings that perform different operations, the job processes only one mapping and ignores the other mappings.
  For example, you want to update the first name and last name of an existing record and then delete the same record. When you configure an ingress job and associate a taskflow that contains two mappings for update and delete operations, the job updates the first name and last name of the record and doesn't delete the record. To perform both operations, if you create different taskflows, the job still processes only one operation and ignores the other.

  To perform different operations on the same set of records, ensure that you run two separate ingress jobs.
- Ensure that the internal IDs of text and picklist fields don't end with `_code`.
  If an internal ID ends with `_code`, the transform step fails. However, if you migrate existing rule associations in your organizations to use Enrichment and Validation Orchestrator, the transform step succeeds even if the internal ID ends with `_code`.

  For more information about migrating rule associations to use Enrichment and Validation Orchestrator, see Migrate existing rule associations.
- If the extract step of an ingress job that uses the Business 360 FEP Connector doesn’t extract any records, MDM SaaS now sets the status of the Transform step and the job to Warning. MDM SaaS doesn't run the remaining Load, Enrichment, Index for Search, and Generate Tokens steps.

This applies to organizations in which you migrated rule associations to Enrichment and Validation Orchestrator in the April 2026 and July 2026 releases. It also applies to new organizations that you created after the October 2025 release.

For more information about migrating rule associations to use Enrichment and Validation Orchestrator, see Migrate existing rule associations.

- When you use rich text format in text fields, use only supported HTML tags and attributes. MDM SaaS removes unsupported tags and attributes for security reasons.
  For more information about rich text formatting, see *Rich text formatting for text fields*.
- When you import decimal data, ensure that the values match the configured precision and scale. For example, if a field has a precision of 3 and a scale of 0, a record with the value 10.00 isn't imported because it exceeds the configured precision and scale.
- To run an ingress job, use one of the following methods:

  - Schedule the ingress job on the **Job Schedules** tab from the **My Jobs** page.

  - Define the ingress job on the **New** tab.

  - Run the ingress job using the Create Ingress Job Instance REST API.

  Note: To run an ingress job, don't run a taskflow from the Monitor page in Data Integration. If you run a taskflow to trigger an ingress job, the job fails.
- Ensure that the target business entity names in the mappings of the selected taskflows from Data Integration don't contain a forward slash.
  When the ingress job runs, MDM SaaS retrieves the target business entities from the taskflow in a folder structure. If a target business entity name contains a forward slash, MDM SaaS can't load the assets from the taskflow. You also can't save the ingress job definition.
- When you run an ingress job with less than 1,000 records and the advanced rule association returns an exception, MDM SaaS loads the records and moves them to exception status even after multiple retries. However, when you run an ingress job with more than 1,000 records and the rule association returns an exception, the ingress job fails.

Automapping source and target transformations

You can start the mapping creation process from a business entity in Business 360 Console. In Cloud Data Integration, the selected business entity is added as a target transformation. After you select a source connection, Cloud Data Integration automatically maps the fields between the source and target transformations.

1. From the **Explore** page, open a business entity
2. Click **Actions**, and then click **Automapping**.

   The **Automapping** page appears in Cloud Data Integration.
3. In Business 360 Console, on the **Sources** tab of the **Choose sources and targets** page, click **Add Sources**.
4. Select the packages and sources along with their objects.

   You can select multiple objects. Use the **Find** field to search for the objects if required.
5. Click **Add**.

   The selected sources and their objects appear on the **Sources** tab.
6. Optionally, verify the target business entity.

   Note that the target is predefined and you can't configure it.

7. Click **Create Mapping**.

   The mapping appears in the mapping canvas. Save and validate the mapping.
   You can configure the mapping to add one or more supported transformations.

Considerations for excluding source records from the match process

During the ingress process, you can specify source records as not ready for match and exclude them from participating in the match process.

Excluding source records from the match process impacts the statuses of master and patch records in the following ways:

- If you specify a new record as not ready for match, the ingress process excludes the record from participating in the match process. The record remains as a source record in MDM SaaS. To include the record in the match process, you need to ingress the record again and after changing its status to ready for match.
- If a master record contains a single source record, specifying that source record as not ready for match automatically changes the statuses of the master and patch records to not ready for match.
  For example, consider a source record S1 and a patch record P1 that contribute to form a master record M1. If you specify the status of S1 as not ready for match, the statuses of M1 and P1 automatically change to not ready for match.
- If multiple source records contribute to a master record, specifying individual source records as not ready for match doesn't impact the statuses of the other source records or the master record they contribute to. However, if you collectively exclude all the source records from the match process, the statuses of the source records and the master record automatically change to not ready for match. The statuses of the patch records depend on the status of the master record.
  For example, consider the source records S1, S2, and S3 along with patch records P1 and P2 that contribute to form a master record M1. If you specify S1 as not ready for match, the statuses of S2, S3, P1, P2 and M1 don't change. However, if you specify S1, S2, and S3 as not ready for match, the statuses of M1, P1, and P2 automatically change to not ready for match.

Ingress data

Create an ingress job to ingress data from an external source system to the Business 360 data store.

1. Click **New** > **Jobs** > **Ingress** > **Create**.

   The **Ingress** dialog box appears.
2. Specify the job properties, and click **OK**.

   The ingress job page appears.
3. Click the asset picker and select the **MDMIngress** process.
4. Select the source system from which you want to ingress data.

   The default source system is *Default*.

5. To update existing records irrespective of the last updated dates in the source system, enable **Force Record Update**.

   When you choose the update operation in a Target transformation in Data Integration and ingress records without any updates to field values, the records are rejected in the load step. However, the ingress job processes each record internally, which might cause the load step to run longer than expected.

   If you don't want to reject the records, ensure that you select **Force Record Update**.

6. To update only the mapped fields that contain values in the source system without overwriting other field values, select **Update only Fields Containing Data**.

   Ensure that you also select the update operation in a Target transformation in Data Integration.

   Note: Ingress jobs process records based on the operation type of the root field in Data Integration mappings, regardless of the operations specified for field groups. When you specify an update operation for any field group of records without a root field in Data Integration mappings, ingress jobs perform the update operation on the records.

7. If you want to overwrite the mapped target field values with null for empty fields in the source system, select **Set Empty Fields to Null**.

   If the fields are empty in the source system and the target fields have no default value, the update overwrites all the mapped target fields with null.

   Note: After migrating your rule associations to use Enrichment and Validation Orchestrator in organizations created before the October 2025 release, you can update only fields that contain values and set empty fields to null.

8. To add a taskflow, perform the following tasks:

   a. Click **Add Taskflow**.

      The **Select an Asset** page appears.

   b. Select the required taskflows, and click **Select**.

      The taskflows appear in the **Taskflows** section. The associated assets appear in the **Assets** section. To run an ingress job successfully, ensure that the number of assets associated with the taskflows doesn't exceed 80.

   c. Verify that the taskflows you added have unique names and are published.

      If multiple taskflows in the ingress job have the same name, you can't save the job.

9. Click **Save**.

10. To execute the job, click **Run**.

    You can monitor the status of the job on the **My Jobs** page.
    For more information about monitoring ingress jobs, see *Monitor MDM SaaS*.

Ingress data with business ID

When you ingress records with business IDs, the ingress job merges the records directly with the existing records even if you specify them as not ready for match. If the business IDs of records that you ingress align

with the business ID format defined in Business 360 Console and the same business IDs exist in the MDM SaaS data store, the records are ingressed. Otherwise, the records are rejected.

The records don't go through the match and merge process because the ingress job considers them as existing records. When you use the Source Record API to verify the statuses of the records that you ingress with business IDs, they appear as CONSOLIDATED.

For example, you want to ingress employee records from different source systems into the MDM SaaS data store. Some records include business IDs, and some records don't include business IDs. Few business IDs don't match any existing records, and few business IDs match the existing records.

You can ingress records with business IDs that were used before a data purge, but the business IDs must be lower than the last generated business ID. The business ID format for a business entity must remain consistent before and after the purge. For example, if 999000000008899 was the last generated business ID before the data purge, you can ingress records with business IDs lower than the last generated sequence number 8899, such as 999000000007755.

The MDM SaaS data store shows the master records with their business IDs.

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000123	Mary	Williams	F	01-01-1991
MDM000000000456	John	Johnsons	M	03-03-2001

The MDM SaaS data store shows the contributing source records with their configured business ID format.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	CRM	Mary	Williams	F	01-01-1991
MDM000000000789	SFDC	Mary	W	F	-
MDM000000000456	SAP	John	Johnsons	M	03-03-2001

Business ID of an input record doesn't exist in the MDM SaaS data store

If the business ID of an input record doesn't match the business ID of an existing source or master record, the system considers the input record as a new one and creates a master record. However, if the business ID format contains the prefix that's set for the business ID format defined in Business 360 Console, the system doesn't create a new master record. If you specify custom business IDs for records, ensure that you don't use the prefix assigned to the business ID format defined in the Business 360 Console.

For example, the business ID configuration is numeric, with a length of 15, and a prefix of 999. If you ingress a record with the business ID 1210000, the record is ingressed. However, if you try to ingress a record with the business ID 999000218888912220, the record isn't ingressed because it matches the defined business ID format. The input record doesn't participate in the match process and retains its business ID.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
121000000000001	Billing	Fred	Weasley	M	2-02-1987

After you run an ingress job, the input record becomes a source record and retains its business ID.

The MDM SaaS data store shows the newly added source record.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	CRM	Mary	Williams	F	01-01-1991
MDM000000000789	SFDC	Mary	W	F	-
MDM000000000456	SAP	John	Johnsons	M	03-03-2001
121000000000001 (Retains the business ID)	Billing	Fred	Weasley	M	2-02-1987

The ingress job creates a master record that contains the business ID of the input record.

The MDM SaaS data store shows the newly added master record.

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000123	Mary	Williams	F	01-01-1991
MDM000000000456	John	Johnsons	M	03-03-2001
121000000000001	Fred	Weasley	M	2-02-1987

Business ID of an input record matches the business ID of a master record

The business ID format can either be a defined or custom format. The input record bypasses the match process before merging with the master record. If the business ID of an input record matches the business ID of an existing master record, the ingress job merges the input record with the master record.

The input record contains a business ID that matches an existing master record.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	Admin	Mary	Wills	-	02-01-1991

After you run an ingress job, the input record merges with the master record.

The MDM SaaS data store shows that the input record is merged with the existing master record.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	CRM	Mary	Williams	F	01-01-1991
	Admin	Mary	Wills		02-01-1991
MDM000000000789	SFDC	Mary	W	F	-
MDM000000000456	SAP	John	Johnsons	M	03-03-2001
MDM000000000890	Billing	Fred	Weasley	M	2-02-1987

The ingress job merges the input record with the master record. The record doesn't go through the match and merge process.

The MDM SaaS data store shows the master records.

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000123	Mary	Wills	F	01-01-1991
MDM000000000456	John	Johnsons	M	03-03-2001
MDM000000000890	Fred	Weasley	M	2-02-1987

Business ID of an input record matches the business ID of a source record

The business ID format can either be a defined or custom format. If the business ID of an input record matches the business ID of a source record, the ingress job merges the input record with the master record to which the source record contributes. The input record doesn't go through the match process before merging with the master record. The job assigns a business ID to the input record based on the defined business ID format.

The input record contains a business ID that matches a source record.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000890	CRM	Fred	W	M	02-02-1987

After you run the ingress job, the input record becomes a source record that contributes to the master record, and a new business ID is assigned to the record.

The MDM SaaS data store shows the source records.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	CRM	Mary	Williams	F	01-01-1991
MDM000000000789	SFDC	Mary	W	F	-
MDM000000000412	Admin	Mary	Willis		02-01-1991
MDM000000000456	SAP	John	Johnsons	M	03-03-2001
MDM000000000890	Billing	Fred	Weasley	M	2-02-1987
MDM000000000911 (Autogenerated business ID for MDM000000000890)	CRM	Fred	W	M	02-02-1987

The ingress job merges the input record with the master record. The record doesn't go through the match and merge process.

The MDM SaaS data store shows the master records.

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000123	Mary	Wills	F	01-01-1991

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000456	John	Johnsons	M	03-03-2001
MDM000000000890	Fred	W	M	02-02-1987

Input record without a business ID

If an input record doesn't contain a business ID, the input record goes through the match and merge process. The ingress job assigns a business ID to the input record based on the defined business ID format.

The input record doesn't contain a business ID.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
-	CRM	Chase	Wolfinger	Male	05-05-1987

The ingress job creates a master record along with the corresponding source record. The input record goes through the match and merge process. The job assigns a business ID to the input record.

The MDM SaaS data store shows the newly added source record.

Business ID	Source System	First Name	Last Name	Gender	Birth Date
MDM000000000123	CRM	Mary	Williams	F	01-01-1991
MDM000000000789	SFDC	Mary	W	F	-
MDM000000000412	Admin	Mary	Willis		02-01-1991
MDM000000000456	SAP	John	Johnsons	M	03-03-2001
MDM000000000890	Billing	Fred	Weasley	M	2-02-1987
MDM000000000911	CRM	Fred	W	M	02-02-1987
MDM000000000977 (Autogenerated business ID)	CRM	Chase	Wolfinger	Male	05-05-1987

The ingress job creates a master record for the corresponding source record.

The MDM SaaS data store shows the newly added master record.

Business ID	First Name	Last Name	Gender	Birth Date
MDM000000000123	Mary	Wills	F	01-01-1991
MDM000000000456	John	Johnsons	M	03-03-2001
MDM000000000890	Fred	W	M	02-02-1987
MDM000000000977	Chase	Wolfinger	Male	05-05-1987

CHAPTER 3

Defining egress jobs

You can export data from Business 360 data store to an external data source. For example, your organization uses Customer 360 to master customer data. To analyze the purchase behavior of the customers, you want to load the mastered customer data to Tableau. You can export data from Customer 360 to Tableau.

You can export records based on their validation statuses.

You can define an egress job based on the following validation statuses of records:

- All. Exports all the records.
- Valid. Exports records that don't have any validation errors.
- Validation Errors. Exports records that have validation errors.

Key concepts

Before you create the export job, you must understand the following concepts:

Process

A Cloud Application Integration asset that provides a set of instructions to automate a business requirement. For more information about process, see *Informatica Cloud Application Integration Design*. The supported process to export data is Extract data from Business 360.

Taskflow

Cloud Data Integration workflow that consists of multiple tasks linked together. You can use a taskflow to run multiple tasks in a sequential order or in parallel. Use Cloud Data Integration to create taskflows that map source systems to target systems.

For example, if you want to export person and organization data from Customer 360 to Tableau, create a mapping to read customer details, and another mapping for organization details. Add mapping tasks for each of the mappings and create a taskflow with the two mapping tasks. Use the taskflow to export data from Customer 360 to Tableau. For more information about taskflows, see *Informatica Cloud Data Integration Taskflows*.

Note: Ensure that you do not include disabled fields in mappings. When you run a taskflow related to mappings that include disabled fields, the exported data does not include the data in disabled fields.

Assets

The Business 360 assets from which you want to export the mastered data. The supported assets are the business entities available in the Business 360 data store.

Supported Assets

You can egress data to the following types of assets:

- Predefined and custom business entities
- Predefined and custom relationships
- Hierarchies

Egress Process

The process available to egress data is MDMEgress.

The egress process includes the following steps:

1. Loads records from the MDM SaaS data store to a staging area.
2. Extracts records from the staging collection and writes them to an external data source.

For more details about these steps, see *Monitor MDM SaaS*.

Prerequisites

Before you export data, ensure that you meet the following prerequisites:

1. In Administrator, create a target connection to write data to a target and a Business 360 connection to read data from the Business 360 assets. For more information about creating connections, see Configuring a connection in the Administrator help.
2. In Administrator, specify a Secure Agent that is up and running as the runtime environment to run a mapping task.

   Note: Ensure that you don't share runtime environments between parent and sub-organizations. If you use a runtime environment of the parent organization in the sub-organizations, MDM SaaS can't retrieve the data from the parent organization.

   For more information about Secure Agent, see Runtime environments in the Administrator help.
3. In Cloud Data Integration, create a mapping with the target connection as the target transformation and the Business 360 connection as the source transformation. Define field mappings for the source and target fields. Ensure that you create an in-out parameter `jobInstanceId` in the Parameters panel. The name of the in-out parameter is case sensitive. For more information about creating a mapping, see Mapping configuration in the Data Integration help.
4. In Cloud Data Integration, create a mapping task by selecting the runtime environment and adding the mapping that you create. For more information about configuring a mapping task, see Mapping task configuration in the Data Integration help.
5. In Cloud Data Integration, create the required taskflows. Publish the taskflows to use in your egress job. For more information about creating taskflows, see Taskflows in the Data Integration help.

   Note: Ensure that you don't add a Command Task step to the taskflows that you create. If the taskflows contain the Command Task step, the egress jobs fail.

Export job types

After you master your data, you can export the mastered data to an external data source. You can either export all data or incremental data after exporting all data for the first time. You can also export source records. You can specify whether to export only master records or source records of the specific source systems.

You can use any one of the following export types:

Standard export

Exports all the records in the first run of a job based on their creation date, and then incrementally exports the records added or updated after the first run based on their last updated date.

For example, you add 30 records. During the first run of the job, the job exports 30 records. After the initial run of the job, you update 15 records. During the second run of the job, the job exports the 15 records that you updated.

Note: When you run an egress job to perform a standard export of active records in a hierarchy, the exported data includes deleted child records.

Custom export

Exports all the records added or modified after the specified date in the first run of the job, and then exports the records added or updated after the first run incrementally.

For example, you add 20 records after October 15, 2020, 5:00 p.m. During the first run of the job, the job exports 20 records. After the initial run of the job, you update 10 records. During the second run of the job, the job exports the last updated 10 records.

Export all

Exports all the records in each run of the job based on their creation date.

Note: When you run an egress job to incrementally export records, the job exports records that were created or updated before the job runs. The exported data doesn't include records that are created or updated during the execution of the job.

Rules and guidelines for exporting data

Consider the following rules and guidelines when you create an egress job to export data:

- If you rename or delete a business entity in Business 360 Console, existing mappings that reference the business entity fail when you run the mappings. Egress jobs that use these mappings also fail.
- Ensure that you don't use a dot (.) in the display name of a business entity. If the display name contains a dot, MDM SaaS retrieves only the root fields when you egress the field groups using Business 360 FEP Connector.
- If you update source objects in existing mappings, the updates aren't reflected in egress jobs that use these mappings. The mappings in the egress jobs use the objects that existed before the update. To apply the new objects, edit and save these egress jobs again in Business 360 Console.
- When you use rich text format in text fields, use only supported HTML tags and attributes. MDM SaaS removes unsupported tags and attributes for security reasons.

  For more information about rich text formatting, see *Rich text formatting for text fields*.

Egress data

Create an egress job to export data from Business 360 data store to an external data source.

1. In Business 360 Console, click **New** > **Jobs** > **Egress** > **Create**.
2. In the Export Job dialog box, enter the details, and click **OK**.

   The export job page appears.
3. Click the asset picker, and select the **MDMEgress** process.

   Note: Reference 360 uses the RDMEgressFlow process, so ensure that you don't select it in Business 360 Console.
4. Select whether you want to export active records, deleted records, or both. Default is Active.

   Note: Egress jobs created before the July 2024 release will have the record type set to Active by default. To include deleted records, you can edit the job and select Deleted.
5. Select one of the export types.

   For more information about export types, see "Export job types" on page 21.
6. To add a taskflow, perform the following steps:
   a. Click **Add Taskflow**.

      The Select a Taskflow page appears.
   b. Select the taskflow, and click **OK**.

      The taskflow appears in the Taskflows section and the associated assets appear in the Assets section.

      Note: Ensure that you select taskflows that use the same connector type. You can't add taskflows that use both Business 360 Connector and Business 360 FEP Connector to an egress job.
   c. In the **Record Type** list, specify whether to export master or source records.

      Note: When you add taskflows that use Business 360 FEP Connector, you can export both source and master records for relationships and hierarchies.
   d. Select the source system from which you want to egress data. The default source system is *Default*.

      Note: The master records from all the source systems are exported by default. To export source records from specific source systems, clear the source systems from the list as required.
7. After you add a taskflow, select whether you want to export all records, valid records, or those with validation errors.
8. Save the job.
9. To run the job, click **Run**, or schedule the job to run later.

   On the **My Jobs** page, you can monitor the status of the job.
   For more information about monitoring egress jobs, see *Monitor MDM SaaS*.

Exported data

The egress job to export source records exports the changed and updated business entity, relationship, or hierarchy data to a file. The file includes the states of field groups, such as active and deleted.

When you change or add a business entity, relationship, or hierarchy data in your business application, the egress job for source records exports the following data to a file:

- Changed or newly added attributes of relationships and relationships within hierarchies.
- Attributes of relationships and relationships within hierarchies that were added after the previous run of the export job.
- Changes in business entity data and the state of field groups, such as active and deleted.
- System fields, such as source last updated date, match and merge status, and the population name used to match records.

  Note: The source last update date field appears for field groups only when it's enabled. By default, the source last updated date field is enabled only for the root fields.

If changes are made before the first run of an egress job, the egress job exports the entire data. During subsequent runs, the egress job exports only new and changed values.

Note: In the exported data, the updated fields contain values and the fields without updates appear empty.

When you run an egress job that uses Business 360 FEP Connector in the mapping to export field groups, the exported data includes the source systems of the field groups. If multiple entries of field groups appear in the exported data, you can uniquely identify them based on their source systems. For example, when your exported data contains multiple entries of billing addresses, you can identify each address based on its source system.

Master records aren't associated with source systems. However, when you run an egress job to export master records, the source system column in the exported data displays MDM. To view source records from specific source systems that contribute to master records, run an egress job to export source records.

For example, you manage customer data in different source systems, such as CRM and Salesforce. You get the contact and account details of customers from CRM and purchase history of customers from Salesforce. The details of customers from these source systems are consolidated to form master records. When you export the master records, the exported data displays MDM as the source system and doesn't include CRM and Salesforce.

Parent IDs of field groups in the exported data

You can include the parentId values for each field group when you export business entity records. The parentId fields determine the correct structure of the business entity when you consolidate data exported by multiple egress jobs into a single record in the target system.

The parentId values differ for master records and source records. When you export master records, the parentId value of a first-level field group is the businessId value of the corresponding business entity record. When you export source records, the parentId value of a first-level field group is the source primary key value of the root record. To include the parentId values in the exported data, map the parentId fields when you create mappings in Cloud Data Integration and use those mappings in the taskflow that you use to export data. For more information about mappings, see the *Business 360 Connector Guide*.

When you use Business 360 FEP Connector to export field group data, the exported data contains a column that displays the parent ID value of the root field associated with the field group. For example, if you export the Address field group of a source record, the exported data contains a column that displays the parent ID value, which is the source primary key value of the root record associated with the Address field group.

When you export a nested field group, the exported data contains a column that displays the ID values of the root field associated with the field group and an additional column that displays the ID value of the field group's first-level parent. However, the additional column always appears empty because the egress process requires only the parent ID value of the selected field group for the export. For example, if you export the Home Address field group nested within the Address field group, the exported data contains a column that displays the parent ID value of the Home Address field group. The exported data also contains an additional column that displays the parent ID value of the Address field group. The additional column that displays the parent ID value of the Address field group always appears empty in the exported data.

Business IDs of records in the exported data

When you run the egress job to export the master or source records, the egress job exports the records and displays the merged business IDs and the original business IDs in the exported file.

The exported file includes the following business IDs:

Merged Business IDs

When you export master records, the exported file contains the mergedBusinessId column. This column contains all the business IDs of the source records that merged into the master records.

Note: By default, the character limit for the mergedBusinessId column is 255. To include a maximum of 1000 merged business IDs in the exported file, modify the mergedBusinessId field value up to 30000 in the source transformation mapping. For more information, see the *Business 360 Connector Guide*.

When you export the master records, the exported file doesn't display any values in the originalBusinessId column.

Original Business IDs

When you export the source records from specific source systems, the egress job exports the surviving business ID of the master record for each of the source records. The exported file contains the originalBusinessId column that displays the business ID that is assigned to the source records at the time of record creation.

When you unmerge the source records and export the records, the business ID of the master record is replaced with the original business ID.

When you export the source records, the exported file doesn't display any values in the mergedBusinessId column.

Match pairs

The match process matches records and generates match pairs based on the match model configuration. You can export the match pairs that the match process generates.

When you export match pairs that are generated by the match and merge jobs, the exported data displays the business IDs of the match pairs.

You can export a maximum of 20 million match pairs. When you export more than 20 million match pairs, the egress job fails. To increase the export limit, contact Informatica Global Customer Support.

Note: The exported data contains the <Business entity>_jobInstanceId column that displays the match and merge job instance ID. For example, the values in the Person_jobInstanceId column indicate the match and merge job instance IDs of the Person business entity.

CHAPTER 4

Defining match and merge jobs

After you configure the match model, you can define a job to match records and another job to merge records or a single job to match and merge records. The match and merge job depends on the match and merge process. When you run a match and merge job, it completes the match and merge process.

Additionally, you can run a match and merge job exclusively to update match explainability metrics based on the most recent match jobs. After the job completes, the match analysis and explainability dashboard in your business application shows the latest metrics. Alternatively, you can update the metrics as part of a regular match and merge job. However, if you want the job to complete faster, you can exclude the metrics update. When you configure a job to update the match explainability metrics, you can also choose to update large cluster metrics.

When you configure a job to update the match explainability metrics, you can also update the large cluster metrics. Large clusters form when a large number of records match one another. You can update the large cluster metrics to identify and analyze these clusters, or exclude them to complete the job faster.

A process is a Cloud Application Integration asset that is a set of instructions to automate a business requirement. For more information about processes, see *Informatica Cloud Application Integration Design*.

When you define jobs to match and merge records, you can choose the following process types:

Match and Merge

Identifies matching records, creates record pairs, and automatically merges them depending on the merge configuration. Based on the merge configuration of the model, the process merges the records automatically, queues the records for manual merge, or skips the records as not a candidate for merge. Optionally updates the match explainability metrics, and can also update the large cluster metrics.

Match Only

Identifies matching records and creates record pairs. If you select the Match Only process, you can view and analyze the number of record pairs that automatically merge or require manual review. You can then decide whether you want to enhance the match configuration. Optionally updates the match explainability metrics, and can also update the large cluster metrics.

Merge Only

Merges record pairs that are identified by the match process for automated merge. You can choose the Merge Only process for the existing matched records.

Reset the Matched Records

Resets the matched records that are not yet merged and makes the records available for matching again. You can reuse the records multiple times for matching. For example, if you publish a new match model, you can choose to rematch the matched records that are not yet merged.

Update Match Explainability Metrics

Updates the match explainability metrics, including large cluster metrics, on the match analysis and explainability dashboard based on the most recent match jobs. If no match job has run, the metrics don't appear.

Run a match and merge job after you complete running the ingress jobs to load all your data. If you run a match and merge job after every ingress job, data that has already undergone matching goes through the match process again.

If declarative rules aren't configured properly or the quality of data is poor, a match job can generate excessive match pairs that might affect the performance of your organization. To prevent excessive match pair generation, MDM SaaS limits the number of match pairs a match job can generate. When the match pairs exceed the limit, MDM SaaS fails the job. Modify the declarative rules or enhance the quality of the data before running the job again.

For more information about generating fewer match pairs, contact Informatica Global Customer Support.

After you run match and merge jobs, you can monitor the status of the jobs on the My Jobs page. For more information about monitoring jobs, see *Monitor MDM SaaS*.

Note: You cannot run two match and merge jobs in parallel for a business entity.

Define and run a match and merge job

To match and merge duplicate records in the Business 360 data store, define and run a match and merge job.

1. Click **New** > **Jobs** > **Match and Merge** > **Create**.

   The **Match and Merge** dialog box appears.
2. Specify the job properties, and click **OK**.

   The job page appears.
3. Select a process. The supported process is MDMMatchMerge.
4. Select one of the following process types:

Option	Description
Match and Merge	Identifies matching records and automatically merges them.
Match Only	Identifies matching records.
Merge Only	Merges matching records that are identified by the match process.
Reset the Matched Records	Resets the matched records that are not yet merged and makes the records available for matching again.
Update Match Explainability Metrics	Updates the key metrics, including large cluster metrics, on the match analysis and explainability dashboard based on the most recent match jobs.

5. Select the business entity.
6. If you select the **Match and Merge** or **Match Only** process type, perform the following steps:
   a. Select a match model and the model version to use for the job.

b. To skip the group potential matches step of the job, select **Skip grouping potential matches**.

   You can skip the step for the following reasons:

   - The declarative rules in the match model use the automated merge strategy.
   - You don't need to optimize the number of approval tasks in the workflow inbox.

   For more information about the group potential matches step, see *Group potential matches*.

c. To update key metrics on the match analysis and explainability dashboard , select **Update match explainability metrics**.

d. If you select **Update match explainability metrics**, then to update the metrics related to large clusters, select **Update large clusters metrics**.

7. If you select the **Update Match Explainability Metrics** process type, select **Update large clusters metrics** to include the large clusters metrics in the update.
8. Save the job.
9. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page.
   For more information about monitoring match and merge jobs, see *Monitor MDM SaaS*.

CHAPTER 5

Defining generate merge tasks jobs

The match process identifies pairs or records that require manual review. Use the generate merge tasks job to group the pairs or records and generate review tasks for groups that require manual review. Users then review the tasks and manually merge the appropriate records.

You can define generate merge tasks jobs for native or external workflows.

You can run your existing jobs that don't have the business event type without editing them. When you try to edit the task limits of existing jobs, you have to configure the business event type and task limit.

: Effective in the October 2026 release, the ability to define generate merge tasks jobs for native workflows is available for preview.

Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

After you run a generate merge tasks job, you can monitor the status of the job on the My Jobs page.

For more information about monitoring jobs, see *Monitor jobs*.

Define and run a generate merge tasks job

To generate merge tasks for pairs identified by the match process and require a review, define and run a generate merge tasks job. For example, you might want to generate merge tasks for pairs identified for the Person business entity records.

When you edit a job for which you configured a limit that exceeds the permitted task limit, you have to enter a new value within the permitted limit.

1. Click **New** > **Jobs** > **Generate Merge Tasks** > **Create**.

   The **Generate Merge Tasks** dialog box appears.
2. Specify the job properties, and click **OK**.

   The generate merge tasks job page appears.
3. Select a process.

   The supported process is MDMGenerateMergeTasks.

4. Select the business event type.

   Use one of the following event types:

   - Native workflow-based. Creates manual merge tasks in the task inbox for business events based on native workflows.
   - External workflow-based. Creates manual merge tasks in the workflow inbox for business events based on external workflows.

5. If you select the native workflow-based business event type, select the task limit type.

   Use one of the following task limit types:

   - Custom. Uses a custom value within the permitted limit for your organization.
   - Default. Uses the predefined maximum permitted limit for your organization.

6. Enter a numerical value within the permitted range.

   If you select the default task limit type for the native workflow-based business event type, MDM SaaS automatically sets the task limit to the predefined maximum for your organization.

   For more information about task limits for generate merge tasks jobs, see *Job definitions*.

7. In the **Assets** section, click **Add**.
8. In the asset window, select the asset types that you want to run the job on, and click **Select**.

   Note: You can configure only one asset for the native workflow-based business event type.

9. Save the job.
10. To run the job, click **Run**.

    You can monitor the status of the job on the My Jobs page.
    For more information about monitoring generate merge tasks jobs, see *Monitor MDM SaaS*.

CHAPTER 6

Defining recover a failed job

When you run a job, such as a match and merge job, some records might not get processed. You can run the recover a failed job to identify records that were not processed and process them.

After you run the recover a failed job, you can monitor the status of the job on the **My Jobs** page. For more information about monitoring jobs, see *Monitor Jobs*.

Define and run a recover failed job

To find and process records that are not fully processed, define and run a recover failed job. For example, you might want to find and process Person business entity records that are not fully processed and then process them.

1. Click **New** > **Jobs** > **Recover a Failed Job** > **Create**.

   The **Recover a Failed Job** dialog box appears.
2. Specify the job properties, and click **OK**.

   The job page appears.
3. Select the business entity for which you want to process the records.
4. Select a match model and the model version to use for the job.
5. Save the job.
6. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page.
   For more information about monitoring the recovery of failed jobs, see *Monitor MDM SaaS*.

CHAPTER 7

Defining generate search indexes or match keys job

You can define a job that indexes records and their tasks based on native workflows for search requests or generates match keys for the match process. When you index for search requests, you can index both records and their tasks, or only tasks. You can generate match keys for both source and master records in a business entity.

When you update the search configuration of a business entity, run this job so that the search indexes reflect the latest configuration. When you enable reference data as multilingual and add reference data in multiple languages, run this job so that the search indexes include the localized data.

When you update the match model configurations and run the match and merge job, the match process uses the existing match keys. To generate updated match keys for the merged records and the records that are in the process of merge, run the generate search indexes or match keys job.

After you set the fields in a business entity as reportable and update the business entity, run this job to generate report indexes for the business entity records. Otherwise, the report data continues to use outdated report configuration.

Note: Effective in the October 2026 release, the ability to index native workflow-based tasks for records and search for records by using localized picklist values is available for preview. Effective in the November 2023 release, the ability to generate indexes for reportable fields in a business entity is available for preview.

Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

For records created before the July 2024 release, match keys weren't generated for the master records by default. To generate match keys for the master records, run the generate search indexes or match keys job.

Define and run the generate search indexes or match keys job

When you update the search configurations or match model configurations for the business entity, you can run this job using the MDMSearchIndex process or the MDMMatchReindex process. You can also run the job using the MDMSearchIndex process to index native workflow-based tasks for records.

Note: Effective in the November 2023 release, the ability to run this job to generate report indexes is available for preview. To index report data, you can run this job by using the MDMSearchAndReportsIndex process.

Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

1. Click **New > Jobs > Generate Search Indexes or Match Keys > Create**.

   The index job dialog box appears.
2. Specify the job properties and click **OK**.

   The index job page appears.
3. Enter a name for the job and click **OK**.
4. Select one of the following processes:
   - MDMSearchIndex or MDMSearchAndReportsIndex. If you see the MDMSearchIndex option, it indexes records and their tasks for search requests. If you see the MDMSearchAndReportsIndex option, it indexes records for search requests and report data.
   - MDMMatchReindex. Generates match keys for the match process.
5. If you select the MDMSearchIndex or MDMSearchAndReportsIndex process, perform the following actions:
   a. To index only tasks and not records when you select the MDMSearchIndex process, select **Index Only Tasks**.
   b. In the **Assets** section, click **Add Asset**.

      The **Select an Asset** dialog box appears.
   c. Select the business entities for the job, and click **Select**.
6. If you select the MDMMatchReindex process, select a business entity and the record type that you want to generate match keys for.

   You can select the following options:
   - Source. Generates match keys for all the source records in the business entity.
   - Master. Generates match keys for all the master records in the business entity.

     Important: To match and export data, generate match keys for all the master records. The match process uses the match keys of master records to match the data from the input file with that of the master records.
7. To save the job, click **Save**.
8. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page.
   For more information about monitoring generate search indexes or match keys jobs, see *Monitoring generate search indexes or match keys jobs*.

CHAPTER 8

Defining publish business events jobs

You define the publish business events job to publish events from business applications to external targets that Cloud Data Integration supports. You can publish events that are related to actions on business entity records, such as create, update, and delete.

A publish business events job depends on the publish process. A process is a Cloud Application Integration asset that is a set of instructions to automate a business requirement. For more information about processes, see *Informatica Cloud Application Integration Design*.

When you run the publish business events job, the publish process runs the taskflow that you create in Data Integration to publish events to external targets. After you run the job, you can monitor the status of the job on the **My Jobs** page. For more information about monitoring jobs, see *Monitor Jobs*.

Prerequisites for a publish business events job

Before you define a publish business events job, complete the following prerequisite tasks:

1. In Business 360 Console, define a publishing event. For more information about defining a publishing event, see Defining publishing events in the Business 360 Console help.
2. In Administrator, specify a Secure Agent that is up and running as the runtime environment to run a mapping task. For more information about Secure Agent, see Runtime environments in the Administrator help.
3. In Administrator, create a Business 360 Events connection to read events from a Business 360 application and a target connection to publish events to an external target. For more information about creating connections, see Configuring a connection in the Administrator help.
4. In Cloud Data Integration, create a mapping with the Business 360 Events connection as the source transformation and the target connection as the target transformation. Ensure that you create the in-out parameters `startAtTimestamp` and `endAtTimestamp` in the Parameters panel. For more information about creating a mapping, see Mapping configuration in the Cloud Data Integration help.

   Note: The name of the in-out parameter is case sensitive.
5. In Cloud Data Integration, create a mapping task by selecting the runtime environment and adding the mapping that you create. For more information about configuring a mapping task, see Mapping task configuration in the Cloud Data Integration help.

6. In Cloud Data Integration, create the required taskflows. Publish the taskflows to use in your business events publishing job. For more information about creating taskflows, see Creating a taskflow in the Cloud Data Integration help.

Define and run a publish business events job

To publish business events from the Business 360 data store to an external target, define and run a publish business events job.

1. Click **New** > **Jobs** > **Publish Business Events** > **Create**.

   The **Publish Business Events** dialog box appears.
2. Specify the job properties, and click **OK**.

   The job page appears.
3. Select a process. The supported process is **Publish Business Events**.
4. Select one of the following publish types:

Publish Type	Description
Standard publish	Publishes all events in the first job run and incrementally publishes new events in subsequent runs.
Custom publish	Publishes events based on the specified dates. If only a start date is specified, the job publishes all events from the specified date to the current date of each run. If a date range is specified, the job exports events for the specified date range.

5. To add a taskflow, perform the following steps:
   a. In the **Taskflows** section, click **Add Taskflow**.

      The **Select a Taskflow** dialog box appears.
   b. Select the taskflow for the job, and click **Select**.

      The taskflow appears in the **Taskflows** section, and the associated business events appear in the **Business Events** section.
6. Save the job.
7. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page.
   For more information about monitoring publish business events jobs, see *Monitor MDM SaaS*.

CHAPTER 9

Defining process hierarchies jobs

You can define a job to index a hierarchy and to process the inheritance of dynamic field definitions within a searchable hierarchy.

After users update hierarchies or add dynamic field definitions to records that are part of a hierarchy, run a process hierarchies job. This job ensures that the child records inherit the dynamic field definitions, and hierarchy filters on the search results page reflect the changes in hierarchies.

To help optimize performance and promote fair utilization of shared resources, MDM SaaS introduced limits for dynamic fields and hierarchy filtering. For more information about the limits, see *Getting started* in the Business 360 Console help.

When you manually run a process hierarchies job, the job indexes all records in hierarchies. When you schedule a process hierarchies job, MDM SaaS checks whether it's efficient to index all the records or only the changes in hierarchies before running the job. For example, after you update a hierarchy model, a scheduled job indexes all the records in hierarchies. Similarly, if users update a hierarchy by adding or deleting relationships, a scheduled job might index only the changes in the hierarchy. To ensure that inheritance of dynamic fields and search results reflect the latest changes in hierarchies, schedule a process hierarchies job to run at regular intervals. For information about scheduling jobs, see the Monitor MDM SaaS chapter in the Business 360 Console help.

Note: The process hierarchies job doesn't index tasks for hierarchies.

Define and run a process hierarchies job

After users update hierarchies, you can run a process hierarchies job to index the records that are part of the hierarchies and to process the inheritance of dynamic field definitions.

1. Click **New > Jobs > Process Hierarchies > Create**.

   The **Process Hierarchies** dialog box appears.
2. Specify the job properties, and click **OK**.
3. On the job page, select the hierarchy that you want to process.

   If the hierarchy that you want to select doesn't appear, ensure that the hierarchy is configured to be searchable.
4. To save the job, click **Save**.
5. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page
   For more information about monitoring process hierarchies jobs, see *Monitoring process hierarchies jobs*.

CHAPTER 10

Defining reprocess master data jobs

You can define a reprocess master data job to apply the latest data enrichment and validation and survivorship configurations to active and deleted records.

After you update data enrichment and validation configurations or survivorship configurations, run the reprocess master data job to apply the updated configurations to master records. When you run the reprocess master data job for active records, the data enrichment and validation and survivorship configurations are applied to both active and pending master records. The updated records are indexed for search.

If a deleted master record has active source records, the job applies the configurations to its active source records. If a deleted master record has no active source records, the job applies the configurations to its deleted source records.

Preview Notice: Effective in the April 2026 release, the ability to apply data enrichment and validation configurations to master records is available for preview. Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

If a publishing event is defined for updates to business entity records, the update events are published only for records that changed based on the updates to data enrichment and validation or survivorship configurations.

Effective in the July 2024 release, if you delete any master records, you can search for the deleted records and view them. If you deleted any master records before the July 2024 release, those records weren't indexed for search, and the trust scores of their field values weren't up to date.

If you want to view master records that you deleted before the July 2024 release, you have to reprocess them and recalculate trust scores for the field values based on the survivorship configuration. This job also indexes the deleted master records for search, and you can search for them.

Define and run a reprocess master data job

Before you run the reprocess master data job, ensure that jobs to match and merge, generate merge tasks, or recover failed jobs aren't in progress so the job can process the latest records. If you run the job to apply

data enrichment and validation and survivorship configurations to active or deleted records, also ensure that all changes that require data reprocessing are complete.

1. Click **New** > **Jobs** > **Reprocess Master Data** > **Create**.

   The **Reprocess Master Data** dialog box appears.
2. Specify the job properties, and click **OK**.

   The job page appears.
3. Select a process.

   The supported process is MDMProcessMasterData.
4. Select one of the following process types:

Process Type	Description
Reprocess Master Data	Applies the data enrichment and validation configurations to master records, and recalculates trust scores of master records based on the survivorship configurations. If a configuration isn't updated, only the updated configuration is applied. For example, if you update the data enrichment and validation configuration but not the survivorship configuration, the process applies only the data enrichment and validation configuration.
Recalculate Trust Score	Recalculates trust scores of master records based on the survivorship configurations.

5. Select whether you want to apply the configurations for active records, deleted records, or both. Default is Active.
6. In the **Assets** section, click **Add**.
7. Browse to a business entity that you want to run the job on, and click **Select**.
8. Save the job.
9. To run the job, click **Run**.

   You can monitor the status of the job on the **My Jobs** page.
   For more information about monitoring reprocess master data jobs, see *Monitor MDM SaaS*.

INDEX

G

generate merge tasks
  create 28
  overview 28
generate merge tasks job
  define 28

J

job
  publish business events 33, 35

M

match and merge job
  create 26
  define 26
  run 26, 28

P

publish business events job
  about 33, 35
  create 34
  define 34
  run 34