

Scan37: geometry and coverage across nine methods

One new scene; 24 disjoint source-vertex patches, 1,024 input points per patch.

Method	MAE↓ mm	Recall↑ % at 1 mm	F-score↑ at 1 mm	Move RMS mm
Identity	0.437246	92.358	0.912854	0.000000
Frozen V18	0.459480	87.688	0.887500	0.376979
APSS2	0.436517	92.169	0.912036	0.034471
RIMLS2	0.437229	92.219	0.912017	0.030153
Local plane, $k = 64$	0.431515	91.414	0.908295	0.155598
Local quadratic, $k = 64$	0.434305	92.109	0.911920	0.097220
Multiscale, full update	0.433563	91.975	0.911316	0.088351
V22 consensus (primary)	0.434631	92.025	0.911513	0.060456
Matched-RMS constant damping	0.434344	92.037	0.911430	0.060456

Blue identifies the preselected primary method, not the best score. Every metric is averaged equally over the 24 patches. Evaluation uses the fixed observed local region; scored point counts can differ from the 1,024-point input. Recall measures reference coverage within 1 mm. These are local patch results, not official full-scene DTU scores.

Paired reading. Against identity, the primary method reduces mean MAE by 0.598%, while recall decreases by 0.333 percentage points. Matched-RMS constant damping has a slightly lower MAE than the primary method.