PhishX | Scanner guide

Person 3 final review - 21 October 2026. Local academic prototype; model scores are not calibrated probabilities of real-world phishing.

1. Start the established demo

From the project folder on macOS, after installing dependencies and extracting the trusted classical model handoff:

```
cd /Users/gauri/Documents/ChatGPT/PhishX
bash scripts/start-dev.sh --live
```

Open **http://127.0.0.1:5173**. Keep the terminal running. Ctrl+C stops both services. Omit **--live** to keep scans text-only. On Windows, use the existing scripts/start-model.ps1 launcher and run pnpm dev in frontend.

2. Scan a URL and read the result

Enter a complete http:// or https:// URL and choose **Analyze URL** (or press Enter). A score and normalized host appear with the model path, version, observed features and available explanations. Scanning alone analyzes the URL as text.

Score	Band	Interpretation
0-30	Low	Lower model output; not a safety guarantee
31-60	Medium	Inspect the URL and context carefully
61-80	High	Strong model concern; independently verify
81-100	Critical	Very strong model concern; mistakes remain possible

3. Choose optional live checks

After a model result, choose **Run live checks**. This contacts the target for headers and registration services for RDAP data. DNS, TLS, redirects and domain age show explicit statuses. Page content is not analyzed, and the model score is unchanged. Private targets and unsupported ports are blocked. Unavailable data is not a benign verdict.

4. Know the research limitations

The default is classical v6. The optional CNN/cascade requires a separate handoff and explicit research enablement. It produced substantially more false positives on broader-source testing, so it is not promoted. CNN-routed outputs have no validated SHAP explanation; no substitute reasons are shown. The small Person 3 fixture is a regression check, not a benchmark.

5. Recover from errors

Invalid URL: check scheme, spaces, hostname and percent encoding. **Backend unreachable:** start the API, then choose Retry connection. **Port occupied:** use the running app or stop its original terminal with Ctrl+C. **Live checks timeout:** retry; the text-model result remains valid as the recorded model output.

Detailed findings, sources and screenshots: docs/person3-final-review.md. No production safety claim or human teammate sign-off is implied.