PhishX: local scanner guide

Classical prototype | Revised model v6 | 7 October 2026

1 Receive the model

Pull branch **gauri**. Extract the trusted **PhishX_model_handoff_v6.zip** into the repository root. Weights belong at artifacts/revised-run06/classical.joblib and are shared separately from Git.

2 Set up once (Windows PowerShell)

Run these commands from the repository root:

```
python -m venv .venv
.\.venv\Scripts\python.exe -m pip install -r backend/requirements-dev.txt
.\.venv\Scripts\python.exe -m pip install -r ml/requirements-verified.txt -e .
```

3 Start the real API

The launcher verifies the model checksum and enables model mode:

```
powershell -ExecutionPolicy Bypass -File scripts/start-model.ps1
```

4 Start the interface

In a second terminal, run **cd frontend**, **pnpm install --frozen-lockfile**, then **pnpm dev**. Open **http://127.0.0.1:5173**. On macOS/Linux use the repository setup guide or VS Code task **PhishX model backend**.

5 Analyze and interpret

Confirm **Model API ready**. Enter an HTTP/HTTPS URL (maximum 2,048 characters), then select **Analyze URL** or press Enter. The scanner treats URLs as text and never visits the submitted page. Synthetic examples are pattern tests, not verified attacks.

Low	Medium	High	Critical
0-30	31-60	61-80	81-100

The score is an **uncalibrated model output**. Model contributions show up to three positive SHAP features; observed signals are separate. A low score does not guarantee safety. Live DNS/TLS/age/redirect checks and the Char-CNN cascade remain unavailable.

6 Recover and review

For input errors, check the scheme, hostname, spaces and percent encoding. For connection errors, restart the API, select **Retry connection**, then scan again. A missing model returns not-ready/503; fixture mode is opt-in and illustrative. Read the footer evaluation report and person3-review.md. The separate fixture exposed two false positives and one phishing miss; these are retained in the bug list.