

Qty	Part	Description	Notes
Electronics			
1	Motor	42AIM, 57AIM, 60AIM, 60AIM40F	See recommended builds for more information
1	PCB	R+D or ALT	
1	* Remote	Wired remote or RADR	Wired remote for R+D PCB only
Rails			
1	MGN12	≤ 400 mm	Std Head
1	MGN15	350 ~ 500 mm	Std Head
1	HGR20	≥ 500 mm	XL Head
<i>Select one, size / type depending on your Super OSSM build</i>			
1	MGN12H	MGN12 rail	Std Head
1	MGN15H	MGN15 rail	Std Head
1	HGH20HA / QHH20A	HGR20 rail	XL Head
<i>Select one, size / type depending on your Super OSSM build</i>			
4	M3 x 12 mm	Socket head	MGN12 rail
4	M3 x 10 mm	Socket head	MGN15 rail
4	M5 x 15 mm	Socket head	HGR20 rail
<i>Select one, size / type depending on your Super OSSM build</i>			
Belts & Pulleys			
1	2MGT x 12 mm	~1 m length, cut to size	MGN12 rail
1	3MGT x 12 mm	~1 m length, cut to size	MGN12 rail
1	2MGT x 15 mm	~1 m length, cut to size	MGN15 rail
1	3MGT x 15 mm	~1 m length, cut to size	MGN15 rail
1	HTD-3M x 15 mm	~1 m length, cut to size	HGR20 rail
1	Dyneema 1.5 mm	~2 m length, cut to size	Capstan Drive
<i>Select one, size / type depending on your Super OSSM build</i>			
1	2MGT 20T 8 mm Bore Pulley	12 ~ 15 mm for belt width	Motors - 42AIM, 57AIM
1	3MGT 20T 8 mm Bore Pulley	12 ~ 15 mm for belt width	Motors - 42AIM, 57AIM
1	HTD-3M 25T 14 mm Bore Pulley	15 mm for belt width	Motors - 60AIM, 60AIM40F
1	Capstan Pulley	Print version for motor type & head size	Motors - ALL
<i>Select one, size / type depending on your Super OSSM build</i>			
* Bearings			
8	688-ZZ / 688-2RS	8 x 16 x 5 mm	Required for Belt drive only
Head			
4	M4 x 30 mm	Socket head	Std Head
4	M4 x 50 mm	Socket head	XL Head
4	M4 nut	Nylon locknut	
Motor Ring			
4	* M3 x 6 mm	Countersunk head	Motor Ring - 42AIM
4	M5 x 15 mm	Countersunk head	Std Head Motor Ring - 60AIM
4	M5 x 20 mm	Countersunk head	Std Head Motor Ring - 42AIM, 57AIM, 60AIM40F XL Head Motor Ring - 60AIM
4	M5 x 25 mm	Countersunk head	XL Head Motor Ring - 42 AIM, 57AIM, 60AIM40F
4	* M5 nut	Nylon locknut	Motor Ring - 42 AIM, 57AIM, 60AIM40F
<i>Select, size / type depending on your Super OSSM build</i>			
PCB Housing			

Qty	Part	Description	Notes
4	* M2 nut	Standard nut	Optional to lock the PCB cover
2	* M2 x 6 mm	Button or Socket head	Optional to lock the PCB cover
#	M3 nut	Standard nut	(3) R+D PCB (2) ALT PCB
#	M3 x 10 mm	Button or Socket head	(3) R+D PCB (2) ALT PCB
* Rail Ends			
1	M4 nut	Standard nut	Tensioner
1	M4 x 25 mm	Socket head	Tensioner (MGN12 & MGN15)
1	M4 x 30 mm	Socket head	Tensioner (HGR20)
1	M3 nut	Nylon locknut	Fixed end (MGN12 & MGN15)
1	M3 x 18 mm	Socket head	Fixed end (MGN12 & MGN15)
1	M5 nut	Nylon locknut	Fixed end (HGR20)
1	M5 x 22 mm	Socket head	Fixed end (HGR20)
<i>Select, size / type depending on your Super OSSM build</i>			
* Capstan Drive			
2	M3 washer	Flat washer	Std Head - 7 mm OD XL Head - 10 mm OD
2	M3 nut	Standard nut	
2	M3 x 6 mm	Socket head	Std Head
2	M3 x 10 mm	Socket head	XL Head
4	U604ZZ	Groove bearing 4 x 13 x 4 mm	
6	M4 nut	Nylon locknut	
4	M4 x 25 mm	Socket head	Bearings
2	M4 x 50 mm	Socket head	Tensioner
1	M4 x 20 mm	Countersunk head	Pulley to motor (42AIM & 57AIM)
1	M4 x 30 mm	Countersunk head	Pulley to motor (60AIM)
1	M5 x 25 mm	Countersunk head	Pulley to motor (60AIM40F)
Clamp			
2	M4 washer	Flat washer	Max OD 8 mm
1	M4 nut	Standard nut	
4	M4 nut	Nylon locknut	
1	M4 x 12 mm	Socket head	
4	M4 x 25 mm	Socket head	Replace (2) with M4x30mm for 4040 version
2	M6 x 12 mm	Socket head	
1	M6 Double T-Nut	25 mm hole spacing	Alternative - (2) M6 Single T-nuts
#	Furniture Pad	38 mm / 1.5 inch self-adhesive	Desk and Bed mounts

* Optional part * Additional part

Note : Due to the modular design of the Super OSSM, parts for all build configurations listed in the BOM.
Please check the Notes and compile YOUR parts list carefully before ordering.