

有界示向误差下无线电干扰源的 覆盖认证搜索与快速清除

摘要

无线电干扰源数量、接收半径以及定向源的发射方向均未知，因而快速定位不仅是多条示向线求交，还必须解决误差约束、全区域发现与正确停止三个问题。本文采用“确定性覆盖保证正确性、观测驱动调度降低耗时”的统一框架。

针对问题一，将每次示向度转为正向楔形半平面约束，给出空集、有界和无界情形的判别及顶点对直径算法。构造由合法测向观测实现的边长 36 米等边三角形反例，证明直径为区域直径的圆不一定覆盖区域；以最小包围圆半径代替区域直径作为一次清除判据。

针对问题二，利用首次接收到信号隐含的接收半径下界，推导无需已知目标距离的三圆交候选区域。以交会夹角与距离共同刻画测向条件，并以候选点的后验可行域包围圆半径进行采样极小极大评分，区分可证明的接收安全性与启发式的最优性。

针对问题三，建立七点全向覆盖及其精确半径公式，以 1200 米环保留 31.10 米接收余量；针对问题四，以原点和错相双十二点环构成 25 点骨架，用 36 个闭三角形证明任意发射方向不漏检。每频道分别维护清除或全覆盖无源证书，局部保留有界测向与完整光学后备。

在 Q3、Q4 各 10 轮官方模拟器演练（非正式测试）中，原策略分别清除 139/139 与 138/138 个源；移动占虚拟时间约 74.38% 和 73.20%。据此提出 `field`：保留原路线作为控制，加入多初解、2-opt 与单点搬移；Q3 另用负观测的保守凸外包、原地预检测及认证清除点接近减少移动。冻结后，在每间 1000 个新合成世界上，相对原 `refined` 的单源耗时由 258.99、542.41 秒降至 250.17、508.60 秒，降低 3.40% 和 6.23%，两题均全清。新确认、压力和误差替代试验共 9400 次，全部逐动作复算计时；聚集源部分组的区间仍含零，不主张普遍占优。这些提升是本地配对证据，不冒充新策略的官方成绩。补充的非配对官方模拟器演练显示 Q3 的 `field` 为 263.550883 秒/源而原 `refined` 为 237.998263 秒/源，Q4 的 `field` 为 484.966300 秒/源而原 `refined` 为 531.177617 秒/源；由于案例不同且新日志未归档，本文不作因果推断。综合这一诊断与本地配对证据，程序默认在 Q3 使用 `refined`、在 Q4 使用 `field`，并允许显式覆盖。

关键词：有界误差；交会定位；最小包围圆；覆盖证书；主动测向；定向源搜索

1 问题理解、目标与证据边界

1.1 四问之间的依赖关系

题目给定半径 1800 米的目标圆域，最多 20 个频道、每频道至多一个静止干扰源；在问题三、四中目标总数为 10 至 16 但不向程序公开。每次检测只报告无信号、近源或带误差的示向度，没有场强数值、距离或源数接口 [1]。因此不能从信号强弱反推距离，不能把 20 个频道同时检测，也不能把“已发现列表清空”当成全清。

问题一回答怎样描述和计算定位不确定性；问题二回答下一次测向应走向何处；问题三在全向条件下把发现、定位、清除和调度结合；问题四进一步解决从发射背面完全看不到信号的困难。本文不采用需要训练真值标签的端到端学习，也不对未知目标先验进行未经说明的概率化。主模型只用题目给定的确定界，概率分布仅用于可复现的合成实验。

1.2 优化目标和两种时间

设总行程为 L ，检测次数为 M ，实际切换频道次数为 S ，失败清除次数为 F ，成功清除数为 K 。 N 表示该世界中隐藏的真实源总数，只在退出后的评价器中使用； K 表示已收到成功清除响应的频道数。由附件计时规则，虚拟任务时间为

$$T = \frac{L}{5} + 5M + S + 3F + 5K. \quad (1)$$

式中距离单位为米、时间单位为秒；成功清除已含 3 秒光学精确定位与 2 秒激光清除，不能另加一次 3 秒。/clear 中的频道只指定目标，不改变测向机频道。

优化是字典序的：先在模型与资源条件下保证全清，再减小 T 。题目评价量为清除率 K/N 和平均定位清除时间 T/K ($K > 0$)；所有列示合成运行满足 $K = N$ ，因此本文逐世界计算 $T/N = T/K$ 后再平均，不用所有时间之和除以所有源数之和。另记程序现实运行时间 T_{real} ；它不等于虚拟时间，也不包含为每次虚拟 5 秒检测实际休眠的要求。

由于目标状态未知且实际反馈尚未出现，不能预先给出一个对所有世界同时最短的固定路径。本文的覆盖和清除安全性有解析证明，调度效率则由同口径对照实验支持，不声称全局时间最优。

1.3 当前证据等级

原题与附件规定已知条件，覆盖命题给出解析保证；历史合成研究、用户提供的 20 轮官方演练及新策略本地配对分层报告。实测日志只包含执行过的观测，不提供新路线上的真实反馈，因此不能由事后清除点猜测官方反事实。当前尚缺问题 3、4 各三次正式结果、六份官方加密日志和参赛队人工核验，本稿不宣称已具备完整正式提交条件。

2 符号、假设和统一信息状态

表 1: 主要符号及来源

符号	含义	来源或单位
$\mathcal{D}$	$\{g : \ g\ \leq 1800\}$, 源所在区域	题目, 米
c, g_c	频道编号、该频道源坐标	$c \in \{1, \dots, 20\}$
R_c	源的有效接收半径	未知, $[1000, 1500]$ 米
n_c	定向源发射半平面的单位法向	未知, 固定
s_i, θ_i	第 i 次检测点及示向度	可观察量
α	示向度容差	理论 1° , 实现 1.005°
$\mathcal{P}_c$	包含真实源的保守位置多边形	在线维护
$D(\mathcal{P}), r_*(\mathcal{P})$	直径、最小包围圆半径	米
ρ_{opt}	规划使用的光学覆盖半径	19.9 米
$V_c \subseteq V$	已完成的骨架索引与完整骨架索引集	每频道单独记录

除题目条件外, 仅作以下实现约定:

1. 示向度接口保留两位小数。为兼容先加入 $\pm 1^\circ$ 误差再舍入的过程, 计算使用 1.005° 容差; 这是额外的保守余量, 不改变题面误差定义。
2. 以外切正 180 边形近似目标圆盘, 绝不使用内接近似删除边界可能源。该外切多边形的径向过估计为 $1800(\sec(\pi/180) - 1)$, 小于 0.275 米。
3. 为控制数值误差, 一次保证清除的计算半径设为 19.9 米, 小于设备允许的 20 米。几何半平面向外添加极小浮点余量, 约束矛盾时报告错误而不擅自丢弃旧观测。
4. 源静止、频道唯一、方向固定和未清除前持续发射均来自题意。不同地点误差的具体分布及独立性没有给定; 重复原地测向不得被当作独立样本平均降噪。

定向源的可检测条件写作

$$\|s - g_c\| \leq R_c, \quad n_c^\top (s - g_c) \geq 0. \quad (2)$$

全向源没有第二个条件。距离不超过 5 米且可检测时返回 `near`, 此时原地清除必定成功。光学清除只要求 $\|s - g_c\| \leq 20$, 与式(2)的方向条件无关。

完整隐藏状态可以表示为各频道的存在性、位置、类型、接收半径和方向。程序不读取这个隐藏状态, 而只维护位置多边形、正测向记录、失败清除记录、清除成功集合及逐频道骨架检测记录。这种保守的信息压缩可能放弃部分负观测信息, 但不会因此误删真实源。

3 问题一：交会区域直径与清除判据

3.1 从示向度到正向半平面交

定义 $u(\theta) = (\cos \theta, \sin \theta)$, $u_i^\pm = u(\theta_i \pm \alpha)$, 二维叉积为 $\text{cross}(a, b) = a_x b_y - a_y b_x$ 。一次观测对应

$$W_i = \left\{ g : \begin{array}{l} \text{cross}(u_i^-, g - s_i) \geq 0, \\ \text{cross}(u_i^+, g - s_i) \leq 0, \\ u(\theta_i)^\top (g - s_i) \geq 0 \end{array} \right\}. \quad (3)$$

前两个半平面在 $\alpha > 0$ 时已经给出正向楔形, 第三个条件显式排除精确零误差情形下的背向射线。使用正弦、余弦表达使 359.9° 和 0.1° 之间的跨零问题无需分支处理。

原始交会区域为 $P = \bigcap_i W_i$ 。若题意需要同时利用已知目标区域或距离上限, 可再取交集; 但添加先验后的区域不是原始无限楔形交, 不能混淆二者的直径。

3.2 空集、无界集和有界多边形的算法

将全部约束写成 $Ag \leq b$ 。一个透明、易核查的实现如下。

1. 解二维可行性线性规划。无可行解时报告观测或条件矛盾, 不返回虚假的零直径。
2. 分别最大化及最小化 x, y 。任一坐标目标无界, 则非空区域无界, 直径为 $+\infty$; 四个坐标上下界都有限则区域有界。
3. 对每对非平行边界直线求交, 保留满足全部半平面约束的交点; 去除数值重复点, 按凸边界排序。
4. 求所有顶点对距离的最大值。单点直径为 0, 线段直径为两端点距离。

配套 `intersection.py` 直接完成上述分类, 不用任意大包围盒冒充原区域的有界性。若约束数为 m , 直线交点枚举并逐个检验的朴素复杂度为 $O(m^3)$; 通常只需少数测向, 足够迅速。大规模情形可改为按极角排序的半平面交和旋转卡壳, 几何阶段降至 $O(m \log m)$, 但这不是本题在线计算的瓶颈。

结论 1 (直径的顶点刻画). 若 $P = \text{conv}\{v_1, \dots, v_n\}$ 非空、有界, 则

$$D(P) = \max_{i,j} \|v_i - v_j\|. \quad (4)$$

证明. 任取 $p = \sum_i a_i v_i$ 与 $q = \sum_j b_j v_j$, 其中权重非负且各自和为 1, 有

$$\|p - q\| = \left\| \sum_{i,j} a_i b_j (v_i - v_j) \right\| \leq \sum_{i,j} a_i b_j \|v_i - v_j\| \leq \max_{i,j} \|v_i - v_j\|.$$

反向不等式由各顶点本身属于 P 得到。□

3.3 直径圆不能总是覆盖：一个真实可实现的反例

边长为 D 的等边三角形直径就是 D , 最小包围圆半径却是 $D/\sqrt{3} > D/2$ 。这不仅是任意多边形反例, 还能由本题 $\pm 1^\circ$ 测向直接生成。

取 $D = 36$, $A = (0, 0)$ 、 $B = (36, 0)$ 、 $C = (18, 18\sqrt{3})$ 。依次对三条逆时针有向边取单位方向 e_j , 令

$$S_j = V_j - L e_j, \quad L = 18\sqrt{3} \cot 2^\circ - 18. \quad (5)$$

测向读数取边方向加 1° , 即 $1^\circ, 121^\circ, 241^\circ$ 。每个楔形下边界沿对应边、上边界经过对角顶点；三个楔形都包含该三角形, 而三条下边界的内半平面交恰为该三角形。所有三角形点距对应检测站小于 1000 米, 故可取合法接收半径 1000 米。

实际计算得到直径约 36.000000 米, 最小包围圆半径约 20.784610 米。于是即使 $D < 40$, 仍不一定能在某一点以 20 米光学半径保证一次清除。




图 1: 直径为 36 米的可实现三角形反例。任何半径 18 米的圆都无法覆盖三顶点；正确包围半径约 20.785 米。

3.4 用最小包围圆直接连接定位与清除

定义

$$r_*(P) = \min_z \max_{p \in P} \|p - z\|, \quad z_*(P) = \arg \min_z \max_{p \in P} \|p - z\|. \quad (6)$$

圆盘是凸集, 包含多边形所有顶点即包含整个多边形。最小包围圆由一个、两个或三个边界支持点确定, 可用随机增量支持点算法求解 [2]。本文实现对近共线三点重算高精度行列式, 并在最终半径上保留向外余量。

平面 Jung 界为

$$\frac{D(P)}{2} \leq r_*(P) \leq \frac{D(P)}{\sqrt{3}}. \quad (7)$$

两点支持时左端取等；三点支持时圆心在支持三角形内, 三段圆心角中最大的一段至少 120° , 对应弦长至少 $\sqrt{3}r_*$, 得到右端。等边三角形取右端等号。因此：

- $r_*(P) \leq 20$ 是存在一次保证清除点的充要几何条件；执行点取 $z_*(P)$ 。
- 仅使用直径时， $D(P) \leq 20\sqrt{3}$ 是充分条件， $D(P) > 40$ 则必不可能一次保证覆盖。
- $20\sqrt{3} < D(P) \leq 40$ 时必须进一步算包围圆，不能凭直径直接清除。

3.5 在线使用的保守多边形

在问题三、四中，每次有效示向度还说明 $\|g - s_i\| \leq 1500$ 。为保持纯线性裁剪，可使用安全松弛

$$u(\theta_i)^\top (g - s_i) \leq 1500. \quad (8)$$

这不是把接收半径错误设为 1500，而是利用其已知上界。若初始外切多边形为 A_{180} ，则维护

$$\mathcal{P}_c = A_{180} \cap \bigcap_{i \in I_c} (W_i \cap \{g : u(\theta_i)^\top (g - s_i) \leq 1500\}). \quad (9)$$

真实源初始在 A_{180} 内，每条新增约束也包含它，故归纳得到 $g_c \in \mathcal{P}_c$ 。一次观测裁剪四个半平面， m 次观测最多形成 $180 + 4m$ 条边，复杂度 $O(180m + m^2)$ 。空交集是需要定位原因的异常，而不是允许重置状态的信号。

4 问题二：第二检测点的安全候选区域与选点策略

4.1 单次测向为什么没有唯一最优第二点

只有角度而没有距离时，目标位于长而窄的扇形中。若第二点沿首次示向方向移动，两条示向线可能几乎平行或反平行，径向误差难以压缩。若仅为了接近 90° 交会而绕行很远，则会增加移动时间，未必有利于题目总目标。

令 $r_i = \|g - s_i\|$ 、 $u_i = (g - s_i)/r_i$ 、 $n_i = (-u_{iy}, u_{ix})$ 。对小误差线性化，有

$$|n_i^\top \delta g| \leq \alpha r_i. \quad (10)$$

两条误差带交形成的平行四边形面积近似为

$$A \approx \frac{4\alpha^2 r_1 r_2}{|\sin \beta|}, \quad (11)$$

其中 β 为两条真实视线夹角， α 以弧度计。固定距离时， 90° 交会最有利；距离也变化时，应同时考虑缩短 r_2 、避免共线及移动代价。该式是局部解释，不能代替精确楔形裁剪。

若额外采用独立高斯角误差的辅助似然，才可写出 Fisher 信息 $J = \sigma^{-2} \sum_i n_i n_i^\top / r_i^2$ 及 $\det J = \sin^2 \beta / (\sigma^4 r_1^2 r_2^2)$ 。没有这种似然假设时，这至多是加权最小二乘的局部信息代理，不能当成题目提供的真实误差统计模型。最终安全性仍由式(9)保证。

4.2 利用首次已接收事实推导三圆交

取第一次检测点 S_1 为局部原点，首次读数方向为 u ，法向为 n ，第二点写为

$$S_2 = S_1 + tu + bn. \quad (12)$$

若可能真实距离为 r ，首次已经接收说明

$$R \geq \max(1000, r), \quad (13)$$

而不仅仅是 $R \geq 1000$ 。设 F_1 为当前全部可能源位置，则保证全向源在第二点仍有信号或返回近源的精确鲁棒条件为

$$S_2 \in \bigcap_{g \in F_1} B(g, \max(1000, \|g - S_1\|)). \quad (14)$$

用完整扇形 $r \in [0, 1500]$ 、角差 $\varphi \in [-\alpha, \alpha]$ 覆盖真实 F_1 ，可得闭式充分候选域。

结论 2 (三圆交接收保证). 令 $u_{\pm} = u(\theta_1 \pm \alpha)$ 。以下候选域内的任一点，对整个放宽扇形都能保证全向接收：

$$\mathcal{C} = S_1 + [B(0, 1000) \cap B(1000u_-, 1000) \cap B(1000u_+, 1000)]. \quad (15)$$

对这一完整扇形，式(15)也恰好是式(14)的交集；若再利用圆域等更强先验，它可能不是最大的安全候选域。

证明. 写 $q = S_2 - S_1$ 。必要性由 $r = 0$ 和 $r = 1000, \varphi = \pm\alpha$ 给出。反之，两端圆约束意味着 $q^T u_{\pm} \geq \|q\|^2 / 2000 \geq 0$ 。小于 180° 的中间短弧上， $q^T u_{\varphi}$ 的最小值在端点，因此对所有允许角度都满足同样下界。若 $r \leq 1000$ ，距离 $\|q - ru_{\varphi}\|$ 关于 r 是凸函数，两端 $r = 0, 1000$ 均不超过 1000，内部也不超过 1000；若 $r \geq 1000$ ，

$$\|q - ru_{\varphi}\|^2 - r^2 = \|q\|^2 - 2rq^T u_{\varphi} \leq 0.$$

故距离不超过 $\max(1000, r)$ ，由首次接收所隐含的半径下界即可保证可检测。 $\square$

4.3 显式候选区域与可执行搜索

在 (t, b) 局部坐标中，三圆交等价于

$$\begin{cases} t^2 + b^2 \leq 1000^2, \\ (t - 1000 \cos \alpha)^2 + (b - 1000 \sin \alpha)^2 \leq 1000^2, \\ (t - 1000 \cos \alpha)^2 + (b + 1000 \sin \alpha)^2 \leq 1000^2. \end{cases} \quad (16)$$

令

$$b_{\max}(t) = \min \left\{ \sqrt{1000^2 - t^2}, \sqrt{1000^2 - (t - 1000 \cos \alpha)^2} - 1000 \sin \alpha \right\}. \quad (17)$$

根号有定义且 $b_{\max} \geq 0$ 时， $0 < t < 1000$ 、 $0 < |b| \leq b_{\max}(t)$ 形成首次方位两侧的横向候选区。排除 $b = 0$ 用于避免把共线点作为唯一方案，而非禁止为了接近目标沿轴行进。

程序按下式构造 42 个候选：

$$\begin{aligned} t &\in \{125, 250, 375, 500, 625, 750, 875\} \text{ 米}, \\ b &= \pm \kappa b_{\max}(t), \quad \kappa \in \{1/4, 1/2, 3/4\}. \end{aligned} \quad (18)$$

对每个候选模拟允许的第二读数，计算新多边形最小包围圆；优先选择采样最坏半径较小的点，可再以本步移动和检测代价打破并列。所有这些点的接收安全性来自定理2，不是来自采样。




图 2: 第二点的三圆交候选区域。横向基线改善交会条件，但候选排序仍需兼顾移动耗时和未知径向距离。

在 $S_1 = (0, 0), \theta_1 = 0$ 的归一化示例中，取 60 个径向位置、3 个首次真实角差和 3 个第二次测向误差进行比较。程序得到采样最佳几何候选约为 (750, -496.078) 米，采样最坏包围半径约 65.426 米；共线对照 (750, 0) 的对应值约 375.231 米。两者本步耗时分别约 184.844 秒和 155 秒。这说明增加约 29.844 秒移动检测成本可显著改善此例的径向辨识，但第二次测向后仍未必能一次清除。

该示例是候选域与评分算法的演示，不是题目给定正式案例，也不是连续最坏情形或总时间的全局最优解。二维方位误差的连续极值、未知距离分布及后续代价若未严格处理，不能将网格最小值写成“最优定位策略”。

5 局部定位：快速测向与有限光学兜底

5.1 正常测向路径

基础 refined 及新 field 共用以下局部过程；field 在此之前至多补一次原地测量，并在已认证清除点上作安全接近，详见第10节。对已确认存在的频道，反复计算 (z_*, r_*) ：

1. 当前点到全部多边形顶点距离都不超过 19.9 米时，直接原地保证清除；否则若 $r_* \leq 19.9$ ，移动到 z_* 保证清除。

2. 若 $r_* \leq 38$ 米，可先在 z_* 进行一次光学尝试。失败仅花 3 秒且记录为失败，不将其写成保证成功；随后使用全区域覆盖，避免为一个很小区域继续绕远测向。
3. 设最近一次正测向点为 s^+ ，从 s^+ 指向 z_* 的单位方向为 u 、法向为 n ，候选测点取 $z_* \pm \delta n$ ，其中 $\delta = \min(120, \max(25, 0.22r_*))$ 米。优先较近且未重复正读数的位置。
4. 对实际返回的正示向度继续裁剪；`near` 立即原地清除。每次局部定位最多使用 6 个新测向点，随后转入光学覆盖。

这里的 25、120、38、0.22 和 6 是公开的工程策略参数，而非从题面推导的自然常数。它们影响效率，不影响后备覆盖的正确性。问题二给出的是保证全向接收的完整候选域；本节采用更直接的中心横向点以降低重复评分开销，**没有声称每个在线测点都属于三圆交或总能保持信号**，而是对失去信号设置了可靠处理。

5.2 定向源丢信号后的有限恢复

问题四中，新的点可能越过发射半平面的边界。设失败点相对最近正测向点的分解为 $q^- - s^+ = au + bn$ ，下一点建议取

$$q^{\text{next}} = s^+ + \frac{1}{2}(au - bn). \quad (19)$$

其含义是向已知能接收的位置退回，同时尝试另一侧。新正测向可收缩位置多边形并更新 s^+ ；持续无信号则继续有限恢复，直到达到 6 次测向上限。

式(19)只是利用正负观测进行选点的启发式，不据此删除任何可能源位置，也不假称一定重获信号。它的价值通过最低接收半径、朝外边界源和聚集源的消融实验评价；最终清除保证不依赖恢复成功。

5.3 覆盖整个可行多边形，而非只覆盖顶点

若无法继续有效测向，取多边形的一条直径方向为局部 x 轴，将 P 包含在投影矩形中。把矩形划分为边长分别不超过 $\sqrt{2}\rho_{\text{opt}}$ 的网格单元，在每个单元中心放置半径 $\rho_{\text{opt}} = 19.9$ 米的光学清除圆盘。每个单元半对角线不超过 ρ_{opt} ，故

$$P \subseteq \bigcup_{j=1}^J B(q_j, \rho_{\text{opt}}). \quad (20)$$

注意多个圆盘的并集一般不凸，覆盖所有顶点并不能推出覆盖内部；本文覆盖的是整个外包矩形，因此不存在内部孔洞。

按蛇形访问这些中心，可把起点循环移动到距离当前位置最近的中心；这样最多增加一次跨行程的长跳。每个失败清除只排除该清除圆盘里的目标可能性，不把剩余非凸集合强行当成一个更小的凸多边形。实际源始终在 P 内，故尝试完全部中心之前必有一次成功，随后立即停止该频道的搜索。

6 问题三：全向七点覆盖与环半径收缩

6.1 从 900 米覆盖基线到可调七点构型

记源区域为 $\mathcal{D} = \{g : \|g\| \leq R\}$ ，其中 $R = 1800$ 米，接收半径的题给下界为 1000 米。全向发现只需保证每个可能源位置至少落入一个检测点的接收圆盘；但覆盖半径越小，并不意味着式(1)中的总时间越少。为分离覆盖安全性与行程代价，考虑原点加正六边形环的同一构型族：

$$p_0 = (0, 0), \quad p_{k+1} = d u(k\pi/3), \quad k = 0, \dots, 5, \quad u(\theta) = (\cos \theta, \sin \theta). \quad (21)$$

原始保守基线取 $d = 900\sqrt{3}$ ，最终策略取 $d = 1200$ 。两者均保留七个检测位置，变化的是完整覆盖所需的圆盘半径，而不是逐频道排查的逻辑。

结论 3 (七点构型的精确覆盖半径). 对 $1200 \leq d \leq 900\sqrt{3}$ ，式(21)在 $\mathcal{D}$ 上的精确覆盖半径为

$$\rho(d) = \max_{g \in \mathcal{D}} \min_{0 \leq j \leq 6} \|g - p_j\| = \max \left\{ \frac{d}{\sqrt{3}}, \sqrt{R^2 + d^2 - \sqrt{3}Rd} \right\}. \quad (22)$$

特别地， $\rho(900\sqrt{3}) = 900$ ，故原 900 米圆盘覆盖基线成立。

证明. 将源写为 $g = r u(\theta)$ 。总有一个环点与之极角相差不超过 $\pi/6$ ；固定 r 时，相邻环点的角平分线给出到最近环点的最坏距离。因此该圆周上到最近检测点的最大距离恰为

$$f_d(r) = \min \left\{ r, \sqrt{r^2 + d^2 - \sqrt{3}dr} \right\}. \quad (23)$$

两项在 $r = d/\sqrt{3}$ 相等，此前原点更近，此后环点更近。在 $[d/\sqrt{3}, R]$ 上，后一项的平方是凸二次函数，其最大值位于两个端点；在 $[0, d/\sqrt{3}]$ 上， $f_d(r) = r$ 。于是全域最大值为式(22)。两端值均在角平分线上实际达到，故该式不是仅有充分性的上界，也不依赖空间网格采样。代入 $d = 900\sqrt{3}$ 后两项均为 900 米，证明包含圆周边界和扇区接缝。□

由式(22)，给定安全覆盖半径 $q \geq R/2$ 时，需要同时满足

$$d \leq \sqrt{3}q, \quad \frac{\sqrt{3}R - \sqrt{4q^2 - R^2}}{2} \leq d \leq \frac{\sqrt{3}R + \sqrt{4q^2 - R^2}}{2}. \quad (24)$$

当 $q = 900$ 时，这些条件将环半径固定为 $900\sqrt{3}$ ；允许覆盖半径向物理下界 1000 米靠近，则可以向内收缩检测环。最终采用 $d = 1200$ 米，解析式给出

$$\begin{aligned} \rho(1200) &= \sqrt{1800^2 + 1200^2 - \sqrt{3} \cdot 1800 \cdot 1200} \approx 968.901572 \text{ m}, \\ 1000 - \rho(1200) &\approx 31.098428 \text{ m}. \end{aligned} \quad (25)$$

因而收缩后仍保留约 31.098 米距离余量。若理想检测点到实际检测位置的总欧氏偏差不超过 η ，三角不等式给出实际覆盖半径至多为 $\rho(1200) + \eta$ ；例如 $\eta \leq 1$ 米时仍严格小于 1000 米。这里的余量属于全局发现骨架，与示向度误差和局部清除半径是不同的量。

6.2 骨架路径代价与七点下界的适用范围

从原点出发、访问全部六个环点而不要求返回时，纯骨架路径的精确最短长度为

$$L_{\text{ring}}^{\min}(d) = 6d. \quad (26)$$

起点到首个环点必须走 d ；任意两个不同环点的距离至少为相邻点弦长 d ，故其后五次转移各至少走 d 。沿圆周依次访问即可达到该下界。插入额外中间停靠点不能突破这一界，因为折线路径不短于对应直线。因此，环收缩使完整纯骨架路线由 $5400\sqrt{3}$ 米变为 7200 米。在所用参数区间内， $\rho(d)$ 由边界项控制，且

$$\rho'(d) = \frac{d - \sqrt{3}R/2}{\sqrt{R^2 + d^2 - \sqrt{3}Rd}} \leq 0, \quad \frac{dL_{\text{ring}}^{\min}}{dd} = 6.$$

这说明扩大环半径能改善最坏覆盖距离，却增加骨架行程；收缩则作相反交换。式(26)不包含定位支线、检测与切换费用，也不适用于达到 16 源上界后省略余点的路线，故其差额不能直接充当每局实际节省时间。

结论 4 (900 米覆盖要求下至少需要七点). 用半径 900 米的闭圆盘覆盖半径 1800 米的整个圆域，至少需要七个圆盘；式(21)在 $d = 900\sqrt{3}$ 时达到此下界。

证明. 设一个检测圆盘的圆心距原点为 $t > 0$ ，与源圆周的交弧角半宽为 β 。有交弧时余弦定理给出

$$\cos \beta = \frac{R^2 + t^2 - q^2}{2Rt} = \frac{1}{2R} \left(t + \frac{R^2 - q^2}{t} \right) \geq \frac{\sqrt{R^2 - q^2}}{R}, \quad q = 900.$$

所以 $\beta \leq \arcsin(q/R) = \pi/6$ ，等号仅在 $t = \sqrt{R^2 - q^2} = 900\sqrt{3}$ 时成立。圆心为原点的 900 米圆盘不与源圆周相交。六个圆盘若覆盖整条圆周，六条交弧都必须达到最大角宽 $\pi/3$ ，且不能有正长度重叠。于是六个圆心均在半径 $900\sqrt{3}$ 的环上，按 $\pi/3$ 间隔排列；然而它们距原点均大于 900 米，不能覆盖原点。六个及更少圆盘均不可能覆盖全域，结合前述七点构造即得结论。 $\square$

这一精确下界只针对 900 米覆盖要求。将允许半径改为 1000 米后，最大交弧变宽，上述等号论证不再成立；因此本文没有证明物理接收半径下任意布局仍至少需要七点，也不把 $d = 1200$ 称为连续参数空间的全局最优值。最终采用的七点环是在完整发现保证下减少骨架移动的明确构造，其任务时间表现另由冻结策略的实验评价。

7 问题四：具有严格方向余量的 25 点双环覆盖

7.1 由近邻覆盖转向方向覆盖

定向源不仅要求检测点距源不超过接收半径，还要求检测点位于发射前方。设源的单位发射法向为 n ，前方闭半平面为 $n^T(p - g) \geq 0$ 。边界源若朝圆外发射，圆内近邻点可能全部位于背面，因此问题三的距离覆盖不能直接用于问题四。题目允许提交源圆域外的机器人位置，本文利用这一条件重新设计骨架，而不把外部检测点投影回圆内。

历史 enhanced 对照保留边长 990 米的 31 点三角格，配合原有滚动骨架排序、分离式调度和全部未清除频道扫描。该格点集合的逐点不可删性，说明从固定的 31 点集合直接删除一个点可能失去覆盖见证；它并不意味着任意布局都至少需要 31 点。最终 refined 采用下面独立证明的 25 点双环，其改进来自重新布点而不是未经证明的删点。

取 $a = 940$ 米、 $b = 1870$ 米，定义原点、内环和外环为

$$\begin{aligned} p_0 &= O = (0, 0), \\ p_{1+k} &= I_k = a u(k\pi/6), \\ p_{13+k} &= E_k = b u(k\pi/6 + \pi/12), \quad k = 0, \dots, 11. \end{aligned} \quad (27)$$

内环角间隔为 30° ，外环相对内环错开 15° 。共有 13 个点在源圆域内，12 个点在圆域外。索引只标识覆盖义务，不规定访问顺序。

7.2 36 个闭三角形组成的有限覆盖证书

令所有下标按模 12 计算，构造三类闭三角形

$$\begin{aligned} T_k^{(1)} &= \text{conv}\{O, I_k, I_{k+1}\}, \\ T_k^{(2)} &= \text{conv}\{I_k, E_k, I_{k+1}\}, \\ T_k^{(3)} &= \text{conv}\{I_{k+1}, E_k, E_{k+1}\}. \end{aligned} \quad (28)$$

这 36 个三角形完整剖分外正十二边形 $H = \text{conv}\{E_0, \dots, E_{11}\}$ 。具体而言，第一类剖分内正十二边形；内外连接线分别位于端点极角确定的 15° 扇区，不同扇区内部互不相交。外端点位于相应内边支撑线之外，而 $a < b \cos(\pi/12)$ 保证内点严格位于相应外边内侧。因此后两类恰好填满内外多边形之间的环带，不产生交叉边或孔洞。所有三角形按式中顺序逆时针定向，内部边成对反向出现，余下边界正是外十二边形；25 个顶点、60 条无向边与 36 个面还满足 $25 - 60 + 36 = 1$ 。边计数是有限结构的核对，而完整性依赖上述无交叉剖分。

记 $c = \cos(\pi/12)$ 、 $s = \sin(\pi/12)$ 。剖分中只有四种边长：

$$\begin{aligned} \ell_0 &= a, \quad \ell_I = 2as, \\ \ell_E &= 2bs, \quad \ell_{IE} = \sqrt{a^2 + b^2 - 2abc}. \end{aligned} \quad (29)$$

任一三角形的直径等于其最长边，故只需给出这四种边长的共同上界。利用精确根式

$$c = \frac{\sqrt{6} + \sqrt{2}}{4}, \quad s = \frac{\sqrt{6} - \sqrt{2}}{4},$$

以及可由平方比较得到的 $1.4142 < \sqrt{2} < 1.4143$ 、 $2.4494 < \sqrt{6} < 2.4495$ ，可得有理界

$$c > \frac{9659}{10000}, \quad \frac{1}{4} < s < \frac{259}{1000}. \quad (30)$$

以下比较均使用有限有理数，不依赖浮点近似决定不等号方向：

$$\begin{aligned}
bc &> 1870 \cdot \frac{9659}{10000} = 1806.233 > 1805, \\
\ell_0 &= 940 < 993, \quad \ell_I < 486.92 < 993, \\
\ell_E &< 968.66 < 993, \\
\ell_{IE}^2 &< 940^2 + 1870^2 - 2 \cdot 940 \cdot 1870 \cdot \frac{9659}{10000} \\
&= 984781.96 < 993^2 = 986049.
\end{aligned} \tag{31}$$

因此每个闭三角形的直径 $D_T < 993$ 米，而外十二边形的内切圆半径 $bc > 1805$ 米，特别有 $B(O, 1805) \subset H$ 。这两个严格界分别控制接收距离与源边界之外的辅助空间。

结论 5 (25 点的任意方向鲁棒覆盖). 对任意 $g \in \mathcal{D}$ 、任意单位发射法向 n ，式(27)中至少有一个点 v ，使得其实际检测位置 v' 在满足 $\|v' - v\| \leq 1$ 米时仍有

$$n^\top(v' - g) \geq 4 \text{ m}, \quad \|v' - g\| < 999 \text{ m}. \tag{32}$$

故该点严格位于发射前方，且严格处于题给最小接收半径 1000 米以内。

证明. 取仅用于证明的辅助点 $h = g + 5n$ 。由 $\|h\| \leq 1805$ 及式(31)，有 $h \in H$ ，故 h 属于剖分中的某个闭三角形 T 。写成重心组合

$$h = \sum_{i=1}^3 \lambda_i v_i, \quad \lambda_i \geq 0, \quad \sum_{i=1}^3 \lambda_i = 1.$$

投影满足

$$\sum_{i=1}^3 \lambda_i n^\top(v_i - g) = n^\top(h - g) = 5. \tag{33}$$

所以至少一个正权重顶点 v 满足 $n^\top(v - g) \geq 5$ 。又因 $v, h \in T$,

$$\|v - g\| \leq \|v - h\| + \|h - g\| \leq D_T + 5 < 998.$$

加入不超过 1 米的总位置偏差后，由柯西不等式与三角不等式得

$$n^\top(v' - g) \geq 5 - \|v' - v\| \geq 4, \quad \|v' - g\| \leq \|v - g\| + \|v' - v\| < 999.$$

这就证明了式(32)。 □

上述证明不要求源 g 与辅助点 h 位于同一个三角形，也不需要在线知道 g 或 n 。源在圆周上并朝外发射、源在圆心或内环点、辅助点恰落在三角形边或顶点等情况均包含在闭三角形论证中。正投影下界还排除了所选点与源重合的退化情形，不需依赖零距离方位定义或恰好落在发射边界上的浮点判断。1 米是理想点到实际测量位置的总欧氏误差预算，包括坐标计算、传输舍入和实际位置偏差之和；不能对每一种误差分别重复使用 1 米。仅将两个坐标四舍五入到整米所造成的误差至多 $\sqrt{1/2}$ 米，但仍须计入其余误差。




图 3: 问题四发现骨架的同尺度比较: 左为历史 31 点三角格, 右为最终 25 点错相双环及 36 个闭三角形。源区域均为半径 1800 米圆盘; 右图外十二边形包含辅助半径 1805 米圆盘, 圆外点是方向覆盖义务的一部分。

7.3 可实现路线、有限核验与点数结论

双环给出一条显式开放扫描路线

$$O, I_0, I_1, \dots, I_{11}, E_{11}, E_{10}, \dots, E_0,$$

其长度为

$$L_{25} = a + 22(a + b) \sin(\pi/12) + \sqrt{a^2 + b^2 - 2ab \cos(\pi/12)}. \quad (34)$$

它恰访问每个点一次, 不要求回到原点。保存的独立研究核验给出最大边长约 992.316061 米、该显式路线长度约 17932.509429 米, 并核对了 36 个三角形、60 条边及无交叉完整剖分。这些数值与实现检查补充解析证书, 不替代定理中的全称证明; 式(34)也只是一条可行路线, 不是旅行商最优值或联合调度的实际路径预测。

在 20 个频道都需完成全骨架扫描的义务计数下, 31 点对应 $31 \times 20 = 620$ 次检测, 25 点对应 500 次, 少 120 次检测, 即式(1)的检测项少 600 秒。实际任务会提前清除频道并跳过部分已知源补测, 还可能增加定位分支; 因此 600 秒不是每局固定节省, 路线和切换收益也须独立核算。另一方面, 本文没有证明 25 点是任意非规则布局、任意层数或任意方向覆盖方法中的全局最少点数。可成立的结论是: 31 点固定格不可删与 25 点重新设计可覆盖并不矛盾, 后者提供了点数更少且留有明确扰动余量的完整发现骨架。

8 联合调度、扫描筛选与逐频道停止证书

8.1 在共同任务路线中选择下一项

分开评价一个待扫描骨架点或一个已知源，会忽略执行当前任务后与其他任务的位置关系。最终策略将二者放入同一个开放路线：令当前位置为 q ，每个未完成骨架任务的代理点为其检测坐标、半径为 0；每个已发现未清除频道 c 的代理点为保守区域 P_c 的最小包围圆中心 z_c ，半径为 r_c 。对全部 n 个任务的排列 π 定义

$$J_\gamma(\pi) = \|q - z_{\pi_1}\| + \sum_{j=1}^{n-1} \|z_{\pi_{j+1}} - z_{\pi_j}\| + \gamma r_{\pi_1}. \quad (35)$$

问题三取 $\gamma = 0$ ，对应 **center**；问题四取 $\gamma = 1$ ，对应 **guarded**。后者只在首项为目标时增加其半径，抑制立即向一个不确定中心作长距离承诺；半径不是障碍半径，也不是未来真实任务时间的误差界。该代理不含未知的后续示向、光学尝试和频道切换，最终优劣仍以式(1)评价。

实现先用最近插入法构造完整排列：首项最小化当前位置距离加首项惩罚，此后选离已有路线最近的未插入任务，将其放入代理增量最小的空隙。再进行至多 n 轮 2-opt 扫描，每轮按固定次序检查连续区间反转，只接受严格改善的首个交换；没有改善即停止。开放路线不增加返回起点的虚拟边，反转从首项开始时还须计入半径惩罚的变化。距离矩阵占 $O(n^2)$ 空间，最近插入耗时 $O(n^2)$ ，每轮 2-opt 检查 $O(n^2)$ 个区间，总时间上界 $O(n^3)$ 。轮数上限保证计算量可控，但不保证到达局部或全局最优。

每次只执行排列首项，依据已接受动作确定的新位置与新观测重建任务集。选中目标仍调用既有局部定位与完整光学后备，不在代理中心直接假定清除成功。任务按类型和频道或骨架索引区分，即使坐标重合也不合并；插入和反转都保持全部输入任务。因此联合调度改变访问顺序，不会删除无源认证所需的骨架义务。

8.2 区分首次发现义务与已知源的补测价值

骨架扫描先剔除已确认成功清除的频道，并优先检测当前测向机频道，再按频道编号排序，以避免一次不必要的初始切换。对其余频道采用以下准确规则：

- 问题三的 **unknown** 规则：尚未建立源轨迹的频道必须检测；已有正测向轨迹的未清除频道跳过骨架补测，保留为独立定位清除任务。
- 问题四的 **useful** 规则：未知频道仍必须检测；对已有轨迹的频道，在骨架点 p 仅当 $r_c > 19.9$ 且 $\|p - z_c\| - r_c \leq 1500$ 时补测。换言之， $r_c \leq 19.9$ 或 $\|p - z_c\| - r_c > 1500$ 才跳过；距离下界恰为 1500 时不跳过。

第二条中， $r_c \leq 19.9$ 表示已具备既有局部清除条件；由 $P_c \subseteq B(z_c, r_c)$ 可知， $\|p - z_c\| - r_c > 1500$ 时整个保守区域都超过最大电磁接收距离，补充示向没有价值。反向条件只表示可能有用，不保证定向源处于发射前方。局部任务完成后的停靠共享同样保留区域大小与 1500 米筛选，并额外跳过该频道曾在完全相同坐标检测过的位置；此去重条件不被误写为 **useful** 骨架扫描本身的条件。

两种规则都不跳过未知频道的必需检测。已知源从骨架扫描中省下的观测不算作无信号，也不填入已完成索引集合；其完成义务由“发现”转为“收到该频道成功清除

反馈”。尤其在问题四，`no_signal` 可以来自距离过远或位于发射背面，不能据此删除 1000 米位置圆盘，也不能将已知源改判为不存在。

8.3 安全停止不依赖启发式代理是否准确

记 V 为当前完整骨架索引集，问题三为 $\{0, \dots, 6\}$ ，最终问题四为 $\{0, \dots, 24\}$ ； V_c 只记录该频道已接受的实际骨架检测。定义频道完成证书

$$\text{Cert}_c = \begin{cases} C, & \text{已收到频道 } c \text{ 的 success 清除反馈,} \\ N, & \text{从未发现该频道源, 且全部 } V \text{ 上的有效检测均无信号,} \\ U \text{ 或 } D, & \text{尚未确定或已发现未清除.} \end{cases} \quad (36)$$

若一个从未发现的频道在 $V_c = V$ 后仍全部无信号，则假设其有源将与问题三或问题四的覆盖定理矛盾，故 N 证书可靠；一旦进入 D 状态，只能以成功清除完成，不能转成 N 。合法停止条件为

$$[\forall c \in \{1, \dots, 20\}, \text{Cert}_c \in \{C, N\}] \quad \text{或} \quad [\#\{c : \text{Cert}_c = C\} = 16]. \quad (37)$$

第二项利用题给总数上界，统计的是 16 个不同频道的成功清除；已清除 10 个、队列暂时为空或长时间没有新发现均不满足停止条件。动作异常或时间中断也不能替代证书。

式(9)的真实源包含关系仅依赖先验和实际返回的有效正观测，不依赖选点代理是否准确。联合调度不改写观测，扫描筛选不虚构负证据，定向失信号不作不安全的位置删减；因此这些效率层动作不会破坏既有几何包含不变量。配合保留的有限局部测向和完整光学覆盖，发现、清除与停止分别拥有可核查的依据，而效率由真实执行的 L, M, S, F, K 统一结算。

9 官方演练观察：结果与可识别的瓶颈

用户提供了 2026 年 9 月 12 日在官方模拟器完成的 Q3、Q4 各 10 轮演练：每局包含脱敏请求日志、控制器摘要及模拟器退出后结果文件，案例关联由 `manifest.csv` 固定。执行时采用原 `refined`，不是新增 `field`。事后公开的源数和类型仅用于评价，绝不传入在线规划器。`official_analysis.py` 逐请求与响应独立复算移动距离、检测、换频及清除费用，并按微秒累计与每步虚拟时刻核对；客户端派生的距离和换频字段只用于交叉检查。

表 2: 20 轮官方演练的汇总；每题 10 轮均全清，时间单位秒/源

问题	局数	全清源数	局等权 T/K	汇总 T/K	移动占比/%	检测/局
Q3	10	139	238.00	235.82	74.38	128.90
Q4	10	138	531.18	519.38	73.20	311.80

其中“局等权”为 $\frac{1}{10} \sum_j T_j / K_j$ ，“汇总”为 $\sum_j T_j / \sum_j K_j$ ，后者给予源数更多的局更高权重。问题三 139 个、问题四 138 个源均清除；局等权均值分别为 238.00、531.18

秒/源。问题四第 8 局只有 10 个源，仍需完成 25 点搜索，因此 $T/K = 768.87$ 秒/源，说明小源数案例的固定发现成本不能忽略。

表 3: 20 轮官方演练逐局结果； N 为退出后标签，不是正式测试分母

题号	轮次	案例编码	N	K	T/s	$T/K/(s/源)$
Q3	1	BUWJ-NM9Q-E3FP-KBNQ	16	16	3501.15	218.82
Q3	2	XSTE-PSFN-9F8U-8P2D	12	12	2929.34	244.11
Q3	3	WQXS-VYHK-4B2N-4NWU	13	13	3230.83	248.53
Q3	4	3YB4-CC66-WNAD-XVQ9	15	15	3301.25	220.08
Q3	5	AKGC-XRSQ-KQ42-DE4U	14	14	2867.24	204.80
Q3	6	F22D-5NT7-9XRW-7DY6	13	13	3119.85	239.99
Q3	7	FDS3-ZJ7Q-V3E9-2QDN	11	11	3334.99	303.18
Q3	8	XMZP-GEJC-W9KA-UTWY	14	14	3452.13	246.58
Q3	9	8V3W-N88T-ED46-PXCE	15	15	3294.33	219.62
Q3	10	HGVD-7ZTC-XNGP-2JRT	16	16	3748.24	234.26
Q4	1	ZGME-Z9ZY-UQDJ-UZRF	15	15	7091.90	472.79
Q4	2	AQVF-W7A2-YAFY-F6JT	16	16	7385.70	461.61
Q4	3	HS4Z-3F9D-BE4W-FUBW	13	13	7233.66	556.44
Q4	4	BFSU-HJRZ-2WQX-63MP	14	14	7461.23	532.95
Q4	5	RFFB-U23B-VMS7-ASRE	15	15	6420.23	428.02
Q4	6	AJFX-AY9F-VETM-UBJ8	15	15	7089.98	472.67
Q4	7	CR6D-5DV5-WCJQ-6N3F	16	16	7677.93	479.87
Q4	8	TY94-4B9M-J2RU-EDHA	10	10	7688.73	768.87
Q4	9	5J2D-BATC-W2P2-BNQ2	13	13	7151.24	550.10
Q4	10	CENN-WQ49-E4D5-9JJ7	11	11	6473.24	588.48

移动约占 Q3 的 74.38%、Q4 的 73.20%，失败光学清除仅占 0.11%、0.12%。因此优先改进移动与观测价值，而不是以减少失败尝试次数这一小分项代替总时间目标。20 轮未出现 near、HTTP 拒绝或传输重试；它们支持正常协议联通，不支持“官方已经验证故障恢复”的结论。Q3、Q4 在已发现频道后分别仍有 223 和 530 次无信号反馈，尤其不能对 Q4 据此删去 1000 米位置圆盘。

严格回放与反事实边界。 历史日志没有真实源位置、接收半径或发射方向；成功清除点距源至多 20 米，不能作为源坐标真值。严格回放只在新请求与记录路径、频道、坐标一致时返回原反馈，一旦分岔立即停止，不为未测位置猜反馈。原算法在本机可完整匹配 8/20 局，其余在任务顺序或对称测点选择处分岔；这与跨平台浮点近似及近等价几何决策相容，但仅凭日志不能唯一确定原因。20 局的实际费用仍全部由原始坐标和响应核验，不依赖策略回放成功。故以下新策略收益来自独立合成配对，不是这 20 局的官方反事实成绩；新 field 仍需另做官方演练。

10 由官方演练瓶颈驱动的安全效率层

官方 20 轮演练的已接受动作表明，历史 `refined` 的主要费用来自移动，而不是失败清除。这是按式(1)分解已执行动作得到的诊断，不是新路线的反事实成绩。为此，`field` 在不改变发现骨架和清除证书的前提下，改进任务排序、利用问题三的负观测，并减少可避免的局部接入移动。问题三仍用 1200 米七点环、`center/unknown`；问题四仍用 `compact25`、`guarded/useful`。两题固定横向探测比例均为 0.22；历史 `refined` 保持原算法，不能把其官方记录重新标成 `field` 记录。以下包含关系和有限性是解析结论；完整时间收益须由独立本地配对实验评价，尚不构成 `field` 通过官方测试的证据。

10.1 保留旧路线的多初解与单点搬移

每轮仍对全部待扫描骨架点和已知未清除源构造开放路线，目标沿用式(35)的 J_γ ，问题三、四分别取 $\gamma = 0, 1$ ，不添加返回原点的边。候选包括：原最近插入及其有界 2-opt 所得的完整控制路线；每步同时选择未插入任务与插入空隙的全局最便宜插入路线；按当前位置距离加首项半径惩罚排序，以前两个不同任务分别起步的近邻路线。重复排列只计算一次，但同坐标的不同任务绝不合并。

每个初解最多进行 $\min(n, 12)$ 轮最佳改善搜索，同时检查连续区间反转 (2-opt) 和把一个任务移入另一空隙 (Or-opt1)。涉及首项的操作同步更新起点边及半径惩罚。候选增量须超过与当前代理值尺度相关的 10^{-12} 数值门槛，接受前再完整重算 J_γ 并要求严格下降；无改善或完整复算不通过即停止。原控制路线始终保留，最后取代理值最小的完整排列，因此在同一任务集与同一代理计算下

$$J_\gamma(\pi_{\text{field}}) \leq J_\gamma(\pi_{\text{control}}). \quad (38)$$

该不等式不保证首跳更短、真实总行程更短或式(1)中的 T 更小：实际只执行首任务，随后的观测、清除终点和频道切换均会改变未来费用。有限轮数也不保证达到局部或全局最优。距离矩阵占 $O(n^2)$ 空间，有界多初解搜索的保守时间上界仍为 $O(n^3)$ 。

10.2 仅问题三使用负观测的保守凸外包

问题三所有源全向发射，故在位置 s 收到有效 `no_signal` 时，若该频道有未清除源 g ，必有 $\|g - s\| > r$ ，其中 $r = 1000$ 米。直接将圆盘差表示为单个凸多边形并不成立。为保留既有凸几何接口，构造严格位于该圆盘内部的正十六边形

$$Q = \text{conv} \left\{ s + r \cos \frac{\pi}{16} \begin{pmatrix} \cos(2j\pi/16) \\ \sin(2j\pi/16) \end{pmatrix} : j = 0, \dots, 15 \right\}. \quad (39)$$

这里顶点半径是 $r \cos(\pi/16)$ ，不是 r 。 Q 的内切半径为 $r \cos^2(\pi/16)$ ，因此相对于半径 r 的圆，其最大径向缺口为

$$\text{gap} = r(1 - \cos^2(\pi/16)). \quad (40)$$

这刻意保留一圈不删的余量；它不是最终可行域误差界，因为随后取凸包还可能填回被排除的区域。

令 H_j^{out} 为 Q 第 j 条边的闭外侧半平面，将当前保守域 P 分别向外侧裁剪，再取所有保留片的凸包：

$$P^+ = \text{conv} \left(\bigcup_{j=0}^{15} (P \cap H_j^{\text{out}}) \right), \quad g \in P \setminus B^\circ(s, r) \implies g \in P^+ \subseteq P. \quad (41)$$

证明只需注意 $Q \subset B^\circ(s, r)$ ，圆外真源必处于至少一条边的外侧，而 P 为凸集。式(9)提供正观测的初始包含不变量；交替施加正约束与式(41)即可归纳保留真源。实现缓存首次发现前的有效负观测，建轨及后续更新时再使用；半平面向保留侧外扩极小浮点余量，空结果报告观测不一致，不能重置域或虚构无源。上述证明针对精确几何及显式保守余量，并非全套浮点运算的形式化认证。

问题四绝不删盘。定向源可能因机器人处于发射背面而在 1000 米内无信号；该反馈不蕴含任何完整位置圆盘为空。问题四禁用上述更新，继续保留正观测约束和原有限恢复规则。

10.3 一次原地预检测与保证清除的安全接近

对即将定位的已知频道，设当前位置为 q 、当前最小包围圆为 $B(z_*, r_*)$ 。仅当 $r_* > 38$ 米、该频道未在完全相同坐标 q 检测过，且 $\|q - z_*\| - r_* \leq 1500$ 米时，先执行一次原地预检测 (premeasure)。最后一个条件只说明保守域可能与接收范围相交，不保证收到信号，尤其不能保证定向源可见。预检测不产生移动，但仍支付 5 秒检测及可能的换频费用；它不是免费信息，也不是重复独立采样降噪。实际 `near` 按原规则清除，正示向更新域，负反馈仅按本题许可解释，之后进入原局部过程。**这一次在原有至多 6 次固定测向之外**，不能写成六次预算内。两题均保留该条件分支，问题四是否触发取决于此前扫描和共享观测，不能因通常不触发而删去预算。

问题三还对已满足保证清除条件的计划点 a 缩短接入距离；问题四关闭此优化。取 $\rho = 19.9$ 米，先逐顶点确认 $\|a - v\| \leq \rho$ 。若 $q \neq a$ ，令 $u = (q - a)/\|q - a\|$ ，沿 $a + tu$ 靠近机器人，且 $0 \leq t \leq \|q - a\|$ 。记 $d_v = a - v$ ，每个顶点的安全圆盘条件等价于

$$t^2 + 2(d_v \cdot u)t + \|d_v\|^2 - \rho^2 \leq 0. \quad (42)$$

由于 $t = 0$ 已可行，沿此射线的共同可行上端为

$$t \leq \min_{v \in \text{vert}(P)} \left[-d_v \cdot u + \sqrt{(d_v \cdot u)^2 + \rho^2 - \|d_v\|^2} \right], \quad t \leq \|q - a\|. \quad (43)$$

实现从上端再退 10^{-6} 米且不取负位移，并对候选点 a' 重新检验全部顶点距离不超过 19.9 米。圆盘凸性保证覆盖全部顶点即覆盖 P ，故由 $g \in P$ 可知清除合法；相对设备 20 米半径另留 0.1 米余量。根号判别式若数值为负、出现非有限值或最终顶点复验不通过，就退回原计划清除点 a ，不把负数截成零来伪造证书。此处的“原点”是 $t = 0$ 的原计划点，不是全局坐标原点。几何保证仍须由接口实际返回 `success` 落实，不能提前记为清除成功。

10.4 有限性不依赖效率代理准确

所有路线操作都是完整任务排列，不删除任务；未知频道仍完成七点或 25 点的实际骨架观测。问题三沿用七点覆盖，问题四沿用定理5，故全骨架无信号仍能认证从未

发现的频道无源。已知频道的跳过检测不构成负证据，该频道只能收到 `success` 后完成，不能改判无源；合法停止仍为所有频道均有清除或无源证书，或 16 个不同频道成功清除。

在接口正常、误差模型成立且没有现实期限中断的条件下，每个局部任务最多一次预检测、六次固定测向，然后成功清除或进入有限矩形光学覆盖；真源保留于覆盖域，因而每个正常完成任务清除一个新源，任务数至多 16。路线重排不增加骨架点数，负观测凸外包只缩小域，安全接近只缩短当次已认证清除的接入段。故第10.5节的旧 31 点范数、行程和光学次数上界仍适用，仅总检测预算增加至多 16 次： $M \leq 1212 + 16 = 1228$ 。这是保守有限性界，不是紧界、最优性证明或官方完成保证；现实期限中断必须如实报告，不能以解析虚拟时间界替代。

10.5 默认配置的有限动作与虚拟时间上界

本节覆盖最终 `field`、官方演练所用原 `refined` 及历史 `enhanced` 策略：问题三均用原点及半径 1200 的六点环，问题四前两者用 25 点双环、后者用 990 米 31 点三角格。联合调度只重排任务，已知频道筛选不增加补测义务；均保留每局部任务至多 6 次固定测向和原矩形光学后备。`field` 每任务另允许至多一次原地预检测，问题三负观测的保守凸外包不扩大原域、保证清除的安全接近不增加当次接入距离。假定接口正常、误差模型成立且无现实时间中断。以下沿用较大的 31 点范数与次数界，仅为新预检测增加检测预算；不涵盖条带光学或自适应候选。此界不声称紧或最优，距离单位均为米。

可行域尺寸与 216 单元证书。 记真源为 g ，最近正示向点为 s ， $\alpha = 1.005^\circ$ 。示向轴坐标满足 $0 \leq x \leq 1500$ 、 $|y| \leq x \tan \alpha$ 。计入显式外扩，令 $\varepsilon = 10^{-7}$ ，取

$$X = 1500 + 2\varepsilon, \quad W = 2((1500 + \varepsilon) \tan \alpha + \varepsilon / \cos \alpha).$$

于是纵向长度至多 X ，横向宽度至多 $W < 53$ ， $\sqrt{X^2 + W^2} < 1501$ 。最小包围圆圆心 $z \in P$ ，故 $\text{diam}(P) < 1501$ 且 $\|z - s\| < 1501$ 。正测点范数至多 3300、初始外切多边形范数小于 1801，使相关 `_padding` 为 $10^{-9} < \varepsilon$ ；此为几何与显式外扩的解析界，不是全部浮点运算的形式化认证。

单点域直接用一圆覆盖。否则设直径端点差为 (a, b) 、 $d = \sqrt{a^2 + b^2} > 0$ 。任意点差满足 $|\Delta x| \leq d$ 、 $|\Delta y| \leq W$ 、 $|b| \leq W$ ，故直径法向投影差 $|-b\Delta x + a\Delta y|/d \leq 2W$ 。计入投影外扩，直径对齐矩形仍长小于 1501、宽小于 106，对角线小于 1505。令 $h_- = \sqrt{2}(19.9 - 8\varepsilon)$ ，不大于代码单元边长上限，则

$$J \leq \left\lceil \frac{1501}{h_-} \right\rceil \left\lceil \frac{106}{h_-} \right\rceil = 54 \times 4 = 216 \quad (44)$$

个半径 19.9 的圆盘覆盖整个矩形。蛇形相邻中心距至多 $\sqrt{2} 19.9$ ，循环移位至多增加一条矩形内跳跃，故

$$L_{\text{snake}} \leq (216 - 1)\sqrt{2} 19.9 + \sqrt{1501^2 + 106^2} < 7570. \quad (45)$$

每个覆盖中心 q_{opt} 与 g 均在同一矩形中，故 $\|q_{\text{opt}} - g\| < 1505$ 。

恢复点必须以最近正测点为中心估计。 固定候选 $q_0 = z \pm \delta n$ 满足 $n \perp (z-s)$ 、 $\delta \leq 120$ ，因此 $\|q_0 - s\| \leq A := \sqrt{1501^2 + 120^2} < 1506$ 。在获得新正示向前，所有恢复仍使用同一个 s 。设 R_k 为相应轴向反射，则

$$q_{k+1} - s = \frac{1}{2}R_k(q_k - s), \quad \|q_{k+1} - s\| = \frac{1}{2}\|q_k - s\|.$$

反射只保持到 s 的距离，不能把失败点的源距与 1500 取平均。故连续恢复有 $\|q_k - s\| \leq 2^{-k}A$ ；新正示向更新 s 后重用首点界。由 $\|s - g\| \leq 1500$ ，全部局部测向点满足

$$\|q - g\| \leq B := 1500 + A < 3006, \quad \|q\| \leq 1800 + B < 4806. \quad (46)$$

圆心源距小于 1501，覆盖中心源距小于 1505，两者范数亦小于 4806。测向间连线至多 $2B < 6020$ ；额外圆心清除接入至多 $B + 1501 < 4520$ ；光学接入至多 $B + 1505 < 4520$ ，若紧接圆心试清则至多 $1501 + 1505 < 4520$ 。

任务进出、动作计数与总界。 每任务至多 6 次固定测向，field 在进入该过程前另可执行一次原地预检测；各提前返回分支均成功清除或转入有限光学覆盖。真源在覆盖域内，故每个正常完成任务必清除一新源，任务数至多 16。成功终点距该源至多 20、范数至多 1820；原地预检测、共享补测及其 near 清除不移动。这处理了从另一源清除点进入下一任务的情形。

骨架点范数至多 $990\sqrt{7} < 2620$ 。集成策略整次骨架扫描不插入局部移动，故至多 31 次骨架抵达，出发于原点、骨架或成功清除点，每段小于 5240。任务首个需移动的动作由范数至多 2620 的任务外位置进入范数小于 4806 的局部点，入口小于 7500；原地预检测不改变入口位置。此后至多 5 条测向连线、一次额外圆心清除移动（保证清除或小区域试清）、一次光学接入及一条蛇形，故

$$L \leq 31 \times 5240 + 16(7500 + 5 \times 6020 + 4520 + 4520 + 7570). \quad (47)$$

若首动作即圆心清除或光学首点，入口已支付该段，多余预算仅为放宽。任务至下一骨架的退出段已计入 31 次骨架抵达；无需返回原锚点。

骨架至多 31×20 次测向；共享只在任务结束后调用，至多 16 次、每次至多 16 源；固定局部测向至多 16×6 次。field 原地预检测在六次之外，每任务至多一次，另加 16 次且不新增行程。放宽共享预算得到

$$M \leq 31 \times 20 + 16 \times 16 + 16 \times 6 + 16 \leq 31 \times 20 + 31 \times 16 + 16 \times 6 + 16 = 1228.$$

每源无信号后试清至多 6 次、小区域试清至多一次、覆盖至多 216 次，另留一次给非覆盖成功清除（骨架、共享、局部 near 或保证清除）；成功后不再处理，故 $C \leq 16(216 + 6 + 1 + 1) = 3584$ 。移动速度为 5 米/秒，测向含换频至多 6 秒，清除至多 5 秒，因而

$$T \leq \frac{31 \times 5240 + 16(7500 + 5 \times 6020 + 4520 + 4520 + 7570)}{5} + 1228 \times 6 + 3584 \times 5 < 100 \times 3600 \text{ s}. \quad (48)$$

这是虚拟时间保守界，不是预期成绩或最优界；refined/enhanced 没有新增预检测，仍可使用原 $M \leq 1212$ 。field 的任务重排及域缩小不改变其余范数、行程和光学次数预算，上界也不表示每个实例更快。现实 20 分钟限制须由客户端期限机制另行遵守。

网络故障可能耗尽现实时间，任何算法都不能对无限网络延迟保证 20 分钟内完成。客户端必须按剩余时间停止并报告未完成，不能将异常伪装成全清；现有官方演练仅验证原 refined 的正常链路，不能替代新 field 的官方时限确认。

11 合成环境与历史对照的保存

11.1 分布、误差与信息隔离

本地环境按公开动作协议生成反馈。常规世界源数在 10 至 16 间离散均匀，频道无放回抽样，位置在半径 1800 米圆盘内按面积均匀分布，接收半径在 1000 至 1500 米间均匀。问题三全部全向；问题四随机选择至少一个但非全部为定向源，发射方向均匀。这些是**合成分布假设**，不是官方数据的统计结论。策略只调用动作接口，总数、类型和真实位置不能参与在线决策；退出后评价器才用总数核对清除率。

同地点同频道的误差固定。实验设置三类误差场：有界双正弦平滑场、按位置哈希取 $\pm 1^\circ$ 端点的极端场、按位置哈希在 $[-1^\circ, 1^\circ]$ 中取值的场。第三类不表示原地重复读数独立。接口统一进行两位小数舍入，几何层按 1.005° 保守处理。

三类压力位置分别为：全部接收半径 1000 米；16 个圆周源且问题四中 15 个向外发射、另一个全向；16 个源聚集在距圆心 1650 米处的 35 米小圆盘。它们分别检验最小接收边界、定向搜索不能局限于圆内，以及集中多源时调度可能改变效率的情况。

11.2 历史研究不是本轮新改进的对照分母

历史 baseline 采用逐源往返，batched 批量扫描，integrated 增加停靠共享，enhanced 采用问题三 1200 米环和问题四 31 点滚动骨架，refined 进一步采用 25 点双环与联合调度。前述几何和局部算法先说明已在官方演练执行的 refined 基础；本轮 field 只在其上增加效率层，不将旧日志重新标为新策略成绩。

原 4430 次基础、3080 次增强、2200 次环半径筛选、2550 次开发及 10700 次 refined 确认均保留原种子、原参数与原结果。特别地，原 refined 两题横偏移比例始终为 0.22，不因本轮试探 0.12 而回写历史。原每问 1000 世界的 refined 均值为 261.46、544.74 秒/源，相对 enhanced 降低 5.38%、31.21%；这些不是本轮 field 的增益。1200 米环与 1250 米环的历史配对节省 2.377 秒/源，区间 $[1.608, 3.145]$ ，只用于保留参数来源，不再在本轮确认集上调参。

本轮曾试探缩环 fast25、硬限制已知频道补测和延后定位。fast25 保留 25 点且可证明安全，但不同合成组的平均收益方向不一致；微调探测比例也只有小幅收益。因此没有把它们列为默认改进，更没有用猜测隐藏源的事后重放证明收益。下节以独立命名的 field 和不变的 refined 进行新对照。

12 新策略的独立配对验证与收益来源

12.1 冻结规则、样本分工和实验分母

实测日志用于识别移动占比高、重复无信号和清除接入等瓶颈，不作为可随意查询的世界。开发阶段仅使用 6100000 至 6100149 的 150 个合成世界/问，Q3 七个、Q4 八个有限配置共 2250 次运行；比较原地补测、Q3 负约束、路线组合、首项半径权重及安全清除接近。只增加补测、硬限制补扫次数或轻微缩环均不足以解释主要收益；最终保留原 compact25 和两题 0.22 固定探测比例，不将此前临时参数试探当作正式改进。

冻结后使用 7100000 至 7100999 的每问 1000 个新世界。Q3 对照、仅路线、路线与信息、完整 field 四配置，Q4 对照和 field 两配置，共 6000 次；三种压力位置、三种误差场、两策略、两题各 50 对 (7200000 至 7200049)，共 1800 次；随机位置的另两种误差各 200 对 (7210000 至 7210199)，共 1600 次。合计 9400 次本地运行，全部完成全清并逐动作独立核对微秒计时。它们与 20 轮官方演练、早期 10700 次研究和 2250 次开发分别计数，不能相加称为独立世界数。

统计以每世界的 T_j/K_j 为等权单位，并按同一世界作差 $d_j = T_j^{\text{refined}}/K_j - T_j^{\text{field}}/K_j$ 。配对均值差的近似 95% 区间为 $\bar{d} \pm 1.96s_d/\sqrt{n}$ 。这说明合成分布下的均值不确定性，不是未来官方成绩的置信区间。参数、骨架与策略在本次确认前冻结，确认结果不再用于回调参数。

12.2 相对已演练 refined 的直接比较

表 4: 每问 1000 个新合成世界的配对结果，单位秒/源；不是官方反事实成绩

问题	策略	均值	p_{90}	最坏	全清
Q3	原 refined	258.99	305.38	370.28	1000/1000
Q3	仅路线改进	254.07	301.86	352.51	1000/1000
Q3	路线与信息	251.13	299.49	340.73	1000/1000
Q3	新 field	250.17	298.55	338.79	1000/1000
Q4	原 refined	542.41	682.86	825.03	1000/1000
Q4	新 field	508.60	642.48	760.05	1000/1000

问题三从 258.99 降至 250.17 秒/源，降低 3.40%；问题四从 542.41 降至 508.60 秒/源，降低 6.23%。节省均值分别为 8.82 和 33.81 秒/源，近似 95% 区间分别为 [8.01, 9.62] 与 [31.61, 36.01]；分别 827/1000 和 843/1000 局更快。两题均 1000/1000 全清，不以降低清除率换时间。问题四 p_{90} 由 682.86 降至 642.48 秒/源，样本最坏值由 825.03 降至 760.05 秒/源。补充的用户汇总记录 (results/user_supplied_field_practice_summary.json) 报告了新的非配对官方模拟器演练：field 在 Q3 为 11 局、134/134 个源，逐局等权平均 263.550883 秒/源；原 refined 为 10 局、139/139 个源，237.998263 秒/源。Q4 中 field 为 12 局、166/166 个源，484.966300 秒/源；原 refined 为 10 局、138/138 个源，531.177617 秒/源。案例不同且原始新日志未纳入本匿名包，因此这只是策略选择的诊断依据，不是因果比较。综合该非配对官方信号与本地配对证据，最终可

执行默认取 Q3refined、Q4field；两题均保留显式--strategy 覆盖选项。




图 4: 已冻结 field 与原 refined 的同世界耗时分布；两题均保留原覆盖骨架与完整停止证书。

12.3 消融和完整成本分解

表 5: 相邻配置的配对节省，单位秒/源；信息项合并原地补测与 Q3 负约束

问题	相邻配置	节省均值	近似 95% 区间
Q3	原 refined 至仅路线改进	4.92	[4.13, 5.70]
Q3	仅路线改进至路线与信息	2.94	[2.59, 3.28]
Q3	路线与信息至新 field	0.96	[0.87, 1.05]
Q4	原 refined 至新 field	33.81	[31.61, 36.01]

问题三的路线改进节省 4.92 秒/源，加入原地信息与负约束再节省 2.94 秒/源，安全接近再节省 0.96 秒/源。三者沿同一配置链比较，增量有条件性，不声称各机制脱离其他条件仍有相同贡献。问题四的主要收益来自路线组合；安全清除点移动在开发中没有体现稳定增益，因此对 Q4 关闭，不为堆叠机制而采用。

表 6: 按每世界每源的完整计费分解；移动含逐步微秒舍入，展示保留两位小数

问题	策略	移动	检测	换频	失败清除	成功清除	合计
Q3	原 refined	195.50	48.98	9.32	0.19	5.00	258.99
Q3	新 field	188.36	47.58	9.06	0.17	5.00	250.17
Q4	原 refined	383.47	129.62	23.91	0.41	5.00	542.41
Q4	新 field	350.93	128.53	23.66	0.48	5.00	508.60

Q3 平均行程由 12607.63 降至 12143.48 米，Q4 由 24581.18 降至 22499.71 米。Q4 失败清除尝试均值却由 1.782 增至 2.089 次/局，说明不能把失败次数本身当作任务目标；它的增加被移动节省抵消。这里的失败统计是尝试次数/局，不是失败案例比例，所有案例最终均全清。

12.4 压力、数值与现实运行边界

22 个本地压力/替代误差组全部全清，完整逐组均值、区间和更快案例数保存在 `results/field_confirmation.json` 及 `report/generated/field_stress.tex`。Q4 最小接收半径三组平均改善约 5.90% 至 7.06%，边界向外三组约 5.49% 至 5.86%；聚集源部分组的节省区间为 $[-9.37, 44.84]$ 秒/源，包含零，不能宣称在该组证实改善。Q3 边界源收益较小，聚集组约 0.53% 至 0.63%，不主张逐场景等比例下降，更不主张每局占优。

独立检查包含 3000 次负约束真实源包含性、1000 米边界与退化域、双精度溢出拒绝、开放路线任务守恒、两任务可解析最优例、200 组清除圆交接近及现实截止。保守内接多边形和顶点复验提供几何依据，随机检查只补充实现证据。两题新策略在主检验中本地单局最大运算耗时分别约 0.018 秒、0.072 秒；这些数值不包含官方 HTTP 延迟，不能替代 20 分钟现实期限的实测。现有 20 轮官方日志验证的是原 refined，新 field 必须新的官方演练局确认，正式测试仍需各题三次原始结果及加密日志。

13 正确性核验与工程实现

13.1 独立几何检查与状态回归

解析证明之外，另用不同计算路径检查实现：包围圆与 1/2/3 点支持圆穷举交叉核对；测向区间加入两位小数舍入后检查真实源包含；新 25 点构造核对三角剖分的内部反向边、无交叉和面积一致，使用 70 位十进制根式构造核对实际双精度坐标。双环坐

表 7: 核验项目及其证明范围，所有执行均为本地

项目	实际规模	核验目的
最小包围圆独立穷举	504 组点集	含点、线、近共线和随机点集
真实源包含	2000 组、每组 4 测向	角度跨零、边界源、端点误差及舍入
双环有限结构	每构型 36 三角形、60 边	无交叉、闭合剖分与最大边界
双环方向及扰动	每构型 22050 名义例、44100 扰动	包含辅助点恰在边或顶点，分别恶化投影与源距
已知频道跳过与停止	两题默认扫描规则	跳过不产生无源证书，负观测仍保持已发现，成功清除才完成
终端状态与 HTTP 重试	期限、near、16 源及截断响应	不确定动作不推进，超时不伪造退出

标对 70 位构造的最大差约 1.52×10^{-12} 米，远小于 1 米预算。方向采样补充而不取代

全称证明；光学条带候选也另核对 125 个凸域的 24072 个内外边界样点，但其小收益不足以让默认策略承担精确有理分割的额外复杂度。

13.2 协议、计时及期限

每个新动作使用唯一请求编号，传输失败只重发同路径、同编号和同请求字节；完整 HTTP 响应和 `accepted=true` 同时成立才提交位置、频道和虚拟时间。`/clear` 不改变测向机频道，拒绝响应中的零时间不能重置当前时刻。程序不等待虚拟动作耗时；现实截止采用 `/enter` 返回的剩余时间，虚拟上限为 360000 秒。

本地截断响应夹具在首次检测已经执行后中断响应，客户端重试同 ID，只计费一次；附件示例最终为 199 秒。慢速响应夹具验证绝对期限而非仅空闲 socket 超时。达到期限后保留最后确认状态，不再通过 `/exit` 查询已经关闭的接口。所有合成实验逐接受动作独立累计距离、换频和操作费用，并核对清除频道唯一性。已接受终端动作可以恰好完成证书；没有完成时则明确报告不完整。

13.3 复现与不能替代的官方证据

支撑包保留源代码、全部逐世界结果、开发与检验种子、生成图表脚本及输入哈希。复现按几何核验、实验、资产生成、LaTeX 编译的顺序进行，解压到独立目录重建，不以原目录已有文件充当复现成功。PDF 从摘要页起编号，正文不超过 30 页，完整代码置于附录 [3]。

官方演练已取得 20 轮原 refined 观察，但新 field 尚未取得官方确认。正式测试仍须在 GUI 选择正确题号、接口就绪后运行控制器，各题三次，记录实际案例编码、 K 、 T/K 和 GUI 定义的程序时间，导出六份原名原字节加密日志并核对上传。当前这些正式材料尚缺，本文不填写虚构正式表。支撑包仅包含经核对的脱敏演练日志及事后结果标签，不包含真实队号原始日志；它们不能替代正式加密文件。

14 结论与模型局限

问题一由正向半平面交求区域直径，最小包围圆而非直径圆是一次保证清除的判据；问题二给出有全向接收保证的三圆交候选域，并区分有限采样与在线启发式的最优性边界。问题三以七点收缩环、问题四以 25 点双环保证发现，逐频道证书负责正确停止。基于 20 轮演练识别的移动瓶颈，field 通过路线组合和 Q3 保守信息更新进一步提高独立合成配对的效率，不降低全清要求。

优势是几何安全层与启发式效率层分离，每条停止结论有证书，每个效率结论有同世界对照；不读取隐藏源数或假设原地误差独立。局限是 25 点及任务路线没有全局最优证明，Q3 负约束凸化仍丢弃部分非凸信息，聚集源部分组未体现显著改善，官方误差场和生成分布未标定。原算法严格回放出现分岔时不生成假响应；新 field 的本地提升也不等同于官方提升。后续仍须完成新演练、正式测试及真实参赛队人工核验，不以自动审查代替参赛责任 [4]。

AI 工具使用声明

本研究过程中使用了 AI 工具，参与核心模型推导、代码实现、实验设计、结果整理、独立自动审查及论文写作，详细过程见支撑材料中的《AI 工具使用详情》。本稿尚无真实参赛队完成逐项人工核验的记录，不将自动审查写作人工审查；该声明用于如实披露研究过程，不能替代正式提交前应完成的参赛队责任。

参考文献

- [1] 全国大学生数学建模竞赛组委会. 2026 年高教社杯全国大学生数学建模竞赛 B 题：无线电干扰源的快速自动定位与清除，以及附件 1、附件 2[Z]. 2026. https://www.mcm.edu.cn/html_cn/node/27b6e148f8113f09b0269f64a02629fb.html.
- [2] Welzl E. Smallest enclosing disks (balls and ellipsoids)[C]//New Results and New Trends in Computer Science. Lecture Notes in Computer Science, 555. Springer, 1991: 359–370. DOI: 10.1007/BFb0038202.
- [3] 全国大学生数学建模竞赛组委会. 全国大学生数学建模竞赛论文格式规范（2026 年修订稿）[EB/OL]. https://www.mcm.edu.cn/html_cn/node/4cd596519c9eb9fbd866398f6df0caa3.html.
- [4] 全国大学生数学建模竞赛组委会. 全国大学生数学建模竞赛人工智能工具使用规定（2026 年试行）[EB/OL]. https://www.mcm.edu.cn/html_cn/node/fef94648f2836ab6cc81586f4c38512b.html.

A 匿名复现附录

本附录只列出匿名包中实际存在、可供复现使用的源文件。代码路径均相对于本文件所在的 `report/` 目录；结果路径均相对于匿名包项目根目录；不含个人绝对路径、队伍身份或私有凭据。主文件应在导言区加载 `listings` 并设置合适的 Python 样式。

A.1 运行与验证源代码

Listing 1: 规划器与恢复策略

```
1 """Coverage-certified search; consumes observations only, never simulator truth."""
2
3 from dataclasses import dataclass, field
4 from math import dist, hypot
5 from time import monotonic
6
7 from active_policy_candidate import choose_probe
8 from client import AmbiguousActionError, DeadlineExceeded
9 from coverage import directional_waypoints, omni_waypoints
10 from geometry import clip_bearing, enclosing_circle, initial_polygon, optical_cover
11 from route_policy_candidate import optimize_waypoints
12 from joint_dispatch_candidate import choose_task
13 from optical_policy_candidate import certified_optical_cover
14 from polar_coverage_candidate import polar_waypoints
15
16
17 class SessionTerminated(RuntimeError):
18     """The simulator closed after an accepted action reached its limit."""
19
20
21 class InconsistentObservations(RuntimeError):
22     """The specified bounded-error model no longer contains a possible source."""
23
24
25 @dataclass
26 class Track:
27     polygon: list = field(default_factory=initial_polygon)
28     readings: list = field(default_factory=list)
29     observations: list = field(default_factory=list)
30     failures: list = field(default_factory=list)
31
32
33 class Planner:
34     """Baseline clears detections immediately; integrated batches and shares stops.
35
36     Sampling and route heuristics affect time only. Completeness comes from the
37     waypoint certificate and the conservative, finite optical-cover fallback.
38     """
39
40     def __init__(
41         self,
42         environment,
43         problem=3,
44         strategy="refined",
45         spacing=990.0,
46         probe_scale=0.22,
47         max_probes=6,
48         loss_recovery=True,
49         anchor_policy=None,
50         probe_policy="fixed",
51         ring_radius=None,
52         coverage_policy=None,
53         optical_policy="rectangle",
```

```

54     dispatch_policy=None,
55     scan_policy=None,
56 ):
57     if problem not in (3, 4) or strategy not in (
58         "baseline",
59         "batched",
60         "integrated",
61         "enhanced",
62         "refined",
63     ):
64         raise ValueError("Unsupported problem or strategy")
65     if anchor_policy is None:
66         anchor_policy = "rolling" if strategy in ("enhanced", "refined") and problem == 4 else "nearest"
67     if ring_radius is None and strategy in ("enhanced", "refined") and problem == 3:
68         ring_radius = 1200.0
69     if coverage_policy is None:
70         coverage_policy = "compact25" if strategy == "refined" and problem == 4 else "lattice"
71     if dispatch_policy is None:
72         dispatch_policy = ("center" if problem == 3 else "guarded") if strategy == "refined" else "separate"
73
74     if scan_policy is None:
75         scan_policy = ("unknown" if problem == 3 else "useful") if strategy == "refined" else "all"
76     if anchor_policy not in ("nearest", "two_opt", "rolling"):
77         raise ValueError("Unsupported anchor policy")
78     if probe_policy not in ("fixed", "adaptive"):
79         raise ValueError("Unsupported probe policy")
80     if not 900 <= spacing <= 999:
81         raise ValueError("Directional lattice spacing must be in [900, 999] m")
82     if not 0 < probe_scale <= 1 or max_probes < 1:
83         raise ValueError("Invalid localization policy parameters")
84     if coverage_policy not in ("lattice", "seed25", "compact25", "fast25"):
85         raise ValueError("Unsupported discovery coverage policy")
86     if optical_policy not in ("rectangle", "slabs"):
87         raise ValueError("Unsupported optical covering policy")
88     if dispatch_policy not in ("separate", "center", "guarded"):
89         raise ValueError("Unsupported task dispatch policy")
90     if scan_policy not in ("all", "unknown", "useful"):
91         raise ValueError("Unsupported known-channel scan policy")
92     self.scan_policy = scan_policy
93     self.coverage_policy = coverage_policy if problem == 4 else "ring"
94     self.optical_policy = optical_policy
95     self.dispatch_policy = dispatch_policy
96     self.environment = environment
97     self.problem = problem
98     self.strategy = strategy
99     self.waypoints = (
100         omni_waypoints(ring_radius) if problem == 3 else
101         directional_waypoints(spacing) if coverage_policy == "lattice" else
102         polar_waypoints(coverage_policy)
103     )
104     self.anchor_policy = anchor_policy
105     self.anchor_order = optimize_waypoints(self.waypoints) if anchor_policy == "two_opt" else []
106     self.anchor_rank = {index: rank for rank, index in enumerate(self.anchor_order)}
107     self.pending = set(range(len(self.waypoints)))
108     self.visited = []
109     self.tracks = {}
110     self.cleared = set()
111     self.scan_records = {ch: set() for ch in range(1, 21)}
112     self.position = (0.0, 0.0)
113     self.radio_channel = 1
114     self.virtual_time = 0.0
115     self.deadline = float("inf")
116     self.max_virtual_duration = float("inf")
117     self.terminal_reason = None
118     self.observation_points = {ch: [] for ch in range(1, 21)}
119     self.channel_state = {ch: "unresolved" for ch in range(1, 21)}
120     self.probe_scale = probe_scale

```

```

120     self.max_probes = max_probes
121     self.loss_recovery = bool(loss_recovery) and problem == 4
122     self.fallbacks = 0
123     self.probe_policy = probe_policy
124     self.adaptive_probes = 0
125     self.termination = None
126
127     def action(self, path, point=None, channel=None):
128         if self.terminal_reason is not None:
129             raise SessionTerminated(self.terminal_reason)
130         if monotonic() >= self.deadline - 2.0 and path != "/exit":
131             raise TimeoutError("Insufficient real time: completeness not certified")
132         response = self.environment.act(path, position=point, channel=channel)
133         if response.get("accepted") is not True:
134             raise RuntimeError("Rejected action; cached state was not advanced")
135         self.virtual_time = float(response["virtual_time_s"])
136         if path == "/enter":
137             self.max_virtual_duration = float(response.get("max_virtual_duration_s", float("inf")))
138         if point is not None:
139             self.position = tuple(point)
140         if path == "/measure":
141             self.radio_channel = channel
142         if path in ("/measure", "/clear") and self.virtual_time >= self.max_virtual_duration:
143             self.terminal_reason = "virtual_timeout"
144         return response
145
146     def clear(self, channel, point, guaranteed=False):
147         result = self.action("/clear", point, channel)["clear_result"]
148         if result == "success":
149             self.cleared.add(channel)
150             self.channel_state[channel] = "cleared"
151             self.tracks.pop(channel, None)
152             return True
153         if result != "no_target_in_range":
154             raise RuntimeError(f"Unknown clear result: {result}")
155         if guaranteed:
156             raise InconsistentObservations("Certified radius-20 clearing failed")
157         if channel in self.tracks:
158             self.tracks[channel].failures.append(tuple(point))
159         return False
160
161     def measure(self, channel, point):
162         result = self.action("/measure", point, channel)
163         status = result["measure_result"]
164         self.observation_points[channel].append(tuple(point))
165         track = self.tracks.get(channel)
166         if track is None and status == "direction":
167             track = Track(observations=self.observation_points[channel])
168             self.tracks[channel] = track
169         if track is not None:
170             track.observations = self.observation_points[channel]
171         if status == "near":
172             self.channel_state[channel] = "detected"
173             if self.terminal_reason is None:
174                 self.clear(channel, point, guaranteed=True)
175         elif status == "direction":
176             self.channel_state[channel] = "detected"
177             track.polygon = clip_bearing(track.polygon, point, result["svd_deg"])
178             if not track.polygon:
179                 raise InconsistentObservations(
180                     f"Empty feasible region on channel {channel}"
181                 )
182             track.readings.append((tuple(point), float(result["svd_deg"])))
183         elif status != "no_signal":
184             raise RuntimeError(f"Unknown measure result: {status}")
185         # No-signal observations are not convex halfplanes. In Q4 in particular,
186         # deleting a 1000-m disk would silently exclude real sources.

```

```

187         return status
188
189     def scan_anchor(self, index):
190         point = self.waypoints[index]
191         channels = [ch for ch in range(1, 21) if ch not in self.cleared]
192         channels.sort(key=lambda ch: (ch != self.radio_channel, ch))
193         for channel in channels:
194             if channel in self.cleared:
195                 continue
196             if channel in self.tracks:
197                 if self.scan_policy == "unknown":
198                     continue
199                 if self.scan_policy == "useful":
200                     center, radius = enclosing_circle(self.tracks[channel].polygon)
201                     if radius <= 19.9 or dist(point, center) - radius > 1500:
202                         continue
203             self.measure(channel, point)
204             self.scan_records[channel].add(index)
205             if len(self.cleared) == 16:
206                 self.termination = "known_count_upper_bound_16"
207                 break
208             if self.terminal_reason is not None:
209                 break
210             if self.strategy == "baseline" and channel in self.tracks:
211                 self.localize(channel)
212             if len(self.cleared) == 16:
213                 self.termination = "known_count_upper_bound_16"
214                 break
215             if self.terminal_reason is not None:
216                 break
217         self.pending.discard(index)
218         if index not in self.visited:
219             self.visited.append(index)
220
221     def optical_finish(self, channel):
222         self.fallbacks += 1
223         covering = certified_optical_cover if self.optical_policy == "slabs" else optical_cover
224         cover = covering(self.tracks[channel].polygon, radius=19.9)
225         if not cover:
226             raise InconsistentObservations("An empty region cannot certify clearing")
227         start = min(range(len(cover)), key=lambda k: dist(self.position, cover[k]))
228         # Rotate the certified snake to the nearest cell. At most one long
229         # wraparound jump; the remaining edges are adjacent rectangle cells.
230         order = cover[start:] + cover[:start]
231         for point in order:
232             if self.clear(channel, point):
233                 return
234             if self.terminal_reason is not None:
235                 return
236         raise InconsistentObservations("Exhausted a certified optical cover without clearing")
237
238     def localize(self, channel):
239         losses = 0
240         failed_probe = None
241         for probe_index in range(self.max_probes):
242             if channel in self.cleared or self.terminal_reason is not None:
243                 return
244             track = self.tracks[channel]
245             center, radius = enclosing_circle(track.polygon)
246             if max(dist(self.position, p) for p in track.polygon) <= 19.9:
247                 self.clear(channel, self.position, guaranteed=True)
248                 return
249             if radius <= 19.9:
250                 self.clear(channel, center, guaranteed=True)
251                 return
252             # When the remaining uncertainty is small, a 3-s failed optical
253             # attempt can cost less than travelling to take another bearing.

```

```

254     if radius <= 38 and center not in track.failures:
255         if self.clear(channel, center):
256             return
257         if self.terminal_reason is not None:
258             return
259         self.optical_finish(channel)
260         return
261     previous = track.readings[-1][0]
262     dx, dy = center[0] - previous[0], center[1] - previous[1]
263     length = hypot(dx, dy)
264     if length < 1e-8:
265         self.optical_finish(channel)
266         return
267     unit, normal = (dx / length, dy / length), (-dy / length, dx / length)
268     if failed_probe is not None and self.loss_recovery:
269         vector = (failed_probe[0] - previous[0], failed_probe[1] - previous[1])
270         axial = vector[0] * unit[0] + vector[1] * unit[1]
271         lateral = vector[0] * normal[0] + vector[1] * normal[1]
272         point = (
273             previous[0] + 0.5 * (axial * unit[0] - lateral * normal[0]),
274             previous[1] + 0.5 * (axial * unit[1] - lateral * normal[1]),
275         )
276         if any(point == p for p in track.observations) or point in track.failures:
277             self.optical_finish(channel)
278             return
279     else:
280         point = None
281         if self.probe_policy == "adaptive":
282             point = choose_probe(
283                 track.polygon,
284                 track.readings,
285                 self.position,
286                 self.problem,
287                 probes_remaining=self.max_probes - probe_index,
288                 rejected_points=track.failures + track.observations,
289                 probe_scale=self.probe_scale,
290             )
291         if point is not None:
292             self.adaptive_probes += 1
293         if point is None:
294             offset = min(120.0, max(25.0, self.probe_scale * radius))
295             candidates = [
296                 (
297                     center[0] + sign * offset * normal[0],
298                     center[1] + sign * offset * normal[1],
299                 )
300                 for sign in (-1, 1)
301             ]
302             fresh = [
303                 p
304                 for p in candidates
305                 if p not in track.observations
306                 and all(p != s for s in track.failures)
307             ]
308             if not fresh:
309                 self.optical_finish(channel)
310                 return
311             point = min(fresh, key=lambda p: dist(self.position, p))
312     status = self.measure(channel, point)
313     if channel in self.cleared or self.terminal_reason is not None:
314         return
315     if status == "no_signal":
316         losses += 1
317         if self.clear(channel, point):
318             return
319         if self.terminal_reason is not None:
320             return

```

```

321         failed_probe = point
322         if losses >= 2 and not self.loss_recovery:
323             self.optical_finish(channel)
324             return
325         else:
326             failed_probe = None
327         if channel not in self.cleared and self.terminal_reason is None:
328             self.optical_finish(channel)
329
330     def share_current_stop(self):
331         """Fuse an extra bearing for known sources at an already reached stop."""
332         if self.strategy not in ("integrated", "enhanced", "refined") or self.terminal_reason is not None or
333         len(self.cleared) == 16:
334             return
335         for channel in list(self.tracks):
336             if channel in self.cleared:
337                 continue
338             track = self.tracks[channel]
339             center, radius = enclosing_circle(track.polygon)
340             if radius <= 19.9:
341                 continue
342             if any(self.position == p for p in track.observations):
343                 continue
344             if dist(self.position, center) - radius > 1500:
345                 continue
346             self.measure(channel, self.position)
347             if self.terminal_reason is not None:
348                 return
349
350     def next_anchor(self):
351         if self.anchor_policy == "two_opt":
352             return min(self.pending, key=lambda i: self.anchor_rank[i])
353         if self.anchor_policy == "rolling":
354             indices = sorted(self.pending)
355             order = optimize_waypoints([self.waypoints[i] for i in indices], self.position)
356             return indices[order[0]]
357         return min(self.pending, key=lambda i: (dist(self.position, self.waypoints[i]), i))
358     def _result(self):
359         complete = len(self.cleared) == 16
360         if not complete:
361             for channel in range(1, 21):
362                 if channel in self.cleared:
363                     self.channel_state[channel] = "cleared"
364                 elif (self.channel_state[channel] != "detected"
365                     and len(self.scan_records[channel]) == len(self.waypoints)):
366                     self.channel_state[channel] = "absent-certified"
367                 else:
368                     complete = False
369                     break
370             else:
371                 complete = True
372         if self.terminal_reason is not None:
373             self.termination = ("complete_after_" if complete else "incomplete_") + self.terminal_reason
374         return {
375             "problem": self.problem,
376             "strategy": self.strategy,
377             "cleared_channels": sorted(self.cleared),
378             "n_cleared": len(self.cleared),
379             "virtual_time_s": self.virtual_time,
380             "average_time_s": self.virtual_time / len(self.cleared)
381             if self.cleared else None,
382             "probe_policy": self.probe_policy,
383             "probe_scale": self.probe_scale,
384             "anchor_policy": self.anchor_policy,
385             "ring_radius_m": hypot(*self.waypoints[1]) if self.problem == 3 else None,
386             "loss_recovery": self.loss_recovery,

```

```

387         "adaptive_probes": self.adaptive_probes,
388         "channel_certificates": dict(self.channel_state),
389         "certificate_complete": complete,
390         "terminal_reason": self.terminal_reason,
391         "visited_anchors": len(self.visited),
392         "total_anchors": len(self.waypoints),
393         "optical_fallbacks": self.fallbacks,
394         "termination": self.termination,
395         "coverage_policy": self.coverage_policy,
396         "optical_policy": self.optical_policy,
397         "dispatch_policy": self.dispatch_policy,
398         "scan_policy": self.scan_policy,
399     }
400
401     def run(self):
402         try:
403             return self._run_body()
404         except (TimeoutError, ConnectionError, AmbiguousActionError,
405                 DeadlineExceeded, SessionTerminated) as exc:
406             self.terminal_reason = self.terminal_reason or type(exc).__name__
407             self.termination = self.termination or "incomplete_" + type(exc).__name__
408             return self._result()
409
410     def select_task(self):
411         return choose_task(
412             self.position,
413             {i: self.waypoints[i] for i in sorted(self.pending)},
414             {ch: enclosing_circle(track.polygon) for ch, track in self.tracks.items()},
415             choice=self.dispatch_policy,
416         )
417
418     def _run_body(self):
419         entry_started = monotonic()
420         entered = self.action("/enter")
421         self.deadline = entry_started + entered["remaining_real_duration_s"]
422         self.scan_anchor(0)
423         while (self.pending or self.tracks) and self.terminal_reason is None:
424             if len(self.cleared) == 16:
425                 self.termination = "known_count_upper_bound_16"
426                 break
427             if self.strategy == "baseline":
428                 if self.tracks:
429                     self.localize(next(iter(self.tracks)))
430                 elif self.pending:
431                     self.scan_anchor(self.next_anchor())
432                 continue
433             if self.dispatch_policy != "separate":
434                 kind, index = self.select_task()
435                 if kind == "target":
436                     self.localize(index)
437                     self.share_current_stop()
438                 else:
439                     self.scan_anchor(index)
440                 continue
441             targets = [
442                 (dist(self.position, enclosing_circle(track.polygon)[0]), ch)
443                 for ch, track in self.tracks.items()
444             ]
445             anchors = [
446                 (
447                     dist(self.position, self.waypoints[i])
448                     + 30.0 * (20 - len(self.cleared)),
449                     i,
450                 )
451                 for i in ([self.next_anchor()] if self.pending and self.anchor_policy == "rolling" else self.
pending)
452             ]

```

```

453         # Convert a full scan to equivalent travel metres (6 s * 5 m/s).
454         # This is a myopic time heuristic, not a global-optimality claim.
455         if targets and (not anchors or min(targets)[0] <= min(anchors)[0]):
456             self.localize(min(targets)[1])
457             self.share_current_stop()
458         else:
459             self.scan_anchor(self.next_anchor())
460     if self.termination is None:
461         if self.terminal_reason is None:
462             for channel in range(1, 21):
463                 if channel in self.cleared:
464                     self.channel_state[channel] = "cleared"
465                 elif (self.channel_state[channel] != "detected"
466                       and len(self.scan_records[channel]) == len(self.waypoints)):
467                     self.channel_state[channel] = "absent-certified"
468                 else:
469                     raise RuntimeError("Incomplete per-channel discovery coverage")
470             self.termination = "all_channels_cleared_or_coverage_certified_absent"
471         else:
472             current = self._result()
473             if current["certificate_complete"]:
474                 self.termination = "complete_after_" + self.terminal_reason
475             else:
476                 self.termination = "incomplete_" + self.terminal_reason
477     if self.terminal_reason is None:
478         self.action("/exit")
479     return self._result()

```

Listing 2: 实验主程序

```

1  """Reproducible synthetic comparison; these are NOT official simulator scores."""
2
3  from __future__ import annotations
4
5  import argparse
6  import json
7  import math
8  import statistics
9  from pathlib import Path
10
11  from environment import LocalSimulator
12  from planner import Planner
13
14
15  def run_case(
16      seed,
17      problem,
18      strategy,
19      scenario="random",
20      error_mode="smooth",
21      probe_scale=0.22,
22      spacing=990.0,
23      loss_recovery=True,
24      anchor_policy=None,
25      ring_radius=None,
26      probe_policy="fixed",
27      coverage_policy=None,
28      optical_policy="rectangle",
29      dispatch_policy=None,
30      scan_policy=None,
31  ):
32      env = LocalSimulator(seed, problem, error_mode, scenario)
33      planner = Planner(
34          env,
35          problem,
36          strategy,
37          spacing=spacing,

```

```

38     probe_scale=probe_scale,
39     loss_recovery=loss_recovery,
40     anchor_policy=anchor_policy,
41     ring_radius=ring_radius,
42     probe_policy=probe_policy,
43     coverage_policy=coverage_policy,
44     optical_policy=optical_policy,
45     dispatch_policy=dispatch_policy,
46     scan_policy=scan_policy,
47 )
48 p = planner.run()
49 assert p["certificate_complete"] is True
50 s = env.summary()
51 # Independent action-by-action accounting, without reading hidden world data.
52 position, radio, total = (0.0, 0.0), 1, 0.0
53 successes = set()
54 for event in env.log:
55     request, response = event["request"], event["response"]
56     if not response["accepted"]:
57         continue
58     path = request["path"]
59     if path in ("/measure", "/clear"):
60         q = (request["position"]["x"], request["position"]["y"])
61         total += round(math.dist(position, q) / 5, 6)
62         position = q
63         if path == "/measure":
64             total += 5 + int(radio != request["channel"])
65             radio = request["channel"]
66         else:
67             success = response["clear_result"] == "success"
68             total += 5 if success else 3
69             if success:
70                 assert request["channel"] not in successes
71                 successes.add(request["channel"])
72     assert abs(total - response["virtual_time_s"]) < 2e-6
73 assert len(successes) == s["n_cleared"] == p["n_cleared"]
74 assert s["n_sources"] == s["n_cleared"], (seed, problem, scenario, error_mode, s)
75 return {
76     **s,
77     "strategy": strategy,
78     "visited_anchors": p["visited_anchors"],
79     "optical_fallbacks": p["optical_fallbacks"],
80     "probe_scale": p["probe_scale"],
81     "loss_recovery_requested": loss_recovery,
82     "loss_recovery": p["loss_recovery"],
83     "anchor_policy": p["anchor_policy"],
84     "ring_radius_m": p["ring_radius_m"],
85     "spacing_m": spacing,
86     "certificate_complete": p["certificate_complete"],
87     "timing_independently_verified": True,
88     "coverage_policy": p["coverage_policy"],
89     "optical_policy": p["optical_policy"],
90     "dispatch_policy": p["dispatch_policy"],
91     "scan_policy": p["scan_policy"],
92 }
93
94
95 def aggregate(rows):
96     values = sorted(row["average_time_s"] for row in rows)
97     return {
98         "cases": len(rows),
99         "all_cleared_cases": sum(r["fraction_cleared"] == 1 for r in rows),
100         "mean_average_time_s": statistics.mean(values),
101         "median_average_time_s": statistics.median(values),
102         "p90_average_time_s": values[math.ceil(0.9 * len(values)) - 1],
103         "worst_average_time_s": values[-1],
104         "mean_total_time_s": statistics.mean(r["virtual_time_s"] for r in rows),

```

```

105     "mean_distance_m": statistics.mean(r["distance_m"] for r in rows),
106     "mean_measures": statistics.mean(r["measures"] for r in rows),
107     "mean_failed_clears": statistics.mean(r["failed_clears"] for r in rows),
108     "max_real_duration_s": max(r["real_duration_s"] for r in rows),
109 }
110
111
112 def main():
113     parser = argparse.ArgumentParser()
114     parser.add_argument("--cases", type=int, default=200)
115     parser.add_argument("--output", type=Path, default=Path("results/experiments.json"))
116     args = parser.parse_args()
117     if args.cases < 2:
118         parser.error("At least two paired cases required")
119     rows, grouped, paired, stress, sensitivity = [], {}, {}, {}, {}
120     for problem in (3, 4):
121         strategy_rows = {}
122         for strategy in ("baseline", "batched", "integrated"):
123             current = [
124                 run_case(600000 + k, problem, strategy) for k in range(args.cases)
125             ]
126             rows.extend(current)
127             strategy_rows[strategy] = current
128             grouped[f"Q{problem}_{strategy}"] = aggregate(current)
129         differences = [
130             a["average_time_s"] - b["average_time_s"]
131             for a, b in zip(strategy_rows["baseline"], strategy_rows["integrated"])
132         ]
133         delta = statistics.mean(differences)
134         standard_error = statistics.stdev(differences) / math.sqrt(len(differences))
135         paired[f"Q{problem}"] = {
136             "mean_saved_s_per_source": delta,
137             "approx_95pct_ci_s": [
138                 delta - 1.96 * standard_error,
139                 delta + 1.96 * standard_error,
140             ],
141             "mean_time_reduction_pct": 100
142             * delta
143             / grouped[f"Q{problem}_baseline"]["mean_average_time_s"],
144             "faster_cases": sum(d > 0 for d in differences),
145             "paired_cases": len(differences),
146         }
147         share_differences = [
148             a["average_time_s"] - b["average_time_s"]
149             for a, b in zip(strategy_rows["batched"], strategy_rows["integrated"])
150         ]
151         paired[f"Q{problem}_sharing_ablation"] = {
152             "mean_saved_s_per_source": statistics.mean(share_differences),
153             "faster_cases": sum(d > 0 for d in share_differences),
154             "paired_cases": len(share_differences),
155         }
156     for scenario in ("minimum_radius", "outward_boundary", "clustered"):
157         for mode in ("smooth", "extreme", "iid_location"):
158             current = [
159                 run_case(700000 + k, problem, "integrated", scenario, mode)
160                 for k in range(20)
161             ]
162             rows.extend(current)
163             stress[f"Q{problem}_{scenario}_{mode}"] = aggregate(current)
164     # Sensitivity uses different seeds, no held-out retuning afterwards.
165     for scale in (0.12, 0.22, 0.40):
166         current = [
167             run_case(800000 + k, problem, "integrated", probe_scale=scale)
168             for k in range(30)
169         ]
170         rows.extend(current)
171         sensitivity[f"Q{problem}_probe_{scale}"] = aggregate(current)

```

```

172     for spacing in (900.0, 950.0, 990.0):
173         current = [
174             run_case(900000 + k, 4, "integrated", spacing=spacing) for k in range(30)
175         ]
176         rows.extend(current)
177         sensitivity[f"Q4_spacing_{spacing}"] = aggregate(current)
178     recovery_ablation = {}
179     for scenario in ("random", "minimum_radius", "outward_boundary", "clustered"):
180         for enabled in (False, True):
181             current = [
182                 run_case(610000 + k, 4, "integrated", scenario, loss_recovery=enabled)
183                 for k in range(100)
184             ]
185             rows.extend(current)
186             recovery_ablation[f"{scenario}_recovery_{enabled}"] = aggregate(current)
187     result = {
188         "evidence": "local_synthetic_not_official",
189         "assumptions": "See environment.py module docstring",
190         "paired_random_cases_per_problem": args.cases,
191         "total_runs": len(rows),
192         "summary": grouped,
193         "paired_comparison": paired,
194         "stress": stress,
195         "sensitivity": sensitivity,
196         "recovery_ablation": recovery_ablation,
197         "runs": rows,
198     }
199     args.output.parent.mkdir(parents=True, exist_ok=True)
200     args.output.write_text(
201         json.dumps(result, ensure_ascii=False, indent=2) + "\n", encoding="utf-8"
202     )
203     print(
204         json.dumps(
205             {k: v for k, v in result.items() if k != "runs"},
206             ensure_ascii=False,
207             indent=2,
208         )
209     )
210
211
212 if __name__ == "__main__":
213     main()

```

Listing 3: 统一运行入口

```

1  """Run local synthetic practice; official GUI sessions require client.HTTPClient separately."""
2
3  from __future__ import annotations
4
5  import argparse
6  import json
7  from pathlib import Path
8
9  from environment import LocalSimulator
10 from field_policy import FieldPlanner
11 from planner import Planner
12
13
14 def run_local(
15     seed: int,
16     problem: int,
17     scenario: str = "random",
18     error_mode: str = "smooth",
19     strategy: str | None = None,
20 ) -> dict:
21     env = LocalSimulator(
22         seed, problem=problem, scenario=scenario, error_mode=error_mode

```

```

23     )
24     effective_strategy = strategy if strategy is not None else ("refined" if problem == 3 else "field")
25     planner = (
26         FieldPlanner(env, problem=problem)
27         if effective_strategy == "field"
28         else Planner(env, problem=problem, strategy=effective_strategy)
29     )
30     planner_result = planner.run()
31     result = {"planner": planner_result, "simulator": env.summary()}
32     return result
33
34
35 def main() -> None:
36     parser = argparse.ArgumentParser()
37     parser.add_argument("--seed", type=int, default=20260910)
38     parser.add_argument("--problem", type=int, choices=(3, 4), default=3)
39     parser.add_argument("--scenario", default="random")
40     parser.add_argument("--error-mode", default="smooth")
41     parser.add_argument(
42         "--strategy",
43         choices=("baseline", "batched", "integrated", "enhanced", "refined", "field"),
44         default=None,
45         help="默认Q3使用refined、Q4使用field; 可显式指定任一策略",
46     )
47     parser.add_argument("--output", type=Path)
48     args = parser.parse_args()
49     result = run_local(
50         args.seed, args.problem, args.scenario, args.error_mode, args.strategy
51     )
52     text = json.dumps(result, ensure_ascii=False, indent=2)
53     if args.output:
54         args.output.parent.mkdir(parents=True, exist_ok=True)
55         args.output.write_text(text + "\n", encoding="utf-8")
56     print(text)
57
58
59 if __name__ == "__main__":
60     main()

```

Listing 4: 几何计算

```

1  """Conservative bearing geometry and whole-region optical clearing certificates.
2
3  Polygons are ordered convex vertex lists (either winding); [] means infeasible,
4  never unbounded. All distances are metres and bearings are counterclockwise degrees.
5  """
6
7  from __future__ import annotations
8
9  from decimal import Decimal, localcontext
10 from math import ceil, cos, hypot, isfinite, nextafter, pi, radians, sin, sqrt, ulp
11 from random import Random
12
13 Point = tuple[float, float]
14 Circle = tuple[Point, float]
15 ARENA_RADIUS = 1800.0
16 MAX_RADIO_RADIUS = 1500.0
17 BEARING_ERROR_DEG = 1.005
18
19
20 def _check_points(points: list[Point]) -> None:
21     if any(not (isfinite(x) and isfinite(y)) for x, y in points):
22         raise ValueError("Geometry requires finite coordinates")
23
24
25 def _padding(scale: float) -> float:
26     return max(1e-9, 64.0 * ulp(max(1.0, scale)))

```

```

27
28
29 def initial_polygon(sides: int = 180) -> list[Point]:
30     """Return a CCW circumscribed polygon, never an inscribed approximation."""
31     if isinstance(sides, bool) or not isinstance(sides, int) or sides < 3:
32         raise ValueError("sides must be an integer at least three")
33     radius = (ARENA_RADIUS + _padding(ARENA_RADIUS)) / cos(pi / sides)
34     return [
35         (radius * cos(2 * pi * i / sides), radius * sin(2 * pi * i / sides))
36         for i in range(sides)
37     ]
38
39
40 def _clip_halfplane(
41     poly: list[Point], origin: Point, normal: Point, bound: float, padding: float
42 ) -> list[Point]:
43     """Clip n.(x-origin) <= bound+padding using the same shifted boundary."""
44     if not poly:
45         return []
46     nx, ny = normal
47     ox, oy = origin
48     limit = bound + padding
49     result: list[Point] = []
50     previous = poly[-1]
51     dp = nx * (previous[0] - ox) + ny * (previous[1] - oy) - limit
52     for current in poly:
53         dc = nx * (current[0] - ox) + ny * (current[1] - oy) - limit
54         if (dp <= 0.0) != (dc <= 0.0):
55             # Opposite signs prevent cancellation in dp-dc. Interpolate from
56             # the nearer endpoint to reduce cancellation near a polygon vertex.
57             if abs(dp) <= abs(dc):
58                 t = dp / (dp - dc)
59                 crossing = (
60                     previous[0] + t * (current[0] - previous[0]),
61                     previous[1] + t * (current[1] - previous[1]),
62                 )
63             else:
64                 t = dc / (dc - dp)
65                 crossing = (
66                     current[0] + t * (previous[0] - current[0]),
67                     current[1] + t * (previous[1] - current[1]),
68                 )
69             if not result or crossing != result[-1]:
70                 result.append(crossing)
71             if dc <= 0.0 and (not result or current != result[-1]):
72                 result.append(current)
73             previous, dp = current, dc
74     if len(result) > 1 and result[0] == result[-1]:
75         result.pop()
76     return result
77
78
79 def clip_bearing(
80     poly: list[Point],
81     point: Point,
82     bearing_deg: float,
83     error_deg: float = BEARING_ERROR_DEG,
84 ) -> list[Point]:
85     """Intersect a bounded region with a forward wedge and a safe range cap.
86
87     The default includes the 0.005-degree two-decimal API rounding allowance.
88     The cap is a relaxation of distance <= 1500, not an assumed known range.
89     Contradictions remain []; no fallback region or constraint reset is applied.
90     """
91     _check_points(poly)
92     _check_points([point])
93     if not isfinite(bearing_deg) or not isfinite(error_deg) or not 0 <= error_deg < 90:

```

```

94         raise ValueError("Use finite bearing and 0 <= error_deg < 90")
95     if not poly:
96         return []
97     theta = radians(bearing_deg % 360.0)
98     error = radians(error_deg)
99     low, high = theta - error, theta + error
100     scale = max(
101         MAX_RADIO_RADIUS,
102         abs(point[0]),
103         abs(point[1]),
104         *(max(abs(x), abs(y)) for x, y in poly),
105     )
106     padding = _padding(scale)
107     # cross(u_low, x-point)>=0 and cross(u_high, x-point)<=0.
108     result = _clip_halfplane(poly, point, (sin(low), -cos(low)), 0.0, padding)
109     result = _clip_halfplane(result, point, (-sin(high), cos(high)), 0.0, padding)
110     result = _clip_halfplane(result, point, (-cos(theta), -sin(theta)), 0.0, padding)
111     return _clip_halfplane(
112         result, point, (cos(theta), sin(theta)), MAX_RADIO_RADIUS, padding
113     )
114
115
116 def _farthest_pair(poly: list[Point]) -> tuple[Point, Point, float]:
117     first = second = poly[0]
118     distance = 0.0
119     for i, a in enumerate(poly):
120         for j in range(i):
121             b = poly[j]
122             candidate = hypot(a[0] - b[0], a[1] - b[1])
123             if candidate > distance:
124                 first, second, distance = a, b, candidate
125     return first, second, distance
126
127
128 def diameter(poly: list[Point]) -> float:
129     """Exact vertex-pair characterization, O(n^2); empty input is an error."""
130     _check_points(poly)
131     if not poly:
132         raise ValueError("An infeasible region has no localization diameter")
133     return _farthest_pair(poly)[2]
134
135
136 def _pair_circle(a: Point, b: Point) -> Circle:
137     center = (a[0] + (b[0] - a[0]) / 2, a[1] + (b[1] - a[1]) / 2)
138     return center, max(hypot(center[0] - p[0], center[1] - p[1]) for p in (a, b))
139
140
141 def _cross(a: Point, b: Point, c: Point) -> float:
142     bx, by = b[0] - a[0], b[1] - a[1]
143     cx, cy = c[0] - a[0], c[1] - a[1]
144     determinant = bx * cy - by * cx
145     scale = max(abs(bx), abs(by), abs(cx), abs(cy))
146     if abs(determinant) > 64 * ulp(max(1.0, scale * scale)):
147         return determinant
148     with localcontext() as context:
149         context.prec = 80
150         ax, ay = Decimal(a[0]), Decimal(a[1])
151         return float(
152             (Decimal(b[0]) - ax) * (Decimal(c[1]) - ay)
153             - (Decimal(b[1]) - ay) * (Decimal(c[0]) - ax)
154         )
155
156
157 def _circumcircle(a: Point, b: Point, c: Point) -> Circle | None:
158     bx, by = b[0] - a[0], b[1] - a[1]
159     cx, cy = c[0] - a[0], c[1] - a[1]
160     determinant = bx * cy - by * cx

```

```

161 scale = max(abs(bx), abs(by), abs(cx), abs(cy))
162 if abs(determinant) <= 64 * ulp(max(1.0, scale * scale)):
163     # Decimal fallback resolves almost-collinear triples from the actual
164     # binary input values, without pretending a small determinant is zero.
165     with localcontext() as context:
166         context.prec = 80
167         axd, ayd = Decimal(a[0]), Decimal(a[1])
168         bxd, byd = Decimal(b[0]) - axd, Decimal(b[1]) - ayd
169         cxd, cyd = Decimal(c[0]) - axd, Decimal(c[1]) - ayd
170         det = 2 * (bxd * cyd - byd * cxd)
171         if not det:
172             return None
173         bb, cc = bxd * bxd + byd * byd, cxd * cxd + cyd * cyd
174         center = (
175             float(axd + (cyd * bb - byd * cc) / det),
176             float(ayd + (bxd * cc - cxd * bb) / det),
177         )
178     else:
179         bb, cc = bx * bx + by * by, cx * cx + cy * cy
180         center = (
181             a[0] + (cy * bb - by * cc) / (2 * determinant),
182             a[1] + (bx * cc - cx * bb) / (2 * determinant),
183         )
184     return center, max(hypot(center[0] - p[0], center[1] - p[1]) for p in (a, b, c))
185
186
187 def _contains(circle: Circle, point: Point) -> bool:
188     center, radius = circle
189     return hypot(point[0] - center[0], point[1] - center[1]) <= nextafter(
190         radius, float("inf")
191     )
192
193
194 def _two_boundary_circle(points: list[Point], end: int, a: Point, b: Point) -> Circle:
195     base = _pair_circle(a, b)
196     left: Circle | None = None
197     right: Circle | None = None
198     left_cross = right_cross = 0.0
199     for i in range(end):
200         p = points[i]
201         if _contains(base, p):
202             continue
203         side = _cross(a, b, p)
204         candidate = _circumcircle(a, b, p)
205         if candidate is None:
206             continue
207         center_side = _cross(a, b, candidate[0])
208         if side > 0 and (left is None or center_side > left_cross):
209             left, left_cross = candidate, center_side
210         elif side < 0 and (right is None or center_side < right_cross):
211             right, right_cross = candidate, center_side
212     if left is None:
213         return base if right is None else right
214     if right is None:
215         return left
216     return left if left[1] <= right[1] else right
217
218
219 def enclosing_circle(poly: list[Point]) -> Circle:
220     """Minimum enclosing circle, with a tiny outward floating-point guard.
221
222     Randomized incremental 1/2/3-support construction, not a diameter-disk or
223     approximate iterative fit. The local fixed shuffle never alters global RNG.
224     Empty input raises instead of manufacturing a spurious clearing location.
225     """
226     _check_points(poly)
227     if not poly:

```

```

228         raise ValueError("An infeasible region has no enclosing-circle center")
229 points = list(dict.fromkeys(poly))
230 Random(0).shuffle(points)
231 circle: Circle | None = None
232 for i, p in enumerate(points):
233     if circle is not None and _contains(circle, p):
234         continue
235     circle = (p, 0.0)
236     for j in range(i):
237         q = points[j]
238         if _contains(circle, q):
239             continue
240         if circle[1] == 0.0:
241             circle = _pair_circle(p, q)
242         else:
243             circle = _two_boundary_circle(points, j + 1, p, q)
244 assert circle is not None
245 center = circle[0]
246 radius = max(hypot(p[0] - center[0], p[1] - center[1]) for p in points)
247 if radius == 0.0:
248     return center, 0.0
249 scale = max(radius, abs(center[0]), abs(center[1]))
250 return center, nextafter(radius + _padding(scale), float("inf"))
251
252
253 def optical_cover(poly: list[Point], radius: float = 19.9) -> list[Point]:
254     """Cover the ENTIRE convex polygon, not merely its vertices or boundary.
255
256     Use its MEC when possible; otherwise tile an enclosing rectangle aligned
257     with a diameter. Every grid cell fits in its own radius-radius disk. Some
258     centers may lie outside the polygon or arena, which the API permits.
259     [] stays []: callers must treat it as infeasibility, not successful clearing.
260     """
261     _check_points(poly)
262     if not isfinite(radius) or radius <= 0:
263         raise ValueError("Optical covering radius must be finite and positive")
264     if not poly:
265         return []
266     center, enclosing_radius = enclosing_circle(poly)
267     if enclosing_radius <= radius:
268         return [center]
269     a, b, distance = _farthest_pair(poly)
270     if distance == 0.0:
271         return [a]
272     ux, uy = (b[0] - a[0]) / distance, (b[1] - a[1]) / distance
273     # Re-normalize before forming the orthogonal frame.
274     norm = hypot(ux, uy)
275     ux, uy = ux / norm, uy / norm
276     projected = [
277         ((x - a[0]) * ux + (y - a[1]) * uy, -(x - a[0]) * uy + (y - a[1]) * ux)
278         for x, y in poly
279     ]
280     scale = max(distance, *(max(abs(x), abs(y)) for x, y in poly))
281     guard = _padding(scale)
282     safe_radius = radius - 8 * guard
283     if safe_radius <= 0:
284         raise ValueError(
285             "Radius is below floating-point resolution at these coordinates"
286         )
287     xmin, xmax = (
288         min(p[0] for p in projected) - guard,
289         max(p[0] for p in projected) + guard,
290     )
291     ymin, ymax = (
292         min(p[1] for p in projected) - guard,
293         max(p[1] for p in projected) + guard,
294     )

```

```

295     side = sqrt(2.0) * safe_radius
296     nx = max(1, ceil((xmax - xmin) / side))
297     ny = max(1, ceil((ymax - ymin) / side))
298     dx, dy = (xmax - xmin) / nx, (ymax - ymin) / ny
299     centers: list[Point] = []
300     for j in range(ny):
301         y = ymin + (j + 0.5) * dy
302         indices = range(nx) if j % 2 == 0 else range(nx - 1, -1, -1)
303         for i in indices:
304             x = xmin + (i + 0.5) * dx
305             centers.append((a[0] + x * ux - y * uy, a[1] + x * uy + y * ux))
306     return centers

```

Listing 5: 几何验证

```

1  """Independent numerical geometry checks; no official simulator calls."""
2
3  from __future__ import annotations
4
5  import itertools
6  import json
7  import math
8  import random
9  from pathlib import Path
10
11  import numpy as np
12  from scipy.optimize import linprog
13
14  from coverage import coverage_certificate, directional_waypoints, omni_waypoints
15  from geometry import (
16      clip_bearing,
17      diameter,
18      enclosing_circle,
19      initial_polygon,
20      optical_cover,
21  )
22
23
24  def contains(poly, p, tolerance=1e-6):
25      if not poly:
26          return False
27      area = sum(a[0] * b[1] - a[1] * b[0] for a, b in zip(poly, poly[1:] + poly[:1]))
28      sign = 1 if area >= 0 else -1
29      return all(
30          sign * ((b[0] - a[0]) * (p[1] - a[1]) - (b[1] - a[1]) * (p[0] - a[0]))
31          >= -tolerance
32          for a, b in zip(poly, poly[1:] + poly[:1])
33      )
34
35
36  def reference_circle(points):
37      """Exhaust every 1/2/3-point support, independently of incremental MEC."""
38      candidates = [(p, 0.0) for p in points]
39      for a, b in itertools.combinations(points, 2):
40          c = ((a[0] + b[0]) / 2, (a[1] + b[1]) / 2)
41          candidates.append((c, math.dist(a, b) / 2))
42      for a, b, c in itertools.combinations(points, 3):
43          ab, ac = np.asarray(b) - a, np.asarray(c) - a
44          matrix = 2 * np.array([ab, ac])
45          if abs(np.linalg.det(matrix)) < 1e-12:
46              continue
47          offset = np.linalg.solve(matrix, np.array([ab @ ab, ac @ ac]))
48          center = np.asarray(a) + offset
49          candidates.append((tuple(center), math.dist(center, a)))
50      feasible = [
51          (c, r)
52          for c, r in candidates

```

```

53         if all(math.dist(c, p) <= r + 1e-7 for p in points)
54     ]
55     return min(feasible, key=lambda item: item[1])
56
57
58 def main():
59     exact_ray = clip_bearing(
60         [(-100.0, 0.0), (100.0, 0.0)], (0.0, 0.0), 0.0, error_deg=0.0
61     )
62     assert min(p[0] for p in exact_ray) >= -1e-6, (
63         "Zero-error bearing retained its backward ray"
64     )
65     try:
66         directional_waypoints(1e-300)
67     except ValueError:
68         pass
69     else:
70         raise AssertionError("Extreme lattice refinement was not rejected")
71     rng = random.Random(831762)
72     max_mec_error = 0.0
73     sets = [
74         [(0.0, 0.0)],
75         [(0.0, 0.0), (36.0, 0.0), (18.0, 18 * math.sqrt(3))],
76         [(0.0, 0.0), (1.0, 1e-12), (2.0, 0.0)],
77         [(7.0, 5.0), (7.0, 5.0)],
78     ]
79     sets += [
80         [
81             (rng.uniform(-2000, 2000), rng.uniform(-2000, 2000))
82             for _ in range(rng.randint(2, 9))
83         ]
84         for _ in range(500)
85     ]
86     for points in sets:
87         actual = enclosing_circle(points)
88         expected = reference_circle(points)
89         max_mec_error = max(max_mec_error, abs(actual[1] - expected[1]))
90         assert abs(actual[1] - expected[1]) < 1e-6, (points, actual, expected)
91         assert all(math.dist(actual[0], p) <= actual[1] for p in points)
92     triangle = [(0.0, 0.0), (36.0, 0.0), (18.0, 18 * math.sqrt(3))]
93     polygon = initial_polygon()
94     length = 18 * math.sqrt(3) / math.tan(math.radians(2)) - 18
95     stations = []
96     for i, (a, b) in enumerate(zip(triangle, triangle[1:] + triangle[:1])):
97         unit = ((b[0] - a[0]) / 36, (b[1] - a[1]) / 36)
98         s = (a[0] - length * unit[0], a[1] - length * unit[1])
99         stations.append(s)
100     polygon = clip_bearing(polygon, s, 1 + 120 * i, error_deg=1.0)
101     counterexample = {
102         "stations": stations,
103         "bearings_deg": [1, 121, 241],
104         "diameter_m": diameter(polygon),
105         "mec_radius_m": enclosing_circle(polygon)[1],
106     }
107     assert abs(counterexample["diameter_m"] - 36) < 1e-6
108     assert counterexample["mec_radius_m"] > 20
109     # True-source containment including boundary source, wraparound and +/-1 noise.
110     containment_trials = 2000
111     optical_trials = 0
112     for index in range(containment_trials):
113         angle = rng.uniform(0, math.tau)
114         radius = 1800 if index % 5 == 0 else 1800 * math.sqrt(rng.random())
115         source = (radius * math.cos(angle), radius * math.sin(angle))
116         poly = initial_polygon()
117         for j in range(4):
118             r, phi = rng.uniform(6, 1500), rng.uniform(0, math.tau)
119             station = (source[0] + r * math.cos(phi), source[1] + r * math.sin(phi))

```

```

120         error = rng.choice([-1.0, 1.0]) if index % 2 else rng.uniform(-1, 1)
121         bearing = round((math.degrees(phi) + 180 + error) % 360, 2) % 360
122         poly = clip_bearing(poly, station, bearing)
123         assert contains(poly, source), (index, source, poly)
124     if index < 200:
125         centers = optical_cover(poly)
126         for _ in range(20):
127             weights = [rng.random() for _ in poly]
128             total = sum(weights)
129             p = tuple(
130                 sum(w * vertex[k] for w, vertex in zip(weights, poly)) / total
131                 for k in (0, 1)
132             )
133             assert min(math.dist(p, c) for c in centers) <= 19.9 + 1e-7
134             optical_trials += 1
135     omni, directional = omni_waypoints(), directional_waypoints()
136     max_omni_distance, min_directional_slack = 0.0, float("inf")
137     for i in range(2000):
138         angle = rng.uniform(0, math.tau)
139         radius = 1800 if i % 2 else 1800 * math.sqrt(rng.random())
140         p = (radius * math.cos(angle), radius * math.sin(angle))
141         max_omni_distance = max(max_omni_distance, min(math.dist(p, s) for s in omni))
142         nearby = [s for s in directional if math.dist(p, s) <= 990 + 1e-7]
143         # Independent convex-hull feasibility, all orientations at once for p.
144         points = np.asarray(nearby)
145         solved = linprog(
146             np.zeros(len(points)),
147             A_eq=np.vstack([points.T, np.ones(len(points))]),
148             b_eq=np.array([*p, 1.0]),
149             bounds=(0, None),
150             method="highs",
151         )
152         assert solved.success, p
153         for _ in range(5):
154             phi = rng.uniform(0, math.tau)
155             seen = [
156                 math.dist(p, s)
157                 for s in directional
158                 if (s[0] - p[0]) * math.cos(phi) + (s[1] - p[1]) * math.sin(phi) >= 0
159             ]
160             min_directional_slack = min(min_directional_slack, 1000 - min(seen))
161     assert max_omni_distance <= 900 + 1e-7 and min_directional_slack >= 0
162     # Exact triple-lens safe region sampled as a separate numerical sanity check.
163     alpha = math.radians(1.005)
164     max_reception_excess = -float("inf")
165     for _ in range(10000):
166         t = rng.uniform(1, 999)
167         bmax = min(
168             math.sqrt(1e6 - t * t),
169             math.sqrt(1e6 - (t - 1000 * math.cos(alpha)) ** 2) - 1000 * math.sin(alpha),
170         )
171         b = rng.uniform(-1, 1) * max(0.0, bmax)
172         r, phi = rng.uniform(0, 1500), rng.uniform(-alpha, alpha)
173         excess = math.dist((t, b), (r * math.cos(phi), r * math.sin(phi))) - max(
174             1000, r
175         )
176         max_reception_excess = max(max_reception_excess, excess)
177     assert excess <= 1e-6
178     result = {
179         "evidence": "independent_numerical_checks_not_a_substitute_for_analytic_proofs",
180         "exact_forward_ray_regression": True,
181         "unbounded_refinement_rejected": True,
182         "mec_reference_cases": len(sets),
183         "maximum_mec_radius_error_m": max_mec_error,
184         "realizable_counterexample": counterexample,
185         "containment_cases": containment_trials,
186         "bearings_per_case": 4,

```

```

187     "optical_interior_samples": optical_trials,
188     "coverage_source_samples": 2000,
189     "maximum_sampled_omni_distance_m": max_omni_distance,
190     "minimum_sampled_directional_radio_slack_m": min_directional_slack,
191     "triple_lens_samples": 10000,
192     "maximum_sampled_reception_excess_m": max_reception_excess,
193     "coverage_certificate": coverage_certificate(),
194 }
195 Path("results").mkdir(exist_ok=True)
196 Path("results/geometry_verification.json").write_text(
197     json.dumps(result, ensure_ascii=False, indent=2) + "\n"
198 )
199 # The default enhanced policy uses the 1200m Q3 ring and rolling Q4
200 # skeleton. The fixed-probe/local-recovery bound is deliberately separate
201 # from the optional adaptive candidate. Reflection is about the last
202 # positive station and contracts its station distance by one half.
203 station_probe_bound = math.hypot(1501, 120)
204 source_probe_bound = 1500 + station_probe_bound
205 assert station_probe_bound < 1506 and source_probe_bound < 3006
206 max_move = 31 * 5240 + 16 * (7500 + 5 * 6020 + 4520 + 4520 + 7570)
207 max_time = max_move / 5 + 1212 * 6 + 3584 * 5
208 assert max_time < 100 * 3600 <= 360000
209 bound = {
210     "evidence": "arithmetic_of_analytic_bound_not_simulation",
211     "scope": "enhanced policy: Q3 ring1200, Q4 rolling skeleton, fixed probes, six probes",
212     "skeleton_edge_upper_m": 5240,
213     "skeleton_move_upper_m": 31 * 5240,
214     "positive_source_distance_upper_m": 1500,
215     "strip_axial_upper_m": 1501,
216     "strip_width_upper_m": 53,
217     "station_probe_bound_m": station_probe_bound,
218     "source_probe_bound_m": source_probe_bound,
219     "local_transition_upper_m": 6020,
220     "local_task_entry_upper_m": 7500,
221     "optional_center_clear_access_upper_m": 4520,
222     "optical_access_upper_m": 4520,
223     "optical_cover_centers_upper": 216,
224     "optical_snake_length_upper_m": 7570,
225     "distance_upper_m": max_move,
226     "measure_upper": 1212,
227     "clear_attempt_upper": 3584,
228     "virtual_time_upper_s": max_time,
229     "virtual_time_upper_h": max_time / 3600,
230     "proof": "report/bound_proof.tex; no guarantee for real network deadline",
231 }
232 Path("results/operation_bound.json").write_text(json.dumps(bound, indent=2) + "\n")
233 print(json.dumps(result, ensure_ascii=False, indent=2))
234
235
236 if __name__ == "__main__":
237     main()

```

Listing 6: 问题一原始交会区域分类与直径

```

1 """Q1: actual bearing-halfplane intersection, without an artificial bounding box.
2
3 Feasibility and four coordinate LPs distinguish empty/unbounded/bounded sets.
4 For a bounded set all feasible pairwise boundary intersections are enumerated.
5 This optional Q1 analysis uses SciPy; the online search policy uses stdlib only.
6 """
7
8 from __future__ import annotations
9
10 import itertools
11 import json
12 import math
13 from pathlib import Path

```

```

14
15 import numpy as np
16 from scipy.optimize import linprog
17
18 from geometry import diameter, enclosing_circle
19
20
21 def solve_intersection(stations, bearings_deg, error_deg=1.0):
22     if len(stations) != len(bearings_deg) or not 0 <= error_deg < 90:
23         raise ValueError("Match stations/readings and use an error in [0,90) degrees")
24     if not stations:
25         return {"status": "unbounded", "vertices": [], "diameter_m": None}
26     rows, rhs = [], []
27     alpha = math.radians(error_deg)
28     for (x, y), angle in zip(stations, bearings_deg):
29         if not all(math.isfinite(value) for value in (x, y, angle)):
30             raise ValueError("Finite coordinates and bearings are required")
31         theta = math.radians(angle % 360)
32         for normal in (
33             (math.sin(theta - alpha), -math.cos(theta - alpha)),
34             (-math.sin(theta + alpha), math.cos(theta + alpha)),
35             (-math.cos(theta), -math.sin(theta)),
36         ):
37             rows.append(normal)
38             rhs.append(normal[0] * x + normal[1] * y)
39     a, b = np.asarray(rows), np.asarray(rhs)
40     feasible = linprog(
41         np.zeros(2), A_ub=a, b_ub=b, bounds=[(None, None)] * 2, method="highs"
42     )
43     if feasible.status == 2:
44         return {"status": "infeasible", "vertices": [], "diameter_m": None}
45     if not feasible.success:
46         raise RuntimeError(f"Halfplane feasibility LP failed: {feasible.message}")
47     for objective in ((1.0, 0.0), (-1.0, 0.0), (0.0, 1.0), (0.0, -1.0)):
48         bound = linprog(
49             objective, A_ub=a, b_ub=b, bounds=[(None, None)] * 2, method="highs"
50         )
51         if bound.status == 3:
52             return {"status": "unbounded", "vertices": [], "diameter_m": None}
53         if not bound.success:
54             raise RuntimeError(f"Halfplane boundedness LP failed: {bound.message}")
55     vertices = []
56     for i, j in itertools.combinations(range(len(a)), 2):
57         determinant = a[i, 0] * a[j, 1] - a[i, 1] * a[j, 0]
58         if determinant == 0:
59             continue
60         point = (
61             (b[i] * a[j, 1] - a[i, 1] * b[j]) / determinant,
62             (a[i, 0] * b[j] - b[i] * a[j, 0]) / determinant,
63         )
64         if np.max(a @ point - b) <= 1e-7 and all(
65             math.dist(point, old) > 1e-7 for old in vertices
66         ):
67             vertices.append(point)
68     if not vertices:
69         raise ArithmeticError(
70             "Bounded nonempty intersection had no numerical vertex; inspect conditioning"
71         )
72     center = tuple(np.mean(vertices, axis=0))
73     vertices.sort(
74         key=lambda point: math.atan2(point[1] - center[1], point[0] - center[0])
75     )
76     circle = enclosing_circle(vertices)
77     return {
78         "status": "bounded",
79         "vertices": vertices,
80         "diameter_m": diameter(vertices),

```

```

81     "mec_center": circle[0],
82     "mec_radius_m": circle[1],
83     "max_halfplane_residual_m": max(float(np.max(a @ p - b)) for p in vertices),
84 }
85
86
87 def main():
88     triangle = [(0.0, 0.0), (36.0, 0.0), (18.0, 18 * math.sqrt(3))]
89     length = 18 * math.sqrt(3) / math.tan(math.radians(2)) - 18
90     stations = []
91     for first, second in zip(triangle, triangle[1:] + triangle[:1]):
92         stations.append(
93             (
94                 first[0] - length * (second[0] - first[0]) / 36,
95                 first[1] - length * (second[1] - first[1]) / 36,
96             )
97         )
98     bounded = solve_intersection(stations, [1, 121, 241])
99     unbounded = solve_intersection([(0.0, 0.0)], [0.0])
100     infeasible = solve_intersection([(0.0, 0.0), (-10.0, 0.0)], [0.0, 180.0])
101     assert bounded["status"] == "bounded" and abs(bounded["diameter_m"] - 36) < 1e-6
102     assert unbounded["status"] == "unbounded" and infeasible["status"] == "infeasible"
103     result = {
104         "evidence": "Q1_direct_halfplane_algorithm_examples",
105         "bounded": bounded,
106         "unbounded": unbounded,
107         "infeasible": infeasible,
108     }
109     Path("results").mkdir(exist_ok=True)
110     Path("results/intersection_verification.json").write_text(
111         json.dumps(result, indent=2) + "\n"
112     )
113     print(json.dumps(result, indent=2))
114
115
116 if __name__ == "__main__":
117     main()

```

Listing 7: 覆盖与采样工具

```

1  """Finite, analytically justified discovery waypoint sets for CUMCM B Q3/Q4.
2
3  These functions prescribe measurement locations, not a route or a stopping rule.
4  Every unresolved channel needs its own completed coverage record. In particular,
5  Q4 waypoints outside the source arena must not be projected back into the arena.
6  """
7
8  from __future__ import annotations
9
10 import math
11
12 Point = tuple[float, float]
13
14 ARENA_RADIUS = 1800.0
15 MIN_RADIO_RADIUS = 1000.0
16 OMNI_COVER_RADIUS = 900.0
17 DEFAULT_SPACING = 990.0
18
19
20 def omni_waypoints(ring_radius: float | None = None) -> list[Point]:
21     """Return origin plus six ring points; the legacy radius certifies 900 m.
22
23     The 1200-m contracted ring instead has exact cover radius given by
24     ring_cover_radius, still below the guaranteed 1000-m reception distance.
25     No unspecified source-position prior is used by this geometric guarantee.
26     """
27     ring_radius = OMNI_COVER_RADIUS * math.sqrt(3.0) if ring_radius is None else float(ring_radius)

```

```

28     if not math.isfinite(ring_radius) or not 1200.0 <= ring_radius <= OMNI_COVER_RADIUS * math.sqrt(3.0):
29         raise ValueError("Supported ring radius is [1200, 900*sqrt(3)] m")
30     return [(0.0, 0.0)] + [
31         (
32             ring_radius * math.cos(k * math.pi / 3.0),
33             ring_radius * math.sin(k * math.pi / 3.0),
34         )
35         for k in range(6)
36     ]
37
38
39 def ring_cover_radius(ring_radius: float) -> float:
40     """Exact covering radius of origin plus six equally spaced ring points."""
41     omni_waypoints(ring_radius)
42     return max(ring_radius / math.sqrt(3.0),
43               math.sqrt(ARENA_RADIUS**2 + ring_radius**2
44                       - math.sqrt(3.0) * ARENA_RADIUS * ring_radius))
45
46
47 def directional_waypoints(spacing: float = DEFAULT_SPACING) -> list[Point]:
48     """Return a finite triangular lattice with a full source-domain guard.
49
50     For a source g inside the arena, the elementary triangle containing g has
51     vertices within spacing of g and norm <= ARENA_RADIUS + spacing.
52     If g is a lattice vertex, all six nearest neighbours satisfy that same
53     norm bound, so every emission direction has a nonzero forward neighbour.
54     No such six-neighbour claim is made for vertices outside the source arena.
55     Support 900 <= spacing <= 999; ordering is origin then row and column.
56     """
57     spacing = float(spacing)
58     if not math.isfinite(spacing) or not 900.0 <= spacing <= MIN_RADIO_RADIUS - 1.0:
59         raise ValueError("spacing must be finite and in [900, 999] m")
60
61     # With a=(s,0), b=(s/2,s*sqrt(3)/2), the squared norm of i*a+j*b
62     # is s*s*(i*i+i*j+j*j). Compare the radial cutoff using integers, so
63     # floating-point rounding cannot accidentally remove a boundary vertex.
64     numerator, denominator = spacing.as_integer_ratio()
65     guard_numerator = 1800 * denominator + numerator
66     numerator_squared = numerator * numerator
67     guard_squared = guard_numerator * guard_numerator
68     # q=i*i+i*j+j*j >= 3*i*i/4 and >= 3*j*j/4. The simpler bound
69     # |il,|jl| <= ceil(2*(1800+s)/s) safely contains the radial selection.
70     bound = (2 * guard_numerator + numerator - 1) // numerator
71     row_height = spacing * math.sqrt(3.0) / 2.0
72     points: list[Point] = [(0.0, 0.0)]
73     for j in range(-bound, bound + 1):
74         for i in range(-bound, bound + 1):
75             if i == 0 and j == 0:
76                 continue
77             norm_squared_units = i * i + i * j + j * j
78             if norm_squared_units * numerator_squared <= guard_squared:
79                 points.append((spacing * (i + j / 2.0), row_height * j))
80     return points
81
82
83 def coverage_certificate() -> dict:
84     """Return analytic constants/counts, not a sampled or experimental result.
85
86     Counts describe the default 990 m lattice. Norm shells are exact integer
87     values of i*i+i*j+j*j; their multiplicities can be checked independently.
88     No simulator actions, numerical coverage sampling, or routing occur here.
89     """
90     return {
91         "certificate_kind": "analytic_geometric_cover",
92         "arena_radius_m": ARENA_RADIUS,
93         "minimum_radio_radius_m": MIN_RADIO_RADIUS,
94         "channels": 20,

```

```

95     "omni_legacy": {
96         "waypoint_count": 7,
97         "ring_radius_m": OMNI_COVER_RADIUS * math.sqrt(3.0),
98         "cover_radius_m": OMNI_COVER_RADIUS,
99         "radio_slack_m": MIN_RADIO_RADIUS - OMNI_COVER_RADIUS,
100        "proof": (
101            "r<=900 is covered by the origin. For 900<=r<=1800, "
102            "choose a ring center with angular gap <=pi/6. Then "
103            "distance^2<=r^2-2700*r+2430000<=810000 by convexity "
104            "and equality of the two endpoint values."
105        ),
106    },
107    "omni_enhanced": {
108        "waypoint_count": 7,
109        "ring_radius_m": 1200.0,
110        "cover_radius_m": ring_cover_radius(1200.0),
111        "radio_slack_m": MIN_RADIO_RADIUS - ring_cover_radius(1200.0),
112        "proof": "Exact envelope formula ring_cover_radius(1200); no point or channel obligation is removed
113    },
114    "omni": {
115        "waypoint_count": 7,
116        "ring_radius_m": OMNI_COVER_RADIUS * math.sqrt(3.0),
117        "cover_radius_m": OMNI_COVER_RADIUS,
118        "radio_slack_m": MIN_RADIO_RADIUS - OMNI_COVER_RADIUS,
119        "proof": "Legacy 900m certificate; enhanced 1200m certificate is in omni_enhanced.",
120    },
121    "directional": {
122        "spacing_m": DEFAULT_SPACING,
123        "basis_m": [
124            [DEFAULT_SPACING, 0.0],
125            [DEFAULT_SPACING / 2.0, DEFAULT_SPACING * math.sqrt(3.0) / 2.0],
126        ],
127        "selection_radius_m": ARENA_RADIUS + DEFAULT_SPACING,
128        "maximum_source_vertex_distance_m": DEFAULT_SPACING,
129        "radio_slack_m": MIN_RADIO_RADIUS - DEFAULT_SPACING,
130        "waypoint_count": 31,
131        "inside_or_on_arena_count": 13,
132        "outside_arena_count": 18,
133        "norm_squared_units_counts": {0: 1, 1: 6, 3: 6, 4: 6, 7: 12},
134        "maximum_waypoint_radius_m": DEFAULT_SPACING * math.sqrt(7.0),
135        "closed_halfplane_required": True,
136        "boundary_guard_required": True,
137        "proof": (
138            "An elementary triangular-lattice triangle containing g has "
139            "three vertices within spacing of g. Their norms are at most "
140            "1800+spacing, hence all are selected. Write "
141            "g=sum(lambda_i*v_i), lambda_i>=0, sum(lambda_i)=1. "
142            "For any emission normal n, sum(lambda_i*n dot (v_i-g))=0, "
143            "so at least one vertex is in the closed emission halfplane. "
144            "If g is a lattice vertex inside the source arena, all six "
145            "nearest neighbors have norm <=1800+spacing and are selected; "
146            "one makes angle <=pi/6 with any emission normal."
147        ),
148        "count_proof": (
149            "At spacing 990 the cutoff is i^2+i*j+j^2<=961/121. "
150            "The possible shells are 0,1,3,4,7 with multiplicities "
151            "1,6,6,6,12. The arena cutoff is 400/121, leaving shells "
152            "0,1,3 inside and shells 4,7 outside."
153        ),
154    },
155    "termination": (
156        "For each of 20 channels, retain either a confirmed successful "
157        "clear or a complete all-no_signal covering scan for that channel. "
158        "A detected but uncleared channel remains unresolved. With at "
159        "most one source per channel, all 20 certificates imply no "
160        "remaining source. Independently, 16 distinct confirmed clears "

```

```

161         "reach the stated global upper bound. Fewer clears alone do not."
162     ),
163     "no_signal": {
164         "q3": "Excludes every source at distance <=1000 from that detector.",
165         "q4": (
166             "Does not exclude that disk: a source may emit away from the "
167             "detector. Only the completed per-channel halfplane cover "
168             "excludes every source position and orientation."
169         ),
170     },
171     "assumptions": [
172         "Sources are stationary, persist until cleared, and use distinct channels.",
173         "Directional emission is a closed 180-degree halfplane with fixed orientation.",
174         "Reception reaches at least 1000 m throughout the emission halfplane.",
175         "All designated measurements actually complete on the indicated channel.",
176         "Near-source responses count as detections, not as no_signal.",
177         "Robot coordinates outside the radius-1800 source arena are permitted.",
178         "Geometric proofs use exact real coordinates; default float coordinates have 10 m range slack.",
179     ],
180 }

```

Listing 8: 环境与模拟器接口

```

1  """Synthetic, not official, CUMCM 2026 B environment (standard library only).
2
3  Generation assumptions are deliberately explicit, not claims about official data:
4  * random: N is discrete uniform on 10..16; N distinct channels sampled uniformly
5    without replacement; positions iid uniform in the radius-1800 disk (sqrt(U)
6    radial law); radio radii iid uniform [1000,1500]; orientations uniform [0,2*pi).
7    Q3 is all omni. Q4 chooses a uniform count in 1..N-1 and a uniform subset
8    of directional sources, guaranteeing both types.
9  * minimum_radius: random geometry, but every radio radius is exactly 1000.
10 * outward_boundary: 16 equally spaced sources on the arena boundary, a seeded
11   common rotation, all radii 1000. Q4 has 15 outward-facing directional sources
12   and one omni, so inward-only search is deliberately inadequate.
13 * clustered: 16 sources uniform in a 35m disk around a seeded center at radius
14   1650; all radio radii 1000, with the random mixed-type rule for Q4.
15
16 Errors are deterministic functions of (seed, channel, exact coordinate): smooth
17 is a bounded two-sinusoid field; extreme is spatial-hashed +/-1 degree;
18 iid_location is spatial-hashed uniform [-1,1], NOT independent repeat readings.
19 The latter is a synthetic hash field, not an assertion of official IID noise.
20 Sources and their parameters are private. Only post-exit summary reveals counts.
21 There are no virtual-duration sleeps; movement time is rounded to microseconds.
22 """
23
24 from __future__ import annotations
25
26 import hashlib
27 import math
28 import random
29 import struct
30 import threading
31 import time
32 from dataclasses import dataclass
33
34 Point = tuple[float, float]
35 SCENARIOS = ("random", "minimum_radius", "outward_boundary", "clustered")
36 ERROR_MODES = ("smooth", "extreme", "iid_location")
37
38
39 def _action_args(path: str, position: Point | None, channel: int | None):
40     """Validate before any state mutation; match protocol coordinate limits."""
41     if path not in ("/enter", "/exit", "/measure", "/clear"):
42         raise ValueError("Unknown action path (paths must be exact)")
43     if path in ("/enter", "/exit"):
44         if position is not None or channel is not None:

```

```

45         raise ValueError("enter/exit do not accept position or channel")
46     return None, None
47 if not isinstance(position, (tuple, list)) or len(position) != 2:
48     raise ValueError("position must contain exactly two finite coordinates")
49 if any(isinstance(v, bool) or not isinstance(v, (int, float)) for v in position):
50     raise ValueError("Coordinates must be JSON numbers")
51 try:
52     point = (float(position[0]), float(position[1]))
53 except OverflowError as exc:
54     raise ValueError("Coordinate outside protocol range") from exc
55 if any(not math.isfinite(v) or abs(v) > 2_000_000 for v in point):
56     raise ValueError("Coordinates must be finite and within +/-2000000m")
57 if (
58     isinstance(channel, bool)
59     or not isinstance(channel, (int, float))
60     or not 1 <= channel <= 20
61     or int(channel) != channel
62 ):
63     raise ValueError("channel must be an integer in 1..20")
64 return point, int(channel)
65
66
67 @dataclass(slots=True)
68 class _Source:
69     position: Point
70     radius: float
71     normal: Point | None
72     phase: float
73     cleared: bool = False
74
75
76 class LocalSimulator:
77     """One local test session; /enter initializes state, duplicate entry rejects.
78
79     log contains only observable request/response/timing data. After termination,
80     construct a new instance for another session, just as the official interface
81     requires a new GUI test. Automatic deadline termination closes this session;
82     no fabricated /exit response is generated in that case.
83     """
84
85     def __init__(
86         self,
87         seed: int,
88         problem: int = 3,
89         error_mode: str = "smooth",
90         scenario: str = "random",
91     ):
92         if isinstance(seed, bool) or not isinstance(seed, int):
93             raise TypeError("seed must be an integer")
94         if problem not in (3, 4):
95             raise ValueError("problem must be 3 or 4")
96         if error_mode not in ERROR_MODES or scenario not in SCENARIOS:
97             raise ValueError(f"Use scenarios {SCENARIOS} and modes {ERROR_MODES}")
98         self._seed, self._problem = seed, problem
99         self._error_mode, self._scenario = error_mode, scenario
100         self._lock = threading.Lock()
101         self._status = "ready"
102         self._sources: dict[int, _Source] = {}
103         self._position: Point = (0.0, 0.0)
104         self._radio_channel = 1
105         self._virtual_us = 0
106         self._distance = 0.0
107         self._measures = self._switches = self._clear_attempts = self._failed_clears = 0
108         self._started: float | None = None
109         self._finished: float | None = None
110         self._exit_reason: str | None = None
111         self.log: list[dict] = []

```

```

112
113 def _generate(self):
114     rng = random.Random(self._seed)
115     n = (
116         16
117         if self._scenario in ("outward_boundary", "clustered")
118         else rng.randint(10, 16)
119     )
120     channels = rng.sample(range(1, 21), n)
121     if self._problem == 3:
122         directional = set()
123     elif self._scenario == "outward_boundary":
124         directional = set(channels[:-1])
125     else:
126         directional = set(rng.sample(channels, rng.randint(1, n - 1)))
127     rotation = rng.uniform(0, math.tau)
128     center = (1650 * math.cos(rotation), 1650 * math.sin(rotation))
129     sources = {}
130     for i, channel in enumerate(channels):
131         theta = rng.uniform(0, math.tau)
132         if self._scenario == "outward_boundary":
133             theta = rotation + math.tau * i / n
134             position = (1800 * math.cos(theta), 1800 * math.sin(theta))
135         elif self._scenario == "clustered":
136             r = 35 * math.sqrt(rng.random())
137             position = (
138                 center[0] + r * math.cos(theta),
139                 center[1] + r * math.sin(theta),
140             )
141         else:
142             r = 1800 * math.sqrt(rng.random())
143             position = (r * math.cos(theta), r * math.sin(theta))
144             radius = rng.uniform(1000, 1500) if self._scenario == "random" else 1000.0
145             orientation = (
146                 theta
147                 if self._scenario == "outward_boundary"
148                 else rng.uniform(0, math.tau)
149             )
150             normal = (
151                 (math.cos(orientation), math.sin(orientation))
152                 if channel in directional
153                 else None
154             )
155             sources[channel] = _Source(
156                 position, radius, normal, rng.uniform(0, math.tau)
157             )
158     self._sources = sources
159
160 def _bearing_error(self, point: Point, channel: int, source: _Source) -> float:
161     x, y = point
162     if self._error_mode == "smooth":
163         return 0.6 * math.sin(x / 173 + y / 251 + source.phase) + 0.4 * math.sin(
164             x / 419 - y / 137 + 2 * source.phase
165         )
166     # Canonicalize signed zero: it is the same physical coordinate.
167     packed = struct.pack("!dB", x or 0.0, y or 0.0, channel)
168     salt = str(self._seed).encode("ascii") + b":"
169     value = int.from_bytes(
170         hashlib.blake2b(salt + packed, digest_size=8).digest(), "big"
171     )
172     if self._error_mode == "extreme":
173         return 1.0 if value & 1 else -1.0
174     return 2 * (value / ((1 << 64) - 1)) - 1
175
176 def _visible(self, source: _Source, point: Point) -> bool:
177     dx, dy = point[0] - source.position[0], point[1] - source.position[1]
178     if math.hypot(dx, dy) > source.radius:

```

```

179         return False
180     if source.normal is None:
181         return True
182     a, b = dx * source.normal[0], dy * source.normal[1]
183     # Include the closed halfplane boundary despite floating-point dot error;
184     # tolerance is only a handful of machine ulps, not an angular margin.
185     return a + b >= -8 * math.ulp(max(abs(a), abs(b), 1.0))
186
187 def _response(self, accepted: bool = True, **fields) -> dict:
188     return {
189         "accepted": accepted,
190         "real_timestamp_ms": int(time.time() * 1000),
191         "virtual_time_s": self._virtual_us / 1_000_000 if accepted else 0,
192         **fields,
193     }
194
195 def _finish(self, reason: str):
196     self._status = "exited"
197     self._finished = time.monotonic()
198     self._exit_reason = reason
199
200 def act(
201     self, path: str, position: Point | None = None, channel: int | None = None
202 ) -> dict:
203     position, channel = _action_args(path, position, channel)
204     with self._lock:
205         if self._status == "exited":
206             raise ConnectionError(
207                 "Local session interface closed after exit/timeout"
208             )
209         if self._started is not None and time.monotonic() >= self._started + 1200:
210             self._finish("real_timeout")
211             raise ConnectionError("Local session reached its real deadline")
212         request = {"path": path}
213         if position is not None:
214             request.update(
215                 position={"x": position[0], "y": position[1]}, channel=channel
216             )
217         before = self._virtual_us
218         radio_before = self._radio_channel
219         distance = 0.0
220         switched = False
221         action_seconds = 0
222         if path == "/enter":
223             if self._status != "ready":
224                 response = self._response(False)
225             else:
226                 self._generate()
227                 self._position, self._radio_channel = (0.0, 0.0), 1
228                 self._virtual_us = 0
229                 self._started = time.monotonic()
230                 self._status = "active"
231                 response = self._response(
232                     max_virtual_duration_s=360000,
233                     max_real_duration_s=1200,
234                     remaining_real_duration_s=1200,
235                 )
236             elif self._status != "active":
237                 response = self._response(False)
238             elif path == "/exit":
239                 self._finish("user_exit")
240                 response = self._response(exit_reason="user_exit")
241             else:
242                 distance = math.dist(self._position, position)
243                 source = self._sources.get(channel)
244                 live = source is not None and not source.cleared
245                 if path == "/measure":

```

```

246         switched = channel != self._radio_channel
247         self._radio_channel = channel
248         self._switches += int(switched)
249         self._measures += 1
250         action_seconds = 5
251         fields = {"measure_result": "no_signal"}
252         if live and self._visible(source, position):
253             if math.dist(position, source.position) <= 5:
254                 fields = {"measure_result": "near"}
255             else:
256                 angle = math.degrees(
257                     math.atan2(
258                         source.position[1] - position[1],
259                         source.position[0] - position[0],
260                     )
261                 )
262                 bearing = (
263                     round(
264                         (
265                             angle
266                             + self._bearing_error(position, channel, source)
267                         )
268                         % 360,
269                         2,
270                     )
271                     % 360
272                 )
273                 fields = {"measure_result": "direction", "svd_deg": bearing}
274         else:
275             self._clear_attempts += 1
276             success = live and math.dist(position, source.position) <= 20
277             if success:
278                 source.cleared = True
279             else:
280                 self._failed_clears += 1
281             action_seconds = 5 if success else 3
282             fields = {
283                 "clear_result": "success" if success else "no_target_in_range"
284             }
285             self._position = position
286             self._distance += distance
287             self._virtual_us += (
288                 round(distance / 5 * 1_000_000)
289                 + (action_seconds + int(switched)) * 1_000_000
290             )
291             response = self._response(**fields)
292             if self._virtual_us >= 360000 * 1_000_000:
293                 # An action registered before the deadline is allowed to finish.
294                 self._finish("virtual_timeout")
295             self.log.append(
296                 {
297                     "request": request,
298                     "response": dict(response),
299                     "distance_m": distance,
300                     "move_time_s": round(distance / 5, 6),
301                     "switch_time_s": int(switched),
302                     "action_time_s": action_seconds,
303                     "radio_channel_before": radio_before,
304                     "radio_channel_after": self._radio_channel,
305                     "action_virtual_time_s": (self._virtual_us - before) / 1_000_000,
306                 }
307             )
308             return response
309
310     def summary(self) -> dict:
311         """Evaluation only: inaccessible during a run; never consumed by planner."""
312         with self._lock:

```

```

313         if self._status != "exited":
314             raise RuntimeError("summary is available only after session exit")
315         n = len(self._sources)
316         cleared = sum(source.cleared for source in self._sources.values())
317         virtual_time = self._virtual_us / 1_000_000
318         directional = sum(
319             source.normal is not None for source in self._sources.values()
320         )
321         return {
322             "evidence": "local_synthetic_not_official",
323             "seed": self._seed,
324             "problem": self._problem,
325             "scenario": self._scenario,
326             "error_mode": self._error_mode,
327             "n_sources": n,
328             "n_cleared": cleared,
329             "n_omnidirectional": n - directional,
330             "n_directional": directional,
331             "fraction_cleared": cleared / n,
332             "virtual_time_s": virtual_time,
333             "average_time_s": virtual_time / cleared if cleared else None,
334             "distance_m": self._distance,
335             "measures": self._measures,
336             "switches": self._switches,
337             "clear_attempts": self._clear_attempts,
338             "failed_clears": self._failed_clears,
339             "real_duration_s": self._finished - self._started,
340             "exit_reason": self._exit_reason,
341         }

```

Listing 9: 第二交点计算

```

1  """Q2 robust reception lens and explicitly sampled min-max geometry scoring."""
2
3  from __future__ import annotations
4
5  import json
6  import math
7  from pathlib import Path
8
9  from geometry import clip_bearing, enclosing_circle, initial_polygon
10
11
12  def safe_candidates(station=(0.0, 0.0), bearing_deg=0.0, alpha_deg=1.005):
13      alpha, angle = math.radians(alpha_deg), math.radians(bearing_deg)
14      u, n = (math.cos(angle), math.sin(angle)), (-math.sin(angle), math.cos(angle))
15      choices = []
16      for t in (125.0, 250.0, 375.0, 500.0, 625.0, 750.0, 875.0):
17          bound = min(
18              math.sqrt(1000**2 - t * t),
19              math.sqrt(1000**2 - (t - 1000 * math.cos(alpha)) ** 2)
20              - 1000 * math.sin(alpha),
21          )
22          for proportion in (0.25, 0.5, 0.75):
23              for sign in (-1, 1):
24                  b = sign * proportion * bound
25                  point = (
26                      station[0] + t * u[0] + b * n[0],
27                      station[1] + t * u[1] + b * n[1],
28                  )
29                  choices.append({"point": point, "t_m": t, "b_m": b})
30      return choices
31
32
33  def example():
34      """Normalized illustrative station/readout, not a supplied official case.
35

```

```

36 Safe reception follows the analytic lens theorem; sampled ranking does not
37 certify continuous worst-case optimality. No prior distribution is assumed.
38 """
39 first = clip_bearing(initial_polygon(), (0.0, 0.0), 0.0)
40 source_samples = [
41     (r * math.cos(math.radians(phi)), r * math.sin(math.radians(phi)))
42     for r in range(25, 1501, 25)
43     for phi in (-1.0, 0.0, 1.0)
44 ]
45 output = []
46 choices = safe_candidates() + [{"point": (750.0, 0.0), "t_m": 750.0, "b_m": 0.0}]
47 for candidate in choices:
48     q = candidate["point"]
49     worst_radius = 0.0
50     for source in source_samples:
51         assert math.dist(q, source) <= max(1000, math.dist((0, 0), source)) + 1e-7
52         if math.dist(q, source) <= 5:
53             radius = 5.0
54         else:
55             truth = math.degrees(math.atan2(source[1] - q[1], source[0] - q[0]))
56             radius = 0.0
57             for error in (-1.0, 0.0, 1.0):
58                 reading = round((truth + error) % 360, 2) % 360
59                 poly = clip_bearing(first, q, reading)
60                 radius = max(radius, enclosing_circle(poly)[1])
61             worst_radius = max(worst_radius, radius)
62     output.append(
63         {
64             **candidate,
65             "sampled_worst_mec_radius_m": worst_radius,
66             "first_move_and_measure_s": math.hypot(*q) / 5 + 5,
67         }
68     )
69 best = min(
70     output,
71     key=lambda row: (
72         row["sampled_worst_mec_radius_m"],
73         row["first_move_and_measure_s"],
74     ),
75 )
76 result = {
77     "evidence": "illustrative_Q2_grid_score_not_global_optimum",
78     "first_station": [0, 0],
79     "first_reading_deg": 0,
80     "source_samples": len(source_samples),
81     "second_error_values_deg": [-1, 0, 1],
82     "best_sampled_geometry": best,
83     "collinear_control": output[-1],
84     "candidates": output,
85 }
86 Path("results").mkdir(exist_ok=True)
87 Path("results/second_point_example.json").write_text(
88     json.dumps(result, indent=2) + "\n"
89 )
90 print(json.dumps({k: v for k, v in result.items() if k != "candidates"}, indent=2))
91
92
93 if __name__ == "__main__":
94     example()

```

Listing 10: 恢复策略比较

```

1 import json
2 import statistics
3 from pathlib import Path
4
5 from environment import LocalSimulator

```

```

6 from planner import Planner
7
8 rows, summary = [], {}
9 for scenario in ("random", "minimum_radius", "outward_boundary", "clustered"):
10     for enabled in (False, True):
11         name = "recovery" if enabled else "two_flanks"
12         group = []
13         for seed in range(500000, 500100):
14             env = LocalSimulator(seed, 4, "smooth", scenario)
15             result = Planner(env, 4, strategy="integrated", loss_recovery=enabled).run()
16             actual = env.summary()
17             assert actual["fraction_cleared"] == 1
18             group.append(actual)
19             rows.append(**actual, "policy": name)
20             summary[f"{scenario}_{name}"] = {
21                 "runs": len(group),
22                 "mean_average_time_s": statistics.mean(r["average_time_s"] for r in group),
23                 "mean_failed_clears": statistics.mean(r["failed_clears"] for r in group),
24                 "worst_virtual_time_s": max(r["virtual_time_s"] for r in group),
25             }
26 result = {
27     "evidence": "synthetic_development_comparison_not_final_holdout",
28     "summary": summary,
29     "runs": rows,
30 }
31 Path("results/recovery_development.json").write_text(
32     json.dumps(result, indent=2) + "\n"
33 )
34 print(json.dumps(summary, indent=2))

```

Listing 11: HTTP 客户端

```

1 """Serial, append-only-logged HTTP adapter for an already-open simulator test.
2
3 This module does NOT authenticate, launch a GUI, or start a formal test. The user
4 must first start the intended test in the official GUI and wait for readiness.
5 Only explicit act calls cause simulator actions; close never sends /exit.
6
7 A new logical action receives a UUID. Transient retries preserve exactly the
8 same bytes, path, and request ID. Exhausted ambiguous actions fail closed: no
9 new action can be submitted on this client because the previous action may have
10 executed. Logs are ordinary plaintext observations, NOT official encrypted logs.
11 Real sleeps are used solely for short transport-retry backoff, never virtual time.
12 """
13
14 from __future__ import annotations
15
16 import http.client
17 import json
18 import math
19 import queue
20 import threading
21 import time
22 import unicodedata
23 import uuid
24 from pathlib import Path
25 from urllib.error import HTTPError, URLError
26 from urllib.parse import urlsplit
27 from urllib.request import HTTPRedirectHandler, ProxyHandler, Request, build_opener
28
29 from environment import Point, _action_args
30
31
32 class ClientError(RuntimeError):
33     """An action did not produce a verified accepted response."""
34
35

```

```

36 class RejectedActionError(ClientError):
37     def __init__(self, status: int, response: dict):
38         self.status, self.response = status, response
39         super().__init__(
40             f"Simulator rejected action: HTTP {status}, accepted={response.get('accepted')}!r}"
41         )
42
43
44 class AmbiguousActionError(ClientError):
45     """The action may have executed; consult the log and simulator GUI."""
46
47
48 class ClientProtocolError(ClientError):
49     pass
50
51
52 class DeadlineExceeded(ClientError):
53     pass
54
55
56 class _NoRedirect(HTTPRedirectHandler):
57     def redirect_request(self, req, fp, code, msg, headers, newurl):
58         # Never let urllib turn a POST into a GET or send identifiers elsewhere.
59         return None
60
61
62 def _number(value) -> bool:
63     return (
64         not isinstance(value, bool)
65         and isinstance(value, (int, float))
66         and math.isfinite(value)
67     )
68
69
70 def _unique_object(pairs):
71     result = {}
72     for key, value in pairs:
73         if key in result:
74             raise ValueError(f"Duplicate response key: {key}")
75         result[key] = value
76     return result
77
78
79 class HTTPClient:
80     """Official wire schema, no truth API, one in-flight logical action at a time.
81
82     Cached public position/radio_channel/virtual_time_s describe only confirmed
83     accepted actions. The real deadline uses /enter.remaining_real_duration_s,
84     conservatively subtracting all elapsed time since its first send, including
85     transport retries. Before entry, a bounded 20-second connection budget applies
86     because the actual GUI window deadline is not available through the API.
87     """
88
89     _MAX_ATTEMPTS = 4
90     _REQUEST_TIMEOUT_S = 5.0
91     _ACTION_RETRY_BUDGET_S = 20.0
92     _MAX_RESPONSE_BYTES = 65536
93     _TRANSIENT_HTTP = frozenset((429, 500, 502, 503, 504))
94
95     def __init__(self, base_url: str, robot_id: str, log_path: str):
96         parsed = urlsplit(base_url)
97         if (
98             parsed.scheme not in ("http", "https")
99             or not parsed.hostname
100             or parsed.path not in ("", "/")
101             or parsed.query
102             or parsed.fragment

```

```

103         or parsed.username is not None
104         or parsed.password is not None
105     ):
106         raise ValueError(
107             "base_url must be an HTTP(S) origin, without credentials/path/query"
108         )
109     # Force port validation before sending anything.
110     _ = parsed.port
111     if (
112         not isinstance(robot_id, str)
113         or not 1 <= len(robot_id.encode("utf-8")) <= 64
114     ):
115         raise ValueError("robot_id must contain 1..64 UTF-8 bytes")
116     if any(unicodedata.category(c) in ("Cc", "Cf") for c in robot_id):
117         raise ValueError("robot_id cannot contain control or format characters")
118     self._base_url, self._robot_id = base_url.rstrip("/"), robot_id
119     self._lock = threading.Lock()
120     self._opener = build_opener(ProxyHandler({}), _NoRedirect())
121     self._closed = False
122     self._uncertain = False
123     self._entered = self._exited = False
124     self._deadline: float | None = None
125     self._max_virtual_duration_s: float | None = None
126     self.position: Point = (0.0, 0.0)
127     self.radio_channel = 1
128     self.virtual_time_s = 0.0
129     self._log = Path(log_path).open("a", encoding="utf-8", buffering=1) # noqa: SIM115 - lifecycle closed
    by close()
130
131     @property
132     def remaining_real_duration_s(self) -> float | None:
133         """Locally conservative seconds left; unknown until accepted /enter."""
134         return (
135             None
136             if self._deadline is None
137             else max(0.0, self._deadline - time.monotonic())
138         )
139
140     def _record(self, event: dict):
141         self._log.write(
142             json.dumps(
143                 {"logged_at_ms": int(time.time() * 1000), **event},
144                 ensure_ascii=False,
145                 allow_nan=False,
146                 separators=(",", ":"),
147             )
148             + "\n"
149         )
150         self._log.flush()
151
152     def _decode(self, raw: bytes) -> dict:
153         if len(raw) > self._MAX_RESPONSE_BYTES:
154             raise ClientProtocolError("Response exceeds bounded JSON body size")
155         try:
156             response = json.loads(raw.decode("utf-8"), object_pairs_hook=_unique_object)
157         except (UnicodeDecodeError, ValueError) as exc:
158             raise ClientProtocolError(
159                 "Response is not valid unambiguous UTF-8 JSON"
160             ) from exc
161         if not isinstance(response, dict) or type(response.get("accepted")) is not bool:
162             raise ClientProtocolError("Response lacks a boolean accepted field")
163         if (
164             not _number(response.get("real_timestamp_ms"))
165             or not _number(response.get("virtual_time_s"))
166             or response["virtual_time_s"] < 0
167         ):
168             raise ClientProtocolError("Response lacks valid numeric timestamps")

```

```

169         return response
170
171     def _validate_accepted(self, path: str, response: dict):
172         virtual_time = response["virtual_time_s"]
173         if path == "/enter":
174             remaining = response.get("remaining_real_duration_s")
175             if (
176                 not _number(remaining)
177                 or not 0 <= remaining <= 1200
178                 or int(remaining) != remaining
179             ):
180                 raise ClientProtocolError("Invalid actual remaining real duration")
181             if (
182                 not _number(response.get("max_virtual_duration_s"))
183                 or response["max_virtual_duration_s"] <= 0
184                 or not _number(response.get("max_real_duration_s"))
185                 or response["max_real_duration_s"] <= 0
186                 or virtual_time != 0
187             ):
188                 raise ClientProtocolError(
189                     "Invalid accepted entry limits or initial time"
190                 )
191         elif virtual_time < self.virtual_time_s:
192             raise ClientProtocolError("Accepted action moved virtual time backwards")
193         if path == "/measure":
194             result = response.get("measure_result")
195             if result not in ("near", "no_signal", "direction"):
196                 raise ClientProtocolError("Unknown measure result")
197             if result == "direction":
198                 angle = response.get("svd_deg")
199                 if not _number(angle) or not 0 <= angle < 360:
200                     raise ClientProtocolError("Invalid direction angle")
201             elif "svd_deg" in response:
202                 raise ClientProtocolError("Bearing supplied without direction result")
203         elif path == "/clear" and response.get("clear_result") not in (
204             "success",
205             "no_target_in_range",
206         ):
207             raise ClientProtocolError("Unknown clear result")
208         elif path == "/exit" and response.get("exit_reason") != "user_exit":
209             raise ClientProtocolError("Unexpected successful exit reason")
210
211     def _commit(
212         self,
213         path: str,
214         position: Point | None,
215         channel: int | None,
216         response: dict,
217         first_send: float,
218     ):
219         if path == "/enter":
220             self._entered = True
221             self.position, self.radio_channel = (0.0, 0.0), 1
222             self._deadline = first_send + response["remaining_real_duration_s"]
223             self._max_virtual_duration_s = response["max_virtual_duration_s"]
224         elif path == "/exit":
225             self._exited = True
226         else:
227             self.position = position
228             if path == "/measure":
229                 self.radio_channel = channel
230             self.virtual_time_s = response["virtual_time_s"]
231             self._uncertain = False
232
233     def _exchange(self, request: Request, deadline: float) -> tuple[int, bytes]:
234         """Bound connection, headers and body together, not just idle sockets.
235

```

```

236     On expiry the daemon may finish the same in-flight request, but cannot
237     mutate client state or send another action. act remains fail-closed.
238     """
239     completed = queue.Queue(maxsize=1)
240
241     def receive():
242         try:
243             available = deadline - time.monotonic()
244             if available <= 0:
245                 raise TimeoutError("Absolute HTTP deadline elapsed")
246             try:
247                 stream = self._opener.open(
248                     request, timeout=min(self._REQUEST_TIMEOUT_S, available)
249                 )
250             except HTTPError as exc:
251                 stream = exc
252             with stream:
253                 status = stream.code
254                 expected_length = stream.headers.get("Content-Length")
255                 if expected_length is not None:
256                     try:
257                         expected_length = int(expected_length)
258                     except ValueError as exc:
259                         raise ClientProtocolError("Invalid Content-Length") from exc
260                     if not 0 <= expected_length <= self._MAX_RESPONSE_BYTES:
261                         raise ClientProtocolError(
262                             "Response exceeds bounded JSON body size"
263                         )
264                     raw = stream.read(self._MAX_RESPONSE_BYTES + 1)
265                     if expected_length is not None and len(raw) < expected_length:
266                         raise http.client.IncompleteRead(
267                             raw, expected_length - len(raw)
268                         )
269                     completed.put((True, (status, raw)))
270         except (
271             ClientError,
272             OSError,
273             ValueError,
274             TypeError,
275             TimeoutError,
276             http.client.HTTPException,
277         ) as exc:
278             completed.put((False, exc))
279
280     threading.Thread(target=receive, daemon=True, name="simulator-response").start()
281     try:
282         succeeded, value = completed.get(
283             timeout=max(0.0, deadline - time.monotonic())
284         )
285     except queue.Empty as exc:
286         raise TimeoutError(
287             "Absolute HTTP deadline elapsed; outcome remains unknown"
288         ) from exc
289     if not succeeded:
290         raise value
291     return value
292
293     def act(
294         self, path: str, position: Point | None = None, channel: int | None = None
295     ) -> dict:
296         position, channel = _action_args(path, position, channel)
297         with self._lock:
298             if self._closed:
299                 raise ClientError("Client is closed")
300             if self._uncertain:
301                 raise AmbiguousActionError(
302                     "Previous outcome is unresolved; no different action may be sent"

```

```

303         )
304     if self._exited:
305         raise ClientError("Session already exited; do not query /exit again")
306     if self._deadline is not None and time.monotonic() >= self._deadline:
307         raise DeadlineExceeded(
308             "Actual remaining real duration has elapsed; interface may be closed"
309         )
310     if (
311         self._max_virtual_duration_s is not None
312         and self.virtual_time_s >= self._max_virtual_duration_s
313     ):
314         raise DeadlineExceeded(
315             "Virtual deadline reached; no post-timeout /exit query is legal"
316         )
317     if path == "/enter" and self._entered:
318         raise ClientError("Cannot enter the same test twice")
319     if path != "/enter" and not self._entered:
320         raise ClientError(
321             "Explicit successful /enter is required before other actions"
322         )
323     request_id = uuid.uuid4().hex
324     payload = {
325         "arena_id": "default",
326         "robot_id": self._robot_id,
327         "request_id": request_id,
328     }
329     if position is not None:
330         payload.update(
331             position={"x": position[0], "y": position[1]}, channel=channel
332         )
333     body = json.dumps(
334         payload, ensure_ascii=False, allow_nan=False, separators=(",", ":")
335     ).encode("utf-8")
336     first_send = time.monotonic()
337     stop = first_send + self._ACTION_RETRY_BUDGET_S
338     if self._deadline is not None:
339         stop = min(stop, self._deadline)
340     last_error = "No response"
341     for attempt in range(1, self._MAX_ATTEMPTS + 1):
342         available = stop - time.monotonic()
343         if available <= 0:
344             break
345         self._record(
346             {
347                 "event": "request",
348                 "path": path,
349                 "request_id": request_id,
350                 "attempt": attempt,
351                 "body": payload,
352             }
353         )
354         request = Request(
355             self._base_url + path,
356             data=body,
357             headers={"Content-Type": "application/json"},
358             method="POST",
359         )
360         # From this point until a valid outcome, execution is uncertain.
361         self._uncertain = True
362         try:
363             status, raw = self._exchange(request, stop)
364             self._record(
365                 {
366                     "event": "response",
367                     "path": path,
368                     "request_id": request_id,
369                     "attempt": attempt,

```

```

370         "http_status": status,
371         "body_utf8": raw.decode("utf-8", errors="replace"),
372     }
373 )
374 except (URLError, OSError, http.client.HTTPException) as exc:
375     # Includes connection refusal, broken connections, timeouts,
376     # truncated HTTP bodies. No state is inferred from any of these.
377     last_error = f"{type(exc).__name__}: {exc}"
378     self._record(
379         {
380             "event": "transport_error",
381             "path": path,
382             "request_id": request_id,
383             "attempt": attempt,
384             "error": last_error,
385         }
386     )
387 else:
388     if status in self._TRANSIENT_HTTP:
389         last_error = f"Transient HTTP {status}"
390     else:
391         response = self._decode(raw)
392         if status != 200 or response["accepted"] is not True:
393             if response["accepted"] is True:
394                 raise ClientProtocolError(
395                     "accepted=true with non-200 HTTP status"
396                 )
397             self._uncertain = False
398             raise RejectedActionError(status, response)
399         self._validate_accepted(path, response)
400         radio_before = self.radio_channel
401         distance = (
402             math.dist(self.position, position)
403             if position is not None
404             else 0.0
405         )
406         switch = int(path == "/measure" and channel != radio_before)
407         self._record(
408             {
409                 "event": "accepted",
410                 "path": path,
411                 "request_id": request_id,
412                 "distance_m": distance,
413                 "radio_channel_before": radio_before,
414                 "radio_channel_after": channel
415                 if path == "/measure"
416                 else radio_before,
417                 "switch_time_s": switch,
418                 "action_virtual_time_s": response["virtual_time_s"]
419                 - self.virtual_time_s,
420             }
421         )
422         self._commit(path, position, channel, response, first_send)
423         return response
424     if attempt < self._MAX_ATTEMPTS:
425         delay = min(
426             0.2 * 2 ** (attempt - 1), max(0.0, stop - time.monotonic())
427         )
428         if delay > 0:
429             time.sleep(delay)
430         raise AmbiguousActionError(
431             f"Action {request_id} has no confirmed outcome after bounded retries: {last_error}"
432         )
433
434 def close(self):
435     """Close only this adapter's log. Never start/end a simulator session."""
436     with self._lock:

```

```

437         if not self._closed:
438             self._log.close()
439             self._closed = True

```

Listing 12: HTTP 验证

```

1  """HTTP fault-injection regression. Local test server, never the official simulator.
2
3  Start --server with hub; run without --server as a finite client verification.
4  The server executes the first measure, truncates its HTTP body, then answers its
5  same-ID retry from cache. Passing requires exactly-once virtual-time effects.
6  """
7
8  from __future__ import annotations
9
10 import argparse
11 import json
12 import tempfile
13 import time
14 from http.server import BaseHTTPRequestHandler, HTTPServer
15 from pathlib import Path
16
17 from client import AmbiguousActionError, HTTPClient
18 from environment import LocalSimulator
19
20
21 def serve(port, case):
22     environment = LocalSimulator(20260910)
23     cache = {}
24     truncated = False
25
26     class Handler(BaseHTTPRequestHandler):
27         def log_message(self, format, *args):
28             return
29
30         def do_POST(self):
31             nonlocal truncated
32             raw = self.rfile.read(int(self.headers["Content-Length"]))
33             body = json.loads(raw)
34             identity = body["request_id"]
35             key = (self.path, raw)
36             if identity in cache:
37                 old_key, response = cache[identity]
38                 if key != old_key:
39                     self.send_error(409)
40                     return
41             else:
42                 point = body.get("position")
43                 point = None if point is None else (point["x"], point["y"])
44                 response = environment.act(self.path, point, body.get("channel"))
45                 cache[identity] = (key, response)
46             encoded = json.dumps(response).encode()
47             self.send_response(200)
48             self.send_header("Content-Type", "application/json")
49             self.send_header("Content-Length", str(len(encoded)))
50             self.end_headers()
51             if self.path == "/measure" and not truncated:
52                 truncated = True
53                 if case == "deadline":
54                     size = max(1, len(encoded) // 8)
55                     for start in range(0, len(encoded), size):
56                         self.wfile.write(encoded[start : start + size])
57                         self.wfile.flush()
58                         time.sleep(0.3)
59                 else:
60                     self.wfile.write(encoded[: len(encoded) // 2])
61                     self.wfile.flush()

```

```

62         self.close_connection = True
63     else:
64         self.wfile.write(encoded)
65
66 server = HTTPServer(("127.0.0.1", port), Handler)
67 print(f"HTTP fault fixture ready on {port}", flush=True)
68 server.serve_forever()
69
70
71 def verify(port, case):
72     Path("results").mkdir(exist_ok=True)
73     with tempfile.TemporaryDirectory(prefix="b-http-check-") as directory:
74         path = Path(directory) / "requests.jsonl"
75         client = HTTPClient(f"http://127.0.0.1:{port}", "local-regression", str(path))
76         try:
77             client.act("/enter")
78             if case == "deadline":
79                 client._ACTION_RETRY_BUDGET_S = 0.5
80                 started = time.monotonic()
81                 try:
82                     client.act("/measure", (300.0, 400.0), 1)
83                 except AmbiguousActionError:
84                     elapsed = time.monotonic() - started
85                 else:
86                     raise AssertionError("Slow response bypassed the absolute deadline")
87                 assert elapsed < 1.5, elapsed
88                 assert client.virtual_time_s == 0
89                 try:
90                     client.act("/measure", (0.0, 0.0), 2)
91                 except AmbiguousActionError:
92                     pass
93             else:
94                 raise AssertionError(
95                     "Different action sent after an ambiguous timeout"
96                 )
97             result = {
98                 "evidence": "local_HTTP_fault_fixture_not_official",
99                 "absolute_deadline_fail_closed": True,
100                 "deadline_s": 0.5,
101                 "observed_elapsed_s": elapsed,
102                 "no_unconfirmed_state_advance": True,
103             }
104             output = Path("results/http_deadline_verification.json")
105         else:
106             assert (
107                 client.act("/measure", (300.0, 400.0), 1)["virtual_time_s"] == 105
108             )
109             assert (
110                 client.act("/measure", (300.0, 400.0), 2)["virtual_time_s"] == 111
111             )
112             clear = client.act("/clear", (300.0, 0.0), 3)
113             expected = 196 if clear["clear_result"] == "success" else 194
114             assert clear["virtual_time_s"] == expected
115             assert client.radio_channel == 2
116             assert (
117                 client.act("/measure", (300.0, 0.0), 2)["virtual_time_s"]
118                 == expected + 5
119             )
120             assert client.act("/exit")["virtual_time_s"] == expected + 5
121             result = {
122                 "evidence": "local_HTTP_fault_fixture_not_official",
123                 "truncated_response_recovered": True,
124                 "retry_reused_identical_request": True,
125                 "virtual_time_exactly_once": True,
126                 "clear_kept_radio_channel": True,
127                 "final_virtual_time_s": expected + 5,
128             }

```

```

129         output = Path("results/http_verification.json")
130     finally:
131         client.close()
132     events = [json.loads(line) for line in path.read_text().splitlines()]
133     requests = [
134         row
135         for row in events
136         if row["event"] == "request" and row["path"] == "/measure"
137     ]
138     if case == "deadline":
139         assert len(requests) == 1
140     else:
141         assert requests[0]["request_id"] == requests[1]["request_id"]
142         assert requests[0]["body"] == requests[1]["body"]
143     output.write_text(json.dumps(result, indent=2) + "\n")
144     output.with_suffix(".jsonl").write_text(path.read_text())
145     print(json.dumps(result, indent=2))
146
147
148 if __name__ == "__main__":
149     parser = argparse.ArgumentParser()
150     parser.add_argument("--server", action="store_true")
151     parser.add_argument("--port", type=int, default=12026)
152     parser.add_argument(
153         "--case", choices=("truncated", "deadline"), default="truncated"
154     )
155     arguments = parser.parse_args()
156     serve(arguments.port, arguments.case) if arguments.server else verify(
157         arguments.port, arguments.case
158     )

```

Listing 13: 官方运行入口（仅获授权后使用）

```

1  """Connect the policy to an already started OFFICIAL simulator session.
2
3  Never starts a formal test or supplies team credentials automatically. Use the
4  real GUI to choose the intended practice/formal module, then invoke this CLI.
5  Plaintext request logs include robot_id and are private working files: do not
6  put them unredacted in anonymous submission. Official encrypted logs are exported
7  separately from the simulator with unchanged filenames.
8  """
9
10 from __future__ import annotations
11
12 import argparse
13 import json
14 from pathlib import Path
15 from time import monotonic
16
17 from client import HTTPClient
18 from field_policy import FieldPlanner
19 from planner import Planner
20
21
22 def main():
23     parser = argparse.ArgumentParser()
24     parser.add_argument("--robot-id", required=True)
25     parser.add_argument("--problem", required=True, type=int, choices=(3, 4))
26     parser.add_argument("--base-url", default="http://127.0.0.1:2026")
27     parser.add_argument(
28         "--strategy",
29         choices=("field", "refined"),
30         default=None,
31         help="默认Q3使用refined、Q4使用field; 可显式指定任一策略",
32     )
33     parser.add_argument("--output-dir", type=Path, required=True)
34     args = parser.parse_args()

```

```

35     if args.output_dir.exists():
36         parser.error("Output directory must be new to keep separate session evidence")
37     args.output_dir.mkdir(parents=True)
38     client = HTTPClient(
39         args.base_url, args.robot_id, str(args.output_dir / "private_requests.jsonl")
40     )
41     started = monotonic()
42     try:
43         effective_strategy = args.strategy if args.strategy is not None else ("refined" if args.problem == 3
44                                     else "field")
45         planner = (
46             FieldPlanner(client, problem=args.problem)
47             if effective_strategy == "field"
48             else Planner(client, problem=args.problem, strategy=effective_strategy)
49         )
50         result = planner.run()
51         result.update(
52             evidence="HTTP_observations_require_simulator_GUI_provenance_not_encrypted_export",
53             local_wall_duration_s=monotonic() - started,
54             case_code="Obtain actual case code from simulator GUI; not returned by HTTP",
55             total_source_count="Not disclosed by official formal interface",
56         )
57         (args.output_dir / "observed_result.json").write_text(
58             json.dumps(result, ensure_ascii=False, indent=2) + "\n"
59         )
60         print(json.dumps(result, ensure_ascii=False, indent=2))
61     finally:
62         client.close()
63
64 if __name__ == "__main__":
65     main()

```

Listing 14: 数据驱动图表与轨迹生成

```

1  """Deterministic local-evidence assets; run with conda run -n py314 python make_assets.py.
2
3  No official service is accessed. Replay logs contain public observations, not source
4  coordinates. Wall-clock durations in raw replay evidence are inherently variable;
5  figures, table values, and virtual-time paths do not depend on those durations.
6  """
7
8  from __future__ import annotations
9
10 import hashlib
11 import json
12 import math
13 import os
14 import statistics
15 import tempfile
16 from pathlib import Path
17
18 import matplotlib
19
20 matplotlib.use("Agg")
21 import matplotlib.pyplot as plt
22 import numpy as np
23 from matplotlib.patches import Circle, Polygon
24
25 from coverage import directional_waypoints, omni_waypoints
26 from environment import LocalSimulator
27 from geometry import BEARING_ERROR_DEG, clip_bearing, enclosing_circle, initial_polygon
28 from planner import Planner
29
30 ROOT = Path(__file__).resolve().parent
31 GENERATED = ROOT / "report" / "generated"
32 FIGURES = ROOT / "report" / "figures"

```

```

33 POLICIES = ("baseline", "batched", "integrated")
34 SCENARIOS = ("random", "minimum_radius", "outward_boundary", "clustered")
35 SCENARIO_LABELS = ("Random", "Min. radius", "Outward boundary", "Clustered")
36 COLORS = ("#0072B2", "#E69F00", "#009E73")
37 WIDTH = 16 / 2.54
38
39
40 def require(condition, message):
41     if not condition:
42         raise ValueError(message)
43
44
45 def atomic_bytes(path, content):
46     """Replace only our named outputs; never remove/rewrite source evidence."""
47     require(path.parent in (GENERATED, FIGURES), "Output outside owned directories")
48     path.parent.mkdir(parents=True, exist_ok=True)
49     fd, temporary = tempfile.mkstemp(prefix="." + path.name + ".", dir=path.parent)
50     try:
51         with os.fdopen(fd, "wb") as stream:
52             stream.write(content)
53             os.replace(temporary, path)
54     finally:
55         Path(temporary).unlink(missing_ok=True)
56
57
58 def write_json(name, value):
59     atomic_bytes(
60         GENERATED / name,
61         (
62             json.dumps(value, ensure_ascii=False, indent=2, allow_nan=False) + "\n"
63         ).encode("utf-8"),
64     )
65
66
67 def save_figure(fig, name):
68     # Fixed physical width, not bbox_inches=tight (which changes final font scale).
69     from io import BytesIO
70
71     buffer = BytesIO()
72     fig.savefig(
73         buffer,
74         format="pdf",
75         metadata={"CreationDate": None, "ModDate": None, "Creator": "make_assets.py"},
76     )
77     atomic_bytes(FIGURES / name, buffer.getvalue())
78     plt.close(fig)
79
80
81 def tex_escape(value):
82     return str(value).replace("_", r"\_").replace("%", r"\%")
83
84
85 def table(name, headers, rows, alignment=None):
86     alignment = alignment or "l" + "r" * (len(headers) - 1)
87     lines = [
88         r"\begin{tabular}{%s}" % alignment + "}",
89         r"\toprule",
90         " & ".join(headers) + r" \\",
91         r"\midrule",
92     ]
93     for row in rows:
94         require(len(row) == len(headers), "Ragged table")
95         lines.append(" & ".join(str(v) for v in row) + r" \\\n")
96     lines += [r"\bottomrule", r"\end{tabular}"]
97     atomic_bytes(GENERATED / name, ("\\n".join(lines) + "\\n").encode("utf-8"))
98
99

```

```

100 def number(value):
101     require(
102         isinstance(value, (int, float)) and math.isfinite(value), "Nonfinite metric"
103     )
104     return f"{value:.2f}"
105
106
107 def metrics(rows):
108     values = sorted(row["average_time_s"] for row in rows)
109     require(bool(values), "Empty evidence group")
110     return {
111         "cases": len(rows),
112         "all_cleared_cases": sum(r["fraction_cleared"] == 1 for r in rows),
113         "mean_average_time_s": statistics.mean(values),
114         "median_average_time_s": statistics.median(values),
115         "p90_average_time_s": values[math.ceil(0.9 * len(values)) - 1],
116         "mean_failed_clears": statistics.mean(r["failed_clears"] for r in rows),
117     }
118
119
120 def validate_group(rows, summary, name):
121     actual = metrics(rows)
122     for key, value in actual.items():
123         require(
124             key in summary
125             and math.isclose(value, summary[key], rel_tol=1e-10, abs_tol=1e-8),
126             f"{name}: summary mismatch for {key}",
127         )
128     return rows
129
130
131 def load_inputs():
132     names = (
133         "final_experiments.json",
134         "geometry_verification.json",
135         "http_verification.json",
136         "second_point_example.json",
137     )
138     data, hashes = {}, {}
139     for name in names:
140         raw = (ROOT / "results" / name).read_bytes()
141         data[name] = json.loads(raw)
142         hashes["results/" + name] = hashlib.sha256(raw).hexdigest()
143     final = data[names[0]]
144     require(
145         final["evidence"] == "local_synthetic_not_official", "Not synthetic evidence"
146     )
147     require(final["total_runs"] == len(final["runs"]), "Run denominator mismatch")
148     for row in final["runs"]:
149         require(
150             row["evidence"] == "local_synthetic_not_official"
151             and row["fraction_cleared"] == 1,
152             "Incomplete or wrongly attributed run",
153         )
154         require(row["n_sources"] == row["n_cleared"] > 0, "Invalid clearing count")
155         require(
156             math.isclose(
157                 row["average_time_s"],
158                 row["virtual_time_s"] / row["n_sources"],
159                 rel_tol=1e-10,
160             ),
161             "Metric is not per-world T/N",
162         )
163     require(row["timing_independently_verified"] is True, "Missing timing evidence")
164     require(row["certificate_complete"] is True, "Missing complete certificate")
165     require(row["loss_recovery"] is (row["problem"] == 4 and row.get("loss_recovery_requested", True)),
166             "Effective recovery mismatch")

```

```

167 main, recovery = {}, {}
168 n = final["paired_random_cases_per_problem"]
169 for problem in (3, 4):
170     for strategy in POLICIES:
171         key = f"Q{problem}_{strategy}"
172         rows = sorted(
173             (
174                 r
175                 for r in final["runs"]
176                 if r["problem"] == problem
177                 and r["strategy"] == strategy
178                 and 600000 <= r["seed"] < 600000 + n
179             ),
180             key=lambda r: r["seed"],
181         )
182         require(
183             [r["seed"] for r in rows] == list(range(600000, 600000 + n)),
184             "Missing/duplicate paired seed",
185         )
186         main[key] = validate_group(rows, final["summary"][key], key)
187         paired = final["paired_comparison"][f"Q{problem}"]
188         saved = statistics.mean(
189             a["average_time_s"] - b["average_time_s"]
190             for a, b in zip(
191                 main[f"Q{problem}_baseline"], main[f"Q{problem}_integrated"]
192             )
193         )
194         require(
195             paired["paired_cases"] == n
196             and math.isclose(saved, paired["mean_saved_s_per_source"], rel_tol=1e-10),
197             "Pairing mismatch",
198         )
199         require(
200             math.isclose(
201                 paired["mean_time_reduction_pct"],
202                 100
203                 * saved
204                 / final["summary"][f"Q{problem}_baseline"]["mean_average_time_s"],
205                 rel_tol=1e-10,
206             ),
207             "Gain mismatch",
208         )
209         for scenario in SCENARIOS[1:]:
210             for mode in ("smooth", "extreme", "iid_location"):
211                 key = f"Q{problem}_{scenario}_{mode}"
212                 rows = [
213                     r
214                     for r in final["runs"]
215                     if r["problem"] == problem
216                     and r["scenario"] == scenario
217                     and r["error_mode"] == mode
218                     and 700000 <= r["seed"] < 700020
219                 ]
220                 validate_group(rows, final["stress"][key], key)
221         for scale in (0.12, 0.22, 0.40):
222             key = f"Q{problem}_probe_{scale}"
223             rows = [
224                 r
225                 for r in final["runs"]
226                 if r["problem"] == problem
227                 and r["probe_scale"] == scale
228                 and 800000 <= r["seed"] < 800030
229             ]
230             validate_group(rows, final["sensitivity"][key], key)
231         for spacing in (900.0, 950.0, 990.0):
232             key = f"Q4_spacing_{spacing}"
233             rows = [

```

```

234         r
235         for r in final["runs"]
236         if r["problem"] == 4
237         and r["spacing_m"] == spacing
238         and 900000 <= r["seed"] < 900030
239     ]
240     validate_group(rows, final["sensitivity"][key], key)
241 for scenario in SCENARIOS:
242     for enabled in (False, True):
243         key = f"{scenario}_recovery_{enabled}"
244         rows = sorted(
245             (
246                 r
247                 for r in final["runs"]
248                 if r["problem"] == 4
249                 and r["scenario"] == scenario
250                 and r["loss_recovery"] is enabled
251                 and 610000 <= r["seed"] < 610100
252             ),
253             key=lambda r: r["seed"],
254         )
255         require(
256             [r["seed"] for r in rows] == list(range(610000, 610100)),
257             "Recovery pairing mismatch",
258         )
259         recovery[key] = validate_group(rows, final["recovery_ablation"][key], key)
260 geometry, http, second = (data[name] for name in names[1:])
261 require(
262     geometry["evidence"]
263     == "independent_numerical_checks_not_a_substitute_for_analytic_proofs",
264     "Geometry evidence mismatch",
265 )
266 require(
267     http["evidence"] == "local_HTTP_fault_fixture_not_official",
268     "HTTP evidence mismatch",
269 )
270 require(
271     second["evidence"] == "illustrative_Q2_grid_score_not_global_optimum",
272     "Q2 evidence mismatch",
273 )
274 for key in (
275     "truncated_response_recovered",
276     "retry_reused_identical_request",
277     "virtual_time_exactly_once",
278     "clear_kept_radio_channel",
279 ):
280     require(http[key] is True, f"Failed fixture: {key}")
281 return final, geometry, http, second, main, recovery, hashes
282
283
284 def generate_tables(final, geometry, http):
285     summary = final["summary"]
286     macros = {"ExperimentRuns": str(final["total_runs"])}
287     for problem, word in ((3, "Three"), (4, "Four")):
288         macros[f"Q{word}Time"] = number(
289             summary[f"Q{problem}_integrated"]["mean_average_time_s"]
290         )
291         macros[f"Q{word}Baseline"] = number(
292             summary[f"Q{problem}_baseline"]["mean_average_time_s"]
293         )
294         # Numeric macro: paper supplies its own percent sign and unit.
295         macros[f"Q{word}Gain"] = number(
296             final["paired_comparison"][f"Q{problem}"]["mean_time_reduction_pct"]
297         )
298     atomic_bytes(
299         GENERATED / "numbers.tex",
300         (

```

```

301         "\n".join(
302             r"\newcommand{" + "\\" + k + "}" + v + "}" for k, v in macros.items()
303         )
304         + "\n"
305     ).encode(),
306 )
307 rows = []
308 for problem in (3, 4):
309     for policy in POLICIES:
310         s = summary[f"Q{problem}_{policy}"]
311         rows.append(
312             (
313                 f"Q{problem} {policy}",
314                 number(s["mean_average_time_s"]),
315                 number(s["median_average_time_s"]),
316                 number(s["p90_average_time_s"]),
317                 f"{s['all_cleared_cases']}/{s['cases']}",
318             )
319         )
320 table(
321     "comparison_table.tex",
322     ("Policy", r"Mean  $\$/N$  (s)", "Median (s)", " $\$/p_{90}$  (s)", "Complete"),
323     rows,
324 )
325 rows = []
326 for scenario, label in zip(SCENARIOS[1:], SCENARIO_LABELS[1:]):
327     for mode, mode_label in (
328         ("smooth", "Smooth"),
329         ("extreme", r" $\$/pmi^{\circ}$  hash"),
330         ("iid_location", "Uniform hash"),
331     ):
332         s3, s4 = (final["stress"][f"Q{p}_{scenario}_{mode}"] for p in (3, 4))
333         require(s3["cases"] == s4["cases"], "Stress denominator mismatch")
334         rows.append(
335             (
336                 label,
337                 mode_label,
338                 number(s3["mean_average_time_s"]),
339                 number(s4["mean_average_time_s"]),
340                 str(s3["cases"]),
341             )
342         )
343 table(
344     "stress_table.tex",
345     ("Geometry", "Error field", "Q3 mean (s)", "Q4 mean (s)", " $\$/n/Q$ "),
346     rows,
347     "llrrr",
348 )
349 rows = []
350 for key, s in final["sensitivity"].items():
351     problem, parameter, value = key.split("_")
352     label = (
353         r" $\$/lambda$ =" + value + " $\$/$ "
354         if parameter == "probe"
355         else " $\$/s$ =" + f"{float(value):.0f}" + r" $\$, \mathrm{m}$ "
356     )
357     rows.append(
358         (
359             problem,
360             label,
361             number(s["mean_average_time_s"]),
362             number(s["p90_average_time_s"]),
363             str(s["cases"]),
364         )
365     )
366 table(
367     "sensitivity_table.tex",

```

```

368     ("Problem", "Setting", "Mean (s)", "$p_{90}$ (s)", "$n$"),
369     rows,
370     "llrrr",
371 )
372 rows = []
373 for scenario, label in zip(SCENARIOS, SCENARIO_LABELS):
374     off, on = (
375         final["recovery_ablation"][f"{scenario}_recovery_{enabled}"]
376         for enabled in (False, True)
377     )
378     rows.append(
379         (
380             label,
381             number(off["mean_average_time_s"]),
382             number(on["mean_average_time_s"]),
383             number(off["mean_failed_clears"]),
384             number(on["mean_failed_clears"]),
385             str(on["cases"]),
386         )
387     )
388     table(
389         "recovery_table.tex",
390         ("Scenario", "$T/N$ off", "$T/N$ on", "Fails off", "Fails on", "Pairs"),
391         rows,
392     )
393     rows = [
394         (
395             "MEC reference",
396             str(geometry["mec_reference_cases"]),
397             f"{geometry['maximum_mec_radius_error_m']:.2e} m",
398         ),
399         (
400             "Bearing containment",
401             str(geometry["containment_cases"]),
402             f"{geometry['bearings_per_case']} readings/case",
403         ),
404         (
405             "Optical cover samples",
406             str(geometry["optical_interior_samples"]),
407             "Contained",
408         ),
409         (
410             "Discovery samples",
411             str(geometry["coverage_source_samples"]),
412             "Both geometries",
413         ),
414         (
415             "Triple-lens samples",
416             str(geometry["triple_lens_samples"]),
417             "Reception checked",
418         ),
419         ("Local HTTP fixture", "1", "Four checks passed"),
420     ]
421     table(
422         "verification_table.tex",
423         ("Numerical / local check", "Cases / points", "Observed result"),
424         rows,
425         "lrl",
426     )
427
428
429 def spatial_axis(ax, limit, unit="km"):
430     ax.set(
431         xlim=(-limit, limit),
432         ylim=(-limit, limit),
433         xlabel=f"x ({unit})",
434         ylabel=f"y ({unit})",

```

```

435         aspect="equal",
436     )
437     ax.grid(alpha=0.18)
438
439
440 def coverage_figure(geometry):
441     cert = geometry["coverage_certificate"]
442     omni, lattice = np.array(omni_waypoints()), np.array(directional_waypoints())
443     require(
444         len(omni) == cert["omni"]["waypoint_count"]
445         and len(lattice) == cert["directional"]["waypoint_count"],
446         "Coverage count mismatch",
447     )
448     fig, axes = plt.subplots(1, 2, figsize=(WIDTH, 3.7))
449     fig.subplots_adjust(left=0.08, right=0.98, bottom=0.30, top=0.88, wspace=0.4)
450     for ax in axes:
451         spatial_axis(ax, 3.0)
452         ax.add_patch(
453             Circle(
454                 (0, 0), cert["arena_radius_m"] / 1000, fill=False, color="black", lw=1.3
455             )
456         )
457     for point in omni / 1000:
458         axes[0].add_patch(
459             Circle(
460                 point,
461                 cert["omni"]["cover_radius_m"] / 1000,
462                 color=COLORS[0],
463                 fill=False,
464                 alpha=0.6,
465                 lw=0.8,
466             )
467         )
468     axes[0].scatter(
469         *(omni / 1000).T, s=20, color=COLORS[0], label=f"{len(omni)} detectors"
470     )
471     inside = np.linalg.norm(lattice, axis=1) <= cert["arena_radius_m"]
472     require(
473         int((~inside).sum()) == cert["directional"]["outside_arena_count"],
474         "Outside-node count mismatch",
475     )
476     # Draw only nearest-neighbour lattice edges, including exterior nodes.
477     for i, p in enumerate(lattice):
478         for q in lattice[:i]:
479             if math.isclose(
480                 math.dist(p, q), cert["directional"]["spacing_m"], abs_tol=1e-6
481             ):
482                 axes[1].plot(
483                     [p[0] / 1000, q[0] / 1000],
484                     [p[1] / 1000, q[1] / 1000],
485                     color="0.78",
486                     lw=0.6,
487                     zorder=0,
488                 )
489     axes[1].scatter(
490         *(lattice[inside] / 1000).T,
491         color=COLORS[0],
492         s=22,
493         label=f"Inside: {int(inside.sum())}",
494     )
495     axes[1].scatter(
496         *(lattice[~inside] / 1000).T,
497         color="#D55E00",
498         marker="^",
499         s=30,
500         label=f"Outside: {int((~inside).sum())}",
501     )

```

```

502 axes[0].set_title("Q3: 900 m covering disks")
503 axes[1].set_title(f"Q4: {len(lattice)} lattice nodes")
504 for ax in axes:
505     box = ax.get_position()
506     ax.legend(loc="lower center", bbox_to_anchor=((box.x0 + box.x1) / 2, 0.01),
507             bbox_transform=fig.transFigure, frameon=False)
508 save_figure(fig, "coverage.pdf")
509
510
511 def geometry_figure(geometry):
512     example = geometry["realizable_counterexample"]
513     polygon = initial_polygon()
514     for station, bearing in zip(example["stations"], example["bearings_deg"]):
515         polygon = clip_bearing(polygon, tuple(station), bearing, error_deg=1.0)
516     center, radius = enclosing_circle(polygon)
517     require(
518         math.isclose(radius, example["mec_radius_m"], abs_tol=1e-6),
519         "Triangle reconstruction mismatch",
520     )
521     a, b = max(
522         ((a, b) for a in polygon for b in polygon), key=lambda pair: math.dist(*pair)
523     )
524     midpoint = tuple((x + y) / 2 for x, y in zip(a, b))
525     fig, ax = plt.subplots(figsize=(WIDTH, 3.6), layout="constrained")
526     ax.add_patch(Polygon(polygon, facecolor="#56B4E9", alpha=0.35, edgecolor=COLORS[0]))
527     ax.plot(
528         *zip(*(polygon + [polygon[0]])),
529         color=COLORS[0],
530         label=f"Feasible region: D={example['diameter_m']:.0f} m",
531     )
532     ax.add_patch(
533         Circle(
534             midpoint,
535             example["diameter_m"] / 2,
536             fill=False,
537             color="#D55E00",
538             ls="--",
539             label=f"Diameter circle: {example['diameter_m'] / 2:.2f} m",
540         )
541     )
542     ax.add_patch(
543         Circle(
544             center,
545             radius,
546             fill=False,
547             color=COLORS[2],
548             lw=1.5,
549             label=f"MEC: {radius:.2f} m > 20 m",
550         )
551     )
552     ax.scatter(*center, color=COLORS[2], marker="+", s=60)
553     ax.set(
554         xlim=(-9, 49), ylim=(-22, 40), xlabel="x (m)", ylabel="y (m)", aspect="equal"
555     )
556     ax.legend(loc="center left", bbox_to_anchor=(1.0, 0.5), frameon=False)
557     ax.grid(alpha=0.2)
558     save_figure(fig, "geometry.pdf")
559
560
561 def second_point_figure(second):
562     require(
563         second["first_station"] == [0, 0] and second["first_reading_deg"] == 0,
564         "Q2 figure expects normalized illustrative case",
565     )
566     alpha = math.radians(BEARING_ERROR_DEG)
567     centers = np.array(
568         [

```

```

569         (0, 0),
570         (1000 * math.cos(alpha), 1000 * math.sin(alpha)),
571         (1000 * math.cos(alpha), -1000 * math.sin(alpha)),
572     ]
573 )
574 t = np.linspace(0, 1000, 1001)
575 lower = np.full_like(t, -np.inf)
576 upper = np.full_like(t, np.inf)
577 for x, y in centers:
578     h = np.sqrt(np.maximum(0, 1000**2 - (t - x) ** 2))
579     lower, upper = np.maximum(lower, y - h), np.minimum(upper, y + h)
580 mask = lower <= upper
581 fig, ax = plt.subplots(figsize=(WIDTH, 3.6), layout="constrained")
582 ax.fill_between(
583     t,
584     lower,
585     upper,
586     where=mask,
587     color="#56B4E9",
588     alpha=0.35,
589     label="Triple-disk reception lens",
590 )
591 ax.plot(t[mask], lower[mask], color=COLORS[0])
592 ax.plot(t[mask], upper[mask], color=COLORS[0])
593 candidates = second["candidates"]
594 ax.scatter(
595     [c["t_m"] for c in candidates],
596     [c["b_m"] for c in candidates],
597     color="0.55",
598     marker=".",
599     s=12,
600     label="Finite candidate grid",
601 )
602 for key, label, marker, color in (
603     ("best_sampled_geometry", "Sampled choice", "*", COLORS[2]),
604     ("collinear_control", "Collinear control", "s", "#D55E00"),
605 ):
606     c = second[key]
607     require(
608         all(math.dist(c["point"], p) <= 1000 + 1e-6 for p in centers),
609         "Candidate outside lens",
610     )
611     ax.scatter(
612         c["t_m"],
613         c["b_m"],
614         s=90,
615         marker=marker,
616         color=color,
617         label=f"{label}\nSampled max R={c['sampled_worst_mec_radius_m']:.2f} m",
618     )
619 ax.scatter(0, 0, color="black", s=20)
620 ax.axhline(0, color="0.6", lw=0.6, ls="--")
621 ax.set(
622     xlabel="Along first bearing t (m)",
623     ylabel="Transverse b (m)",
624     xlim=(-40, 1040),
625     ylim=(-920, 920),
626 )
627 ax.legend(loc="center left", bbox_to_anchor=(1.0, 0.5), frameon=False)
628 save_figure(fig, "q2_lens.pdf")
629
630
631 def performance_figure(main):
632     fig, axes = plt.subplots(
633         1, 2, figsize=(WIDTH, 3.7), layout="constrained", sharey=True
634     )
635     for problem, ax in zip((3, 4), axes):

```

```

636     for policy, color, style in zip(POLICIES, COLORS, ("-", "--", "-.")):
637         rows = main[f"Q{problem}_{policy}"]
638         values = sorted(r["average_time_s"] for r in rows)
639         ax.step(
640             values,
641             np.arange(1, len(values) + 1) / len(values),
642             where="post",
643             color=color,
644             ls=style,
645             label=policy.capitalize(),
646         )
647     ax.set(
648         title=f"Q{problem}: {len(rows)} matched worlds",
649         xlabel="Per-world T/N (s)",
650         ylim=(0, 1.02),
651     )
652     ax.grid(alpha=0.2)
653     ax.legend(loc="lower right", frameon=False)
654     axes[0].set_ylabel("Empirical cumulative fraction")
655     save_figure(fig, "performance.pdf")
656
657
658 def replay_trajectories():
659     traces = []
660     for problem in (3, 4):
661         env = LocalSimulator(
662             20260910, problem=problem, error_mode="smooth", scenario="random"
663         )
664         planner = Planner(
665             env, problem=problem, strategy="enhanced", loss_recovery=True
666         )
667         result = planner.run()
668         summary = env.summary() # Evaluation after termination; never supplied to Planner.
669         require(summary["fraction_cleared"] == 1, "Trajectory replay incomplete")
670         require(result["certificate_complete"] is True, "Trajectory certificate incomplete")
671         points, clears = [[0.0, 0.0]], []
672         for event in env.log:
673             request, response = event["request"], event["response"]
674             if not response["accepted"] or "position" not in request:
675                 continue
676             point = [request["position"]["x"], request["position"]["y"]]
677             if point != points[-1]:
678                 points.append(point)
679             if response.get("clear_result") == "success":
680                 clears.append(
681                     {
682                         "channel": request["channel"],
683                         "point": point,
684                         "virtual_time_s": response["virtual_time_s"],
685                     }
686                 )
687         require(
688             len(clears) == summary["n_cleared"] == result["n_cleared"],
689             "Replay clear count mismatch",
690         )
691         trace = {
692             "evidence": "local_synthetic_not_official",
693             "seed": 20260910,
694             "problem": problem,
695             "strategy": "enhanced",
696             "scenario": "random",
697             "error_mode": "smooth",
698             "requested_loss_recovery": True,
699             "effective_loss_recovery": problem == 4,
700             "point_semantics": "Accepted robot coordinates; successful clear within 20 m, not source
coordinates",
701             "path": points,

```

```

702         "successful_clears": clears,
703         "planner": result,
704         "post_exit_summary": summary,
705         "observable_log": env.log,
706     }
707     write_json(f"trajectory_q{problem}.json", trace)
708     traces.append(trace)
709 write_json(
710     "trajectory_summary.json",
711     [
712         {k: t[k] for k in ("problem", "seed", "planner", "post_exit_summary")}
713         for t in traces
714     ],
715 )
716 fig, axes = plt.subplots(1, 2, figsize=(WIDTH, 3.8), layout="constrained")
717 limit = max(
718     2.0, max(abs(v) / 1000 for t in traces for p in t["path"] for v in p) + 0.15
719 )
720 for ax, trace in zip(axes, traces):
721     path = np.array(trace["path"]) / 1000
722     clear = np.array([c["point"] for c in trace["successful_clears"]]) / 1000
723     spatial_axis(ax, limit)
724     ax.add_patch(Circle((0, 0), 1.8, color="0.5", fill=False, ls="--"))
725     ax.plot(*path.T, color=COLORS[0], lw=0.8, label="Accepted path")
726     ax.scatter(
727         *clear.T,
728         color="#D55E00",
729         marker="x",
730         s=26,
731         label="Successful clear",
732         zorder=3,
733     )
734     ax.scatter(0, 0, color="black", marker="s", s=22, label="Start", zorder=4)
735     ax.set_title(
736         f"Q{trace['problem']}: {len(clear)} clears\nT/N={trace['post_exit_summary']['average_time_s']:.2f} s"
737     )
738     handles, labels = axes[0].get_legend_handles_labels()
739     fig.legend(handles, labels, loc="outside lower center", ncol=3, frameon=False)
740     save_figure(fig, "trajectories.pdf")
741     return traces
742
743
744 def recovery_figure(final):
745     fig, axes = plt.subplots(
746         2, 1, figsize=(WIDTH, 5.2), layout="constrained", sharex=True
747     )
748     x = np.arange(len(SCENARIOS))
749     for enabled, offset, color, hatch, label in (
750         (False, -0.18, COLORS[0], "/", "Recovery off"),
751         (True, 0.18, COLORS[2], "", "Recovery on"),
752     ):
753         summaries = [
754             final["recovery_ablation"][f"{s}_recovery_{enabled}"] for s in SCENARIOS
755         ]
756         for ax, metric in zip(axes, ("mean_average_time_s", "mean_failed_clears")):
757             ax.bar(
758                 x + offset,
759                 [s[metric] for s in summaries],
760                 width=0.34,
761                 color=color,
762                 hatch=hatch,
763                 label=label,
764             )
765             ax.grid(axis="y", alpha=0.2)
766             ax.set_axisbelow(True)
767     axes[0].set_ylabel("Mean T/N (s)")

```

```

768 axes[1].set_ylabel("Mean failed clears")
769 axes[1].set_xticks(x, SCENARIO_LABELS, rotation=12, ha="right")
770 axes[0].legend(frameon=False, ncol=2, loc="upper left")
771 counts = sorted({v["cases"] for v in final["recovery_ablation"].values()})
772 require(len(counts) == 1, "Recovery counts differ")
773 axes[0].set_title(f"Q4: {counts[0]} matched worlds per scenario")
774 save_figure(fig, "recovery.pdf")
775
776
777 def main():
778     plt.rcParams.update(
779         {
780             "font.family": "DejaVu Sans",
781             "font.size": 10,
782             "axes.titlesize": 10,
783             "axes.labelsize": 10,
784             "xtick.labelsize": 10,
785             "ytick.labelsize": 10,
786             "legend.fontsize": 10,
787             "pdf.fonttype": 42,
788             "savefig.transparent": False,
789             "figure.facecolor": "white",
790         }
791     )
792     final, geometry, http, second, main_rows, _recovery_rows, hashes = load_inputs()
793     generate_tables(final, geometry, http)
794     coverage_figure(geometry)
795     geometry_figure(geometry)
796     second_point_figure(second)
797     performance_figure(main_rows)
798     traces = replay_trajectories()
799     recovery_figure(final)
800     for name in (
801         "make_assets.py",
802         "planner.py",
803         "environment.py",
804         "geometry.py",
805         "coverage.py",
806         "second_point.py",
807     ):
808         hashes[name] = hashlib.sha256((ROOT / name).read_bytes()).hexdigest()
809     enhancement_input = ROOT / "results" / "enhancement_experiments.json"
810     if enhancement_input.exists():
811         hashes["results/enhancement_experiments.json"] = hashlib.sha256(enhancement_input.read_bytes()).
812         hexdigest()
813     ring_sweep_input = ROOT / "results" / "ring_sweep.json"
814     if ring_sweep_input.exists():
815         hashes["results/ring_sweep.json"] = hashlib.sha256(ring_sweep_input.read_bytes()).hexdigest()
816     write_json(
817         "metadata.json",
818         {
819             "evidence": "local_synthetic_not_official",
820             "official_calls": 0,
821             "asset_set": "base_comparison_with_enhanced_trajectory",
822             "input_sha256": hashes,
823             "matplotlib_version": matplotlib.__version__,
824             "figures": [
825                 "coverage.pdf", "geometry.pdf", "q2_lens.pdf", "performance.pdf",
826                 "trajectories.pdf", "recovery.pdf", "enhancement_geometry.pdf",
827                 "enhancement_performance.pdf",
828             ],
829             "tables": [
830                 "comparison_table.tex", "stress_table.tex", "sensitivity_table.tex",
831                 "recovery_table.tex", "verification_table.tex", "enhancement_table.tex",
832                 "enhancement_costs.tex", "enhancement_stress.tex", "candidate_table.tex",
833                 "coverage_limits_table.tex",
834             ],
835         },

```

```

834     "enhancement_metadata": "enhancement_metadata.json",
835     "layout": {
836         "width_cm": 16,
837         "minimum_font_pt": 10,
838         "backend": "Agg",
839         "format": "vector PDF",
840     },
841     "metric": "Mean, median and nearest-rank p90 of per-world T/N; never pooled sum(T)/sum(N). Gains
are reduction of group means; ECDFs use the same seeds per policy.",
842     "denominators": {
843         "all_runs_including_paired_repeats": final["total_runs"],
844         "main_worlds_per_problem": final["paired_random_cases_per_problem"],
845         "trajectory_replays_additional_to_experiments": len(traces),
846     },
847     "seed_ranges": {
848         "main": [600000, 600000 + final["paired_random_cases_per_problem"] - 1],
849         "stress": [700000, 700019],
850         "probe_sensitivity": [800000, 800029],
851         "spacing_sensitivity": [900000, 900029],
852         "recovery": [610000, 610099],
853         "trajectory": 20260910,
854     },
855     "parameters": {
856         "strategy": "enhanced",
857         "anchor_policy_Q3": "nearest",
858         "anchor_policy_Q4": "rolling",
859         "ring_radius_Q3_m": 1200,
860         "spacing_Q4_m": 990,
861         "probe_scale": 0.22,
862         "max_probes": 6,
863         "loss_recovery_Q4": True,
864         "bearing_halfwidth_deg": BEARING_ERROR_DEG,
865         "Q2_source_samples": second["source_samples"],
866         "Q2_second_errors_deg": second["second_error_values_deg"],
867         "Q2_optimality": "Finite candidate/sample comparison only, no global or continuous minimax
certificate",
868     },
869     "distributions": {
870         "random": "N uniform integer 10..16; distinct channels uniformly sampled; positions iid area-
uniform radius-1800 disk; radii uniform [1000,1500]; orientations uniform [0,2pi). Q3 all omni; Q4 uniform
directional count 1..N-1 and uniform subset.",
871         "minimum_radius": "Random geometry, radio radius exactly 1000 m.",
872         "outward_boundary": "16 equally spaced boundary sources with seeded rotation, radius 1000; Q4
15 outward directional and one omni.",
873         "clustered": "16 area-uniform sources in radius-35 disk with center at radius1650; radio
radius1000.",
874     },
875     "error_fields": {
876         "smooth": "Deterministic bounded two-sinusoid field.",
877         "extreme": "Coordinate/seed/channel hash selecting +/-1 degree.",
878         "iid_location": "Coordinate/seed/channel hash uniform [-1,1], not independent repeat
measurements.",
879     },
880     "trajectory_evidence": "trajectory_q3.json and trajectory_q4.json preserve complete observable logs
, accepted paths, successful robot clearing locations and post-exit aggregate summaries. No hidden source
coordinates inspected.",
881     "determinism": "PDF creation timestamps suppressed; no random plotting jitter. Raw real-duration/
timing observations may vary between replays; figures use virtual time only.",
882     },
883 )
884 print(
885     "Generated six local-evidence PDFs, five tabular fragments, numbers.tex, metadata.json and two complete
observable replay logs."
886 )
887
888
889 if __name__ == "__main__":

```

Listing 15: PDF 逐页渲染与结构审计

```

1  """Render every PDF page and record structural/layout evidence for visual review."""
2
3  from __future__ import annotations
4
5  import argparse
6  import hashlib
7  import json
8  import re
9  from pathlib import Path
10
11  import pymupdf
12  from PIL import Image, ImageDraw
13
14
15  def audit(pdf_path: Path, prefix: str, dpi: int = 120):
16      directory = Path(__file__).resolve().parent / "report" / "visual"
17      directory.mkdir(parents=True, exist_ok=True)
18      document = pymupdf.open(pdf_path)
19      pages, outside, thin, replacements = [], [], [], 0
20      for number, page in enumerate(document, 1):
21          text = page.get_text()
22          replacements += text.count("\ufffd")
23          if len(text.strip()) < 15:
24              thin.append(number)
25          spans = [
26              span
27              for block in page.get_text("dict")["blocks"]
28              if "lines" in block
29              for line in block["lines"]
30              for span in line["spans"]
31              if span["text"].strip()
32          ]
33          for span in spans:
34              rect = pymupdf.Rect(span["bbox"])
35              if (
36                  rect.x0 < -0.5
37                  or rect.y0 < -0.5
38                  or rect.x1 > page.rect.width + 0.5
39                  or rect.y1 > page.rect.height + 0.5
40              ):
41                  outside.append(
42                      {"page": number, "text": span["text"], "bbox": list(rect)}
43                  )
44          image = directory / f"{prefix}_{number:03d}.png"
45          page.get_pixmap(dpi=dpi).save(image)
46          pages.append(
47              {
48                  "page": number,
49                  "characters": len(text),
50                  "image": image.name,
51                  "smallest_text_pt": min((s["size"] for s in spans), default=None),
52                  "largest_text_pt": max((s["size"] for s in spans), default=None),
53              }
54          )
55      sheets = []
56      for start in range(0, len(pages), 6):
57          width, height, gutter = 600, 880, 15
58          sheet = Image.new(
59              "RGB", (3 * width + 4 * gutter, 2 * height + 3 * gutter), "#d4d4d4"
60          )
61          draw = ImageDraw.Draw(sheet)
62          for offset, record in enumerate(pages[start : start + 6]):
63              picture = Image.open(directory / record["image"]).convert("RGB")

```

```

64         picture.thumbnail((width, height - 28), Image.Resampling.LANCZOS)
65         x = gutter + (offset % 3) * (width + gutter)
66         y = gutter + (offset // 3) * (height + gutter)
67         draw.text((x + 8, y + 4), f"Page {record['page']}", fill="black")
68         sheet.paste(picture, (x + (width - picture.width) // 2, y + 27))
69         name = f"{prefix}_sheet_{start // 6 + 1:02d}.png"
70         sheet.save(directory / name)
71         sheets.append(name)
72     endbody = None
73     auxiliary = pdf_path.with_suffix(".aux")
74     if auxiliary.exists():
75         match = re.search(
76             r"\newlabel{endbody}\{[^\}]*\}\{(\d+)\}", auxiliary.read_text()
77         )
78         if match:
79             endbody = int(match[1])
80     result = {
81         "pdf": str(pdf_path),
82         "sha256": hashlib.sha256(pdf_path.read_bytes()).hexdigest(),
83         "pages": len(document),
84         "size_mib": pdf_path.stat().st_size / 2**20,
85         "body_end_page": endbody,
86         "body_pages_excluding_abstract": endbody - 1 if endbody else None,
87         "abstract_keywords_on_first_page": "关键词" in document[0].get_text(),
88         "out_of_page_spans": outside,
89         "replacement_characters": replacements,
90         "near_empty_pages": thin,
91         "rendered_all_pages": True,
92         "dpi": dpi,
93         "contact_sheets": sheets,
94         "page_records": pages,
95         "visual_review_status": "rendered_for_inspection_not_automatically_approved",
96     }
97     output = directory / f"{prefix}_audit.json"
98     output.write_text(json.dumps(result, ensure_ascii=False, indent=2) + "\n")
99     if outside or replacements:
100         raise RuntimeError(f"PDF has structural text issues; inspect {output}")
101     if prefix == "paper" and (
102         endbody is None
103         or endbody - 1 > 30
104         or not result["abstract_keywords_on_first_page"]
105     ):
106         raise RuntimeError(
107             f"Paper abstract/body page requirement failed; inspect {output}"
108         )
109     print(
110         json.dumps(
111             {k: v for k, v in result.items() if k != "page_records"},
112             ensure_ascii=False,
113             indent=2,
114         )
115     )
116     return result
117
118
119 if __name__ == "__main__":
120     parser = argparse.ArgumentParser()
121     parser.add_argument("--pdf", type=Path, default=Path("report/paper.pdf"))
122     parser.add_argument("--prefix", default="paper")
123     parser.add_argument("--dpi", type=int, default=120)
124     args = parser.parse_args()
125     audit(args.pdf, args.prefix, args.dpi)

```

Listing 16: 匿名材料打包与解压复现验证

```

1  """Build anonymous research materials; replay local studies and supplied practice."""
2

```

```

3 from __future__ import annotations
4
5 import argparse
6 import csv
7 import hashlib
8 import importlib.metadata
9 import json
10 import os
11 import re
12 import shutil
13 import subprocess
14 import sys
15 import tempfile
16 import time
17 import zipfile
18 from pathlib import Path, PurePosixPath
19
20 import pymupdf
21
22 ROOT = Path(__file__).resolve().parent
23 SOURCES = (
24     "geometry.py",
25     "coverage.py",
26     "planner.py",
27     "environment.py",
28     "client.py",
29     "run.py",
30     "official_run.py",
31     "intersection.py",
32     "second_point.py",
33     "experiments.py",
34     "compare_recovery.py",
35     "compare_routes.py",
36     "compare_probes.py",
37     "verify_geometry.py",
38     "verify_coverage_limits.py",
39     "verify_refinements.py",
40     "verify_terminal.py",
41     "verify_http.py",
42     "make_enhancement_assets.py",
43     "make_assets.py",
44     "audit_pdf.py",
45     "package.py",
46     "active_policy_candidate.py",
47     "route_policy_candidate.py",
48     "active_policy_notes.txt",
49     "route_policy_notes.txt",
50     "polar_coverage_candidate.py",
51     "polar_coverage_notes.txt",
52     "joint_dispatch_candidate.py",
53     "joint_dispatch_notes.txt",
54     "optical_policy_candidate.py",
55     "optical_policy_notes.txt",
56     "refinement_study.py",
57     "research_experiments.py",
58     "verify_research.py",
59     "make_research_assets.py",
60     "make_official_assets.py",
61     "fast_vs_compact_410.py",
62     "field_policy.py",
63     "negative_geometry.py",
64     "route_portfolio.py",
65     "field_study.py",
66     "field_confirmation.py",
67     "verify_field.py",
68     "official_analysis.py",
69     "make_field_assets.py",

```

```

70     "negative_geometry_notes.txt",
71     "route_portfolio_notes.txt",
72     "contracts.json",
73     "report_contracts.json",
74     "enhancements.py",
75     "ring_sweep.py",
76     "develop_anchors.py",
77     "theory_additions.txt",
78     "paper_expansion.txt",
79     "coverage_notes.txt",
80     "coverage_limits.tex",
81     "requirements.txt",
82     "reproduce.txt",
83     "official_status.json",
84     "audit/route_exact_audit.py",
85     "audit/q3_ablation_audit.py",
86     "audit/distribution_audit.py",
87     "audit/correctness_audit.py",
88     "audit/alternative_screen.py",
89     "audit/freeze_compare.py",
90 )
91 RESULTS = (
92     "final_experiments.json",
93     "geometry_verification.json",
94     "intersection_verification.json",
95     "second_point_example.json",
96     "recovery_development.json",
97     "route_candidate_comparison.json",
98     "adaptive_candidate_comparison.json",
99     "terminal_verification.json",
100    "ring_sweep.json",
101    "enhancement_experiments.json",
102    "anchor_development.json",
103    "enhancement_review.json",
104    "coverage_limits.json",
105    "refinement_verification.json",
106    "refinement_development.json",
107    "research_experiments.json",
108    "research_verification.json",
109    "research_review.json",
110    "field_development.json",
111    "field_confirmation.json",
112    "field_verification.json",
113    "field_review.json",
114    "official_practice_analysis.json",
115    "fast_vs_compact_410.json",
116    "practice_optimization_screen.json",
117    "http_verification.json",
118    "http_deadline_verification.json",
119    "review_resolutions.json",
120    "operation_bound.json",
121    "paper_review.json",
122    "visual_review.json",
123    "final_review.json",
124    "user_supplied_field_practice_summary.json",
125    "environment_manifest.json",
126    "audit_route_exact.json",
127    "audit_q3_ablation.json",
128    "audit_distribution.json",
129    "audit_correctness.json",
130    "audit_alternatives.json",
131    "audit_freeze_compare.json",
132 )
133
134 def verify_asset_inputs(root: Path):
135     for metadata_name in ("metadata.json", "enhancement_metadata.json", "research_metadata.json", "
        official_practice_metadata.json", "field_metadata.json"):

```

```

136     metadata = json.loads((root / "report/generated" / metadata_name).read_text())
137     for name, expected in metadata["input_sha256"].items():
138         actual = hashlib.sha256((root / name).read_bytes()).hexdigest()
139         if actual != expected:
140             raise ValueError(f"Stale generated asset input: {name}")
141
142
143 def deterministic_content(value):
144     """Exclude measured wall clocks and their maximum, not behavioral statistics."""
145     if isinstance(value, dict):
146         return {key: deterministic_content(item) for key, item in value.items()
147                 if key not in ("real_duration_s", "max_real_duration_s", "max_real_s")}
148     if isinstance(value, list):
149         return [deterministic_content(item) for item in value]
150     return value
151
152
153 def practice_files(root: Path):
154     """Allow only the manifest's 60 sanitized practice files, never private raw logs."""
155     root = root.resolve()
156     manifest = root / "manifest.csv"
157     if manifest.is_symlink():
158         raise ValueError("Practice manifest must not be a symbolic link")
159     with manifest.open(encoding="utf-8", newline="") as stream:
160         rows = list(csv.DictReader(stream))
161         if len(rows) != 20 or {(int(r["problem"]), int(r["round"])) for r in rows} != {
162             (p, n) for p in (3, 4) for n in range(1, 11)
163         }:
164             raise ValueError("Expected exactly ten supplied practice rounds per problem")
165     files = {"manifest.csv": manifest}
166
167     def check_identifiers(value):
168         if isinstance(value, dict):
169             for key, item in value.items():
170                 if key == "robot_id" and item != "TEAM_REDACTED":
171                     raise ValueError("Unredacted robot_id in practice data")
172                 check_identifiers(item)
173         elif isinstance(value, list):
174             for item in value:
175                 check_identifiers(item)
176
177     for row in rows:
178         controller = f"data/controller/q{int(row['problem'])}/round_{int(row['round']):02d}"
179         for key in ("private_requests", "observed_result", "simulator_result"):
180             name = row[key]
181             relative = PurePosixPath(name)
182             if relative.is_absolute() or "." in relative.parts or "\\" in name:
183                 raise ValueError(f"Unsafe practice path: {name}")
184             if key == "simulator_result":
185                 allowed = (relative.parent == PurePosixPath("data/simulator_results")
186                           and re.fullmatch(r"practice-p[34]-[0-9]+-[A-Z0-9-]+\result\.json", relative.name))
187             else:
188                 filename = "private_requests.jsonl" if key == "private_requests" else "observed_result.json"
189                 allowed = name == f"{controller}/{filename}"
190             path = root / relative
191             if not allowed or path.is_symlink() or not path.resolve().is_relative_to(root):
192                 raise ValueError(f"Practice path outside permitted source scope: {name}")
193             if name in files:
194                 raise ValueError(f"Repeated practice source: {name}")
195             text = path.read_text(encoding="utf-8")
196             values = [json.loads(line) for line in text.splitlines()] if key == "private_requests" else [json.
197                 loads(text)]
198             for value in values:
199                 check_identifiers(value)
200                 if key == "private_requests" and value.get("event") == "request":
201                     if value["body"].get("robot_id") != "TEAM_REDACTED":
202                         raise ValueError(f"Missing sanitized request identity: {name}")

```

```

202         if isinstance(value, dict) and "body_utf8" in value:
203             check_identifiers(json.loads(value["body_utf8"]))
204         files[name] = path
205     if len(files) != 61:
206         raise ValueError("Expected 60 distinct practice files plus manifest")
207     return files
208
209
210 def verify_practice_inputs(root: Path):
211     files = practice_files(root / "practice_data")
212     analysis = json.loads((root / "results/official_practice_analysis.json").read_text())
213     actual = {name: hashlib.sha256(path.read_bytes()).hexdigest() for name, path in files.items()}
214     if actual != analysis["input_sha256"]:
215         raise ValueError("Official practice source hashes do not match analysis")
216     return actual
217
218 def verify_archive(archive: Path):
219     records = []
220     with tempfile.TemporaryDirectory(prefix="b-reproduce-") as directory:
221         extracted = Path(directory)
222         with zipfile.ZipFile(archive) as bundle:
223             for item in bundle.infolist():
224                 relative = PurePosixPath(item.filename)
225                 if relative.is_absolute() or ".." in relative.parts:
226                     raise ValueError("Unsafe member in generated archive")
227                 bundle.extractall(extracted)
228             manifest = json.loads((extracted / "MANIFEST.json").read_text())
229             for name, information in manifest["files"].items():
230                 raw = (extracted / name).read_bytes()
231                 assert hashlib.sha256(raw).hexdigest() == information["sha256"], name
232             verify_asset_inputs(extracted)
233             practice_hashes = verify_practice_inputs(extracted)
234             immutable_names = [name for name in manifest["files"]
235                                if name in SOURCES or name.startswith("practice_data/")
236                                or (name.startswith("report/") and name.endswith(".tex")
237                                    and not name.startswith("report/generated/"))]
238             expected_runs = {
239                 "final_experiments.json": 4430,
240                 "enhancement_experiments.json": 3080,
241                 "ring_sweep.json": 2200,
242                 "refinement_development.json": 2550,
243                 "research_experiments.json": 10700,
244                 "field_development.json": 2250,
245                 "field_confirmation.json": 9400,
246             }
247             baselines = {
248                 name: json.loads((extracted / "results" / name).read_text())
249                 for name in (*expected_runs, "research_verification.json", "field_verification.json", "
250                 official_practice_analysis.json", "fast_vs_compact_410.json", "practice_optimization_screen.json")
251             }
252             commands = [
253                 [sys.executable, "verify_geometry.py"],
254                 [sys.executable, "intersection.py"],
255                 [sys.executable, "second_point.py"],
256                 [
257                     sys.executable,
258                     "experiments.py",
259                     "--cases",
260                     "500",
261                     "--output",
262                     "results/final_experiments.json",
263                 ],
264                 [sys.executable, "enhancements.py"],
265                 [sys.executable, "ring_sweep.py"],
266                 [sys.executable, "verify_terminal.py"],
267                 [sys.executable, "verify_refinements.py"],
268                 [sys.executable, "verify_coverage_limits.py"],

```

```

268     [sys.executable, "compare_routes.py"],
269     [sys.executable, "compare_probes.py"],
270     [sys.executable, "verify_research.py"],
271     [sys.executable, "official_analysis.py", "--handoff", "practice_data"],
272     [sys.executable, "make_official_assets.py"],
273     [sys.executable, "fast_vs_compact_410.py"],
274     [sys.executable, "refinement_study.py", "--cases", "150", "--seed", "3100000"],
275     [sys.executable, "research_experiments.py"],
276     [sys.executable, "verify_field.py"],
277     [sys.executable, "field_study.py", "--cases", "150", "--seed", "6100000"],
278     [sys.executable, "field_confirmation.py"],
279     [sys.executable, "make_assets.py"],
280     [sys.executable, "make_enhancement_assets.py"],
281     [sys.executable, "make_research_assets.py"],
282     [sys.executable, "make_field_assets.py"],
283     [
284         "latexmk",
285         "-xelatex",
286         "-interaction=nonstopmode",
287         "-halt-on-error",
288         "paper.tex",
289     ],
290     [
291         "latexmk",
292         "-xelatex",
293         "-interaction=nonstopmode",
294         "-halt-on-error",
295         "ai_usage.tex",
296     ],
297 ]
298 environment = {key: value for key, value in os.environ.items() if key != "PYTHONPATH"}
299 environment["MPLBACKEND"] = "Agg"
300 for command in commands:
301     started = time.monotonic()
302     cwd = extracted / "report" if command[0] == "latexmk" else extracted
303     completed = subprocess.run(
304         command,
305         cwd=cwd,
306         text=True,
307         stdout=subprocess.PIPE,
308         stderr=subprocess.STDOUT,
309         timeout=1800,
310         check=False,
311         env=environment,
312     )
313     records.append(
314         {
315             "command": [Path(command[0]).name, *command[1:]],
316             "returncode": completed.returncode,
317             "seconds": time.monotonic() - started,
318         }
319     )
320     if completed.returncode:
321         raise RuntimeError(
322             f"Extracted archive command failed: {command}\n{completed.stdout[-12000:]}"
323         )
324 reproduced_runs = {}
325 auxiliary_runs = {}
326 for name, baseline in baselines.items():
327     replay = json.loads((extracted / "results" / name).read_text())
328     if name in expected_runs:
329         expected = expected_runs[name]
330         assert baseline["total_runs"] == replay["total_runs"] == expected, name
331         if name == "ring_sweep.json":
332             count = sum(len(group["runs"]) for phase in ("development", "held_out")
333                         for group in replay[phase].values())
334     else:

```

```

335         count = len(replay["runs"])
336         for old, new in zip(baseline["runs"], replay["runs"], strict=True):
337             assert deterministic_content(old) == deterministic_content(new), (name, old["seed"])
338         assert count == expected, (name, count)
339         reproduced_runs[name] = count
340     if name == "fast_vs_compact_410.json":
341         assert baseline["total_runs"] == replay["total_runs"] == 2000
342         for label in ("compact25", "fast25"):
343             old_rows = [r for r in baseline["runs"] if r["configuration"] == label]
344             new_rows = [r for r in replay["runs"] if r["configuration"] == label]
345             assert [r["seed"] for r in old_rows] == list(range(4100000, 4101000))
346             assert [r["seed"] for r in new_rows] == list(range(4100000, 4101000))
347             for old, new in zip(old_rows, new_rows, strict=True):
348                 assert deterministic_content(old) == deterministic_content(new)
349             auxiliary_runs[name] = len(replay["runs"])
350         assert deterministic_content(baseline) == deterministic_content(replay), name
351     verify_asset_inputs(extracted)
352     assert verify_practice_inputs(extracted) == practice_hashes
353     for name in immutable_names:
354         assert hashlib.sha256((extracted / name).read_bytes()).hexdigest() == manifest["files"][name][
355             "sha256"], name
356     assert sum(reproduced_runs.values()) == 34610
357     for filename in ("paper", "ai_usage"):
358         log = (extracted / "report" / f"{filename}.log").read_text(errors="replace")
359         assert "Missing character:" not in log and "Overfull" not in log
360         assert (
361             "undefined references" not in log and "undefined citations" not in log
362         )
363     assert len(pymupdf.open(extracted / "report" / f"{filename}.pdf")) > 0
364 return {
365     "status": "passed",
366     "archive_sha256": hashlib.sha256(archive.read_bytes()).hexdigest(),
367     "manifest_hashes_verified": True,
368     "all_4430_behavioral_runs_reproduced_exactly": True,
369     "all_3080_enhancement_runs_reproduced_exactly": True,
370     "ring_sweep_reproduced_exactly": True,
371     "all_2200_ring_runs_reproduced_exactly": True,
372     "all_10700_research_runs_reproduced_exactly": True,
373     "all_2550_development_runs_reproduced_exactly": True,
374     "research_verification_reproduced_exactly": True,
375     "all_2250_field_development_runs_reproduced_exactly": True,
376     "all_9400_field_confirmation_runs_reproduced_exactly": True,
377     "field_verification_reproduced_exactly": True,
378     "practice_source_hashes_verified_before_and_after": practice_hashes,
379     "immutable_source_hashes_verified_after_replay": True,
380     "pythonpath_removed": True,
381     "official_practice_analysis_reproduced_exactly": True,
382     "fast_vs_compact_screen_reproduced_exactly": True,
383     "generated_asset_input_hashes_verified": True,
384     "experiment_runs_reproduced_by_dataset": reproduced_runs,
385     "experiment_runs_reproduced_total": sum(reproduced_runs.values()),
386     "auxiliary_runs_excluded_from_core_total": auxiliary_runs,
387     "excluded_nondeterminism": "local measured wall-clock real_duration_s, max_real_duration_s and
388     max_real_s only; official timestamp/runtime observations remain exact",
389     "commands": records,
390 }
391
392 def main():
393     parser = argparse.ArgumentParser()
394     parser.add_argument("--verify", action="store_true")
395     parser.add_argument("--handoff", type=Path, default=(ROOT / "practice_data" if (ROOT / "practice_data").
396         is_dir()
397         else ROOT.parent / "ai_optimization_handoff_20260912"))
398     args = parser.parse_args()
399     verify_asset_inputs(ROOT)
400     for prefix, name in (("paper", "paper"), ("ai", "ai_usage")):

```

```

399     audit = json.loads((ROOT / "report/visual" / f"{prefix}_audit.json").read_text())
400     actual = hashlib.sha256((ROOT / "report" / f"{name}.pdf").read_bytes()).hexdigest()
401     if audit["sha256"] != actual or audit["out_of_page_spans"] or audit["replacement_characters"]:
402         raise ValueError(f"Missing or stale PDF audit: {name}")
403     if prefix == "paper" and not (audit["abstract_keywords_on_first_page"]
404                                   and 0 < audit["body_pages_excluding_abstract"] <= 30):
405         raise ValueError("Paper abstract/body page rule violated")
406     environment = {
407         "python": sys.version,
408         "environment": "conda py314",
409         "packages": {
410             name: importlib.metadata.version(name)
411             for name in ("numpy", "scipy", "matplotlib", "pymupdf")
412         },
413     }
414     (ROOT / "results/environment_manifest.json").write_text(
415         json.dumps(environment, indent=2) + "\n"
416     )
417     files = {name: ROOT / name for name in SOURCES}
418     files.update({"results/" + name: ROOT / "results" / name for name in RESULTS})
419     supplied_practice = practice_files(args.handoff)
420     analysis = json.loads((ROOT / "results/official_practice_analysis.json").read_text())
421     practice_hashes = {name: hashlib.sha256(path.read_bytes()).hexdigest()
422                        for name, path in supplied_practice.items()}
423     if practice_hashes != analysis["input_sha256"]:
424         raise ValueError("Supplied practice files do not match official analysis input hashes")
425     files.update({"practice_data/" + name: path for name, path in supplied_practice.items()})
426     files["AI工具使用详情.pdf"] = ROOT / "report/ai_usage.pdf"
427     for path in (ROOT / "report").iterdir():
428         if path.suffix in (".tex", ".pdf"):
429             files[path.relative_to(ROOT).as_posix()] = path
430     for folder in ("generated", "figures"):
431         for path in (ROOT / "report" / folder).iterdir():
432             if path.is_file() and not path.name.startswith("."):
433                 files[path.relative_to(ROOT).as_posix()] = path
434     for filename in ("paper_audit.json", "ai_audit.json"):
435         path = ROOT / "report" / "visual" / filename
436         files[path.relative_to(ROOT).as_posix()] = path
437     missing = [name for name, path in files.items() if not path.is_file()]
438     if missing:
439         raise RuntimeError(f"Deliverable proof is missing: {missing}")
440     anonymous_pattern = re.compile(r"/Users/[A-Za-z0-9._-]+/")
441     for name, path in files.items():
442         if path.suffix in (".py", ".txt", ".tex", ".json", ".jsonl", ".csv") and anonymous_pattern.search(
443             path.read_text(encoding="utf-8")
444         ):
445             raise ValueError(f"Personal absolute path in anonymous material: {name}")
446         if path.suffix == ".pdf":
447             document = pymupdf.open(path)
448             if anonymous_pattern.search(
449                 "\n".join(page.get_text() for page in document)
450             ):
451                 raise ValueError(f"Personal absolute path in PDF: {name}")
452     manifest = {
453         "status": "RESEARCH_VERSION_OFFICIAL_PRACTICE_COMPLETE_FORMAL_TESTS_PENDING",
454         "not_ready_for_contest_submission": True,
455         "official_practice": "Twenty user-supplied Q3/Q4 practice observations were analyzed offline; formal
456         tests and encrypted exports remain pending",
457         "official_practice_replay_boundary": "All 20 supplied traces are independently costed; strict baseline
458         policy replay matches only 8/20. Divergence stops replay, with no fabricated responses.",
459         "practice_source_files": 60,
460         "default_strategy": "Q3 refined, Q4 field; explicit --strategy overrides",
461         "official_practice_control": "refined, probe_scale=0.22 for Q3 and Q4",
462         "human_review": "No actual contestant review record; AI review is not human review",
463         "python_environment": "conda py314",
464         "python_version": sys.version.split()[0],
465         "files": {

```

```

464         name: {
465             "sha256": hashlib.sha256(path.read_bytes()).hexdigest(),
466             "bytes": path.stat().st_size,
467         }
468         for name, path in sorted(files.items())
469     },
470 }
471 destination = ROOT / "delivery"
472 destination.mkdir(exist_ok=True)
473 archive = destination / "B题研究支撑材料.zip"
474 with zipfile.ZipFile(
475     archive, "w", compression=zipfile.ZIP_DEFLATED, compresslevel=9
476 ) as bundle:
477     for name, path in sorted(files.items()):
478         bundle.write(path, name)
479     bundle.writestr(
480         "MANIFEST.json", json.dumps(manifest, ensure_ascii=False, indent=2) + "\n"
481     )
482 with zipfile.ZipFile(archive) as bundle:
483     assert bundle.testzip() is None
484     for name, information in manifest["files"].items():
485         assert hashlib.sha256(bundle.read(name)).hexdigest() == information["sha256"], name
486 verify_asset_inputs(ROOT)
487 for name, path in supplied_practice.items():
488     assert hashlib.sha256(path.read_bytes()).hexdigest() == practice_hashes[name], name
489 shutil.copy2(ROOT / "report/paper.pdf", destination / "B题研究论文.pdf")
490 shutil.copy2(ROOT / "report/ai_usage.pdf", destination / "AI工具使用详情.pdf")
491 for path in (
492     archive,
493     destination / "B题研究论文.pdf",
494     destination / "AI工具使用详情.pdf",
495 ):
496     assert path.stat().st_size <= 20 * 2**20, path.name
497 status = {
498     "status": manifest["status"],
499     "official_tests": "PRACTICE_COMPLETE_FORMAL_PENDING",
500     "human_review": "OUTSTANDING",
501     "source_files": len(files),
502     "archive_bytes": archive.stat().st_size,
503     "archive_sha256": hashlib.sha256(archive.read_bytes()).hexdigest(),
504 }
505 if args.verify:
506     proof = verify_archive(archive)
507     (destination / "复现验证.json").write_text(
508         json.dumps(proof, ensure_ascii=False, indent=2) + "\n"
509     )
510     status["extracted_archive_reproduction"] = "passed"
511 (destination / "交付状态.json").write_text(
512     json.dumps(status, ensure_ascii=False, indent=2) + "\n"
513 )
514 print(json.dumps(status, ensure_ascii=False, indent=2))
515
516
517 if __name__ == "__main__":
518     main()

```

Listing 17: 区间评分自适应测点候选

```

1  """Unexecuted research candidate: observation-only, bounded active probing.
2
3  No action or belief update occurs here. ``None`` means use the unchanged
4  localizer/optical cover; a selected point is NOT a clearing certificate.
5  """
6
7  from __future__ import annotations
8
9  from math import acos, cos, dist, hypot, isfinite, nextafter, pi, radians, sin

```

```

10
11 from geometry import (
12     BEARING_ERROR_DEG,
13     MAX_RADIO_RADIUS,
14     Point,
15     _clip_halfplane,
16     _padding,
17     enclosing_circle,
18 )
19 from second_point import safe_candidates
20
21
22 def _bearing_bound(polygon, point, radius, bins, error_deg):
23     """Upper-bound every positive-bearing posterior using overlapping wedges.
24
25     Each angular bin is enlarged by the measurement error; unlike clip_bearing,
26     the scoring relaxation has NO projected range cap. A bounding-box circle
27     encloses each relaxed polygon. The original MEC is also an enclosing disk.
28     """
29     half_bin = 180.0 / bins
30     width = radians(error_deg + half_bin)
31     scale = max(
32         MAX_RADIO_RADIUS,
33         abs(point[0]),
34         abs(point[1]),
35         *(max(abs(x), abs(y)) for x, y in polygon),
36     )
37     # A padded narrow wedge is a translated exact wedge. Its apex shift is
38     # epsilon/sin(alpha); this larger pad also covers that displacement.
39     padding = 4.0 * _padding(scale) / sin(radians(error_deg))
40     worst, nonempty = 0.0, 0
41     for index in range(bins):
42         angle = 2.0 * pi * index / bins
43         low, high = angle - width, angle + width
44         outer = _clip_halfplane(
45             polygon, point, (sin(low), -cos(low)), 0.0, padding
46         )
47         outer = _clip_halfplane(
48             outer, point, (-sin(high), cos(high)), 0.0, padding
49         )
50         if not outer:
51             continue
52         nonempty += 1
53         xmin = min(p[0] for p in outer)
54         xmax = max(p[0] for p in outer)
55         ymin = min(p[1] for p in outer)
56         ymax = max(p[1] for p in outer)
57         box_radius = nextafter(
58             0.5 * hypot(xmax - xmin, ymax - ymin) + padding, float("inf")
59         )
60         worst = max(worst, min(radius, box_radius))
61     # An unexpected empty partition must not look like perfect information.
62     return (worst if nonempty else radius), nonempty
63
64
65 def _loss_risk(samples, readings, point, problem):
66     """Geometric risk index, NOT an identified no-signal probability."""
67     total = 0.0
68     station = readings[-1][0]
69     for source in samples:
70         query_distance = dist(point, source)
71         # A positive station implies range >= its distance, even in Q4.
72         lower_range = max(1000.0, *(dist(s, source) for s, _ in readings))
73         if query_distance > lower_range:
74             total += 1.0
75             continue
76         if problem == 3:

```

```

77         continue
78     old_distance = dist(station, source)
79     if old_distance <= 1e-9 or query_distance <= 1e-9:
80         # Direction is undefined here; do not manufacture guaranteed signal.
81         total += 1.0
82         continue
83     cosine = sum(
84         (station[i] - source[i]) * (point[i] - source[i]) for i in (0, 1)
85     ) / (old_distance * query_distance)
86     total += acos(max(-1.0, min(1.0, cosine))) / pi
87     return total / len(samples)
88
89
90 def score_probes(
91     polygon,
92     readings,
93     current_position,
94     problem,
95     *,
96     probes_remaining=1,
97     rejected_points=(),
98     bearing_bins=72,
99     error_deg=BEARING_ERROR_DEG,
100     probe_scale=0.22,
101     movement_weight=0.15,
102     loss_weight=1.0,
103     include_lens=True,
104 ):
105     """Return a deterministic score table; consume only public observations.
106
107     polygon: nonempty ordered convex conservative vertices, as Track.polygon.
108     readings: positive (station, svd_deg) pairs for ONE known channel only.
109     rejected_points: previous unsuccessful probes/clears; excludes locations,
110         never source hypotheses. The caller retains all underlying history.
111     probes_remaining: caller-owned remaining bound; this function cannot debit it.
112
113     Legal coordinates are finite and within +/-2,000,000 m per protocol, NOT
114     restricted to the radius-1800 source arena. Scores are dimensionless.
115     Empty output signals fallback. Malformed/contradictory inputs raise, rather
116     than resetting a belief or silently substituting a made-up polygon.
117     """
118     if problem not in (3, 4):
119         raise ValueError("Only Q3 and Q4 localization is supported")
120     if not isinstance(probes_remaining, int) or probes_remaining < 0:
121         raise ValueError("probes_remaining must be a nonnegative integer")
122     if not isinstance(bearing_bins, int) or bearing_bins < 4:
123         raise ValueError("bearing_bins must be an integer >= 4")
124     if not isfinite(error_deg) or not BEARING_ERROR_DEG <= error_deg < 90:
125         raise ValueError("error_deg must include the public rounding allowance")
126     if error_deg + 180.0 / bearing_bins >= 90.0:
127         raise ValueError("Expanded bearing bins must be narrower than 180 degrees")
128     if not isfinite(probe_scale) or not 0 < probe_scale <= 1:
129         raise ValueError("probe_scale must lie in (0, 1]")
130     if any(not isfinite(w) or w < 0 for w in (movement_weight, loss_weight)):
131         raise ValueError("Score weights must be finite and nonnegative")
132     poly = [tuple(p) for p in polygon]
133     history = [(tuple(s), float(a)) for s, a in readings]
134     position = tuple(current_position)
135     rejected = [tuple(p) for p in rejected_points]
136     points = poly + [position] + rejected + [s for s, _ in history]
137     if any(len(p) != 2 or not all(isfinite(v) for v in p) for p in points):
138         raise ValueError("All points must contain two finite coordinates")
139     if any(not isfinite(a) for _, a in history):
140         raise ValueError("Readings must have finite public bearing angles")
141     center, radius = enclosing_circle(poly) # Empty belief must raise.
142     if not history or probes_remaining == 0 or radius <= 19.9:
143         return []

```

```

144
145 station, bearing = history[-1]
146 dx, dy = center[0] - station[0], center[1] - station[1]
147 length = hypot(dx, dy)
148 axis = (dx / length, dy / length) if length > 1e-8 else (
149     cos(radians(bearing)), sin(radians(bearing))
150 )
151 normal = (-axis[1], axis[0])
152 offset = min(120.0, max(25.0, probe_scale * radius))
153 candidates = [("mec_center", center), ("positive_station", station)]
154 for name, direction in (("normal", normal), ("axis", axis)):
155     for sign in (-1, 1):
156         candidates.append((
157             f"mec_{name}_{sign:+d}",
158             tuple(center[i] + sign * offset * direction[i] for i in (0, 1)),
159         ))
160 if include_lens:
161     candidates.extend(
162         (f"q2_lens_{index}", tuple(row["point"])))
163     for index, row in enumerate(safe_candidates(station, bearing, error_deg))
164 )
165
166 samples = list(dict.fromkeys(poly + [center]))
167 exclusions = [s for s, _ in history] + rejected
168 table, seen = [], set()
169 for label, point in candidates:
170     if point in seen:
171         continue
172     seen.add(point)
173     reason = None
174     if any(not isfinite(v) or abs(v) > 2_000_000 for v in point):
175         reason = "outside_protocol_coordinates"
176     elif any(dist(point, old) <= 0.5 for old in exclusions):
177         reason = "previous_observation_or_rejected_location"
178     row = {
179         "candidate": label,
180         "point": point,
181         "eligible": reason is None,
182         "rejection": reason,
183         "score": None,
184     }
185     if reason is None:
186         bound, bins_used = _bearing_bound(
187             poly, point, radius, bearing_bins, error_deg
188         )
189         movement = dist(position, point)
190         risk = _loss_risk(samples, history, point, problem)
191         row.update({
192             "prior_mec_radius_m": radius,
193             "positive_bearing_radius_upper_m": bound,
194             "movement_m": movement,
195             "no_signal_risk_index": risk,
196             "radius_term": bound / radius,
197             "movement_term": movement_weight * movement / 1000.0,
198             "loss_term": loss_weight * risk,
199             "worst_including_uninformative_no_signal_m": radius,
200             "nonempty_bearing_bins": bins_used,
201             "bearing_bins": bearing_bins,
202             "error_deg": error_deg,
203             "risk_samples": len(samples),
204             "score": (
205                 bound / radius
206                 + movement_weight * movement / 1000.0
207                 + loss_weight * risk
208             ),
209         })
210     table.append(row)

```

```

211     return table
212
213
214 def choose_probe(
215     polygon, readings, current_position, problem, **options
216 ) -> Point | None:
217     """Choose minimum score, then minimum travel, then generation-order tie.
218
219     The caller MUST debit its existing finite probe budget, apply only actual
220     positive bearings via Planner.measure, and retain the original fallback.
221     Use score_probes with identical arguments to obtain the full score table.
222     """
223     table = score_probes(polygon, readings, current_position, problem, **options)
224     eligible = [row for row in table if row["eligible"]]
225     if not eligible:
226         return None
227     best = min(eligible, key=lambda row: (row["score"], row["movement_m"]))
228     return best["point"]

```

Listing 18: 骨架路由候选

```

1  """Deterministic routing and task-priority candidates.
2
3  These helpers are deliberately separate from :mod:`planner`: they can improve
4  travel order without changing the certified waypoint set or its discovery
5  obligations. No simulator/source-truth state is read here.
6  """
7
8  from __future__ import annotations
9
10 import math
11 from collections.abc import Sequence
12 from numbers import Real
13
14
15 def _point(value: object) -> tuple[float, float] | None:
16     if isinstance(value, (str, bytes)) or not isinstance(value, Sequence) or len(value) != 2:
17         return None
18     x, y = value
19     if not isinstance(x, Real) or not isinstance(y, Real):
20         return None
21     x, y = float(x), float(y)
22     return (x, y) if math.isfinite(x) and math.isfinite(y) else None
23
24
25 def optimize_waypoints(points: Sequence[object], start: tuple[float, float] = (0.0, 0.0)) -> list[int]:
26     """Return a deterministic nearest-neighbour + 2-opt index order.
27
28     Every valid input point occurs exactly once. Invalid point data, or an
29     invalid start, uses the exact identity order as a safe, obligation-
30     preserving fallback; it never silently removes or fabricates a waypoint.
31     The 2-opt pass only reverses contiguous order segments, so it changes
32     travel length but cannot change the waypoint certificate.
33     """
34     try:
35         n = len(points)
36     except (TypeError, AttributeError):
37         return []
38     fallback = list(range(n))
39     origin = _point(start)
40     if origin is None:
41         return fallback
42     coords = [_point(p) for p in points]
43     if any(p is None for p in coords):
44         return fallback
45     xy = [p for p in coords if p is not None]
46     remaining = set(range(n))

```

```

47 route: list[int] = []
48 current = origin
49 while remaining:
50     index = min(remaining, key=lambda i: ((xy[i][0] - current[0]) ** 2 + (xy[i][1] - current[1]) ** 2, i))
51     route.append(index)
52     remaining.remove(index)
53     current = xy[index]
54
55 def edge(a: tuple[float, float], b: tuple[float, float]) -> float:
56     return math.hypot(a[0] - b[0], a[1] - b[1])
57
58 # First-improvement, lexicographically scanned, strict 2-opt is stable.
59 # Repeat until no improving exchange remains.
60 changed = True
61 while changed:
62     changed = False
63     for i in range(-1, n - 2): # edge from start (i=-1) or route[i]
64         a = origin if i == -1 else xy[route[i]]
65         ai = i + 1
66         for j in range(ai + 1, n):
67             b = xy[route[ai]]
68             c = xy[route[j]]
69             d = xy[route[j + 1]] if j + 1 < n else None
70             old = edge(a, b) + (edge(c, d) if d is not None else 0.0)
71             new = edge(a, c) + (edge(b, d) if d is not None else 0.0)
72             if new + 1e-12 < old:
73                 route[ai : j + 1] = reversed(route[ai : j + 1])
74                 changed = True
75                 break
76         if changed:
77             break
78     return route

```

Listing 19: 路由候选对照实验

```

1  """Paired route-order candidate comparison on declared synthetic worlds."""
2  from __future__ import annotations
3
4  import json
5  import statistics
6  from pathlib import Path
7
8  from environment import LocalSimulator
9  from planner import Planner
10
11
12 def run(seed, problem, anchor_policy):
13     env = LocalSimulator(seed, problem=problem, scenario="random", error_mode="smooth")
14     planner = Planner(env, problem=problem, strategy="integrated", anchor_policy=anchor_policy)
15     planner.run()
16     result = env.summary()
17     assert result["fraction_cleared"] == 1
18     return result
19
20
21 def main():
22     output = {}
23     records = []
24     for problem in (3, 4):
25         pairs = [(run(950000 + k, problem, "nearest"), run(950000 + k, problem, "two_opt")) for k in range(200)]
26         records.extend({"problem": problem, "seed": 950000 + k,
27                        "nearest": a, "two_opt": b} for k, (a, b) in enumerate(pairs))
28         deltas = [a["average_time_s"] - b["average_time_s"] for a, b in pairs]
29         output[f"Q{problem}"] = {
30             "cases": len(pairs),
31             "all_nearest_cleared": sum(a["fraction_cleared"] == 1 for a, _ in pairs),

```

```

32         "all_two_opt_cleared": sum(b["fraction_cleared"] == 1 for _, b in pairs),
33         "nearest_mean_s_per_source": statistics.mean(a["average_time_s"] for a, _ in pairs),
34         "two_opt_mean_s_per_source": statistics.mean(b["average_time_s"] for _, b in pairs),
35         "mean_saved_s_per_source": statistics.mean(deltas),
36         "median_saved_s_per_source": statistics.median(deltas),
37         "faster_cases": sum(d > 0 for d in deltas),
38         "mean_distance_saved_m": statistics.mean(a["distance_m"] - b["distance_m"] for a, b in pairs),
39     }
40     result = {"evidence": "local_synthetic_route_candidate_not_official", "seed_range": [950000, 950199], "
41             summary": output, "runs": records}
42     Path("results/route_candidate_comparison.json").write_text(json.dumps(result, ensure_ascii=False, indent=2)
43                       + "\n")
44     print(json.dumps(result, ensure_ascii=False, indent=2))
45
46 if __name__ == "__main__":
47     main()

```

Listing 20: 自适应测点对照实验

```

1  """Paired comparison for the interval-scored adaptive probe candidate."""
2  from __future__ import annotations
3
4  import json
5  import statistics
6  from pathlib import Path
7
8  from environment import LocalSimulator
9  from planner import Planner
10
11
12 def run(seed, problem, probe_policy):
13     env = LocalSimulator(seed, problem=problem, scenario="random", error_mode="smooth")
14     planner = Planner(env, problem=problem, strategy="integrated", probe_policy=probe_policy)
15     planner.run()
16     summary = env.summary()
17     assert summary["fraction_cleared"] == 1
18     return {**summary, "adaptive_probes": planner.adaptive_probes}
19
20
21 def aggregate(rows):
22     delta = [a["average_time_s"] - b["average_time_s"] for a, b in rows]
23     return {
24         "cases": len(rows),
25         "fixed_all_cleared": sum(a["fraction_cleared"] == 1 for a, _ in rows),
26         "adaptive_all_cleared": sum(b["fraction_cleared"] == 1 for _, b in rows),
27         "fixed_mean_s_per_source": statistics.mean(a["average_time_s"] for a, _ in rows),
28         "adaptive_mean_s_per_source": statistics.mean(b["average_time_s"] for _, b in rows),
29         "mean_saved_s_per_source": statistics.mean(delta),
30         "median_saved_s_per_source": statistics.median(delta),
31         "faster_cases": sum(d > 0 for d in delta),
32         "fixed_mean_failed_clears": statistics.mean(a["failed_clears"] for a, _ in rows),
33         "adaptive_mean_failed_clears": statistics.mean(b["failed_clears"] for _, b in rows),
34         "mean_adaptive_probes": statistics.mean(b["adaptive_probes"] for _, b in rows),
35     }
36
37
38 def main():
39     summary = {}
40     records = []
41     for problem in (3, 4):
42         pairs = [(run(960000 + k, problem, "fixed"), run(960000 + k, problem, "adaptive")) for k in range(200)]
43         summary[f"Q{problem}"] = aggregate(pairs)
44         records.extend({"problem": problem, "seed": 960000 + k, "fixed": fixed, "adaptive": adaptive}
45                       for k, (fixed, adaptive) in enumerate(pairs))
46     result = {"evidence": "local_synthetic_adaptive_candidate_not_official", "seed_range": [960000, 960199], "
47             summary": summary, "runs": records}

```

```

47     Path("results/adaptive_candidate_comparison.json").write_text(json.dumps(result, ensure_ascii=False, indent
    =2) + "\n")
48     print(json.dumps({"evidence": result["evidence"], "summary": summary}, ensure_ascii=False, indent=2))
49
50
51 if __name__ == "__main__":
52     main()

```

Listing 21: 超时终端状态回归

```

1  """Finite Planner terminal/deadline regression using a protocol-shaped fake adapter."""
2  from __future__ import annotations
3
4  import json
5  from pathlib import Path
6
7  from planner import Planner
8
9
10 class DeadlineAdapter:
11     def __init__(self, remaining=1200, max_virtual=10, near_channel=None):
12         self.remaining = remaining
13         self.max_virtual = max_virtual
14         self.virtual = 0.0
15         self.channel = 1
16         self.paths = []
17         self.near_channel = near_channel
18
19     def act(self, path, position=None, channel=None):
20         self.paths.append(path)
21         if path == "/enter":
22             return {"accepted": True, "virtual_time_s": 0.0,
23                     "remaining_real_duration_s": self.remaining,
24                     "max_virtual_duration_s": self.max_virtual}
25         if path == "/exit":
26             if self.virtual >= self.max_virtual:
27                 raise AssertionError("Planner sent /exit after automatic virtual close")
28             return {"accepted": True, "virtual_time_s": self.virtual,
29                     "exit_reason": "user_exit"}
30         if path == "/clear":
31             self.virtual += 5
32             return {"accepted": True, "virtual_time_s": self.virtual, "clear_result": "success"}
33         switch = int(path == "/measure" and channel != self.channel)
34         self.virtual += 5 + switch
35         self.channel = channel
36         return {"accepted": True, "virtual_time_s": self.virtual,
37                 "measure_result": "near" if channel == self.near_channel else "no_signal"}
38
39
40 def main():
41     automatic = DeadlineAdapter(remaining=1200, max_virtual=10)
42     result_auto = Planner(automatic, problem=3).run()
43     assert result_auto["terminal_reason"] == "virtual_timeout"
44     assert result_auto["certificate_complete"] is False
45     assert "/exit" not in automatic.paths
46
47     real = DeadlineAdapter(remaining=1, max_virtual=360000)
48     result_real = Planner(real, problem=3).run()
49     assert result_real["terminal_reason"] == "TimeoutError"
50     assert result_real["certificate_complete"] is False
51     assert "/exit" not in real.paths
52     near = DeadlineAdapter(max_virtual=119, near_channel=20)
53     policy = Planner(near, problem=3)
54     for record in policy.scan_records.values():
55         record.update(range(1,7))
56     near_result = policy.run()
57     assert near_result["channel_certificates"][20] == "detected"

```

```

58     assert not near_result["certificate_complete"] and "/clear" not in near.paths
59     assert "/exit" not in near.paths
60     completed = DeadlineAdapter(max_virtual=119)
61     policy = Planner(completed, problem=3)
62     for record in policy.scan_records.values():
63         record.update(range(1,7))
64     completed_result = policy.run()
65     assert completed_result["certificate_complete"]
66     assert completed_result["termination"] == "complete_after_virtual_timeout"
67     assert "/exit" not in completed.paths
68     final_clear = DeadlineAdapter(max_virtual=5)
69     policy = Planner(final_clear, problem=3)
70     policy.action("/enter")
71     policy.cleared.update(range(1,16))
72     policy.clear(16,(0.0,0.0))
73     assert policy._result()["certificate_complete"] and "/exit" not in final_clear.paths
74     result = {"evidence": "local_protocol_shaped_terminal_regression_not_official",
75              "automatic_virtual_timeout": result_auto,
76              "preflight_real_deadline": result_real,
77              "never_exited_after_terminal": True,
78              "near_at_limit_not_absent": True,
79              "final_absence_certificate_at_limit": True,
80              "sixteenth_clear_at_limit_complete": True,
81              "never_claimed_certificate": True}
82     Path("results/terminal_verification.json").write_text(json.dumps(result, indent=2) + "\n")
83     print(json.dumps(result, indent=2))
84
85
86 if __name__ == "__main__":
87     main()

```

Listing 22: 环半径与滚动调度开发比较

```

1  """Development-only anchor geometry and rolling route screen, no official calls."""
2  from __future__ import annotations
3
4  import json
5  import statistics
6  from pathlib import Path
7
8  from environment import LocalSimulator
9  from planner import Planner
10
11
12 def case(seed, problem, route, ring_radius=None):
13     env = LocalSimulator(seed, problem=problem)
14     policy = Planner(env, problem=problem, strategy="integrated", anchor_policy=route,
15                     ring_radius=ring_radius)
16     result = policy.run()
17     actual = env.summary()
18     assert result['certificate_complete'] and actual['fraction_cleared'] == 1
19     return actual
20
21
22 def main():
23     results = {}
24     for problem in (3, 4):
25         configs = [('nearest', None), ('rolling', None)]
26         if problem == 3:
27             configs += [('nearest', 1200.), ('rolling', 1200.)]
28         baseline = None
29         for route, radius in configs:
30             rows = [case(1000000+k, problem, route, radius) for k in range(150)]
31             if baseline is None:
32                 baseline = rows
33             differences = [a['average_time_s']-b['average_time_s'] for a,b in zip(baseline,rows)]
34             results[f'Q{problem}_{route}_{radius}'] = {

```

```

35         'cases':len(rows), 'mean_s_per_source':statistics.mean(r['average_time_s'] for r in rows),
36         'mean_distance_m':statistics.mean(r['distance_m'] for r in rows),
37         'mean_measures':statistics.mean(r['measures'] for r in rows),
38         'mean_saved_s_per_source':statistics.mean(differences),
39         'faster_cases':sum(d>0 for d in differences), 'all_cleared':True,
40         'runs':rows}
41     Path('results/anchor_development.json').write_text(json.dumps(results,indent=2)+'\n')
42     print(json.dumps({k:{f:v for f,v in row.items() if f!='runs'} for k,row in results.items()},indent=2))
43
44
45 if __name__ == '__main__':
46     main()

```

Listing 23: 增强策略样本外实验

```

1  """Frozen held-out comparison of accepted geometric/rolling enhancements."""
2  from __future__ import annotations
3
4  import json
5  import math
6  import statistics
7  from pathlib import Path
8
9  from coverage import ring_cover_radius
10 from experiments import aggregate, run_case
11
12
13 def paired_summary(control, enhanced):
14     assert [r['seed'] for r in control] == [r['seed'] for r in enhanced]
15     differences = [a['average_time_s']-b['average_time_s'] for a,b in zip(control, enhanced)]
16     average = statistics.mean(differences)
17     stderr = statistics.stdev(differences)/math.sqrt(len(differences))
18     return {'cases':len(differences), 'mean_saved_s_per_source':average,
19             'mean_reduction_pct':100*average/statistics.mean(r['average_time_s'] for r in control),
20             'approx_95pct_ci_s':[average-1.96*stderr, average+1.96*stderr],
21             'faster_cases':sum(d>0 for d in differences),
22             'mean_distance_saved_m':statistics.mean([a['distance_m']-b['distance_m'] for a,b in zip(control,
23             enhanced)])}
23
24
25 def main():
26     rows, summary, comparison, stress = [], {}, {}, {}
27     for problem in (3,4):
28         paired = []
29         for policy in ('integrated','enhanced'):
30             group = [run_case(1100000+k,problem,policy) for k in range(500)]
31             rows.extend(group)
32             summary[f'Q{problem}_{policy}'] = aggregate(group)
33             paired.append(group)
34             comparison[f'Q{problem}'] = paired_summary(*paired)
35         for scenario in ('minimum_radius','outward_boundary','clustered'):
36             for mode in ('smooth','extreme','iid_location'):
37                 groups = []
38                 for policy in ('integrated','enhanced'):
39                     group = [run_case(1110000+k,problem,policy,scenario,mode) for k in range(30)]
40                     rows.extend(group)
41                     groups.append(group)
42                 key = f'Q{problem}_{scenario}_{mode}'
43                 stress[key] = {'integrated':aggregate(groups[0]), 'enhanced':aggregate(groups[1]),
44                               'paired':paired_summary(*groups)}
45     result = {'evidence':'held_out_local_synthetic_not_official',
46             'selection':'Only development seeds1000000..1000149 used; final seeds excluded from choice',
47             'main_seed_range':[1100000,1100499], 'stress_seed_range':[1110000,1110029],
48             'total_runs':len(rows), 'summary':summary, 'comparison':comparison, 'stress':stress,
49             'contracted_ring':{'radius_m':1200., 'exact_cover_radius_m':ring_cover_radius(1200.),
50                               'radio_margin_m':1000-ring_cover_radius(1200.)}, 'runs':rows}
51     Path('results/enhancement_experiments.json').write_text(json.dumps(result,indent=2)+'\n')

```

```

52     print(json.dumps({k:v for k,v in result.items() if k not in ('runs','stress')},indent=2))
53
54
55 if __name__ == '__main__':
56     main()

```

Listing 24: Q3 环半径筛选与新世界确认

```

1  """Development and held-out sweep for the safe Q3 ring radius."""
2  from __future__ import annotations
3
4  import json
5  import math
6  import statistics
7  from pathlib import Path
8
9  from coverage import ring_cover_radius
10 from experiments import run_case
11
12 CANDIDATES = (1200.0, 1250.0, 1300.0, 1350.0, 1400.0,
13               1450.0, 1500.0, 1550.0)
14 DEV_SEEDS = range(1000000, 1000150)
15 HELD_OUT_SEEDS = range(2300000, 2300500)
16
17
18 def summarize(rows):
19     values = sorted(row["average_time_s"] for row in rows)
20     return {
21         "cases": len(rows),
22         "all_cleared_cases": sum(row["fraction_cleared"] == 1 for row in rows),
23         "mean_average_time_s": statistics.mean(values),
24         "median_average_time_s": statistics.median(values),
25         "p90_average_time_s": values[math.ceil(0.9 * len(values)) - 1],
26         "mean_distance_m": statistics.mean(row["distance_m"] for row in rows),
27         "mean_measures": statistics.mean(row["measures"] for row in rows),
28     }
29
30
31 def run_radius(radius, seeds):
32     cover = ring_cover_radius(radius)
33     if cover > 1000.0:
34         raise ValueError(f"unsafe candidate radius {radius}: cover={cover}")
35     rows = []
36     for seed in seeds:
37         row = run_case(seed, 3, "enhanced", ring_radius=radius,
38                       anchor_policy="nearest")
39         row.pop("real_duration_s") # Exclude wall-clock noise from geometry comparison.
40         rows.append(row)
41     return rows
42
43
44 def paired_summary(control, candidate):
45     assert [row["seed"] for row in control] == [row["seed"] for row in candidate]
46     deltas = [a["average_time_s"] - b["average_time_s"]
47               for a, b in zip(control, candidate, strict=True)]
48     mean = statistics.mean(deltas)
49     standard_error = statistics.stdev(deltas) / math.sqrt(len(deltas))
50     return {
51         "cases": len(deltas),
52         "mean_saved_s_per_source": mean,
53         "approx_95pct_ci_s": [mean - 1.96 * standard_error,
54                               mean + 1.96 * standard_error],
55         "faster_candidate_cases": sum(delta > 0 for delta in deltas),
56         "all_control_cleared_cases": sum(row["fraction_cleared"] == 1 for row in control),
57         "all_candidate_cleared_cases": sum(row["fraction_cleared"] == 1 for row in candidate),
58         "deltas_s_per_source": deltas,
59     }

```

```

60
61
62 def main():
63     development = {}
64     for radius in CANDIDATES:
65         rows = run_radius(radius, DEV_SEEDS)
66         development[str(radius)] = {
67             "ring_radius_m": radius,
68             "exact_cover_radius_m": ring_cover_radius(radius),
69             "summary": summarize(rows),
70             "runs": rows,
71         }
72     ordered = sorted(development,
73                       key=lambda key: development[key]["summary"]["mean_average_time_s"])
74     winner, runner_up = ordered[0], ordered[1]
75     held_out = {}
76     held_out_rows = {}
77     for radius in sorted({1200.0, float(winner), float(runner_up)}):
78         rows = run_radius(radius, HELD_OUT_SEEDS)
79         held_out_rows[str(radius)] = rows
80         held_out[str(radius)] = {
81             "ring_radius_m": radius,
82             "exact_cover_radius_m": ring_cover_radius(radius),
83             "summary": summarize(rows),
84             "runs": rows,
85         }
86     control = "1200.0" if winner != "1200.0" else runner_up
87     comparison = paired_summary(held_out_rows[control], held_out_rows[winner])
88     comparison.update({"control_ring_radius_m": float(control),
89                      "candidate_ring_radius_m": float(winner),
90                      "control_role": "incumbent" if control == "1200.0" else "development_runner_up"})
91     result = {
92         "evidence": "held_out_local_synthetic_not_official",
93         "selection": "Eight radii compared on existing development seeds; fresh confirmation seeds replace
94         exploratory reuse of 1100000..1100499. No retuning after confirmation.",
95         "total_runs": len(CANDIDATES) * len(DEV_SEEDS) + len(held_out_rows) * len(HELD_OUT_SEEDS),
96         "candidate_radii_m": list(CANDIDATES),
97         "development_seed_range": [DEV_SEEDS.start, DEV_SEEDS.stop - 1],
98         "held_out_seed_range": [HELD_OUT_SEEDS.start, HELD_OUT_SEEDS.stop - 1],
99         "development": development,
100        "development_winner_m": float(winner),
101        "development_runner_up_m": float(runner_up),
102        "held_out": held_out,
103        "held_out_comparison": comparison,
104    }
105    Path("results/ring_sweep.json").write_text(
106        json.dumps(result, ensure_ascii=False, indent=2) + "\n", encoding="utf-8"
107    )
108    print(json.dumps({
109        "total_runs": result["total_runs"],
110        "development_winner_m": float(winner),
111        "development_runner_up_m": float(runner_up),
112        "held_out_seed_range": result["held_out_seed_range"],
113        "held_out": {key: value["summary"] for key, value in held_out.items()},
114        "comparison": {key: value for key, value in comparison.items()
115                       if key != "deltas_s_per_source"},
116    }, indent=2))
117
118 if __name__ == "__main__":
119     main()

```

Listing 25: 增强几何及区间评分交叉验证

```

1 """Independent checks for ring contraction, 2-opt and interval probe bounds."""
2 from __future__ import annotations
3

```

```

4 import itertools
5 import json
6 import math
7 import random
8 from pathlib import Path
9
10 from active_policy_candidate import score_probes
11 from coverage import directional_waypoints, omni_waypoints, ring_cover_radius
12 from geometry import clip_bearing, enclosing_circle, initial_polygon
13 from route_policy_candidate import optimize_waypoints
14
15
16 def length(points, order, start):
17     sequence = [start] + [points[i] for i in order]
18     return sum(math.dist(a, b) for a, b in itertools.pairwise(sequence))
19
20
21 def main():
22     rng = random.Random(417072)
23     route_cases, interval_cases = 0, 0
24     for size in (0,1,2,7,31):
25         for _ in range(10):
26             points = [(rng.uniform(-2500,2500), rng.uniform(-2500,2500)) for _ in range(size)]
27             start = (rng.uniform(-1000,1000),rng.uniform(-1000,1000))
28             route = optimize_waypoints(points,start)
29             assert sorted(route) == list(range(size))
30             current, pending, greedy = start, set(range(size)), []
31             while pending:
32                 i = min(pending,key=lambda i:(math.dist(current,points[i]),i))
33                 greedy.append(i); pending.remove(i); current = points[i]
34                 assert length(points,route,start) <= length(points,greedy,start)+1e-7
35                 route_cases += 1
36     ring = omni_waypoints(1200.)
37     rho = ring_cover_radius(1200.)
38     for _ in range(2000):
39         r, phi = 1800*math.sqrt(rng.random()), rng.uniform(0,math.tau)
40         source = (r*math.cos(phi), r*math.sin(phi))
41         assert min(math.dist(source,p) for p in ring) <= rho + 1e-7
42         attained = min(math.dist((1800*math.cos(math.pi/6),1800*math.sin(math.pi/6)),p) for p in ring)
43         assert abs(attained-rho)<1e-7 and rho<1000
44     ring_tours = []
45     for d in (1200.0, 1550.0, 900.0 * math.sqrt(3.0)):
46         centers = omni_waypoints(d)[1:]
47         minimum = min(length(centers, order, (0.0, 0.0))
48                        for order in itertools.permutations(range(6)))
49         assert abs(minimum - 6 * d) < 1e-7
50         ring_tours.append({"radius_m": d, "permutations": 720,
51                           "minimum_length_m": minimum, "analytic_length_m": 6 * d})
52     vertex_cases = 0
53     for spacing in (900.0, 950.0, 990.0, 999.0):
54         vertices = directional_waypoints(spacing)
55         for source in vertices:
56             if math.hypot(*source) > 1800.0 + 1e-8:
57                 continue
58             for k in range(6):
59                 neighbor = (source[0] + spacing * math.cos(k * math.pi / 3),
60                           source[1] + spacing * math.sin(k * math.pi / 3))
61                 assert min(math.dist(neighbor, v) for v in vertices) < 1e-7
62             vertex_cases += 1
63     max_violation = -float('inf')
64     for bearing in (0., 89., 179., 359.99):
65         poly = clip_bearing(initial_polygon(),(0.,0.),bearing)
66         table = score_probes(poly,[(0.,0.),bearing]),(0.,0.),3,include_lens=False)
67         for row in table:
68             if not row['eligible']:
69                 continue
70             for angle in range(0,360,2):

```

```

71         post = clip_bearing(poly,row['point'],angle)
72         if not post:
73             continue
74         violation = enclosing_circle(post)[1] - row['positive_bearing_radius_upper_m']
75         max_violation = max(max_violation,violation)
76         assert violation <= 1e-6
77         interval_cases += 1
78     result = {'evidence':'numerical_sanity_plus_analytic_geometry_not_official',
79             'route_cases':route_cases, 'ring_samples':2000,
80             'ring_radius_m':1200., 'exact_ring_cover_radius_m':rho,
81             'attained_boundary_radius_m':attained, 'radio_margin_m':1000-rho,
82             'ring_tour_exhaustive':ring_tours,
83             'source_vertex_six_neighbor_cases':vertex_cases,
84             'candidate_posterior_cases':interval_cases, 'max_interval_bound_violation_m':max_violation}
85     Path('results/refinement_verification.json').write_text(json.dumps(result,indent=2)+'\n')
86     print(json.dumps(result,indent=2))
87
88
89 if __name__ == '__main__':
90     main()

```

Listing 26: 31 格点不可删反例验证

```

1  """Generate exact, auditable coverage-limit witnesses (Python 3.14).
2
3  No simulator is used: every assertion is a direct Euclidean calculation on the
4  31 points returned by ``coverage.directional_waypoints``. The JSON file is a
5  reproducible calculation artifact, not a hand-entered table.
6  """
7  from __future__ import annotations
8
9  import json
10 import math
11 import sys
12 from pathlib import Path
13
14 ROOT = Path(__file__).resolve().parent
15 sys.path.insert(0, str(ROOT))
16 import coverage
17
18 R = coverage.ARENA_RADIUS
19 Q = coverage.MIN_RADIO_RADIUS
20 S = coverage.DEFAULT_SPACING
21 EPS_CANDIDATES = (1.0,)
22
23 # Six nearest-neighbour directions in axial (i,j) coordinates.
24 DIRS = ((1, 0), (0, 1), (-1, 1), (-1, 0), (0, -1), (1, -1))
25
26 def xy(ij: tuple[int, int]) -> tuple[float, float]:
27     i, j = ij
28     return (S * (i + j / 2.0), S * math.sqrt(3.0) * j / 2.0)
29
30 def norm(p: tuple[float, float]) -> float:
31     return math.hypot(*p)
32
33 def sub(a: tuple[float, float], b: tuple[float, float]) -> tuple[float, float]:
34     return (a[0] - b[0], a[1] - b[1])
35
36 def dot(a: tuple[float, float], b: tuple[float, float]) -> float:
37     return a[0] * b[0] + a[1] * b[1]
38
39 def add(a: tuple[float, float], b: tuple[float, float]) -> tuple[float, float]:
40     return (a[0] + b[0], a[1] + b[1])
41
42 def scale(c: float, a: tuple[float, float]) -> tuple[float, float]:
43     return (c * a[0], c * a[1])
44

```

```

45
46 def actual_lattice() -> dict[tuple[int, int], tuple[float, float]]:
47     pts = coverage.directional_waypoints(S)
48     axial: dict[tuple[int, int], tuple[float, float]] = {}
49     for p in pts:
50         # Recover integer coordinates and verify the reconstruction, rather than
51         # silently substituting a separately hard-coded 31-point set.
52         j = round(p[1] / (S * math.sqrt(3.0) / 2.0))
53         i = round(p[0] / S - j / 2.0)
54         ij = (i, j)
55         assert math.dist(p, xy(ij)) < 1e-8
56         axial[ij] = p
57     assert len(axial) == 31
58     return axial
59
60 def witness_for(vij: tuple[int, int], points: dict[tuple[int, int], tuple[float, float]]) -> dict:
61     v = points[vij]
62     candidates = []
63     for k in range(6):
64         d1, d2 = DIRS[k], DIRS[(k + 1) % 6]
65         uij = (vij[0] + d1[0], vij[1] + d1[1])
66         wij = (vij[0] + d2[0], vij[1] + d2[1])
67         if uij not in points or wij not in points:
68             continue
69         m = scale(0.5, add(points[uij], points[wij]))
70         nvec = sub(v, m)
71         h = norm(nvec)
72         n = scale(1.0 / h, nvec)
73         for eps in EPS_CANDIDATES:
74             g = add(m, scale(eps, n))
75             if norm(g) >= R:
76                 continue
77             rows = []
78             for ij, p in points.items():
79                 distance = norm(sub(p, g))
80                 forward = dot(sub(p, g), n)
81                 rows.append((ij, distance, forward))
82             reachable = [row for row in rows if row[1] <= Q + 1e-8 and row[2] >= -1e-8]
83             if len(reachable) == 1 and reachable[0][0] == vij:
84                 candidates.append((eps, m, n, g, rows, uij, wij))
85             break
86     assert candidates, f"no elementary witness for {vij}"
87     eps, m, n, g, rows, uij, wij = min(candidates, key=lambda z: (z[0], z[1]))
88     target_distance = norm(sub(v, g))
89     second = min(norm(sub(p, g)) for ij, p in points.items() if ij != vij)
90     reachable = sorted((dist, ij) for ij, dist, fw in rows if dist <= Q + 1e-8 and fw >= -1e-8)
91     assert reachable[0][1] == vij and len(reachable) == 1
92     return {"solevertex": list(vij), "target": list(vij), "edge_neighbors": [list(uij), list(wij)],
93           "midpoint": list(m), "epsilon": eps, "source": list(g), "n": list(n),
94           "normal": list(n), "source_radius": norm(g),
95           "target_distance": target_distance, "second_detector_distance": second,
96           "reachable": [[list(ij), dist] for dist, ij in reachable],
97           "min_other_forward": min(fw for ij, dist, fw in rows if ij != vij),
98           "midpoint_to_nearest_other_positive": min(norm(sub(p, m)) for ij, p in points.items()
99               if ij not in (uij, wij, vij) and dot(sub(p, m), n) > 1e
100               -8)}
101
102 def main() -> None:
103     points = actual_lattice()
104     witnesses = [witness_for(ij, points) for ij in sorted(points)]
105     for w in witnesses:
106         assert w["source_radius"] < R and w["target_distance"] <= Q
107         assert len(w["reachable"]) == 1
108         assert w["second_detector_distance"] > 5.0
109     optimal_d = math.hypot(R, Q)
110     half_angle = math.atan(Q / R)
111     attained_angle = math.acos(R / optimal_d)

```

```

111     assert abs(attained_angle - half_angle) < 1e-12
112     for i in range(1001):
113         d = R + i * Q / 1000
114         cos_limit = max(R / d, (d*d + R*R - Q*Q) / (2*d*R))
115         assert math.acos(min(1.0, cos_limit)) <= half_angle + 1e-12
116     result = {"parameters": {"arena_radius": R, "receive_radius": Q,
117                             "spacing": S, "point_count": len(points)},
118              "q3_boundary_angle_lower_bound": {"q": 900.0, "minimum_points": 7,
119                  "half_angle_radians": math.asin(900.0 / R),
120                  "reason": "six arcs have total angular capacity 2*pi only at equality; equality ring misses
121                  origin"},
122              "q1000_static_seven_irreducible": {"minimum_fixed_subset": 7,
123                  "boundary_arc_capacity_of_five": 10.0 * math.asin(Q / R),
124                  "origin_to_ring": 900.0 * math.sqrt(3.0)},
125              "q4_global_outer_boundary_lower_bound": {"minimum_outer_detectors": 7,
126                  "half_angle_radians": math.atan(Q / R),
127                  "optimal_detector_radius": optimal_d,
128                  "attained_half_angle_radians": attained_angle,
129                  "checked_detector_radaii": 1001,
130                  "statement": "lower bound for arbitrary placements at an outward boundary source; not a 31-
131                  point global optimum claim"},
132              "witnesses": witnesses}
133     out = ROOT / "results" / "coverage_limits.json"
134     out.parent.mkdir(exist_ok=True)
135     out.write_text(json.dumps(result, indent=2, sort_keys=True) + "\n", encoding="utf-8")
136
137 if __name__ == "__main__":
138     main()

```

Listing 27: 增强策略图表生成

```

1  """Generate enhancement-only paper assets from saved local experiment evidence.
2
3  Run from any directory with conda run -n py314 python <path>/make_enhancement_assets.py.
4  No planner, simulator, hidden world, or source file is loaded or executed.
5  """
6  from __future__ import annotations
7
8  import hashlib
9  import json
10 import math
11 import os
12 import statistics
13 import tempfile
14 from collections import defaultdict
15 from io import BytesIO
16 from pathlib import Path
17
18 import matplotlib
19
20 matplotlib.use("Agg")
21 import matplotlib.pyplot as plt
22 from matplotlib.lines import Line2D
23 from matplotlib.patches import Circle
24
25 ROOT = Path(__file__).resolve().parent
26 GENERATED = ROOT / "report" / "generated"
27 FIGURES = ROOT / "report" / "figures"
28 WIDTH = 16 / 2.54
29 POLICIES = ("integrated", "enhanced")
30 SCENARIOS = ("minimum_radius", "outward_boundary", "clustered")
31 MODES = ("smooth", "extreme", "iid_location")
32 COLORS = ("0072B2", "D55E00")
33
34
35 def require(condition, message):
36     if not condition:

```

```

37         raise ValueError(message)
38
39
40 def close(actual, expected, name, tolerance=1e-8):
41     require(math.isfinite(actual) and math.isfinite(expected), f"{name}: nonfinite value")
42     require(math.isclose(actual, expected, rel_tol=1e-10, abs_tol=tolerance),
43             f"{name}: {actual!r} != {expected!r}")
44
45
46 def number(value):
47     require(math.isfinite(value), "Nonfinite table value")
48     return f"{value:.2f}"
49
50
51 def load(name):
52     return json.loads((ROOT / "results" / name).read_text(encoding="utf-8"))
53
54
55 def atomic_bytes(path, content):
56     require(path.parent in (GENERATED, FIGURES), "Output outside owned directories")
57     path.parent.mkdir(parents=True, exist_ok=True)
58     fd, temporary = tempfile.mkstemp(prefix="." + path.name + ".", dir=path.parent)
59     try:
60         with os.fdopen(fd, "wb") as stream:
61             stream.write(content)
62         os.replace(temporary, path)
63     finally:
64         Path(temporary).unlink(missing_ok=True)
65
66
67 def table(name, headers, rows, widths, left_columns=(0, 1)):
68     """Fixed-width booktabs tabular only; the parent paper owns all captions."""
69     require(len(headers) == len(widths), "Invalid table widths")
70     require(sum(widths) + 0.14 * (len(widths) - 1) <= 15.9, "Table exceeds 16 cm")
71     columns = []
72     for index, width in enumerate(widths):
73         align = r"\raggedright" if index in left_columns else r"\raggedleft"
74         columns.append(">{" + align + r"\arraybackslash}p{" + str(width) + "cm}")
75     specification = "@{" + r"@{\hspace{0.14cm}}".join(columns) + "@{"
76     lines = [r"\begin{tabular}" + specification + "}", r"\toprule",
77             " & ".join(headers) + r" \\", r"\midrule"]
78     for row in rows:
79         require(len(row) == len(headers), "Ragged table")
80         lines.append(" & ".join(str(item) for item in row) + r" \\")
81     lines.extend((r"\bottomrule", r"\end{tabular}"))
82     atomic_bytes(GENERATED / name, (r"\n".join(lines) + r"\n").encode("utf-8"))
83
84
85 def save_figure(fig, name):
86     buffer = BytesIO()
87     fig.savefig(buffer, format="pdf", metadata={"CreationDate": None, "ModDate": None,
88                                               "Creator": "make_enhancement_assets.py"})
89     atomic_bytes(FIGURES / name, buffer.getvalue())
90     plt.close(fig)
91
92
93 def check_run(row):
94     for key in ("n_sources", "n_cleared", "measures", "switches", "clear_attempts", "failed_clears"):
95         require(type(row[key]) is int and row[key] >= 0, f"Invalid {key}")
96     n = row["n_sources"]
97     require(n > 0 and row["n_cleared"] <= n, "Invalid per-world denominator")
98     require(row["clear_attempts"] == row["n_cleared"] + row["failed_clears"],
99             "Clear-attempt decomposition mismatch")
100     require(row["distance_m"] >= 0, "Negative distance")
101     close(row["fraction_cleared"], row["n_cleared"] / n, "Clear fraction")
102     close(row["average_time_s"], row["virtual_time_s"] / n, "Per-world average")
103     total = (row["distance_m"] / 5 + 5 * row["measures"] + row["switches"])

```

```

104         + 3 * row["failed_clears"] + 5 * row["n_cleared"])
105     # Each accepted measurement/clear rounds its movement charge to microseconds.
106     rounding_bound = 0.5e-6 * (row["measures"] + row["clear_attempts"]) + 1e-8
107     close(total, row["virtual_time_s"], "Independent cost identity", tolerance=rounding_bound)
108
109
110 def metrics(rows):
111     require(bool(rows), "Empty group")
112     values = sorted(row["average_time_s"] for row in rows)
113     return {"cases": len(rows),
114            "all_cleared_cases": sum(r["n_cleared"] == r["n_sources"] for r in rows),
115            "mean_average_time_s": statistics.mean(values),
116            "median_average_time_s": statistics.median(values),
117            "p90_average_time_s": values[math.ceil(0.9 * len(values)) - 1]}
118
119
120 def check_summary(actual, summary, name):
121     for key, value in actual.items():
122         close(value, summary[key], f"{name}/{key}")
123
124
125 def paired(control, enhanced):
126     require([r["seed"] for r in control] == [r["seed"] for r in enhanced], "Unpaired seeds")
127     for a, b in zip(control, enhanced):
128         require(all(a[key] == b[key] for key in
129                    ("problem", "scenario", "error_mode", "n_sources")), "Unpaired world metadata")
130     delta = [a["average_time_s"] - b["average_time_s"] for a, b in zip(control, enhanced)]
131     mean = statistics.mean(delta)
132     return delta, {"cases": len(delta), "mean_saved_s_per_source": mean,
133                  "mean_reduction_pct": 100 * mean / metrics(control)["mean_average_time_s"],
134                  "faster_cases": sum(value > 0 for value in delta)}
135
136
137 def load_enhancement():
138     data = load("enhancement_experiments.json")
139     require(data["main_seed_range"] == [1100000, 1100499], "Unexpected held-out seeds")
140     require(data["stress_seed_range"] == [1110000, 1110029], "Unexpected pressure seeds")
141     groups = defaultdict(list)
142     for row in data["runs"]:
143         check_run(row)
144         require(row["strategy"] in POLICIES, "Unexpected enhancement policy")
145         groups[(row["problem"], row["scenario"], row["error_mode"], row["strategy"])].append(row)
146     expected = {(q, scenario, mode, policy) for q in (3, 4) for policy in POLICIES
147                for scenario, mode in [("random", "smooth")] +
148                [(s, m) for s in SCENARIOS for m in MODES]}
149     require(set(groups) == expected, "Missing or extra enhancement groups")
150     for key, rows in groups.items():
151         rows.sort(key=lambda r: r["seed"])
152         start, end = data["main_seed_range"] if key[1] == "random" else data["stress_seed_range"]
153         require([r["seed"] for r in rows] == list(range(start, end + 1)),
154                f"{key}: incomplete or duplicate seeds")
155     require(len(data["runs"]) == data["total_runs"] == 3080, "Run total mismatch")
156     require(set(data["summary"]) == {f"Q{q}_{p}" for q in (3, 4) for p in POLICIES},
157            "Unexpected main summary groups")
158     require(set(data["comparison"]) == {"Q3", "Q4"}, "Unexpected main comparisons")
159     require(set(data["stress"]) == {f"Q{q}_{s}_{m}" for q in (3, 4)
160                                    for s in SCENARIOS for m in MODES}, "Expected 18 pressure groups")
161
162     for q in (3, 4):
163         controls = groups[q, "random", "smooth", "integrated"]
164         enhancements = groups[q, "random", "smooth", "enhanced"]
165         for policy in POLICIES:
166             check_summary(metrics(groups[q, "random", "smooth", policy]),
167                           data["summary"][f"Q{q}_{policy}"], f"Q{q}/{policy}")
168             check_summary(paired(controls, enhancements)[1], data["comparison"][f"Q{q}"], f"Q{q}/paired")
169         for scenario in SCENARIOS:
170             for mode in MODES:
171                 key = f"Q{q}_{scenario}_{mode}"

```

```

171         for policy in POLICIES:
172             check_summary(metrics(groups[q, scenario, mode, policy]),
173                             data["stress"][key][policy], key + "/" + policy)
174             check_summary(paired(*(groups[q, scenario, mode, p] for p in POLICIES))[1],
175                             data["stress"][key]["paired"], key + "/paired")
176     return data, groups
177
178
179 def enhancement_tables(data, groups):
180     performance_rows, cost_rows, macros = [], [], []
181     for q, word in ((3, "Three"), (4, "Four")):
182         control, enhanced = (groups[q, "random", "smooth", p] for p in POLICIES)
183         for policy, rows in zip(POLICIES, (control, enhanced)):
184             stats = metrics(rows)
185             label = "原集成" if policy == "integrated" else "增强"
186             performance_rows.append((f"Q{q}", label,
187                                     number(stats["mean_average_time_s"]),
188                                     number(stats["median_average_time_s"]),
189                                     number(stats["p90_average_time_s"]),
190                                     f'{stats["all_cleared_cases"]}/{stats["cases"]}')
191                                     # Average each world's cost/N; never divide pooled costs by pooled N.
192                                     components = [statistics.mean(value(r) / r["n_sources"] for r in rows)
193                                                     for value in (lambda r: r["distance_m"] / 5,
194                                                                lambda r: 5 * r["measures"], lambda r: r["switches"],
195                                                                lambda r: 3 * r["failed_clears"], lambda r: 5 * r["n_cleared"])]])
196             rounding_bound = statistics.mean(
197                 (0.5e-6 * (r["measures"] + r["clear_attempts"]) + 1e-8) / r["n_sources"]
198                 for r in rows)
199             close(sum(components), stats["mean_average_time_s"], "Mean cost identity", tolerance=rounding_bound)
200
201             cost_rows.append((f"Q{q}", label, *(number(v) for v in components),
202                             number(stats["mean_average_time_s"])))
203             comparison = paired(control, enhanced)[1]
204             macros.extend(((f"EnhancedQ{word}Time", number(metrics(enhanced)["mean_average_time_s"])),
205                             (f"EnhancedQ{word}Gain", number(comparison["mean_reduction_pct"]))))
206             macros.extend(((f"EnhancementRuns", str(len(data["runs"]))),
207                             (f"ContractedRadius", number(data["contracted_ring"]["radius_m"]))))
208             atomic_bytes(GENERATED / "enhancement_numbers.tex",
209                           ("% Gains are percentage reductions of paired-group mean T/N.\n" +
210                            "\n".join("\newcommand{" + key + "}" + value + "}" for key, value in macros)
211                            + "\n").encode("utf-8"))
212             table("enhancement_table.tex", ("问题", "策略", "均值/s", "中位数/s", "$P_{90}$s", "全清/世界"),
213                 performance_rows, (0.9, 1.7, 2.6, 2.6, 2.6, 2.6))
214             table("enhancement_costs.tex", ("问题", "策略", "$L/(5N)$", "$5M/N$", "$S/N$", "$3F/N$", "$5K/N$", "合计/s"),
215                 cost_rows, (0.9, 1.5, 2.1, 1.8, 1.7, 1.7, 1.7, 2.1))
216             scenario_labels = {"minimum_radius": "最小半径", "outward_boundary": "边界朝外", "clustered": "聚集"}
217             mode_labels = {"smooth": "平滑", "extreme": "极端", "iid_location": "位置独立"}
218             pressure_rows = []
219             for q in (3, 4):
220                 for scenario in SCENARIOS:
221                     for mode in MODES:
222                         control, enhanced = (groups[q, scenario, mode, p] for p in POLICIES)
223                         comparison = paired(control, enhanced)[1]
224                         both_clear = sum(a["n_cleared"] == a["n_sources"] and b["n_cleared"] == b["n_sources"]
225                                         for a, b in zip(control, enhanced))
226                         pressure_rows.append((f"Q{q}", scenario_labels[scenario], mode_labels[mode],
227                                             number(metrics(control)["mean_average_time_s"]),
228                                             number(metrics(enhanced)["mean_average_time_s"]),
229                                             number(comparison["mean_saved_s_per_source"]),
230                                             f'{comparison["faster_cases"]}/{len(control)}',
231                                             f'{both_clear}/{len(control)}'))
232             table("enhancement_stress.tex", ("问题", "场景", "误差", "原集成/s", "增强/s", "节省/s", "更快/对", "双全清/对"),
233                 pressure_rows, (0.8, 1.7, 1.7, 2.1, 2.1, 2.1, 1.6, 2.0), left_columns=(0, 1, 2))
234

```

```

235 def candidate_table():
236     static = load("route_candidate_comparison.json")
237     adaptive = load("adaptive_candidate_comparison.json")
238     require(set(static["summary"]) == set(adaptive["summary"]) == {"Q3", "Q4"},
239             "Unexpected candidate problems")
240     static_start, static_end = static["seed_range"]
241     adaptive_start, adaptive_end = adaptive["seed_range"]
242     require(type(static_start) is int and type(static_end) is int and static_end >= static_start,
243             "Invalid static seed range")
244     require(type(adaptive_start) is int and type(adaptive_end) is int and adaptive_end >= adaptive_start,
245             "Invalid adaptive seed range")
246     static_count, adaptive_count = static_end - static_start + 1, adaptive_end - adaptive_start + 1
247     static_groups = defaultdict(list)
248     for pair in static.get("runs", []):
249         require(pair["problem"] in (3, 4), "Unexpected static problem")
250         nearest, two_opt = pair["nearest"], pair["two_opt"]
251         check_run(nearest)
252         check_run(two_opt)
253         require(nearest["seed"] == two_opt["seed"] == pair["seed"]
254                 and nearest["problem"] == two_opt["problem"] == pair["problem"],
255                 "Static pair metadata mismatch")
256         static_groups[pair["problem"]].append(pair)
257     adaptive_groups = defaultdict(list)
258     for pair in adaptive.get("runs", []):
259         require(pair["problem"] in (3, 4), "Unexpected adaptive problem")
260         for policy in ("fixed", "adaptive"):
261             row = pair[policy]
262             check_run(row)
263             require(row["seed"] == pair["seed"] and row["problem"] == pair["problem"],
264                     "Adaptive pair metadata mismatch")
265             adaptive_groups[pair["problem"]].append(pair)
266     rows = []
267     for q in (3, 4):
268         pairs = sorted(static_groups[q], key=lambda p: p["seed"])
269         require([p["seed"] for p in pairs] == list(range(static_start, static_end + 1)),
270                 "Static seed mismatch")
271         nearest = [p["nearest"] for p in pairs]
272         two_opt = [p["two_opt"] for p in pairs]
273         deltas = [a["average_time_s"] - b["average_time_s"]
274                  for a, b in zip(nearest, two_opt)]
275         s = {"cases": static_count,
276              "all_nearest_cleared": sum(a["fraction_cleared"] == 1 for a in nearest),
277              "all_two_opt_cleared": sum(b["fraction_cleared"] == 1 for b in two_opt),
278              "nearest_mean_s_per_source": statistics.mean(a["average_time_s"] for a in nearest),
279              "two_opt_mean_s_per_source": statistics.mean(b["average_time_s"] for b in two_opt),
280              "mean_saved_s_per_source": statistics.mean(deltas),
281              "faster_cases": sum(d > 0 for d in deltas)}
282         for key, value in s.items():
283             if key in static["summary"][f"Q{q}"]:
284                 close(value, static["summary"][f"Q{q}"][key], f"Static Q{q}/{key}")
285         close(s["nearest_mean_s_per_source"] - s["two_opt_mean_s_per_source"],
286              s["mean_saved_s_per_source"], "Static mean difference")
287         rows.append((f"Q{q}", "静态2-opt", number(s["nearest_mean_s_per_source"]),
288                     number(s["two_opt_mean_s_per_source"]), number(s["mean_saved_s_per_source"]),
289                     f'{s["faster_cases"]}/{static_count}',
290                     f'{s["all_nearest_cleared"]}/{s["all_two_opt_cleared"]}'))
291     pairs = sorted(adaptive_groups[q], key=lambda p: p["seed"])
292     require([p["seed"] for p in pairs] == list(range(adaptive_start, adaptive_end + 1)),
293             "Adaptive seed mismatch")
294     fixed, adapted = [p["fixed"] for p in pairs], [p["adaptive"] for p in pairs]
295     fixed_metrics, adapted_metrics = metrics(fixed), metrics(adapted)
296     delta, comparison = paired(fixed, adapted)
297     actual = {"cases": len(pairs), "fixed_all_cleared": fixed_metrics["all_cleared_cases"],
298              "adaptive_all_cleared": adapted_metrics["all_cleared_cases"],
299              "fixed_mean_s_per_source": fixed_metrics["mean_average_time_s"],
300              "adaptive_mean_s_per_source": adapted_metrics["mean_average_time_s"],
301              "mean_saved_s_per_source": comparison["mean_saved_s_per_source"],

```

```

302         "median_saved_s_per_source": statistics.median(delta),
303         "faster_cases": comparison["faster_cases"]}]
304     check_summary(actual, adaptive["summary"][f"Q{q}"], f"Adaptive Q{q}")
305     rows.append((f"Q{q}", "自适应探测", number(actual["fixed_mean_s_per_source"]),
306                 number(actual["adaptive_mean_s_per_source"]), number(actual["mean_saved_s_per_source"]),
307                 f'{actual["faster_cases"]}/{adaptive_count}',
308                 f'{actual["fixed_all_cleared"]}/{actual["adaptive_all_cleared"]}'))
309 table("candidate_table.tex", ("问题", "候选", "对照/s", "候选/s", "节省/s", "更快/对", "全清数\\newline 对照/
    候选"),
310     rows, (0.8, 2.4, 2.1, 2.1, 2.1, 1.9, 2.6))
311
312
313 def coverage_limits_table():
314     certificate = load("coverage_limits.json")
315     witnesses = certificate["witnesses"]
316     require(len(witnesses) == certificate["parameters"]["point_count"] == 31,
317            "Witness count mismatch")
318     target_distances = [row["target_distance"] for row in witnesses]
319     other_distances = [row["second_detector_distance"] for row in witnesses]
320     rows = [
321         ("Q3 q=900 lower bound", "7", "six boundary arcs at equality; origin uncovered"),
322         ("Q3 fixed seven-set at q=1000", "7", "five ring arcs leave a boundary gap"),
323         ("Q4 outer-boundary lower bound", "7", "arbitrary placements; outer detectors only"),
324         ("Q4 current lattice witnesses", str(len(witnesses)),
325          f"target d={min(target_distances):.3f}--{max(target_distances):.3f} m"),
326         ("Q4 nearest other lattice point", f"{min(other_distances):.3f} m",
327          "every witness remains outside near threshold"),
328     ]
329     table("coverage_limits_table.tex", ("Statement", "Value", "Interpretation"), rows,
330         (4.1, 2.0, 8.7), left_columns=(0, 2))
331
332
333 def ring_sweep_table():
334     data = load("ring_sweep.json")
335     require(data["development_seed_range"] == [1000000, 1000149], "Ring development seeds")
336     require(data["held_out_seed_range"] == [23000000, 2300499], "Ring fresh confirmation seeds")
337     candidates = data["candidate_radii_m"]
338     require(candidates == [1200., 1250., 1300., 1350., 1400., 1450., 1500., 1550.],
339            "Unexpected frozen ring candidates")
340     count = 0
341     for phase, seed_key in (("development", "development_seed_range"),
342                            ("held_out", "held_out_seed_range")):
343         start, end = data[seed_key]
344         for key, group in data[phase].items():
345             runs = group["runs"]
346             require([r["seed"] for r in runs] == list(range(start, end + 1)), "Ring paired seeds")
347             count += len(runs)
348             radius = float(key)
349             envelope = max(radius / math.sqrt(3),
350                            math.sqrt(1800**2 + radius**2 - math.sqrt(3) * 1800 * radius))
351             close(envelope, group["exact_cover_radius_m"], "Ring envelope")
352             require(envelope < 1000, "Unsafe ring candidate")
353             for row in runs:
354                 check_run(row)
355                 require(row["problem"] == 3 and row["strategy"] == "enhanced"
356                        and row["scenario"] == "random" and row["error_mode"] == "smooth",
357                        "Ring world contract")
358                 close(row["ring_radius_m"], radius, "Ring run geometry")
359                 require(row["certificate_complete"] and row["timing_independently_verified"]
360                        and row["n_cleared"] == row["n_sources"], "Incomplete ring run")
361             check_summary(metrics(runs), group["summary"], "Ring summary")
362             require(count == data["total_runs"] == 2200, "Ring run denominator")
363             ordered = sorted(data["development"], key=lambda k:
364                             data["development"][k]["summary"]["mean_average_time_s"])
365             winner, runner_up = ordered[:2]
366             close(float(winner), data["development_winner_m"], "Ring development winner")
367             close(float(runner_up), data["development_runner_up_m"], "Ring runner-up")

```

```

368 control = "1200.0" if winner != "1200.0" else runner_up
369 comparison = data["held_out_comparison"]
370 close(comparison["candidate_ring_radius_m"], float(winner), "Ring candidate")
371 close(comparison["control_ring_radius_m"], float(control), "Ring control")
372 deltas, calculated = paired(data["held_out"][control]["runs"], data["held_out"][winner]["runs"])
373 require(deltas == comparison["deltas_s_per_source"], "Ring raw paired deltas")
374 require(comparison["faster_candidate_cases"] == calculated["faster_cases"], "Ring win count")
375 close(calculated["mean_saved_s_per_source"], comparison["mean_saved_s_per_source"], "Ring mean")
376 se = statistics.stdev(deltas) / math.sqrt(len(deltas))
377 for observed, expected in zip(comparison["approx_95pct_ci_s"],
378                               (statistics.mean(deltas) - 1.96 * se,
379                                statistics.mean(deltas) + 1.96 * se), strict=True):
380     close(observed, expected, "Ring paired CI")
381 rows = []
382 for radius in candidates:
383     key = str(float(radius))
384     group = data["development"][key]
385     held = data["held_out"].get(key)
386     rows.append((f"{radius:.0f}", number(group["exact_cover_radius_m"]),
387                number(group["summary"]["mean_average_time_s"]),
388                number(held["summary"]["mean_average_time_s"]) if held else "--",
389                number(comparison["mean_saved_s_per_source"]) if key == winner else "--",
390                "保留" if key == winner else ("次优" if key == runner_up else "")))
391 table("ring_sweep_table.tex", ("环半径/m", "解析覆盖/m", "开发T/N", "新样本T/N", "相对对照节省/s", "选择"),
392       rows, (1.5, 2.2, 2.0, 2.1, 2.6, 1.0), left_columns=(5,))
393 macros = {
394     "RingSelectedTime": number(data["held_out"][winner]["summary"]["mean_average_time_s"]),
395     "RingControlTime": number(data["held_out"][control]["summary"]["mean_average_time_s"]),
396     "RingSaving": f'{{comparison["mean_saved_s_per_source"]:.3f}}',
397     "RingLowerCI": f'{{comparison["approx_95pct_ci_s"][0]:.3f}}',
398     "RingUpperCI": f'{{comparison["approx_95pct_ci_s"][1]:.3f}}',
399     "RingFaster": str(comparison["faster_candidate_cases"]),
400 }
401 atomic_bytes(GENERATED / "ring_numbers.tex", "".join(
402     "\\newcommand{\\{} + key + "\\}{" + value + "\\}\\n" for key, value in macros.items()).encode())
403
404
405 def geometry_figure(data, groups):
406     certificate = load("coverage_limits.json")
407     arena = certificate["parameters"]["arena_radius"]
408     radio = certificate["parameters"]["receive_radius"]
409     legacy = certificate["q1000_static_seven_irreducible"]["origin_to_ring"]
410     contracted = data["contracted_ring"]
411     radius = contracted["radius_m"]
412     for policy, expected in (("integrated", legacy), ("enhanced", radius)):
413         for row in groups[3, "random", "smooth", policy]:
414             close(row["ring_radius_m"], expected, "Ring geometry/run mismatch")
415     def exact_cover(r):
416         return max(r / math.sqrt(3), math.sqrt(arena**2 + r**2 - math.sqrt(3) * arena * r))
417     q = exact_cover(radius)
418     close(q, contracted["exact_cover_radius_m"], "Contracted cover radius")
419     close(radius - q, contracted["radio_margin_m"], "Contracted radial distance margin")
420     fig, axes = plt.subplots(1, 2, figsize=(WIDTH, 4.5))
421     fig.subplots_adjust(left=0.10, right=0.99, bottom=0.37, top=0.85, wspace=0.30)
422     for ax, r, color, title in zip(axes, (legacy, radius), COLORS, ("Integrated", "Contracted")):
423         centers = [(0., 0.)] + [(r * math.cos(k * math.pi / 3), r * math.sin(k * math.pi / 3))
424                                for k in range(6)]
425         for x, y in centers:
426             ax.add_patch(Circle((x / 1000, y / 1000), radio / 1000,
427                                facecolor=color, edgecolor=color, alpha=0.12, linewidth=0.8))
428             if title == "Contracted":
429                 ax.add_patch(Circle((x / 1000, y / 1000), q / 1000, fill=False,
430                                    edgecolor=color, linestyle="--", linewidth=0.7))
431     ax.add_patch(Circle((0, 0), arena / 1000, fill=False, color="black", linewidth=1.1))
432     ax.scatter([x / 1000 for x, _ in centers], [y / 1000 for _, y in centers],
433               color=color, s=16, zorder=4)
434     boundary = (arena * math.cos(math.pi / 6), arena * math.sin(math.pi / 6))

```

```

435     ax.plot([r / 1000, boundary[0] / 1000], [0, boundary[1] / 1000], color="black", linewidth=1.1)
436     ax.plot(boundary[0] / 1000, boundary[1] / 1000, "kx", markersize=5)
437     ax.set(xlim=(-2.7, 2.7), ylim=(-2.7, 2.7), xlabel="x (km)", ylabel="y (km)",
438           title=f"{title}\nr = {r:.2f} m")
439     ax.set_xticks((-2, 0, 2))
440     ax.set_yticks((-2, 0, 2))
441     ax.set_aspect("equal")
442     ax.grid(alpha=0.15)
443     ax.text(0.5, -0.27, f"q = {exact_cover(r):.2f} m\nmargin = {radio-exact_cover(r):.2f} m",
444            transform=ax.transAxes, ha="center", va="top", fontsize=10)
445     handles = [Line2D([], [], color="black", label="Source arena"),
446               Line2D([], [], color=COLORS[0], alpha=0.5, label=f"Radio: {radio:.0f} m"),
447               Line2D([], [], color=COLORS[1], linestyle="--", label=f"Cover: {q:.2f} m (right)")]
448     fig.legend(handles=handles, loc="lower center", bbox_to_anchor=(0.5, 0.005),
449              ncol=1, frameon=False, fontsize=10)
450     save_figure(fig, "enhancement_geometry.pdf")
451
452
453 def ecdf(ax, values, **kwargs):
454     ordered = sorted(values)
455     require(bool(ordered), "Empty ECDF")
456     ax.step([ordered[0]] + ordered, [0.] + [(i + 1) / len(ordered) for i in range(len(ordered))],
457            where="post", **kwargs)
458
459
460 def performance_figure(groups):
461     fig, axes = plt.subplots(2, 2, figsize=(WIDTH, 5.8), sharey=True)
462     fig.subplots_adjust(left=0.11, right=0.98, top=0.93, bottom=0.14, hspace=0.56, wspace=0.34)
463     for column, q in enumerate((3, 4)):
464         control, enhanced = (groups[q, "random", "smooth", p] for p in POLICIES)
465         delta, _ = paired(control, enhanced)
466         ax = axes[0, column]
467         ecdf(ax, delta, color=COLORS[column], linewidth=1.5)
468         ax.axvline(0, color="0.4", linestyle="--", linewidth=0.8)
469         ax.set(title=f"Q{q}: paired savings", xlabel="Integrated - enhanced (s/source)")
470         ax = axes[1, column]
471         for rows, color, label in zip((control, enhanced), COLORS, ("Integrated", "Enhanced")):
472             ecdf(ax, [r["average_time_s"] for r in rows], color=color, linewidth=1.5, label=label)
473         ax.set(title=f"Q{q}: time distributions", xlabel="T/N (s/source)")
474     for ax in axes.flat:
475         ax.set_ylim(0, 1.02)
476         ax.set_yticks((0, 0.5, 1))
477         ax.grid(alpha=0.18)
478         ax.tick_params(axis="x", labelrotation=0)
479     for ax in axes[:, 0]:
480         ax.set_ylabel("Empirical probability")
481     handles, labels = axes[1, 0].get_legend_handles_labels()
482     fig.legend(handles, labels, loc="lower center", ncol=2, frameon=False, bbox_to_anchor=(0.5, 0.015))
483     save_figure(fig, "enhancement_performance.pdf")
484
485
486 def main():
487     plt.rcParams.update({"font.family": "DejaVu Sans", "font.size": 10,
488                        "axes.titlesize": 10, "axes.labelsize": 10,
489                        "xtick.labelsize": 10, "ytick.labelsize": 10,
490                        "legend.fontsize": 10, "pdf.fonttype": 42,
491                        "savefig.transparent": False, "figure.facecolor": "white"})
492     data, groups = load_enhancement()
493     enhancement_tables(data, groups)
494     candidate_table()
495     coverage_limits_table()
496     ring_sweep_table()
497     geometry_figure(data, groups)
498     performance_figure(groups)
499     print(f"Generated enhancement assets from {len(data['runs'])} saved runs; "
500           "raw candidate pairs and ring sweep validated. No simulator executed.")
501     input_names = ("enhancement_experiments.json", "route_candidate_comparison.json",

```

```

502         "adaptive_candidate_comparison.json", "coverage_limits.json",
503         "ring_sweep.json", "refinement_verification.json", "anchor_development.json")
504     output_names = ("enhancement_numbers.tex", "enhancement_table.tex", "enhancement_costs.tex",
505                    "enhancement_stress.tex", "candidate_table.tex", "coverage_limits_table.tex",
506                    "ring_sweep_table.tex", "ring_numbers.tex", "enhancement_geometry.pdf", "
507                    enhancement_performance.pdf")
508     metadata = {
509         "evidence": "held_out_local_synthetic_not_official",
510         "policy": {"Q3": "enhanced ring radius 1200m selected by a development-only sweep, nearest anchor",
511                   "Q4": "enhanced 990m triangular lattice, rolling remaining-anchor route",
512                   "probe": "fixed probe and bounded recovery; adaptive candidate is negative control"},
513         "input_sha256": {"results/" + name: hashlib.sha256((ROOT / "results" / name).read_bytes()).hexdigest()
514                          for name in input_names},
515         "outputs": list(output_names),
516         "main_seed_range": data["main_seed_range"],
517         "stress_seed_range": data["stress_seed_range"],
518         "total_runs": data["total_runs"],
519         "ring_sweep_runs": 2200,
520         "ring_confirmation_seed_range": [2300000, 2300499],
521         "metric": "per-world T/N; paired savings are control minus enhanced",
522         "official_calls": 0,
523         "reproducibility": "Generated after validating every raw run, paired seed and cost decomposition",
524     }
525     atomic_bytes(GENERATED / "enhancement_metadata.json",
526                  (json.dumps(metadata, ensure_ascii=False, indent=2) + "\n").encode("utf-8"))
527
528 if __name__ == "__main__":
529     main()

```

Listing 28: 25 点极坐标覆盖候选与解析证书

```

1  """Independent Q4 polar discovery candidates; no planner/default integration.
2
3  The certificate is an analytic triangulation, not a sampled coverage result.
4  Each unresolved channel must still complete every waypoint obligation.  Returned
5  coordinates approximate the ideal real construction; the certificate explicitly
6  allows a bounded Euclidean error at each commanded measurement location.
7  """
8
9  from __future__ import annotations
10
11  import math
12
13  Point = tuple[float, float]
14
15
16  def _parameters(variant: str) -> tuple[float, float, float, float, float]:
17      if variant == "seed25":
18          return 990.0, 1865.0, 1.0, 0.25, 990.0
19      if variant == "compact25":
20          return 940.0, 1870.0, 5.0, 1.0, 993.0
21      if variant == "fast25":
22          return 928.0, 1865.0, 1.0, 0.75, 998.25
23      raise ValueError("variant must be 'seed25', 'compact25' or 'fast25'")
24
25
26  def polar_waypoints(variant: str = "seed25") -> list[Point]:
27      """Return origin, 12 inner points, then 12 outer points shifted by 15 deg.
28
29      Index 1+k has angle 30*k degrees; index 13+k has angle 30*k+15.
30      This order specifies stable obligation indices, not a recommended route.
31      """
32      inner, outer, _, _, _ = _parameters(variant)
33      points: list[Point] = [(0.0, 0.0)]
34      for radius, phase in ((inner, 0.0), (outer, math.pi / 12.0)):
35          for k in range(12):

```

```

36         angle = k * math.pi / 6.0 + phase
37         points.append((radius * math.cos(angle), radius * math.sin(angle)))
38     return points
39
40
41 def polar_certificate(variant: str = "seed25") -> dict:
42     """Return finite indices, closed-form constants, and conservative bounds.
43
44     Floats in ``analytic_values_m`` are evaluations for independent checking,
45     not interval-arithmetic proofs. The exact proof uses the rational bounds
46     9659/10000 < cos(pi/12) and 1/4 < sin(pi/12) < 259/1000.
47     The integer/rational inequalities are documented in the companion notes.
48     """
49     inner, outer, shift, error, edge_bound = _parameters(variant)
50     sine = (math.sqrt(6.0) - math.sqrt(2.0)) / 4.0
51     cosine = (math.sqrt(6.0) + math.sqrt(2.0)) / 4.0
52     inner_chord = 2.0 * inner * sine
53     outer_chord = 2.0 * outer * sine
54     cross_edge = math.sqrt(inner**2 + outer**2 - 2.0 * inner * outer * cosine)
55     triangles: list[tuple[int, int, int]] = []
56     for k in range(12):
57         i = 1 + k
58         j = 1 + (k + 1) % 12
59         o = 13 + k
60         p = 13 + (k + 1) % 12
61         triangles.extend(((0, i, j), (i, o, j), (j, o, p)))
62     edges = sorted({tuple(sorted((triangle[k], triangle[(k + 1) % 3]))
63                             for triangle in triangles for k in range(3)))
64     route = list(range(13)) + list(range(24, 12, -1))
65     return {
66         "variant": variant,
67         "evidence": "analytic finite triangulation; not an experiment",
68         "source_radius_m": 1800.0,
69         "minimum_radio_radius_m": 1000.0,
70         "point_count": 25,
71         "inside_source_disk_count": 13,
72         "outside_source_disk_count": 12,
73         "origin_index": 0,
74         "inner_indices": list(range(1, 13)),
75         "outer_indices": list(range(13, 25)),
76         "inner_radius_m": inner,
77         "outer_radius_m": outer,
78         "outer_phase_degrees": 15.0,
79         "points": polar_waypoints(variant),
80         "triangles_ccw": triangles,
81         "edges": edges,
82         "boundary_ccw": list(range(13, 25)),
83         "triangle_count": 36,
84         "edge_count": 60,
85         "closed_form": {
86             "cos_15": "(sqrt(6)+sqrt(2))/4",
87             "sin_15": "(sqrt(6)-sqrt(2))/4",
88             "outer_apothem": "b*cos(pi/12)",
89             "inner_chord": "2*a*sin(pi/12)",
90             "outer_chord": "2*b*sin(pi/12)",
91             "cross_edge": "sqrt(a*a+b*b-2*a*b*cos(pi/12))",
92             "maximum_edge": "max(a,inner_chord,outer_chord,cross_edge)",
93         },
94         "analytic_values_m": {
95             "outer_apothem": outer * cosine,
96             "inner_chord": inner_chord,
97             "outer_chord": outer_chord,
98             "cross_edge": cross_edge,
99             "maximum_edge": max(inner, inner_chord, outer_chord, cross_edge),
100     },
101     "rational_trig_bounds": {
102         "cos_15_lower": (9659, 10000),

```

```

103         "sin_15_lower": (1, 4),
104         "sin_15_upper": (259, 1000),
105     },
106     "robust_certificate": {
107         "shift_m": shift,
108         "per_waypoint_euclidean_error_bound_m": error,
109         "triangle_diameter_upper_bound_m": edge_bound,
110         "guard_disk_radius_m": 1800.0 + shift,
111         "ideal_forward_projection_lower_bound_m": shift,
112         "perturbed_forward_projection_lower_bound_m": shift - error,
113         "perturbed_detection_distance_upper_bound_m": edge_bound + shift + error,
114         "proof": "h=g+shift*n lies in the outer polygon; a triangle containing h has a vertex v with n.(v-g
115     )>=shift and |v-g|<=diameter+shift",
116     },
117     "explicit_open_scan_route": {
118         "indices": route,
119         "length_formula": "a+22*(a+b)*sin(pi/12)+cross_edge",
120         "analytic_length_m": inner + 11.0 * (inner_chord + outer_chord) + cross_edge,
121         "returns_to_origin": False,
122         "is_optimal": False,
123     },
124     "baseline_comparison": {
125         "unchanged_baseline": "enhanced Q4: s=990, 31 triangular-lattice points",
126         "baseline_waypoint_count": 31,
127         "candidate_waypoint_count": 25,
128         "baseline_full_20_channel_measurement_obligations": 620,
129         "candidate_full_20_channel_measurement_obligations": 500,
130         "claimed_total_runtime_gain": None,
131     },
132     "smaller_candidate": {
133         "accepted": False,
134         "reason": "No fewer-point construction is certified here; the notes exclude equal two-ring sizes
135         <=11 and 12 regular outer vertices with <=11 inner vertices of radius <=1000 under the diameter-
136         triangulation certificate.",
137         "global_minimality_claim": False,
138     },
139 }

```

Listing 29: 发现与清除联合调度候选

```

1  """Joint, obligation-preserving open-route dispatch from public track summaries.
2
3  This module only chooses a task. It does not certify a target position, execute
4  an action, mark an anchor visited, or remove any discovery obligation.
5  """
6
7  from __future__ import annotations
8
9  from math import dist, isfinite
10
11  Point = tuple[float, float]
12  Task = tuple[str, int]
13
14
15  def choose_task(
16      position: Point,
17      anchors: dict[int, Point],
18      targets: dict[int, tuple[Point, float]],
19      *,
20      choice: str = "guarded",
21      risk_weight: float = 1.0,
22  ) -> Task:
23      """Choose the first task of a joint nearest-insertion/open-2-opt route.
24
25      ``center`` minimizes a point-center open-route surrogate. ``guarded``
26      adds the first task's MEC radius (zero for anchors), discouraging an
27      immediate commitment to an uncertain center. Neither surrogate predicts

```

```

28 localization actions or total simulator time. Rebuild inputs after every
29 completed task; a returned target must use the existing certified localizer,
30 not clear at a surrogate point.
31
32 All tasks remain in the internal permutation, even at identical positions.
33 Ties use target before anchor, then ascending integer ID; insertion gaps
34 and 2-opt segments are scanned left to right. Inputs are not modified.
35 Both mappings empty, invalid choice, nonfinite geometry, or an invalid risk
36 weight raises ValueError.
37 """
38 if choice not in ("center", "guarded"):
39     raise ValueError("choice must be 'center' or 'guarded'")
40 tasks: list[Task] = [("target", key) for key in sorted(targets)]
41 tasks.extend(("anchor", key) for key in sorted(anchors))
42 n = len(tasks)
43 if not n:
44     raise ValueError("cannot dispatch an empty task set")
45
46 coords = [targets[key][0] for key in sorted(targets)]
47 coords.extend(anchors[key] for key in sorted(anchors))
48 radii = [targets[key][1] for key in sorted(targets)]
49 radii.extend(0.0 for _ in anchors)
50 if any(len(point) != 2 or not all(isfinite(x) for x in point)
51       for point in [position, *coords]):
52     raise ValueError("positions must be finite two-dimensional points")
53 if any(not isfinite(radius) or radius < 0 for radius in radii):
54     raise ValueError("MEC radii must be finite and nonnegative")
55 if not isfinite(risk_weight) or risk_weight < 0:
56     raise ValueError("risk_weight must be finite and nonnegative")
57 penalty = [risk_weight * radius for radius in radii] if choice == "guarded" else [0.0] * n
58 origin = [dist(position, point) for point in coords]
59 edges = [[0.0] * n for _ in range(n)]
60 for i in range(n):
61     for j in range(i):
62         edges[i][j] = edges[j][i] = dist(coords[i], coords[j])
63 if (any(not isfinite(value) for value in origin)
64     or any(not isfinite(value) for row in edges for value in row)):
65     raise ValueError("pairwise distances must be finite")
66
67 # Nearest insertion: select the task nearest the current route (including
68 # the fixed origin), then insert it in the least-cost open-route gap.
69 first = min(range(n), key=lambda i: (origin[i] + penalty[i], i))
70 route = [first]
71 remaining = set(range(n))
72 remaining.remove(first)
73 nearest = [min(origin[i], edges[first][i]) for i in range(n)]
74 while remaining:
75     node = min(remaining, key=lambda i: (nearest[i], i))
76     best_gap = 0
77     best_delta = (origin[node] + edges[node][route[0]] - origin[route[0]]
78                  + penalty[node] - penalty[route[0]])
79     for gap in range(1, len(route) + 1):
80         before = route[gap - 1]
81         delta = edges[before][node]
82         if gap < len(route):
83             after = route[gap]
84             delta += edges[node][after] - edges[before][after]
85         if delta < best_delta:
86             best_gap, best_delta = gap, delta
87     route.insert(best_gap, node)
88     remaining.remove(node)
89     for other in remaining:
90         nearest[other] = min(nearest[other], edges[node][other])
91
92 # Symmetric internal edges cancel on reversal; an open tail has no return
93 # edge. A reversal starting at zero also changes the first-radius penalty.
94 # Cap accepted moves to make online CPU cost predictable, not a claim of

```

```

95     # reaching a local or global optimum.
96     for _ in range(n):
97         changed = False
98         for left in range(n - 1):
99             for right in range(left + 1, n):
100                 old = (origin[route[left]] if left == 0
101                        else edges[route[left - 1]][route[left]])
102                 new = (origin[route[right]] if left == 0
103                        else edges[route[left - 1]][route[right]])
104                 if right + 1 < n:
105                     old += edges[route[right]][route[right + 1]]
106                     new += edges[route[left]][route[right + 1]]
107                 if left == 0:
108                     old += penalty[route[left]]
109                     new += penalty[route[right]]
110                 if new + 1e-12 * max(1.0, old, new) < old:
111                     route[left:right + 1] = reversed(route[left:right + 1])
112                     changed = True
113                     break
114             if changed:
115                 break
116         if not changed:
117             break
118     return tasks[route[0]]

```

Listing 30: 分层光学覆盖候选（非默认）

```

1  """Deterministic, whole-region optical-cover candidate for convex polygons.
2
3  The existing geometry.optical_cover remains the explicit fallback/control.
4  Only public feasible-region vertices are used. No actions or state are mutated.
5  """
6
7  from __future__ import annotations
8
9  from fractions import Fraction
10 from math import ceil, dist, hypot, isfinite, sqrt, ulp
11
12 from geometry import _farthest_pair, optical_cover
13
14 Point = tuple[float, float]
15 _ExactPoint = tuple[Fraction, Fraction]
16
17
18 def _cycle_length(points: list[Point]) -> float:
19     return sum(dist(points[i - 1], point) for i, point in enumerate(points))
20
21
22 def _strip_bounds(
23     vertices: list[_ExactPoint],
24     edges: list[tuple[Fraction, Fraction, Fraction, Fraction]],
25     left: Fraction,
26     right: Fraction,
27 ) -> tuple[Fraction, Fraction] | None:
28     """Exact transverse extrema of polygon intersected with a closed slab."""
29     values = [y for x, y in vertices if left <= x <= right]
30     # Edge tuple: left endpoint x/y, right endpoint x, exact dy/dx.
31     # Vertical edges need no intersections: their endpoints are already above.
32     for x, y, end, slope in edges:
33         if x <= left <= end:
34             values.append(y + (left - x) * slope)
35         if x <= right <= end:
36             values.append(y + (right - x) * slope)
37     if not values:
38         return None
39     return min(values), max(values)
40

```

```

41
42 def _certified_center(
43     left: Fraction,
44     right: Fraction,
45     bottom: Fraction,
46     top: Fraction,
47     origin: _ExactPoint,
48     axis: _ExactPoint,
49     radius_squared: Fraction,
50 ) -> Point | None:
51     """Certify the actual returned float center against four exact corners."""
52     ox, oy = origin
53     ux, uy = axis
54     x, y = (left + right) / 2, (bottom + top) / 2
55     center = (float(ox + x * ux - y * uy), float(oy + x * uy + y * ux))
56     if not all(isfinite(value) for value in center):
57         return None
58     cx, cy = Fraction(center[0]), Fraction(center[1])
59     for x in (left, right):
60         for y in (bottom, top):
61             dx = ox + x * ux - y * uy - cx
62             dy = oy + x * uy + y * ux - cy
63             if dx * dx + dy * dy > radius_squared:
64                 return None
65     return center
66
67
68 def certified_optical_cover(poly: list[Point], radius: float = 19.9) -> list[Point]:
69     """Cover the entire convex region using certified, locally trimmed slabs.
70
71     Accepts either winding, repeated vertices, points and line segments. Empty
72     input raises ValueError (the legacy planner also treats it as infeasible).
73     Output centers may lie outside the polygon/arena, as with optical_cover.
74
75     Every new cell has an exact rational four-corner disk certificate for the
76     returned float center. Any unsuccessful candidate is discarded in full;
77     the existing cover is the safe fallback. Selection never increases cover
78     count or cyclic travel relative to that control, but entry travel depends
79     on the caller's position and is not covered by that comparison.
80     """
81     if not isfinite(radius) or radius <= 0:
82         raise ValueError("Optical covering radius must be finite and positive")
83     if not poly:
84         raise ValueError("An infeasible region has no optical cover")
85     if any(not (isfinite(x) and isfinite(y)) for x, y in poly):
86         raise ValueError("Geometry requires finite coordinates")
87
88     control = optical_cover(poly, radius)
89     if len(control) <= 1:
90         return control
91     origin_float, end, diameter = _farthest_pair(poly)
92     if not isfinite(diameter) or diameter == 0:
93         return control
94     ux = (end[0] - origin_float[0]) / diameter
95     uy = (end[1] - origin_float[1]) / diameter
96     norm = hypot(ux, uy)
97     if not isfinite(norm) or norm == 0:
98         return control
99     axis = Fraction(ux / norm), Fraction(uy / norm)
100     origin = Fraction(origin_float[0]), Fraction(origin_float[1])
101     norm_squared = axis[0] ** 2 + axis[1] ** 2
102     metric_scale = sqrt(float(norm_squared))
103     # Treat the float axis as exact, not as an exactly unit vector. This exact
104     # inverse and the corner check remove reliance on rounded orthogonality.
105     vertices = []
106     for px, py in poly:
107         dx, dy = Fraction(px) - origin[0], Fraction(py) - origin[1]

```

```

108         vertices.append(
109             ((dx * axis[0] + dy * axis[1]) / norm_squared,
110              (-dx * axis[1] + dy * axis[0]) / norm_squared)
111         )
112     edges = []
113     for index, a in enumerate(vertices):
114         b = vertices[index - 1]
115         if a[0] == b[0]:
116             continue
117         if a[0] > b[0]:
118             a, b = b, a
119         edges.append((a[0], a[1], b[0], (b[1] - a[1]) / (b[0] - a[0])))
120     xmin = min(x for x, _ in vertices)
121     xmax = max(x for x, _ in vertices)
122     span = xmax - xmin
123     height = float(max(y for _, y in vertices) - min(y for _, y in vertices))
124     scale = max(diameter, *(max(abs(x), abs(y)) for x, y in poly))
125     guard = max(1e-9, 64.0 * ulp(max(1.0, scale)))
126     safe_radius = radius - 8.0 * guard
127     if safe_radius <= 0 or not isfinite(height):
128         return control
129     local_radius = safe_radius / metric_scale
130     # Square-ish slabs serve broad regions; elongated slabs serve narrow ones.
131     widths = [sqrt(2.0) * local_radius, sqrt(3.0) * local_radius, local_radius]
132     if height < 2.0 * local_radius:
133         widths.append(2.0 * sqrt((local_radius - height / 2.0)
134                                * (local_radius + height / 2.0)))
135     radius_squared = Fraction(radius) ** 2
136     control_cycle = _cycle_length(control)
137     best = control
138     best_cost = 3.0 * len(control) + control_cycle / 5.0
139     tried_counts: set[int] = set()
140     for width in widths:
141         if width <= 0 or not isfinite(width):
142             continue
143         count = max(1, ceil(span / Fraction(width)))
144         if count in tried_counts or count > len(control):
145             continue
146         tried_counts.add(count)
147         slab_width = span / count
148         half_width = float(slab_width) / 2.0
149         if half_width >= local_radius:
150             continue
151         capacity = 2.0 * sqrt((local_radius - half_width)
152                               * (local_radius + half_width))
153         if capacity <= 0 or not isfinite(capacity):
154             continue
155         candidate: list[Point] = []
156         valid = True
157         for index in range(count):
158             left = xmin + index * slab_width
159             right = xmin + (index + 1) * slab_width
160             bounds = _strip_bounds(vertices, edges, left, right)
161             if bounds is None:
162                 # For a nonempty convex polygon every slab across its x-span
163                 # intersects it. Do not silently skip an unexplained hole.
164                 valid = False
165                 break
166             bottom, top = bounds
167             rows = max(1, ceil((top - bottom) / Fraction(capacity)))
168             if len(candidate) + rows > len(control):
169                 valid = False
170                 break
171             step = (top - bottom) / rows
172             indices = range(rows) if index % 2 == 0 else range(rows - 1, -1, -1)
173             for row in indices:
174                 point = _certified_center(

```

```

175         left, right, bottom + row * step, bottom + (row + 1) * step,
176         origin, axis, radius_squared,
177     )
178     if point is None:
179         valid = False
180         break
181     candidate.append(point)
182     if not valid:
183         break
184     if not valid:
185         continue
186     cycle = _cycle_length(candidate)
187     cost = 3.0 * len(candidate) + cycle / 5.0
188     if cycle <= control_cycle and cost < best_cost:
189         best, best_cost = candidate, cost
190     return best

```

Listing 31: 独立开发集上的候选筛选

```

1  """Paired development screen of independent candidates; no official calls."""
2  from __future__ import annotations
3
4  import argparse
5  import json
6  import math
7  import statistics
8  from pathlib import Path
9
10 from experiments import aggregate, run_case
11
12 # Fixed candidates, not a Cartesian hyperparameter search. Every run retains
13 # full discovery obligations and the same bounded-probe localization contract.
14 CONFIGS = {
15     "control": {},
16     "optical": {"optical_policy": "slabs"},
17     "joint_center": {"dispatch_policy": "center"},
18     "joint_guarded": {"dispatch_policy": "guarded"},
19     "polar_seed": {"coverage_policy": "seed25"},
20     "polar_compact": {"coverage_policy": "compact25"},
21     "polar_joint": {"coverage_policy": "compact25", "dispatch_policy": "center"},
22     "polar_guarded": {"coverage_policy": "compact25", "dispatch_policy": "guarded"},
23     "combined": {"coverage_policy": "compact25", "optical_policy": "slabs", "dispatch_policy": "center"},
24     "joint_unknown": {"dispatch_policy": "center", "scan_policy": "unknown"},
25     "joint_useful": {"dispatch_policy": "center", "scan_policy": "useful"},
26     "polar_unknown": {"coverage_policy": "compact25", "dispatch_policy": "guarded", "scan_policy": "unknown"},
27     "polar_useful": {"coverage_policy": "compact25", "dispatch_policy": "guarded", "scan_policy": "useful"},
28 }
29
30
31 def paired(control, candidate):
32     assert [r["seed"] for r in control] == [r["seed"] for r in candidate]
33     values = [a["average_time_s"] - b["average_time_s"] for a, b in zip(control, candidate, strict=True)]
34     mean = statistics.mean(values)
35     sem = statistics.stdev(values) / math.sqrt(len(values)) if len(values) > 1 else 0.0
36     return {"mean_saved_s_per_source": mean,
37             "reduction_pct": 100 * mean / statistics.mean(r["average_time_s"] for r in control),
38             "approx_95pct_ci_s": [mean - 1.96 * sem, mean + 1.96 * sem],
39             "faster_cases": sum(value > 0 for value in values), "cases": len(values)}
40
41
42 def main():
43     parser = argparse.ArgumentParser()
44     parser.add_argument("--cases", type=int, default=150)
45     parser.add_argument("--seed", type=int, default=3100000)
46     parser.add_argument("--output", type=Path, default=Path("results/refinement_development.json"))
47     args = parser.parse_args()
48     if args.cases < 2:

```

```

49     parser.error("At least two cases are required")
50 rows, summary = [], {}
51 for problem in (3, 4):
52     names = ("control", "optical", "joint_center", "joint_guarded", "joint_unknown", "joint_useful") if
53     problem == 3 else tuple(name for name in CONFIGS if name not in ("joint_unknown", "joint_useful"))
54     control = None
55     for name in names:
56         group = []
57         for seed in range(args.seed, args.seed + args.cases):
58             row = run_case(seed, problem, "enhanced", **CONFIGS[name])
59             row["configuration"] = name
60             group.append(row)
61         rows.extend(group)
62         if name == "control":
63             control = group
64         key = f"Q{problem}_{name}"
65         summary[key] = {**aggregate(group), **paired(control, group)}
66         print(key, json.dumps(summary[key], ensure_ascii=False), flush=True)
67 result = {"evidence": "development_only_local_synthetic_not_official",
68         "seed_range": [args.seed, args.seed + args.cases - 1],
69         "configs": CONFIGS, "total_runs": len(rows), "summary": summary, "runs": rows}
70 args.output.parent.mkdir(parents=True, exist_ok=True)
71 args.output.write_text(json.dumps(result, ensure_ascii=False, indent=2) + "\n")
72
73 if __name__ == "__main__":
74     main()

```

Listing 32: 冻结策略的样本外消融与压力实验

```

1  """Frozen holdout/ablation/robustness study; all observations are synthetic.
2
3  Development uses 3100000..3100149 only. No choice is made from this file's
4  holdout results: refined defaults are frozen before its first execution.
5  """
6  from __future__ import annotations
7
8  import json
9  from pathlib import Path
10
11  from experiments import aggregate, run_case
12  from refinement_study import paired
13
14  CONFIGS = {
15      3: {
16          "control": ("enhanced", {}),
17          "joint_all": ("enhanced", {"dispatch_policy": "center"}),
18          "refined": ("refined", {}),
19      },
20      4: {
21          "control": ("enhanced", {}),
22          "polar_only": ("enhanced", {"coverage_policy": "compact25"}),
23          "joint_all": ("enhanced", {"coverage_policy": "compact25", "dispatch_policy": "guarded"}),
24          "refined": ("refined", {}),
25      },
26  }
27
28
29  def group(problem, name, seeds, scenario="random", mode="smooth", **override):
30      strategy, config = CONFIGS[problem][name]
31      result = []
32      for seed in seeds:
33          row = run_case(seed, problem, strategy, scenario, mode, **(config | override))
34          row["configuration"] = name
35          result.append(row)
36      return result
37

```

```

38
39 def main():
40     rows, summary, comparisons, stress, sensitivity = [], {}, {}, {}, {}
41     for problem in (3, 4):
42         current = {}
43         for name in CONFIGS[problem]:
44             current[name] = group(problem, name, range(4100000,4101000))
45             rows.extend(current[name])
46             summary[f"Q{problem}_{name}"] = aggregate(current[name])
47             comparisons[f"Q{problem}"] = paired(current["control"],current["refined"])
48             order=list(current)
49             comparisons[f"Q{problem}_incremental"] = {
50                 f"{a}_to_{b}":paired(current[a],current[b]) for a,b in zip(order,order[1:])}
51             print(f"holdout Q{problem}",json.dumps(comparisons[f"Q{problem}"]),flush=True)
52             scenarios=[(scenario,mode,range(4200000,4200050))
53                         for scenario in ("minimum_radius","outward_boundary","clustered")
54                         for mode in ("smooth","extreme","iid_location")]
55             scenarios.extend(("random",mode,range(4210000,4210200)) for mode in ("extreme","iid_location"))
56             for scenario,mode,seeds in scenarios:
57                 control=group(problem,"control",seeds,scenario,mode)
58                 refined=group(problem,"refined",seeds,scenario,mode)
59                 rows.extend(control);rows.extend(refined)
60                 key=f"Q{problem}_{scenario}_{mode}"
61                 stress[key]={ "control":aggregate(control), "refined":aggregate(refined), "paired":paired(control,
62                 refined)}
63                 print(key,json.dumps(stress[key]["paired"]),flush=True)
64                 for scale in (.12,.22,.4):
65                     selected=group(problem,"refined",range(4300000,4300050),probe_scale=scale)
66                     rows.extend(selected)
67                     sensitivity[f"Q{problem}_probe_{scale}"]=aggregate(selected)
68             result={"evidence":"frozen_held_out_local_synthetic_not_official",
69                     "selection":"Q3 center/unknown, Q4 compact25/guarded/useful frozen using development
70                     3100000..3100149 only; rectangle optical cover retained",
71                     "development_seed_range":[3100000,3100149], "main_seed_range":[4100000,4100999],
72                     "stress_seed_range":[4200000,4200049], "alternate_error_seed_range":[4210000,4210199],
73                     "sensitivity_seed_range":[4300000,4300049], "main_cases_per_problem":1000,
74                     "configs":CONFIGS, "total_runs":len(rows), "summary":summary, "comparison":comparisons,
75                     "stress":stress, "sensitivity":sensitivity, "runs":rows}
76             Path("results/research_experiments.json").write_text(json.dumps(result,ensure_ascii=False,indent=2)+"\n")
77             print(json.dumps({"total_runs":len(rows), "summary":summary, "comparison":comparisons},ensure_ascii=False,
78                             indent=2))
79
80 if __name__=="__main__":
81     main()

```

Listing 33: 新覆盖与策略行为的独立核验

```

1  """Independent geometry/behavior verification for the new research candidates."""
2  from __future__ import annotations
3
4  from collections import Counter
5  from decimal import Decimal, localcontext
6  from fractions import Fraction
7  import json
8  import math
9  import random
10 from pathlib import Path
11
12 from geometry import clip_bearing, initial_polygon, optical_cover
13 from joint_dispatch_candidate import choose_task
14 from optical_policy_candidate import certified_optical_cover
15 from planner import Planner, Track
16 from verify_terminal import DeadlineAdapter
17 from polar_coverage_candidate import polar_certificate, polar_waypoints
18
19

```

```

20 def cross(a, b, c):
21     return (b[0]-a[0])*(c[1]-a[1])-(b[1]-a[1])*(c[0]-a[0])
22
23
24 def verify_polar(variant):
25     cert = polar_certificate(variant)
26     points = polar_waypoints(variant)
27     triangles = cert["triangles_ccw"]
28     counts = Counter(tuple(sorted((t[k], t[(k+1)%3]))) for t in triangles for k in range(3))
29     boundary = {tuple(sorted((13+k, 13+(k+1)%12))) for k in range(12)}
30     assert len(points) == len(set(points)) == 25 and points[0] == (0., 0.)
31     assert {edge for edge, count in counts.items() if count == 1} == boundary
32     assert all(count == (1 if edge in boundary else 2) for edge, count in counts.items())
33     assert len(counts) == 60 and len(triangles) == 36
34     assert all(cross(*(points[i] for i in triangle)) > 0 for triangle in triangles)
35     directed = Counter((t[k], t[(k+1)%3]) for t in triangles for k in range(3))
36     for a,b in counts:
37         if (a,b) not in boundary:
38             assert directed[a,b] == directed[b,a] == 1
39     for a,b in counts:
40         for c,d in counts:
41             if len({a,b,c,d}) < 4:
42                 continue
43             # Strict crossings would invalidate the triangulation argument.
44             assert not (cross(points[a],points[b],points[c])*cross(points[a],points[b],points[d]) < -1e-8
45                         and cross(points[c],points[d],points[a])*cross(points[c],points[d],points[b]) < -1e-8)
46     area = sum(cross(*(points[i] for i in t))/2 for t in triangles)
47     outer_area = sum(cross((0,0),points[13+k],points[13+(k+1)%12])/2 for k in range(12))
48     assert abs(area-outer_area) < 1e-6
49     maximum = max(math.dist(points[a],points[b]) for a,b in counts)
50     bound = cert["robust_certificate"]
51     assert maximum <= bound["triangle_diameter_upper_bound_m"] + 1e-9
52     # Exact rational lower/upper radical bounds used by the written proof.
53     assert Fraction(14142,10000)**2 < 2 < Fraction(14143,10000)**2
54     assert Fraction(24494,10000)**2 < 6 < Fraction(24495,10000)**2
55     a,b = map(int,(cert["inner_radius_m"],cert["outer_radius_m"]))
56     assert Fraction(b*9659,10000) > bound["guard_disk_radius_m"]
57     assert a*a+b*b-2*a*b*Fraction(9659,10000) < bound["triangle_diameter_upper_bound_m"]**2
58     with localcontext() as context:
59         context.prec = 70
60         root2, root3, root6 = Decimal(2).sqrt(), Decimal(3).sqrt(), Decimal(6).sqrt()
61         c15, s15 = (root6+root2)/4, (root6-root2)/4
62         expected = [(Decimal(0), Decimal(0))]
63         for radius, start in ((a,(Decimal(1),Decimal(0))), (b,(c15,s15))):
64             x,y = start
65             for k in range(12):
66                 expected.append((radius*x,radius*y))
67                 x,y = x*root3/2-y/2, x/2+y*root3/2
68             error = max(float(((Decimal(px)-ex)**2+(Decimal(py)-ey)**2).sqrt())
69                        for (px,py),(ex,ey) in zip(points,expected,strict=True)))
70     assert error < 1e-8 < bound["per_waypoint_euclidean_error_bound_m"]
71     rng = random.Random(340091)
72     positions = [(1800*math.cos(k*math.pi/180),1800*math.sin(k*math.pi/180)) for k in range(360)]
73     positions += points[:13]
74     positions += (((points[a][0]+points[b][0])/2,(points[a][1]+points[b][1])/2)
75                  for a,b in counts if math.hypot((points[a][0]+points[b][0])/2,
76                                                    (points[a][1]+points[b][1])/2)<=1800)
77     for _ in range(400):
78         r,phi = 1800*math.sqrt(rng.random()),rng.uniform(0,math.tau)
79         positions.append((r*math.cos(phi),r*math.sin(phi)))
80     checks, worst_distance, least_forward = 0, 0.0, float("inf")
81     shift = bound["shift_m"]
82     perturbation_cases = 0
83     special = list(points[:13])
84     special.extend(((points[a][0]+points[b][0])/2,(points[a][1]+points[b][1])/2)
85                   for a,b in counts if math.hypot((points[a][0]+points[b][0])/2,
86                                                    (points[a][1]+points[b][1])/2)<1790)

```

```

87     for h in special:
88         n = (math.cos(.713), math.sin(.713))
89         positions.append((h[0]-shift*n[0],h[1]-shift*n[1]))
90     for g in positions:
91         angles = [k*math.pi/12 for k in range(24)] + [.713]
92         for angle in angles:
93             n = math.cos(angle), math.sin(angle)
94             h = g[0]+shift*n[0],g[1]+shift*n[1]
95             containing = next(t for t in triangles if all(cross(points[t[i]],points[t[(i+1)%3]],h) >= -1e-7 for
96                 i in range(3)))
97             v = max((points[i] for i in containing),key=lambda p:(p[0]-g[0])*n[0]+(p[1]-g[1])*n[1])
98             projection = (v[0]-g[0])*n[0]+(v[1]-g[1])*n[1]
99             distance = math.dist(v,g)
100             assert projection >= shift-1e-8 and distance <= maximum+shift+1e-8
101             epsilon = bound["per_waypoint_euclidean_error_bound_m"]
102             for offset in ((-epsilon*n[0],-epsilon*n[1]),
103                 (epsilon*(v[0]-g[0])/distance,epsilon*(v[1]-g[1])/distance)):
104                 q = v[0]+offset[0],v[1]+offset[1]
105                 assert (q[0]-g[0])*n[0]+(q[1]-g[1])*n[1] >= shift-epsilon-1e-7
106                 assert math.dist(q,g) <= bound["perturbed_detection_distance_upper_bound_m"]+1e-7
107                 perturbation_cases += 1
108             checks += 1
109             worst_distance=max(worst_distance,distance)
110             least_forward=min(least_forward,projection)
111 route=cert["explicit_open_scan_route"]["indices"]
112 route_length=sum(math.dist(points[a],points[b]) for a,b in zip(route,route[1:]))
113 assert abs(route_length-cert["explicit_open_scan_route"]["analytic_length_m"])<1e-7
114 return {"variant":variant,"triangles":len(triangles),"edges":len(counts),
115     "noncrossing_tiling_verified":True,"maximum_edge_m":maximum,
116     "coordinate_error_against_decimal_m":error,"directional_cases":checks,
117     "adverse_single_vertex_perturbations":perturbation_cases,
118     "maximum_witness_distance_m":worst_distance,"minimum_witness_projection_m":least_forward,
119     "explicit_route_length_m":route_length,"robust_certificate":bound}
120
121 def verify_optical():
122     rng=random.Random(342091)
123     polygons=[[(0.,0.),[(0.,0.), (1000.,0.)],[(0.,0.), (1000.,1e-9), (500.,0.)],
124         [(0.,0.), (1500.,0.), (1500.,52.)],
125         [(-100.,-40.), (100.,-40.), (100.,40.), (-100.,40.)]]
126     for _ in range(120):
127         phi=rng.uniform(0,math.tau)
128         r=1800*math.sqrt(rng.random())
129         g=r*math.cos(phi),r*math.sin(phi)
130         poly=initial_polygon()
131         for j in range(rng.randrange(1,5)):
132             theta=rng.uniform(0,math.tau); distance=rng.uniform(6,1500)
133             s=g[0]+distance*math.cos(theta),g[1]+distance*math.sin(theta)
134             poly=clip_bearing(poly,s,(math.degrees(theta)+180+rng.uniform(-1,1))%360)
135         assert poly
136         polygons.append(poly)
137     samples=0; improved=0; max_distance=0.0
138     for poly in polygons:
139         old=optical_cover(poly); new=certified_optical_cover(poly)
140         old_cost=3*len(old)+sum(math.dist(p,old[i-1]) for i,p in enumerate(old))/5
141         new_cost=3*len(new)+sum(math.dist(p,new[i-1]) for i,p in enumerate(new))/5
142         assert new_cost<=old_cost+1e-7
143         improved+=new_cost<old_cost-1e-7
144         probes=list(poly)
145         for a,b in zip(poly,poly[1:]+poly[:1]):
146             probes.extend(((1-t/20)*a[0]+t/20*b[0],(1-t/20)*a[1]+t/20*b[1]) for t in range(21))
147         for _ in range(100):
148             weights=[rng.random() for _ in poly]; total=sum(weights)
149             probes.append(tuple(sum(w*p[k] for w,p in zip(weights,poly))/total for k in (0,1)))
150         for p in probes:
151             distance=min(math.dist(p,c) for c in new)
152             assert distance<=19.9+1e-7

```

```

153         max_distance=max(max_distance,distance);samples+=1
154     return {"polygons":len(polygons),"interior_and_boundary_samples":samples,
155            "maximum_sampled_distance_m":max_distance,"lower_cover_proxy_cost_cases":improved,
156            "scope":"interior sampling supplements exact per-cell corner certificates, not a proof by sampling"
157    }
158
159 def verify_dispatch():
160     anchors={7:(-2.,0.),9:(10.,0.)};targets={3:((1.,0.),20.)}
161     kinds=[]
162     for mode in ("center","guarded"):
163         remaining_a=dict(anchors);remaining_t=dict(targets);position=(0.,0.);visited=[]
164         while remaining_a or remaining_t:
165             kind,key=choose_task(position,remaining_a,remaining_t,choice=mode)
166             position=remaining_a.pop(key) if kind=="anchor" else remaining_t.pop(key)[0]
167             visited.append((kind,key))
168             assert set(visited)=="{"anchor",7},{"anchor",9},{"target",3}"
169             kinds.append({"choice":mode,"completed":visited})
170         assert choose_task((0,0),{1:(0,0)},{2:(0,0),0}) in (("anchor",1),("target",2))
171     try:
172         choose_task((0,0),{},{})
173     except ValueError:
174         pass
175     else:
176         raise AssertionError("Empty dispatch must not fabricate a task")
177     return kinds
178
179 def verify_scan_obligations():
180     records = []
181     for problem, mode in ((3,"unknown"),(4,"useful")):
182         adapter = DeadlineAdapter(max_virtual=360000)
183         policy = Planner(adapter,problem=problem)
184         policy.action("/enter")
185         # A previously detected, unresolved singleton: a ready optical target,
186         # not an absent channel even when every other channel has been scanned.
187         policy.tracks[1] = Track(polygon=[(100.,0.)],readings=[((0.,0.),0.)])
188         policy.channel_state[1] = "detected"
189         for index in sorted(policy.pending):
190             policy.scan_anchor(index)
191         assert not policy.scan_records[1]
192         assert not policy._result()["certificate_complete"]
193         assert policy.channel_state[1] == "detected"
194         policy.measure(1,(200.,0.))
195         assert policy.channel_state[1] == "detected"
196         policy.clear(1,(100.,0.))
197         result = policy._result()
198         assert result["certificate_complete"] and result["n_cleared"] == 1
199         assert all(state == ("cleared" if channel == 1 else "absent-certified")
200                    for channel,state in result["channel_certificates"].items())
201         records.append({"problem":problem,"scan_policy":mode,
202                        "known_skip_never_certified_absent":True,
203                        "negative_reading_kept_detected":True,
204                        "success_completed_remaining_obligation":True})
205     return records
206
207
208 def main():
209     polar=[verify_polar(variant) for variant in ("seed25","compact25","fast25")]
210     assert polar[0]["explicit_route_length_m"]-polar[1]["explicit_route_length_m"]>179.5
211     assert polar[1]["explicit_route_length_m"]-polar[2]["explicit_route_length_m"]>100
212     result={"evidence":"independent_finite_geometry_and_behavior_checks_not_official",
213            "polar":polar,"optical":verify_optical(),"dispatch":verify_dispatch(),
214            "scan_obligations":verify_scan_obligations()}
215     Path("results/research_verification.json").write_text(json.dumps(result,ensure_ascii=False,indent=2)+"\n")
216     print(json.dumps(result,ensure_ascii=False,indent=2))
217
218

```

```

219 if __name__=="__main__":
220     main()

```

Listing 34: 历史冻结研究图表生成

```

1  """Generate checked research tables, vector figures and observable trajectories."""
2  from __future__ import annotations
3
4  from collections import defaultdict
5  import hashlib
6  import json
7  import math
8  import statistics
9  from pathlib import Path
10
11 import matplotlib
12 matplotlib.use("Agg")
13 import matplotlib.pyplot as plt
14 import numpy as np
15
16 from coverage import directional_waypoints
17 from environment import LocalSimulator
18 from experiments import aggregate
19 from make_assets import atomic_bytes, table, save_figure, number, write_json, GENERATED, ROOT
20 from planner import Planner
21 from polar_coverage_candidate import polar_certificate, polar_waypoints
22 from refinement_study import paired
23
24 plt.rcParams.update({"font.size":10,"axes.labelsize":10,"legend.fontsize":9,
25                     "pdf.fonttype":42,"ps.fonttype":42,"axes.spines.top":False,"axes.spines.right":False})
26 LABELS={"control":"原增强", "refined":"最终策略", "polar_only":"仅双环", "joint_all":"联合调度",
27         "optical":"条带光学", "joint_center":"中心联合", "joint_guarded":"半径联合",
28         "joint_unknown":"中心联合+未知扫描", "joint_useful":"中心联合+筛选补测",
29         "polar_seed":"双环990/1865", "polar_compact":"双环940/1870",
30         "polar_joint":"双环+中心联合", "polar_guarded":"双环+半径联合",
31         "polar_unknown":"双环联合+未知扫描", "polar_useful":"双环联合+筛选补测", "combined":"双环中心联合+条带"}
32
33
34 def checked_rows(data):
35     assert data["total_runs"] == len(data["runs"])
36     for row in data["runs"]:
37         assert row["evidence"] == "local_synthetic_not_official"
38         assert row["certificate_complete"] and row["timing_independently_verified"]
39         assert row["n_cleared"] == row["n_sources"] and row["fraction_cleared"] == 1
40         assert row["exit_reason"] == "user_exit"
41         assert math.isclose(row["average_time_s"],row["virtual_time_s"]/row["n_cleared"],abs_tol=1e-9)
42         cost=row["distance_m"]/5+5*row["measures"]+row["switches"]+3*row["failed_clears"]+5*row["n_cleared"]
43         assert abs(cost-row["virtual_time_s"]) <= (row["measures"]+row["clear_attempts"])*.000001+1e-8
44     return data["runs"]
45
46
47 def main_tables(data):
48     groups=defaultdict(list)
49     for row in checked_rows(data):
50         if 4100000 <= row["seed"] <= 4100999:
51             assert row["scenario"]=="random" and row["error_mode"]=="smooth"
52             groups[row["problem"],row["configuration"]].append(row)
53     comparison_rows=[];cost_rows=[];ablation_rows=[];macro=[]
54     for problem,configs in data["configs"].items():
55         problem=int(problem)
56         for name in configs:
57             current=sorted(groups[problem,name],key=lambda r:r["seed"])
58             assert [row["seed"] for row in current]==list(range(4100000,4101000))
59             assert aggregate(current)==data["summary"][f"Q{problem}_{name}"]
60             s=aggregate(current)
61             comparison_rows.append([f"Q{problem}",LABELS[name],number(s["mean_average_time_s"]),
62                                   number(s["median_average_time_s"]),number(s["p90_average_time_s"]),

```

```

63         number(s["worst_average_time_s"]),f'{s["all_cleared_cases"]}/{s["cases"]}')
64     if name in ("control","refined"):
65         parts=[statistics.mean(row["distance_m"]/(5*row["n_sources"]) for row in current),
66               statistics.mean(5*row["measures"]/row["n_sources"] for row in current),
67               statistics.mean(row["switches"]/row["n_sources"] for row in current),
68               statistics.mean(3*row["failed_clears"]/row["n_sources"] for row in current),5.]
69         cost_rows.append([f"Q{problem}",LABELS[name],*[number(v) for v in parts],number(s["
mean_average_time_s"])]])
70     pair=paired(groups[problem,"control"],groups[problem,"refined"])
71     assert pair==data["comparison"][f"Q{problem}"]
72     word="Three" if problem==3 else "Four"
73     macro.extend([(f"ResearchQ{word}Time",number(data["summary"][f"Q{problem}_refined"]["
mean_average_time_s"])),
74                  (f"ResearchQ{word}Gain",number(pair["reduction_pct"])]))
75     macro.extend([(f"ResearchQ{word}Saved",number(pair["mean_saved_s_per_source"])),
76                  (f"ResearchQ{word}Lower",number(pair["approx_95pct_ci_s"][0])),
77                  (f"ResearchQ{word}Upper",number(pair["approx_95pct_ci_s"][1]))])
78     for key,value in data["comparison"][f"Q{problem}_incremental"].items():
79         a,b=key.split("_to_")
80         assert paired(groups[problem,a],groups[problem,b])==value
81         ablation_rows.append([f"Q{problem}",LABELS[a]+"至"+LABELS[b],number(value["mean_saved_s_per_source"]
)],
82                               f'[{number(value["approx_95pct_ci_s"][0])}, {number(value["approx_95pct_ci_s"][1])}]',f'{value
["faster_cases"]}/1000')
83     macro.append(("ResearchRuns",str(data["total_runs"])))
84     atomic_bytes(GENERATED/"research_numbers.tex",("\n".join("\newcommand{\"+k+\">{+v+\}" for k,v in macro)+"
\n").encode())
85     table("research_comparison.tex",["问题","配置","均值","中位数","$p_{90}$","最坏","全清"],comparison_rows)
86     table("research_costs.tex",["问题","配置","移动","检测","换频","失败","成功","合计"],cost_rows)
87     table("research_ablation.tex",["问题","单步增量","节省均值","r近似95%区间","更快案例"],ablation_rows)
88     return groups
89
90
91 def auxiliary_tables([data,development]):
92     scenario_labels={"minimum_radius":"最小半径","outward_boundary":"边界外向","clustered":"边缘聚集","random":"
随机位置"}
93     mode_labels={"smooth":"平滑","extreme":"端点","iid_location":"位置哈希"}
94     pressure=[]
95     for key,item in data["stress"].items():
96         problem=int(key[1]);suffix=key[3:]
97         scenario=next(s for s in scenario_labels if suffix.startswith(s+"_"))
98         mode=suffix[len(scenario)+1:]
99         control=[r for r in data["runs"] if r["problem"]==problem and r["scenario"]==scenario and r["error_mode
"]=="mode and r["configuration"]=="control" and 4200000<=r["seed"]<4220000]
100         refined=[r for r in data["runs"] if r["problem"]==problem and r["scenario"]==scenario and r["error_mode
"]=="mode and r["configuration"]=="refined" and 4200000<=r["seed"]<4220000]
101         assert aggregate(control)==item["control"] and aggregate(refined)==item["refined"]
102         assert paired(control,refined)==item["paired"]
103         pressure.append([f"Q{problem}",scenario_labels[scenario],mode_labels[mode],
104                          number(item["control"]["mean_average_time_s"]),number(item["refined"]["mean_average_time_s"]),
105                          number(item["paired"]["mean_saved_s_per_source"])],f'{item["paired"]["faster_cases"]}/{len(control)}
'])
106     table("research_stress.tex",["问题","位置场景","误差场","对照","最终","节省","更快"],pressure)
107     sensitivities=[]
108     for key,value in data["sensitivity"].items():
109         p=int(key[1]);scale=float(key.split("_")[-1])
110         current=[r for r in data["runs"] if r["problem"]==p and 4300000<=r["seed"]<4300050 and r["probe_scale"
]=="scale]
111         assert aggregate(current)==value
112         sensitivities.append([f"Q{p}",str(scale),number(value["mean_average_time_s"]),number(value["
p90_average_time_s"])],f'{value["all_cleared_cases"]}/50')
113     table("research_sensitivity.tex",["问题","横偏移比例","均值","$p_{90}$","全清"],sensitivities)
114     checked_rows(development)
115     screens=[]
116     for key,value in development["summary"].items():
117         p=int(key[1]);name=key[3:]
118         current=[r for r in development["runs"] if r["problem"]==p and r["configuration"]==name]

```

```

119         assert len(current)==150
120         screens.append([f"Q{p}",LABELS[name],number(value["mean_average_time_s"]),number(value["
mean_saved_s_per_source"])] ,f'{value["all_cleared_cases"]}/150'])
121     table("research_screen.tex",["问题","开发候选","均值","较对照节省","全清"],screens)
122
123
124 def coverage_figure():
125     fig,axes=plt.subplots(1,2,figsize=(16/2.54,3.5),layout="constrained")
126     for ax,points,label in zip(axes,[directional_waypoints(),polar_waypoints("compact25")],["Control: 31
lattice points","Refined: 25 polar points"]):
127         points=np.asarray(points)
128         ax.add_patch(plt.Circle((0,0),1800,fill=False,color="black",lw=1.4,label="Source disk"))
129         ax.scatter(points[:,0],points[:,1],s=15,color="#0072B2",zorder=3)
130         if "25" in label:
131             for t in polar_certificate("compact25")["triangles_ccw"]:
132                 p=points[list(t)+[t[0]]]
133                 ax.plot(p[:,0],p[:,1],color="#56B4E9",lw=.5,alpha=.7)
134         ax.set(xlim=(-2800,2800),ylim=(-2800,2800),xlabel="East (m)",ylabel="North (m)",title=label)
135         ax.set_aspect("equal");ax.set_xticks([-2000,0,2000]);ax.set_yticks([-2000,0,2000]);ax.grid(alpha=.15)
136     save_figure(fig,"research_coverage.pdf")
137
138
139 def performance_figure(groups):
140     fig,axes=plt.subplots(1,2,figsize=(16/2.54,3.2),layout="constrained")
141     for p,ax in zip((3,4),axes):
142         for name,color in (("control","#0072B2"),("refined","#D55E00")):
143             values=sorted(r["average_time_s"] for r in groups[p,name])
144             ax.plot(values,np.arange(1,len(values)+1)/len(values),label="Control" if name=="control" else "
Refined",color=color,lw=1.5)
145         ax.set(xlabel="Total time / cleared source (s)",ylabel="Empirical cumulative probability",title=f"Q{p}:
1,000 paired worlds",ylim=(0,1))
146         ax.legend(loc="lower right");ax.grid(alpha=.2)
147     save_figure(fig,"research_performance.pdf")
148
149
150 def trajectories():
151     fig,axes=plt.subplots(1,2,figsize=(16/2.54,3.8),layout="constrained")
152     summaries={}
153     for p,ax in zip((3,4),axes):
154         environment=LocalSimulator(20260910,problem=p)
155         planner=Planner(environment,problem=p)
156         result=planner.run();truth_after_exit=environment.summary()
157         assert result["strategy"]=="refined" and result["certificate_complete"]
158         assert result["n_cleared"]==truth_after_exit["n_sources"]
159         route=[(0.,0.)];clears=[]
160         for event in environment.log:
161             request,response=event["request"],event["response"]
162             if response["accepted"] and "position" in request:
163                 point=(request["position"]["x"],request["position"]["y"])
164                 route.append(point)
165                 if response.get("clear_result")=="success":clears.append(point)
166         route=np.asarray(route);clears=np.asarray(clears);anchors=np.asarray(planner.waypoints)
167         ax.add_patch(plt.Circle((0,0),1800,fill=False,color="black",lw=1))
168         ax.plot(route[:,0],route[:,1],color="#0072B2",lw=.65,alpha=.75,label="Accepted movement")
169         ax.scatter(anchors[:,0],anchors[:,1],color="gray",s=12,marker="+",label="Discovery points")
170         ax.scatter(clears[:,0],clears[:,1],color="#D55E00",s=18,marker="x",label="Successful clear positions")
171         ax.set(xlim=(-2350,2350),ylim=(-2350,2350),xlabel="East (m)",ylabel="North (m)",title=f"Q{p}: T={result
['virtual_time_s']:.1f} s")
172         ax.set_aspect("equal");ax.set_xticks([-2000,0,2000]);ax.set_yticks([-2000,0,2000]);ax.grid(alpha=.15)
173         evidence={"evidence":"observable_local_synthetic_trajectory_not_official","seed":20260910,
174                 "planner":result,"post_exit_evaluation":truth_after_exit,"observable_log":environment.log}
175         write_json(f"research_trajectory_q{p}.json",evidence)
176         summaries[f"Q{p}"]={k:result[k] for k in ("n_cleared","virtual_time_s","average_time_s",
certificate_complete")}
177     handles,labels=axes[0].get_legend_handles_labels()
178     fig.legend(handles,labels,loc="outside lower center",ncol=1,fontsize=8)
179     save_figure(fig,"research_trajectories.pdf")

```

```

180     return summaries
181
182
183 def main():
184     data=json.loads((ROOT/"results/research_experiments.json").read_text())
185     development=json.loads((ROOT/"results/refinement_development.json").read_text())
186     assert data["total_runs"]==10700 and development["total_runs"]==2550
187     groups=main_tables(data);auxiliary_tables(data,development)
188     coverage_figure();performance_figure(groups);traces=trajectories()
189     inputs=["results/research_experiments.json","results/refinement_development.json","results/
        research_verification.json",
190            "planner.py","geometry.py","coverage.py","environment.py","polar_coverage_candidate.py",
191            "joint_dispatch_candidate.py","make_research_assets.py","research_experiments.py","refinement_study
        .py"]
192     write_json("research_metadata.json",{ "evidence":data["evidence"],"official_calls":0,"total_runs":10700,
193            "development_runs":2550,"input_sha256":{name:hashlib.sha256((ROOT/name).read_bytes()).hexdigest
        () for name in inputs},
194            "summary":data["summary"],"comparison":data["comparison"],"trajectory_summary":traces})
195     print(json.dumps({"research_runs":10700,"development_runs":2550,"main_groups":len(groups),"
        trajectory_summary":traces},indent=2))
196
197
198 if __name__=="__main__":
199     main()

```

Listing 35: 官方演练汇总资产生成

```

1  """Generate a compact table from user-supplied official practice observations."""
2
3  from __future__ import annotations
4  import hashlib
5  import json
6  from pathlib import Path
7
8  ROOT = Path(__file__).resolve().parent
9  GENERATED = ROOT / "report" / "generated"
10
11
12 def fmt(value):
13     return f"{float(value):.2f}"
14
15
16 def main():
17     data = json.loads(
18         (ROOT / "results" / "official_practice_analysis.json").read_text(
19             encoding="utf-8"
20         )
21     )
22     assert data["official_practice"] is True and data["formal_test"] is False
23     assert (
24         data["offline_analysis_only"] is True
25         and data["hidden_truth_used_online"] is False
26     )
27     assert len(data["runs"]) == 20
28     rows = []
29     for row in data["runs"]:
30         assert row["certificate_complete"] is True
31         assert row["n_cleared"] == row["source_count"] == row["n_cleared"]
32         assert (
33             abs(
34                 float(row["average_time_s"])
35                 - float(row["virtual_time_s"]) / row["n_cleared"]
36             )
37             < 1e-5
38         )
39         assert (
40             abs(float(row["accounted_virtual_time_s"]) - float(row["virtual_time_s"]))

```

```

41         < 2e-5
42     )
43     rows.append(
44         [
45             f"Q{row['problem']}",
46             str(row["round"]),
47             row["case_code"],
48             str(row["source_count"]),
49             str(row["n_cleared"]),
50             fmt(row["virtual_time_s"]),
51             fmt(row["average_time_s"]),
52         ]
53     )
54     lines = [
55         r"\begin{tabular}{rrlrrrr}",
56         r"\toprule",
57         "题号 & 轮次 & 案例编码 & $N$ & $K$ & $T$/s & $T/K$/(s/源) \\\\",
58         r"\midrule",
59     ]
60     lines += [" & ".join(row) + r" \\" for row in rows]
61     lines += [r"\bottomrule", r"\end{tabular}"]
62     (GENERATED / "official_practice_table.tex").write_text(
63         "\n".join(lines) + "\n", encoding="utf-8"
64     )
65     q3 = data["summary"]["3"]
66     q4 = data["summary"]["4"]
67     macros = {
68         "OfficialQThreeWeighted": fmt(q3["weighted_s_per_source"]),
69         "OfficialQThreeMeanRun": fmt(q3["mean_per_source_s"]),
70         "OfficialQThreeMedianRun": fmt(q3["median_per_source_s"]),
71         "OfficialQThreeSourceTotal": str(q3["source_total"]),
72         "OfficialQFourWeighted": fmt(q4["weighted_s_per_source"]),
73         "OfficialQFourMeanRun": fmt(q4["mean_per_source_s"]),
74         "OfficialQFourMedianRun": fmt(q4["median_per_source_s"]),
75         "OfficialQFourSourceTotal": str(q4["source_total"]),
76         "OfficialPracticeRuns": str(data["run_count"]),
77     }
78     (GENERATED / "official_practice_numbers.tex").write_text(
79         "\n".join("\newcommand{\\" + k + "{\\" + v + "}" for k, v in macros.items())
80         + "\n",
81         encoding="utf-8",
82     )
83     (GENERATED / "official_practice_metadata.json").write_text(
84         json.dumps(
85             {
86                 "evidence": "user_supplied_official_practice_observations_not_formal_scores",
87                 "input_sha256": {
88                     "results/official_practice_analysis.json": hashlib.sha256(
89                         (ROOT / "results/official_practice_analysis.json").read_bytes()
90                     ).hexdigest()
91                 },
92                 "run_count": data["run_count"],
93             },
94             ensure_ascii=False,
95             indent=2,
96         )
97         + "\n",
98         encoding="utf-8",
99     )
100     print(
101         json.dumps(
102             {
103                 "evidence": data["evidence"],
104                 "runs": len(data["runs"]),
105                 "q3_weighted": q3["weighted_s_per_source"],
106                 "q4_weighted": q4["weighted_s_per_source"],
107             },

```

```

108         ensure_ascii=False,
109     )
110 )
111
112
113 if __name__ == "__main__":
114     main()

```

Listing 36: fast25 与 compact25 配对筛选

```

1 from pathlib import Path
2 import json, statistics, sys
3
4 sys.path.insert(0, str(Path(__file__).resolve().parent))
5 from experiments import run_case
6
7 old = []
8 new = []
9 for seed in range(4100000, 4101000):
10     old.append(
11         run_case(
12             seed,
13             4,
14             "enhanced",
15             coverage_policy="compact25",
16             dispatch_policy="guarded",
17             scan_policy="useful",
18         )
19     )
20     new.append(
21         run_case(
22             seed,
23             4,
24             "refined",
25             coverage_policy="fast25",
26             dispatch_policy="guarded",
27             scan_policy="useful",
28         )
29     )
30 d = [a["average_time_s"] - b["average_time_s"] for a, b in zip(old, new)]
31 summary = {
32     "evidence": "local_synthetic_paired_check_not_official",
33     "seed_range": [4100000, 4100999],
34     "cases": len(d),
35     "compact_mean": statistics.mean(r["average_time_s"] for r in old),
36     "fast_mean": statistics.mean(r["average_time_s"] for r in new),
37     "mean_saved_fast": statistics.mean(d),
38     "median_saved_fast": statistics.median(d),
39     "approx_95pct_ci": [
40         statistics.mean(d) - 1.96 * statistics.stdev(d) / (len(d) ** 0.5),
41         statistics.mean(d) + 1.96 * statistics.stdev(d) / (len(d) ** 0.5),
42     ],
43     "faster_cases": sum(x > 0 for x in d),
44     "compact_all_clear": sum(r["fraction_cleared"] == 1 for r in old),
45     "fast_all_clear": sum(r["fraction_cleared"] == 1 for r in new),
46     "compact_mean_distance": statistics.mean(r["distance_m"] for r in old),
47     "fast_mean_distance": statistics.mean(r["distance_m"] for r in new),
48     "compact_mean_measures": statistics.mean(r["measures"] for r in old),
49     "fast_mean_measures": statistics.mean(r["measures"] for r in new),
50     "compact_mean_failures": statistics.mean(r["failed_clears"] for r in old),
51     "fast_mean_failures": statistics.mean(r["failed_clears"] for r in new),
52 }
53 print(json.dumps(summary, indent=2))
54 for row in old:
55     row["configuration"] = "compact25"
56 for row in new:
57     row["configuration"] = "fast25"

```

```

58 summary["total_runs"] = len(old) + len(new)
59 summary["runs"] = old + new
60 Path("results/fast_vs_compact_410.json").write_text(
61     json.dumps(summary, indent=2) + "\n"
62 )

```

Listing 37: 官方演练驱动的新策略

```

1  """Field-informed candidates; consumes public responses, never practice labels.
2
3  Historical Planner(strategy='refined') remains unchanged. Candidate options
4  are explicit for paired ablation, and only verified configurations are exposed
5  by the final runner.
6  """
7
8  from __future__ import annotations
9
10 from math import dist, sqrt
11
12 from geometry import enclosing_circle
13 from joint_dispatch_candidate import choose_task
14 from negative_geometry import exclude_omni_disk
15 from planner import InconsistentObservations, Planner
16 from route_portfolio import choose_portfolio_task
17
18
19 class FieldPlanner(Planner):
20     def __init__(
21         self,
22         environment,
23         problem=3,
24         *,
25         premeasure=True,
26         negative_updates=True,
27         portfolio=True,
28         risk_weight=None,
29         probe_scale=0.22,
30         approach_clear=None,
31     ):
32         super().__init__(
33             environment, problem=problem, strategy="refined", probe_scale=probe_scale
34         )
35         self.premeasure = premeasure
36         self.negative_updates = negative_updates and problem == 3
37         self.portfolio = portfolio
38         self.approach_clear = problem == 3 if approach_clear is None else approach_clear
39         self.risk_weight = (
40             (0.0 if problem == 3 else 1.0) if risk_weight is None else risk_weight
41         )
42         self.negative_stations = {channel: [] for channel in range(1, 21)}
43         self.premeasured_channels = set()
44         self.zero_travel_probes = 0
45         self.negative_cuts = 0
46         self.clear_access_saved_m = 0.0
47
48     def measure(self, channel, point):
49         status = super().measure(channel, point)
50         if not self.negative_updates or channel in self.cleared:
51             return status
52         if status == "no_signal":
53             self.negative_stations[channel].append(tuple(point))
54         track = self.tracks.get(channel)
55         if track is not None and status in ("direction", "no_signal"):
56             # A convex outer approximation remains safe after each disk
57             # exclusion, including negatives collected before first detection.
58             for station in self.negative_stations[channel]:
59                 before = track.polygon

```

```

60         track.polygon = exclude_omni_disk(before, station, sides=16)
61         self.negative_cuts += track.polygon != before
62         if not track.polygon:
63             raise InconsistentObservations(
64                 "Omnidirectional negative readings exclude the entire track"
65             )
66         return status
67
68     def localize(self, channel):
69         track = self.tracks.get(channel)
70         if (
71             self.premeasure
72             and channel not in self.premeasured_channels
73             and track is not None
74             and self.terminal_reason is None
75         ):
76             center, radius = enclosing_circle(track.polygon)
77             if (
78                 radius > 38
79                 and tuple(self.position) not in track.observations
80                 and dist(self.position, center) - radius <= 1500
81             ):
82                 self.zero_travel_probes += 1
83                 self.measure(channel, self.position)
84                 self.premeasured_channels.add(channel)
85                 if channel in self.cleared or self.terminal_reason is not None:
86                     return
87             return super().localize(channel)
88
89     def clear(self, channel, point, guaranteed=False):
90         track = self.tracks.get(channel)
91         length = dist(self.position, point)
92         if (
93             self.approach_clear
94             and guaranteed
95             and track is not None
96             and length > 1e-6
97             and max(dist(point, p) for p in track.polygon) <= 19.9
98         ):
99             # Slide toward the robot inside the intersection of all vertex
100             # radius-19.9 disks. Each vertex supplies an exact quadratic bound.
101             u = (
102                 (self.position[0] - point[0]) / length,
103                 (self.position[1] - point[1]) / length,
104             )
105             shift = length
106             for p in track.polygon:
107                 dx, dy = point[0] - p[0], point[1] - p[1]
108                 dot = dx * u[0] + dy * u[1]
109                 discriminant = dot * dot + 19.9**2 - dx * dx - dy * dy
110                 if discriminant < 0.0:
111                     shift = 0.0
112                     break
113                 shift = min(shift, -dot + sqrt(discriminant))
114             shift = max(0.0, shift - 1e-6)
115             candidate = (point[0] + shift * u[0], point[1] + shift * u[1])
116             if max(dist(candidate, p) for p in track.polygon) <= 19.9:
117                 self.clear_access_saved_m += length - dist(self.position, candidate)
118                 point = candidate
119             return super().clear(channel, point, guaranteed=guaranteed)
120
121     def select_task(self):
122         anchors = {i: self.waypoints[i] for i in sorted(self.pending)}
123         targets = {
124             ch: enclosing_circle(track.polygon) for ch, track in self.tracks.items()
125         }
126         if self.portfolio:

```

```

127         return choose_portfolio_task(
128             self.position, anchors, targets, risk_weight=self.risk_weight
129         )
130     return choose_task(
131         self.position,
132         anchors,
133         targets,
134         choice="guarded",
135         risk_weight=self.risk_weight,
136     )
137
138     def _result(self):
139         result = super()._result()
140         result.update(
141             strategy="field",
142             premeasure=self.premeasure,
143             negative_updates=self.negative_updates,
144             portfolio=self.portfolio,
145             risk_weight=self.risk_weight,
146             zero_travel_probes=self.zero_travel_probes,
147             negative_cuts=self.negative_cuts,
148             approach_clear=self.approach_clear,
149             clear_access_saved_m=self.clear_access_saved_m,
150         )
151         return result

```

Listing 38: Q3 无信号保守几何更新

```

1  """Conservative exclusion of a station-centred open disk (Q3 only).
2
3  The routine here is deliberately independent of planner state: it only removes
4  information justified by a Q3 ``no_signal`` observation.
5  """
6
7  from __future__ import annotations
8
9  from math import cos, isfinite, pi, sin
10
11  from geometry import Point, _clip_halfplane, _cross, _padding
12
13
14  def _hull(points: list[Point]) -> list[Point]:
15      """Monotone-chain hull, retaining no duplicate vertices."""
16      pts = sorted(set(points))
17      if len(pts) <= 2:
18          return pts
19
20      lower: list[Point] = []
21      for p in pts:
22          while len(lower) >= 2 and _cross(lower[-2], lower[-1], p) <= 0.0:
23              lower.pop()
24          lower.append(p)
25      upper: list[Point] = []
26      for p in reversed(pts):
27          while len(upper) >= 2 and _cross(upper[-2], upper[-1], p) <= 0.0:
28              upper.pop()
29          upper.append(p)
30      return lower[:-1] + upper[:-1]
31
32
33  def exclude_omni_disk(
34      poly: list[Point], station: Point, radius: float = 1000.0, *, sides: int = 16
35  ) -> list[Point]:
36      """Return a conservative convex outer approximation of ``poly`` minus the open disk.
37
38      ``no_signal`` in Q3 proves that a source is strictly farther than
39      ``radius`` from ``station``. An inscribed regular polygon is used as a

```

```

40     finite certificate for the disk. Each clipped outside piece is safe, and
41     their convex hull is returned. The input list and its point objects are
42     never modified.
43     """
44     if sides not in (16, 32):
45         raise ValueError("sides must be 16 or 32")
46     if len(station) != 2 or not all(isfinite(v) for v in station):
47         raise ValueError("station must have finite coordinates")
48     if not isfinite(radius) or radius <= 0.0:
49         raise ValueError("radius must be a positive finite number")
50     if not poly:
51         return []
52     if any(len(p) != 2 or not all(isfinite(v) for v in p) for p in poly):
53         raise ValueError("polygon requires finite coordinates")
54     scale = max(1.0, radius, *(abs(v) for p in poly for v in p), *map(abs, station))
55     if not isfinite(16.0 * scale * scale):
56         raise ValueError("Geometry scale exceeds finite half-plane arithmetic")
57
58     # Q is strictly inscribed: its vertices are at radius*cos(pi/sides).
59     # This makes every Q point, including edges, safely inside the disk.
60     qradius = radius * cos(pi / sides)
61     cx, cy = station
62     q = [
63         (
64             cx + qradius * cos(2.0 * pi * i / sides),
65             cy + qradius * sin(2.0 * pi * i / sides),
66         )
67         for i in range(sides)
68     ]
69     pad = _padding(scale)
70     pieces: list[Point] = []
71
72     # Q is CCW. For edge a->b, Q satisfies cross(b-a,x-a)>=0;
73     # outside is the opposite half-plane, expressed in _clip_halfplane form.
74     for i, a in enumerate(q):
75         b = q[(i + 1) % sides]
76         ex, ey = b[0] - a[0], b[1] - a[1]
77         normal = (ey, -ex) # normal with n.(x-a) <= 0 inside Q
78         bound = 0.0
79         # If every input vertex is on this outside side, P is already safe.
80         if all(
81             normal[0] * (x - a[0]) + normal[1] * (y - a[1]) >= -pad for x, y in poly
82         ):
83             return list(poly)
84         part = _clip_halfplane(poly, a, (-normal[0], -normal[1]), -bound, pad)
85         pieces.extend(part)
86     if not pieces:
87         return []
88     return _hull(pieces)

```

Listing 39: 有界路线组合优化

```

1  """Bounded deterministic open-route portfolio using public task summaries only.
2
3  This module chooses an order, not an execution path or a clearance certificate.
4  It never executes actions, drops obligations, or reads simulator/source state.
5  """
6
7  from __future__ import annotations
8
9  from math import dist, fsum, isfinite
10
11  Point = tuple[float, float]
12  Task = tuple[str, int]
13
14
15  def _cost(

```

```

16     route: list[int],
17     origin: list[float],
18     edges: list[list[float]],
19     penalty: list[float],
20 ) -> float:
21     try:
22         value = fsum(
23             (
24                 origin[route[0]],
25                 penalty[route[0]],
26                 *(edges[a][b] for a, b in zip(route, route[1:])),
27             )
28         )
29     except OverflowError as error:
30         raise ValueError("route proxy must be finite") from error
31     if not isfinite(value):
32         raise ValueError("route proxy must be finite")
33     return value
34
35
36 def _insertion_delta(
37     route: list[int],
38     node: int,
39     gap: int,
40     origin: list[float],
41     edges: list[list[float]],
42     penalty: list[float],
43 ) -> float:
44     if gap == 0:
45         return (
46             origin[node]
47             + edges[node][route[0]]
48             - origin[route[0]]
49             + penalty[node]
50             - penalty[route[0]]
51         )
52     before = route[gap - 1]
53     delta = edges[before][node]
54     if gap < len(route):
55         after = route[gap]
56         delta += edges[node][after] - edges[before][after]
57     return delta
58
59
60 def _control_route(
61     origin: list[float], edges: list[list[float]], penalty: list[float]
62 ) -> list[int]:
63     """Exact route construction/move order of joint_dispatch_candidate.choose_task.
64
65     Keep this control independent of portfolio refinements: first task, nearest
66     updates, insertion arithmetic, scan order, tolerance and accepted-move cap
67     deliberately match the existing guarded implementation (center at weight 0).
68     """
69     n = len(origin)
70     first = min(range(n), key=lambda i: (origin[i] + penalty[i], i))
71     route = [first]
72     remaining = set(range(n))
73     remaining.remove(first)
74     nearest = [min(origin[i], edges[first][i]) for i in range(n)]
75     while remaining:
76         node = min(remaining, key=lambda i: (nearest[i], i))
77         best_gap = 0
78         best_delta = _insertion_delta(route, node, 0, origin, edges, penalty)
79         for gap in range(1, len(route) + 1):
80             delta = _insertion_delta(route, node, gap, origin, edges, penalty)
81             if delta < best_delta:
82                 best_gap, best_delta = gap, delta

```

```

83     route.insert(best_gap, node)
84     remaining.remove(node)
85     for other in remaining:
86         nearest[other] = min(nearest[other], edges[node][other])
87
88     for _ in range(n):
89         changed = False
90         for left in range(n - 1):
91             for right in range(left + 1, n):
92                 old = (
93                     origin[route[left]]
94                     if left == 0
95                     else edges[route[left - 1]][route[left]]
96                 )
97                 new = (
98                     origin[route[right]]
99                     if left == 0
100                    else edges[route[left - 1]][route[right]]
101                )
102                if right + 1 < n:
103                    old += edges[route[right]][route[right + 1]]
104                    new += edges[route[left]][route[right + 1]]
105                if left == 0:
106                    old += penalty[route[left]]
107                    new += penalty[route[right]]
108                if new + 1e-12 * max(1.0, old, new) < old:
109                    route[left : right + 1] = reversed(route[left : right + 1])
110                    changed = True
111                    break
112            if changed:
113                break
114        if not changed:
115            break
116    return route
117
118
119 def _cheapest_route(
120     origin: list[float], edges: list[list[float]], penalty: list[float]
121 ) -> list[int]:
122     """Choose the globally cheapest (remaining task, gap), not nearest task."""
123     n = len(origin)
124     first = min(range(n), key=lambda i: (origin[i] + penalty[i], i))
125     route = [first]
126     remaining = set(range(n))
127     remaining.remove(first)
128     while remaining:
129         # Tuple comparison makes node/gap ties independent of set iteration.
130         _, node, gap = min(
131             (_insertion_delta(route, node, gap, origin, edges, penalty), node, gap)
132             for node in remaining
133             for gap in range(len(route) + 1)
134         )
135         route.insert(gap, node)
136         remaining.remove(node)
137     return route
138
139
140 def _nearest_route(first: int, edges: list[list[float]]) -> list[int]:
141     remaining = set(range(len(edges)))
142     remaining.remove(first)
143     route = [first]
144     while remaining:
145         node = min(remaining, key=lambda i: (edges[route[-1]][i], i))
146         route.append(node)
147         remaining.remove(node)
148     return route
149

```

```

150
151 def _improve(
152     route: list[int],
153     origin: list[float],
154     edges: list[list[float]],
155     penalty: list[float],
156 ) -> tuple[list[int], float]:
157     """Best improvement across reversals and one-node relocations, bounded passes."""
158     n = len(route)
159     cost = _cost(route, origin, edges, penalty)
160     for _ in range(min(n, 12)):
161         # Ignore changes below the scale-dependent numerical margin. Every
162         # accepted move is also checked against the complete recomputed proxy.
163         best_delta = -1e-12 * max(1.0, cost)
164         move: tuple[str, int, int] | None = None
165         for left in range(n - 1):
166             for right in range(left + 1, n):
167                 old = (
168                     origin[route[left]]
169                     if left == 0
170                     else edges[route[left - 1]][route[left]]
171                 )
172                 new = (
173                     origin[route[right]]
174                     if left == 0
175                     else edges[route[left - 1]][route[right]]
176                 )
177                 if right + 1 < n:
178                     old += edges[route[right]][route[right + 1]]
179                     new += edges[route[left]][route[right + 1]]
180                 if left == 0:
181                     old += penalty[route[left]]
182                     new += penalty[route[right]]
183                 delta = new - old
184                 if delta < best_delta:
185                     best_delta, move = delta, ("reverse", left, right)
186
187         for index, node in enumerate(route):
188             if n == 1:
189                 break
190             if index == 0:
191                 following = route[1]
192                 removal = (
193                     origin[following]
194                     + penalty[following]
195                     - origin[node]
196                     - penalty[node]
197                     - edges[node][following]
198                 )
199             else:
200                 before = route[index - 1]
201                 removal = -edges[before][node]
202                 if index + 1 < n:
203                     following = route[index + 1]
204                     removal += edges[before][following] - edges[node][following]
205             # Gaps are in the ORIGINAL route. The two adjacent gaps are no-ops;
206             # every other gap retains its endpoints when node is removed.
207             for gap in range(n + 1):
208                 if gap == index or gap == index + 1:
209                     continue
210                 delta = removal + _insertion_delta(
211                     route, node, gap, origin, edges, penalty
212                 )
213                 if delta < best_delta:
214                     best_delta, move = delta, ("relocate", index, gap)
215
216     if move is None:

```

```

217         break
218     candidate = route.copy()
219     kind, left, right = move
220     if kind == "reverse":
221         candidate[left : right + 1] = reversed(candidate[left : right + 1])
222     else:
223         node = candidate.pop(left)
224         candidate.insert(right if right < left else right - 1, node)
225         candidate_cost = _cost(candidate, origin, edges, penalty)
226         if not candidate_cost < cost:
227             # Cancellation in an edge delta must never worsen the true proxy.
228             break
229         route, cost = candidate, candidate_cost
230     return route, cost
231
232
233 def choose_portfolio_task(
234     position: Point,
235     anchors: dict[int, Point],
236     targets: dict[int, tuple[Point, float]],
237     risk_weight: float = 1.0,
238 ) -> Task:
239     """Return the first task of the best complete deterministic open permutation.
240
241     Proxy = origin-to-first distance + all consecutive center/anchor distances
242     + risk_weight * first target radius (zero for a first anchor). Weight zero
243     reproduces the old center objective. No return-to-origin edge is charged.
244     The retained control is exactly the old nearest-insertion/capped-2-opt
245     route, so the selected complete route's computed proxy is never worse.
246     This is NOT a guarantee about the first hop, executed distance or total T.
247
248     At most four seeds (control, global cheapest insertion, two nearest-neighbor
249     starts) receive min(n, 12) best-improvement passes each. Tasks sort target
250     before anchor, then integer key; equal costs retain the earlier candidate.
251     All tasks survive, including identical coordinates/keys across task kinds.
252     Inputs are never mutated. Empty tasks, nonfinite geometry/proxy or negative
253     radii/risk weight raise ValueError. Time  $O(n^3)$ , memory  $O(n^2)$ .
254     """
255     target_keys = sorted(targets)
256     anchor_keys = sorted(anchors)
257     tasks: list[Task] = [("target", key) for key in target_keys]
258     tasks.extend(("anchor", key) for key in anchor_keys)
259     n = len(tasks)
260     if not n:
261         raise ValueError("cannot dispatch an empty task set")
262     coords = [targets[key][0] for key in target_keys]
263     coords.extend(anchors[key] for key in anchor_keys)
264     radii = [targets[key][1] for key in target_keys]
265     radii.extend(0.0 for _ in anchor_keys)
266     if any(
267         len(point) != 2 or not all(isfinite(x) for x in point)
268         for point in [position, *coords]
269     ):
270         raise ValueError("positions must be finite two-dimensional points")
271     if any(not isfinite(radius) or radius < 0 for radius in radii):
272         raise ValueError("MEC radii must be finite and nonnegative")
273     if not isfinite(risk_weight) or risk_weight < 0:
274         raise ValueError("risk_weight must be finite and nonnegative")
275     penalty = [risk_weight * radius for radius in radii]
276     if any(not isfinite(value) for value in penalty):
277         raise ValueError("weighted radii must be finite")
278     origin = [dist(position, point) for point in coords]
279     edges = [[0.0] * n for _ in range(n)]
280     for i in range(n):
281         for j in range(i):
282             edges[i][j] = edges[j][i] = dist(coords[i], coords[j])
283     if any(not isfinite(value) for value in origin) or any(

```

```

284         not isfinite(value) for row in edges for value in row
285     ):
286         raise ValueError("pairwise distances must be finite")
287     # This conservative finite upper bound also excludes overflow in local
288     # delta arithmetic; physical simulator distances are far below this limit.
289     try:
290         bound = fsum((max(origin), max(penalty), *(max(row) for row in edges)))
291     except OverflowError as error:
292         raise ValueError("route proxy bound must be finite") from error
293     if not isfinite(bound):
294         raise ValueError("route proxy bound must be finite")
295
296     control = _control_route(origin, edges, penalty)
297     control_cost = _cost(control, origin, edges, penalty)
298     best_route, best_cost = control, control_cost
299     # The second start is the next distinct task in origin+penalty order, not
300     # another random restart or a second copy of the same first task.
301     starts = sorted(range(n), key=lambda i: (origin[i] + penalty[i], i))[:2]
302     seeds = [control, _cheapest_route(origin, edges, penalty)]
303     seeds.extend(_nearest_route(first, edges) for first in starts)
304     seen: set[tuple[int, ...]] = set()
305     for seed in seeds:
306         identity = tuple(seed)
307         if identity in seen:
308             continue
309         seen.add(identity)
310         route, cost = _improve(seed, origin, edges, penalty)
311         if cost < best_cost:
312             best_route, best_cost = route, cost
313     # Explicit control fallback guards the proxy guarantee, not actual travel.
314     if best_cost > control_cost:
315         return tasks[control[0]]
316     return tasks[best_route[0]]

```

Listing 40: 新策略独立开发筛选

```

1  """Finite field-informed development screen; no official counterfactual claims."""
2
3  from __future__ import annotations
4  import argparse
5  import json
6  import math
7  import statistics
8  from pathlib import Path
9  from environment import LocalSimulator
10 from field_policy import FieldPlanner
11 from planner import Planner
12
13 CONFIGS = {
14     "control": None,
15     "premeasure": {"premeasure": True},
16     "negative": {"premeasure": False, "negative_updates": True},
17     "pre_negative": {"premeasure": True, "negative_updates": True},
18     "risk2": {"premeasure": True, "risk_weight": 2.0},
19     "risk4": {"premeasure": True, "risk_weight": 4.0},
20     "risk8": {"premeasure": True, "risk_weight": 8.0},
21     "portfolio": {"premeasure": True, "portfolio": True},
22     "portfolio_negative": {
23         "premeasure": True,
24         "portfolio": True,
25         "negative_updates": True,
26     },
27     "portfolio_risk2": {"premeasure": True, "portfolio": True, "risk_weight": 2.0},
28     "portfolio_clear": {"premeasure": True, "portfolio": True, "approach_clear": True},
29     "all": {
30         "premeasure": True,
31         "portfolio": True,

```

```

32     "negative_updates": True,
33     "approach_clear": True,
34 },
35 }
36
37
38 def run_field(seed, problem, config, scenario="random", mode="smooth"):
39     env = LocalSimulator(seed, problem, mode, scenario)
40     settings = {
41         "premeasure": False,
42         "negative_updates": False,
43         "portfolio": False,
44         "approach_clear": False,
45     }
46     planner = (
47         Planner(env, problem, probe_scale=0.22)
48         if config is None
49         else FieldPlanner(env, problem, **(settings | config))
50     )
51     result = planner.run()
52     actual = env.summary()
53     assert (
54         result["certificate_complete"] and actual["n_cleared"] == actual["n_sources"]
55     ), (seed, problem, result, actual)
56     pos = (0.0, 0.0)
57     radio = 1
58     us = 0
59     successes = set()
60     for event in env.log:
61         request, response = event["request"], event["response"]
62         assert response["accepted"]
63         if request["path"] in ("/measure", "/clear"):
64             p = request["position"]["x"], request["position"]["y"]
65             us += round(math.dist(pos, p) / 5 * 1000000)
66             pos = p
67             if request["path"] == "/measure":
68                 us += (5 + int(radio != request["channel"])) * 1000000
69                 radio = request["channel"]
70             else:
71                 success = response["clear_result"] == "success"
72                 us += (5 if success else 3) * 1000000
73                 if success:
74                     assert request["channel"] not in successes
75                     successes.add(request["channel"])
76         assert abs(us / 1000000 - response["virtual_time_s"]) < 2e-6
77     assert len(successes) == actual["n_sources"]
78     return {
79         **actual,
80         "certificate_complete": True,
81         "timing_independently_verified": True,
82         "zero_travel_probes": result.get("zero_travel_probes", 0),
83         "negative_cuts": result.get("negative_cuts", 0),
84     }
85
86
87 def pair_stats(control, candidate):
88     assert [r["seed"] for r in control] == [r["seed"] for r in candidate]
89     diffs = [
90         a["average_time_s"] - b["average_time_s"]
91         for a, b in zip(control, candidate, strict=True)
92     ]
93     mean = statistics.mean(diffs)
94     se = statistics.stdev(diffs) / math.sqrt(len(diffs))
95     return {
96         "mean_saved_s": mean,
97         "saving_pct": 100
98         * mean

```

```

99         / statistics.mean(r["average_time_s"] for r in control),
100         "approx_95pct_ci": [mean - 1.96 * se, mean + 1.96 * se],
101         "faster_cases": sum(d > 0 for d in diffs),
102     }
103
104
105 def summarize(group):
106     values = sorted(r["average_time_s"] for r in group)
107     return {
108         "cases": len(group),
109         "all_clear": sum(r["fraction_cleared"] == 1 for r in group),
110         "mean": statistics.mean(values),
111         "p90": values[math.ceil(0.9 * len(values)) - 1],
112         "worst": max(values),
113         "distance": statistics.mean(r["distance_m"] for r in group),
114         "measures": statistics.mean(r["measures"] for r in group),
115         "mean_failed_clear_attempts_per_case": statistics.mean(
116             r["failed_clears"] for r in group
117         ),
118         "max_real_s": max(r["real_duration_s"] for r in group),
119     }
120
121
122 def main():
123     parser = argparse.ArgumentParser()
124     parser.add_argument("--cases", type=int, default=150)
125     parser.add_argument("--seed", type=int, default=6100000)
126     parser.add_argument(
127         "--output", type=Path, default=Path("results/field_development.json")
128     )
129     args = parser.parse_args()
130     summaries = {}
131     rows = []
132     for p in (3, 4):
133         names = (
134             (
135                 "control",
136                 "premeasure",
137                 "negative",
138                 "pre_negative",
139                 "portfolio",
140                 "portfolio_negative",
141                 "all",
142             )
143             if p == 3
144             else (
145                 "control",
146                 "premeasure",
147                 "risk2",
148                 "risk4",
149                 "risk8",
150                 "portfolio",
151                 "portfolio_risk2",
152                 "portfolio_clear",
153             )
154         )
155     control = None
156     for name in names:
157         group = [
158             run_field(seed, p, CONFIGS[name])
159             for seed in range(args.seed, args.seed + args.cases)
160         ]
161         for row in group:
162             row["configuration"] = name
163         rows.extend(group)
164         if control is None:
165             control = group

```

```

166         summaries[f"Q{p}_{name}"] = {
167             **summarize(group),
168             **pair_stats(control, group),
169         }
170         print(f"Q{p}_{name}", json.dumps(summaries[f"Q{p}_{name}"]), flush=True)
171     args.output.write_text(
172         json.dumps(
173             {
174                 "evidence": "field_informed_local_development_not_official",
175                 "seed_range": [args.seed, args.seed + args.cases - 1],
176                 "configs": CONFIGS,
177                 "summary": summaries,
178                 "total_runs": len(rows),
179                 "runs": rows,
180             },
181             ensure_ascii=False,
182             indent=2,
183         )
184         + "\n"
185     )
186
187
188 if __name__ == "__main__":
189     main()

```

Listing 41: 新策略冻结后的新世界确认

```

1  """Frozen field-policy confirmation; disjoint from official and development cases."""
2
3  from __future__ import annotations
4  import json
5  from pathlib import Path
6  from field_study import run_field, pair_stats, summarize
7
8  CONFIGS = {
9      3: {
10         "control": None,
11         "route_only": {"premeasure": False, "portfolio": True},
12         "route_info": {"premeasure": True, "negative_updates": True, "portfolio": True},
13         "field": {
14             "premeasure": True,
15             "negative_updates": True,
16             "portfolio": True,
17             "approach_clear": True,
18         },
19     },
20     4: {"control": None, "field": {"premeasure": True, "portfolio": True}},
21 }
22
23
24 def group(problem, name, seeds, scenario="random", mode="smooth"):
25     rows = [
26         run_field(seed, problem, CONFIGS[problem][name], scenario, mode)
27         for seed in seeds
28     ]
29     for row in rows:
30         row["configuration"] = name
31     return rows
32
33
34 def main():
35     records = []
36     summary = {}
37     comparisons = {}
38     stress = {}
39     for p in (3, 4):
40         groups = {}

```

```

41     for name in CONFIGS[p]:
42         groups[name] = group(p, name, range(7100000, 7101000))
43         records.extend(groups[name])
44         summary[f"Q{p}_{name}"] = summarize(groups[name])
45     comparisons[f"Q{p}"] = pair_stats(groups["control"], groups["field"])
46     comparisons[f"Q{p}_ablation"] = {
47         f"{a}_to_{b}": pair_stats(groups[a], groups[b])
48         for a, b in zip(groups, list(groups)[1:])
49     }
50     print(f"Q{p}", json.dumps(comparisons[f"Q{p}"]), flush=True)
51     cases = [
52         (s, m, range(7200000, 7200050))
53         for s in ("minimum_radius", "outward_boundary", "clustered")
54         for m in ("smooth", "extreme", "iid_location")
55     ]
56     cases += [
57         ("random", m, range(7210000, 7210200)) for m in ("extreme", "iid_location")
58     ]
59     for s, m, seeds in cases:
60         a = group(p, "control", seeds, s, m)
61         b = group(p, "field", seeds, s, m)
62         records.extend(a)
63         records.extend(b)
64         key = f"Q{p}_{s}_{m}"
65         stress[key] = {
66             "control": summarize(a),
67             "field": summarize(b),
68             "paired": pair_stats(a, b),
69         }
70         print(key, json.dumps(stress[key]["paired"]), flush=True)
71     result = {
72         "evidence": "fresh_local_paired_confirmation_not_official_counterfactual",
73         "selection": "Selected using official-observation bottlenecks and development seeds6100000..6100149",
74         "main_seed_range": [7100000, 7100999],
75         "stress_seed_range": [7200000, 7200049],
76         "alternate_error_seed_range": [7210000, 7210199],
77         "development_seed_range": [6100000, 6100149],
78         "main_runs": 6000,
79         "stress_runs": 1800,
80         "alternate_error_runs": 1600,
81         "total_runs": len(records),
82         "configs": CONFIGS,
83         "summary": summary,
84         "comparison": comparisons,
85         "stress": stress,
86         "runs": records,
87     }
88     assert len(records) == 9400
89     Path("results/field_confirmation.json").write_text(
90         json.dumps(result, ensure_ascii=False, indent=2) + "\n"
91     )
92     print(json.dumps({"total_runs": len(records), "summary": summary}, indent=2))
93
94
95 if __name__ == "__main__":
96     main()

```

Listing 42: 新策略几何和行为核验

```

1  """Boundary/invariant checks for field policy; synthetic and analytic evidence."""
2
3  from __future__ import annotations
4  import json
5  import math
6  from pathlib import Path
7  import random

```

```

8
9 from field_policy import FieldPlanner
10 from geometry import _cross, clip_bearing, enclosing_circle, initial_polygon
11 from negative_geometry import exclude_omni_disk
12 from planner import Track
13 from route_portfolio import _control_route, _cost, _improve, choose_portfolio_task
14 from joint_dispatch_candidate import choose_task
15 from verify_terminal import DeadlineAdapter
16
17
18 def contains(poly, p, tolerance=2e-6):
19     if not poly:
20         return False
21     if len(poly) == 1:
22         return math.dist(poly[0], p) <= tolerance
23     if len(poly) == 2:
24         a, b = poly
25         return abs(math.dist(a, p) + math.dist(b, p) - math.dist(a, b)) <= tolerance
26     return all(
27         _cross(poly[i], poly[(i + 1) % len(poly)], p)
28         >= -tolerance * max(1, math.dist(poly[i], poly[(i + 1) % len(poly)]))
29         for i in range(len(poly))
30     )
31
32
33 def negative_checks():
34     rng = random.Random(6311000)
35     count = 0
36     largest_cut = 0.0
37     for sides in (16, 32):
38         for index in range(500):
39             phi = rng.uniform(0, math.tau)
40             r = 1800 * math.sqrt(rng.random())
41             source = (r * math.cos(phi), r * math.sin(phi))
42             theta = rng.uniform(0, math.tau)
43             distance = rng.uniform(6, 1500)
44             station = (
45                 source[0] - distance * math.cos(theta),
46                 source[1] - distance * math.sin(theta),
47             )
48             poly = clip_bearing(
49                 initial_polygon(),
50                 station,
51                 (math.degrees(theta) + rng.uniform(-1, 1)) % 360,
52             )
53             for j in range(3):
54                 a = rng.uniform(0, math.tau)
55                 gap = 1000 + 1e-8 if index % 3 == 0 else rng.uniform(1000, 2500)
56                 negative = (
57                     source[0] + gap * math.cos(a),
58                     source[1] + gap * math.sin(a),
59                 )
60                 before = poly.copy()
61                 poly = exclude_omni_disk(poly, negative, sides=sides)
62                 assert before and poly and contains(poly, source), (
63                     sides,
64                     index,
65                     source,
66                     negative,
67                 )
68                 assert all(contains(before, v) for v in poly)
69                 largest_cut = max(
70                     largest_cut, enclosing_circle(before)[1] - enclosing_circle(poly)[1]
71                 )
72                 count += 1
73             assert exclude_omni_disk([(1000.0, 0.0)], (0.0, 0.0), sides=sides) == [
74                 (1000.0, 0.0)

```

```

75     ]
76     assert exclude_omni_disk([(0.0, 0.0)], (0.0, 0.0), sides=sides) == []
77     segment = [(-1200.0, 0.0), (1200.0, 0.0)]
78     assert exclude_omni_disk(segment, (0.0, 0.0), sides=sides) == segment
79     for shift in ((2e6, -2e6), (0.0, 0.0)):
80         p = [
81             (shift[0] + 1200, shift[1] - 5),
82             (shift[0] + 1400, shift[1] - 5),
83             (shift[0] + 1400, shift[1] + 5),
84         ]
85         assert exclude_omni_disk(p, shift, sides=sides) == p
86     try:
87         exclude_omni_disk([(0.0, 0.0)], (1e308, 1e308), radius=1e308)
88     except ValueError:
89         pass
90     else:
91         raise AssertionError("Unrepresentable half-plane arithmetic must be rejected")
92     return {
93         "true_source_containment_cases": count,
94         "boundary_and_degenerate_cases": 10,
95         "maximum_observed_radius_cut_m": largest_cut,
96         "scope": "sampling complements finite inscribed-polygon exclusion proof",
97     }
98
99
100 def route_checks():
101     rng = random.Random(6312000)
102     cases = 0
103     for n in (1, 2, 3, 7, 25, 41, 51):
104         for iteration in range(10):
105             pts = [
106                 (rng.uniform(-2500, 2500), rng.uniform(-2500, 2500)) for _ in range(n)
107             ]
108             pos = (rng.uniform(-1000, 1000), rng.uniform(-1000, 1000))
109             penalty = [rng.uniform(0, 750) for _ in pts]
110             origin = [math.dist(pos, p) for p in pts]
111             edges = [[math.dist(a, b) for b in pts] for a in pts]
112             control = _control_route(origin, edges, penalty)
113             improved, cost = _improve(control, origin, edges, penalty)
114             assert sorted(improved) == list(range(n)) and cost <= _cost(
115                 control, origin, edges, penalty
116             )
117             targets = {i: (p, penalty[i]) for i, p in enumerate(pts)}
118             assert choose_task(pos, {}, targets, choice="guarded") == (
119                 "target",
120                 control[0],
121             )
122             assert choose_portfolio_task(pos, {}, targets)[1] in targets
123             cases += 1
124     # Exact two-task optimum is useful because an open tail has no return edge.
125     for positions in (
126         ((1.0, 0.0), (2.0, 0.0)),
127         ((-1.0, 0.0), (2.0, 0.0)),
128         ((0.0, 0.0), (0.0, 0.0)),
129     ):
130         for risk in (0.0, 1.0, 2.0):
131             targets = {i: (point, float(i * 4)) for i, point in enumerate(positions)}
132             selected = choose_portfolio_task((0.0, 0.0), {}, targets, risk)
133             costs = {
134                 i: math.dist((0, 0), positions[i])
135                 + math.dist(*positions)
136                 + risk * targets[i][1]
137                 for i in range(2)
138             }
139             assert costs[selected[1]] == min(costs.values())
140     return {
141         "random_route_cases": cases,

```

```

142     "exact_two_task_cases": 9,
143     "control_never_worsened": True,
144 }
145
146
147 def clearing_checks():
148     rng = random.Random(6313000)
149     count = 0
150     saved = 0.0
151     for _ in range(200):
152         env = DeadlineAdapter(max_virtual=360000)
153         policy = FieldPlanner(env, 3, approach_clear=True)
154         policy.action("/enter")
155         c = (rng.uniform(-1500, 1500), rng.uniform(-1500, 1500))
156         radius = rng.uniform(0.01, 19.8)
157         poly = [
158             (
159                 c[0] + radius * math.cos(k * math.pi / 3),
160                 c[1] + radius * math.sin(k * math.pi / 3),
161             )
162             for k in range(6)
163         ]
164         policy.tracks[1] = Track(polygon=poly)
165         policy.channel_state[1] = "detected"
166         original = list(poly)
167         before = math.dist(policy.position, c)
168         assert policy.clear(1, c, guaranteed=True)
169         assert all(math.dist(v, policy.position) <= 19.9 for v in original)
170         assert math.dist((0, 0), policy.position) <= before + 1e-7
171         saved += policy.clear_access_saved_m
172         count += 1
173     for p in (3, 4):
174         env = DeadlineAdapter(remaining=1, max_virtual=360000)
175         result = FieldPlanner(env, p).run()
176         assert not result["certificate_complete"] and "/exit" not in env.paths
177     return {
178         "clearing_regions": count,
179         "shortened_approach_total_m": saved,
180         "real_deadline_cases": 2,
181     }
182
183
184 def main():
185     result = {
186         "evidence": "local_field_geometry_and_behavior_verification_not_official",
187         "negative_geometry": negative_checks(),
188         "routes": route_checks(),
189         "clearing": clearing_checks(),
190     }
191     Path("results/field_verification.json").write_text(
192         json.dumps(result, indent=2) + "\n"
193     )
194     print(json.dumps(result, indent=2))
195
196
197 if __name__ == "__main__":
198     main()

```

Listing 43: 脱敏官方演练原始反馈分析与严格回放

```

1 """Validate and analyze supplied official practice logs; no simulator requests.
2
3 The source count/type files are post-exit evaluation labels. The policy replay
4 receives only the original responses and must match every requested action;
5 unobserved actions are rejected, never simulated using guessed source truth.
6 """
7

```

```

8 from __future__ import annotations
9
10 import argparse
11 from collections import Counter
12 import csv
13 import hashlib
14 import json
15 import math
16 from pathlib import Path
17 import statistics
18
19 from geometry import enclosing_circle
20 from planner import Planner
21
22 ROOT = Path(__file__).resolve().parent
23 DEFAULT_HANDOFF = ROOT.parent / "ai_optimization_handoff_20260912"
24
25
26 def load_actions(path):
27     events = [
28         json.loads(line) for line in path.read_text(encoding="utf-8").splitlines()
29     ]
30     requests = {}
31     replies = {}
32     actions = []
33     accepted_ids = set()
34     in_flight = None
35     repeated = transport_errors = rejected = 0
36     for event in events:
37         kind = event["event"]
38         rid = event.get("request_id")
39         assert kind in ("request", "response", "accepted", "transport_error"), (
40             "Unknown event kind"
41         )
42         assert event["path"] in ("/enter", "/measure", "/clear", "/exit"), (
43             "Unknown action path"
44         )
45         if kind == "request":
46             assert event["body"]["robot_id"] == "TEAM_REDACTED", "Unredacted identifier"
47             assert event["body"]["request_id"] == rid, "Request identity mismatch"
48             signature = (event["path"], event["body"])
49             if rid in requests:
50                 assert requests[rid] == signature, "Idempotency content mismatch"
51                 repeated += 1
52             requests[rid] = signature
53             assert in_flight is None or in_flight == rid, "Concurrent logical actions"
54             in_flight = rid
55         elif kind == "response":
56             assert in_flight == rid
57             assert event["path"] == requests[rid][0], "Response path mismatch"
58             body = json.loads(event["body_utf8"])
59             if event["http_status"] != 200 or body["accepted"] is not True:
60                 rejected += 1
61             else:
62                 if rid in replies:
63                     assert replies[rid] == body, (
64                         "Same action returned inconsistent accepted responses"
65                     )
66                 replies[rid] = body
67                 in_flight = None
68         elif kind == "transport_error":
69             assert in_flight == rid and event["path"] == requests[rid][0], (
70                 "Unmatched transport error"
71             )
72             transport_errors += 1
73         elif kind == "accepted":
74             assert in_flight is None, "Accepted record precedes complete response"

```

```

75         assert rid in replies
76         assert rid not in accepted_ids, "Duplicate accepted-action record"
77         accepted_ids.add(rid)
78         route, body = requests[rid]
79         assert route == event["path"]
80         actions.append(
81             {
82                 "path": route,
83                 "body": body,
84                 "response": replies[rid],
85                 "request_id": rid,
86                 "client_accepted": event,
87             }
88         )
89     assert (
90         in_flight is None
91         and actions[0]["path"] == "/enter"
92         and actions[-1]["path"] == "/exit"
93     )
94     return actions, {
95         "jsonl_records": len(events),
96         "retries": repeated,
97         "transport_errors": transport_errors,
98         "rejected_responses": rejected,
99     }
100
101
102 class TraceDivergence(RuntimeError):
103     pass
104
105
106 class StrictReplay:
107     def __init__(self, actions):
108         self.actions = actions
109         self.index = 0
110         self.maximum_coordinate_difference_m = 0.0
111
112     def act(self, path, position=None, channel=None):
113         if self.index == len(self.actions):
114             raise TraceDivergence("Policy requested an action after recorded exit")
115         item = self.actions[self.index]
116         body = item["body"]
117         error = 0.0
118         if position is not None and "position" in body:
119             error = math.dist(position, (body["position"]["x"], body["position"]["y"]))
120         if (
121             path != item["path"]
122             or channel != body.get("channel")
123             or (position is None) != ("position" not in body)
124             or error > 1e-5
125         ):
126             raise TraceDivergence(
127                 f"Unobserved action at index {self.index}: {path}/{channel}; coordinate difference {error:.6g}m"
128             )
129         self.maximum_coordinate_difference_m = max(
130             self.maximum_coordinate_difference_m, error
131         )
132         self.index += 1
133         return dict(item["response"])
134
135
136 class PhaseReplayPlanner(Planner):
137     def __init__(self, env, problem):
138         super().__init__(env, problem, probe_scale=0.22)
139         self.phase = "entry_exit"
140         self.phase_records = []

```

```

141
142 def action(self, path, point=None, channel=None):
143     track = self.tracks.get(channel)
144     before = enclosing_circle(track.polygon)[1] if track else None
145     old_pos = self.position
146     response = super().action(path, point, channel)
147     self.phase_records.append(
148         {
149             "phase": self.phase,
150             "known_before": track is not None,
151             "radius_before_m": before,
152             "movement_m": 0.0 if point is None else math.dist(old_pos, point),
153         }
154     )
155     return response
156
157 def _within(self, name, method, *args):
158     previous = self.phase
159     self.phase = name
160     try:
161         return method(*args)
162     finally:
163         self.phase = previous
164
165 def scan_anchor(self, index):
166     return self._within("anchor", super().scan_anchor, index)
167
168 def localize(self, channel):
169     return self._within("localize", super().localize, channel)
170
171 def share_current_stop(self):
172     return self._within("shared_stop", super().share_current_stop)
173
174 def optical_finish(self, channel):
175     return self._within("optical_fallback", super().optical_finish, channel)
176
177
178 def analyze_run(root, row):
179     actions, wire = load_actions(root / row["private_requests"])
180     observed = json.loads((root / row["observed_result"]).read_text(encoding="utf-8"))
181     labels = json.loads((root / row["simulator_result"]).read_text(encoding="utf-8"))
182     problem = int(row["problem"])
183     assert problem == observed["problem"] == labels["problem_no"]
184     assert labels["case_code"] == row["case_code"]
185     assert str(labels["practice_run_no"]) == row["practice_run_no"]
186     assert labels["jammer_count"] == int(row["source_count"])
187     assert (
188         labels["directional_jammer_count"] + labels["omnidirectional_jammer_count"]
189         == labels["jammer_count"]
190     )
191     assert labels["directional_jammer_count"] == int(row["directional_count"])
192     assert labels["omnidirectional_jammer_count"] == int(row["omni_count"])
193     assert observed["certificate_complete"] is True
194     assert row["certificate_complete"].lower() == "true"
195     assert observed["strategy"] == "refined"
196     assert observed["coverage_policy"] == ("ring" if problem == 3 else "compact25")
197     if "probe_scale" in observed:
198         assert observed["probe_scale"] == 0.22
199     replay = StrictReplay(actions)
200     policy = PhaseReplayPlanner(replay, problem)
201     try:
202         result = policy.run()
203         assert replay.index == len(actions)
204         replay_status = {
205             "matched": True,
206             "matched_actions": replay.index,
207             "maximum_coordinate_difference_m": replay.maximum_coordinate_difference_m,

```

```

208     }
209     assert result["certificate_complete"] is True
210     phases = policy.phase_records
211 except TraceDivergence as exc:
212     replay_status = {
213         "matched": False,
214         "matched_actions": replay.index,
215         "reason": str(exc),
216     }
217     phases = []
218 # Use original coordinates, not replayed float approximations, for timing.
219 position = (0.0, 0.0)
220 radio = 1
221 clock_us = 0
222 movement_us = 0
223 distance = 0.0
224 switches = 0
225 counts = Counter()
226 outcomes = Counter()
227 cleared = set()
228 known = set()
229 first_positive = {}
230 negative_after_positive = 0
231 max_residual = 0.0
232 by_phase = {}
233 for i, item in enumerate(actions):
234     path, request, response = item["path"], item["body"], item["response"]
235     counts[path] += 1
236     move = 0.0
237     operation = switch = 0
238     ch = request.get("channel")
239     if path in ("/measure", "/clear"):
240         p = (request["position"]["x"], request["position"]["y"])
241         move = math.dist(position, p)
242         distance += move
243         position = p
244         movement_us += round(move / 5 * 1_000_000)
245         clock_us += round(move / 5 * 1_000_000)
246         if path == "/measure":
247             switch = int(ch != radio)
248             radio = ch
249             switches += switch
250             operation = 5
251             outcome = response["measure_result"]
252             assert outcome in ("direction", "near", "no_signal")
253             if outcome in ("direction", "near"):
254                 known.add(ch)
255                 first_positive.setdefault(ch, i)
256             elif ch in known and ch not in cleared:
257                 negative_after_positive += 1
258         else:
259             outcome = response["clear_result"]
260             assert outcome in ("success", "no_target_in_range")
261             operation = 5 if outcome == "success" else 3
262             if outcome == "success":
263                 assert ch not in cleared
264                 cleared.add(ch)
265             outcomes[outcome] += 1
266             clock_us += (operation + switch) * 1_000_000
267     assert math.isclose(move, item["client_accepted"]["distance_m"], abs_tol=1e-7)
268     assert switch == item["client_accepted"]["switch_time_s"]
269     residual = abs(clock_us / 1_000_000 - float(response["virtual_time_s"]))
270     max_residual = max(max_residual, residual)
271     assert residual < 3e-6, (problem, row["round"], i, residual)
272     if phases:
273         name = phases[i]["phase"]
274         cost = by_phase.setdefault(

```

```

275         name,
276         {
277             "actions": 0,
278             "distance_m": 0.0,
279             "measures": 0,
280             "known_measures": 0,
281             "time_s": 0.0,
282         },
283     )
284     cost["actions"] += 1
285     cost["distance_m"] += move
286     cost["measures"] += path == "/measure"
287     cost["known_measures"] += path == "/measure" and phases[i]["known_before"]
288     cost["time_s"] += (
289         round(move / 5 * 1_000_000) / 1_000_000 + operation + switch
290     )
291     assert (
292         len(cleared)
293         == observed["n_cleared"]
294         == labels["jammer_count"]
295         == int(row["cleared"])
296     )
297     assert set(observed["cleared_channels"]) == cleared
298     T = float(actions[-1]["response"]["virtual_time_s"])
299     K = len(cleared)
300     assert abs(T - float(row["virtual_time_s"])) < 3e-6
301     assert math.isclose(T, float(observed["virtual_time_s"]), rel_tol=0.0, abs_tol=3e-6)
302     assert math.isclose(T / K, observed["average_time_s"], abs_tol=1e-6)
303     assert math.isclose(T / K, float(row["average_time_s"]), abs_tol=1e-6)
304     return {
305         "problem": problem,
306         "round": int(row["round"]),
307         "case_code": row["case_code"],
308         "source_count": labels["jammer_count"],
309         "omni_count": labels["omnidirectional_jammer_count"],
310         "directional_count": labels["directional_jammer_count"],
311         "n_cleared": K,
312         "virtual_time_s": T,
313         "average_time_s": T / K,
314         "certificate_complete": observed["certificate_complete"],
315         "controller_strategy": observed["strategy"],
316         "replay_probe_scale": 0.22,
317         "coverage_policy": observed["coverage_policy"],
318         "termination": observed["termination"],
319         "visited_anchors": observed["visited_anchors"],
320         "total_anchors": observed["total_anchors"],
321         "measures": counts["/measure"],
322         "switches": switches,
323         "distance_m": distance,
324         "clear_attempts": counts["/clear"],
325         "clear_failures": outcomes["no_target_in_range"],
326         "optical_fallbacks": observed["optical_fallbacks"],
327         "move_time_s": movement_us / 1_000_000,
328         "measure_time_s": 5 * counts["/measure"],
329         "switch_time_s": switches,
330         "failed_clear_time_s": 3 * outcomes["no_target_in_range"],
331         "successful_clear_time_s": 5 * K,
332         "accounted_virtual_time_s": clock_us / 1_000_000,
333         "maximum_step_residual_s": max_residual,
334         "outcomes": dict(outcomes),
335         "no_signal_after_positive": negative_after_positive,
336         "first_positive_action_index": first_positive,
337         "phase_costs": by_phase,
338         "http_enter_to_exit_s": (
339             actions[-1]["response"]["real_timestamp_ms"]
340             - actions[0]["response"]["real_timestamp_ms"]
341         )

```

```

342         / 1000,
343         "controller_wall_s": observed["local_wall_duration_s"],
344         "manifest_timestamp_delta_s": float(row["timestamp_delta_s"]),
345         "strict_baseline_replay": replay_status,
346         **wire,
347     }
348
349
350 def analyze(root):
351     with (root / "manifest.csv").open(encoding="utf-8", newline="") as stream:
352         rows = list(csv.DictReader(stream))
353         assert len(rows) == 20 and {(int(r["problem"]), int(r["round"])) for r in rows} == {
354             (p, n) for p in (3, 4) for n in range(1, 11)
355         }
356         assert len({r["case_code"] for r in rows}) == 20
357         inputs = {"manifest.csv"}
358         for row in rows:
359             inputs.update(
360                 row[key]
361                 for key in ("private_requests", "observed_result", "simulator_result")
362             )
363         runs = [analyze_run(root, row) for row in rows]
364         summary = {}
365         for p in (3, 4):
366             group = [r for r in runs if r["problem"] == p]
367             T = sum(r["virtual_time_s"] for r in group)
368             K = sum(r["n_cleared"] for r in group)
369             summary[str(p)] = {
370                 "runs": len(group),
371                 "source_total": sum(r["source_count"] for r in group),
372                 "cleared_total": K,
373                 "all_cleared": sum(r["n_cleared"] == r["source_count"] for r in group),
374                 "mean_virtual_time_s": T / len(group),
375                 "weighted_s_per_source": T / K,
376                 "mean_per_source_s": statistics.mean(r["average_time_s"] for r in group),
377                 "median_per_source_s": statistics.median(
378                     r["average_time_s"] for r in group
379                 ),
380                 "cost_fractions": {
381                     key: sum(r[key] for r in group) / T
382                     for key in (
383                         "move_time_s",
384                         "measure_time_s",
385                         "switch_time_s",
386                         "failed_clear_time_s",
387                         "successful_clear_time_s",
388                     )
389                 },
390             }
391         for key in (
392             "distance_m",
393             "measures",
394             "switches",
395             "clear_failures",
396             "optical_fallbacks",
397             "http_enter_to_exit_s",
398             "controller_wall_s",
399         ):
400             summary[str(p)]["mean_" + key] = statistics.mean(r[key] for r in group)
401     return {
402         "evidence": "official_simulator_practice_observations_from_user_supplied_logs",
403         "official_practice": True,
404         "formal_test": False,
405         "offline_analysis_only": True,
406         "hidden_truth_used_online": False,
407         "run_count": 20,
408         "input_sha256": {

```

```

409         name: hashlib.sha256((root / name).read_bytes()).hexdigest()
410         for name in sorted(inputs)
411     },
412     "summary": summary,
413     "runs": runs,
414     "limits": [
415         "Practice counts/types are post-exit labels, not policy inputs.",
416         "Strict replay supplies only observed responses and fails at the first unobserved request; it does
not predict improved-policy results.",
417         "Phase attribution is emitted only when the complete baseline action sequence matches, up to stated
coordinate roundoff.",
418         "manifest_timestamp_delta_s has no established runtime meaning. HTTP timestamp difference is an
auxiliary runtime check, not a GUI formal score.",
419         "No encrypted formal-test logs were supplied.",
420     ],
421 }
422
423
424 def main():
425     parser = argparse.ArgumentParser()
426     parser.add_argument("--handoff", type=Path, default=DEFAULT_HANDOFF)
427     parser.add_argument(
428         "--output", type=Path, default=ROOT / "results/official_practice_analysis.json"
429     )
430     args = parser.parse_args()
431     result = analyze(args.handoff)
432     args.output.write_text(
433         json.dumps(result, ensure_ascii=False, indent=2) + "\n", encoding="utf-8"
434     )
435     print(
436         json.dumps(
437             {
438                 "summary": result["summary"],
439                 "strict_replay": [r["strict_baseline_replay"] for r in result["runs"]],
440             },
441             indent=2,
442         )
443     )
444
445
446 if __name__ == "__main__":
447     main()

```

Listing 44: 新策略数据驱动图表生成

```

1  """Checked field-policy assets; official observations and synthetic gains stay separate."""
2
3  from __future__ import annotations
4  from collections import defaultdict
5  import hashlib
6  import json
7  import statistics
8
9  import matplotlib
10
11  matplotlib.use("Agg")
12  import matplotlib.pyplot as plt
13  import numpy as np
14
15  from field_study import pair_stats, summarize
16  from make_assets import (
17      ROOT,
18      GENERATED,
19      atomic_bytes,
20      table,
21      number,
22      save_figure,

```

```

23     write_json,
24 )
25 from make_research_assets import checked_rows
26
27 LABELS = {
28     "control": "原refined",
29     "route_only": "仅路线改进",
30     "route_info": "路线与信息",
31     "field": "新field",
32 }
33
34
35 def main():
36     data = json.loads((ROOT / "results/field_confirmation.json").read_text())
37     development = json.loads((ROOT / "results/field_development.json").read_text())
38     official = json.loads(
39         (ROOT / "results/official_practice_analysis.json").read_text()
40     )
41     assert data["total_runs"] == 9400 and development["total_runs"] == 2250
42     checked_rows(data)
43     checked_rows(development)
44     groups = defaultdict(list)
45     for row in data["runs"]:
46         groups[
47             row["problem"],
48             row["scenario"],
49             row["error_mode"],
50             row["configuration"],
51             row["seed"] // 10000,
52         ].append(row)
53     main_groups = {}
54     comparison_rows = []
55     cost_rows = []
56     macros = []
57     ablation = []
58     for p in (3, 4):
59         names = (
60             ("control", "route_only", "route_info", "field")
61             if p == 3
62             else ("control", "field")
63         )
64         for name in names:
65             group = groups[p, "random", "smooth", name, 710]
66             assert [r["seed"] for r in group] == list(range(7100000, 7101000))
67             summary = summarize(group)
68             assert summary == data["summary"][f"Q{p}_{name}"]
69             main_groups[p, name] = group
70             comparison_rows.append(
71                 [
72                     f"Q{p}",
73                     LABELS[name],
74                     number(summary["mean"]),
75                     number(summary["p90"]),
76                     number(summary["worst"]),
77                     f"{summary['all_clear']}/1000",
78                 ]
79             )
80             if name in ("control", "field"):
81                 # Recover the charged movement component from the independently
82                 # verified total and integer action costs, retaining microsecond rounding.
83                 costs = [
84                     statistics.mean(
85                         (
86                             r["virtual_time_s"]
87                             - 5 * r["measures"]
88                             - r["switches"]
89                             - 3 * r["failed_clears"]

```

```

90         - 5 * r["n_cleared"]
91     )
92     / r["n_sources"]
93     for r in group
94 ),
95 statistics.mean(5 * r["measures"] / r["n_sources"] for r in group),
96 statistics.mean(r["switches"] / r["n_sources"] for r in group),
97 statistics.mean(
98     3 * r["failed_clears"] / r["n_sources"] for r in group
99 ),
100     5.0,
101 ]
102 assert abs(sum(costs) - summary["mean"]) < 1e-9
103 cost_rows.append(
104     [
105         f"Q{p}",
106         LABELS[name],
107         *[number(v) for v in costs],
108         number(summary["mean"]),
109     ]
110 )
111 pair = pair_stats(main_groups[p, "control"], main_groups[p, "field"])
112 assert pair == data["comparison"][f"Q{p}"]
113 word = "Three" if p == 3 else "Four"
114 s = data["summary"][f"Q{p}_field"]
115 macros.extend(
116     [
117         (f"FieldQ{word}Time", number(s["mean"])),
118         (
119             f"FieldQ{word}Control",
120             number(data["summary"][f"Q{p}_control"]["mean"]),
121         ),
122         (f"FieldQ{word}Gain", number(pair["saving_pct"])),
123         (f"FieldQ{word}Saved", number(pair["mean_saved_s"])),
124         (f"FieldQ{word}Lower", number(pair["approx_95pct_ci"][0])),
125         (f"FieldQ{word}Upper", number(pair["approx_95pct_ci"][1])),
126         (f"FieldQ{word}Faster", str(pair["faster_cases"])),
127         (f"FieldQ{word}Wall", f"{s['max_real_s']:.3f}"),
128     ]
129 )
130 for a, b in zip(names, names[1:]):
131     values = pair_stats(main_groups[p, a], main_groups[p, b])
132     ablation.append(
133         [
134             f"Q{p}",
135             LABELS[a] + "至" + LABELS[b],
136             number(values["mean_saved_s"]),
137             "[",
138             + number(values["approx_95pct_ci"][0])
139             + ", "
140             + number(values["approx_95pct_ci"][1])
141             + "]",
142         ]
143     )
144 macros.extend([(f"FieldRuns", "9400"), (f"FieldDevelopmentRuns", "2250")])
145 atomic_bytes(
146     GENERATED / "field_numbers.tex",
147     (
148         "\n".join("\newcommand{\k + }{\k + v + }" for k, v in macros) + "\n"
149     ).encode(),
150 )
151 table(
152     "field_comparison.tex",
153     ["问题", "策略", "均值", "$p_{90}$", "最坏", "全清"],
154     comparison_rows,
155 )
156 table(

```

```

157     "field_costs.tex",
158     ["问题", "策略", "移动", "检测", "换频", "失败清除", "成功清除", "合计"],
159     cost_rows,
160 )
161 table(
162     "field_ablation.tex",
163     ["问题", "相邻配置", "节省均值", r"近似95%区间"],
164     ablation,
165 )
166 stress_rows = []
167 for key, item in data["stress"].items():
168     p = int(key[1])
169     scenario = next(
170         s
171         for s in ("minimum_radius", "outward_boundary", "clustered", "random")
172         if key.startswith(f"Q{p}_{s}_")
173     )
174     mode = key[len(f"Q{p}_{scenario}_") :]
175     seed_prefix = 721 if scenario == "random" else 720
176     a = groups[p, scenario, mode, "control", seed_prefix]
177     b = groups[p, scenario, mode, "field", seed_prefix]
178     assert pair_stats(a, b) == item["paired"]
179     assert summarize(a) == item["control"] and summarize(b) == item["field"]
180     labels = {
181         "minimum_radius": "最小半径",
182         "outward_boundary": "边界外向",
183         "clustered": "聚集",
184         "random": "随机",
185     }
186     modes = {"smooth": "平滑", "extreme": "端点", "iid_location": "位置哈希"}
187     stress_rows.append(
188         [
189             f"Q{p}",
190             labels[scenario],
191             modes[mode],
192             str(len(a)),
193             number(item["paired"]["mean_saved_s"]),
194             "[",
195             + number(item["paired"]["approx_95pct_ci"][0])
196             + ", "
197             + number(item["paired"]["approx_95pct_ci"][1])
198             + "]",
199             f"{item['paired']['faster_cases']}/{len(a)}",
200         ]
201     )
202 table(
203     "field_stress.tex",
204     ["问题", "场景", "误差", "配对数", "节省", r"近似95%区间", "更快"],
205     stress_rows,
206 )
207 # Official evidence has no new field outcomes; plot only actual cost shares.
208 official_rows = []
209 for p in (3, 4):
210     s = official["summary"][str(p)]
211     official_rows.append(
212         [
213             f"Q{p}",
214             "10",
215             str(s["source_total"]),
216             number(s["mean_per_source_s"]),
217             number(s["weighted_s_per_source"]),
218             number(100 * s["cost_fractions"]["move_time_s"]),
219             number(s["mean_measures"]),
220         ]
221     )
222 table(
223     "official_cost_summary.tex",

```

```

224     ["问题", "局数", "全清源数", "局等权T/K", "汇总T/K", "移动占比/\%", "检测/局"],
225     official_rows,
226 )
227 plt.rcParams.update({"font.size": 10, "pdf.fonttype": 42})
228 fig, axes = plt.subplots(1, 2, figsize=(16 / 2.54, 3.3), layout="constrained")
229 for p, ax in zip((3, 4), axes):
230     for name, color in [("control", "#0072B2"), ("field", "#D55E00")]:
231         values = sorted(r["average_time_s"] for r in main_groups[p, name])
232         ax.plot(
233             values,
234             np.arange(1, len(values) + 1) / len(values),
235             label="refined" if name == "control" else "field",
236             color=color,
237         )
238     ax.set(
239         title=f"Q{p}: 1,000 fresh paired worlds",
240         xlabel="Full virtual time / source (s)",
241         ylabel="Empirical cumulative probability",
242         ylim=(0, 1),
243     )
244     ax.legend(loc="lower right")
245     ax.grid(alpha=0.2)
246 save_figure(fig, "field_performance.pdf")
247 inputs = [
248     "results/field_confirmation.json",
249     "results/field_development.json",
250     "results/field_verification.json",
251     "results/official_practice_analysis.json",
252     "field_policy.py",
253     "negative_geometry.py",
254     "route_portfolio.py",
255     "field_study.py",
256     "field_confirmation.py",
257     "official_analysis.py",
258     "make_field_assets.py",
259     "planner.py",
260     "geometry.py",
261 ]
262 write_json(
263     "field_metadata.json",
264     {
265         "evidence": data["evidence"],
266         "official_calls_by_generator": 0,
267         "official_practice_runs_analyzed": 20,
268         "field_main_worlds_per_problem": 1000,
269         "field_confirmation_runs": 9400,
270         "field_development_runs": 2250,
271         "main_comparison": data["comparison"],
272         "input_sha256": {
273             name: hashlib.sha256((ROOT / name).read_bytes()).hexdigest()
274             for name in inputs
275         },
276     },
277 )
278 print(
279     json.dumps(
280         {
281             "confirmation_runs": 9400,
282             "development_runs": 2250,
283             "main": data["comparison"],
284             "official_runs": 20,
285         },
286         indent=2,
287     )
288 )
289
290

```

```

291 if __name__ == "__main__":
292     main()

```

Listing 45: 局部最优、机制消融、分布与状态专项审查

```

1 """Deterministic exhaustive audit of open-route dispatch proxies.
2
3 Synthetic evidence only: this script never starts the official simulator and does not
4 read or alter historical result files. Run from b_solution: python audit/route_exact_audit.py
5 """
6 from __future__ import annotations
7 import json, math, random, itertools, sys
8 from pathlib import Path
9 from statistics import mean
10 ROOT = Path(__file__).resolve().parents[1]
11 if str(ROOT) not in sys.path:
12     sys.path.insert(0, str(ROOT))
13 from route_portfolio import (_control_route, _cost, _improve,
14                             _cheapest_route, _nearest_route, choose_portfolio_task)
15 from joint_dispatch_candidate import choose_task
16
17 OUT = Path(__file__).resolve().parents[1] / "results" / "audit_route_exact.json"
18 SEED_RANGE = (8200150, 8200199) # outside reserved 8200000..8200149
19
20 def instance(origin, targets, anchors, weight):
21     tasks=[("target",k) for k in sorted(targets)]+[("anchor",k) for k in sorted(anchors)]
22     pts=[targets[k][0] for _,k in tasks[:len(targets)]] + [anchors[k] for _,k in tasks[len(targets):]]
23     # above task order is targets then anchors by construction
24     radii=[targets[k][1] for k in sorted(targets)]+[0.0 for _ in anchors]
25     o=[math.dist(origin,p) for p in pts]
26     e=[[math.dist(a,b) for b in pts] for a in pts]
27     pen=[weight*r for r in radii]
28     return tasks,o,e,pen
29
30 def exact(o,e,p):
31     best=None; route_count=0
32     for r in itertools.permutations(range(len(o))):
33         c=o[r[0]]+p[r[0]]+sum(e[a][b] for a,b in zip(r,r[1:]))
34         route_count+=1
35         if best is None or (c, r)<(best[0],best[1]): best=(c,r)
36     return list(best[1]),best[0],route_count
37
38 def ils(seed,o,e,p):
39     # deterministic iterated local search: exhaustive neighborhood perturbations,
40     # then the same strict best-improvement kernel used by portfolio.
41     best,_=improve(list(seed),o,e,p)
42     bestc=_cost(best,o,e,p)
43     for cut in range(1,len(seed)):
44         q=list(best); x=q.pop(cut); q.insert((cut*3+1)%len(q),x)
45         q,c=_improve(q,o,e,p)
46         if c<bestc: best,bestc=q,c
47     return best,bestc
48
49 def evaluate(name, origin, targets, anchors, weight, source):
50     tasks,o,e,p=instance(origin,targets,anchors,weight); n=len(tasks)
51     opt,oc,rc=exact(o,e,p)
52     control=_control_route(o,e,p); cr=_cost(control,o,e,p)
53     starts=sorted(range(n),key=lambda i:(o[i]+p[i],i))[:2]
54     candidates=[("portfolio", _cheapest_route(o,e,p)), ("nn0",_nearest_route(starts[0],e))]
55     if len(starts)>1: candidates.append(("nn1",_nearest_route(starts[1],e)))
56     routes={"exact":(opt,oc),"control":(control,cr)}
57     for label,s in candidates:
58         r,c=_improve(s,o,e,p); routes[label]=(r,c)
59     routes["ils"]=ils(control,o,e,p)
60     # local-world T/N: paired deterministic worlds differ only in target miss radius;
61     # T is actual open travel, N is weighted unresolved exposure after the route.
62     rows=[]

```

```

63     for label,(r,c) in routes.items():
64         travel=o[r[0]]+sum(e[a][b] for a,b in zip(r,r[1:]))
65         nmiss=sum((p[i] > 0 and p[i] > weight*0.5) for i in r) # transparent local-world proxy
66         rows.append({"method":label,"route": [tasks[i] for i in r], "J":c,
67             "T":travel, "N":int(nmiss), "gap_abs":c-oc, "gap_rel":(c/oc-1 if oc else 0),
68             "first_hop":tasks[r[0]]})
69     rev_targets=dict(reversed(list(targets.items())))
70     rev_anchors=dict(reversed(list(anchors.items())))
71     invariant=(choose_portfolio_task(origin,anchors,targets,weight)==
72         choose_portfolio_task(origin,rev_anchors,rev_targets,weight))
73     return {"case":name,"evidence":source,"n":n,"weight":weight,"origin":origin,
74         "insertion_order_invariant":invariant,
75         "tasks": [{"kind":k,"key":i,"point":(targets[i][0] if k=="target" else anchors[i]),
76             "radius":(targets[i][1] if k=="target" else 0)} for k,i in tasks],
77         "exhaustive":True,"permutations":rc,"optimum_J":oc,"routes":rows}
78
79 def main():
80     cases=[]
81     crafted=[
82         ("mixed",[(0,0),(3,0),(0,4)],[(3,4)], [2,0,5],1),
83         ("duplicates",[(0,0),(0,0),(4,0)],[(0,0),(4,0)], [0,4,1],4),
84         ("ties",[(1,0),(-1,0)],[(0,1),(0,-1)], [1,1],0),
85         ("risk0",[(2,0),(8,0)],[(4,2)], [0,4],0),
86         ("risk1",[(2,0),(8,0)],[(4,2)], [0,4],1),
87         ("risk4",[(2,0),(8,0)],[(4,2)], [0,4],4),
88     ]
89     for name,pts,aps,rs,w in crafted:
90         cases.append(evaluate(name,(0,0),{i:(p,rs[i]) for i,p in enumerate(pts)},
91             {i:p for i,p in enumerate(aps)},w,"crafted synthetic"))
92     rng=random.Random(8200150)
93     for j in range(50):
94         nt=2+(j%3); na=1+((j//3)%3); pts=[(rng.randrange(-10,11),rng.randrange(-10,11)) for _ in range(nt)]
95         aps=[(rng.randrange(-10,11),rng.randrange(-10,11)) for _ in range(na)]
96         rs=[rng.choice([0,1,4]) for _ in range(nt)]; w=[0,1,4][j%3]
97         cases.append(evaluate(f"random_{j:02d}",(rng.randrange(-3,4),rng.randrange(-3,4)),
98             {i:(p,rs[i]) for i,p in enumerate(pts)},{i:p for i,p in enumerate(aps)},w,"bounded random synthetic"))
99     # rank/discordance summaries against exact J and local T/N (all methods/cases).
100     gaps=[r["gap_abs"] for c in cases for r in c["routes"] if r["method"]!="exact"]
101     lower_higher=[]
102     for c in cases:
103         rr=c["routes"]
104         for a,b in itertools.permutations(rr,2):
105             if a["J"]<b["J"] and (a["T"],a["N"])>(b["T"],b["N"]): lower_higher.append((c["case"],a["method"],b["method"]))
106     jt_discord=tn_discord=pairs=0
107     for c in cases:
108         for a,b in itertools.combinations(c["routes"],2):
109             pairs += 1
110             if (a["J"]-b["J"])*(a["T"]-b["T"]) < 0: jt_discord += 1
111             if (a["J"]-b["J"])*(a["N"]-b["N"]) < 0: tn_discord += 1
112     result={"evidence_type":"synthetic audit only; no official logs and no simulator",
113         "configuration":{"objective":"origin + consecutive open edges + weight*first target radius",
114             "no_return_edge":True,
115             "seed_range":list(SEED_RANGE),"random_cases":50,"crafted_cases":6},
116         "hard_gates":{"exhaustive_n_le_8":all(c["n"]<=8 and c["exhaustive"] for c in cases),
117             "insertion_order_invariant":all(c["insertion_order_invariant"] for c in cases),
118             "official_simulator_started":False,"reserved_seeds_consumed":False},
119         "aggregate":{"cases":len(cases),"nonexact_route_rows":sum(len(c["routes"])-1 for c in cases),
120             "max_abs_gap":max(gaps),"max_relative_gap":max(r["gap_rel"] for c in cases for r in c["routes"]),
121             "lower_J_higher_TN_count":len(lower_higher),"lower_J_higher_TN_examples":lower_higher[:20],
122             "first_hop_disagreements":sum(len({r["first_hop"] for r in c["routes"]})>1 for c in cases),
123             "J_vs_T_pair_discordance":jt_discord,"J_vs_N_pair_discordance":tn_discord,"rank_pairs":pairs},
124         "cases":cases}
125     OUT.parent.mkdir(parents=True,exist_ok=True); OUT.write_text(json.dumps(result,indent=2,sort_keys=True)+"\n")
126     print(json.dumps({"output":str(OUT),"cases":len(cases),"permutation_proof":sum(c["permutations"] for c in cases),
127         "hard_gates":result["hard_gates"]},indent=2))

```

```
126 if __name__=="__main__": main()
```

Listing 46: Q3 八组机制消融

```
1 """Deterministic paired Q3 mechanism ablation on the local synthetic simulator.
2
3 This is an audit only: it does not alter production policy or consume reserved
4 integration seeds. Run from b_solution (or pass --output explicitly).
5 """
6 from __future__ import annotations
7 import argparse, hashlib, json, math, random, statistics
8 from pathlib import Path
9 from environment import LocalSimulator
10 from field_policy import FieldPlanner
11
12 START, CASES = 8200200, 150
13 CONFIGS = {
14     "refined": {},
15     "refined+route_only": {"portfolio": True},
16     "refined+premeasure_only": {"premeasure": True},
17     "refined+negative_geometry_only": {"negative_updates": True},
18     "refined+approach_clear_only": {"approach_clear": True},
19     "route+premeasure": {"portfolio": True, "premeasure": True},
20     "route+negative": {"portfolio": True, "negative_updates": True},
21     "full_field": {"portfolio": True, "premeasure": True, "negative_updates": True, "approach_clear": True},
22 }
23
24 def metrics(env, result):
25     pos=(0.0,0.0); radio=1; move=measure_t=0.0
26     measures=switches=clears=failed=0; switch_t=success_clear_time=failed_clear_time=0.0
27     for event in env.log:
28         req,resp=event["request"],event["response"]
29         if req["path"] not in ("/measure","/clear"): continue
30         p=(req["position"]["x"],req["position"]["y"]); move += math.dist(pos,p); pos=p
31         if req["path"]=="/measure":
32             measures+=1; measure_t+=event.get("action_time_s",0.0)
33             if radio!=req["channel"]: switches+=1; switch_t+=event.get("switch_time_s",0.0)
34             radio=req["channel"]
35         else:
36             clears+=1
37             if resp.get("clear_result")=="success": success_clear_time+=event.get("action_time_s",0.0)
38             else: failed+=1; failed_clear_time+=event.get("action_time_s",0.0)
39     order=[(e["request"]["path"],e["request"].get("channel"),e["request"].get("position")) for e in env.log if
40             e["request"]["path"] in ("/measure","/clear"))]
41     order_hash=hashlib.sha256(json.dumps(order,sort_keys=True,separators=(",",":")).encode()).hexdigest()
42     s=env.summary()
43     return {"seed":s["seed"],"problem":s["problem"],"scenario":s["scenario"],"error_mode":s["error_mode"],"T_s":
44             s["virtual_time_s"],"N":s["n_sources"],"n_sources":s["n_sources"],"T_over_N_s":s["virtual_time_s"]/s["
45             n_sources"],"movement_distance_m":move,"movement_time_s":move/5,"measure_time_s":measure_t,"measure_count":
46             measures,"switch_time_s":switch_t,"switch_count":switches,"success_clear_time_s":success_clear_time,"
47             failed_clear_time_s":failed_clear_time,"failed_clear_count":failed,"clear_attempt_count":clears,"
48             route_replanning_count":sum(1 for e in env.log if e["request"]["path"]=="/clear" and e.get("distance_m",0)
49             >0),"probes":result.get("zero_travel_probes",0),"negative_cuts":result.get("negative_cuts",0),"certificate":
50             bool(result.get("certificate_complete")),"cleared_count":s["n_cleared"],"termination":result.get("
51             termination") or result.get("terminal_reason"),"action_order_hash":order_hash}
52
53 def run(seed, config):
54     # FieldPlanner defaults to the full field policy; every ablation must
55     # explicitly disable omitted mechanisms so the refined row is genuine.
56     settings = {"premeasure": False, "negative_updates": False,
57                 "portfolio": False, "approach_clear": False}
58     env=LocalSimulator(seed,3,"smooth","random")
59     planner=FieldPlanner(env,3,**(settings | config),probe_scale=0.22)
60     result=planner.run()
61     return metrics(env,result)
62
63 def bootstrap(diffs, seed=99173, reps=5000):
```

```

55     rng=random.Random(seed); n=len(diffs); vals=[sum(diffs[rng.randrange(n)] for _ in range(n))/n for _ in
        range(reps)]; vals.sort(); return [vals[int(.025*reps)],vals[int(.975*reps)-1]]
56
57 def summary(rows, baseline):
58     vals=[r["T_over_N_s"] for r in rows]; diffs=[a["T_over_N_s"]-b["T_over_N_s"] for a,b in zip(baseline,rows)
        ]; sv=sorted(vals); n=len(vals); bh={r["seed"]:r["action_order_hash"] for r in baseline}
59     return {"cases":n,"mean_T_over_N_s":statistics.mean(vals),"median_T_over_N_s":statistics.median(vals),"
        p90_T_over_N_s":sv[math.ceil(.9*n)-1],"worst_T_over_N_s":max(vals),"mean_saved_vs_refined_s":statistics.
        mean(diffs),"win_rate_vs_refined":sum(x>0 for x in diffs)/n,"paired_bootstrap_95pct_CI_s":bootstrap(diffs)
        ,"ordering_changes_vs_refined":sum(r["action_order_hash"]!=bh[r["seed"]] for r in rows),"hard_gates":{"
        all_certificate":all(r["certificate"] for r in rows),"all_sources_cleared":all(r["cleared_count"]==r["
        n_sources"] for r in rows),"p90_not_materially_worse":sv[math.ceil(.9*n)-1]<=sorted(x["T_over_N_s"] for x
        in baseline)[math.ceil(.9*n)-1]*1.05}}
60 def main():
61     ap=argparse.ArgumentParser(); ap.add_argument("--start",type=int,default=START); ap.add_argument("--cases",
        type=int,default=CASES); ap.add_argument("--output",type=Path,default=Path("results/audit_q3_ablation.json
        ")); a=ap.parse_args()
62     if a.start < 8200150: raise SystemExit("seed range overlaps reserved 8200000..8200149")
63     if a.output.exists(): raise SystemExit(f"refusing to overwrite {a.output}")
64     seeds=list(range(a.start,a.start+a.cases)); allrows={name:[{*run(seed,cfg),"configuration":name} for seed
        in seeds] for name,cfg in CONFIGS.items()}
65     base=allrows["refined"]; summaries={k:summary(v,base) for k,v in allrows.items()}
66     out={"evidence_type":"local_synthetic_standard_random_smooth_not_official","exploratory_seed_range":[a.
        start,seeds[-1]],"configuration_contract":CONFIGS,"world_metadata":{"problem":3,"scenario":"random","
        error_mode":"smooth","paired_identical":True},"hard_gate_policy":"certificate and all sources cleared
        required; p90 <= refined p90*1.05; no verification claim from proxy alone","summaries":summaries,"runs":[r
        for rows in allrows.values() for r in rows]}
67     a.output.parent.mkdir(parents=True,exist_ok=True); a.output.write_text(json.dumps(out,indent=2)+"\n");
        print(json.dumps({"output":str(a.output),"seed_range":out["exploratory_seed_range"],"configs":len(CONFIGS)
        ,"rows":len(out["runs"])}),sort_keys=True))
68 if __name__=="__main__": main()

```

Listing 47: 分布偏差诊断

```

1  """Distribution/overfitting audit; diagnostic only, never starts simulator.
2  Evidence is official sanitized observations plus immutable synthetic result rows.
3  Run from repository root: python b_solution/audit/distribution_audit.py
4  """
5  from __future__ import annotations
6  import csv, json, math, statistics
7  from collections import Counter
8  from pathlib import Path
9
10 ROOT=Path(__file__).resolve().parents[1]
11 HANDOFF=ROOT.parent/'ai_optimization_handoff_20260912'
12 OUT=ROOT/'results'/'audit_distribution.json'
13 SYN_FILES=[ROOT/'results'/'field_development.json', ROOT/'results'/'field_confirmation.json']
14 SEED_RANGES={'development_reserved_8200000_8200149':range(8200000,8200150), 'freeze_reserved_8300000_8300999':
    range(8300000,8301000)}
15
16 def qstats(xs):
17     xs=[float(x) for x in xs if x is not None]
18     if not xs:return {'n':0}
19     ys=sorted(xs); q=lambda p: ys[min(len(ys)-1,max(0,math.ceil(p*len(ys))-1))]
20     return {'n':len(xs),'min':ys[0],'p10':q(.1),'median':statistics.median(ys),'p90':q(.9),'max':ys[-1],'mean':
        statistics.mean(xs)}
21
22 def official():
23     rows=list(csv.DictReader((HANDOFF/'manifest.csv').open()))
24     out=[]
25     for r in rows:
26         log=HANDOFF/r['private_requests']; events=[json.loads(x) for x in log.read_text().splitlines()]
27         accepted={e['request_id']:e for e in events if e['event']=='accepted'}
28         replies={e['request_id']:json.loads(e['body_utf8']) for e in events if e['event']=='response' and e['
            http_status']==200}
29         actions=[]
30         for e in events:

```

```

31         if e['event']=='accepted' and e['request_id'] in replies:
32             actions.append((e['path'],e,replies[e['request_id']]))
33             measures=[(e,b) for p,e,b in actions if p=='/measure']; clears=[(e,b) for p,e,b in actions if p=='/
clear']
34             outcomes=Counter(b.get('measure_result','clear_'+str(b.get('clear_result')))) for e,b in measures+clears
35             moves=[float(e.get('distance_m',0)) for p,e,b in actions if p in ('/measure','/clear')]
36             switches=sum(float(e.get('switch_time_s',0))>0 for p,e,b in actions)
37             phases=Counter()
38             # Observable phase boundaries: pre-localization anchors are inferred only from policy labels, never
hidden truth.
39             obs=json.loads((HANDOFF/r['observed_result']).read_text())
40             phases['entry_exit']=2; phases['measure_or_clear']=len(actions)-2
41             out.append({'problem':int(r['problem']),'round':int(r['round']),'case_code':r['case_code'],'N_label':
int(r['source_count']),'directional_label':int(r['directional_count']),'omni_label':int(r['omni_count']),'
T_s':float(r['virtual_time_s']),'T_per_N_s':float(r['average_time_s']),'action_counts':Counter(p for p,e,b
in actions),'measure_outcomes':outcomes,'measure_count':len(measures),'clear_count':len(clears),'switches
':switches,'movement_m':sum(moves),'movement_share':None,'phase_counts':dict(phases),'
phase_lengths_unavailable':True,'strategy':obs.get('strategy'),'coverage_policy':obs.get('coverage_policy'
),'official_not_paired_counterfactual':True)})
42             out[-1]['movement_share']=None # no total-time decomposition is asserted from log metadata
43         return out
44
45 def synthetic():
46     out=[]
47     for path in SYN_FILES:
48         d=json.loads(path.read_text())
49         for r in d.get('runs',[]):
50             x=dict(r); x['source_file']=path.name; x['T_per_N_s']=x.get('average_time_s'); x['movement_share']=
(x.get('distance_m',0)/5)/x['virtual_time_s'] if x.get('virtual_time_s') else None
51             out.append(x)
52     return out
53
54 def grouped(rows,key):
55     return {str(k):qstats([r[key] for r in rows if r.get(key) is not None]) for k in sorted(set(r.get(key) for
r in rows))}
56
57 def main():
58     off=official(); syn=synthetic(); allseeds=Counter(int(r['seed']) for r in syn if 'seed' in r)
59     overlap=[]
60     for name,rr in SEED_RANGES.items():
61         used=sorted(s for s in allseeds if s in rr); overlap.append({'range':name,'count':len(used),'seeds':
used[:20], 'truncated':len(used)>20})
62     bycfg=Counter((r.get('problem'),r.get('configuration','unknown')) for r in syn)
63     result={'evidence_type':'diagnostic distribution audit; official observations are unpaired and synthetic
rows are local only','commands':['python b_solution/audit/distribution_audit.py'],'hard_gate_status':{'
official_counterfactual_pairing':'FAIL_NOT_APPLICABLE','strategy_verified':'NOT_CLAIMED','
reserved_seed_contamination':'PASS' if not any(x['count'] for x in overlap) else 'FAIL'},'provenance':{'
official_manifest':'ai_optimization_handoff_20260912/manifest.csv','official_logs':'sanitized
private_requests + observed_result + post-exit labels; no hidden coordinates/truth','synthetic_files':[str
(p.relative_to(ROOT)) for p in SYN_FILES],'synthetic_configs':dict((f'Q{p}_{c}',n) for (p,c),n in bycfg.
items())},'official':{'runs':off,'N':qstats([r['N_label'] for r in off]),'T_per_N':qstats([r['T_per_N_s']
for r in off]),'by_problem':{f'Q{p}':'runs':[r for r in off if r['problem']==p],'N':qstats([r['N_label']
for r in off if r['problem']==p]),'T_per_N':qstats([r['T_per_N_s'] for r in off if r['problem']==p])} for
p in (3,4)},'unavailable':['true source coordinates/radii/orientations','official action phase durations
separated by semantic phase','official movement share (wire accepted distance is available but time
decomposition is not asserted)','official failed-clear truth beyond responses'],'synthetic':{'runs':syn,
'by_problem':{f'Q{p}':{'runs':len([r for r in syn if r.get('problem')==p]),'N':qstats([r.get('n_sources')
for r in syn if r.get('problem')==p]),'measures':qstats([r.get('measures') for r in syn if r.get('problem'
)==p]),'switches':qstats([r.get('switches') for r in syn if r.get('problem')==p]),'failed_clears':qstats([
r.get('failed_clears') for r in syn if r.get('problem')==p]),'movement_share':qstats([r.get('
movement_share') for r in syn if r.get('problem')==p]),'T_per_N':qstats([r.get('T_per_N_s') for r in syn
if r.get('problem')==p])} for p in (3,4)}},'seed_overlap_table':overlap,'diagnosis':{'likely':['Synthetic
N is uniform 10..16 while official labels range 10..16 but only 10 cases per question; unequal N weighting
can shift T/N.','Synthetic positions are iid uniform in radius-1800 disk and radii uniform 1000..1500;
official coordinates/radii are unavailable, so boundary/cluster and directional geometry gaps can reverse
Q3 direction.','Synthetic error fields are deterministic smooth/extreme/hash modes, not established

```

```

        official noise; repeated-coordinate semantics may differ.', 'Field parameters explicitly state selection
        from official-observation bottlenecks and development seeds; this is post-observation informed design, not
        an independent official holdout.'], 'unsupported': ['No evidence supports treating official logs as paired
        refined-vs-field counterfactuals.', 'No evidence identifies official source placement, radio radius,
        directional orientation, or error distribution.', 'No evidence supports extrapolating 20 official runs to
        population quantiles.'], 'protocol_controls': ['Development 8200000..8200149 and final freeze
        8300000..8300999 are reserved and uncontaminated by this audit.', 'Synthetic rows retain Q3/Q4 and
        configuration labels; no relabeling of refined as field.']]}}
64 OUT.write_text(json.dumps(result, indent=2, ensure_ascii=False)+'\n'); print(json.dumps(result['
    hard_gate_status'], indent=2))
65 if __name__ == '__main__': main()

```

Listing 48: 正确性与状态核验

```

1 from __future__ import annotations
2
3 """Targeted, synthetic-only correctness audit for field extensions.
4
5 This script intentionally does not contact the official service or invoke the
6 official simulator. Evidence is limited to deterministic pure geometry and a
7 small recording environment implementing the public LocalSimulator protocol.
8 """
9 import json
10 from math import dist, isfinite
11 from pathlib import Path
12 import sys
13
14 ROOT = Path(__file__).resolve().parents[1]
15 sys.path.insert(0, str(ROOT))
16 from field_policy import FieldPlanner
17 from negative_geometry import exclude_omni_disk
18 from route_portfolio import choose_portfolio_task
19 from geometry import initial_polygon
20
21 OUT = ROOT / "results" / "audit_correctness.json"
22 def rec(name, evidence, cases, failures, **extra):
23     return {"name": name, "evidence_type": evidence, "cases": cases,
24            "failures": failures, "hard_gate": not failures,
25            "command": "conda run -n py314 python b_solution/audit/correctness_audit.py",
26            "seed_range": extra.pop("seed_range", "deterministic pure cases; no RNG"), **extra}
27
28
29 def negative_audit():
30     failures = []
31     # Exact feasible witness model: all witnesses outside the open disk must
32     # remain in the returned convex outer approximation.
33     polys = [((-1800., -1800.), (1800., -1800.), (1800., 1800.), (-1800., 1800.)),
34              ((-100., -100.), (100., -100.), (100., 100.), (-100., 100.)),
35              [(0., 0.), (100., 0.), (0., 100.)]]
36     witnesses = [(1400., 0.), (-1400., 0.), (0., 1400.), (0., -1400.),
37                  (1000.0001, 0.), (0., 0.)]
38     # point-in-convex-polygon with boundary tolerance, independent from module
39     def inside(poly, p):
40         signs = []
41         for a, b in zip(poly, poly[1:] + poly[:1]):
42             c = (b[0]-a[0])*(p[1]-a[1])-(b[1]-a[1])*(p[0]-a[0])
43             signs.append(c)
44         return all(c >= -1e-7 for c in signs) or all(c <= 1e-7 for c in signs)
45     count = 0
46     for poly in polys:
47         out = exclude_omni_disk(poly, (0., 0.), sides=16)
48         for p in witnesses:
49             if dist(p, (0., 0.)) > 1000.0 and inside(poly, p):
50                 count += 1
51                 if not inside(out, p): failures.append({"poly": poly, "witness": p})
52     return rec("q3_negative_source_retention", "synthetic_exact_feasible_geometry", count, failures,
53              model="source feasible iff distance(station)>1000; convex outer approximation")

```

```

54
55
56 def portfolio_audit():
57     anchors = {2: (0., 0.), 7: (100., 0.), 9: (0., 0.)}
58     targets = {3: ((100., 0.), 10.), 8: ((0., 0.), 0.)}
59     task = choose_portfolio_task((0., 0.), anchors, targets, risk_weight=2.)
60     expected = {"anchor", 2}, {"anchor", 7}, {"anchor", 9}, {"target", 3}, {"target", 8}
61     # Exercise dictionary order permutations and ties.
62     failures = []
63     for reverse in (False, True):
64         a = dict(reversed(list(anchors.items()))) if reverse else dict(anchors)
65         t = dict(reversed(list(targets.items()))) if reverse else dict(targets)
66         got = choose_portfolio_task((0., 0.), a, t, risk_weight=2.)
67         if got != task: failures.append({"reverse": reverse, "got": got, "expected": task})
68     if task not in expected: failures.append({"selected": task, "tasks": sorted(expected)})
69     return rec("portfolio_obligation_and_ties", "synthetic_pure_route_proxy", 3, failures,
70             selected=task, complete_task_count=len(expected), duplicate_coordinate_keys=True)
71
72
73 def q4_negative_audit():
74     # All current field paths disable negative updates for Q4 by construction.
75     failures = []
76     class E:
77         def act(self, path, position=None, channel=None):
78             return {"accepted": True, "virtual_time_s": 0., "measure_result": "no_signal"}
79     for options in ({}, {"premeasure": False}, {"portfolio": False}, {"negative_updates": True},
80                 {"premeasure": True, "portfolio": True, "approach_clear": True}):
81         p = FieldPlanner(E(), problem=4, **options)
82         if p.negative_updates or p.negative_cuts != 0:
83             failures.append(options)
84     return rec("q4_negative_cuts", "synthetic_constructor_and_state", 5, failures,
85             claim_scope="current FieldPlanner paths only; not official behavior")
86
87
88 def timing_and_state_audit():
89     # Public action accounting fixture: rejected action must not mutate planner;
90     # accepted actions expose exact increments and one premeasure per localize.
91     failures = []
92     class E:
93         def __init__(self): self.calls = []
94         def act(self, path, position=None, channel=None):
95             self.calls.append((path, position, channel))
96             if path == "/enter": return {"accepted": True, "virtual_time_s": 0., "remaining_real_duration_s":
100., "max_virtual_duration_s": 100.}
97             return {"accepted": True, "virtual_time_s": 5., "measure_result": "no_signal", "
100            action_virtual_time_s": 5.}
98     e = E(); p = FieldPlanner(e, problem=3, premeasure=False, negative_updates=False, portfolio=False)
99     before = (p.position, p.virtual_time, list(p.visited), set(p.pending))
100     class Reject(E):
101         def act(self, path, position=None, channel=None):
102             if path == "/measure": return {"accepted": False, "virtual_time_s": 999.}
103             return super().act(path, position, channel)
104     r = FieldPlanner(Reject(), problem=3, premeasure=False)
105     try: r.action("/measure", (1., 2.), 1)
106     except RuntimeError: pass
107     if (r.position, r.virtual_time) != ((0., 0.), 0.): failures.append("rejected action advanced state")
108     # Exercise the one-per-channel contract across two localize calls at
109     # different positions; the second call must not issue another probe.
110     from planner import Track
111     spy = FieldPlanner(E(), problem=3, premeasure=True)
112     spy.tracks[1] = Track(polygon=[(-100., -100.), (100., -100.), (100., 100.), (-100., 100.)])
113     attempts = []
114     def one_measure(channel, point):
115         attempts.append((channel, tuple(point)))
116         spy.terminal_reason = "spy_stop"
117         return "no_signal"
118     spy.measure = one_measure

```

```

119     spy.localize(1)
120     spy.position = (500., 0.)
121     spy.localize(1)
122     if len(attempts) != 1: failures.append({"premeasure_attempts": len(attempts)})
123     # Independent virtual-time recomputation from observable LocalSimulator log.
124     from environment import LocalSimulator
125     env = LocalSimulator(500000, problem=3, scenario="minimum_radius")
126     env.act("/enter"); env.act("/measure", (300., 400.), 1); env.act("/measure", (300., 400.), 2); env.act("/
    exit")
127     recomputed = sum(row["action_virtual_time_s"] for row in env.log)
128     observed = env.log[-1]["response"]["virtual_time_s"]
129     if abs(recomputed - observed) > 2e-6: failures.append({"recomputed": recomputed, "observed": observed})
130     return rec("state_rejection_virtual_time_premeasure", "synthetic_public_action_fixture", 5, failures,
131               premeasure_calls=len(attempts), independent_virtual_time=True,
132               seed_range="500000 (single synthetic LocalSimulator fixture; permitted historical family)",
133               initial_state={"position": list(before[0]), "virtual_time": before[1],
134                             "visited": list(before[2]), "pending_count": len(before[3])})
135
136
137 def main():
138     rows = [negative_audit(), q4_negative_audit(), portfolio_audit(), timing_and_state_audit()]
139     payload = {"evidence": "synthetic_targeted_audit_only", "official_behavior_claimed": False,
140               "command": "conda run -n py314 python b_solution/audit/correctness_audit.py", "seed_range": None
141               ,
142               "configuration": {"official_simulator": False, "synthetic_model": "pure geometry + public action
    fixture"}},
143               "hard_gate": all(r["hard_gate"] for r in rows), "cases": rows,
144               "failing_case_count": sum(len(r["failures"]) for r in rows)}
145     OUT.parent.mkdir(parents=True, exist_ok=True)
146     OUT.write_text(json.dumps(payload, indent=2, sort_keys=True) + "\n")
147     print(json.dumps(payload, indent=2, sort_keys=True))
148
149 if __name__ == "__main__": main()

```

Listing 49: 独立候选筛选

```

1  """Independent shallow alternatives screen on standard local synthetic worlds.
2
3  Evidence is diagnostic only (never official). Candidates are deliberately
4  small, fixed a priori, and do not use FieldPlanner's route portfolio, negative
5  geometry, or premeasure. Candidate A bounds a global waypoint reordering to
6  six pending stops; B replans a two-stop rolling prefix; C uses a fixed dual
7  travel/uncertainty score when dispatching. No output is used for tuning.
8  """
9  from __future__ import annotations
10
11  import json
12  import math
13  import statistics
14  import sys
15  from pathlib import Path
16
17  ROOT = Path(__file__).resolve().parents[2]
18  sys.path.insert(0, str(ROOT / "b_solution"))
19  from environment import LocalSimulator # noqa: E402
20  from planner import Planner # noqa: E402
21  from geometry import enclosing_circle # noqa: E402
22  from route_policy_candidate import optimize_waypoints # noqa: E402
23
24  SEEDS = range(8201000, 8201040) # outside all prior and reserved parent ranges
25
26
27  class BoundedOrderPlanner(Planner):
28      """Refined mechanics plus a bounded, deterministic six-stop reorder."""
29      def next_anchor(self):
30          indices = sorted(self.pending)
31          if len(indices) <= 6 and indices:

```

```

32         order = optimize_waypoints([self.waypoints[i] for i in indices], self.position)
33         return indices[order[0]]
34     return super().next_anchor()
35
36     def select_task(self):
37         kind, index = super().select_task()
38         return (kind, self.next_anchor()) if kind == "anchor" else (kind, index)
39
40
41 class RollingTwoPlanner(Planner):
42     """Refined mechanics with an explicit rolling two-task lookahead."""
43     def next_anchor(self):
44         indices = sorted(self.pending)
45         if not indices:
46             return super().next_anchor()
47         # Recompute a route over at most the nearest two pending anchors.
48         nearest = sorted(indices, key=lambda i: (math.dist(self.position, self.waypoints[i]), i))[:2]
49         order = optimize_waypoints([self.waypoints[i] for i in nearest], self.position)
50         return nearest[order[0]]
51
52     def select_task(self):
53         kind, index = super().select_task()
54         return (kind, self.next_anchor()) if kind == "anchor" else (kind, index)
55
56
57 class DualScorePlanner(Planner):
58     """Fixed conservative dual score: travel plus 0.25 uncertainty radius."""
59     uncertainty_weight = 0.25
60
61     def select_task(self):
62         anchors = {i: self.waypoints[i] for i in sorted(self.pending)}
63         targets = {ch: enclosing_circle(track.polygon) for ch, track in self.tracks.items()}
64         # Compare one-step expected cost; radius is an information/uncertainty
65         # proxy, not simulator truth. Anchor scan cost is fixed at 120 m proxy.
66         options = [(math.dist(self.position, p) + 120.0, "anchor", i)
67                     for i, p in anchors.items()]
68         options += [(math.dist(self.position, c) + self.uncertainty_weight * r,
69                     "target", ch) for ch, (c, r) in targets.items()]
70         if not options:
71             return "anchor", self.next_anchor()
72         _, kind, ident = min(options, key=lambda x: (x[0], x[1], x[2]))
73         return kind, ident
74
75 CANDIDATES = {
76     "control_refined": lambda env, p: Planner(env, problem=p, strategy="refined"),
77     "A_bounded_order": lambda env, p: BoundedOrderPlanner(env, problem=p, strategy="refined"),
78     "B_rolling_two": lambda env, p: RollingTwoPlanner(env, problem=p, strategy="refined"),
79     "C_dual_score": lambda env, p: DualScorePlanner(env, problem=p, strategy="refined"),
80 }
81
82
83 def run_one(seed, problem, name):
84     env = LocalSimulator(seed, problem=problem, scenario="random", error_mode="smooth")
85     planner = CANDIDATES[name](env, problem)
86     result = planner.run()
87     actual = env.summary()
88     row = {"seed": seed, "problem": problem, "candidate": name,
89           "evidence": "local_synthetic_not_official", "scenario": "random",
90           "error_mode": "smooth", "result": result, "summary": actual}
91     row["decomposition"] = {k: actual.get(k) for k in (
92         "virtual_time_s", "average_time_s", "distance_m", "measures", "switches",
93         "clear_attempts", "failed_clears", "n_sources", "n_cleared", "fraction_cleared",
94         "real_duration_s")}
95     row["certificate"] = {"certificate_complete": result.get("certificate_complete"),
96                          "termination": result.get("termination"),
97                          "terminal_reason": result.get("terminal_reason")}
98     return row

```

```

99
100
101 def pct(values, q):
102     vals = sorted(values)
103     return vals[min(len(vals) - 1, max(0, math.ceil(q * len(vals)) - 1))]
104
105
106 def paired(control, candidate):
107     deltas = [a["summary"]["average_time_s"] - b["summary"]["average_time_s"]
108               for a, b in zip(control, candidate)]
109     mean = statistics.mean(deltas)
110     se = statistics.stdev(deltas) / math.sqrt(len(deltas)) if len(deltas) > 1 else 0.0
111     return {"paired_cases": len(deltas), "mean_saved_T_per_N_s": mean,
112            "approx_95pct_ci_s": [mean - 1.96 * se, mean + 1.96 * se],
113            "p90_saved_s": pct(deltas, .90), "worst_saved_s": min(deltas),
114            "faster_cases": sum(d > 0 for d in deltas),
115            "all_pairs_certificate_complete": all(
116                a["result"]["certificate_complete"] and b["result"]["certificate_complete"]
117                for a, b in zip(control, candidate)),
118            "failure_counts": {"control": sum(not r["result"]["certificate_complete"] for r in control),
119                             "candidate": sum(not r["result"]["certificate_complete"] for r in candidate)}}
120
121
122 def main():
123     runs, summary = [], {}
124     for problem in (3, 4):
125         groups = {name: [run_one(seed, problem, name) for seed in SEEDS] for name in CANDIDATES}
126         for rows in groups.values(): runs.extend(rows)
127         summary[f"Q{problem}"] = {}
128         for name, rows in groups.items():
129             times = [r["summary"]["average_time_s"] for r in rows]
130             summary[f"Q{problem}"][name] = {"cases": len(rows), "mean_T_per_N_s": statistics.mean(times),
131             "p90_T_per_N_s": pct(times, .90), "worst_T_per_N_s": max(times),
132             "all_cleared": sum(r["summary"]["fraction_cleared"] == 1 for r in rows),
133             "certificate_failures": sum(not r["result"]["certificate_complete"] for r in rows),
134             "failed_clear_attempts": sum(r["summary"]["failed_clears"] for r in rows)}
135         summary[f"Q{problem}"]["paired_vs_control"] = {
136             name: paired(groups["control_refined"], rows)
137             for name, rows in groups.items() if name != "control_refined"}
138     out = {"evidence": "local_synthetic_not_official", "diagnostic": True,
139           "seed_range": [SEEDS.start, SEEDS.stop - 1], "seeds_per_problem": len(SEEDS),
140           "configuration": {"error_mode": "smooth", "scenario": "random", "strategy": "refined",
141           "A": "bounded reorder only when <=6 pending anchors",
142           "B": "rolling optimize over nearest two pending anchors",
143           "C": "travel + 0.25*enclosing-radius fixed dual score",
144           "dependencies_excluded": ["route_portfolio", "negative_geometry", "premeasure"]},
145           "hard_gate": {"status": "diagnostic_only", "verified": False,
146           "rule": "No candidate is verified; paired CI/p90/worst and certificate gates are reported."},
147           "summary": summary, "runs": runs}
148     path = ROOT / "b_solution/results/audit_alternatives.json"
149     path.write_text(json.dumps(out, ensure_ascii=False, indent=2) + "\n")
150     print(json.dumps({"output": str(path), "evidence": out["evidence"], "seed_range": out["seed_range"], "
151                       summary": summary}, ensure_ascii=False))
152
153 if __name__ == "__main__":
154     main()

```

Listing 50: 补充冻结配对核验

```

1  """Locked final paired comparison; do not retune after execution."""
2  from __future__ import annotations
3  import json, math, random, statistics
4  from pathlib import Path
5  from field_study import run_field
6
7  START, COUNT = 8300000, 1000
8  CONFIGS = {

```

```

9     3: {"refined": None, "candidate": {"premeasure": True, "negative_updates": True, "portfolio": True, "
    approach_clear": True}},
10    4: {"refined": None, "candidate": {"premeasure": True, "negative_updates": False, "portfolio": True, "
    approach_clear": False}},
11 }
12 OUT = Path(__file__).resolve().parents[1] / "results" / "audit_freeze_compare.json"
13
14 def boot(xs, seed=190912, reps=5000):
15     r=random.Random(seed); n=len(xs); z=[]
16     for _ in range(reps): z.append(sum(xs[r.randrange(n)] for _ in range(n))/n)
17     z.sort(); return [z[int(.025*reps)], z[int(.975*reps)-1]]
18
19 def stats(control, candidate):
20     d=[a["average_time_s"]-b["average_time_s"] for a,b in zip(control,candidate)]
21     cv=[a["average_time_s"] for a in control]; nv=[a["average_time_s"] for a in candidate]
22     def q(v,p): return sorted(v)[math.ceil(p*len(v))-1]
23     return {"cases":len(d),"mean_saved_s":statistics.mean(d),"median_saved_s":statistics.median(d),"win_rate":
    sum(x>0 for x in d)/len(d),"paired_bootstrap_95pct_CI_s":boot(d),"control_mean":statistics.mean(cv),"
    candidate_mean":statistics.mean(nv),"control_median":statistics.median(cv),"candidate_median":statistics.
    median(nv),"control_p90":q(cv,.9),"candidate_p90":q(nv,.9),"control_worst":max(cv),"candidate_worst":max(
    nv),"all_clear_control":all(x["fraction_cleared"]==1 for x in control),"all_clear_candidate":all(x["
    fraction_cleared"]==1 for x in candidate),"all_certificate_control":all(x["certificate_complete"] for x in
    control),"all_certificate_candidate":all(x["certificate_complete"] for x in candidate)}
24
25 def main():
26     rows={}
27     for p, configs in CONFIGS.items():
28         groups={}
29         for name,cfg in configs.items():
30             groups[name]=[dict(run_field(s,p,cfg), configuration=name) for s in range(START,START+COUNT)]
31         rows[str(p)]={"seed_range": [START,START+COUNT-1],"summary":stats(groups["refined"],groups["candidate"])
    ,"runs":groups}
32     out={"evidence":"supplemental_locked_local_synthetic_paired_not_official","selection":"candidate
    configuration copied from the separately documented field_confirmation decision; this 8300000..8300999 run
    is an independent supplemental freeze check, not a parameter-selection dataset","seed_range": [START,START
    +COUNT-1],"configurations":CONFIGS,"results":rows}
33     OUT.write_text(json.dumps(out,ensure_ascii=False,indent=2)+"\n")
34     print(json.dumps({p:v["summary"] for p,v in rows.items()},ensure_ascii=False,indent=2))
35 if __name__=="__main__": main()

```

A.2 匿名文件清单与结果接口

文件或目录	用途
results/final_experiments.json	4430 次最终合成运行
results/enhancement_experiments.json	3080 次样本外增强运行
results/refinement_development.json	2550 次独立开发运行（非样本外）
results/research_experiments.json	10700 次冻结策略研究运行
results/research_verification.json	新覆盖、光学与行为证书核验
results/research_review.json	本轮最终独立自动审查
results/field_development.json	2250 次新策略开发运行（非样本外）
results/field_confirmation.json	9400 次新策略冻结确认运行

results/field_verification.json	新策略几何与行为有限核验
results/field_review.json	新策略独立自动审查
results/official_practice_analysis.json	用户提供的 20 轮官方演练
	离线动作分解
results/fast_vs_compact_410.json	fast25 与 compact25 的本地
	配对筛选负结果
results/practice_optimization_screen.json	官方演练轨迹驱动的参数筛
	选及否决记录
results/ring_sweep.json	Q3 环半径开发筛选及样本
	外配对证据
results/coverage_limits.json	全部 31 点不可删构造
results/refinement_verification.json	收缩环与角区间上界验证
results/geometry_verification.json	几何交叉核验与回归
results/intersection_verification.json	原始交会区域三种状态
results/http_verification.json	幂等重试与计时验证
results/http_deadline_verification.json	慢速响应绝对期限验证
results/second_point_example.json	第二测点候选评分
results/recovery_development.json	恢复策略开发对照
results/visual_review.json	PDF 逐页视觉检查记录
results/enhancement_review.json	增强策略独立审阅记录
results/paper_review.json	非官方自动审阅记录
results/final_review.json	历史增强结论与新世界证据
	的独立审查
report/generated/	自动数字、表格与轨迹证据
report/figures/	基础、历史增强及新研究矢
	量图
report/ai_usage.tex	AI 使用详情源文件
reproduce.txt、requirements.txt	命令、环境及依赖
MANIFEST.json	支撑包内文件校验值
results/route_candidate_comparison.json	路由候选负结果
results/adaptive_candidate_comparison.json	自适应测点候选负结果与子
	指标
results/terminal_verification.json	虚拟/现实期限终端回归
theory_additions.txt、paper_expansion.txt	独立理论草稿
report/generated/coverage_limits_table.tex	不可删性汇总表
polar_coverage_notes.txt	极坐标覆盖推导草稿
joint_dispatch_notes.txt	联合调度推导草稿
optical_policy_notes.txt	光学候选推导草稿
report/research_theory.tex	正文直接引用的新理论片段
report/generated/research_metadata.json	新图表输入哈希与分母记录
negative_geometry_notes.txt、route_portfolio_	负反馈几何及路线组合推导
notes.txt	

<code>report/generated/field_metadata.json</code>	field 图表输入哈希与分母
<code>practice_data/manifest.csv</code>	20 轮演练脱敏原始文件对应表
<code>practice_data/data/</code>	manifest 指定的 60 个脱敏原始文件
<code>contracts.json、report_contracts.json</code>	接口与证据口径的描述性快照

图表由`make_assets.py`、`make_enhancement_assets.py`、`make_research_assets.py`、`make_official_assets.py` 和`make_field_assets.py` 读取对应 JSON 生成，完整可运行代码如上。理论片段已在正文引用，不重复以代码字体排印中文。`notes` 文件只记录推导，实际结果以结果 JSON 为准。入口按问题默认 Q3 refined、Q4 field，`--strategy` 可显式覆盖；两题探测比例均为 0.22；历史 enhanced 另列。完整复现所需审查脚本及结果也保留在支撑包中。`audit_pdf.py` 渲染全部页面并检查文字边界；`package.py--verify` 在移除 PYTHONPATH 的临时解压目录中完整重建七组核心实验，共 34610 次执行，逐项比较完整 JSON，仅排除本地墙钟 `real_duration_s` 及派生 `max_real_duration_s`、`max_real_s`。五份 metadata 输入哈希在初末校验。脱敏演练文件不重生，逐个核对 SHA-256，运行`official_analysis.py--handoffpractice_data` 重新分析并比较；随后重建全部图表与编译，不以原目录存在文件代替复现通过。

未经脱敏的私有 HTTP 日志、正式加密日志及模拟器程序不进入本匿名研究包。仅收录 manifest 指定、经 `robot_id=TEAM_REDACTED` 及路径范围检查的 60 个演练原始文件；退出后源数、类型和案例标签只能用于离线评价。20 轮成本均由原始请求与反馈独立复算；严格旧策略动作回放仅 8 轮完整匹配，其余在首次未观测动作处停止，不造反馈。随包原始材料支持离线分析复现，不代表新策略官方成绩或全部旧策略回放通过。正式六份加密日志和真实人工审核仍未完成。