Workshop 2: Map Your Hard-to-Reverse Decisions

Project 60: Vision-Based Gesture Control for Terminal Multiplexers

Farzaan Wadiwalla wadiwalf@oregonstate.edu, Havel Konda kondah@oregonstate.edu, Justin Lee leeju8@oregonstate.edu, Tobias Kohn kohnto@oregonstate.edu

Decision	To Reverse	Validator
Gesture vocabulary: which hand poses and motions map to commands the system recognizes	Easy	
Intent schema: what information the multiplexer parses	Hard	Team, during initial architecture discussion
Process topology: multiplexer itself, headless recognizer, and visual dashboard	Hard	Guyer, at the next biweekly mentor meeting
Process communication: unix socket vs localhost TCP	Easy	
Multiplexer architecture: Electron/Tauri vs CLI native	Hard	Justin, before beginning multiplexer implementation
Multiplexer language: C vs Go	Hard	Justin, before beginning multiplexer implementation
Dashboard stack: plain web page vs Electron	Easy	
Input method: glasses-mounted camera vs built-in webcam vs EMG band vs hybrid	Easy	
Target platforms: macOS only vs cross platform	Easy (Depending on architecture)	
Repository license: MIT, GPL, or closed-source	Hard	Team, before we begin pushing code