

AE MCP Bridge: user manual

AE MCP Bridge lets an AI assistant (Claude Code, Claude Desktop, Cowork, Codex) work inside Adobe After Effects: build compositions, layers, effects and animation, look at the result frame by frame, and fix it, while you keep a normal, editable After Effects project.

It is inspired by "**After Effects MCP by Ruslan Tsapenko**" (v0.1.0, [YouTube @RuslanTsapenko](#), tsapenko.com) and ports tools and ideas from [TheLlamainator/after-effects-mcp](#) (MIT).

Parameter reference for every tool: [TOOLS.pdf](#).

Two ways to install

Let your AI agent install it. Start Claude Code (or Codex) in any folder and write:

Install AE MCP Bridge from <https://github.com/justajazz/ae-mcp-bridge> into C:\MCP\ae-mcp, following docs/INSTALL-AGENT.md in that repository.


If the files are already on your disk: "*Install AE MCP Bridge following C:\MCP\ae-mcp\docs\INSTALL-AGENT.md*". The agent follows [INSTALL-AGENT.pdf](#): it runs the commands, checks every step and asks you only for what it cannot do itself: confirm the Windows UAC prompt, tick one After Effects preference, start the panel, approve the server and restart your apps. About five minutes. The chat in Claude Desktop and Cowork cannot do this (they have no access to your system), but once installed they work with the bridge like any other client.

Install by hand. Follow [section 3](#) and [section 4](#) below.

Contents

1. [How it works](#)
2. [Requirements](#)
3. [Installation](#)
4. [Connecting an AI client](#) (and the optional skill)
5. [First steps](#)
6. [Working with the bridge](#)
7. [Tools](#)
8. [Safety: undo, backups, logs](#)
9. [Configuration](#)
10. [Troubleshooting](#)
11. [For developers](#)

1. How it works



How the bridge works: AI client, MCP server, bridge folder, panel inside After Effects

- `src/mcp-server.mjs` is the MCP server. The AI client starts it with Node.js; it has no dependencies and needs no `npm install` or build step.
- `src/ae-mcp-panel.jsx` is a small panel inside After Effects. While its bridge is running it checks the bridge folder ten times a second, executes commands and writes the results back.
- **The bridge folder** (`C:\MCP\ae-bridge` on Windows, `~/Library/Application Support/ae-mcp-bridge` on macOS) is where the two exchange files. It also holds temporary frames, logs, renders and project backups.
- Every request is synchronous and has a unique id, so a slow command is never executed twice.
- Tools are ExtendScript templates kept in the server; your data (names, text, paths) is passed separately and is never pasted into code, so quotes or Cyrillic in a layer name cannot break anything.

2. Requirements

- **Adobe After Effects** 2023 or newer (tested with After Effects 2026 on Windows 10; macOS paths are supported but not tested yet). Track mattes by layer need 2023+.
- **Node.js** 18.17 or newer (LTS recommended): <https://nodejs.org>. Check with `node --version`.
- An MCP client: **Claude Code**, **Claude Desktop** (chat and Cowork) or **Codex**.

3. Installation

These are the manual steps. An AI agent can do them for you: see [Two ways to install](#).

3.1 Get the files

Put the bridge in a permanent local folder, **not** inside Google Drive, OneDrive, Dropbox or iCloud. Recommended: `C:\MCP\ae-mcp` on Windows, `~/MCP/ae-mcp` on macOS.

```
git clone https://github.com/justajazz/ae-mcp-bridge.git C:\MCP\ae-mcp
```

(or download the ZIP and unpack it there). All paths below assume `C:\MCP\ae-mcp`; adjust them if you chose another folder.

3.2 Allow scripts in After Effects

After Effects: **Edit > Preferences > Scripting & Expressions** (macOS: *After Effects > Settings*), enable **Allow Scripts to Write Files and Access Network**, click OK.


3.3 Install the panel

Run the installer (After Effects may stay open; restart it afterwards):

```
node C:\MCP\ae-mcp\src\install-panel.mjs --link
```

- `--link` (recommended) installs a tiny loader into `ScriptUI Panels` that runs the panel from your bridge folder. After an update of the bridge you only reopen the panel; nothing has to be reinstalled.
- Without `--link` the full panel is copied. Use that if the bridge folder may move; rerun the installer after updates.
- `--uninstall` removes it; `--ae "C:\Program Files\Adobe\Adobe After Effects 2026"` targets one version.
- Writing into `Program Files` needs administrator rights: Windows shows a UAC prompt, confirm it. On macOS the `Applications` folder needs `sudo`; pass the full Node path so it is found under `sudo` as well: `sudo "$(which node)" ~/MCP/ae-mcp/src/install-panel.mjs --link`.

Then **restart After Effects**, open **Window > ae-mcp-panel.jsx**, dock the panel where you like and click **Start bridge**. The status line shows `Running: C:/MCP/ae-bridge`.



The ae-mcp-panel docked in After Effects, bridge running, autostart enabled

Tick **Start automatically when this panel opens**: the bridge then starts by itself whenever After Effects opens the panel (a docked panel reopens with your workspace).

Check the whole chain without any AI client:

```
node C:\MCP\ae-mcp\scripts\check-install.mjs
```

It starts the server the way a client does, asks After Effects for its status and ends with `RESULT: connected`.

Without installing: **File > Scripts > Run Script File...** and choose `src/ae-mcp-panel.jsx` opens the same panel as a floating window for one session (After Effects may ask for confirmation if *Warn User When Executing Files* is on).

4. Connecting an AI client

The server is always started the same way: `node <bridge folder>\src\mcp-server.mjs`. If `node` is not found by the client, use the full path from `where node` (Windows) or `which node` (macOS), e.g. `C:\Program Files\nodejs\node.exe`.

4.1 Claude Code

Two ways, choose one:

Option 1: per project (recommended to start with). In a terminal, inside the folder where you work with Claude:

```
claude mcp add --scope project after-effects -- node "C:\MCP\ae-mcp\src\mcp-server.mjs"
```

This creates `.mcp.json` in that folder. The next time you start `claude` there it asks whether to trust the server: choose **Use this MCP server**. To use the bridge in another project, run the same command there or copy `.mcp.json` into it (the path inside is absolute, so the file works anywhere).

Option 2: for all your sessions.

```
claude mcp add --scope user after-effects -- node "C:\MCP\ae-mcp\src\mcp-server.mjs"
```

Trade-offs of option 2: the descriptions of all tools are loaded into every Claude Code session (a few thousand tokens), an idle server process starts with each session, and After Effects becomes reachable from unrelated projects. This is not dangerous by itself: Claude Code asks permission for each tool call unless you allow it, the project is backed up before the first change and every call is one undo step. A middle ground is to keep a dedicated work folder for After Effects projects with its own `.mcp.json`.

Check with `/mcp` inside Claude Code: `after-effects` should be **connected**.

4.2 Claude Desktop (chat) and Cowork

Edit the config file (Claude Desktop: **Settings > Developer > Edit Config**):

- Windows: `%APPDATA%\Claude\claude_desktop_config.json`
- macOS: `~/Library/Application Support/Claude/claude_desktop_config.json`


Add the server inside `mcpServers` (keep everything else in the file unchanged):

```
{
  "mcpServers": {
    "after-effects": {
      "command": "C:\\Program Files\\nodejs\\node.exe",
      "args": ["C:\\MCP\\ae-mcp\\src\\mcp-server.mjs"]
    }
  }
}
```

Or let the helper do it (it backs the file up and adds only this entry):

```
node C:\MCP\ae-mcp\scripts\configure-client.mjs claude-desktop
```

Then **quit Claude Desktop completely** (tray / menu bar icon > Quit; closing the window is not enough) and start it again. In a chat, the + > **Connectors** menu lists **after-effects**; Cowork uses the same connectors. + > **Connectors** > **Add from after-effects** offers two ready prompts: *motion design guidelines* and *review the animation*.



Claude Desktop: + > Connectors > Add from after-effects with the two prompts

4.3 Codex

Add the server in Codex settings (**Settings** > **MCP**, add a server named `ae_mcp_bridge`, command `node`, argument: full path to `mcp-server.mjs`) or in `~/.codex/config.toml`:

```
[mcp_servers.ae_mcp_bridge]
command = "node"
args = ["C:\\MCP\\ae-mcp\\src\\mcp-server.mjs"]
```

(or run `node C:\MCP\ae-mcp\scripts\configure-client.mjs codex`). Restart Codex completely. Notes for Codex (not tested by us yet):

- All tools work the same way, including frames returned as images.
- Codex may not show MCP prompts; the guidelines are still available through the `ae_guidelines` tool and the short version arrives with the server instructions. Ask: *"Read ae_guidelines first."*
- Codex asks permission to run tools; allowing them for the session saves time.

Already using "After Effects MCP by Ruslan Tsapenko"? The two bridges can be installed side by side: they use different bridge folders and different panels, so neither sees the other's commands. Their tools, however, have the same names (`ae_health`, `ae_run_jsx`, ...), which confuses the assistant. While you use this bridge, turn the original off in **Codex Settings** > **MCP** (its server is usually named `after_effects`; it stays configured and can be turned on again) and keep its panel stopped. That is also why this bridge is registered as `ae_mcp_bridge` in Codex.

4.4 Optional: the `after-effects-motion` skill (Claude)

`skills/after-effects-motion` is a Claude skill with the working loop (orient, build, check, animate, review with a storyboard, report), a review checklist and recipes (card with bounce, text wave, counter, track matte, beat markers). Claude loads it automatically when a task involves After Effects. The motion rules themselves stay in the `ae_guidelines` tool, so the skill and the server never disagree.

- **Claude Code:** copy the folder to `%USERPROFILE%\.claude\skills\after-effects-motion` (macOS: `~/.claude/skills/after-effects-motion`), or to `.claude/skills/` of one project.
- **Claude Desktop / Cowork:** zip the `after-effects-motion` folder and upload it in **Settings** > **Capabilities** > **Skills**.

5. First steps


With After Effects open and the panel showing **Running**:

1. *"Check the connection to After Effects through MCP. Don't change anything."*: the assistant calls `ae_health` and reports versions, the open project and the active composition.
2. *"Create a 1080x1080 composition 'Test' with a rounded card and a title in the center, animate their entrance and show me a storyboard."*: the assistant builds the scene, animates it and checks the motion with `ae_capture_frames`.
3. Press **Ctrl+Z** in After Effects: each tool call is undone as one step.

6. Working with the bridge

6.1 The loop

Ask, then look, then fix. A good session goes: design the static layout, check it with a frame (`ae_capture_frame`), agree on it, animate, check the motion with a storyboard (`ae_capture_frames`), refine. Ask for a storyboard whenever something moves: a single frame cannot show timing problems.



A storyboard from `ae_capture_frames`: a card opening through its `Size` with an overshoot, text appearing through text animators

A storyboard like this one shows at a glance what a single frame hides: here the card opens from a line (0.2 s), overshoots (0.4 s) and settles, the number and the texts appear one after another inside the card, with motion blur.

6.2 Useful requests

Goal	Example request
Design from scratch	"Create an Apple-style activity card 500x800 with rounded corners in a 1080x1080 comp. The step count is the focus."
Recreate a reference	"Create a 1200x900 comp and rebuild this reference as precisely as possible." (attach the image; then "compare it with the reference" uses <code>compareWith</code>)

Goal	Example request
Critique	"Take a screenshot of the current frame, analyse the design and tell me what to improve. Don't change anything."
Animate	"Animate this in Apple style: the card opens through its rectangle Size with a small bounce, the texts appear with text animators, 4 frames apart, motion blur on."
Review motion	"Make a storyboard of 'Intro' and evaluate the animation." or the review the animation prompt
Work with what you selected	Select a layer or a text animator in AE, then: "Analyse the selected animator and apply the same animation to all text layers except the counter, 4 frames apart."
Copy animation	"Copy the Drop Shadow from Card to Title and Subtitle."
Clip content	"Make the subtitle visible only inside the card (track matte), keep the card visible."
Music markers	"Find the beats in the Music layer and put markers on them."
Watch it	"Render an MP4 preview of the first 3 seconds at half resolution."
Scripts	"Run C:\MCP\scripts\rename-layers.jsx on the active comp."

6.3 Tips

- Small position tweaks are often faster by hand in AE; leave structure, repetitive work and analysis to the assistant.
- Before asking for animation, ask the assistant to read the guidelines (`ae_guidelines`) or use the *motion design guidelines* prompt: it then avoids opacity-only fades, uses asymmetric easing, text animators, stagger, track mattes and motion blur.
- Name your layers; the assistant addresses layers by name.
- Tell the assistant which composition to use if several are open.

7. Tools

34 tools. Every parameter is described in [TOOLS.pdf](#).

Properties are addressed by paths through the layer's property tree:



Property paths: Transform/Position, Effects/Gaussian Blur/Blurriness, Contents/Group 1/Contents/Rectangle Path 1/Size, Text/Animators/MCP Reveal

Bridge and project

Tool	What it does
<code>ae_health</code>	Versions, open project, active comp, panel state.
<code>ae_guidelines</code>	Motion-design and workflow guide for the assistant.
<code>ae_list_project</code>	Compositions with layers, plus folders, footage and solids.
<code>ae_open_project</code>	Open another .aep (asks to save or discard unsaved changes).
<code>ae_save_project</code>	Save, or save as.
<code>ae_get_result</code>	Collect the result of a command that outlived its timeout.

Scripting

Tool	What it does
<code>ae_run_jsx</code>	Run any ExtendScript; returns the last value.
<code>ae_run_jsx_file</code>	Run a .jsx file from disk.

Looking at the result

Tool	What it does
<code>ae_capture_frame</code>	One frame as an image (background filled with the comp color; optional reference image beside it).
<code>ae_capture_frames</code>	Storyboard: several frames in one image with time labels.
<code>ae_render_preview</code>	MP4 or PNG sequence through the Render Queue.
<code>ae_get_selection</code>	What you selected in AE, with keyframes and property trees.
<code>ae_inspect</code>	Full property tree of a layer or group: values, keys, easing, expressions.

Compositions and layers

Tool	What it does
<code>ae_create_comp</code>	New composition.
<code>ae_set_comp</code>	Size, duration, frame rate, background, motion blur, work area, current time.
<code>ae_create_layer</code>	Text, shape (rectangle, ellipse, polygon, star), solid, adjustment or null layer.
<code>ae_set_layer</code>	Transform, timing, parent, 3D, label, text style, motion blur, track matte.
<code>ae_center_layers</code>	Center layers visually (anchor moved to the content center).
<code>ae_get_layer_timing</code>	In/out points in seconds and frames.

Properties and animation

Tool	What it does
<code>ae_set_property</code>	Any property by path, static or at a time.
<code>ae_set_keyframes</code>	Keyframes with easing (linear, hold, bezier, easy, easyIn, easyOut, custom).
<code>ae_set_expression</code>	Set or remove an expression; reports expression errors.
<code>ae_add_text_animator</code>	Text reveal through a text animator (soft wave by characters/words, or by lines).

Tool	What it does
<code>ae_copy_animation</code>	Copy animators, effects or properties with keys to other layers, staggered.

Effects and presets

Tool	What it does
<code>ae_list_available_effects</code>	Search installed effects.
<code>ae_apply_effect</code>	Apply an effect by name and set its parameters.
<code>ae_list_layer_effects</code>	Effects on a layer with their values.
<code>ae_remove_effects</code>	Remove effects.
<code>ae_list_presets</code>	Find .ffx animation presets.
<code>ae_apply_preset</code>	Apply a preset to a layer.

Markers and audio

Tool	What it does
<code>ae_add_markers</code>	Layer or composition markers, one or many.
<code>ae_get_audio_info</code>	Audio source file, levels and markers of a layer.
<code>ae_set_audio_levels</code>	Audio Levels, static or keyed.
<code>ae_analyze_audio</code>	Find peaks in a WAV file and optionally place markers on them.

8. Safety: undo, backups, logs

- **Undo.** Every changing tool call is one undo group named `MCP: <tool>` : one Ctrl+Z undoes the whole call.
- **Backups.** Before the first change to a project in a server session, the saved `.aep` is copied to `C:\MCP\ae-bridge\backups\<name>_<date>_<time>.aep` ; the last 5 per project are kept. The copy is the state of the file on disk, so save your project before a session if you want unsaved work included.
- **Logs.** Every executed script is written to `C:\MCP\ae-bridge\logs\ae-mcp-<date>.log` (kept 30 days).
- **No arbitrary code mode.** Set `AE_MCP_DISABLE_RUN_JSX=1` for the server: `ae_run_jsx` and `ae_run_jsx_file` disappear and only the built-in tools remain.
- **Permissions.** Claude and Codex ask before each tool call until you allow a tool permanently. `ae_run_jsx` can do anything a script can do in After Effects, including reading and writing files; keep that in mind before allowing it without prompts.
- Work on copies of important projects when you experiment.

9. Configuration

Environment variables of the **server** (set them in the client config: `env` in `.mcp.json` / `claude_desktop_config.json` , or `env` in Codex):

Variable	Default	Meaning
AE_MCP_BRIDGE_DIR	C:\MCP\ae-bridge / ~/Library/Application Support/ae-mcp-bridge	Bridge folder. If you change it, set the same variable for After Effects too (see below).
AE_MCP_TIMEOUT_MS	30000	How long a tool waits before returning a <code>commandId</code> (renders and frames wait longer).
AE_MCP_PICKUP_TIMEOUT_MS	10000	How long to wait for the panel to pick a command up before reporting it is not running.
AE_MCP_DISABLE_RUN_JSX	off	1 disables <code>ae_run_jsx</code> and <code>ae_run_jsx_file</code> .
AE_MCP_BACKUP	on	0 disables project backups.
AE_MCP_BACKUP_KEEP	5	Backups kept per project.
AE_MCP_BACKUP_DIR	<bridge>\backups	Backup folder.
AE_MCP_LOG	on	0 disables the script log.
AE_MCP_LOG_DAYS	30	Days to keep logs.

The panel reads `AE_MCP_BRIDGE_DIR` from the environment of After Effects. On Windows set it as a user variable (`setx AE_MCP_BRIDGE_DIR "D:\my-bridge"`), then restart After Effects and the AI client. Keep the bridge folder out of cloud-synced folders: sync clients lock files, and the server warns about it.

Example `.mcp.json` entry with options:

```
{
  "mcpServers": {
    "after-effects": {
      "command": "node",
      "args": ["C:\MCP\ae-mcp\src\mcp-server.mjs"],
      "env": { "AE_MCP_BACKUP_KEEP": "10", "AE_MCP_TIMEOUT_MS": "60000" }
    }
  }
}
```

10. Troubleshooting

Start with `node C:\MCP\ae-mcp\scripts\check-install.mjs` : it tests the server and the panel without any client and tells you which side is missing.

Symptom	What to do
"bridge panel has never run in this bridge folder"	Open Window > ae-mcp-panel.jsx and click Start bridge . If it runs, the panel and the server use different bridge folders: compare the path in the panel with <code>ae_health</code> .
"panel is stopped"	Click Start bridge (or enable autostart).

Symptom	What to do
"did not pick up the command"	After Effects is busy (rendering, a modal dialog is open) or the panel was closed. Close dialogs, check the panel. Nothing was executed.
A tool returns <code>status: running</code>	The command is still running in AE. Ask the assistant to wait for it (<code>ae_get_result</code>); do not repeat the request.
"After Effects is still executing ..."	A previous long command is running; wait for it.
Undo group mismatch dialog in AE	Click OK. It appears when a project is opened or closed inside a script; use <code>ae_open_project</code> instead.
Unable to write file / nothing happens	Enable Allow Scripts to Write Files and Access Network in AE preferences.
The panel is not in the Window menu	Restart After Effects after installing; check that the installer wrote to the right AE version.
Version mismatch warning in <code>ae_health</code>	Reopen the panel (with <code>--link</code>) or rerun the installer.
The client does not list the tools	Check the command and the path to <code>mcp-server.mjs</code> ; use the full path to <code>node</code> ; restart the client completely; in Claude Code check <code>/mcp</code> .
Cloud-sync warning	Move the bridge folder out of OneDrive / Google Drive / Dropbox / iCloud.
Text looks wrong in the frame	Fonts are referenced by PostScript name (e.g. <code>Arial-BoldMT</code>); a missing font falls back silently.

11. For developers

- `npm test` : protocol, serializer, PNG/WAV and documentation tests against a Node mock of the panel (no AE needed).
- Every tool was also verified against a real After Effects 2026 with a dedicated test project.
- `node scripts/gen-tools-doc.mjs` regenerates [TOOLS.pdf](#) after changing tool definitions.
- `scripts/check-install.mjs` and `scripts/configure-client.mjs` are the installation helpers used by [INSTALL-AGENT.pdf](#).
- Architecture: tools are ES3 JSX templates in `src/jsx.mjs` with a shared one-line `lib` prepended; user data goes in `args` . Media processing (PNG compositing, contact sheets, WAV analysis, preset search) is in `src/media.mjs` . The panel (`src/ae-mcp-panel.jsx`) only evaluates code, manages undo groups and serializes results safely.
- ExtendScript is ES3: no `let` / `const` , arrow functions, template literals, `Array.forEach/map/indexOf` ; `tests/panel.test.mjs` lints every template.

Credits

- Inspiration: **Ruslan Tsapenko** and his "After Effects MCP by Ruslan Tsapenko" v0.1.0.
- Tools and ideas ported from [TheLlamainator/after-effects-mcp](#), based on [Dakkshin/after-effects-mcp](#) (MIT, © 2025 Dakkshin).
- Made by **Claude Code** & **Yuriy Martyniuk** (assistant, consultant and producer).
- License: MIT.