VitalPulse — Full Source Code

44 files · generated 2026-10-15

base44/entities/ActivitySession.jsonc

```
{
  "name": "ActivitySession",
  "type": "object",
  "properties": {
    "steps": {
      "type": "number",
      "default": 0,
      "description": "Total steps in session"
    },
    "duration_seconds": {
      "type": "number",
      "default": 0,
      "description": "Session duration in seconds"
    },
    "calories_burned": {
      "type": "number",
      "default": 0,
      "description": "Estimated calories burned"
    },
    "avg_heart_rate": {
      "type": "number",
      "description": "Average heart rate in bpm"
    },
    "max_heart_rate": {
      "type": "number",
      "description": "Peak heart rate in bpm"
    },
    "bmi_at_time": {
      "type": "number",
      "description": "BMI recorded at session time"
    },
    "session_date": {
      "type": "string",
      "format": "date",
      "description": "Date of the session"
    },
    "device_type": {
      "type": "string",
      "enum": [
        "phone",
        "watch"
      ],
      "default": "phone",
      "description": "Device used for tracking"
    }
  },
  "required": [
    "steps"
  ]
}
```

base44/entities/HealthProfile.jsonc

```
{
  "name": "HealthProfile",
  "type": "object",
  "properties": {
    "height_cm": {
      "type": "number",
      "description": "Height in centimeters"
    },
    "weight_kg": {
      "type": "number",
      "description": "Weight in kilograms"
    },
    "age": {
      "type": "number",
      "description": "Age in years"
    },
    "gender": {
      "type": "string",
      "enum": [
        "male",
        "female"
```

```
      ],
      "description": "Biological gender"
    },
    "resting_hr": {
      "type": "number",
      "description": "Resting heart rate in bpm"
    },
    "activity_level": {
      "type": "string",
      "enum": [
        "sedentary",
        "light",
        "moderate",
        "active",
        "very_active"
      ],
      "default": "moderate"
    },
    "health_conditions": {
      "type": "array",
      "items": {
        "type": "string"
      },
      "description": "Health conditions to tailor AI recommendations (e.g. Diabetes, Hypertension)"
    },
    "cycle_phase": {
      "type": "string",
      "enum": [
        "menstrual",
        "follicular",
        "ovulation",
        "luteal"
      ],
      "description": "Current menstrual cycle phase (women only)"
    },
    "pregnancy_status": {
      "type": "string",
      "enum": [
        "not_pregnant",
        "first_trimester",
        "second_trimester",
        "third_trimester"
      ],
      "description": "Pregnancy status (women only)"
    },
    "waist_cm": {
      "type": "number",
      "description": "Waist circumference in centimeters"
    },
    "hip_cm": {
      "type": "number",
      "description": "Hip circumference in centimeters"
    }
  },
  "required": [
    "height_cm",
    "weight_kg"
  ]
}
```

base44/entities/Payment.jsonc

```
{
  "name": "Payment",
  "type": "object",
  "properties": {
    "amount": {
      "type": "number",
      "default": 0.99,
      "description": "Payment amount in USD"
    },
    "status": {
      "type": "string",
      "enum": [
        "pending",
        "completed",
        "failed"
```

```
      ],
      "default": "pending",
      "description": "Payment status"
    },
    "payment_method": {
      "type": "string",
      "default": "simulated",
      "description": "Method used for payment"
    },
    "user_email": {
      "type": "string",
      "description": "Email of the user who paid"
    }
  },
  "required": [
    "amount"
  ]
}
```

base44/entities/User.jsonc

```
{
  "properties": {
    "role": {
      "type": "string",
      "description": "The role of the user in the app",
      "enum": [
        "admin",
        "user"
      ]
    }
  },
  "required": [
    "role"
  ],
  "name": "User",
  "type": "object"
}
```

src/App.jsx

```
import { Toaster } from "@/components/ui/toaster"
import { QueryClientProvider } from '@tanstack/react-query'
import { queryClientInstance } from '@/lib/query-client'
import { BrowserRouter as Router, Route, Routes, Navigate } from 'react-router-dom';
import PageNotFound from './lib/PageNotFound';
import { AuthProvider, useAuth } from '@/lib/AuthContext';
import UserNotRegisteredError from '@/components/UserNotRegisteredError';
import ScrollToTop from './components/ScrollToTop';
import ProtectedRoute from '@/components/ProtectedRoute';
import Login from '@/pages/Login';
import Register from '@/pages/Register';
import ForgotPassword from '@/pages/ForgotPassword';
import ResetPassword from '@/pages/ResetPassword';
import AppLayout from '@/components/AppLayout';
import Home from '@/pages/Home';
import BMICalculator from '@/pages/BMICalculator';
import StepTracker from '@/pages/StepTracker';
import Progress from '@/pages/Progress';
import Paywall from '@/pages/Paywall';
import PaywallGate from '@/components/PaywallGate';
import Insights from '@/pages/Insights';
import ActivityLog from '@/pages/ActivityLog';
import BodyType from '@/pages/BodyType';

const AuthenticatedApp = () => {
  const { isLoadingAuth, isLoadingPublicSettings, authError, navigateToLogin } = useAuth();

  // Show loading spinner while checking app public settings or auth
  if (isLoadingPublicSettings || isLoadingAuth) {
    return (
      <div className="fixed inset-0 flex items-center justify-center">
        <div className="w-8 h-8 border-4 border-slate-200 border-t-slate-800 rounded-full animate-spin"></div>
      </div>
    );
  }
```

```
  // Handle authentication errors
  if (authError) {
    if (authError.type === 'user_not_registered') {
      return <UserNotRegisteredError />;
    } else if (authError.type === 'auth_required') {
      // Redirect to login automatically
      navigateToLogin();
      return null;
    }
  }

  // Render the main app
  return (
    <Routes>
      <Route path="/login" element={<Login />} />
      <Route path="/register" element={<Register />} />
      <Route path="/forgot-password" element={<ForgotPassword />} />
      <Route path="/reset-password" element={<ResetPassword />} />
      <Route element={<ProtectedRoute unauthenticatedElement={<Navigate to="/login" replace />} />}>
        <Route path="/paywall" element={<Paywall />} />
        <Route element={<PaywallGate />}>
          <Route element={<AppLayout />}>
            <Route path="/" element={<Home />} />
            <Route path="/bmi" element={<BMICalculator />} />
            <Route path="/tracker" element={<StepTracker />} />
            <Route path="/progress" element={<Progress />} />
            <Route path="/insights" element={<Insights />} />
            <Route path="/log" element={<ActivityLog />} />
            <Route path="/body-type" element={<BodyType />} />
          </Route>
        </Route>
      </Route>
      <Route path="*" element={<PageNotFound />} />
    </Routes>
  );
};


function App() {

  return (
    <AuthProvider>
      <QueryClientProvider client={queryClientInstance}>
        <Router>
          <ScrollToTop />
          <AuthenticatedApp />
        </Router>
        <Toaster />
      </QueryClientProvider>
    </AuthProvider>
  )
}

export default App
```

src/api/base44Client.js

```
import { createClient } from '@base44/sdk';
import { appParams } from '@/lib/app-params';

const { appId, token, functionsVersion, appBaseUrl } = appParams;

//Create a client with authentication required
export const base44 = createClient({
  appId,
  token,
  functionsVersion,
  serverUrl: '',
  requiresAuth: false,
  appBaseUrl
});
```

src/components/AppLayout.jsx

```
import { Outlet, NavLink } from 'react-router-dom';
import { Activity, Calculator, Footprints, TrendingUp, Heart, Sparkles, LogOut, ClipboardList, Ruler } from
'lucide-react';
import { useAuth } from '@/lib/AuthContext';

const navItems = [
  { to: '/', label: 'Dashboard', icon: Activity, shortLabel: 'Home' },
  { to: '/bmi', label: 'BMI Calculator', icon: Calculator, shortLabel: 'BMI' },
  { to: '/body-type', label: 'Body Type & Ratios', icon: Ruler, shortLabel: 'Body' },
  { to: '/tracker', label: 'Step Tracker', icon: Footprints, shortLabel: 'Track' },
  { to: '/progress', label: 'Progress', icon: TrendingUp, shortLabel: 'Stats' },
  { to: '/insights', label: 'AI Insights', icon: Sparkles, shortLabel: 'AI' },
  { to: '/log', label: 'Daily Log', icon: ClipboardList, shortLabel: 'Log' },
];

export default function AppLayout() {
  const { logout } = useAuth();
  return (
    <div className="dark min-h-screen bg-slate-950 text-white flex">
      {/* Sidebar - desktop */}
      <aside className="hidden md:flex flex-col w-64 bg-slate-900/50 border-r border-slate-800 p-5
backdrop-blur-sm fixed h-full z-40">
        <div className="flex items-center gap-3 mb-10 px-2">
          <div className="w-10 h-10 rounded-xl bg-gradient-to-br from-emerald-400 to-teal-600 flex items-center
justify-center shadow-lg shadow-emerald-500/20">
            <Heart className="w-5 h-5 text-white" />
          </div>
          <div>
            <div className="font-bold text-lg tracking-tight">VitalPulse</div>
            <div className="text-xs text-slate-500">Health Tracker</div>
          </div>
        </div>
        <nav className="flex flex-col gap-1">
          {navItems.map((item) => (
            <NavLink
              key={item.to}
              to={item.to}
              end={item.to === '/'}
              className={({ isActive }) =>
                `flex items-center gap-3 px-3 py-2.5 rounded-xl text-sm font-medium transition-all ${
                  isActive
                    ? 'bg-emerald-500/15 text-emerald-400'
                    : 'text-slate-400 hover:text-white hover:bg-slate-800/50'
                }`
              }
            >
              <item.icon className="w-5 h-5" />
              {item.label}
            </NavLink>
          ))}
        </nav>
        <div className="mt-auto space-y-3">
          <div className="px-2 text-xs text-slate-600">
            <p>Real-time motion tracking</p>
            <p className="mt-1">Phone & wrist watch ready</p>
          </div>
          <button
            onClick={() => logout()}
            className="flex items-center gap-3 px-3 py-2.5 rounded-xl text-sm font-medium text-slate-400
hover:text-rose-400 hover:bg-slate-800/50 transition-all w-full"
          >
            <LogOut className="w-5 h-5" />
            Log out
          </button>
        </div>
      </aside>

      {/* Mobile bottom nav */}
      <nav className="md:hidden fixed bottom-0 left-0 right-0 bg-slate-900/95 border-t border-slate-800
backdrop-blur-lg z-50 flex justify-around py-2 px-2">
        {navItems.map((item) => (
          <NavLink
            key={item.to}
            to={item.to}
            end={item.to === '/'}
```

```
            className={({ isActive }) =>
              `flex flex-col items-center gap-1 px-2 py-1.5 rounded-lg text-[10px] font-medium transition-all ${
                isActive ? 'text-emerald-400' : 'text-slate-500'
              }`
            }
          >
            <item.icon className="w-5 h-5" />
            {item.shortLabel}
          </NavLink>
        ))}
      </nav>

      {/* Main content */}
      <main className="flex-1 md:ml-64 p-4 md:p-8 pb-24 md:pb-8 max-w-5xl mx-auto w-full">
        <div className="flex justify-end md:hidden mb-2">
          <button
            onClick={() => logout()}
            className="flex items-center gap-1.5 px-3 py-1.5 rounded-lg text-xs text-slate-400
hover:text-rose-400 transition-colors"
          >
            <LogOut className="w-4 h-4" />
            Log out
          </button>
        </div>
        <Outlet />
      </main>
    </div>
  );
}
```

src/components/AuthLayout.jsx

```
import React from "react";

export default function AuthLayout({ icon: Icon, title, subtitle, footer, children }) {
  return (
    <div className="min-h-screen flex items-center justify-center bg-background px-4">
      <div className="w-full max-w-md">
        <div className="text-center mb-10">
          <div className="inline-flex items-center justify-center w-14 h-14 rounded-2xl bg-primary mb-4">
            <Icon className="w-7 h-7 text-primary-foreground" aria-hidden="true" />
          </div>
          <h1 className="text-3xl font-bold tracking-tight text-foreground">{title}</h1>
          {subtitle && <p className="text-muted-foreground mt-2">{subtitle}</p>}
        </div>
        <div className="bg-card rounded-2xl shadow-sm border border-border p-8">
          {children}
        </div>
        {footer && (
          <p className="text-center text-sm text-muted-foreground mt-6">{footer}</p>
        )}
      </div>
    </div>
  );
}
```

src/components/BMIGauge.jsx

```
const colorMap = {
  sky: '#0ea5e9',
  emerald: '#10b981',
  amber: '#f59e0b',
  rose: '#f43f5e',
  slate: '#64748b',
};

export default function BMIGauge({ bmi, category }) {
  const radius = 80;
  const circumference = 2 * Math.PI * radius;
  const arcFraction = 0.75;
  const arcLength = circumference * arcFraction;

  const minBmi = 15;
  const maxBmi = 40;
  const clampedBmi = bmi ? Math.max(minBmi, Math.min(maxBmi, bmi)) : minBmi;
```

```
  const progress = bmi ? (clampedBmi - minBmi) / (maxBmi - minBmi) : 0;
  const filledLength = Math.max(0, arcLength * progress);

  const colorKey = category?.bg?.replace('bg-', '').replace('-500', '');
  const stroke = colorMap[colorKey] || '#10b981';

  return (
    <div className="relative w-56 h-56">
      <svg className="w-full h-full rotate-[135deg]" viewBox="0 0 200 200">
        <circle
          cx="100" cy="100" r={radius}
          fill="none"
          stroke="rgb(30 41 59)"
          strokeWidth="14"
          strokeDasharray={`${arcLength} ${circumference}`}
          strokeLinecap="round"
        />
        <circle
          cx="100" cy="100" r={radius}
          fill="none"
          stroke={stroke}
          strokeWidth="14"
          strokeDasharray={`${filledLength} ${circumference}`}
          strokeLinecap="round"
          style={{ transition: 'stroke-dasharray 1s ease-out' }}
        />
      </svg>
      <div className="absolute inset-0 flex flex-col items-center justify-center">
        <div className="text-4xl font-bold text-white">{bmi ? bmi.toFixed(1) : '—'}</div>
        <div className="text-sm text-slate-500 mt-1">BMI</div>
        {category && <div className={`text-sm font-medium mt-2 ${category.color}`}>{category.label}</div>}
      </div>
    </div>
  );
}
```

src/components/GoogleIcon.jsx

```
import React from "react";

export default function GoogleIcon({ className = "w-5 h-5" }) {
  return (
    <svg className={className} viewBox="0 0 24 24" aria-hidden="true">
      <path d="M22.56 12.25c0-.78-.07-1.53-.2-2.25H12v4.26h5.92a5.06 5.06 0 01-2.2 3.32v2.77h3.57c2.08-1.92
3.28-4.74 3.28-8.1z" fill="#4285F4" />
      <path d="M12 23c2.97 0 5.46-.98 7.28-2.66l-3.57-2.77c-.98.66-2.23 1.06-3.71 1.06-2.86
0-5.29-1.93-6.16-4.53H2.18v2.84C3.99 20.53 7.7 23 12 23z" fill="#34A853" />
      <path d="M5.84 14.09c-.22-.66-.35-1.36-.35-2.09s.13-1.43.35-2.09V7.07H2.18C1.43 8.55 1 10.22 1 12s.43 3.45
1.18 4.93l2.85-2.22.81-.62z" fill="#FBBC05" />
      <path d="M12 5.38c1.62 0 3.06.56 4.21 1.64l3.15-3.15C17.45 2.09 14.97 1 12 1 7.7 1 3.99 3.47 2.18 7.07l3.66
2.84c.87-2.6 3.3-4.53 6.16-4.53z" fill="#EA4335" />
    </svg>
  );
}
```

src/components/InsightCard.jsx

```
import { useState } from 'react';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { Button } from '@/components/ui/button';
import { Loader2, Sparkles, Image as ImageIcon } from 'lucide-react';
import { Image } from '@/components/ui/image';

const accentMap = {
  emerald: { text: 'text-emerald-400', bg: 'bg-emerald-500/10', border: 'border-emerald-500/20', btn:
'from-emerald-500 to-teal-600' },
  sky: { text: 'text-sky-400', bg: 'bg-sky-500/10', border: 'border-sky-500/20', btn: 'from-sky-500 to-blue-600'
},
  orange: { text: 'text-orange-400', bg: 'bg-orange-500/10', border: 'border-orange-500/20', btn:
'from-orange-500 to-amber-600' },
  rose: { text: 'text-rose-400', bg: 'bg-rose-500/10', border: 'border-rose-500/20', btn: 'from-rose-500
to-pink-600' },
  violet: { text: 'text-violet-400', bg: 'bg-violet-500/10', border: 'border-violet-500/20', btn:
'from-violet-500 to-purple-600' },
```

```
};

export default function InsightCard({ title, icon: Icon, accent = 'emerald', promptBuilder, imagePromptBuilder,
delay = 0 }) {
  const [data, setData] = useState(null);
  const [image, setImage] = useState(null);
  const [loading, setLoading] = useState(false);
  const [imageLoading, setImageLoading] = useState(false);
  const [error, setError] = useState('');
  const a = accentMap[accent];

  const generate = async () => {
    setError('');
    setLoading(true);
    try {
      const result = await base44.integrations.Core.InvokeLLM({
        prompt: promptBuilder(),
        response_json_schema: {
          type: 'object',
          properties: {
            summary: { type: 'string' },
            recommendations: {
              type: 'array',
              items: {
                type: 'object',
                properties: {
                  title: { type: 'string' },
                  description: { type: 'string' },
                  benefits: { type: 'string' },
                },
              },
            },
          },
        },
      });
      setData(result);
    } catch (err) {
      setError(err.message || 'Failed to generate insights');
    } finally {
      setLoading(false);
    }
  };

  const generateImage = async () => {
    setImageLoading(true);
    try {
      const res = await base44.integrations.Core.GenerateImage({ prompt: imagePromptBuilder() });
      setImage(res.url);
    } catch (err) {
      setError('Image generation failed');
    } finally {
      setImageLoading(false);
    }
  };

  return (
    <motion.div
      initial={{ opacity: 0, y: 12 }}
      animate={{ opacity: 1, y: 0 }}
      transition={{ duration: 0.3, delay }}
      className={`bg-slate-900/60 border ${a.border} rounded-2xl p-5 backdrop-blur-sm`}
    >
      <div className="flex items-center gap-3 mb-4">
        <div className={`w-10 h-10 rounded-xl ${a.bg} flex items-center justify-center`}>
          <Icon className={`w-5 h-5 ${a.text}`} />
        </div>
        <h3 className="font-semibold text-lg">{title}</h3>
      </div>

      <div className="flex gap-2 mb-4">
        <Button
          onClick={generate}
          disabled={loading}
          size="sm"
          className={`bg-gradient-to-r ${a.btn} border-0 text-white hover:opacity-90`}
        >
          {loading ? <Loader2 className="w-4 h-4 mr-1.5 animate-spin" /> : <Sparkles className="w-4 h-4 mr-1.5"
/>}
```

```
          {loading ? 'Generating...' : data ? 'Regenerate' : 'Generate'}
        </Button>
        {data && (
          <Button onClick={generateImage} disabled={imageLoading} size="sm" variant="outline"
className="border-slate-700 text-slate-300">
            {imageLoading ? <Loader2 className="w-4 h-4 mr-1.5 animate-spin" /> : <ImageIcon className="w-4 h-4
mr-1.5" />}
            {imageLoading ? 'Rendering...' : image ? 'New Image' : 'Visualize'}
          </Button>
        )}
      </div>

      {error && <p className="text-rose-400 text-sm mb-3">{error}</p>}

      {image && (
        <div className="mb-4 rounded-xl overflow-hidden">
          <Image src={image} alt={title} className="w-full h-48" fittingType="fill" />
        </div>
      )}

      {data && (
        <div className="space-y-3">
          {data.summary && <p className="text-sm text-slate-300">{data.summary}</p>}
          {data.recommendations?.map((r, i) => (
            <div key={i} className="bg-slate-800/40 border border-slate-800 rounded-xl p-3">
              <div className={`font-medium text-sm ${a.text}`}>{r.title}</div>
              <p className="text-sm text-slate-400 mt-1">{r.description}</p>
                          {r.benefits && <p className="text-xs text-slate
            </div>
          ))}
        </div>
      )}
    </motion.div>
  );
}
```

src/components/InsightsSettings.jsx

```
import { useState } from 'react';
import { base44 } from '@/api/base44Client';
import { Loader2, Save } from 'lucide-react';

const CONDITIONS = ['Diabetes', 'Hypertension', 'Asthma', 'Arthritis', 'Heart Disease'];
const CYCLE_PHASES = ['menstrual', 'follicular', 'ovulation', 'luteal'];
const PREGNANCY_STATUSES = ['not_pregnant', 'first_trimester', 'second_trimester', 'third_trimester'];
const PREGNANCY_LABELS = {
  not_pregnant: 'Not pregnant',
  first_trimester: 'First trimester',
  second_trimester: 'Second trimester',
  third_trimester: 'Third trimester',
};

export default function InsightsSettings({ profile, onSave }) {
  const [conditions, setConditions] = useState(profile.health_conditions || []);
  const [cyclePhase, setCyclePhase] = useState(profile.cycle_phase || '');
  const [pregnancyStatus, setPregnancyStatus] = useState(profile.pregnancy_status || 'not_pregnant');
  const [saving, setSaving] = useState(false);
  const isFemale = profile.gender === 'female';

  const toggleCondition = (c) => {
    setConditions((prev) => (prev.includes(c) ? prev.filter((x) => x !== c) : [...prev, c]));
  };

  const save = async () => {
    setSaving(true);
    try {
      const updated = await base44.entities.HealthProfile.update(profile.id, {
        health_conditions: conditions,
        cycle_phase: isFemale && cyclePhase ? cyclePhase : undefined,
        pregnancy_status: isFemale ? pregnancyStatus : undefined,
      });
      onSave({ ...profile, ...updated });
    } catch (e) {
      // ignore
    }
    setSaving(false);
  };
```

```
  return (
    <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-5">
      <h3 className="font-semibold mb-4 text-sm text-slate-300">Tailor Your Insights</h3>

      <div className="mb-4">
        <label className="text-xs text-slate-500 mb-2 block">Health Conditions</label>
        <div className="flex flex-wrap gap-2">
          {CONDITIONS.map((c) => (
            <button
              key={c}
              onClick={() => toggleCondition(c)}
              className={`px-3 py-1.5 rounded-lg text-xs font-medium transition-all ${
                conditions.includes(c)
                  ? 'bg-rose-500/20 text-rose-400 border border-rose-500/40'
                  : 'bg-slate-800/50 text-slate-400 border border-slate-700 hover:border-slate-600'
              }`}
            >
              {c}
            </button>
          ))}
        </div>
      </div>

      {isFemale && (
        <>
          <div className="mb-4">
            <label className="text-xs text-slate-500 mb-2 block">Cycle Phase</label>
            <div className="flex flex-wrap gap-2">
              {CYCLE_PHASES.map((p) => (
                <button
                  key={p}
                  onClick={() => setCyclePhase(cyclePhase === p ? '' : p)}
                  className={`px-3 py-1.5 rounded-lg text-xs font-medium transition-all capitalize ${
                    cyclePhase === p
                      ? 'bg-violet-500/20 text-violet-400 border border-violet-500/40'
                      : 'bg-slate-800/50 text-slate-400 border border-slate-700 hover:border-slate-600'
                  }`}
                >
                  {p}
                </button>
              ))}
            </div>
          </div>
          <div className="mb-4">
            <label className="text-xs text-slate-500 mb-2 block">Pregnancy Status</label>
            <div className="flex flex-wrap gap-2">
              {PREGNANCY_STATUSES.map((p) => (
                <button
                  key={p}
                  onClick={() => setPregnancyStatus(p)}
                  className={`px-3 py-1.5 rounded-lg text-xs font-medium transition-all ${
                    pregnancyStatus === p
                      ? 'bg-violet-500/20 text-violet-400 border border-violet-500/40'
                      : 'bg-slate-800/50 text-slate-400 border border-slate-700 hover:border-slate-600'
                  }`}
                >
                  {PREGNANCY_LABELS[p]}
                </button>
              ))}
            </div>
          </div>
        </>
      )}

      <button
        onClick={save}
        disabled={saving}
        className="flex items-center gap-2 px-4 py-2 rounded-lg bg-emerald-500 text-white text-sm font-medium
hover:bg-emerald-400 disabled:opacity-50"
      >
        {saving ? <Loader2 className="w-4 h-4 animate-spin" /> : <Save className="w-4 h-4" />}
        Save Preferences
      </button>
    </div>
  );
}
```

src/components/PaywallGate.jsx

```
import { useEffect, useState } from 'react';
import { Outlet, Navigate } from 'react-router-dom';
import { base44 } from '@/api/base44Client';
import { useAuth } from '@/lib/AuthContext';

export default function PaywallGate() {
  const { user, isLoadingAuth } = useAuth();
  const [checking, setChecking] = useState(true);
  const [hasPaid, setHasPaid] = useState(false);

  useEffect(() => {
    async function check() {
      if (isLoadingAuth) return;

      if (!user) {
        setHasPaid(false);
        setChecking(false);
        return;
      }

      // Admins bypass the paywall
      if (user.role === 'admin') {
        setHasPaid(true);
        setChecking(false);
        return;
      }

      try {
        const payments = await base44.entities.Payment.filter({
          created_by_id: user.id,
          status: 'completed',
        });
        setHasPaid(payments.length > 0);
      } catch (e) {
        setHasPaid(false);
      }
      setChecking(false);
    }
    check();
  }, [user, isLoadingAuth]);

  if (isLoadingAuth || checking) {
    return (
      <div className="dark min-h-screen bg-slate-950 flex items-center justify-center">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  if (!hasPaid) {
    return <Navigate to="/paywall" replace />;
  }

  return <Outlet />;
}
```

src/components/ProtectedRoute.jsx

```
import { useEffect } from 'react';
import { Outlet } from 'react-router-dom';
import { useAuth } from '@/lib/AuthContext';
import UserNotRegisteredError from '@/components/UserNotRegisteredError';

const DefaultFallback = () => (
  <div className="fixed inset-0 flex items-center justify-center">
    <div className="w-8 h-8 border-4 border-slate-200 border-t-slate-800 rounded-full animate-spin"></div>
  </div>
);

export default function ProtectedRoute({ fallback = <DefaultFallback />, unauthenticatedElement }) {
  const { isAuthenticated, isLoadingAuth, authChecked, authError, checkUserAuth } = useAuth();

  useEffect(() => {
    if (!authChecked && !isLoadingAuth) {
```

```
      checkUserAuth();
    }
  }, [authChecked, isLoadingAuth, checkUserAuth]);

  if (isLoadingAuth || !authChecked) {
    return fallback;
  }

  if (authError) {
    if (authError.type === 'user_not_registered') {
      return <UserNotRegisteredError />;
    }
    return unauthenticatedElement;
  }

  if (!isAuthenticated) {
    return unauthenticatedElement;
  }

  return <Outlet />;
}
```

src/components/ScrollToTop.jsx

```
import { useEffect } from "react";
import { useLocation, useNavigationType } from "react-router-dom";

const getHashId = (hash) => {
  const rawId = hash.slice(1);

  try {
    return decodeURIComponent(rawId);
  } catch {
    return rawId;
  }
};

export default function ScrollToTop() {
  const { pathname, hash } = useLocation();
  const navigationType = useNavigationType();

  useEffect(() => {
    if (navigationType === "POP") return;

    if (hash) {
      const id = getHashId(hash);
      const timer = window.setTimeout(() => {
        document.getElementById(id)?.scrollIntoView({ behavior: "smooth" });
      }, 50);
      return () => window.clearTimeout(timer);
    }

    window.scrollTo({ top: 0, left: 0, behavior: "instant" });
  }, [pathname, hash, navigationType]);

  return null;
}
```

src/components/StatCard.jsx

```
import { motion } from 'framer-motion';

const accentMap = {
  emerald: 'text-emerald-400 bg-emerald-500/10',
  orange: 'text-orange-400 bg-orange-500/10',
  rose: 'text-rose-400 bg-rose-500/10',
  sky: 'text-sky-400 bg-sky-500/10',
};

export default function StatCard({ icon: Icon, label, value, unit, accent = 'emerald', delay = 0 }) {
  return (
    <motion.div
      initial={{ opacity: 0, y: 12 }}
      animate={{ opacity: 1, y: 0 }}
```

```
      transition={{ duration: 0.3, delay }}
      className="bg-slate-900/60 border border-slate-800 rounded-2xl p-5 backdrop-blur-sm"
    >
      <div className="flex items-center justify-between mb-3">
        <div className={`w-10 h-10 rounded-xl flex items-center justify-center ${accentMap[accent]}`}>
          <Icon className="w-5 h-5" />
        </div>
      </div>
      <div className="text-2xl font-bold text-white">
        {value}
        {unit && <span className="text-sm text-slate-500 ml-1 font-normal">{unit}</span>}
      </div>
      <div className="text-sm text-slate-400 mt-1">{label}</div>
    </motion.div>
  );
}
```

src/components/UserNotRegisteredError.jsx

```
import React from 'react';

const UserNotRegisteredError = () => {
  return (
    <div className="flex flex-col items-center justify-center min-h-screen bg-gradient-to-b from-white
to-slate-50">
      <div className="max-w-md w-full p-8 bg-white rounded-lg shadow-lg border border-slate-100">
        <div className="text-center">
          <div className="inline-flex items-center justify-center w-16 h-16 mb-6 rounded-full bg-orange-100">
            <svg className="w-8 h-8 text-orange-600" fill="none" stroke="currentColor" viewBox="0 0 24 24">
              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="2" d="M12 9v2m0 4h.01m-6.938
4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-.77 1.333.192 3 1.732 3z" />
            </svg>
          </div>
          <h1 className="text-3xl font-bold text-slate-900 mb-4">Access Restricted</h1>
          <p className="text-slate-600 mb-8">
            You are not registered to use this application. Please contact the app administrator to request
access.
          </p>
          <div className="p-4 bg-slate-50 rounded-md text-sm text-slate-600">
            <p>If you believe this is an error, you can:</p>
            <ul className="list-disc list-inside mt-2 space-y-1">
              <li>Verify you are logged in with the correct account</li>
              <li>Contact the app administrator for access</li>
              <li>Try logging out and back in again</li>
            </ul>
          </div>
        </div>
      </div>
    </div>
  );
};

export default UserNotRegisteredError;
```

src/hooks/use-mobile.jsx

```
import * as React from "react"

const MOBILE_BREAKPOINT = 768

export function useIsMobile() {
  const [isMobile, setIsMobile] = React.useState(undefined)

  React.useEffect(() => {
    const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
    const onChange = () => {
      setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    }
    mql.addEventListener("change", onChange)
    setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    return () => mql.removeEventListener("change", onChange);
  }, [])

  return !!isMobile
}
```

src/hooks/use-size.jsx

```
import * as React from "react"

export function useSize(ref) {
  const [size, setSize] = React.useState(null)

  // useLayoutEffect (not useEffect): the initial measurement must land before
  // the browser paints, so consumers can render their real content on the
  // very first painted frame instead of a guess. A ResizeObserver's first
  // callback arrives too late for that — by then an <img> src guess has
  // already been dispatched to the network.
  React.useLayoutEffect(() => {
    const element = ref.current
    if (!element) return

    const rect = element.getBoundingClientRect()
    setSize({ width: rect.width, height: rect.height })

    const observer = new ResizeObserver(([entry]) => {
      const { width, height } = entry.contentRect
      setSize({ width, height })
    })

    observer.observe(element)
    return () => observer.disconnect()
  }, [ref])

  return size
}
```

src/hooks/usePedometer.js

```
import { useState, useRef, useCallback, useEffect } from 'react';

export function usePedometer({ weightKg = 70, age = 30, restingHr = 70 } = {}) {
  const [steps, setSteps] = useState(0);
  const [isActive, setIsActive] = useState(false);
  const [elapsed, setElapsed] = useState(0);
  const [cadence, setCadence] = useState(0);
  const [permissionState, setPermissionState] = useState('unknown');

  const stepCountRef = useRef(0);
  const startTimeRef = useRef(null);
  const lastPeakTimeRef = useRef(0);
  const prevMagnitudeRef = useRef(0);
  const smoothedMagRef = useRef(0);
  const stepTimestampsRef = useRef([]);
  const intervalRef = useRef(null);
  const listeningRef = useRef(false);
  const elapsedRef = useRef(0);

  const estimateHR = useCallback((cad) => {
    const maxHr = 220 - age;
    const intensity = Math.min(cad / 180, 1);
    return Math.round(restingHr + (maxHr - restingHr) * intensity * 0.7);
  }, [age, restingHr]);

  const handleMotion = useCallback((event) => {
    if (!listeningRef.current) return;
    const acc = event.accelerationIncludingGravity;
    if (!acc || acc.x == null) return;

    const magnitude = Math.sqrt(acc.x ** 2 + acc.y ** 2 + acc.z ** 2);
    smoothedMagRef.current = smoothedMagRef.current * 0.8 + magnitude * 0.2;

    const now = Date.now();
    const threshold = 11.5;

    if (smoothedMagRef.current > threshold && prevMagnitudeRef.current <= threshold) {
      if (now - lastPeakTimeRef.current > 250) {
        stepCountRef.current += 1;
        lastPeakTimeRef.current = now;
```

```
      stepTimestampsRef.current.push(now);
      stepTimestampsRef.current = stepTimestampsRef.current.filter(t => now - t < 10000);
      const cad = Math.round(stepTimestampsRef.current.length * 6);
      setCadence(cad);
      setSteps(stepCountRef.current);
    }
  }
  prevMagnitudeRef.current = smoothedMagRef.current;
}, []);

const requestPermission = useCallback(async () => {
  if (typeof DeviceMotionEvent !== 'undefined' && typeof DeviceMotionEvent.requestPermission === 'function') {
    try {
      const result = await DeviceMotionEvent.requestPermission();
      const granted = result === 'granted';
      setPermissionState(granted ? 'granted' : 'denied');
      return granted;
    } catch (e) {
      setPermissionState('denied');
      return false;
    }
  }
  setPermissionState('granted');
  return true;
}, []);

const start = useCallback(async () => {
  const granted = await requestPermission();
  if (!granted) return false;

  listeningRef.current = true;
  setIsActive(true);
  startTimeRef.current = Date.now() - (elapsedRef.current * 1000);

  window.addEventListener('devicemotion', handleMotion);

  intervalRef.current = setInterval(() => {
    const secs = Math.floor((Date.now() - startTimeRef.current) / 1000);
    elapsedRef.current = secs;
    setElapsed(secs);
    const now = Date.now();
    stepTimestampsRef.current = stepTimestampsRef.current.filter(t => now - t < 10000);
    if (stepTimestampsRef.current.length === 0) setCadence(0);
  }, 1000);

  return true;
}, [requestPermission, handleMotion]);

const stop = useCallback(() => {
  listeningRef.current = false;
  setIsActive(false);
  if (intervalRef.current) {
    clearInterval(intervalRef.current);
    intervalRef.current = null;
  }
  window.removeEventListener('devicemotion', handleMotion);
}, [handleMotion]);

const reset = useCallback(() => {
  stop();
  setSteps(0);
  setElapsed(0);
  setCadence(0);
  stepCountRef.current = 0;
  elapsedRef.current = 0;
  stepTimestampsRef.current = [];
  startTimeRef.current = null;
  lastPeakTimeRef.current = 0;
  prevMagnitudeRef.current = 0;
  smoothedMagRef.current = 0;
}, [stop]);

useEffect(() => {
  return () => {
    if (intervalRef.current) clearInterval(intervalRef.current);
    window.removeEventListener('devicemotion', handleMotion);
  };
}, [handleMotion]);
```

```
  const currentHR = estimateHR(cadence);
  const currentCalories = Math.round(steps * (weightKg / 70) * 0.04);

  return {
    steps,
    isActive,
    elapsed,
    cadence,
    currentHR,
    currentCalories,
    permissionState,
    requestPermission,
    start,
    stop,
    reset,
  };
}
```

src/index.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;

@layer base {
  :root {
    --background: 0 0% 100%;
    --foreground: 0 0% 3.9%;
    --card: 0 0% 100%;
    --card-foreground: 0 0% 3.9%;
    --popover: 0 0% 100%;
    --popover-foreground: 0 0% 3.9%;
    --primary: 0 0% 9%;
    --primary-foreground: 0 0% 98%;
    --secondary: 0 0% 96.1%;
    --secondary-foreground: 0 0% 9%;
    --muted: 0 0% 96.1%;
    --muted-foreground: 0 0% 45.1%;
    --accent: 0 0% 96.1%;
    --accent-foreground: 0 0% 9%;
    --destructive: 0 84.2% 60.2%;
    --destructive-foreground: 0 0% 98%;
    --border: 0 0% 89.8%;
    --input: 0 0% 89.8%;
    --ring: 0 0% 3.9%;
    --chart-1: 12 76% 61%;
    --chart-2: 173 58% 39%;
    --chart-3: 197 37% 24%;
    --chart-4: 43 74% 66%;
    --chart-5: 27 87% 67%;
    --radius: 0.5rem;
    --font-heading: ui-sans-serif, system-ui, sans-serif;
    --font-body: ui-sans-serif, system-ui, sans-serif;
    --font-display: ui-sans-serif, system-ui, sans-serif;
    --font-mono: ui-monospace, SFMono-Regular, Menlo, Monaco, Consolas, "Liberation Mono", "Courier New",
monospace;
    --sidebar-background: 0 0% 98%;
    --sidebar-foreground: 240 5.3% 26.1%;
    --sidebar-primary: 240 5.9% 10%;
    --sidebar-primary-foreground: 0 0% 98%;
    --sidebar-accent: 240 4.8% 95.9%;
    --sidebar-accent-foreground: 240 5.9% 10%;
    --sidebar-border: 220 13% 91%;
    --sidebar-ring: 217.2 91.2% 59.8%;
  }

  .dark {
    --background: 0 0% 3.9%;
    --foreground: 0 0% 98%;
    --card: 0 0% 3.9%;
    --card-foreground: 0 0% 98%;
    --popover: 0 0% 3.9%;
    --popover-foreground: 0 0% 98%;
    --primary: 0 0% 98%;
    --primary-foreground: 0 0% 9%;
    --secondary: 0 0% 14.9%;
```

```
    --secondary-foreground: 0 0% 98%;
    --muted: 0 0% 14.9%;
    --muted-foreground: 0 0% 63.9%;
    --accent: 0 0% 14.9%;
    --accent-foreground: 0 0% 98%;
    --destructive: 0 62.8% 30.6%;
    --destructive-foreground: 0 0% 98%;
    --border: 0 0% 14.9%;
    --input: 0 0% 14.9%;
    --ring: 0 0% 83.1%;
    --chart-1: 220 70% 50%;
    --chart-2: 160 60% 45%;
    --chart-3: 30 80% 55%;
    --chart-4: 280 65% 60%;
    --chart-5: 340 75% 55%;
    --sidebar-background: 240 5.9% 10%;
    --sidebar-foreground: 240 4.8% 95.9%;
    --sidebar-primary: 224.3 76.3% 48%;
    --sidebar-primary-foreground: 0 0% 100%;
    --sidebar-accent: 240 3.7% 15.9%;
    --sidebar-accent-foreground: 240 4.8% 95.9%;
    --sidebar-border: 240 3.7% 15.9%;
    --sidebar-ring: 217.2 91.2% 59.8%;
  }
}



@layer base {
  * {
    @apply border-border outline-ring/50;
  }

  body {
    @apply bg-background text-foreground font-body;
  }
}
```

src/lib/AuthContext.jsx

```
import React, { createContext, useState, useContext, useEffect } from 'react';
import { base44 } from '@/api/base44Client';
import { appParams } from '@/lib/app-params';
import { createAxiosClient } from '@base44/sdk/dist/utils/axios-client';

const AuthContext = createContext();

export const AuthProvider = ({ children }) => {
  const [user, setUser] = useState(null);
  const [isAuthenticated, setIsAuthenticated] = useState(false);
  const [isLoadingAuth, setIsLoadingAuth] = useState(true);
  const [isLoadingPublicSettings, setIsLoadingPublicSettings] = useState(true);
  const [authError, setAuthError] = useState(null);
  const [authChecked, setAuthChecked] = useState(false);
  const [appPublicSettings, setAppPublicSettings] = useState(null); // Contains only { id, public_settings }

  useEffect(() => {
    checkAppState();
  }, []);

  const checkAppState = async () => {
    try {
      setIsLoadingPublicSettings(true);
      setAuthError(null);

      // First, check app public settings (with token if available)
      // This will tell us if auth is required, user not registered, etc.
      const appClient = createAxiosClient({
        baseURL: `/api/apps/public`,
        headers: {
          'X-App-Id': appParams.appId
        },
        token: appParams.token, // Include token if available
        interceptResponses: true
      });
```

```
    try {
      const publicSettings = await appClient.get(`/prod/public-settings/by-id/${appParams.appId}`);
      setAppPublicSettings(publicSettings);

      // If we got the app public settings successfully, check if user is authenticated
      if (appParams.token) {
        await checkUserAuth();
      } else {
        setIsLoadingAuth(false);
        setIsAuthenticated(false);
        setAuthChecked(true);
      }
      setIsLoadingPublicSettings(false);
    } catch (appError) {
      console.error('App state check failed:', appError);

      // Handle app-level errors
      if (appError.status === 403 && appError.data?.extra_data?.reason) {
        const reason = appError.data.extra_data.reason;
        if (reason === 'auth_required') {
          setAuthError({
            type: 'auth_required',
            message: 'Authentication required'
          });
        } else if (reason === 'user_not_registered') {
          setAuthError({
            type: 'user_not_registered',
            message: 'User not registered for this app'
          });
        } else {
          setAuthError({
            type: reason,
            message: appError.message
          });
        }
      } else {
        setAuthError({
          type: 'unknown',
          message: appError.message || 'Failed to load app'
        });
      }
      setIsLoadingPublicSettings(false);
      setIsLoadingAuth(false);
    }
  } catch (error) {
    console.error('Unexpected error:', error);
    setAuthError({
      type: 'unknown',
      message: error.message || 'An unexpected error occurred'
    });
    setIsLoadingPublicSettings(false);
    setIsLoadingAuth(false);
  }
};

const checkUserAuth = async () => {
  try {
    // Now check if the user is authenticated
    setIsLoadingAuth(true);
    const currentUser = await base44.auth.me();
    setUser(currentUser);
    setIsAuthenticated(true);
    setIsLoadingAuth(false);
    setAuthChecked(true);
  } catch (error) {
    console.error('User auth check failed:', error);
    setIsLoadingAuth(false);
    setIsAuthenticated(false);
    setAuthChecked(true);

    // If user auth fails, it might be an expired token
    if (error.status === 401 || error.status === 403) {
      setAuthError({
        type: 'auth_required',
        message: 'Authentication required'
      });
    }
  }
```

```
  };

  const logout = (shouldRedirect = true) => {
    setUser(null);
    setIsAuthenticated(false);

    if (shouldRedirect) {
      // Use the SDK's logout method which handles token cleanup and redirect
      base44.auth.logout(window.location.href);
    } else {
      // Just remove the token without redirect
      base44.auth.logout();
    }
  };

  const navigateToLogin = () => {
    // Use the SDK's redirectToLogin method
    base44.auth.redirectToLogin(window.location.href);
  };

  return (
    <AuthContext.Provider value={{
      user,
      isAuthenticated,
      isLoadingAuth,
      isLoadingPublicSettings,
      authError,
      appPublicSettings,
      authChecked,
      logout,
      navigateToLogin,
      checkUserAuth,
      checkAppState
    }}>
      {children}
    </AuthContext.Provider>
  );
};

export const useAuth = () => {
  const context = useContext(AuthContext);
  if (!context) {
    throw new Error('useAuth must be used within an AuthProvider');
  }
  return context;
};
```

src/lib/PageNotFound.jsx

```
import { useLocation } from 'react-router-dom';
import { base44 } from '@/api/base44Client';
import { useQuery } from '@tanstack/react-query';


export default function PageNotFound({}) {
    const location = useLocation();
    const pageName = location.pathname.substring(1);

    const { data: authData, isFetched } = useQuery({
        queryKey: ['user'],
        queryFn: async () => {
            try {
                const user = await base44.auth.me();
                return { user, isAuthenticated: true };
            } catch (error) {
                return { user: null, isAuthenticated: false };
            }
        }
    });

    return (
        <div className="min-h-screen flex items-center justify-center p-6 bg-slate-50">
            <div className="max-w-md w-full">
                <div className="text-center space-y-6">
                    {/* 404 Error Code */}
                    <div className="space-y-2">
```

```
                        <h1 className="text-7xl font-light text-slate-300">404</h1>
                        <div className="h-0.5 w-16 bg-slate-200 mx-auto"></div>
                    </div>

                    {/* Main Message */}
                    <div className="space-y-3">
                        <h2 className="text-2xl font-medium text-slate-800">
                            Page Not Found
                        </h2>
                        <p className="text-slate-600 leading-relaxed">
                            The page <span className="font-medium text-slate-700">"{pageName}"</span> could not
be found in this application.
                        </p>
                    </div>

                    {/* Admin Note */}
                    {isFetched && authData.isAuthenticated && authData.user?.role === 'admin' && (
                        <div className="mt-8 p-4 bg-slate-100 rounded-lg border border-slate-200">
                            <div className="flex items-start space-x-3">
                                <div className="flex-shrink-0 w-5 h-5 rounded-full bg-orange-100 flex
items-center justify-center mt-0.5">
                                    <div className="w-2 h-2 rounded-full bg-orange-400"></div>
                                </div>
                                <div className="text-left space-y-1">
                                    <p className="text-sm font-medium text-slate-700">Admin Note</p>
                                    <p className="text-sm text-slate-600 leading-relaxed">
                                        This could mean that the AI hasn't implemented this page yet. Ask it to
implement it in the chat.
                                    </p>
                                </div>
                            </div>
                        </div>
                    )}

                    {/* Action Button */}
                    <div className="pt-6">
                        <button
                            onClick={() => window.location.href = '/'}
                            className="inline-flex items-center px-4 py-2 text-sm font-medium text-slate-700
bg-white border border-slate-200 rounded-lg hover:bg-slate-50 hover:border-slate-300 transition-colors
duration-200 focus:outline-none focus:ring-2 focus:ring-offset-2 focus:ring-slate-500"
                        >
                            <svg className="w-4 h-4 mr-2" fill="none" stroke="currentColor" viewBox="0 0 24 24">
                                <path strokeLinecap="round" strokeLinejoin="round" strokeWidth={2} d="M3 12l2-2m0
0l7-7 7 7M5 10v10a1 1 0 001 1h3m10-11l2 2m-2-2v10a1 1 0 01-1 1h-3m-6 0a1 1 0 001-1v-4a1 1 0 011-1h2a1 1 0 011
1v4a1 1 0 001 1m-6 0h6" />
                            </svg>
                            Go Home
                        </button>
                    </div>
                </div>
            </div>
        </div>
    )
}
```

src/lib/app-params.js

```
const isNode = typeof window === 'undefined';
const windowObj = isNode ? { localStorage: new Map() } : window;
const storage = windowObj.localStorage;

const toSnakeCase = (str) => {
        return str.replace(/([A-Z])/g, '_$1').toLowerCase();
}

const getAppParamValue = (paramName, { defaultValue = undefined, removeFromUrl = false } = {}) => {
        if (isNode) {
                return defaultValue;
        }
        const storageKey = `base44_${toSnakeCase(paramName)}`;
        const urlParams = new URLSearchParams(window.location.search);
        const searchParam = urlParams.get(paramName);
        if (removeFromUrl) {
                urlParams.delete(paramName);
                const newUrl = `${window.location.pathname}${urlParams.toString() ? `?${urlParams.toString()}` : ""
                        }${window.location.hash}`;
```

```
                window.history.replaceState({}, document.title, newUrl);
        }
        if (searchParam) {
                storage.setItem(storageKey, searchParam);
                return searchParam;
        }
        if (defaultValue) {
                storage.setItem(storageKey, defaultValue);
                return defaultValue;
        }
        const storedValue = storage.getItem(storageKey);
        if (storedValue) {
                return storedValue;
        }
        return null;
}

const getAppParams = () => {
        if (getAppParamValue("clear_access_token") === 'true') {
                storage.removeItem('base44_access_token');
                storage.removeItem('token');
        }
        return {
                appId: getAppParamValue("app_id", { defaultValue: import.meta.env.VITE_BASE44_APP_ID }),
                token: getAppParamValue("access_token", { removeFromUrl: true }),
                fromUrl: getAppParamValue("from_url", { defaultValue: window.location.href }),
                functionsVersion: getAppParamValue("functions_version", { defaultValue:
import.meta.env.VITE_BASE44_FUNCTIONS_VERSION }),
                appBaseUrl: getAppParamValue("app_base_url", { defaultValue: import.meta.env.VITE_BASE44_APP_BASE_URL }),
        }
}


export const appParams = {
        ...getAppParams()
}
```

src/lib/authReturnTo.js

```
// Shared by the auth pages (Login, Register, and any page that resumes a flow
// after sign-in, e.g. the MCP OAuth consent page). Keep the redirect
// validation in one place — it is security-sensitive and easy to drift.

// Resolve ?returnTo= to a safe same-origin path, else "/".
//
// The same-origin check alone is not enough: a value like /.//evil.com or
// /\evil.com parses same-origin but normalizes to a protocol-relative
// //evil.com when assigned to location.href — an open redirect. So require the
// resolved path to be exactly one leading slash (no "//" prefix, no backslash).
export function safeReturnTo() {
  const raw = new URLSearchParams(window.location.search).get("returnTo");
  if (!raw) return "/";
  try {
    const url = new URL(raw, window.location.origin);
    if (url.origin !== window.location.origin) return "/";
    // Strip app-bootstrap params: app-params.js persists these from the URL into
    // localStorage before the SDK initializes, so a crafted returnTo could
    // otherwise poison the freshly issued session — repointing the app at an
    // attacker's backend (app_base_url/app_id/functions_version) or overwriting
    // the token. Normal app-flow params (e.g. the OAuth consent ctx) are kept.
    // The full app-params.js bootstrap set (src/lib/app-params.js) — any of
    // these in a crafted returnTo would be persisted at next load.
    for (const p of ["access_token", "clear_access_token", "app_id", "app_base_url", "functions_version",
"from_url"]) {
      url.searchParams.delete(p);
    }
    const path = url.pathname + url.search;
    if (!path.startsWith("/") || path.startsWith("//") || path.includes("\\")) return "/";
    return path;
  } catch {
    return "/";
  }
}
```

src/lib/healthUtils.js

```
export function calculateBMI(weightKg, heightCm) {
  if (!weightKg || !heightCm) return null;
  const heightM = heightCm / 100;
  const bmi = weightKg / (heightM * heightM);
  return Math.round(bmi * 10) / 10;
}

export function getBMICategory(bmi) {
  if (bmi == null) return { label: '—', color: 'text-slate-400', bg: 'bg-slate-500', advice: 'Enter your
measurements to calculate BMI.' };
  if (bmi < 18.5) return { label: 'Not enough', color: 'text-sky-400', bg: 'bg-sky-500', advice: 'Consider
increasing caloric intake with nutrient-rich foods and strength training.' };
  if (bmi < 25) return { label: 'Looks decent', color: 'text-emerald-400', bg: 'bg-emerald-500', advice: 'Great
work! Maintain your healthy lifestyle with regular activity.' };
  if (bmi < 30) return { label: 'Room for growth', color: 'text-amber-400', bg: 'bg-amber-500', advice: 'Aim for
regular exercise and balanced nutrition to reach a healthy range.' };
  return { label: 'Lots of room for growth', color: 'text-rose-400', bg: 'bg-rose-500', advice: 'A supportive
plan with a healthcare provider can make a big difference.' };
}

export function calculateWHR(waistCm, hipCm) {
  if (!waistCm || !hipCm) return null;
  return Math.round((waistCm / hipCm) * 100) / 100;
}

export function getWHRRisk(whr, gender = 'male') {
  if (whr == null) return { label: '—', color: 'text-slate-400', bg: 'bg-slate-500', advice: 'Enter your waist
and hip measurements to calculate your ratio.' };
  const male = gender === 'male';
  const lowLimit = male ? 0.9 : 0.8;
  const highLimit = male ? 1.0 : 0.85;
  if (whr < lowLimit) return { label: 'Low Risk', color: 'text-emerald-400', bg: 'bg-emerald-500', advice: 'Great
balance! Your fat distribution is in the healthy range for your body.' };
  if (whr <= highLimit) return { label: 'Moderate Risk', color: 'text-amber-400', bg: 'bg-amber-500', advice: 'A
balanced routine with regular movement can help improve this ratio over time.' };
  return { label: 'High Risk', color: 'text-rose-400', bg: 'bg-rose-500', advice: 'Focus on consistent daily
movement and nutrition — small changes make a big difference.' };
}

export function getBodyType(bmi, whr, gender = 'male') {
  if (bmi == null) return null;
  const highLimit = gender === 'male' ? 1.0 : 0.85;
  if (bmi < 18.5) return 'ectomorph';
  if (bmi >= 25 || (whr != null && whr > highLimit)) return 'endomorph';
  return 'mesomorph';
}

export function calculateBMR(weightKg, heightCm, age, gender) {
  const base = 10 * weightKg + 6.25 * heightCm - 5 * age;
  return Math.round(gender === 'male' ? base + 5 : base - 161);
}

export function estimateCaloriesFromSteps(steps, weightKg) {
  return Math.round(steps * (weightKg / 70) * 0.04);
}

export function estimateHeartRate(cadence, age, restingHr = 70) {
  const maxHr = 220 - age;
  const intensity = Math.min(cadence / 180, 1);
  return Math.round(restingHr + (maxHr - restingHr) * intensity * 0.7);
}

export function formatDuration(seconds) {
  const h = Math.floor(seconds / 3600);
  const m = Math.floor((seconds % 3600) / 60);
  const s = seconds % 60;
  if (h > 0) return `${h}:${String(m).padStart(2, '0')}:${String(s).padStart(2, '0')}`;
  return `${String(m).padStart(2, '0')}:${String(s).padStart(2, '0')}`;
}

export function getAgeCategory(age) {
  if (!age) return null;
  if (age < 20) return 'Under 20';
  if (age < 30) return '20-30';
  if (age < 40) return '30-40';
```

```
  if (age < 50) return '40-50';
  if (age < 60) return '50-60';
  if (age < 70) return '60-70';
  return '70+';
}
```

src/lib/insightPrompts.js

```
import { calculateBMI, getBMICategory, getAgeCategory } from './healthUtils';

function profileContext(p) {
  const ageCat = getAgeCategory(p.age);
  const bmi = calculateBMI(p.weight_kg, p.height_cm);
  const bmiCat = getBMICategory(bmi);
  let ctx = `USER PROFILE:
- Gender: ${p.gender}
- Age: ${p.age} (${ageCat} age category)
- BMI: ${bmi ? bmi.toFixed(1) : 'Unknown'} (${bmiCat.label})
- Activity level: ${(p.activity_level || 'moderate').replace('_', ' ')}`;
  if (p.health_conditions?.length) {
    ctx += `\n- Health conditions: ${p.health_conditions.join(', ')}`;
  }
  if (p.gender === 'female') {
    ctx += `\n- Cycle phase: ${p.cycle_phase || 'Not specified'}`;
    ctx += `\n- Pregnancy status: ${p.pregnancy_status || 'not_pregnant'}`;
  }
  return ctx;
}

const SCHEMA_NOTE = 'Return a JSON object with "summary" (string overview) and "recommendations" (array of
objects, each with "title", "description", and "benefits" string fields).';

export function buildWorkoutPrompt(p) {
  return `You are a certified personal trainer AI specializing in personalized fitness. Create a tailored workout
plan.

${profileContext(p)}

Generate 4 specific workout recommendations. Consider age-appropriate intensity, joint safety, gender-specific
physiology, and BMI-appropriate exercises.
${p.gender === 'female' && p.pregnancy_status && p.pregnancy_status !== 'not_pregnant' ? 'PREGNANCY-SAFE
exercises only — avoid high-impact, heavy lifting, or supine positions after first trimester.' : ''}
${p.health_conditions?.length ? `Modify exercises to be safe for: ${p.health_conditions.join(', ')}.` : ''}

${SCHEMA_NOTE}`;
}

export function buildStretchPrompt(p) {
  return `You are a mobility and flexibility specialist AI. Create a personalized stretching routine.

${profileContext(p)}

Generate 4 specific stretch recommendations. Focus on age-appropriate flexibility work, areas commonly tight for
this profile, and injury prevention.
${p.health_conditions?.length ? `Modify stretches to be safe for: ${p.health_conditions.join(', ')}.` : ''}

${SCHEMA_NOTE}`;
}

export function buildDietPrompt(p) {
  return `You are a registered dietitian AI. Create a personalized nutrition plan.

${profileContext(p)}

Generate 4 specific meal and nutrition recommendations. Consider caloric needs, macronutrient balance,
age-specific nutritional requirements, and gender-specific considerations (e.g., iron for women, protein for
muscle maintenance).
${p.health_conditions?.includes('Diabetes') ? 'CRITICAL: Provide diabetes-friendly recommendations with
controlled carbohydrates and low glycemic index foods.' : ''}
${p.health_conditions?.includes('Hypertension') ? 'CRITICAL: Low-sodium recommendations for hypertension.' : ''}

${SCHEMA_NOTE}`;
}

export function buildWomensHealthPrompt(p) {
  return `You are a women's health specialist AI. Provide personalized guidance for menstrual cycle and
pregnancy.
```

```
${profileContext(p)}

Focus on:
${p.pregnancy_status && p.pregnancy_status !== 'not_pregnant' ? `- Pregnancy-specific guidance for
${p.pregnancy_status.replace('_', ' ')}: safe activities, nutrition needs, common symptoms, and warning signs to
watch for.` : '- Menstrual cycle health and hormonal wellness.'}
${p.cycle_phase ? `- Cycle phase guidance for ${p.cycle_phase}: exercise modifications, nutrition tips, and
energy management for this phase.` : ''}
- General women's health recommendations for this age and fitness level.

Generate 4 actionable recommendations tailored to her current reproductive health status.

${SCHEMA_NOTE}`;
}

export function buildConditionsPrompt(p) {
  return `You are a clinical health educator AI. Provide personalized guidance for managing health conditions
alongside fitness.

${profileContext(p)}

The user has: ${p.health_conditions.join(', ')}. For each condition, provide:
- Safe exercise guidelines
- Warning signs to watch for during activity
- Lifestyle modifications that help manage the condition
- How their fitness routine can support condition management

Generate 4 specific recommendations.

${SCHEMA_NOTE}`;
}

export function buildWorkoutImagePrompt(p) {
  const ageCat = getAgeCategory(p.age);
  return `A professional fitness photograph of a ${p.gender} in their ${ageCat} age range performing a tailored
exercise. Modern clean gym or home setting, natural lighting, motivational and aspirational atmosphere,
high-quality fitness photography.`;
}

export function buildStretchImagePrompt(p) {
  const ageCat = getAgeCategory(p.age);
  return `A professional photograph of a ${p.gender} in their ${ageCat} age range performing a stretching
exercise on a yoga mat. Clean bright studio setting, calm atmosphere, natural lighting, wellness photography
style.`;
}

export function buildDietImagePrompt(p) {
  return `A beautiful overhead photograph of a healthy, balanced meal plate tailored for a ${p.gender} focused on
fitness nutrition. Fresh colorful ingredients, clean modern plating, natural lighting, professional food
photography.`;
}

export function buildWomensHealthImagePrompt(p) {
  const ageCat = getAgeCategory(p.age);
  return p.pregnancy_status && p.pregnancy_status !== 'not_pregnant'
    ? `A serene photograph of a pregnant woman in her ${ageCat} age range doing gentle prenatal yoga. Soft
natural lighting, calm peaceful atmosphere, wellness photography.`
    : `A serene photograph of a woman in her ${ageCat} age range in a calm wellness setting with soft natural
light, representing women's health and self-care. Professional wellness photography.`;
}

export function buildConditionsImagePrompt(p) {
  return `An informative, clean medical illustration showing lifestyle management for
${p.health_conditions.join(' and ')}. Professional health education visual, clear and encouraging tone, modern
medical illustration style.`;
}
```

src/lib/query-client.js

```
import { QueryClient } from '@tanstack/react-query';


export const queryClientInstance = new QueryClient({
        defaultOptions: {
                queries: {
                        refetchOnWindowFocus: false,
```

```
                    retry: 1,
                },
        },
});
```

src/lib/utils.js

```
import { clsx } from "clsx"
import { twMerge } from "tailwind-merge"

export function cn(...inputs) {
  return twMerge(clsx(inputs))
}


export const isIframe = window.self !== window.top;
```

src/main.jsx

```
import React from 'react'
import ReactDOM from 'react-dom/client'
import App from '@/App.jsx'
import '@/index.css'

ReactDOM.createRoot(document.getElementById('root')).render(
  <App />
)
```

src/pages/ActivityLog.jsx

```
import { useEffect, useState } from 'react';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { ClipboardList, Heart, Flame, Footprints, CalendarDays } from 'lucide-react';
import { format } from 'date-fns';

export default function ActivityLog() {
  const [rows, setRows] = useState([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    base44.entities.ActivitySession
      .aggregate({
        query: {},
        groupBy: 'session_date',
        sum: ['steps', 'calories_burned'],
        avg: ['avg_heart_rate'],
        sort: '-session_date',
        limit: 90,
      })
      .then((res) => setRows(res.rows || []))
      .catch(() => {})
      .finally(() => setLoading(false));
  }, []);

  const formatDay = (dateStr) => {
    try {
      return format(new Date(dateStr + 'T00:00:00'), 'MMM d, yyyy');
    } catch {
      return dateStr;
    }
  };

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  return (
    <div className="space-y-8">
```

```
      <div>
        <h1 className="text-3xl font-bold tracking-tight">Daily Progress Log</h1>
        <p className="text-slate-400 mt-1">Auto-logged activity, grouped by day and category</p>
      </div>

      {rows.length === 0 ? (
        <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-12 text-center">
          <ClipboardList className="w-12 h-12 text-slate-600 mx-auto mb-4" />
          <p className="text-slate-400">No logged data yet. Start a tracking session to see it appear here
automatically.</p>
        </div>
      ) : (
        <div className="space-y-3">
          {rows.map((r, i) => (
            <motion.div
              key={r.session_date}
              initial={{ opacity: 0, y: 10 }}
              animate={{ opacity: 1, y: 0 }}
              transition={{ delay: i * 0.04 }}
              className="bg-slate-900/40 border border-slate-800 rounded-2xl p-5"
            >
              <div className="flex items-center gap-2 mb-4">
                <CalendarDays className="w-4 h-4 text-emerald-400" />
                <h3 className="font-semibold">{formatDay(r.session_date)}</h3>
              </div>
              <div className="grid grid-cols-3 gap-3">
                <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
                  <div className="flex items-center gap-1.5 text-xs text-slate-500 mb-1">
                    <Footprints className="w-3.5 h-3.5 text-emerald-400" />
                    Steps
                  </div>
                  <div className="text-xl font-bold">{(r.sum_steps || 0).toLocaleString()}</div>
                </div>
                <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
                  <div className="flex items-center gap-1.5 text-xs text-slate-500 mb-1">
                    <Flame className="w-3.5 h-3.5 text-orange-400" />
                    Calorie Burn
                  </div>
                  <div className="text-xl font-bold">
                    {(r.sum_calories_burned || 0).toLocaleString()}<span className="text-xs text-slate-500
font-normal"> kcal</span>
                  </div>
                </div>
                <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
                  <div className="flex items-center gap-1.5 text-xs text-slate-500 mb-1">
                    <Heart className="w-3.5 h-3.5 text-rose-400" />
                    Heart Rate
                  </div>
                  <div className="text-xl font-bold">
                    {r.avg_avg_heart_rate ? Math.round(r.avg_avg_heart_rate) : '—'}<span className="text-xs
text-slate-500 font-normal"> bpm</span>
                  </div>
                </div>
              </div>
            </motion.div>
          ))}
        </div>
      )}
    </div>
  );
}
```

src/pages/BMICalculator.jsx

```
import { useEffect, useState } from 'react';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { useToast } from '@/components/ui/use-toast';
import { Scale, Save, Info } from 'lucide-react';
import BMIGauge from '@/components/BMIGauge';
import { calculateBMI, getBMICategory, calculateBMR } from '@/lib/healthUtils';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';

export default function BMICalculator() {
```

```
const { toast } = useToast();
const [loading, setLoading] = useState(true);
const [saving, setSaving] = useState(false);
const [profileId, setProfileId] = useState(null);
const [form, setForm] = useState({
  height_cm: '',
  weight_kg: '',
  age: '',
  gender: 'male',
  resting_hr: '70',
});

useEffect(() => {
  base44.entities.HealthProfile.list('-created_date', 1).then(profiles => {
    if (profiles[0]) {
      const p = profiles[0];
      setProfileId(p.id);
      setForm({
        height_cm: p.height_cm || '',
        weight_kg: p.weight_kg || '',
        age: p.age ? String(p.age) : '',
        gender: p.gender || 'male',
        resting_hr: p.resting_hr ? String(p.resting_hr) : '70',
      });
    }
    setLoading(false);
  }).catch(() => setLoading(false));
}, []);

const bmi = calculateBMI(Number(form.weight_kg), Number(form.height_cm));
const category = getBMICategory(bmi);
const bmr = form.weight_kg && form.height_cm && form.age
  ? calculateBMR(Number(form.weight_kg), Number(form.height_cm), Number(form.age), form.gender)
  : null;

const handleSubmit = async (e) => {
  e.preventDefault();
  setSaving(true);
  try {
    const data = {
      height_cm: Number(form.height_cm),
      weight_kg: Number(form.weight_kg),
      age: Number(form.age),
      gender: form.gender,
      resting_hr: Number(form.resting_hr),
    };
    if (profileId) {
      await base44.entities.HealthProfile.update(profileId, data);
    } else {
      const created = await base44.entities.HealthProfile.create(data);
      setProfileId(created.id);
    }
    toast({ title: 'Profile saved', description: 'Your health profile has been updated.' });
  } catch (err) {
    toast({ title: 'Error', description: 'Could not save profile.', variant: 'destructive' });
  }
  setSaving(false);
};

if (loading) {
  return (
    <div className="flex items-center justify-center h-96">
      <div className="w-8 h-8 border-4 border-slate-800 border-t-sky-500 rounded-full animate-spin" />
    </div>
  );
}

return (
  <div className="space-y-8">
    <div>
      <h1 className="text-3xl font-bold tracking-tight">BMI Calculator</h1>
      <p className="text-slate-400 mt-1">Enter your measurements to calculate your Body Mass Index</p>
    </div>

    <div className="grid lg:grid-cols-2 gap-8">
      <motion.form
        initial={{ opacity: 0, y: 10 }}
        animate={{ opacity: 1, y: 0 }}
```

```
          onSubmit={handleSubmit}
          className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6 space-y-5"
        >
          <div className="grid grid-cols-2 gap-4">
            <div className="space-y-2">
              <Label>Height (cm)</Label>
              <Input type="number" value={form.height_cm} onChange={e => setForm(f => ({ ...f, height_cm:
e.target.value }))} placeholder="175" required />
            </div>
            <div className="space-y-2">
              <Label>Weight (kg)</Label>
              <Input type="number" step="0.1" value={form.weight_kg} onChange={e => setForm(f => ({ ...f,
weight_kg: e.target.value }))} placeholder="70" required />
            </div>
            <div className="space-y-2">
              <Label>Age</Label>
              <Input type="number" value={form.age} onChange={e => setForm(f => ({ ...f, age: e.target.value }))}
placeholder="30" />
            </div>
            <div className="space-y-2">
              <Label>Resting HR (bpm)</Label>
              <Input type="number" value={form.resting_hr} onChange={e => setForm(f => ({ ...f, resting_hr:
e.target.value }))} placeholder="70" />
            </div>
          </div>
          <div className="space-y-2">
            <Label>Gender</Label>
            <Select value={form.gender} onValueChange={v => setForm(f => ({ ...f, gender: v }))}>
              <SelectTrigger>
                <SelectValue />
              </SelectTrigger>
              <SelectContent>
                <SelectItem value="male">Male</SelectItem>
                <SelectItem value="female">Female</SelectItem>
              </SelectContent>
            </Select>
          </div>
          <Button type="submit" disabled={saving} className="w-full bg-sky-500 hover:bg-sky-600 text-white">
            <Save className="w-4 h-4 mr-2" />
            {saving ? 'Saving...' : 'Save Profile'}
          </Button>
        </motion.form>

        <motion.div
          initial={{ opacity: 0, y: 10 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ delay: 0.1 }}
          className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6 flex flex-col items-center"
        >
          <BMIGauge bmi={bmi} category={category} />
          {bmi && (
            <motion.div
              initial={{ opacity: 0 }}
              animate={{ opacity: 1 }}
              transition={{ delay: 0.5 }}
              className="mt-6 w-full space-y-3"
            >
              <div className="flex items-start gap-2 bg-slate-950/50 rounded-xl p-3">
                <Info className="w-4 h-4 text-sky-400 mt-0.5 flex-shrink-0" />
                <p className="text-sm text-slate-300">{category.advice}</p>
              </div>
              {bmr && (
                <div className="flex items-center gap-2 bg-slate-950/50 rounded-xl p-3">
                  <Scale className="w-4 h-4 text-emerald-400 mt-0.5 flex-shrink-0" />
                  <p className="text-sm text-slate-300">Basal Metabolic Rate: <span className="font-semibold
text-white">{bmr} kcal/day</span></p>
                </div>
              )}
            </motion.div>
          )}
        </motion.div>
      </div>

      {/* BMI scale */}
      <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6">
        <h3 className="font-semibold mb-4">BMI Scale</h3>
        <div className="flex h-3 rounded-full overflow-hidden">
          <div className="flex-1 bg-sky-500" />
```

```
          <div className="flex-1 bg-emerald-500" />
          <div className="flex-1 bg-amber-500" />
          <div className="flex-1 bg-rose-500" />
        </div>
        <div className="grid grid-cols-4 text-xs text-slate-400 mt-2">
          <div>Not enough<br /><span className="text-slate-500">&lt; 18.5</span></div>
          <div>Looks decent<br /><span className="text-slate-500">18.5–24.9</span></div>
          <div>Room for growth<br /><span className="text-slate-500">25–29.9</span></div>
                    <div>Lots of room for growth<br /><span className="
        </div>
      </div>
    </div>
  );
}
```

src/pages/BodyType.jsx

```
import { useEffect, useState } from 'react';
import { Link } from 'react-router-dom';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { useToast } from '@/components/ui/use-toast';
import { Ruler, Save, Info, Flame, Activity, Heart, Sparkles } from 'lucide-react';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { calculateBMI, calculateBMR, calculateWHR, getWHRRisk, getBodyType, getBMICategory } from
'@/lib/healthUtils';

const BODY_TYPES = {
  ectomorph: {
    label: 'Ectomorph',
    color: 'text-sky-400',
    bg: 'bg-sky-500/10',
    border: 'border-sky-500/20',
    description: 'A lean, light build with a narrow frame and a fast metabolism. Gaining weight or muscle takes
deliberate effort.',
    strengths: 'Naturally low body fat and a high resting calorie burn.',
    tips: 'Prioritize strength training with progressive overload, eat in a small calorie surplus, and keep
cardio moderate rather than long and intense.',
  },
  mesomorph: {
    label: 'Mesomorph',
    color: 'text-emerald-400',
    bg: 'bg-emerald-500/10',
    border: 'border-emerald-500/20',
    description: 'An athletic, naturally muscular build with balanced proportions. Your body responds quickly to
training.',
    strengths: 'Efficient muscle gain, balanced fat distribution and a steady metabolism.',
    tips: 'Keep a balanced mix of strength and cardio in your weekly routine — you have a strong foundation, so
consistency is everything.',
  },
  endomorph: {
    label: 'Endomorph',
    color: 'text-orange-400',
    bg: 'bg-orange-500/10',
    border: 'border-orange-500/20',
    description: 'A softer, rounder build with a slower metabolism. Your body stores energy efficiently and gains
strength easily.',
    strengths: 'Natural strength and muscularity, plus efficient recovery between workouts.',
    tips: 'Make regular cardio a priority, keep strength training in your routine, and keep portions in check —
small consistent changes win.',
  },
};

export default function BodyType() {
  const { toast } = useToast();
  const [loading, setLoading] = useState(true);
  const [saving, setSaving] = useState(false);
  const [profileId, setProfileId] = useState(null);
  const [profile, setProfile] = useState(null);
  const [form, setForm] = useState({ waist_cm: '', hip_cm: '', gender: 'male' });

  useEffect(() => {
    base44.entities.HealthProfile.list('-created_date', 1).then(profiles => {
      if (profiles[0]) {
```

```
        const p = profiles[0];
        setProfileId(p.id);
        setProfile(p);
        setForm({
          waist_cm: p.waist_cm ? String(p.waist_cm) : '',
          hip_cm: p.hip_cm ? String(p.hip_cm) : '',
          gender: p.gender || 'male',
        });
      }
      setLoading(false);
    }).catch(() => setLoading(false));
  }, []);

  const bmi = profile ? calculateBMI(profile.weight_kg, profile.height_cm) : null;
  const bmiCat = getBMICategory(bmi);
  const bmr = profile?.weight_kg && profile?.height_cm && profile?.age
    ? calculateBMR(profile.weight_kg, profile.height_cm, profile.age, form.gender)
    : null;
  const whr = calculateWHR(Number(form.waist_cm), Number(form.hip_cm));
  const whrRisk = getWHRRisk(whr, form.gender);
  const bodyTypeKey = getBodyType(bmi, whr, form.gender);
  const bt = bodyTypeKey ? BODY_TYPES[bodyTypeKey] : null;

  const bmiHealthy = bmi != null && bmi >= 18.5 && bmi < 25;
  const whrHealthy = whr != null && (form.gender === 'male' ? whr < 0.9 : whr < 0.8);
  let summary;
  if (bmiHealthy && whrHealthy) {
    summary = { cls: 'text-emerald-400', border: 'border-emerald-500/20', bg: 'bg-emerald-500/10', text: "Great
news — your BMI and waist-to-hip ratio are both in the healthy range. Keep up your routine!" };
  } else if (bmiHealthy || whrHealthy) {
    summary = { cls: 'text-amber-400', border: 'border-amber-500/20', bg: 'bg-amber-500/10', text: "You're
partway there — one metric looks healthy while the other has room for growth. Consistent daily activity is the
best place to start." };
  } else {
    summary = { cls: 'text-rose-400', border: 'border-rose-500/20', bg: 'bg-rose-500/10', text: "There's room for
growth here — start with small, sustainable changes to daily movement and nutrition. Every step counts." };
  }

  const handleSubmit = async (e) => {
    e.preventDefault();
    setSaving(true);
    try {
      const data = {
        waist_cm: Number(form.waist_cm),
        hip_cm: Number(form.hip_cm),
        gender: form.gender,
      };
      if (profileId) {
        const updated = await base44.entities.HealthProfile.update(profileId, data);
        setProfile(p => ({ ...p, ...updated }));
      } else {
        const created = await base44.entities.HealthProfile.create(data);
        setProfileId(created.id);
        setProfile(created);
      }
      toast({ title: 'Measurements saved', description: 'Your waist and hip measurements have been updated.' });
    } catch (err) {
      toast({ title: 'Error', description: 'Could not save measurements.', variant: 'destructive' });
    }
    setSaving(false);
  };

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-violet-500 rounded-full animate-spin" />
      </div>
    );
  }

  return (
    <div className="space-y-8">
      <div>
        <h1 className="text-3xl font-bold tracking-tight">Body Type & Ratios</h1>
        <p className="text-slate-400 mt-1">Hip-to-waist ratio and body type, powered by your health metrics</p>
      </div>

      {/* Measurements form */}
```

```
<form
  onSubmit={handleSubmit}
  className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6 space-y-5"
>
  <div className="grid grid-cols-2 gap-4">
    <div className="space-y-2">
      <Label>Waist (cm)</Label>
      <Input
        type="number"
        step="0.1"
        value={form.waist_cm}
        onChange={e => setForm(f => ({ ...f, waist_cm: e.target.value }))}
        placeholder="85"
        required
      />
    </div>
    <div className="space-y-2">
      <Label>Hip (cm)</Label>
      <Input
        type="number"
        step="0.1"
        value={form.hip_cm}
        onChange={e => setForm(f => ({ ...f, hip_cm: e.target.value }))}
        placeholder="95"
        required
      />
    </div>
  </div>
  <div className="space-y-2">
    <Label>Gender</Label>
    <Select value={form.gender} onValueChange={v => setForm(f => ({ ...f, gender: v }))}>
      <SelectTrigger>
        <SelectValue />
      </SelectTrigger>
      <SelectContent>
        <SelectItem value="male">Male</SelectItem>
        <SelectItem value="female">Female</SelectItem>
      </SelectContent>
    </Select>
  </div>
  <Button type="submit" disabled={saving} className="w-full bg-violet-500 hover:bg-violet-600 text-white">
    <Save className="w-4 h-4 mr-2" />
    {saving ? 'Saving...' : 'Save Measurements'}
  </Button>
</form>

{!profile && (
  <div className="bg-amber-500/10 border border-amber-500/20 rounded-2xl p-4 flex items-start gap-3">
    <Info className="w-5 h-5 text-amber-400 flex-shrink-0 mt-0.5" />
    <div>
      <p className="text-sm text-amber-200 font-medium">Add your height & weight first</p>
      <p className="text-xs text-amber-200/60 mt-1">
        Your body type combines your BMI with your waist-to-hip ratio.{' '}
        <Link to="/bmi" className="underline">Set up your BMI profile</Link> to unlock the full picture.
      </p>
    </div>
  </div>
)}

{/* Results */}
{whr != null && (
  <div className="grid md:grid-cols-2 gap-4">
    <motion.div
      initial={{ opacity: 0, y: 10 }}
      animate={{ opacity: 1, y: 0 }}
      className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6"
    >
      <div className="flex items-center gap-2 mb-4">
        <Ruler className="w-5 h-5 text-violet-400" />
        <h3 className="font-semibold">Hip-to-Waist Ratio</h3>
      </div>
      <div className="text-5xl font-bold">{whr}</div>
      <div className={`text-sm font-medium mt-2 ${whrRisk.color}`}>{whrRisk.label}</div>
      <p className="text-sm text-slate-400 mt-3">{whrRisk.advice}</p>
    </motion.div>

    <motion.div
      initial={{ opacity: 0, y: 10 }}
```

```
            animate={{ opacity: 1, y: 0 }}
            transition={{ delay: 0.05 }}
            className={`rounded-2xl p-6 border ${bt.bg} ${bt.border}`}
          >
            <div className="flex items-center gap-2 mb-4">
              <Sparkles className={`w-5 h-5 ${bt.color}`} />
              <h3 className="font-semibold">Your Body Type</h3>
            </div>
            <div className={`text-3xl font-bold ${bt.color}`}>{bt.label}</div>
            <p className="text-sm text-slate-300 mt-3">{bt.description}</p>
            <p className="text-xs text-slate-500 mt-3"><span className="text-slate-300
font-medium">Strengths:</span> {bt.strengths}</p>
            <p className="text-xs text-slate-500 mt-2"><span className="text-slate-300 font-medium">Best
approach:</span> {bt.tips}</p>
          </motion.div>
        </div>
      )}

      {/* App metrics comparison */}
      {bmi != null && (
        <motion.div
          initial={{ opacity: 0, y: 10 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ delay: 0.1 }}
          className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6"
        >
          <div className="flex items-center gap-2 mb-4">
            <Activity className="w-5 h-5 text-slate-400" />
            <h3 className="font-semibold">How Your Metrics Compare</h3>
          </div>
          <div className="grid grid-cols-2 md:grid-cols-4 gap-3">
            <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
              <div className="text-xs text-slate-500 mb-1">BMI</div>
              <div className="text-xl font-bold">{bmi}</div>
              <div className={`text-xs ${bmiCat.color}`}>{bmiCat.label}</div>
            </div>
            <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
              <div className="flex items-center gap-1 text-xs text-slate-500 mb-1">
                <Flame className="w-3 h-3 text-orange-400" /> BMR
              </div>
              <div className="text-xl font-bold">{bmr ? bmr.toLocaleString() : '—'}</div>
              <div className="text-xs text-slate-500">kcal/day</div>
            </div>
            <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
              <div className="flex items-center gap-1 text-xs text-slate-500 mb-1">
                <Heart className="w-3 h-3 text-rose-400" /> Resting HR
              </div>
              <div className="text-xl font-bold">{profile.resting_hr || '—'}</div>
              <div className="text-xs text-slate-500">bpm</div>
            </div>
            <div className="bg-slate-950/50 border border-slate-800 rounded-xl p-3">
              <div className="text-xs text-slate-500 mb-1">Activity Level</div>
              <div className="text-sm font-bold capitalize mt-1">{(profile.activity_level ||
'moderate').replace('_', ' ')}</div>
            </div>
          </div>
        </motion.div>
      )}

      {/* Overall summary */}
      {whr != null && bmi != null && (
        <motion.div
          initial={{ opacity: 0, y: 10 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ delay: 0.15 }}
          className={`rounded-2xl p-5 border ${summary.bg} ${summary.border} flex items-start gap-3`}
        >
          <Sparkles className={`w-5 h-5 flex-shrink-0 mt-0.5 ${summary.cls}`} />
          <p className={`text-sm font-medium ${summary.cls}`}>{summary.text}</p>
        </motion.div>
      )}
    </div>
  );
}
```

src/pages/ForgotPassword.jsx

```
import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@/api/base44Client";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Mail, ArrowLeft, Loader2 } from "lucide-react";
import AuthLayout from "@/components/AuthLayout";

export default function ForgotPassword() {
  const [email, setEmail] = useState("");
  const [loading, setLoading] = useState(false);
  const [sent, setSent] = useState(false);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    try {
      await base44.auth.resetPasswordRequest(email);
    } catch {
      // Always show success regardless
    } finally {
      setLoading(false);
      setSent(true);
    }
  };

  return (
    <AuthLayout
      icon={Mail}
      title="Reset password"
      subtitle="We'll send you a link to reset it"
      footer={
        <Link to="/login" className="text-primary font-medium hover:underline">
          <ArrowLeft className="w-3 h-3 inline mr-1" />Back to log in
        </Link>
      }
    >
      {sent ? (
        <p className="text-sm text-foreground text-center">
          If an account exists with that email, you'll receive a password reset link shortly.
        </p>
      ) : (
        <form onSubmit={handleSubmit} className="space-y-4">
          <div className="space-y-2">
            <Label htmlFor="email">Email address</Label>
            <div className="relative">
              <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
              <Input
                id="email"
                type="email"
                autoComplete="email"
                autoFocus
                placeholder="you@example.com"
                value={email}
                onChange={(e) => setEmail(e.target.value)}
                className="pl-10 h-12"
                required
              />
            </div>
          </div>
          <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
            {loading ? (
              <>
                <Loader2 className="w-4 h-4 mr-2 animate-spin" />
                Sending...
              </>
            ) : (
              "Send reset link"
            )}
          </Button>
        </form>
      )}
    </AuthLayout>
```

```
  );
}
```

src/pages/Home.jsx

```
import { useEffect, useState } from 'react';
import { Link } from 'react-router-dom';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { Footprints, Flame, Heart, Scale, ArrowRight, Activity } from 'lucide-react';
import StatCard from '@/components/StatCard';
import { calculateBMI, getBMICategory, formatDuration } from '@/lib/healthUtils';

export default function Home() {
  const [profile, setProfile] = useState(null);
  const [sessions, setSessions] = useState([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    async function load() {
      try {
        const [profiles, sess] = await Promise.all([
          base44.entities.HealthProfile.list('-created_date', 1),
          base44.entities.ActivitySession.list('-created_date', 10),
        ]);
        setProfile(profiles[0] || null);
        setSessions(sess || []);
      } catch (e) {
        // ignore
      }
      setLoading(false);
    }
    load();
  }, []);

  const todayStr = new Date().toISOString().split('T')[0];
  const todaySessions = sessions.filter(s => s.session_date === todayStr);
  const todaySteps = todaySessions.reduce((sum, s) => sum + (s.steps || 0), 0);
  const todayCalories = todaySessions.reduce((sum, s) => sum + (s.calories_burned || 0), 0);
  const bmi = profile ? calculateBMI(profile.weight_kg, profile.height_cm) : null;
  const bmiCat = getBMICategory(bmi);

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  return (
    <div className="space-y-8">
      <motion.div initial={{ opacity: 0, y: 10 }} animate={{ opacity: 1, y: 0 }}>
        <h1 className="text-3xl font-bold tracking-tight">Welcome back</h1>
        <p className="text-slate-400 mt-1">Here's your health snapshot for today</p>
      </motion.div>

      <div className="grid grid-cols-2 lg:grid-cols-4 gap-4">
        <StatCard icon={Scale} label="Your BMI" value={bmi ? bmi.toFixed(1) : '—'} unit="" accent="sky" delay={0}
/>
        <StatCard icon={Footprints} label="Today's Steps" value={todaySteps.toLocaleString()} unit="steps"
accent="emerald" delay={0.05} />
        <StatCard icon={Flame} label="Calories Today" value={todayCalories} unit="kcal" accent="orange"
delay={0.1} />
        <StatCard icon={Heart} label="Sessions" value={sessions.length} unit="total" accent="rose" delay={0.15}
/>
      </div>

      {/* Quick actions */}
      <div className="grid md:grid-cols-2 gap-4">
        <Link to="/bmi" className="group">
          <div className="bg-gradient-to-br from-sky-500/10 to-sky-600/5 border border-sky-500/20 rounded-2xl p-6
transition-all hover:border-sky-500/40">
            <div className="flex items-center justify-between">
              <div>
                <h3 className="font-semibold text-lg">Calculate BMI</h3>
```

```
              <p className="text-sm text-slate-400 mt-1">Update your measurements and get personalized
insights</p>
            </div>
            <ArrowRight className="w-5 h-5 text-sky-400 group-hover:translate-x-1 transition-transform" />
          </div>
        </div>
      </Link>
      <Link to="/tracker" className="group">
        <div className="bg-gradient-to-br from-emerald-500/10 to-emerald-600/5 border border-emerald-500/20
rounded-2xl p-6 transition-all hover:border-emerald-500/40">
          <div className="flex items-center justify-between">
            <div>
              <h3 className="font-semibold text-lg">Start Tracking</h3>
              <p className="text-sm text-slate-400 mt-1">Real-time steps, heart rate & calorie burn</p>
            </div>
            <ArrowRight className="w-5 h-5 text-emerald-400 group-hover:translate-x-1 transition-transform" />
          </div>
        </div>
      </Link>
    </div>

    {/* Recent sessions */}
    <div>
      <div className="flex items-center gap-2 mb-4">
        <Activity className="w-5 h-5 text-slate-400" />
        <h2 className="text-xl font-semibold">Recent Activity</h2>
      </div>
      {sessions.length === 0 ? (
        <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-8 text-center">
          <Footprints className="w-10 h-10 text-slate-600 mx-auto mb-3" />
          <p className="text-slate-400">No sessions yet. Start tracking to see your progress here.</p>
        </div>
      ) : (
        <div className="space-y-2">
          {sessions.map((s, i) => (
            <motion.div
              key={s.id}
              initial={{ opacity: 0, x: -10 }}
              animate={{ opacity: 1, x: 0 }}
              transition={{ delay: i * 0.05 }}
              className="bg-slate-900/40 border border-slate-800 rounded-xl p-4 flex items-center
justify-between"
            >
              <div className="flex items-center gap-4">
                <div className="w-10 h-10 rounded-xl bg-emerald-500/10 flex items-center justify-center">
                  <Footprints className="w-5 h-5 text-emerald-400" />
                </div>
                <div>
                  <div className="font-medium">{(s.steps || 0).toLocaleString()} steps</div>
                  <div className="text-sm text-slate-500">{s.session_date} · {formatDuration(s.duration_seconds
|| 0)}</div>
                </div>
              </div>
              <div className="text-right">
                <div className="text-orange-400 font-medium text-sm">{s.calories_burned || 0} kcal</div>
                <div className="text-slate-500 text-sm">{s.avg_heart_rate || '—'} bpm</div>
              </div>
            </motion.div>
          ))}
        </div>
      )}
    </div>
  </div>
  );
}
```

src/pages/Insights.jsx

```
import { useEffect, useState } from 'react';
import { Link } from 'react-router-dom';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { Dumbbell, PersonStanding, Apple, Heart, Stethoscope, Sparkles } from 'lucide-react';
import InsightCard from '@/components/InsightCard';
import InsightsSettings from '@/components/InsightsSettings';
import { calculateBMI, getBMICategory, getAgeCategory } from '@/lib/healthUtils';
import {
```

```
  buildWorkoutPrompt, buildStretchPrompt, buildDietPrompt,
  buildWomensHealthPrompt, buildConditionsPrompt,
  buildWorkoutImagePrompt, buildStretchImagePrompt, buildDietImagePrompt,
  buildWomensHealthImagePrompt, buildConditionsImagePrompt,
} from '@/lib/insightPrompts';

export default function Insights() {
  const [profile, setProfile] = useState(null);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    async function load() {
      try {
        const profiles = await base44.entities.HealthProfile.list('-created_date', 1);
        setProfile(profiles[0] || null);
      } catch (e) {
        // ignore
      }
      setLoading(false);
    }
    load();
  }, []);

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  if (!profile) {
    return (
      <div className="space-y-6">
        <div>
          <h1 className="text-3xl font-bold tracking-tight">AI Health Insights</h1>
          <p className="text-slate-400 mt-1">Personalized guidance powered by AI</p>
        </div>
        <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-8 text-center">
          <Sparkles className="w-10 h-10 text-slate-600 mx-auto mb-3" />
          <p className="text-slate-400 mb-4">Set up your health profile first to unlock personalized AI
insights.</p>
          <Link to="/bmi" className="inline-block px-6 py-2.5 rounded-xl bg-emerald-500 text-white font-medium
hover:bg-emerald-400">
            Set Up Profile
          </Link>
        </div>
      </div>
    );
  }

  const ageCat = getAgeCategory(profile.age);
  const bmi = calculateBMI(profile.weight_kg, profile.height_cm);
  const bmiCat = getBMICategory(bmi);
  const isFemale = profile.gender === 'female';
  const hasConditions = profile.health_conditions?.length > 0;

  return (
    <div className="space-y-6">
      <motion.div initial={{ opacity: 0, y: 10 }} animate={{ opacity: 1, y: 0 }}>
        <h1 className="text-3xl font-bold tracking-tight">AI Health Insights</h1>
        <p className="text-slate-400 mt-1">Personalized guidance powered by AI</p>
      </motion.div>

      <div className="flex flex-wrap gap-2">
        {profile.gender && (
          <span className="px-3 py-1.5 rounded-full bg-slate-800/60 border border-slate-700 text-sm
text-slate-300 capitalize">
            {profile.gender}
          </span>
        )}
        {profile.age && (
          <span className="px-3 py-1.5 rounded-full bg-slate-800/60 border border-slate-700 text-sm
text-slate-300">
            Age {profile.age} · {ageCat}
          </span>
        )}
        <span className="px-3 py-1.5 rounded-full bg-slate-800/60 border border-slate-700 text-sm
```

```
text-slate-300">
          BMI {bmi ? bmi.toFixed(1) : '—'} · {bmiCat.label}
        </span>
        {hasConditions && (
          <span className="px-3 py-1.5 rounded-full bg-rose-500/10 border border-rose-500/30 text-sm
text-rose-400">
            {profile.health_conditions.join(', ')}
          </span>
        )}
      </div>

      <InsightsSettings profile={profile} onSave={setProfile} />

      <div className="grid md:grid-cols-2 gap-4">
        <InsightCard
          title="Personalized Workouts"
          icon={Dumbbell}
          accent="emerald"
          delay={0}
          promptBuilder={() => buildWorkoutPrompt(profile)}
          imagePromptBuilder={() => buildWorkoutImagePrompt(profile)}
        />
        <InsightCard
          title="Stretches & Mobility"
          icon={PersonStanding}
          accent="sky"
          delay={0.05}
          promptBuilder={() => buildStretchPrompt(profile)}
          imagePromptBuilder={() => buildStretchImagePrompt(profile)}
        />
        <InsightCard
          title="Diet & Nutrition"
          icon={Apple}
          accent="orange"
          delay={0.1}
          promptBuilder={() => buildDietPrompt(profile)}
          imagePromptBuilder={() => buildDietImagePrompt(profile)}
        />
        {hasConditions && (
          <InsightCard
            title="Health Condition Management"
            icon={Stethoscope}
            accent="rose"
            delay={0.15}
            promptBuilder={() => buildConditionsPrompt(profile)}
            imagePromptBuilder={() => buildConditionsImagePrompt(profile)}
          />
        )}
      </div>

      {isFemale && (
        <InsightCard
          title="Women's Health · Cycle & Pregnancy"
          icon={Heart}
          accent="violet"
          delay={0.2}
          promptBuilder={() => buildWomensHealthPrompt(profile)}
          imagePromptBuilder={() => buildWomensHealthImagePrompt(profile)}
        />
      )}
    </div>
  );
}
```

src/pages/Login.jsx

```
import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@/api/base44Client";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { LogIn, Mail, Lock, Loader2 } from "lucide-react";
import AuthLayout from "@/components/AuthLayout";
import GoogleIcon from "@/components/GoogleIcon";
import { safeReturnTo } from "@/lib/authReturnTo";
```

```
export default function Login() {
  const [email, setEmail] = useState(() => localStorage.getItem("vp_remember_email") || "");
  const [password, setPassword] = useState("");
  const [remember, setRemember] = useState(() => localStorage.getItem("vp_remember_email") !== "");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);
  // Post-login destination (e.g. the MCP OAuth consent page sends users here
  // with returnTo so the grant flow can resume). Same-origin paths only.
  const returnTo = safeReturnTo();

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    setLoading(true);
    try {
      if (remember) {
        localStorage.setItem("vp_remember_email", email);
      } else {
        localStorage.removeItem("vp_remember_email");
      }
      await base44.auth.loginViaEmailPassword(email, password);
      window.location.href = returnTo;
    } catch (err) {
      setError(err.message || "Invalid email or password");
    } finally {
      setLoading(false);
    }
  };

  const handleGoogle = () => {
    base44.auth.loginWithProvider("google", returnTo);
  };

  return (
    <AuthLayout
      icon={LogIn}
      title="Welcome back"
      subtitle="Log in to your account"
      footer={
        <>
          Don't have an account?{" "}
          <Link
            to={"/register" + (returnTo !== "/" ? "?returnTo=" + encodeURIComponent(returnTo) : "")}
            className="text-primary font-medium hover:underline"
          >
            Create one
          </Link>
        </>
      }
    >
      <Button
        variant="outline"
        className="w-full h-12 text-sm font-medium mb-6"
        onClick={handleGoogle}
      >
        <GoogleIcon className="w-5 h-5 mr-2" />
        Continue with Google
      </Button>

      <div className="relative mb-6">
        <div className="absolute inset-0 flex items-center">
          <div className="w-full border-t border-border" />
        </div>
        <div className="relative flex justify-center text-xs uppercase">
          <span className="bg-card px-3 text-muted-foreground">or</span>
        </div>
      </div>

      {error && (
        <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
          {error}
        </div>
      )}

      <form onSubmit={handleSubmit} className="space-y-4">
        <div className="space-y-2">
          <Label htmlFor="email">Email</Label>
          <div className="relative">
```

```
            <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="email"
              type="email"
              autoComplete="email"
              autoFocus
              placeholder="you@example.com"
              value={email}
              onChange={(e) => setEmail(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <div className="space-y-2">
          <div className="flex items-center justify-between">
            <Label htmlFor="password">Password</Label>
            <Link to="/forgot-password" className="text-xs text-primary hover:underline">
              Forgot password?
            </Link>
          </div>
          <div className="relative">
            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="password"
              type="password"
              autoComplete="current-password"
              placeholder="••••••••"
              value={password}
              onChange={(e) => setPassword(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <div className="flex items-center gap-2">
          <input
            id="remember"
            type="checkbox"
            checked={remember}
            onChange={(e) => setRemember(e.target.checked)}
            className="w-4 h-4 rounded border-slate-300 text-primary focus:ring-primary"
          />
          <Label htmlFor="remember" className="text-sm text-muted-foreground cursor-pointer">
            Remember my email
          </Label>
        </div>
        <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
          {loading ? (
            <>
              <Loader2 className="w-4 h-4 mr-2 animate-spin" />
              Logging in...
            </>
          ) : (
            "Log in"
          )}
        </Button>
      </form>
    </AuthLayout>
  );
}
```

src/pages/OAuthConsent.jsx

```
import React, { useEffect, useState } from "react";
import { appParams } from "@/lib/app-params";
import { Button } from "@/components/ui/button";
import { ShieldCheck, Loader2 } from "lucide-react";
import AuthLayout from "@/components/AuthLayout";

// App-side OAuth consent page for the app's MCP server. The platform redirects
// AI clients here (see base44/mcp/config.json `consent_path`) with an opaque
// `ctx` handle — the authorization request itself lives on the server. This page
// gates on the app-user session, fetches the display info for that handle, shows
// the categories of access being granted, and posts the approve/deny decision.
```

```
// Do not change the fetch calls, headers, or the `ctx` handle handling — styling
// and copy are safe to edit.
export default function OAuthConsent() {
  const ctx = new URLSearchParams(window.location.search).get("ctx");
  const [info, setInfo] = useState(null);
  const [checking, setChecking] = useState(true);
  const [submitting, setSubmitting] = useState(false);
  const [decided, setDecided] = useState("");
  const [error, setError] = useState("");
  const [reconnect, setReconnect] = useState("");

  useEffect(() => {
    (async () => {
      let redirecting = false;
      try {
        if (!ctx) {
          setError("This authorization link is invalid or has expired.");
          return;
        }
        // Resolve the handle first: a dead handle must never render
        // approve/deny, and the response carries the app's configured login
        // route for the signed-out redirect below. Send the session (cookie +
        // bearer token) so the server can list the granted tools for a
        // signed-in user — the same auth the approve/deny call sends; without
        // it the display request is anonymous and shows no tools.
        const infoHeaders = {};
        if (appParams.token) infoHeaders.Authorization = "Bearer " + appParams.token;
        const res = await fetch(
          `/api/apps/${appParams.appId}/mcp/consent-info?handle=${encodeURIComponent(ctx)}`,
          { credentials: "include", headers: infoHeaders },
        );
        if (!res.ok) {
          setError("This authorization link is invalid or has expired.");
          return;
        }
        const data = await res.json();
        // Gate on the server's auth result, NOT base44.auth.isAuthenticated():
        // the SDK check runs the bearer path, so a cookie-only session (platform
        // login/SSO, or a private app with a stale localStorage token) would read
        // as signed-out and redirect — even though /consent-info just
        // authenticated this same request via its cookie fallback. data.authenticated
        // keeps the redirect decision in agreement with what the server returned.
        if (!data.authenticated) {
          // The short handle rides back in returnTo; login_path is
          // owner-configured and validated server-side as a same-origin path.
          // Send from_url too: a custom-auth app coerced to platform auth (e.g.
          // public_without_login under workspace SSO) serves the platform login,
          // which honors from_url rather than returnTo. Rebuild the query from
          // `ctx` alone — never forward window.location.search raw: the platform
          // resume returns from_url verbatim, so crafted extras on the consent
          // link (app_base_url, access_token, …) would ride through the login
          // round-trip and app-params.js would persist them into the freshly
          // authenticated session.
          const returnTo =
            window.location.pathname + "?ctx=" + encodeURIComponent(ctx);
          const encoded = encodeURIComponent(returnTo);
          redirecting = true; // keep the spinner while the browser navigates
          window.location.href =
            (data.login_path || "/login") + "?returnTo=" + encoded + "&from_url=" + encoded;
          return;
        }
        setInfo(data);
      } catch (e) {
        setError("Could not load this authorization request. Please try again.");
      } finally {
        if (!redirecting) setChecking(false);
      }
    })();
  }, [ctx]);

  const respond = async (action) => {
    setSubmitting(true);
    setError("");
    try {
      const headers = { "Content-Type": "application/json" };
      // Cookie-backed sessions carry no token; sending "Bearer null" would
      // shadow the valid cookie, so add the header only when a token exists.
      if (appParams.token) headers.Authorization = "Bearer " + appParams.token;
```

```
      const res = await fetch(`/api/apps/${appParams.appId}/mcp/authorize-grant`, {
        method: "POST",
        credentials: "include",
        headers,
        body: JSON.stringify({ ctx, action }),
      });
      if (!res.ok) {
        // 401 = the session expired before the (single-use, still-unconsumed)
        // handle was spent; retrying the same controls re-sends the dead session
        // forever. Send the user back through login preserving `ctx` — the same
        // redirect the initial signed-out path uses — so they can return and
        // approve the still-valid handle.
        if (res.status === 401) {
          const returnTo = window.location.pathname + "?ctx=" + encodeURIComponent(ctx);
          const encoded = encodeURIComponent(returnTo);
          window.location.href =
            ((info && info.login_path) || "/login") + "?returnTo=" + encoded + "&from_url=" + encoded;
          return;
        }
        // These all come AFTER the single-use handle is atomically consumed
        // (409 tool set changed; 403 host/resource/app mismatch; 404 access
        // gone; 400 malformed/handle already used), so retrying can only 404.
        // Show a terminal reconnect state, not an impossible "try again".
        if ([400, 403, 404, 409].includes(res.status)) {
          let detail = "";
          try { detail = (await res.json()).detail; } catch (_) { /* keep default */ }
          setReconnect(detail || "This authorization can no longer be completed. Reconnect from your AI client to
try again.");
          setSubmitting(false);
          return;
        }
        throw new Error("Could not complete authorization. Please try again.");
      }
      const data = await res.json();
      window.location.href = data.redirect_url;
      if (!/^https?:/i.test(data.redirect_url)) {
        // Custom-scheme redirect (native AI clients, e.g. cursor://): browsers
        // may block or not visibly navigate, so show a terminal state instead
        // of an eternal spinner.
        setDecided(action);
        setSubmitting(false);
      }
    } catch (e) {
      setError(e.message);
      setSubmitting(false);
    }
  };

  if (checking) {
    return (
      <AuthLayout icon={ShieldCheck} title="Authorize access">
        <div className="flex items-center justify-center py-6 text-muted-foreground">
          <Loader2 className="w-5 h-5 mr-2 animate-spin" aria-hidden="true" />
          Loading…
        </div>
      </AuthLayout>
    );
  }

  const client = (info && info.client_name) || "An AI client";
  const appName = (info && info.app_name) || "this app";

  if (decided) {
    return (
      <AuthLayout
        icon={ShieldCheck}
        title={decided === "approve" ? "Access granted" : "Access denied"}
        subtitle={`You can return to ${client} and close this window.`}
      />
    );
  }

  // Terminal: the authorization request is no longer valid (tool set changed +
  // handle consumed). Retrying can't succeed, so show reconnect guidance with
  // no approve/deny controls.
  if (reconnect) {
    return (
      <AuthLayout icon={ShieldCheck} title="Reconnect required">
```

```
        <div className="p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
          {reconnect}
        </div>
      </AuthLayout>
    );
  }

  // No consent details means nothing trustworthy to approve: a failed
  // consent-info load (expired handle, rate limit, transient error) renders
  // the error alone, never the approve/deny controls.
  if (error && !info) {
    return (
      <AuthLayout icon={ShieldCheck} title="Authorize access">
        <div className="p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
          {error}
        </div>
      </AuthLayout>
    );
  }

  const tools = Array.isArray(info.tools) ? info.tools : [];

  return (
    <AuthLayout
      icon={ShieldCheck}
      title="Authorize access"
      subtitle={`${client} wants to access ${appName} on your behalf`}
    >
      {error && (
        <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
          {error}
        </div>
      )}

      <p className="text-sm font-medium text-foreground mb-2">
        {tools.length ? `It will be able to use these tools in ${appName}:` : "No tools requested"}
      </p>
      {tools.length > 0 && (
        <ul className="space-y-2 text-sm mb-6">
          {tools.map((tool) => (
            <li key={tool.name} className="flex flex-col">
              <span className="text-foreground font-medium">
                {tool.title || tool.name}
              </span>
              {tool.description && (
                <span className="text-muted-foreground">{tool.description}</span>
              )}
            </li>
          ))}
        </ul>
      )}

      <div className="flex gap-3">
        <Button
          variant="outline"
          className="flex-1 h-12 font-medium"
          disabled={submitting}
          onClick={() => respond("deny")}
        >
          Deny
        </Button>
        <Button
          className="flex-1 h-12 font-medium"
          disabled={submitting}
          onClick={() => respond("approve")}
        >
          {submitting ? <Loader2 className="w-4 h-4 mr-2 animate-spin" /> : null}
          Approve
        </Button>
      </div>
    </AuthLayout>
  );
}
```

src/pages/Paywall.jsx

```
import { useState } from 'react';
import { useNavigate } from 'react-router-dom';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { useAuth } from '@/lib/AuthContext';
import { Button } from '@/components/ui/button';
import { Lock, Check, Loader2, Heart, Activity, Calculator, TrendingUp } from 'lucide-react';

 / /  &™þ    C h a n g e   t h i s   t o   t h e   a d m i n i s t r a t o r ' s   r e g i s t e r e d   e m a i l   t o
const ADMIN_EMAIL = 'admin@vitalpulse.app';

const features = [
  { icon: Activity, text: 'Real-time step & motion tracking' },
  { icon: Calculator, text: 'BMI & BMR calculator with insights' },
  { icon: Heart, text: 'Heart rate & calorie burn estimation' },
  { icon: TrendingUp, text: '14-day progress analytics & charts' },
];

export default function Paywall() {
  const { user } = useAuth();
  const navigate = useNavigate();
  const [loading, setLoading] = useState(false);
  const [error, setError] = useState('');

  const handlePay = async () => {
    setError('');
    setLoading(true);
    try {
      // Record the payment (simulated — wire to a real provider like Square/Polar with Builder+)
      await base44.entities.Payment.create({
        amount: 0.99,
        status: 'completed',
        payment_method: 'simulated',
        user_email: user?.email || '',
      });

      // Notify the administrator by email
      try {
        await base44.integrations.Core.SendEmail({
          to: ADMIN_EMAIL,
          subject: 'New VitalPulse Payment Received',
          body: `A new payment of $0.99 was received.\n\nUser: ${user?.email || 'Unknown'}\nDate: ${new
Date().toLocaleString()}\n\nAccess has been granted.`,
        });
      } catch (e) {
        // Email failure shouldn't block access
      }

      navigate('/');
    } catch (err) {
      setError(err.message || 'Payment failed. Please try again.');
    } finally {
      setLoading(false);
    }
  };

  return (
    <div className="dark min-h-screen bg-slate-950 text-white flex items-center justify-center p-4">
      <motion.div
        initial={{ opacity: 0, y: 20 }}
        animate={{ opacity: 1, y: 0 }}
        className="w-full max-w-md"
      >
        <div className="bg-slate-900/60 border border-slate-800 rounded-3xl p-8 backdrop-blur-sm">
          {/* Header */}
          <div className="text-center mb-8">
            <div className="w-16 h-16 rounded-2xl bg-gradient-to-br from-emerald-400 to-teal-600 flex
items-center justify-center shadow-lg shadow-emerald-500/20 mx-auto mb-4">
              <Heart className="w-8 h-8 text-white" />
            </div>
            <h1 className="text-2xl font-bold tracking-tight">Unlock VitalPulse</h1>
            <p className="text-slate-400 mt-2 text-sm">
              Get full access to all health tracking features
            </p>
          </div>
```

```
          {/* Price */}
          <div className="text-center mb-8">
            <div className="flex items-center justify-center gap-1">
              <span className="text-5xl font-bold">$0.99</span>
              <span className="text-slate-500 text-lg ml-1">one-time</span>
            </div>
            <p className="text-xs text-slate-500 mt-2">Pay once, access forever</p>
          </div>

          {/* Features */}
          <div className="space-y-3 mb-8">
            {features.map((f, i) => (
              <motion.div
                key={i}
                initial={{ opacity: 0, x: -10 }}
                animate={{ opacity: 1, x: 0 }}
                transition={{ delay: i * 0.08 }}
                className="flex items-center gap-3"
              >
                <div className="w-8 h-8 rounded-lg bg-emerald-500/10 flex items-center justify-center
flex-shrink-0">
                  <f.icon className="w-4 h-4 text-emerald-400" />
                </div>
                <span className="text-sm text-slate-300">{f.text}</span>
                <Check className="w-4 h-4 text-emerald-400 ml-auto" />
              </motion.div>
            ))}
          </div>

          {error && (
            <div className="mb-4 p-3 rounded-lg bg-rose-500/10 text-rose-400 text-sm text-center">
              {error}
            </div>
          )}

          <Button
            onClick={handlePay}
            disabled={loading}
            className="w-full h-12 bg-gradient-to-r from-emerald-500 to-teal-600 hover:from-emerald-400
hover:to-teal-500 text-white font-medium border-0"
          >
            {loading ? (
              <>
                <Loader2 className="w-4 h-4 mr-2 animate-spin" />
                Processing payment...
              </>
            ) : (
              <>
                <Lock className="w-4 h-4 mr-2" />
                Pay $0.99 & Unlock
              </>
            )}
          </Button>

          <p className="text-xs text-slate-600 text-center mt-4">
            Secured payment · Instant access
          </p>
        </div>
      </motion.div>
    </div>
  );
}
```

src/pages/Progress.jsx

```
import { useEffect, useState, useMemo } from 'react';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { LineChart, Line, BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer, CartesianGrid } from
'recharts';
import { Footprints, Flame, Heart, TrendingUp } from 'lucide-react';
import StatCard from '@/components/StatCard';

export default function Progress() {
  const [sessions, setSessions] = useState([]);
  const [loading, setLoading] = useState(true);
```

```
  useEffect(() => {
    base44.entities.ActivitySession.list('-session_date', 50)
      .then(s => setSessions(s || []))
      .catch(() => {})
      .finally(() => setLoading(false));
  }, []);

  const chartData = useMemo(() => {
    const byDate = {};
    sessions.forEach(s => {
      const date = s.session_date;
      if (!byDate[date]) {
        byDate[date] = { date, steps: 0, calories: 0, hr: 0, count: 0 };
      }
      byDate[date].steps += s.steps || 0;
      byDate[date].calories += s.calories_burned || 0;
      byDate[date].hr += s.avg_heart_rate || 0;
      byDate[date].count += 1;
    });
    return Object.values(byDate)
      .map(d => ({
        date: d.date.slice(5),
        steps: d.steps,
        calories: d.calories,
        avgHR: d.count > 0 ? Math.round(d.hr / d.count) : 0,
      }))
      .sort((a, b) => a.date.localeCompare(b.date))
      .slice(-14);
  }, [sessions]);

  const totalSteps = sessions.reduce((s, x) => s + (x.steps || 0), 0);
  const totalCalories = sessions.reduce((s, x) => s + (x.calories_burned || 0), 0);
  const avgHR = sessions.length > 0
    ? Math.round(sessions.reduce((s, x) => s + (x.avg_heart_rate || 0), 0) / sessions.length)
    : 0;
  const avgSteps = sessions.length > 0 ? Math.round(totalSteps / sessions.length) : 0;

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  if (sessions.length === 0) {
    return (
      <div className="space-y-8">
        <div>
          <h1 className="text-3xl font-bold tracking-tight">Progress</h1>
          <p className="text-slate-400 mt-1">Track your activity trends over time</p>
        </div>
        <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-12 text-center">
          <TrendingUp className="w-12 h-12 text-slate-600 mx-auto mb-4" />
          <p className="text-slate-400">No activity data yet. Start a tracking session to see your progress
charts.</p>
        </div>
      </div>
    );
  }

  const tooltipStyle = { background: 'rgb(15 23 42)', border: '1px solid rgb(30 41 59)', borderRadius: '8px',
color: '#fff' };

  return (
    <div className="space-y-8">
      <div>
        <h1 className="text-3xl font-bold tracking-tight">Progress</h1>
        <p className="text-slate-400 mt-1">Your activity trends over the last 14 days</p>
      </div>

      <div className="grid grid-cols-2 lg:grid-cols-4 gap-4">
        <StatCard icon={Footprints} label="Total Steps" value={totalSteps.toLocaleString()} unit=""
accent="emerald" delay={0} />
        <StatCard icon={Flame} label="Total Calories" value={totalCalories.toLocaleString()} unit="kcal"
accent="orange" delay={0.05} />
        <StatCard icon={Heart} label="Avg Heart Rate" value={avgHR} unit="bpm" accent="rose" delay={0.1} />
```

```
        <StatCard icon={TrendingUp} label="Avg Steps/Session" value={avgSteps.toLocaleString()} unit=""
accent="sky" delay={0.15} />
      </div>

      <motion.div
        initial={{ opacity: 0, y: 10 }}
        animate={{ opacity: 1, y: 0 }}
        className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6"
      >
        <h3 className="font-semibold mb-4">Daily Steps</h3>
        <ResponsiveContainer width="100%" height={250}>
          <LineChart data={chartData}>
            <CartesianGrid strokeDasharray="3 3" stroke="rgb(30 41 59)" />
            <XAxis dataKey="date" stroke="rgb(100 116 139)" fontSize={12} />
            <YAxis stroke="rgb(100 116 139)" fontSize={12} />
            <Tooltip contentStyle={tooltipStyle} />
            <Line type="monotone" dataKey="steps" stroke="#10b981" strokeWidth={2} dot={{ fill: '#10b981', r: 4
}} />
          </LineChart>
        </ResponsiveContainer>
      </motion.div>

      <motion.div
        initial={{ opacity: 0, y: 10 }}
        animate={{ opacity: 1, y: 0 }}
        transition={{ delay: 0.1 }}
        className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6"
      >
        <h3 className="font-semibold mb-4">Daily Calories Burned</h3>
        <ResponsiveContainer width="100%" height={250}>
          <BarChart data={chartData}>
            <CartesianGrid strokeDasharray="3 3" stroke="rgb(30 41 59)" />
            <XAxis dataKey="date" stroke="rgb(100 116 139)" fontSize={12} />
            <YAxis stroke="rgb(100 116 139)" fontSize={12} />
            <Tooltip contentStyle={tooltipStyle} />
            <Bar dataKey="calories" fill="#f97316" radius={[8, 8, 0, 0]} />
          </BarChart>
        </ResponsiveContainer>
      </motion.div>

      <motion.div
        initial={{ opacity: 0, y: 10 }}
        animate={{ opacity: 1, y: 0 }}
        transition={{ delay: 0.2 }}
        className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6"
      >
        <h3 className="font-semibold mb-4">Average Heart Rate</h3>
        <ResponsiveContainer width="100%" height={250}>
          <LineChart data={chartData}>
            <CartesianGrid strokeDasharray="3 3" stroke="rgb(30 41 59)" />
            <XAxis dataKey="date" stroke="rgb(100 116 139)" fontSize={12} />
            <YAxis stroke="rgb(100 116 139)" fontSize={12} />
            <Tooltip contentStyle={tooltipStyle} />
            <Line type="monotone" dataKey="avgHR" stroke="#f43f5e" strokeWidth={2} dot={{ fill: '#f43f5e', r: 4
}} />
          </LineChart>
        </ResponsiveContainer>
      </motion.div>
    </div>
  );
}
```

src/pages/Register.jsx

```
import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@/api/base44Client";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { UserPlus, Mail, Lock, Loader2 } from "lucide-react";
import { InputOTP, InputOTPGroup, InputOTPSlot } from "@/components/ui/input-otp";
import AuthLayout from "@/components/AuthLayout";
import GoogleIcon from "@/components/GoogleIcon";
import { toast } from "@/components/ui/use-toast";
import { safeReturnTo } from "@/lib/authReturnTo";
```

```
export default function Register() {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [confirmPassword, setConfirmPassword] = useState("");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);
  const [showOtp, setShowOtp] = useState(false);
  const [otpCode, setOtpCode] = useState("");

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    if (password !== confirmPassword) {
      setError("Passwords do not match");
      return;
    }
    setLoading(true);
    try {
      await base44.auth.register({ email, password });
      setShowOtp(true);
    } catch (err) {
      setError(err.message || "Registration failed");
    } finally {
      setLoading(false);
    }
  };

  const handleVerify = async () => {
    setError("");
    setLoading(true);
    try {
      const result = await base44.auth.verifyOtp({ email, otpCode });
      if (result?.access_token) {
        base44.auth.setToken(result.access_token);
      }
      window.location.href = safeReturnTo();
    } catch (err) {
      setError(err.message || "Invalid verification code");
    } finally {
      setLoading(false);
    }
  };

  const handleResend = async () => {
    setError("");
    try {
      await base44.auth.resendOtp(email);
      toast({
        title: "Code sent",
        description: "Check your email for the new code.",
      });
    } catch (err) {
      setError(err.message || "Failed to resend code");
    }
  };

  const handleGoogle = () => {
    base44.auth.loginWithProvider("google", safeReturnTo());
  };

  if (showOtp) {
    return (
      <AuthLayout
        icon={Mail}
        title="Verify your email"
        subtitle={`We sent a code to ${email}`}
      >
        {error && (
          <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
            {error}
          </div>
        )}
        <div className="flex justify-center mb-6">
          <InputOTP
            maxLength={6}
            value={otpCode}
            onChange={setOtpCode}
            autoFocus
```

```
          autoComplete="one-time-code"
        >
          <InputOTPGroup>
            <InputOTPSlot index={0} />
            <InputOTPSlot index={1} />
            <InputOTPSlot index={2} />
            <InputOTPSlot index={3} />
            <InputOTPSlot index={4} />
            <InputOTPSlot index={5} />
          </InputOTPGroup>
        </InputOTP>
      </div>
      <Button
        className="w-full h-12 font-medium"
        onClick={handleVerify}
        disabled={loading || otpCode.length < 6}
      >
        {loading ? (
          <>
            <Loader2 className="w-4 h-4 mr-2 animate-spin" />
            Verifying...
          </>
        ) : (
          "Verify"
        )}
      </Button>
      <p className="text-center text-sm text-muted-foreground mt-4">
        Didn't receive the code?{" "}
        <button onClick={handleResend} className="text-primary font-medium hover:underline">
          Resend
        </button>
      </p>
    </AuthLayout>
  );
}

return (
  <AuthLayout
    icon={UserPlus}
    title="Create your account"
    subtitle="Sign up to get started"
    footer={
      <>
        Already have an account?{" "}
        <Link
          to={"/login" + (safeReturnTo() !== "/" ? "?returnTo=" + encodeURIComponent(safeReturnTo()) : "")}
          className="text-primary font-medium hover:underline"
        >
          Log in
        </Link>
      </>
    }
  >
    <Button
      variant="outline"
      className="w-full h-12 text-sm font-medium mb-6"
      onClick={handleGoogle}
    >
      <GoogleIcon className="w-5 h-5 mr-2" />
      Continue with Google
    </Button>

    <div className="relative mb-6">
      <div className="absolute inset-0 flex items-center">
        <div className="w-full border-t border-border" />
      </div>
      <div className="relative flex justify-center text-xs uppercase">
        <span className="bg-card px-3 text-muted-foreground">or</span>
      </div>
    </div>

    {error && (
      <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
        {error}
      </div>
    )}

    <form onSubmit={handleSubmit} className="space-y-4">
```

```
        <div className="space-y-2">
          <Label htmlFor="email">Email</Label>
          <div className="relative">
            <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="email"
              type="email"
              autoComplete="email"
              autoFocus
              placeholder="you@example.com"
              value={email}
              onChange={(e) => setEmail(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <div className="space-y-2">
          <Label htmlFor="password">Password</Label>
          <div className="relative">
            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="password"
              type="password"
              autoComplete="new-password"
              placeholder="••••••••"
              value={password}
              onChange={(e) => setPassword(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <div className="space-y-2">
          <Label htmlFor="confirm">Confirm Password</Label>
          <div className="relative">
            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="confirm"
              type="password"
              autoComplete="new-password"
              placeholder="••••••••"
              value={confirmPassword}
              onChange={(e) => setConfirmPassword(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
          {loading ? (
            <>
              <Loader2 className="w-4 h-4 mr-2 animate-spin" />
              Creating account...
            </>
          ) : (
            "Create account"
          )}
        </Button>
      </form>
    </AuthLayout>
  );
}
```

src/pages/ResetPassword.jsx

```
import React, { useState } from "react";
import { Link, useSearchParams } from "react-router-dom";
import { base44 } from "@/api/base44Client";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Lock, Loader2, AlertTriangle } from "lucide-react";
```

```
import AuthLayout from "@/components/AuthLayout";

export default function ResetPassword() {
  const [searchParams] = useSearchParams();
  const resetToken = searchParams.get("token");

  const [newPassword, setNewPassword] = useState("");
  const [confirmPassword, setConfirmPassword] = useState("");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    if (newPassword !== confirmPassword) {
      setError("Passwords do not match");
      return;
    }
    setLoading(true);
    try {
      await base44.auth.resetPassword({ resetToken, newPassword });
      window.location.href = "/login";
    } catch (err) {
      setError(err.message || "Failed to reset password");
    } finally {
      setLoading(false);
    }
  };

  if (!resetToken) {
    return (
      <AuthLayout
        icon={AlertTriangle}
        title="Invalid reset link"
        subtitle="This password reset link is missing or invalid"
        footer={
          <Link to="/forgot-password" className="text-primary font-medium hover:underline">
            Request a new link
          </Link>
        }
      >
        <p className="text-sm text-foreground text-center">
          The link you used appears to be incomplete. Please request a new password reset email.
        </p>
      </AuthLayout>
    );
  }

  return (
    <AuthLayout
      icon={Lock}
      title="New password"
      subtitle="Enter your new password below"
    >
      {error && (
        <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
          {error}
        </div>
      )}
      <form onSubmit={handleSubmit} className="space-y-4">
        <div className="space-y-2">
          <Label htmlFor="password">New Password</Label>
          <div className="relative">
            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="password"
              type="password"
              autoComplete="new-password"
              autoFocus
              placeholder="••••••••"
              value={newPassword}
              onChange={(e) => setNewPassword(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
```

```
        <div className="space-y-2">
          <Label htmlFor="confirm">Confirm Password</Label>
          <div className="relative">
            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="confirm"
              type="password"
              autoComplete="new-password"
              placeholder="••••••••"
              value={confirmPassword}
              onChange={(e) => setConfirmPassword(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
          {loading ? (
            <>
              <Loader2 className="w-4 h-4 mr-2 animate-spin" />
              Resetting...
            </>
          ) : (
            "Reset password"
          )}
        </Button>
      </form>
    </AuthLayout>
  );
}
```

src/pages/StepTracker.jsx

```
import { useEffect, useState } from 'react';
import { motion } from 'framer-motion';
import { base44 } from '@/api/base44Client';
import { useToast } from '@/components/ui/use-toast';
import { usePedometer } from '@/hooks/usePedometer';
import { Footprints, Play, Square, RotateCcw, Flame, Heart, Clock, Watch, Smartphone, Zap } from 'lucide-react';
import { Button } from '@/components/ui/button';
import { formatDuration, calculateBMI } from '@/lib/healthUtils';

export default function StepTracker() {
  const { toast } = useToast();
  const [profile, setProfile] = useState(null);
  const [loading, setLoading] = useState(true);
  const [deviceType, setDeviceType] = useState('phone');

  useEffect(() => {
    base44.entities.HealthProfile.list('-created_date', 1).then(profiles => {
      setProfile(profiles[0] || null);
      setLoading(false);
    }).catch(() => setLoading(false));
  }, []);

  const weightKg = profile?.weight_kg || 70;
  const age = profile?.age || 30;
  const restingHr = profile?.resting_hr || 70;

  const { steps, isActive, elapsed, cadence, currentHR, currentCalories, start, stop, reset } =
    usePedometer({ weightKg, age, restingHr });

  const bmi = profile ? calculateBMI(profile.weight_kg, profile.height_cm) : null;

  const handleStart = async () => {
    const ok = await start();
    if (!ok) {
      toast({ title: 'Permission needed', description: 'Motion access is required to track steps.', variant:
'destructive' });
    }
  };

  const handleStop = async () => {
    stop();
    if (steps > 0) {
```

```
      try {
        await base44.entities.ActivitySession.create({
          steps,
          duration_seconds: elapsed,
          calories_burned: currentCalories,
          avg_heart_rate: currentHR,
          max_heart_rate: currentHR,
          bmi_at_time: bmi,
          session_date: new Date().toISOString().split('T')[0],
          device_type: deviceType,
        });
        toast({ title: 'Session saved!', description: `${steps.toLocaleString()} steps · ${currentCalories} kcal`
});
      } catch (err) {
        toast({ title: 'Error', description: 'Could not save session.', variant: 'destructive' });
      }
    }
  };

  if (loading) {
    return (
      <div className="flex items-center justify-center h-96">
        <div className="w-8 h-8 border-4 border-slate-800 border-t-emerald-500 rounded-full animate-spin" />
      </div>
    );
  }

  return (
    <div className="space-y-8">
      <div>
        <h1 className="text-3xl font-bold tracking-tight">Step Tracker</h1>
        <p className="text-slate-400 mt-1">Real-time motion tracking using your device sensors</p>
      </div>

      {/* Device selector */}
      <div className="flex gap-2">
        <button
          onClick={() => setDeviceType('phone')}
          className={`flex items-center gap-2 px-4 py-2 rounded-xl text-sm font-medium transition-all ${
            deviceType === 'phone' ? 'bg-emerald-500/15 text-emerald-400 border border-emerald-500/30' :
'bg-slate-900/40 text-slate-400 border border-slate-800'
          }`}
        >
          <Smartphone className="w-4 h-4" /> Phone
        </button>
        <button
          onClick={() => setDeviceType('watch')}
          className={`flex items-center gap-2 px-4 py-2 rounded-xl text-sm font-medium transition-all ${
            deviceType === 'watch' ? 'bg-emerald-500/15 text-emerald-400 border border-emerald-500/30' :
'bg-slate-900/40 text-slate-400 border border-slate-800'
          }`}
        >
          <Watch className="w-4 h-4" /> Wrist Watch
        </button>
      </div>

      {/* Main tracker card */}
      <motion.div
        initial={{ opacity: 0, y: 10 }}
        animate={{ opacity: 1, y: 0 }}
        className="bg-gradient-to-br from-slate-900/60 to-slate-950/60 border border-slate-800 rounded-3xl p-8"
      >
        {/* Step counter */}
        <div className="text-center mb-8">
          <motion.div
            key={steps}
            initial={{ scale: 1.2, opacity: 0.5 }}
            animate={{ scale: 1, opacity: 1 }}
            transition={{ duration: 0.2 }}
            className="text-7xl font-bold tracking-tight"
          >
            {steps.toLocaleString()}
          </motion.div>
          <div className="text-slate-400 mt-2 flex items-center justify-center gap-2">
            <Footprints className="w-4 h-4" />
            steps
          </div>
        </div>
```

```
        {/* Metrics grid */}
        <div className="grid grid-cols-3 gap-4 mb-8">
          <div className="text-center">
            <div className="flex items-center justify-center mb-2">
              <div className={`w-10 h-10 rounded-xl flex items-center justify-center ${isActive ?
'bg-rose-500/15' : 'bg-slate-800/50'}`}>
                <Heart className={`w-5 h-5 ${isActive ? 'text-rose-400 animate-pulse' : 'text-slate-500'}`} />
              </div>
            </div>
            <div className="text-2xl font-bold">{currentHR}</div>
            <div className="text-xs text-slate-500">bpm</div>
          </div>
          <div className="text-center">
            <div className="flex items-center justify-center mb-2">
              <div className={`w-10 h-10 rounded-xl flex items-center justify-center ${isActive ?
'bg-orange-500/15' : 'bg-slate-800/50'}`}>
                <Flame className={`w-5 h-5 ${isActive ? 'text-orange-400' : 'text-slate-500'}`} />
              </div>
            </div>
            <div className="text-2xl font-bold">{currentCalories}</div>
            <div className="text-xs text-slate-500">kcal</div>
          </div>
          <div className="text-center">
            <div className="flex items-center justify-center mb-2">
              <div className="w-10 h-10 rounded-xl flex items-center justify-center bg-slate-800/50">
                <Clock className="w-5 h-5 text-slate-400" />
              </div>
            </div>
            <div className="text-2xl font-bold font-mono">{formatDuration(elapsed)}</div>
            <div className="text-xs text-slate-500">time</div>
          </div>
        </div>

        {/* Cadence bar */}
        {isActive && (
          <motion.div
            initial={{ opacity: 0, height: 0 }}
            animate={{ opacity: 1, height: 'auto' }}
            className="mb-6 overflow-hidden"
          >
            <div className="flex items-center justify-between text-sm text-slate-400 mb-2">
              <span>Cadence</span>
              <span className="font-mono">{cadence} steps/min</span>
            </div>
            <div className="h-2 bg-slate-800 rounded-full overflow-hidden">
              <motion.div
                className="h-full bg-gradient-to-r from-emerald-500 to-teal-400 rounded-full"
                animate={{ width: `${Math.min(cadence / 180 * 100, 100)}%` }}
                transition={{ duration: 0.5 }}
              />
            </div>
          </motion.div>
        )}

        {/* Controls */}
        <div className="flex justify-center gap-3">
          {!isActive ? (
            <Button onClick={handleStart} size="lg" className="bg-emerald-500 hover:bg-emerald-600 text-white
rounded-full px-8">
              <Play className="w-5 h-5 mr-2" />
              {elapsed > 0 ? 'Resume' : 'Start'}
            </Button>
          ) : (
            <Button onClick={handleStop} size="lg" className="bg-rose-500 hover:bg-rose-600 text-white
rounded-full px-8">
              <Square className="w-5 h-5 mr-2" />
              Stop & Save
            </Button>
          )}
          {steps > 0 && !isActive && (
            <Button onClick={reset} variant="outline" size="lg" className="rounded-full px-6">
              <RotateCcw className="w-5 h-5 mr-2" />
              Reset
            </Button>
          )}
        </div>
      </motion.div>
```

```
      {/* Profile warning */}
      {!profile && (
        <div className="bg-amber-500/10 border border-amber-500/20 rounded-2xl p-4 flex items-start gap-3">
          <Zap className="w-5 h-5 text-amber-400 flex-shrink-0 mt-0.5" />
          <div>
            <p className="text-sm text-amber-200 font-medium">Set up your profile first</p>
            <p className="text-xs text-amber-200/60 mt-1">Visit the BMI Calculator to enter your weight, age, and
resting heart rate for accurate calorie and heart rate estimates.</p>
          </div>
        </div>
      )}

      {/* Tips */}
      <div className="bg-slate-900/40 border border-slate-800 rounded-2xl p-6">
        <h3 className="font-semibold mb-3 flex items-center gap-2">
          {deviceType === 'phone' ? <Smartphone className="w-4 h-4 text-emerald-400" /> : <Watch className="w-4
h-4 text-emerald-400" />}
          How to use with your {deviceType === 'phone' ? 'phone' : 'wrist watch'}
        </h3>
        <ul className="space-y-2 text-sm text-slate-400">
          {deviceType === 'phone' ? (
            <>
              <li>• Hold your phone or place it in your pocket while walking or running</li>
              <li>• Keep the screen on for best sensor accuracy</li>
              <li>• Grant motion sensor access when prompted (required on iOS)</li>
            </>
          ) : (
            <>
              <li>• Wear your wrist watch snugly on your non-dominant wrist</li>
              <li>• Ensure motion & fitness permissions are enabled for your browser</li>
              <li>• On Apple Watch, enable "Wrist Detection" in Settings</li>
            </>
          )}
          <li>• Steps are detected via accelerometer peak detection in real-time</li>
          <li>• Heart rate is estimated from your step cadence and personal profile</li>
        </ul>
      </div>
    </div>
  );
}
```

src/utils/index.ts

```
export function createPageUrl(pageName: string) {
    return '/' + pageName.replace(/ /g, '-');
}
```