Workflow reliability

Cosie n8n work sample | Verified local sandbox executions

Purpose

Demonstrate how a small workflow behaves when webhooks are repeated, input is invalid, or an HTTP dependency fails. This is an AI-assisted original project with synthetic data, not a customer case study.

Tested flow

Local webhook > JavaScript validation / duplicate checks > native HTTP Request retries > mock receipt verification. Engine: n8n 2.41.3. Five saved executions, four successes and one expected error.

Test	Observed result	HTTP attempts
Normal input	One synthetic receipt	1
Transient HTTP 503	Success after native retry	2
Invalid-only input	Zero approved mock records	1
Duplicate delivery	Original receipt reused	1
Persistent HTTP 503	Expected error; no receipt	3

What the evidence supports

The retry behavior was executed by the actual n8n HTTP Request node, and per-execution attempt counts were reconciled with the mock endpoint call log. Duplicate handling reused a mock receipt; it does not establish restart-safe or production-wide idempotency.

Limits

All HTTP activity stayed on the local test machine. No real CRM, live customer data, external messages, payment processing, production webhook security, uptime or client results were tested. The workflow was inactive after testing.

A suitable first assignment

After an agreed scope: reproduce one workflow failure in authorized staging, implement one bounded fix, demonstrate agreed synthetic tests, and deliver a redacted export with rollback and operations notes.

Justice Linderman | justice.linderman@gmail.com