

Scaling Hidden Markov Language Models

April 30, 2021

Language Modeling

‘OpenAI’s new language generator GPT-3 is shockingly good—and completely mindless’

Will Douglas Heaven (MIT Tech Review)

Able to achieve strong performance in modern NLP tasks with

- ▶ Large, opaque models
- ▶ Pretrained via language modeling on large data
- ▶ Fine-tuned for downstream task

Language modeling either has useful information for or is a necessary component of downstream tasks

Language Modeling

How now, brown _____

- ▶ Given the words seen so far, predict the next word
- ▶ Requires encoding long-range context

Language Models

Modern language models are primarily

- ▶ Transformers
 - ▶ Encode context into a continuous vector with stacks of attention-based neural networks
- ▶ Recurrent neural networks
 - ▶ Encode context into a continuous vector with stacks of nonlinear dynamical systems

Both are difficult to interpret due to model complexity

Hidden Markov Language Models

- ▶ Interpretability as a design decision
- ▶ Context is encoded as a single integer
- ▶ Interpretable, but thought to be poor language models¹

¹Byus, Bisk, and Choi, 'Bridging HMMs and RNNs through Architectural Transformations'.

Research Question

To what extent is the performance of HMMs limited by scale and choices in parameterization?

This work: Scale HMMs on language modeling using techniques drawn from recent advances in neural networks

Background: Hidden Markov Models

Hidden Markov Models (HMMs)

- ▶ Classical models for unsupervised per-word tag induction
 - ▶ Part-of-speech induction²
 - ▶ Word alignment for translation³
- ▶ Admits tractable exact inference
 - ▶ Strong conditional independence assumptions
 - ▶ Simple transition dynamics
 - ▶ Finite set of discrete latent states

²Merialdo, 'Tagging English Text with a Probabilistic Model'.


³Vogel, Ney, and Tillmann, 'HMM-Based Word Alignment in Statistical Translation'.

HMM State Sizes

Year	Data	Model	States
1989	Phoneme Segmentation	HMM	7
1994	POS	HMM	76
2005	Activity Monitoring	DMC HMM	1k
2006	2D Image Tracking	Convolutional HMM	100k
2009	LM	Split-POS HMM	450
2016	POS	Neural HMM	37
2016	Web Traffic Analysis	FFT HMM	81
2019	Char LM	Cloned HMM	30k

Hidden Markov Models (HMMs)

For times t , model states $z_t \in [Z]$, and tokens $x_t \in [X]$,



This yields the joint distribution

$$p(x, z) = \prod_t p(x_t | z_t) p(z_t | z_{t-1})$$

with

start state	$p(z_1),$
transitions	$p(z_t z_{t-1}),$
and emissions	$p(x_t z_t)$

represented as vectors and matrices

Inference

Given observed $x = (x_1, \dots, x_T)$ We wish to maximize

$$p(x) = \sum_{z_1} \cdots \sum_{z_T} p(x, z) = \alpha_1^\top \Lambda_2 \Lambda_3 \cdots \Lambda_T \mathbf{1},$$

where we have the

start, $[\alpha_1]_{z_1} = p(x_1 \mid z_1)p(z_1)$,
and transition operators, $[\Lambda_t]_{z_{t-1}, z_t} = p(x_t \mid z_t)p(z_t \mid z_{t-1})$


- ▶ Matrix representation of forward algorithm:

$$\alpha_t = \alpha_{t-1} \Lambda_t$$

- ▶ Requires $O(TZ^2)$ operations in total!

Inference

$$p(x) = \alpha_1^\top \Lambda_2 \cdots \Lambda_T \mathbf{1}$$



- ▶ Each node corresponds to a state
- ▶ Each edge to an entry in the transition operator matrix

Scaling HMMs

Lessons from Large Neural Language Models

Large models perform better but are . . .

1. Slow to train
2. Prone to overfitting

We must overcome these issues when scaling HMMs

3 Techniques for Training Large HMMs

- ▶ Compact neural parameterization

↑ Generalization

- ▶ State dropout

↑ Speed ↑ Generalization

- ▶ Block-sparse emission constraints

↑ Speed

- ▶ Will cover a fourth in the second part of this talk

Technique 1: Neural Parameterization

- ▶ Transition and emission matrices have Z^2 and ZX entries
- ▶ More states lead to explosion in parameter count
- ▶ Solution: Low dimensional factorization

Neural Parameterization: Softmax Parameterization

The transition matrix A is factorized as follows:

$$\boxed{A} \propto \exp \left(\boxed{U} \times \boxed{V^T} \right)$$

with state embeddings $U, V \in \mathbb{R}^{Z \times D}$

- ▶ Can further parameterize U or $V = \text{MLP}(E_u)$
- ▶ Similar for emissions

Technique 2: State Dropout

- ▶ Dropout is a common technique for regularizing neural networks⁴
 - ▶ Reduces a network's reliance on any particular neuron by via random masking
- ▶ Extend dropout to the states of an HMM
 - ▶ Encourage broad utilization of all states

⁴Srivastava et al., 'Dropout: A Simple Way to Prevent Neural Networks from Overfitting'.

State Dropout


- ▶ At each batch, sample dropout mask $\mathbf{b} \in \{0, 1\}^Z$
- ▶ Compute distributional parameters by indexing into embeddings U, V

$$\left(\mathbf{b} \circ \begin{array}{|c|} \hline U_{\text{trans}} \\ \hline \end{array} \right) \times \left(\mathbf{b} \circ \begin{array}{|c|} \hline V_{\text{trans}} \\ \hline \end{array} \right)^{\top} \quad \left(\mathbf{b} \circ \begin{array}{|c|} \hline U_{\text{emit}} \\ \hline \end{array} \right) \times \begin{array}{|c|} \hline V_{\text{emit}}^{\top} \\ \hline \end{array}$$

(a) Unnormalized transition logits

(b) Unnormalized emission logits

State Dropout: Inference



- ▶ Shaded nodes depict dropped states
- ▶ Ignore dropped states during inference

Technique 3: Block-Sparse Emission Constraints

- ▶ Reduce cost of marginalization by enforcing structure
- ▶ Introduce emission constraints inspired by Cloned HMMs⁵
- ▶ Only allow each word to be emit by a subset of states
- ▶ Cost of inference is quadratic in the size of the largest subset due to sparsity

⁵Dedieu et al., *Learning higher-order sequential structure with cloned HMMs*.


Block-Sparse Emission Constraints: Alignment

Start with a joint partitioning of both states and words

Indices $m \in [M]$

State partitions \mathcal{Z}_m


Word partitions \mathcal{X}_m



Block-Sparse Emission Constraints


Given the unnormalized emission logits,

- ▶ Mask out unaligned state-word entries
- ▶ Normalize rows across words in aligned partition




Block-Sparse Emissions: Inference

Given each word x_t , only the states in the correct group can occur



(a) Block-sparse emission



(b) With state dropout

Method Recap

- ▶ Compact neural parameterization

↑ Generalization

- ▶ State dropout

↑ Speed ↑ Generalization

- ▶ Block-sparse emission constraints

↑ Speed

- ▶ A fourth after experiments


Experiments

Experiments


- ▶ Language modeling on Penn Treebank
- ▶ Evaluate perplexity
 - ▶ Function of $p(x)$
 - ▶ Lower is better
- ▶ Baselines
 - ▶ Feedforward 5-gram model
 - ▶ 2-layer LSTM
 - ▶ A 900 state HMM⁶
- ▶ Model
 - ▶ 2^{15} (32k) state sparse emission HMM (SE-HMM)
 - ▶ $M = 128$ groups (256 states per group), obtained via Brown Clustering
 - ▶ Dropout rate of 0.5 during training

⁶Buys, Bisk, and Choi, 'Bridging HMMs and RNNs through Architectural Transformations'.

Results on PTB Validation Data



State Size Ablation



Validation perplexity on PTB by state size ($\lambda = 0.5$ and $M = 128$)

Other Ablations

Model	Param	Train	Val
SE-HMM (2^{14})	7.2M	115	134
- neural param	423M	119	169
- state dropout	7.2M	88	157

Discussion

- ▶ Greatly scaled the state size of HMMs
- ▶ Performance improved with increasing state size
- ▶ Still a large gap between RNNs and HMMs
- ▶ Does the emission sparsity constraint improve computation complexity at the price of accuracy?

Speeding up HMMs with Low-Rank Factorizations

A work in progress

Fast Inference with Low-Rank Factorizations

- ▶ The previous approach relied a pre-specified emission sparsity constraint
- ▶ Can we scale inference with a weaker constraint?
- ▶ Exploit structure in the transition matrix to speed up inference

Inference

Start by unpacking inference to reveal the most expensive step

$$p(x) = \alpha_1^\top \Lambda_2 \Lambda_3 \cdots \Lambda_T \mathbf{1}$$

with

$$\begin{aligned} \text{start,} \quad & [\alpha_1]_{z_1} = p(x_1 \mid z_1)p(z_1), \\ \text{and transition operators,} \quad & [\Lambda_t]_{z_{t-1}, z_t} = p(x_t \mid z_t)p(z_t \mid z_{t-1}) \end{aligned}$$

Inference

Decompose transition operators into transition matrix A and emission matrix O

$$\begin{aligned} p(x) &= \alpha_1^\top \Lambda_2 \cdot \Lambda_T \mathbf{1} \\ &= \alpha_1^\top (A \operatorname{diag}([O]_{\cdot, x_2})) \cdots \Lambda_T \mathbf{1} \\ &= \alpha_1^\top A \operatorname{diag}([O]_{\cdot, x_2}) \cdots A \operatorname{diag}([O]_{\cdot, x_T}) \mathbf{1} \end{aligned}$$

where the most expensive steps are the matrix-vector products $\alpha_t^\top A$, which take $O(Z^2)$ computation

Fast Matrix-Vector Products

- ▶ Goal is to reduce the naive matvec complexity of $O(Z^2)$
- ▶ Various methods
 - ▶ Sparsity (nnz entries)
 - ▶ Fast Fourier Transform ($Z \log Z$)
 - ▶ Low-Rank factorization (ZR)
- ▶ We utilize low-rank factorizations
- ▶ Connected to work in efficient attention and kernel approximations⁷

⁷Choromanski et al., *Rethinking Attention with Performers*; Peng et al., *Random Feature Attention*; Blanc and Rendle, *Adaptive Sampled Softmax with Kernel Based Sampling*.

Low-Rank Factorization

Factor transitions $A \in [0, 1]^{Z \times Z}$ into product of $U, V \in \mathbb{R}^{Z \times R}$

$$\boxed{\alpha^\top} \times \boxed{A} = \left(\boxed{\alpha^\top} \times \boxed{U} \right) \times \boxed{V^\top}$$

resulting in two matrix-vector products of cost $O(ZR)$ each

- ▶ Constraint: Entries of A must be nonnegative
- ▶ Solution: Use a nonnegative matrix factorization (NMF)

$$A = \phi(U)\phi(V)^\top,$$

with $\phi : \mathbb{R}^{Z \times R} \rightarrow \mathbb{R}_+^{Z \times R}$

Method Recap


- ▶ Target key $O(Z^2)$ matvec step in inference
- ▶ Use NMF to reduce cost to $O(ZR)$
- ▶ How small can R be relative to Z without sacrificing accuracy?

Experiments


Experiments

- ▶ Language modeling on PTB
- ▶ Feature map $\phi(U) = \exp(UW)$, with learned $W \in \mathbb{R}^{R \times R}$
- ▶ Baseline: Softmax HMM


Scaling on PTB (Validation)



Further Scaling on PTB with Dropout (Validation)



Speed Comparison⁸



⁸ 2^{14} (16k) state SE-HMM takes 506 s/epoch on the same data

Discussion

- ▶ Reduced computation complexity of inference by 4x with NMF vs softmax HMM
- ▶ Scaling factor not as large as SE-HMM
- ▶ Validation PPL worse than SE-HMM

Conclusion

- ▶ Demonstrated improvements in perplexity with larger state spaces
- ▶ Extended techniques from neural networks to HMMs

Future Work

- ▶ Explore the performance of more complex interpretable models
 - ▶ Probabilistic context-free grammars
 - ▶ Switching linear dynamical systems⁹
 - ▶ Latent vector grammars¹⁰
- ▶ Explore other structure for fast matrix-vector products and tensor generalizations
 - ▶ FFT-inspired algorithms¹¹
- ▶ Learn sparsity constraints in SE-HMM
- ▶ Apply sparsity constraints to embedded HMMs¹² for use in approximate inference

⁹Foerster et al., 'Intelligible Language Modeling with Input Switched Affine Networks'.








¹⁰Zhao, Zhang, and Tu, 'Gaussian Mixture Latent Vector Grammars'.

¹¹Dao et al., 'Kaleidoscope: An Efficient, Learnable Representation For All Structured Linear Maps'.

¹²Neal, Beal, and Roweis, 'Inferring State Sequences for Non-Linear Systems with Embedded Hidden Markov Models'.

EOS

Citations

-  Blanc, Guy and Steffen Rendle. *Adaptive Sampled Softmax with Kernel Based Sampling*. 2018. arXiv: 1712.00527 [cs.LG].
-  Buys, Jan, Yonatan Bisk, and Yejin Choi. 'Bridging HMMs and RNNs through Architectural Transformations'. In: 2018.
-  Choromanski, Krzysztof et al. *Rethinking Attention with Performers*. 2021. arXiv: 2009.14794 [cs.LG].
-  Dao, Tri et al. 'Kaleidoscope: An Efficient, Learnable Representation For All Structured Linear Maps'. In: *International Conference on Learning Representations*. 2020. URL: <https://openreview.net/forum?id=BkgrBgSYDS>.
-  Dedieu, Antoine et al. *Learning higher-order sequential structure with cloned HMMs*. 2019. arXiv: 1905.00507 [stat.ML].
-  Foerster, Jakob N. et al. 'Intelligible Language Modeling with Input Switched Affine Networks'. In: *CoRR* abs/1611.09434 (2016). arXiv: 1611.09434. URL: <http://arxiv.org/abs/1611.09434>.
-  Merialdo, Bernard. 'Tagging English Text with a Probabilistic Model'. In: *Computational Linguistics* 20.2 (1994), pp. 155–171.

Generalized Softmax

- Softmax

$$p(z_t \mid z_{t-1}) = \frac{\exp(\mathbf{u}_{z_{t-1}}^\top \mathbf{v}_{z_t})}{\sum_z \exp(\mathbf{u}_{z_{t-1}}^\top \mathbf{v}_z)}$$

- Generalized Softmax

$$p(z_t \mid z_{t-1}) = \frac{K(\mathbf{u}, \mathbf{v})}{\sum_z K(\mathbf{u}, \mathbf{v}_z)} = \frac{\phi(\mathbf{u})^\top \phi(\mathbf{v})}{\sum_z \phi(\mathbf{u})^\top \phi(\mathbf{v}_z)},$$

for positive kernel $K : \mathbb{R}^D \times \mathbb{R}^D \rightarrow \mathbb{R}_+$ and feature map $\phi : \mathbb{R}^D \rightarrow \mathbb{R}^R$

Generalized Softmax: Inference

- ▶ The key $O(Z^2)$ step in the forward algorithm:

$$p(z_t \mid x_{<t}) = \sum_{z_{t-1}} p(z_t \mid z_{t-1}) p(z_{t-1} \mid x_{<t})$$

- ▶ In matrix form,

$$\gamma_t = \underbrace{\alpha_{t-1}}_{\mathbb{R}^Z} \underbrace{\Lambda}_{\mathbb{R}^{Z \times Z}},$$

where we have the probability of the

current state,	$[\gamma_t]_{z_t} = p(z_t \mid x_{<t}),$
last state,	$[\alpha_{t-1}]_{z_{t-1}} = p(z_{t-1} \mid x_{<t}),$
transition probability,	$[\Lambda]_{z_{t-1}, z_t} = p(z_t \mid z_{t-1})$

Generalized Softmax: Inference

- Use generalized softmax in transition distribution

$$[\Lambda]_{z_{t-1}, z_t} = p(z_t \mid z_{t-1}) \propto \phi(\mathbf{u}_{z_{t-1}})^\top \phi(\mathbf{v}_{z_t})$$

- Allows us to apply associative property of matrix multiplication

$$\begin{aligned}\gamma_t &= \alpha_{t-1} \Lambda \\ &= \alpha_{t-1} (\text{diag}(d) \phi(U) \phi(V)^\top) \\ &= \underbrace{(\alpha_{t-1} \circ d)}_{\mathbb{R}^Z} \underbrace{\phi(U)}_{\mathbb{R}^{Z \times f}} \underbrace{\phi(V)^\top}_{\mathbb{R}^{f \times Z}},\end{aligned}$$

with stacked embeddings $\phi(U), \phi(V) = [\phi(\mathbf{v}_1), \dots, \phi(\mathbf{v}_Z)]$
and normalizing constants d

- Takes $O(Zf)$ time from left to right!