

# Johns Hopkins Engineering

## **User Experience**

Module 3



JOHNS HOPKINS

WHITING SCHOOL  
*of* ENGINEERING

---

## Introduction

The material in this video is subject to the copyright of the owners of the material and is being provided for educational purposes under rules of fair use for registered students in this course only. No additional copies of the copyrighted work may be made or distributed.

# Module 2 Recap

- UIViewControllers
- Storyboards and Segues
- Autolayout
- Size Classes

# Module 3 Topics

- Threading on iOS
- Asynchronous Multithreading
- Gestures
- Instruments

# Reminders

- Homework 1 is due at the end of this module
- Development Log 2 assignment is now available



JOHNS HOPKINS

WHITING SCHOOL  
*of* ENGINEERING

---

## Discussion

The material in this video is subject to the copyright of the owners of the material and is being provided for educational purposes under rules of fair use for registered students in this course only. No additional copies of the copyrighted work may be made or distributed.

# This week's discussion topic

- How does Grand Central Dispatch (GCD) differ from other threading mechanisms?
- What other tools have you used for profiling?
  - Compare/contrast with Instruments.



JOHNS HOPKINS

WHITING SCHOOL  
*of* ENGINEERING

---

## Threading on iOS

The material in this video is subject to the copyright of the owners of the material and is being provided for educational purposes under rules of fair use for registered students in this course only. No additional copies of the copyrighted work may be made or distributed.



# Threading on iOS

- Your app runs on one or more threads
  - The first of which is started by the OS
  - Your app may spawn off other threads to execute specific tasks
- Threads are exposed at various levels:
  - NSThread
  - POSIX Threads

# The cost of a thread

- Threads are helpful, but keep in mind their cost:
  - Memory Space
    - Kernel Space (~1KB)
    - Program's Memory Space (~1-2MB)
  - Creation Time (~90 microseconds)
    - Processor Load
    - Speed of Computer
    - Available Memory

# Creating an NSThread

- detachNewThreadSelector:toTarget:withObject (class method)
  - Selector: the thread's entry point
  - Target: the object that defines the method
  - Object: any data you wish to pass into the thread
- Create a new NSThread instance
  - Same parameters as above
  - Don't forget to start the thread!

# Creating POSIX Threads

- macOS and iOS both support C-based POSIX Threads
- Allows for cross platform support
- Keep in mind that NSThread is the main interface for making threads in Cocoa and Cocoa Touch apps, you can use POSIX threads if they are more convenient

# Performing a Selector on a Thread

- If you wish to dispatch the execution of a method to a thread, there is built in support, courtesy of a method in NSObject:
  - `performSelector(onMainThread:with:waitUntilDone:)`  
performs the selector on the main thread
  - `perform(_:on:with:waitUntilDone:)`  
performs the selector on the specified thread (`_`)
  - `performSelector(inBackground:with:)`  
performs the selector on a new background thread

# Terminating a Thread

- While you should try to let your thread run to completion, sometimes you can't – for instance, when a user cancels an operation
- Be sure to design your thread to handle a cancel or exit message
- If you do have to cancel, be sure to clean up and exit gracefully!



JOHNS HOPKINS

WHITING SCHOOL  
*of* ENGINEERING