

Johns Hopkins Engineering

Location Services and Frameworks

Module 4




JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

CoreLocation Framework

The material in this video is subject to the copyright of the owners of the material and is being provided for educational purposes under rules of fair use for registered students in this course only. No additional copies of the copyrighted work may be made or distributed.

Location Scale



CLLocationManager

- CLLocationManager is the main class for getting location information from your device:
 - Tracking location changes with a configurable level of accuracy
 - Reporting a heading from the compass
 - Monitoring if the device enters or exits a region
 - Calculating range to nearby beacons
- CLLocationManager needs a delegate object (of type CLLocationManagerDelegate)
- Remember to ask for user permission and check for availability before asking for location data!

CLLocation

- Represents the location data generated by a CLLocationManager
- Geographic Coordinates and Altitude
- Also provides accuracy of measurements and time stamps
- In iOS, provides speed and heading
- Not usually created by user

Common Type Aliases

- CLLocationDegrees – a double, used to represent a longitudinal or latitudinal value, in degrees
- CLLocationDistance – a double, used to represent a distance (in meters) from a given location
- CLFloor – the logical floor of the building in which the user is located
- CLLocationAccuracy – a double, representing the accuracy of a coordinate value, in meters.

CLVisit

- Used to store information about places the user has been
- Created by the CLLocationManager, delivered to the delegate
- Includes location, and information about arrival and departure times
- Not created directly

Geofencing: Using CLCircularRegion

- CLCircularRegion is defined by a center coordinate and a radius
- CLCircularRegion's contains method can be directly queried to see if a particular coordinate is within the region
- CLLocationManager listens for region entrances and exits – it gets notified of such events via delegate methods, such as locationManager(_, didEnterRegion)

CLBeacon and CLBeaconRegion

- Core Location can only provide accuracy to a certain level before various types of interference (e.g. building structures and the materials they are made of) result in bad results
- iOS supports the iBeacon protocol, which allows the device to sense bluetooth signals from small BTLE (Bluetooth Low Energy) devices. This signal can be used to calculate a range to the beacon, based on the power of the signal
- Beacons can be used as the center of a region (CLBeaconRegion), allowing for geofencing around the beacon.
- If an app knows where the various beacons are located in a known space, it can use the signals from the beacons to determine where the device is within that space, allowing for “indoor mapping”
- Estimote (www.estimote.com) is one of the leading manufacturers of beacons and has a very mature set of hardware and software

CLHeading

- Contains the computed values for the device's azimuth (orientation) relative to true or magnetic north
- Also includes the raw, 3 dimensional vector used to calculate the heading
- Instances of this are received from the delegate through the `CLLocationManager` **once** `startUpdatingHeading()` is called

CLGeocoder

- Provides services to convert between a coordinate (longitude/latitude) and a user-friendly representation (street, city, state, country, landmark, or point of interest)
- Reverse-geocoding converts coordinate to user-friendly
- Forward-geocoding converts user-friendly to coordinate
- The results for both are returned via CLPlacemark

CLPlacemark

- Contains a user-friendly description of a geographic coordinate containing
 - Name of the place
 - Address
 - Other relevant information (Points of interest, geographically related data)
- Reverse-geocoding gives you a CLPlacemark for that location
- You can also create an instance yourself and populate information yourself

Asking for Permission

- Just like with CoreMotion, don't forget to ask for permission to access user location data!
 - In Info.plist, set the Privacy - Location Usage Description key, and provide a value stating why you need to use the user's location
 - In the CLLocationManager, invoke the `requestWhenInUseAuthorization()`



JOHNS HOPKINS

WHITING SCHOOL
of ENGINEERING