

# New Customer Setup Runbook — SecureOps Master Template

**Goal:** stand up a brand-new customer on their own copy of the system — same features, zero WCSG data — and wire every integration back up, step by step.

**The model (why this works):** one shared mobile app serves every customer. Each customer gets their **own full backend** — their own copy of the code, their own database, their own domain, their own branding. Customers never share a server or a database. The phone app finds the right backend using a short **org code** (like `wcsg` or `rgp`) that this master project’s directory resolves.

**This project is the master.** It plays three roles at once:

- 1. The golden template you fork for each new customer
- 2. WCSG’s own live backend
- 3. The **org directory** (the phone app asks it “where does code `acme` live?”) and the **only** project that pushes phone-app updates

Keep it healthy and don’t fork *from* a customer copy — always fork from here.

## What copies on a fork — and what doesn’t

|                                                           | Copies automatically                                                 | You must redo it                                                                                            |
|-----------------------------------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| All code & features                                       | <input checked="" type="checkbox"/>                                  |                                                                                                             |
| Committed settings ( <code>.replit</code> env blocks)     | <input checked="" type="checkbox"/> (some must be changed — Phase 2) |                                                                                                             |
| <b>Secrets</b> (passwords, API keys)                      |                                                                      | <input type="checkbox"/> re-enter (Phase 3)                                                                 |
| <b>Replit integrations/connectors</b> (Twilio, Gemini AI) |                                                                      | <input type="checkbox"/> reconnect (Phase 3)                                                                |
| <b>File storage bucket</b> (uploaded documents, logos)    |                                                                      | <input type="checkbox"/> create fresh (Phase 3)                                                             |
| <b>Production database</b>                                |                                                                      | <input type="checkbox"/> <i>created fresh &amp; empty on first publish — real WCSG data never transfers</i> |
| Custom domain, deployment                                 |                                                                      | <input type="checkbox"/> set up new (Phases 4 & 6)                                                          |

**About “no real data”:** production data lives in the production database, which is created empty for each new deployment — so the customer copy starts clean automatically. The only thing to double-check is the *development* database inside the fork (Phase 2, step 4).

## Phase 1 — Fork the template (2 min)

1. Open this project on Replit → **Fork / Remix**.
2. Name it clearly: `SecureOps - <Customer Name>`.
3. Never do customer-specific feature work in the master; never fork from a customer copy.

## Phase 2 — Clean the copy (10 min, inside the fork)

These committed settings carry over from WCSG and **must be changed** in the fork (App Settings → Environment / Secrets panes, or ask the Agent in that fork to do it):

1. **Production env** — delete these two (they point at WCSG's domain; the new deploy then self-resolves to its own `.replit.app` address until you add a custom domain in Phase 6):
  - `APP_BASE_URL`
  - `ALLOWED_ORIGINS`
2. **Shared env** — change:
  - `DEMO_ADMIN_EMAIL` → the **customer's** admin email (this becomes their master login)
  - `SUPER_ADMIN_EMAILS` → same email; optionally add your own (comma-separated) to keep support access to their branding screen
  - `ORG_CODE` → their short code, e.g. `acme` (lowercase, no spaces — this is what staff type into the app)
  - `ORG_DIRECTORY` → **delete** in the fork (only the master keeps the directory)
3. **Seeding must stay ON for the first boot** (`SEED_DEMO_USERS` unset or `true`). This is what creates the customer's first admin account — if it's off on an empty database, nobody can ever log in.
4. **Check the fork's dev database** — if any WCSG data came across, wipe it and re-push the schema (`pnpm --filter @workspace/db run push`). Easiest: ask the Agent in the fork to “wipe the dev database and re-push the schema.”
5. **NEVER add an `EXPO_TOKEN` secret to a customer fork.** That token makes a project push phone-app updates on every publish. Only the master may have it — a customer fork with that token would push *its* code to **every customer's phones**.

## Phase 3 — Secrets & integrations checklist (15-30 min, inside the fork)

Secrets never copy on a fork. Work through this table top to bottom:

| Secret / integration                                                                                                       | What it powers                                                  | Required?                                          | Where the value comes from                                                                                                                                                                                                                               |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>SESSION_SECRET</code>                                                                                                | Login security                                                  | <input type="checkbox"/> (deploy fails without it) | Generate a fresh random string, 32+ characters — <b>unique per customer, never reuse WCSG's</b>                                                                                                                                                          |
| <code>DEMO_ADMIN_PASSWORD</code>                                                                                           | Customer's first admin login                                    | <input type="checkbox"/>                           | Choose a strong temp password; they change it after first login                                                                                                                                                                                          |
| <code>SMTP_HOST</code> / <code>SMTP_PORT</code> / <code>SMTP_USER</code> / <code>SMTP_PASS</code> / <code>SMTP_FROM</code> | All outbound email (invites, password resets, onboarding links) | <input type="checkbox"/> for HR flows              | Ideally a mailbox on the <b>customer's</b> domain (their emails then come from their name); reusing the WCSG mail account works to start. Alternative: set <code>RESEND_API_KEY</code> + <code>RESEND_FROM</code> and <code>EMAIL_PROVIDER=resend</code> |
| <code>LIVEKIT_URL</code> / <code>LIVEKIT_API_KEY</code> / <code>LIVEKIT_API_SECRET</code>                                  | Push-to-talk radio                                              | <input type="checkbox"/> if they use radio         | Create a <b>new (free-tier) LiveKit Cloud project per customer</b> at <a href="https://cloud.livekit.io">cloud.livekit.io</a> — keeps each customer's radio traffic and billing separate                                                                 |
| <code>CONTROL_PLANE_SHARED_SECRET</code>                                                                                   | Lets your fleet console manage this customer                    | Recommended                                        | Generate a fresh random string; you'll paste the same value into the control plane in Phase 8                                                                                                                                                            |
| Twilio (Replit integration pane)                                                                                           | SMS alerts (emergency, shift notices)                           | Optional                                           | Reconnect in the fork's Integrations pane; without it, push notifications still work                                                                                                                                                                     |
| Gemini AI (Replit integration pane)                                                                                        | AI features                                                     | Only if used                                       | Reconnect in the fork's Integrations pane                                                                                                                                                                                                                |
| <code>SCHEDULER_BASE_URL</code> / <code>SCHEDULER_SHARED_SECRET</code>                                                     | External scheduler sync                                         | Only if used                                       | From the customer's scheduler system                                                                                                                                                                                                                     |
| <b>App Storage bucket</b>                                                                                                  | Uploaded documents, licenses, logos                             | <input type="checkbox"/>                           | Create a <b>new bucket</b> in the fork (Object Storage pane, or ask the Agent). Files must not share WCSG's bucket                                                                                                                                       |

Optional per-customer tuning (env, not secrets): `PAYROLL_TIMEZONE` (default America/Chicago), `EMERGENCY_CALL_NUMBER` (default 911), `GEOFENCE_RADIUS_MILES` (default 0.25).

## Phase 4 — First publish (10 min, inside the fork)

1. Publish as **Reserved VM (always-on)** — *not* Autoscale (the radio and live features need an always-on server). A **fresh, empty production database** is created here.
2. After it's live, open `https://<their-address>/api/brand` in a browser — you should see text (JSON), not an error. If it errors persistently, the database schema didn't reach production: run `pnpm --filter @workspace/db run push` against the production database in the fork, or ask the fork's Agent to fix it.
3. Log in at `https://<their-address>/admin-portal/` with the `DEMO_ADMIN_EMAIL` + `DEMO_ADMIN_PASSWORD` you set. If an amber "degraded configuration" banner shows, it lists exactly which setting is still missing.

## Phase 5 — Brand it (5 min, in their admin portal)

Log in as the admin → **Platform** → **Branding**. Set company name, short name, app name, tagline, the three brand colors, logo, and contact emails. Changes apply **live** — no republish needed. (The login screen intentionally stays "SecureOps Command" for everyone; the customer's brand appears everywhere after sign-in.)

## Phase 6 — Custom domain (optional, 15 min + DNS wait)

1. Buy/connect the domain in the fork's Deployment → Settings → Domains.
2. Once it's serving, set in the fork's **production** env: `APP_BASE_URL=https://theirdomain.com` and `ALLOWED_ORIGINS=https://theirdomain.com`, then **republish**.
3. Email links and browser security now use their domain.

## Phase 7 — Register the org code (5 min, back in THIS master project)

1. Edit the master's `ORG_DIRECTORY` env — add one line to the JSON list:

```
{ "code": "acme", "name": "Acme Security", "apiBaseUrl": "https://theirdomain.com" }
```

`apiBaseUrl` is the origin only — no `/api`, no trailing slash. Use the `.replit.app` address if there's no custom domain yet (update it later when the domain lands).

2. **Republish the master** — the directory is read once at startup.
3. Verify: `https://secureops-command.replit.app/api/org-directory/resolve?code=acme` returns their address.

4. Their staff open the same SecureOps app from the store → Connect screen → type `acme` → log in. The customer's own **invite QR / connect link** surface also works now (powered by the `ORG_CODE` you set in Phase 2).

## Phase 8 — Register in the fleet console (5 min)

In the control plane, add the customer: name, org code, backend address, and the `mgmtSecret` = the exact `CONTROL_PLANE_SHARED_SECRET` value you generated in Phase 3. Until both sides hold the same secret, the customer backend simply ignores control-plane requests (safe default).

## Phase 9 — Acceptance checklist (10 min)

Run through every line before handover:

- [ ] `https://<addr>/api/brand` loads (API + database healthy)
- [ ] Admin can log in; **no amber banner** in the portal
- [ ] Branding shows the customer's name/colors/logo after sign-in
- [ ] Send a staff **invitation** — the email arrives, from the right address
- [ ] Public **apply** page loads: `https://<addr>/admin-portal/apply`
- [ ] Phone: same app → Connect → their org code → login works
- [ ] Radio: hold Talk on one device, hear it clearly on another
- [ ] Upload a document (e.g. a license) — it saves and re-opens
- [ ] Org code resolves from the master directory (Phase 7, step 3)
- [ ] Customer appears healthy in the control plane

## Phase 10 — Handover & lockdown (10 min)

1. Customer admin logs in and **changes their password**.
  2. The demo staff accounts (`officer@` / `lead@` / `guest@secureops.com`) are seeded for testing. Once the customer is live, set `SEED_DEMO_USERS=false` in production env and republish, then deactivate those demo users in the Users grid.
  3. Confirm who holds super-admin (`SUPER_ADMIN_EMAILS`) — that's who can change branding and platform settings.
  4. Send them the legal docs (`legal/` folder: Master Subscription Agreement + User Agreement).
-

## Quick-reference: the whole flow

Fork master → clean env (Phase 2) → re-enter secrets & reconnect integrations (Phase 3) → publish Reserved VM, seeding ON (Phase 4) → brand in-app (Phase 5) → domain (Phase 6) → add org code to master directory + republish master (Phase 7) → control plane (Phase 8) → verify (Phase 9) → handover (Phase 10).

### Golden rules

- Always fork from the master, never from a customer copy.
- Seeding ON for every first boot — off too early means permanent lockout.
- `EXPO_TOKEN` lives **only** in the master.
- One customer = one backend = one database = one bucket. Nothing shared.
- The master's `ORG_DIRECTORY` is the single source of truth for org codes; every change needs a master republish.