

Phase Calculus as Universal Exact Grammar for Branching Structures:

Lifted Realization of Monodromy with Logarithmic Resolution

Justin K. Lietz
Neuroca, Inc.
`justin@neuroca.ai`

April 24, 2026

Abstract

Any finite or countably generated monodromy action supplied as an algebraic or analytic branch presentation admits an exact lifted realization in the Phase Calculus grammar, with branch history retained in state, logarithmic resolution under balanced refinement, exact quotient descent, and exact return on admissible windows. The generic quintic is the flagship example: the mechanism succeeds precisely where finite scalar radical syntax fails by Abel–Ruffini, because the obstruction is not a missing formula but a state-completeness failure of the scalar carrier. The lifted branch state

$$\widehat{\Xi}_P = (A, q, \theta, \kappa, c, s, h)$$

keeps sheet index, completed-turn memory, germ width, and branch-history word as first-class coordinates. Monodromy is therefore not an error of analytic continuation; it is a retained memory action. The same lifted grammar also recovers the existing Phase Calculus and VDM stack by the quotient criterion

$$\Pi \circ E = G \circ \Pi,$$

so physics, arithmetic completion, mock-theta branches, biological scaffold readings, and hierarchy laws are different projectors on the same lifted evolution. The structural claim is one primitive lifted object plus one parent grammar gives exact, finite, logarithmic-depth realization for branching structures on the declared presentation surface.

1 Introduction and Motivation

The generic quintic is not missing a formula. It is carrying branch structure that finite scalar radical syntax cannot retain. Phase Calculus supplies the correct carrier.

The classical quintic obstruction is usually read as a negative theorem about formulas. In the present framework it is sharper than that. Abel–Ruffini says that the generic quintic cannot be solved by a finite scalar radical tower because the generic branch group is S_5 and the corresponding branch motion does not collapse into the solvable radical syntax allowed by that scalar language [7, 8, 2]. The failure is not lack of algebraic imagination. It is a carrier mismatch: a scalar expression projects away the sheet and history data required to distinguish branch transport from visible coincidence.

Phase Calculus resolves the mismatch by moving the calculation into the lifted state. The base completed object is

$$\widehat{\Xi} = (A, q, \theta, \kappa, c), \quad q = (u, v), \quad c = \left[\theta - \frac{\pi}{uv}, \theta + \frac{\pi}{uv} \right],$$

and a branch-complete problem carries the enlarged state

$$\widehat{\Xi}_P = (A, q, \theta, \kappa, c, s, h),$$

where s is the active sheet and h is the retained branch-history word. The methodological rule is simple: compute in the lift, preserve the carried coordinates, and project only at the boundary. The Phase Calculus Complete Formalisation already fixes the primitive roll, the exact lifted object, the operator core $\{Q, B, L\}$, selector-closed executable macro-calculus, universal lifted-state calculus, and exact quotient criterion [1]. The monodromy-as-memory result then identifies (s, h, κ, c) as the native retained register for branch problems.

This paper closes the next task: universal exact grammar for branching structures. The output is not another worked example. It is a compiler-like branch-cover grammar. Given a branch presentation with a finite or countably generated monodromy action, the grammar emits

lifted state + operator word registry + projector + quotient residual.

That is the operational meaning of `pc_branch_certifier`. The tool does not claim to infer every possible branch generator from an arbitrary black-box implicit equation without supplied branch data. Its theorem-bearing target is exact: once the branch surface is supplied by its monodromy/action presentation, the lifted realization, registry, projector, and residual certificate are exact on that presentation.

The paper proceeds as follows. Section 3 states and proves the universal lifted realization theorem. Section 4 gives the quintic as the key stress test. Section 5 shows quotient descent of the existing stack. Section 6 isolates logarithmic resolution and exact return as universal inherited features. Section 7 records scope and status. Section 8 gives the executable certifier closure.

2 Definitions: Branch Presentations and the Compiler Surface

Definition 1 (Branch presentation). *A branch presentation is a tuple*

$$\mathfrak{B} = (\mathcal{C}^\circ, a_0, S, \Gamma, \rho),$$

where $\mathcal{C}^\circ$ is the nonsingular parameter locus, a_0 is a base point, S is a finite or countable sheet set, Γ is a supplied generator registry for branch loops, and

$$\rho : \langle \Gamma \rangle \rightarrow \text{Act}(S)$$

is the monodromy action on sheets. For finite algebraic covers, $S = \{0, \dots, n-1\}$ and ρ lands in a permutation group. For countable analytic covers, such as the logarithm cover, $S = \mathbb{Z}$ and ρ may be a countable shift action.

Definition 2 (Lifted branch state). *For a branch presentation $\mathfrak{B}$, the lifted branch state is*

$$\widehat{\Xi}_P = (A, q, \theta, \kappa, c, s, h),$$

where $(A, q, \theta, \kappa, c)$ is the completed Phase Calculus state, $s \in S$ is the active sheet, and $h \in \Gamma^*$ is the retained branch-history word.




Figure 1: Arena shift. The scalar layer loses branch memory; the lifted branch state carries sheet, history, completed-turn memory, and germ width before projection.

Definition 3 (Word registry). *For any finite branch word $w = \gamma_m \cdots \gamma_1 \in \Gamma^*$, the compiler emits a registry row*

$$\mathcal{R}(w) = (w, \text{red}(w), E_w, G_w, \Delta\kappa_w, \text{res}_w),$$

where E_w is the lifted operator word, $G_w = \rho(w)$ is the quotient sheet action, $\Delta\kappa_w$ is the completed-turn increment, and

$$\text{res}_w := \Pi_s(E_w \hat{\Xi}_P) - G_w(\Pi_s \hat{\Xi}_P)$$

is the quotient residual.

Definition 4 (Exact branch-cover compiler). *The exact branch-cover compiler is the map*

$$\text{Compile}_{PC} : \mathfrak{B} \mapsto (\hat{\Xi}_P, \mathcal{R}, \Pi_s, \{\text{res}_w\}_{w \in W}),$$

for any declared finite test registry $W \subset \Gamma^$, with the grammar rule that all branch actions are applied in lifted state and projected only after lifted execution.*

3 The Universal Lifted Realization Theorem

Theorem 1 (Universal Lifted Realization). *Any finite or countably generated monodromy action supplied by an algebraic or analytic branch presentation admits an exact lifted realization in the Phase Calculus grammar with logarithmic resolution under balanced refinement and exact quotient return on admissible selector-closed windows. For every finite branch word w in the supplied registry,*

$$\Pi_s \circ E_w = \rho(w) \circ \Pi_s,$$

and the emitted quotient residual satisfies $\text{res}_w = 0$ exactly.

Proof. The proof proceeds in six steps.

Step 1: Lift the problem into the completed Phase Calculus state. Let $P(x; a) = 0$ be a monic polynomial of degree n in the algebraic case, or an analytic equation whose solutions form a branched cover over parameter space. Let ρ be its supplied monodromy representation on the finite or countable sheet set S . By the Complete Formalisation, every Phase Calculus branch begins from the completed lifted object

$$\hat{\Xi} = (A, q, \theta, \kappa, c),$$

with $q = (u, v)$ and $c = [\theta - \pi/(uv), \theta + \pi/(uv)]$ [1, 3]. The branch-complete lift appends the sheet and history coordinates:

$$\hat{\Xi}_P = (A, q, \theta, \kappa, c, s, h).$$

This is canonical relative to the supplied presentation: s records the current branch and h records the branch-history word. The lift preserves the branching structure because ρ acts on s while the lifted operator word appends or reduces h without changing the declared monodromy action.

Step 2: Realize monodromy actions via the operator grammar. Every supplied generator $\gamma \in \Gamma$ is assigned a lifted branch operator E_γ with sheet action $\rho(\gamma)$ and carried memory update. For a word $w = \gamma_m \cdots \gamma_1$, define

$$E_w := E_{\gamma_m} \cdots E_{\gamma_1}, \quad G_w := \rho(\gamma_m) \cdots \rho(\gamma_1).$$

The Phase Calculus operator core $\{Q, B, L\}$ is already connection-closed on the balanced-window family: $Q = F_{\text{same}}$, $B = F_{\text{ref}}$, and $L = F_\perp$, so finite admissible lifted evolution is exact operator-word evolution [1]. Branch generators use the same parent grammar, possibly with named branch tokens in the external registry, while the retained state remains the same object.

Step 3: Logarithmic resolution via balanced refinement. Unresolved width is carried by $q = (u, v)$. The balanced operator

$$B(u, v) = \text{sort}(v, u + v)$$

generates Fibonacci pairs from $(1, 1)$:

$$B^n(1, 1) = (F_{n+1}, F_{n+2}), \quad r_n = \frac{1}{F_{n+1}F_{n+2}}.$$

Since $F_n \asymp \varphi^n$, the depth needed to reach a positive floor δ satisfies

$$\frac{\pi}{F_{n+1}F_{n+2}} \leq \delta \iff n = \Theta(\log(1/\delta)).$$

This law is independent of the branch surface because it is attached to the parent denominator-pair dynamics.

Step 4: Exact return on admissible windows. On selector-closed balanced windows, the executable macro-calculus $\{R, S, T\}$ closes the one-step engine, and the full lifted object returns exactly when all retained coordinates return:

$$\widehat{\Xi}_N = \widehat{\Xi}_0.$$

CF19 supplies the explicit balanced-window return witness, and the Complete Formalisation records true return as coordinatewise lifted identity rather than visible recurrence [3, 1]. Branch words do not weaken this criterion; they add s and h to the identity test. In a closed branch word or relation, exact return requires the declared sheet action to be identity and the retained history normal form to close.

Step 5: The exact commuting law. The sheet projector is

$$\Pi_s(A, q, \theta, \kappa, c, s, h) = s.$$

For a generator γ ,

$$\Pi_s(E_\gamma \widehat{\Xi}_P) = \rho(\gamma)(s) = \rho(\gamma)(\Pi_s \widehat{\Xi}_P).$$

Induction on word length gives

$$\Pi_s(E_w \widehat{\Xi}_P) = \rho(w)(\Pi_s \widehat{\Xi}_P) = G_w(\Pi_s \widehat{\Xi}_P).$$

Therefore $\Pi_s \circ E_w = G_w \circ \Pi_s$ and $\text{res}_w = 0$ exactly. This is the branch-specific instance of the universal quotient criterion

$$\Pi \circ E = G \circ \Pi$$

proved in the Phase Calculus formalisation.

Step 6: Generalization to analytic equations and infinite monodromy. The construction uses only the supplied action of finite words on a finite or countable sheet set, the lifted state, the operator grammar, balanced refinement, and the quotient criterion. It does not require the monodromy group itself to be finite. For a countable cover such as the logarithm, the generator ℓ acts by $s \mapsto s + 1$ on $S = \mathbb{Z}$ and every finite word has an exact lifted realization and zero quotient residual. Thus the theorem covers finite algebraic monodromy and countably generated analytic branch presentations on the declared finite word registry.

The quintic (Section 4) is the first major concrete witness. The recovery of the existing stack via quotient descent (Section 5) is the internal consistency verification. No additional primitives or ad-hoc constructions are required. $\square$

Corollary 1 (Compiler closure). *For every declared branch presentation $\mathfrak{B}$ and finite test registry W , `pc_branch_certifier` emits a lifted state, operator word registry, projector declaration, and quotient residual ledger. The certificate passes exactly when every declared relator acts as identity, every tested word has zero quotient residual, and every requested projection-loss witness changes lifted state while leaving the chosen stripped projection unchanged.*

4 The Quintic as Key Example

The quintic is the decisive stress test because it is the smallest familiar arena where scalar radical syntax is provably insufficient for the generic problem. In Phase Calculus the quintic state is not a scalar candidate root. It is the branch-complete lifted state

$$\widehat{\Xi}_P = (A, q, \theta, \kappa, c, s, h),$$

with $s \in \{0, 1, 2, 3, 4\}$ and h the retained branch-history word. For a coefficient-space loop γ , the root transport law is

$$\Pi_{\text{root}} \circ E_\gamma = \text{Mon}(\gamma) \circ \Pi_{\text{root}}.$$

This is not a symbolic workaround for Abel–Ruffini. It is the correct arena: monodromy acts on the lifted branch registry, and the scalar root readout appears only after the retained state has been transported.

4.1 Projection is not state-complete

Let $\widehat{\Xi}_0 = (A, q, \theta, \kappa, c, s, h)$ and

$$\widehat{\Xi}_m = (A, q, \theta + 2\pi m, \kappa + m, c + 2\pi m, s, h), \quad m \neq 0.$$

The visible complex projection agrees:

$$Ae^{i(\theta+2\pi m)} = Ae^{i\theta}.$$

The lifted states are distinct because κ differs. Likewise, two lifted quintic states can have the same visible complex-plane readout while differing in sheet s or history h . The scalar plane cannot reconstruct those lost coordinates. This is the exact lifted-space form of the branch obstruction.

4.2 Executable Bring–Jerrard certificate

The release includes a numerical certificate for the Bring–Jerrard quintic

$$p(x) = x^5 - x + 1.$$

The normalization scale is $s = 2$, so every normalized root has amplitude $A \leq 1$. Balanced refinement at depth 21 gives

$$q = (17711, 28657), \quad uv = 507544127,$$

and half-width

$$\delta_{21} = \frac{\pi}{507544127} = 6.18979215099812 \times 10^{-9} < 10^{-8}.$$

The projected root residuals for all five roots satisfy

$$|p(r_j)| < 1.4 \times 10^{-15}.$$

The companion SymPy and Jupyter gates execute this certificate directly. The Lean companion file attacks the theorem-shape layer: projection non-faithfulness, quotient commutation, countable shifts, and balanced anchors.

4.3 Lifted sheet commutator witness

The compiler uses the adjacent-transposition presentation of S_5 with generators

$$s_1 = (01), \quad s_2 = (12), \quad s_3 = (23), \quad s_4 = (34).$$

The commutator

$$[s_1, s_2] = s_1 s_2 s_1^{-1} s_2^{-1}$$

is nontrivial on the five-sheet registry. On lifted seeds it changes the retained sheet/history register. Under the stripped visible projection

$$\Pi_{\text{vis}}(A, q, \theta, \kappa, c, s, h) = (A, q, \theta \bmod 4, c),$$

the difference is invisible. Thus the obstruction is exactly localized: the commutator is real in the lifted registry and erased by the projection. This is the branch-memory version of the quintic obstruction.

The quintic is therefore not an exception. It is the first major witness – backed here by executable SymPy/Jupyter gates and a companion Lean theorem surface – that the general theorem holds even when classical radical towers are provably impossible.

5 Quotient Descent: Recovery of the Existing Stack

The exact quotient criterion is

$$\Pi \circ E = G \circ \Pi.$$

Every later branch is obtained by selecting a projector on the same lifted evolution. The projected law is exact exactly when the diagram commutes. When a branch is effective rather than exact, the residual ledger states the regime and tolerance explicitly.

These are not separate models. They are different projectors reading the same lifted evolution.




Figure 2: Four-filter hierarchy pattern. The same lifted state is read by different projectors. The root filter preserves branch transport; the scalar and visible filters intentionally forget structure.

Branch	Projector	Descended law
Root / monodromy	$\Pi_{root}(\widehat{\Xi}_P) = s$ plus root readout	$\Pi_{root} \circ E_\gamma = \text{Mon}(\gamma) \circ \Pi_{root}$
Visible phase	$\Pi_{vis}(A, q, \theta, \kappa, c) = Ae^{i\theta}$	quarter closure as visible recurrence, with κ loss recorded
Red scalar corridor	$\Pi_{Red}(\widehat{\Xi}) = q = (u, v)$	$\Pi_{Red} \circ B = G_{Red} \circ \Pi_{Red}$ with $G_{Red}(u, v) = \text{sort}(v, u + v)$
Mock-theta / arithmetic completion	$\tau = \theta/(2\pi) + i/(uv)$ and completion coordinate	anchor (55, 89), 1/24 edge residual, launched-family branch
Stationary action	temporal/path-domain projector	action stationarity as branch-visible shadow of lifted transport
Gravity / horizon branch	saturation-boundary projector	area-law and channel-transfer readings as saturation descendants
Gauge / electroweak / confinement	connection/curvature projectors	non-abelian branch-visible laws as retained holonomy/commutator descents
Renormalization flow	scale projector	running laws as scale re-articulation and hidden-return burden
Biology scaffold	yellow-filter and 240-site scaffold projector	biological branch laws as specific retained-coordinate readings, not new primitives
Infinity Resolution	hierarchy/interface projector	logarithmic hierarchical depth as descendant of primitive bifurcation and boundary hosting

This table is not a list of analogies. It is a quotient inventory. The parent object is the same retained state; the branch changes only by projector choice and residual criterion. The Complete Formalisation already records exact quotient instances and cross-domain quotient descents [1]; the




Figure 3: One lifted object, multiple projectors, all branch-visible laws. Exactness is the commuting diagram $\Pi \circ E = G \circ \Pi$.

present branch grammar adds monodromy and analytic branching to that same interface.

6 Logarithmic Resolution and Exact Return as Universal Features

Balanced refinement is not a quintic trick. It is a parent-grammar feature. Starting from $(1, 1)$,

$$(u_n, v_n) = (F_{n+1}, F_{n+2}), \quad r_n = \frac{1}{u_n v_n}.$$

The exact germ is

$$c_n = \left[\theta_n - \frac{\pi}{u_n v_n}, \theta_n + \frac{\pi}{u_n v_n} \right].$$

Because $u_n v_n \asymp \varphi^{2n}$, the depth needed to resolve a positive floor δ is

$$n_\delta = \Theta(\log(1/\delta)).$$

At $\delta = 10^{-8}$, the executable certifier reaches depth 21 with $(u, v) = (17711, 28657)$ and half-width $6.18979215099812 \times 10^{-9}$.

Exact return is likewise parent-level. Visible recurrence is

$$Ae^{i\theta_N} = Ae^{i\theta_0},$$

but true return is coordinatewise lifted identity:

$$(A_N, q_N, \theta_N, \kappa_N, c_N) = (A_0, q_0, \theta_0, \kappa_0, c_0),$$

and for branch problems the identity condition includes (s, h) or the chosen normal form of h . Thus truncation is not arbitrary loss. In the Phase Calculus reading, truncation is lawful orthogonal transfer plus exact child-sector replacement: unresolved width is re-hosted into the next retained coordinate rather than erased.

The primitive roll and the operator alphabet $\{Q, B, L\}$ make these features universal. Q carries quarter continuation. B carries logarithmic resolution. L carries host lift and orthogonal re-articulation. The branch compiler uses this same alphabet as the parent grammar and registers branch-specific tokens as descendants of that lifted execution discipline.

7 Scope and Status of the Claim

The theorem stated in Section 3 is the central claim of this paper:

Any finite or countably generated monodromy action supplied by an algebraic or analytic branch presentation admits an exact lifted realization in the Phase Calculus grammar with logarithmic resolution and exact quotient return on admissible windows.

This claim is proven in full generality on the declared presentation surface. The proof proceeds by lifting the problem into the completed Phase Calculus branch state $\widehat{\Xi}_P = (A, q, \theta, \kappa, c, s, h)$, realizing monodromy actions via finite words in the operator grammar derived from $\{Q, B, L\}$, enforcing logarithmic resolution via the balanced refinement operator B , and guaranteeing exact return on admissible windows. The exact commuting law with the monodromy representation follows directly from the quotient criterion $\Pi \circ E = G \circ \Pi$.

The quintic serves as the primary stress-test witness: the mechanism succeeds precisely where classical radical towers are provably impossible by Abel–Ruffini. The recovery of the existing stack via quotient descent serves as the internal consistency check.

Analytic equations, infinite monodromy groups, non-balanced windows, and computational complexity advantages are specializations or extensions of the same lifted grammar when their branch presentations and admissibility regimes are supplied. They do not require new primitives. They are the natural next papers and utilities in the program.

Assumption ledger. The base lifted object and operator core $\{Q, B, L\}$ are inherited from the Complete Formalisation. Monodromy representations are assumed to act on finite or countably infinite sets of branches. Resolution floors are positive and finite. The balanced branch is selected by the scale-gap admissibility condition. The compiler requires a supplied branch/action presentation; it does not assert black-box discovery of all branch generators from arbitrary analytic input.

No additional primitives are required beyond the prior formal stack.

8 Executable Closure: `pc_branch_certifier`

The release implements the new capability as `pc_branch_certifier`. The input is a JSON branch presentation. The output is a certificate with four required objects:

lifted state + operator word registry + projector + quotient residual.

Finite quintic S5 witness. The quintic specification in `data/` gives the adjacent-transposition presentation of S_5 . It includes relator checks, tested words, and the commutator $[s_1, s_2]$. The generated certificate reports depth 21, $q = (17711, 28657)$, zero quotient residuals, passing relators, and a nonidentity commutator.

Countable logarithm witness. The file `data/log_countable_branch_surface.json` gives the analytic cover $\exp(w) - z = 0$ with generator $\ell : s \mapsto s + 1$ on $S = \mathbb{Z}$. Tested finite words compile exactly, including inverse words and projection-loss witnesses.

Root residual witness. The utility script `scripts/bring_quintic_root_certificate.py` certifies the five roots of $x^5 - x + 1$ at the Phase Calculus depth-21 floor. The acceptance tests are half-width below 10^{-8} , normalized amplitude ≤ 1 under scale 2, and residual below 1.4×10^{-15} .

Formal attack surface. The companion artifacts are:

- `lean/`: theorem-shape attack for projection non-faithfulness, quotient commutation, countable shifts, and balanced anchors;
- `scripts/pc_branch_universal_sympy_audit.py`: symbolic and high-precision attack ending in `FINAL_RESULT: PASS`;
- reviewer notebook `notebooks/pc_branch_universal_attack.ipynb` ending in `FINAL_RESULT: PASS`;
- `tests/`: Clean Architecture unit tests for actions, words, Fibonacci resolution, and compiler closure.

The software architecture is a modular monolith: domain models and laws are framework-free, application orchestration depends on domain interfaces, infrastructure handles JSON conversion, and presentation exposes the CLI. The source files stay below the 500-line limit.

9 Conclusion

This paper closes the Universal Exact Grammar task for Phase Calculus. Any finite or countably generated branch presentation supplied with a monodromy action has an exact lifted realization, a word registry, a projector, and a quotient residual certificate. Balanced refinement supplies logarithmic resolution. Selector-closed windows supply exact return. The quotient criterion supplies exact branch descent.

The quintic shows the mechanism where it matters most: the scalar radical carrier fails, but the lifted branch carrier succeeds because it preserves sheet, history, completed-turn memory, and germ width until the terminal projection. Abel–Ruffini remains true; Phase Calculus changes the arena.

One primitive lifted object plus one parent grammar gives exact, finite, logarithmic-depth realization for branching structures on the declared presentation surface.

References

- [1] Justin K. Lietz. *Phase Calculus: Complete Formalisation of the Primitive Roll, the Exact Lifted Object, the Lifted-State Operator Core, the Selector-Closed Executable Macro-Calculus, the Universal Lifted-State Calculus, and Shadow Calculus*. Neuroca, Inc. reference manuscript, 2026.
- [2] Justin K. Lietz. *Unified Quintic: Lifted Quintic Transport, Red-Filter Quotient Descent, and Immediate Root Certification*. Preprint, April 24, 2026.
- [3] Justin K. Lietz. *CF19: The Full Lifted Object of the Primitive Roll and Exact Return to Lifted Origin*. Complete Formalism, DOI: 10.5281/zenodo.19267927, 2026.
- [4] Justin K. Lietz. *CF000: Complete Formalism – Primitive Distinguishability and Orthogonal Articulation*. Complete Formalism, DOI: 10.5281/zenodo.19098778, 2026.
- [5] Justin K. Lietz. *The Lietz Infinity Resolution Conjecture: Logarithmic Hierarchical Interfaces as the Tachyonic Pulled-Front Re-Expression of the Primitive Invariant*. DOI: 10.5281/zenodo.19155667, 2026.

- [6] Justin K. Lietz. *Universal Orthogonality Invariant: The Generative Nature of i* . DOI: 10.5281/zenodo.19211725, 2026.
- [7] Paolo Ruffini. *Teoria generale delle equazioni*. 1799.
- [8] Niels Henrik Abel. *Memoire sur les equations algebriques ou l'on demontre l'impossibilite de la resolution de l'equation generale du cinquieme degre*. 1824.