GRIDDY

Project documentation

griddy-survey.vercel.app · github.com/suhasp3/GRIDDY · October 2026

Contents on the next page ↓

Contents

1. Overview

What GRIDDY is and how it fits together

2. Using GRIDDY

A visual walkthrough of the app

3. The codebase

Pages, data model, state, key files

4. Building locally

Setup, commands, before you push

5. Deploying to Vercel

Push to deploy, the feature workflow, rollbacks

6. Keeping it healthy

vercel.json, checks, and recent cleanup

1. Overview

↑ Contents

GRIDDY is a browser-only tool for building grid survey questions and exporting them to Qualtrics. There's no backend or database.

- Researchers design a grid in the editor and preview it live.
- Surveys are saved in the browser's `localStorage`. They can be backed up as JSON.
- Export produces a `.qsf` file that Qualtrics imports directly, or a JS snippet to paste.
- Respondents answer inside Qualtrics. Answers are stored as JSON in embedded-data fields (`GridAssignments`, or `GridPrefills` / `GridResponses` in experimental mode).

```
Editor (ConfigPanel) → EditorContext (state) → PreviewPanel
                                ↓
          surveysApi → localStorage    qualtricsExport → .qsf / JS → Qualtrics
```


Stack: React 18, TypeScript, Vite, Tailwind, React Router, Vitest. Hosted on Vercel as static files.

2. Using GRIDDY

↑ Contents


The editor

Settings on the left, live preview on the right. Pick a category in the **Placing** row, then click cells to fill them in. Name the survey at the top and click **Save**.



The editor at `/`: question & grid settings (01), categories (02), and the live preview.


How respondents answer, and experiments



Section 03 picks the input method. Section 04 turns on experimental mode, where the grid is pre-filled and respondents react to it.


Respondent preview

Shows exactly what respondents will see in Qualtrics. It runs the real exported script, and answers here aren't saved.



The **Respondent preview** tab.


My Surveys



`/history`: surveys saved in this browser, with JSON backup and restore.

Export to Qualtrics


Click **Export to Qualtrics**, then **Download .qsf**, and import that file in Qualtrics. The dialog lists the steps and the field the answers are saved to.



The export dialog. A raw-JavaScript option is tucked away under “Advanced”.

Combining several grids into one survey

From My Surveys, click **Make multi-question survey**. Add saved grids, order them, name each data field, then download one `.qsf`.



`/history/combine`: each grid becomes its own page in Qualtrics.

3. The codebase

↑ Contents

Pages

URL	File	Purpose
`/`	`App.tsx`	The editor and live preview
`/history`	`pages/HistoryPage.tsx`	My Surveys: open, delete, JSON backup
`/history/combine`	`pages/CombineSurveysPage.tsx`	Combine several surveys into one `.qsf`

Data model (`src/grid-types.ts`)

A survey is a `GridConfig` with four parts: **layout** (rows, cols, center cell, barriers), **tuning** (sizes), **survey** (categories, selection mode) and optional **experimental** (pre-filled grid + response labels). Cells are keyed `"r{row}-c{col}"`, 1-based.

State (`src/EditorContext.tsx`)

One reducer holds the survey being edited. Components read it with `useEditor()` and change it by dispatching actions such as `updateLayout`, `updateSurvey`, `setConfig` or `newSurvey`.

Key files

`components/ConfigPanel.tsx`	Left-hand editor UI
`components/PreviewPanel.tsx`	Live preview and Export modal
`components/RespondentPreview.tsx`	Runs the real exported script
`lib/qualtricsExport.ts`	Builds the Qualtrics JS and `.qsf`
`lib/surveysApi.ts`	Save, load and import surveys (localStorage)
`lib/imageInput.ts`	Compresses uploaded images into the survey

Adding a new setting

Add it to the type → give it a default in `createDefaultConfig` and `normalizeConfig` → add a control in `ConfigPanel` → render it in `PreviewPanel` **and** in `qualtricsExport.ts` → add a test.

> The Qualtrics script is plain JavaScript, not React, so visual features have to be built in both places. Use the respondent preview to check that they match.

4. Building locally

↑ Contents

Requires Node 20+ and git. No environment variables are needed.

```
git clone https://github.com/suhasp3/GRIDDY.git
cd GRIDDY
npm install
npm run dev        # http://localhost:5173
```

Command	Does
`npm run dev`	Dev server with hot reload
`npm run build`	Type-check, then bundle to `dist/`. This is what Vercel runs.
`npm run preview`	Serve the built `dist/` locally
`npm test`	Run the Vitest tests
`npm run lint`	ESLint

> **Before pushing:** run `npm run build` (and ideally `npm test` and `npm run lint`). If it fails locally, the Vercel deploy fails too. Unused variables count as build errors.

Saved surveys are stored per site: localhost and the live site keep separate lists. Use Export/Import JSON to move them.

5. Deploying to Vercel

↑ Contents


Vercel is connected to the GitHub repo. **Pushing is the deploy.** There's no separate deploy command.

Push to…	Result
`main`	Live site updates in about a minute
Any other branch or PR	A separate preview URL. The live site is untouched.

Adding a feature

```
git switch main && git pull
git switch -c feature/my-change
# ...build it, check npm run build...
git add -A && git commit -m "My change"
git push -u origin feature/my-change
gh pr create --base main --fill
```

1. Test the preview URL that Vercel posts on the PR.
2. Wait for the green **Vercel** check. Red means the build failed: click Details.
3. Merge the PR. Production updates automatically.



Vercel's comment on a PR: **Ready** means the build passed, and **Preview** opens that branch's test site.

If production breaks

- **Fastest:** in the Vercel dashboard, go to Deployments, open the last good one, then ⋯ → *Promote to Production*.
- **Via git:** `git revert <commit>` on main and push.

The Vercel project lives under **suhasp3s-projects**. Ask Suhas for dashboard access.

6. Keeping it healthy

↑ Contents

vercel.json

The app has client-side routes, so there's no real `/history` file. `vercel.json` serves `index.html` for any path that isn't a real file, so loading or refreshing any page works:

```
{ "rewrites": [{ "source": "/(.*)", "destination": "/index.html" }] }
```

Keep it when you add new routes.

Checks

`npm run build`, `npm test` and `npm run lint` all pass cleanly on `main`. If one fails, something you changed caused it.

Cleanup done (October 2026)

- Fixed the 404 when refreshing `/history` and `/history/combine`.
- Updated an outdated test and fixed all lint errors and warnings.
- Removed the unused `LayoutTab.tsx` and `SurveyTab.tsx`, and the unused `localforage` and `react-webcam` packages.