

# Lecture 14. Kernel Methods

COMP90051 Statistical Machine Learning

Semester 2, 2015

Lecturer: Andrey Kan

Based on slides provided by

Ben Rubinstein and

<http://kernel-methods.net>



THE UNIVERSITY OF  
MELBOURNE


Copyright  
University of  
Melbourne

# Kernel Methods

*Very general family of linear techniques that can be made non-linear in a multitude of ways*

# Overview


- Kernel matrix  $K$ 
  - \* Square  $n \times n$  matrix measuring pairwise similarity
  - \* Entries  $K_{ij} = \mathbf{x}_i \cdot \mathbf{x}_j$
- Kernel methods
  - \* Linear methods relying on training data only through  $K$
  - \* **Make non-linear** by running linear approach in new feature space; but don't need to map the data, just need  $K$
- **Modular**: learning algorithm, feature space, decouple
  - \* Can design general learning algorithms
  - \* Can design general feature mappings/kernels



# Dot products, dot products, ...

- How does the SVM depend on the data?

$$\min_{\mathbf{w}} \left( \frac{1}{2} \|\mathbf{w}\|^2 + \frac{C}{n} \sum_{i=1}^n l(1 - y_i \mathbf{w} \cdot \mathbf{x}_i - b) \right)$$




- Famous result: “Representer Theorem”


- \* Solution in span of data!!  $\mathbf{w}^* = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i$
- \* Predictions become  $f(\mathbf{x}) = \mathbf{w} \cdot \mathbf{x} = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i \cdot \mathbf{x}$
- \* Support vectors are those  $\mathbf{x}_i$  with  $\alpha_i \neq 0$   
→ why the SVM is non-parametric!
- \* Finding the  $\alpha_i$  involves only dot products between data

# Non-linear SVM

- Map data into a new feature space
  - \* Example: original features and products of pairs  
$$\varphi(x_1, \dots, x_d) = (x_1, \dots, x_d, x_1x_1, x_1x_2, \dots, x_dx_d)$$
- Run linear SVM in new space (use kernel matrix)
- Decision boundary is non-linear in original space



# Flexibility of non-linear SVM



[www.kernel-methods.net](http://www.kernel-methods.net)

# Blessing of dimensionality

- Kernels implicitly map data to a very high dimensional features space
- Potentially dangerous because it looks like we now have many more parameters than data points
  - \* That is,  $\mathbf{w}$  for the transformed features space is high dimensional
  - \* Curse of dimensionality
  - \* Danger of overfitting
- **Representer theorem:**  $f(\mathbf{x}) = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i \cdot \mathbf{x}$ 
  - \* The number of parameters is at most  $n$ , independent of dimensionality
  - \* Support vectors are those data points with non-zero  $\alpha_i$
- Usually the number of non-zero  $\alpha_i$  is smaller than  $n$ 
  - \* Sparse kernel machines

# *Danger!!* Potential problem



- Training linear SVM cubic in dimension  $d$
- Non-linear  $\rightarrow$  more dimensions  $\rightarrow$  intractable?
- **Representer Theorem** to the rescue
  - \* Need only find  $\alpha_i$ 's which determine weight vector
  - \* "Only"  $n$  of them, independent of  $d$   
... problematic if "big data"




# But wait... what about the kernel matrix?



Stop!

- *Computing* kernel matrix naïvely expensive
  - \* Map data to  $d'$ -dim feature space, then dot product; takes  $O(d'n^2)$
- Computing kernels *directly* can be **cheap** as
- Example:  $p$ -degree polynomial kernel
  - \*  $\varphi(x_1, \dots, x_d) = (x_1, \dots, x_d, x_1x_1, x_1x_2, \dots, x_dx_d, \dots)$
  - \*  $d' = O(d^p)$  is pretty yuck  $\rightarrow O(d^p)$  per matrix entry
  - \* Trick to cut down to  $O(d)$ :  $\varphi(\mathbf{u}) \cdot \varphi(\mathbf{v}) = (1 + \mathbf{u} \cdot \mathbf{v})^p$
- In fact, don't bother with feature spaces just make up matrix
  - \* **Mercer's Theorem**: provides a tool for identifying valid kernels



# Some popular kernels

Kernel	$k(\mathbf{u}, \mathbf{v})$	Parameters	Mapping $\mathbf{x}$ to features
Linear	$\mathbf{u} \cdot \mathbf{v}$	-	Identity
Polynomial	$(1 + \mathbf{u} \cdot \mathbf{v})^p$	Integer degree $p > 1$	Degree $p$ polynomial in the $x_i$ 's
Gaussian aka Radial Basis Function (RBF)	$\exp\left(\frac{-\ \mathbf{u} - \mathbf{v}\ ^2}{2\sigma^2}\right)$	Width $\sigma$	Infinite dimensional, nothing explicit!


# Many more...

Definition 9.1 Polynomial kernel 286  
 Computation 9.6 All-subsets kernel 289  
 Computation 9.8 Gaussian kernel 290  
 Computation 9.12 ANOVA kernel 293  
 Computation 9.18 Alternative recursion for ANOVA kernel 296  
 Computation 9.24 General graph kernels 301  
 Definition 9.33 Exponential diffusion kernel 307  
 Definition 9.34 von Neumann diffusion kernel 307  
 Computation 9.35 Evaluating diffusion kernels 308  
 Computation 9.46 Evaluating randomised kernels 315  
 Definition 9.37 Intersection kernel 309  
 Definition 9.38 Union-complement kernel 310  
 Remark 9.40 Agreement kernel 310  
 Section 9.6 Kernels on real numbers 311  
 Remark 9.42 Spline kernels 313  
 Definition 9.43 Derived subsets kernel 313  
 Definition 10.5 Vector space kernel 325  
 Computation 10.8 Latent semantic kernels 332  
 Definition 11.7 The p-spectrum kernel 342  
 Computation 11.10 The p-spectrum recursion 343  
 Remark 11.13 Blended spectrum kernel 344  
 Computation 11.17 All-subsequences kernel 347  
 Computation 11.24 Fixed length subsequences kernel 352

Computation 11.33 Naive recursion for gap-weighted subsequences kernel 358  
 Computation 11.36 Gap-weighted subsequences kernel 360  
 Computation 11.45 Trie-based string kernels 367  
 Algorithm 9.14 ANOVA kernel 294  
 Algorithm 9.25 Simple graph kernels 302  
 Algorithm 11.20 All-non-contiguous subsequences kernel 350  
 Algorithm 11.25 Fixed length subsequences kernel 352  
 Algorithm 11.38 Gap-weighted subsequences kernel 361  
 Algorithm 11.40 Character weighting string kernel 364  
 Algorithm 11.41 Soft matching string kernel 365  
 Algorithm 11.42 Gap number weighting string kernel 366  
 Algorithm 11.46 Trie-based p-spectrum kernel 368  
 Algorithm 11.51 Trie-based mismatch kernel 371  
 Algorithm 11.54 Trie-based restricted gap-weighted kernel 374  
 Algorithm 11.62 Co-rooted subtree kernel 380  
 Algorithm 11.65 All-subtree kernel 383  
 Algorithm 12.8 Fixed length HMM kernel 401  
 Algorithm 12.14 Pair HMM kernel 407  
 Algorithm 12.17 Hidden tree model kernel 411  
 Algorithm 12.34 Fixed length Markov model Fisher kernel 427

# Modular learning

- More sophisticated learning algorithms, and kernels, exist
- Representer + Mercer Theorems imply their design decouples



# ...and the algorithms

Computation 2.5 Ridge regression 30  
 Computation 5.14 Regularised Fisher discriminant 131  
 Computation 5.15 Regularised kernel Fisher discriminant 133  
 Computation 6.3 Maximising variance 141  
 Computation 6.18 Maximising covariance 154  
 Computation 6.30 Canonical correlation analysis 163  
 Computation 6.32 Kernel CCA 165  
 Computation 6.34 Regularised CCA 169  
 Computation 6.35 Kernel regularised CCA 169  
 Computation 7.1 Smallest enclosing hypersphere 193  
 Computation 7.7 Soft minimal hypersphere 199  
 Computation 7.10  $\nu$ -soft minimal hypersphere 202  
 Computation 7.19 Hard margin SVM 209  
 Computation 7.28 1-norm soft margin SVM 216  
 Computation 7.36 2-norm soft margin SVM 223  
 Computation 7.40 Ridge regression optimisation 229  
 Computation 7.43 Quadratic  $\epsilon$ -insensitive SVR 231  
 Computation 7.46 Linear  $\epsilon$ -insensitive SVR 233  
 Computation 7.50  $\nu$ -SVR 235  
 Computation 8.8 Soft ranking 254  
 Computation 8.17 Cluster quality 261  
 Computation 8.19 Cluster optimisation strategy 265  
 Computation 8.25 Multiclass clustering 272  
 Computation 8.27 Relaxed multiclass clustering 273  
 Computation 8.30 Visualisation quality 277

Algorithm 5.1 Normalisation 110  
 Algorithm 5.3 Centering data 113  
 Algorithm 5.4 Simple novelty detection 116  
 Algorithm 5.6 Parzen based classifier 118  
 Algorithm 5.12 Cholesky decomposition or dual Gram-Schmidt 126  
 Algorithm 5.13 Standardising data 128  
 Algorithm 5.16 Kernel Fisher discriminant 134  
 Algorithm 6.6 Primal PCA 143  
 Algorithm 6.13 Kernel PCA 148  
 Algorithm 6.16 Whitening 152  
 Algorithm 6.31 Primal CCA 164  
 Algorithm 6.36 Kernel CCA 171  
 Algorithm 6.39 Principal components regression 175  
 Algorithm 6.42 PLS feature extraction 179  
 Algorithm 6.45 Primal PLS 182  
 Algorithm 6.48 Kernel PLS 187  
 Algorithm 7.2 Smallest hypersphere enclosing data 194  
 Algorithm 7.8 Soft hypersphere minimisation 201  
 Algorithm 7.11  $\nu$ -soft minimal hypersphere 204  
 Algorithm 7.21 Hard margin SVM 211  
 Algorithm 7.26 Alternative hard margin SVM 214  
 Algorithm 7.29 1-norm soft margin SVM 218  
 Algorithm 7.32  $\nu$ -SVM 221  
 Algorithm 7.37 2-norm soft margin SVM 225  
 Algorithm 7.41 Kernel ridge regression 229  
 Algorithm 7.45 2-norm SVR 232  
 Algorithm 7.47 1-norm SVR 234  
 Algorithm 7.51  $\nu$ -support vector regression 236  
 Algorithm 7.52 Kernel perceptron 237  
 Algorithm 7.59 Kernel adatron 242  
 Algorithm 7.61 On-line SVR 244  
 Algorithm 8.9  $\nu$ -ranking 254  
 Algorithm 8.14 On-line ranking 257  
 Algorithm 8.22 Kernel k-means 269  
 Algorithm 8.29 MDS for kernel-embedded data 276  
 Algorithm 8.33 Data visualisation 280

# Checkpoint

- Which of the following statements is true?



Any method that uses a feature space transformation  $\varphi(\mathbf{x})$  is a kernel method



Support vectors are points from the training set



Feature mapping  $\varphi(\mathbf{x})$  makes data linearly separable

art: OpenClipartVectors at  
pixabay.com (CC0)



# Kernelised SVM

*Historically first kernel method*

# Feature transformations and kernels

- A feature transformation  $\varphi(\mathbf{x})$  can help transforming data into a linearly separable form
- The kernel trick can be used to perform the transformation implicitly, without actually computing the transformation for each point
- One does not have to use kernels: feature transformation  $\varphi(\mathbf{x})$  can be also use explicitly
  - \* If the number of resulting features is reasonable



# Solutions to the SVM problem

- Recall the soft-margin SVM problem statement:

$$\min_{\mathbf{w}} \left( \frac{1}{2} \|\mathbf{w}\|^2 + \frac{C}{2} \sum_{i=1}^n \xi_i \right)$$

Subject to  $\xi_i \geq 0, y_i(\mathbf{w}\mathbf{x}_i + b) \geq 1 - \xi_i$  for  $i = 1, \dots, n$

- This optimization problem (and many others) can be solved in two ways, called the primal formulation and dual formulation
- The primal approach is to solve the problem as it is stated here
  - \* If you wish, you can first apply  $\varphi(\mathbf{x})$  here directly
- The complexity of training is  $O(d^3)$ , where  $d$  is the dimensionality of data
  - \* Recall that [solving optimization = training]
  - \* If you have applied  $\varphi(\mathbf{x})$  then  $d$  is the dimensionality of resulting space

# The dual formulation

- The idea of the dual formulation is to combine equations for the objective function and constraints into a single new objective function without constraints
  - \* This can be analytically convenient
  - \* Also this can lead to a different perspective on the problem
- This method is called *Lagrange multipliers*, and the corresponding new objective function is called *Lagrangian*

# Formulating the dual SVM problem

- Soft-margin SVM original problem:

$$\min_{\mathbf{w}, b} \left( \frac{1}{2} \|\mathbf{w}\|^2 + \frac{C}{n} \sum_{i=1}^n \xi_i \right)$$

- \* Subject to  $\xi_i \geq 0, y_i(\mathbf{w}\mathbf{x}_i + b) \geq 1 - \xi_i$  for  $i = 1, \dots, n$

- Lagrangian

$$L_P \stackrel{\text{def}}{=} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i [y_i(\mathbf{w}\mathbf{x}_i + b) \geq 1 - \xi_i] - \sum_{i=1}^n \mu_i \xi_i$$

- Fix  $\alpha_i, \mu_i$  and minimise Lagrangian with respect to  $\mathbf{w}, b, \xi$ :

- \* Set partial derivatives  $\frac{\partial L_P}{\partial \mathbf{w}_i}, \frac{\partial L_P}{\partial b}, \frac{\partial L_P}{\partial \xi_i}$  to zero

# Solving the SVM problem

- Setting the partial derivatives to zero gives

- \*  $w^* = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i$
- \*  $0 = \sum_{i=1}^n \alpha_i y_i$
- \*  $\alpha_i = C/n - \mu_i$
- \*  $\alpha_i, \mu_i, \xi_i \geq 0$

- Substituting these back into  $L_P$  gives

- \*  $L_D = \sum_{i=1}^n \alpha_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j y_i y_j \mathbf{x}_i \mathbf{x}_j$

**Proofs are  
outside the  
scope**

- $L_D$  gives a lower bound on the original solution
- Therefore we maximize  $L_D$  w.r.t.  $\alpha_i$ , s.t.  $0 = \sum_{i=1}^n \alpha_i y_i$  and  $0 \leq \alpha_i \leq \frac{C}{n}$
- In addition, Karush-Kuhn-Tucker conditions complete unique characterization of solution

# About those alpha's

- Transform

$$\min_{\mathbf{w}} \frac{1}{2} \|\mathbf{w}\|^2 + \frac{C}{2} \sum_{i=1}^n \xi_i$$

into “dual problem”

$$\max_{\alpha} \quad \alpha \cdot \mathbf{1} - \frac{1}{2} \alpha^T G \alpha$$

$$\text{subject to } 0 \leq \alpha_i \leq \frac{C}{n}$$

where  $G_{ij} = y_i y_j \mathbf{x}_i \cdot \mathbf{x}_j = y_i y_j K_{ij}$   
Gram matrix Kernel matrix

*Want different non-linear mapping?  
Swap out  $K$*

- Quadratic program but in  $n$ , not  $d$  variables
- See how regularisation restricts data influence?

# Solutions to the SVM problem


- The complexity of the primal solution is  $O(d^3)$ , where  $d$  is the dimensionality of data (after applying  $\varphi$ )
- The complexity of the dual solution is  $O(n^3)$
- For “big data”, and finite-dimensional explicit transformation  $\varphi(\mathbf{x})$  the primal form can be preferable

# SVM: decisions to make


- Regularisation parameter  $C$
- Choice of a kernel
- Note that some kernels introduce additional parameters, e.g.,  $p$  in polynomial kernel  $(1 + \mathbf{u} \cdot \mathbf{v})^p$
- SVM is a sparse kernel machine
- Regularisation also helps avoid the curse of dimensionality
- In practice: everything is set using cross-validation

# Varying regularization parameter

Low  $C$ , tendency to underfit



High  $C$ , tendency to overfit



Polynomial kernel is used in all cases



# SVMs for multiclass classification

- Multiclass classification has to be reduced to binary classification
- **One-versus-all:**  $K$  binary classifications are made for each of the  $K$  classes. Each time, classification is “class  $k$ ” vs “the rest”. A new instance is assigned to class for which it has the strongest confidence (furthest away from the boundary).
- **One-versus-one:**  $K(K - 1)/2$  classifications are made, covering all possible pairs of classes. A new instance is assigned the most voted class (class that gets most number of “wins”).

# SVM vs Neural Networks

Kernelised SVM	Feed-forward ANN
Linear SVM applied to non-linear data using kernelisation	Non-linear model by design (non-linear transfer functions)
Variable number of parameters, up to $N$ (data points): predictions are made using support vectors	Parametric model: fixed number of parameters
Inherently batch training (see dual formulation, Kernel matrix)	Naturally amenable to online training (e.g., stochastic gradient descent)
SVM training always finds a global minimum (convex problem)	Global minimum is not guaranteed
Single dimensional output	Naturally adaptable for multiclass classification and multidimensional output

# Summary

- Kernel methods
  - \* Modular decoupling of linear learner and feature mapping
  - \* Built on Representer Theorem, Mercer's Theorem
  - \* Tonnes of kernel functions
  - \* Tonnes of kernel methods (SVM, PCA)