

[CS 11] Prac 10f – Warehouse Sort

Problem Statement

The e-commerce company Chopee stores its packages in a giant warehouse. However, the warehouse is not very well-designed. They simply store all packages they have in a single line. This is inconvenient, as they will need to rearrange the packages from time to time!

That's why they have developed a robotic arm that can perform the following operation, assuming there are n packages numbered 0 to $n - 1$ from left to right:

- Choose a *contiguous* subsequence of the packages, and then reverse their order.

More formally:

- Choose a package i , where $0 \leq i < n$;
- Choose a package j , where $i \leq j < n$;
- Reverse the order of packages i to j , inclusive.

Given q operations, where each operation is a reversal operation like the above, what is the order of the packages after these operations are done in the given order?

Task Details

Your task is to implement a function called `warehouse_rearrange`. This function has two parameters:

- the first parameter is the `int` n .
- the second parameter is a `tuple` / `list` of q pairs of `int` s. Each pair looks like (i, j) with $0 \leq i \leq j < n$ and represents a reversal operation.

The function must return a `list` of n `int` s denoting the order of the packages (from left to right) after the operations are done in the given order. Each package number (0 to $n - 1$) must appear exactly once in this `list`.

Restrictions

(See 10a for more restrictions)

For this problem in particular:

- The source code limit is 2000.

Example Calls

Example 1 Function Call

```
warehouse_rearrange(7, (  
    (2, 5),  
    (1, 3),  
    (3, 6),  
    (4, 4),  
    (3, 4),  
))
```




Example 1 Return Value

```
[0, 4, 5, 2, 6, 3, 1]
```

Constraints

- The function `warehouse_rearrange` will be called at most 1,000 times.
- $1 \leq n \leq 90,000$
- $0 \leq q \leq 90,000$
- The sum of n s across all calls will be $\leq 90,000$.
- The sum of q s across all calls will be $\leq 90,000$.

Scoring

- You get 60  points if you solve all test cases where:
 - $n \leq 50$
 - $q \leq 50$
 - The sum of the n s across all calls will be 600.
 - The sum of the q s across all calls will be 600.
- You get 60  points if you solve all test cases where:
 - $n \leq 6,000$
 - $q \leq 6,000$
 - The sum of the n s across all calls will be 12,000.
 - The sum of the q s across all calls will be 12,000.
- You get 100  points if you solve all test cases.


Clarifications


No clarifications have been made at this time.


Report an issue


Submit solution


[CS 11]


Practice 10 


My submissions 


 **Points:** 220 (partial)

 **Time limit:** 12.0s

 **Memory limit:** 1G

 **Author:**
kvatienza (Kevin Atienza)

 **Problem type**

 **Allowed languages**
NONE, py3