

ChipIn — Project Master Document

Version: 1.2 — brand locked, Stage 0 ready **Owner:** Lanardo "Nardo" Gibson — First Glance Bahamas / Traceline Bahamas Ltd. **Status:** Pre-build validation (Stage 0) — brand and design foundation complete **Domain:** chipin242.com (primary) · chipin.bs (secondary redirect)

Version 1.2 changes

- **Section 6 rewritten:** brand identity is locked and delivered; the coin motif is approved language; **DESIGN.md** v1.0 is the authoritative design reference. All required logo variants (including monochrome) now exist.
- **Added Product Principle 7 (proportional operations)** — scales V1 governance requirements to pilot caps. **Approved by the owner on August 3, 2026.**
- **Section 12 open decisions re-sequenced** into schema-blocking vs pilot-closeable.
- **Section 13 updated:** DESIGN.md marked delivered; bank/channel evidence matrix promoted to the top of the queue as the active critical path.
- Free-platform policy (§8.6 / decision 12.4) is **closed** — all personal campaigns remain free; organizations may later pay only for optional tools.

Version 1.1 decisions (carried forward, approved)

- V1/public launch = monetary fundraising; blood coordination is a separate gated pilot.
- Reporting, disputes, moderation, document security, and access controls are V1 scope.
- Donor tips deferred until a compliant collection method exists.
- Status is pre-build validation until bank-reference, staffing, privacy, and moderation gates close.
- Volunteer, event, blood, and payment modules sequence after the monetary pilot.

1. Vision

ChipIn is a Bahamian mutual-aid and fundraising platform built around how Bahamians already help one another: bank transfers, WhatsApp sharing, cookouts, community organizations, and urgent blood-donation callouts.

It replaces scattered flyers and social posts with structured campaign pages, application-recorded pledge and host-attestation history, clear verification labels, and privacy-conscious sharing. At launch, ChipIn does not collect, hold, or transfer donor funds. Donors send money directly to campaign hosts through existing local banking channels, and ChipIn records what donors report and what hosts mark as received.

One-liner: *ChipIn formalizes the way Bahamians already help each other.*

What ChipIn actually is: an audit trail for money that moves outside the platform. Donor reports what was sent; host attests what was received; every action is append-only. ChipIn's value is coordination and honesty, not custody.

Product principles

1. **Local first:** Design around Bahamian banking, community, and mobile-sharing habits.
 2. **Trust before growth:** Verified hosts, auditable actions, visible campaign status, and prompt moderation are launch requirements.
 3. **Host-attested receipts only:** Public fundraising totals increase only when a host marks a reported transfer as received. ChipIn does not independently verify bank settlement or how funds are used.
 4. **Privacy by default:** Collect and display the minimum information needed for trust and coordination.
 5. **Crisis campaigns stay free:** Medical and emergency campaigns will not pay platform fees.
 6. **Start narrow:** Prove the monetary contribution loop before expanding into additional coordination modules.
 7. **Proportional operations** (*approved August 3, 2026*): All operational, staffing, and governance requirements in this document scale to the published pilot caps. A capped invite-only pilot may satisfy review-operations, support, and monitoring requirements with a single named reviewer, defined response windows, and hard intake limits. Enterprise-grade controls phase in with volume; they are exit criteria for expansion, not entry criteria for the pilot.
-

2. The Problem

- International fundraising platforms add processing fees, currency friction, payout delays, and foreign eligibility constraints.
- Local fundraisers circulate as WhatsApp or Facebook flyers containing bank details but provide no structured progress tracking, verification, or dispute trail.
- Donors cannot easily tell whether a campaign is current, verified, funded, or resolved.
- Hosts manually reconcile transfers and answer repeated questions, creating significant work as campaigns grow.
- Blood requests spread rapidly but may continue circulating after they are fulfilled or expired.
- In a small country, unnecessary medical, identity, or location details can expose a person even when their name is withheld.

The opportunity

ChipIn's starting hypothesis is not generic crowdfunding. It is a local coordination layer around direct bank transfers and community sharing: a campaign page, a bank-compatible reference if validation supports it, a QR link, a donor-reported transfer, a host receipt attestation, and an application audit trail.

3. V1 and Pilot Scope

V1/public launch is Phase 1A monetary fundraising only. Phase 1B blood coordination is a separate conditional pilot and is not implied by "launch." A general monetary campaign may fund a cookout or medical need, but specialized ticket, plate, inventory, clinical, or fulfillment workflows are excluded from V1.

3.1 Phase 1A — Monetary Fundraising MVP

Phase 1A includes:

- Mobile-first campaign pages with title, story, goal, host identity, review labels, sharing controls, and host-attested progress.
- No-account donor flow for pledging and reporting a bank transfer.
- Transfer references only if Stage 0 validates bank/channel compatibility, uniqueness, and recipient visibility; otherwise use the approved fallback matching flow.
- QR links for WhatsApp flyers and printed material.
- Host dashboard for reviewing reported transfers, recording actual amounts received, and viewing an audit history.
- Host verification, risk-based campaign review, reporting, disputes, and minimum moderation tooling.
- Notifications or reminders for unresolved reported transfers.
- Privacy-preserving basic analytics with defined metrics, bot handling, retention, and low-volume suppression: page views, pledge count, reported transfers, host-attested total, and conversion rate.

3.2 Contribution and Reconciliation Flow

1. A donor opens a campaign and enters a pledge amount.
2. If Stage 0 bank testing supports it, ChipIn generates a short transfer reference and always provides a documented fallback matching path.
3. The donor completes the transfer outside ChipIn.
4. The donor reports the transfer, entering the amount sent and bank-generated reference and optionally attaching proof.
5. The host compares the report with their bank activity.
6. The host marks the actual amount received, marks it not found, or requests clarification.

7. Only amounts marked received by the host are added to the public total, labeled **"marked received by the campaign host."**
8. Every action appends an actor, timestamp, prior status, new status, and reason; corrections create compensating events rather than erasing history.

Pledges, transfer reconciliation, and disputes are separate lifecycles:

- **Pledge:** `active | cancelled | expired`
- **Transfer report:** `submitted | clarification_requested | marked_received | marked_not_found | partially_matched | closed_unresolved | confirmation_voided`
- **Moderation case:** `open | assigned | awaiting_donor | awaiting_host | escalated | resolved | dismissed`

The state-machine specification must define transition actors, timeouts, notifications, evidence, public-total effects, reopening, idempotency, and whether one pledge can map to multiple transfers before schema freeze. "Confirmation voided" changes Chipln's displayed record; it does not reverse an external bank transfer.

3.3 Required Edge-Case Rules

- **Partial or different amount:** The host records the actual amount received, not the original pledge; the remaining unmatched amount keeps an explicit status.
- **Missing or incorrect reference:** The host can manually match a report using the approved fallback evidence, with the action recorded in the audit trail.
- **Host does not respond:** The donor receives reminders and can open a moderation case after a defined waiting period.
- **False or mistaken receipt mark:** A host or administrator can void it with a required reason; the original event remains in history.
- **High-volume campaigns:** Hosts can search and filter reports. Any multi-select workflow requires an explicit amount and attestation for every row, reauthentication above risk thresholds, and pilot evidence that it does not enable rubber-stamping.
- **Public progress:** The progress bar uses host-marked receipts only. V1 does not expose pending monetary totals publicly; pilot testing may revisit this.
- **Suspicious activity:** Risk signals include rapid or large receipt marks, repeated references or evidence, large amount mismatches, reused contact details, and receipt marks without corresponding donor reports. Rate limits and anti-automation controls protect the no-account flow.

3.4 Phase 1B — Blood Donation Pilot

Blood coordination follows the monetary MVP and launches only after its operational and information requirements are met.

The pilot includes:

- Blood-request pages with blood type, listed hospital or blood-bank location, official contact instructions, urgency window, source, and last-updated time.
- Institution-sourced blood-bank directory information with hours, phone numbers, revalidation interval, stale-data suppression, and a named owner responsible for keeping it current.
- QR and WhatsApp sharing.
- Automatic expiry, controlled extension, fulfillment, and visibly resolved states so stale linked pages do not appear active; copied screenshots and flyer text cannot be remotely withdrawn.
- Privacy-first templates that omit diagnosis, home address, government identifiers, and unnecessary patient details.
- Requester or authorized-representative attestation, including guardian handling for minors.
- A clear statement that ChipIn coordinates information and does not provide medical advice or guarantee donor eligibility, compatibility, availability, facility acceptance, or clinical outcome; donors must follow official facility screening and instructions.
- An urgent review path that is available only when staffing, escalation, creation, approval, update, extension, fulfillment, and withdrawal procedures are defined.

3.5 Deferred Until After the MVP

The following are part of the product vision but not launch scope:

- Volunteer scheduling and slot management.
 - Event, cookout, ticket, or plate-sale workflows.
 - Donor profiles and giving history.
 - Card or diaspora payments.
 - Multi-currency support.
 - Escrow, custody, or automated bank reconciliation.
 - In-product donor tips without a defined collection rail.
 - Direct account-to-account payment integrations.
 - Independent bank-settlement verification, automated bank feeds, or bank reconciliation.
 - Refunds, chargebacks, transfer recovery, escrow, donor protection, tax-deductible receipts, or funds-use verification.
 - Cash/offline contribution tracking, recurring contributions, stored balances, wallets, or multi-beneficiary transfers.
 - Public pending monetary totals, donor profiles/histories, or native mobile applications.
 - Medical donor eligibility, compatibility, or clinical screening.
-

4. Trust, Verification, and Moderation

Fraud and poor dispute handling are the largest reputational risks. Trust controls must ship with Phase 1A rather than being deferred as growth features. Under Principle 7, their *scale* matches pilot caps.

4.1 Verification Tiers

Tier	Applies to	Requirements
Tier 0 — Donor	Anyone pledging or reporting a transfer	No account required; a status-link design with specified entropy, expiry, revocation, forwarding, and recovery behavior; minimum contact information for follow-up.
Tier 1 — General host	Personal, school, funeral, cookout, and community fundraising	Phone OTP, government ID, bank-account relationship check, first-campaign review.
Tier 2 — Medical/emergency host	Medical bills, blood requests, and disaster relief	Tier 1 plus relevant supporting documentation and manual review.
Organization	Churches, NGOs, schools, clubs, and businesses	Authorized representative, organization evidence, and documented authority over the receiving account.

A strict personal-name match will not work for every legitimate campaign. Treasurer accounts, organizations, and "Friends of..." accounts require an alternate evidence-and-review path.

A lower-friction path for small community fundraisers may be tested during the pilot, but its monetary cap, sponsor/vouch requirement, and abuse controls must be approved before launch.

4.2 Review Operations

Before the V1 controlled pilot, ChipIn must define (at pilot scale, per Principle 7):

- Named reviewer(s), backup coverage, operating hours, and a published support channel. *Pilot-scale example: owner reviews within 48 hours; WhatsApp support channel; intake pauses automatically at the pilot campaign cap.*

- Expected campaign, document, report, and dispute volume plus handling-time assumptions.
- Numeric intake caps, maximum queue ages, reviewer-utilization limits, and pause/stop conditions.
- A published review checklist and rejection/appeal reasons.
- Campaign-risk review triggers, including tier, amount, category, complaints, identity or receiving-account changes, expired evidence, suspicious contributions, and material story edits; first-campaign review alone is insufficient.
- Conflict-of-interest rules and reviewer recusal. (*Quality-check programs, formal training, and access recertification phase in with additional reviewers — expansion exit criteria.*)
- A decision log for every manual review.
- Escalation rules for suspicious campaigns, privacy concerns, and legal requests.

Blood-specific urgent coverage is a Phase 1B gate. Targets should be set only after staffing and pilot caps are confirmed. The product must not promise 24/7 service without 24/7 coverage.

4.3 Reports and Disputes

- Every campaign page includes a visible report action.
- Donors can dispute a reported transfer that remains unresolved beyond the defined waiting period.
- Reports and disputes enter one moderation queue with priority, owner, status, evidence, timestamps, and resolution notes.
- Administrators can pause a campaign, hide public bank details, suspend new contributions, void a host receipt-attestation record, or close a campaign.
- ChipIn cannot recover or reverse an external bank transfer. This limitation must be clearly disclosed.
- Use narrow, dated labels such as **Host identity reviewed**, **Receiving-account relationship reviewed**, **Organization authority reviewed**, and **Supporting document reviewed**. Each label states what was not established and expires or is revoked after relevant material changes; never use a generic badge that implies ChipIn guarantees the campaign, each transfer, or use of funds.

5. Privacy, Security, and Data Governance

Government IDs, bank details, transfer proofs, and medical letters are sensitive launch data. Their protection is a Phase 1 requirement.

5.1 Data-Minimization Rules

- Separate public campaign content from private verification and moderation records.
- Treat receiving-account disclosure as a threat-model decision: click-to-reveal alone does not prevent scraping, screenshots, caching, or referrer leakage.

- Never publish government IDs, medical documents, diagnoses, home addresses, reviewer notes, or unredacted transfer proof.
- Default medical and blood pages to first name or approved display name, hospital location rather than home location, and no diagnosis; review rare blood type, location, and time combinations for re-identification risk.
- Define beneficiary authorization, guardian rules for minors, and consent when a host uploads another person's story, image, identity, or medical document.
- Give hosts clear redaction guidance before upload and strip sensitive file metadata where feasible.
- Collect only the contact information required to operate the contribution and dispute flow; specify verification, status-link lifecycle, donor edit rights, anti-automation controls, and retention for no-account donors.

5.2 Technical Controls

- Complete a threat model and data-flow inventory before implementation approval.
- Store verification documents and transfer proofs in private storage buckets.
- Enforce and independently test Supabase Row Level Security on every table and storage object; tightly restrict privileged service credentials.
- Use short-lived, revocable, high-entropy access links for authorized reviewers.
- Require MFA and least-privilege roles for reviewers, moderators, and administrators, with approval, emergency revocation, and periodic access review.
- Reauthenticate and notify hosts for receiving-account changes; pause and re-review high-risk material changes.
- Validate MIME type and file size, reject active content, scan uploads for malware, and strip metadata where feasible.
- Protect sessions and forms against common web abuse; apply CSP, CSRF defenses, rate limits, dependency scanning, secrets rotation, and log redaction.
- Separate production and test data; never copy sensitive production documents into test environments.
- Log access to sensitive documents and all review/moderation actions with append-only permissions, compensating corrections, and tamper-evidence appropriate to the risk.
- Encrypt data in transit and use the platform's supported encryption at rest.
- Define and test backup, restoration, deletion, breach-response, account-recovery, RPO, and RTO procedures before the pilot.

5.3 Governance Requirements

Before launch, obtain qualified guidance on applicable Bahamian data-protection, fundraising, banking, health-information, and record-retention obligations.

Pragmatic Stage 0 path (per Principle 7): one consultation with a qualified Bahamian attorney covering (a) whether the no-custody model stays clear of payment-services regulation, (b) Data Protection Act obligations for ChipIn as controller, and (c) any registration required to operate under Traceline Bahamas Ltd. Obtain written responses; log remaining domains (health-

information handling in particular) as documented open risks to be closed before Phase 1B, which is when they first apply.

Document:

- ChipIn's controller/processor role, lawful purpose, and consent or other authority for each data category.
- Host, beneficiary, patient, guardian, and organization-representative authority and responsibilities.
- Publication rights for stories, images, documents, and organization marks.
- Retention periods for approved, rejected, abandoned, expired, disputed, and legally held records, including backups and social/search caches.
- User access, correction, export, deletion, takedown, and appeal procedures.
- Who may review medical and identity documents.
- Vendor, subprocessor, hosting, data-location, and cross-border-transfer responsibilities.
- Incident notification and regulator/contact procedures.

Retention periods remain an open legal and operational decision; they must not be invented during implementation.

6. Brand and Experience

Status: LOCKED — delivered. Authoritative reference: **DESIGN.md v1.0** (in [chipin-brand/](#)).

Identity

- **Name:** ChipIn — camel case, one word. Never "Chip In," "CHIPIN," or "Chipin."
- **Wordmark:** Dark "Chip" ([#0C1B1A](#)), aquamarine "In" ([#05A39B](#)), and a gold circular tittle ([#F2B01E](#)) over the *i*. **The tittle is the coin — the chip you drop in.** This motif is approved and central to the brand story.
- **Cultural positioning:** Bahamian pride is carried by the flag aquamarine-and-gold palette, never by clichéd iconography.
- **Tone:** Warm, communal, direct, and trustworthy; neighborly rather than institutional. Plain-language status labels are a trust control.
- **Logo variants (complete, vector, locked):** primary, reversed, monochrome ink, monochrome paper, standalone icon (light and dark tiles), and favicon/PWA set. Clear-space, minimum-size, contrast, and misuse rules are defined in [DESIGN.md](#). All type converted to outlines — no font dependency. Artwork © Traceline Bahamas Ltd.; trademark registration is an open pre-marketing action.

Design principles

- Mobile-first for WhatsApp-shared links; campaign-page performance budget for slow connections (≤ 200 KB excl. photo, LCP < 2.5 s on throttled 3G).
 - 48 px minimum touch targets.
 - Plain language and visible status labels; confirmed, pending, disputed, expired, fulfilled, and paused states distinguishable by text and icon — never color alone.
 - Optimized WhatsApp/social previews; auto-generated per-campaign OG images.
 - Printable flyer export (A5) using the monochrome mark, designed for cheap black-and-white printers.
 - Svelte scoped CSS + design-token custom properties; no utility framework. Token set, typography (Bricolage Grotesque display / Public Sans body / Space Grotesk references), spacing, status colors, signature components (including the Progress Coin-Bar and Attestation Row), motion rules, and the WCAG 2.1 AA test matrix are specified in [DESIGN.md](#).
-

7. Technical Architecture

Layer	Choice	Notes
Framework	SvelteKit	Shared team expertise and server-rendered campaign pages.
Backend/DB	Supabase	Auth, Postgres, private storage, RLS, and audit data.
Styling	Scoped CSS + custom properties	Token system per DESIGN.md §6. No utility framework.
Maps	Leaflet	Blood-bank locator after verified data sources exist.
Hosting	Vercel or equivalent	PWA-capable; final choice must support security and data-governance requirements.
Payments	None at launch	Chipln does not collect, hold, or move funds.

Core Data Model

Before schema freeze, specify the campaign lifecycle (`draft` | `submitted` | `under_review` | `active` | `paused` | `rejected` | `withdrawn` | `goal_met` | `expired` | `closed`) and a material-change matrix. Receiving-account, beneficiary, ownership, goal, and major-purpose changes require version history and risk-based re-review; receiving-account changes also require reauthentication, notifications, and a temporary pause.

- `users` — hosts, optional donors, reviewers, moderators, and administrators.
- `organizations` — legal/display identity and authorized representatives.
- `campaigns` — type, owner, goal, status, tier, verification state, expiry, and visibility.
- `pledges` — intended amount, current state, donor status token, and retention metadata.
- `transfer_reports` — reported amount, bank-generated reference, optional ChipIn code, matching status, and reconciliation result.
- `contribution_events` — append-only event history with compensating correction events and tamper-evidence requirements.
- `transfer_proofs` — private attachments and access metadata.
- `verifications` — verification type, status, reviewer, timestamps, and private document links.
- `review_decisions` — checklist results, reasons, conflicts, and appeal status.
- `moderation_cases` — reports, disputes, assignments, evidence, priority, and resolution.
- `blood_requests` — blood type, listed location, source, urgency, last validated time, expiry, and resolution.
- `blood_locations` — hours, contact information, source, owner, and last verified time.
- `notifications` — reconciliation reminders, review updates, disputes, and expiry notices.

The schema must define access policies and deletion behavior alongside the tables, not after implementation.

8. Sustainability

ChipIn will not depend on unproven day-one tips to fund operations.

1. **Funded pilot runway:** Before public intake, approve a budget, committed funding source, pilot duration, post-pilot decision period, contingency, and safe-wind-down plan covering review, moderation, support, legal, security, OTP/email, storage, insurance, retention, and incident obligations — sized to pilot caps per Principle 7.

2. **Corporate sponsorships:** Banks, insurers, telecommunications companies, and other aligned organizations may sponsor the service without controlling campaign review or outcomes.
3. **Government and NGO partnerships:** Explore blood-donation and civic-service partnerships after the pilot demonstrates reliable operations.
4. **Organizational tier:** Churches, NGOs, schools, and businesses may later pay for optional recurring campaign management and reporting tools.
5. **Optional platform support:** Introduce donor tips only as a separate future product after resolving the collection rail, merchant identity, fees, accounting, tax, receipts, refunds, chargebacks, support, fund separation, consent, and regulatory requirements.
6. **Free-use policy — LOCKED:** All personal campaigns remain free of platform fees. Organizations may later pay only for optional campaign-management and reporting tools. This policy was approved by the owner on August 3, 2026.

Sponsorship and government sales cycles may be long, so neither should be treated as immediate launch revenue.

9. Rollout Plan and Exit Criteria

Stage 0 — Pre-Build Validation (*ACTIVE*)

Complete before freezing the schema:

- **Bank/channel evidence matrix (critical path — empirical, start first):** cover major banks (RBC, Scotiabank, CIBC FirstCaribbean, Commonwealth, Fidelity, Bank of The Bahamas); same-bank and interbank paths; mobile, web, branch, scheduled, and standing-order transfers; editable memo availability; character rules; truncation/case conversion; recipient visibility; settlement timing; and bank-generated references. Small live transfers between real accounts; record what the recipient actually sees. Both outcomes are already handled: memos survive → ChipIn references; memos unreliable → approved fallback matching (amount + date range + bank reference + audited manual match).
- Decide whether ChipIn codes are contribution-level identifiers and QR links are campaign-level; define collision scope, expiry, reuse, and fallbacks. ChipIn codes cannot be the sole reconciliation method.
- Validate flows for partial transfers, one-to-many/many-to-one matching, name mismatches, organizations, disputes, and correction events.
- Obtain qualified legal guidance per §5.3 (pragmatic Stage 0 path).
- Confirm reviewer staffing, hours, escalation, and service targets at pilot scale.
- Recruit known churches, NGOs, schools, or community organizers for a controlled pilot.
- Identify reliable owners and sources for blood-bank information (Phase 1B preparation only; not a Stage 0 blocker).

Phase 1A — Monetary MVP and Controlled Pilot

Build and pilot:

- Host authentication and verification.
- Campaign creation and review.
- Campaign pages and WhatsApp-ready sharing.
- Validated reference/fallback matching and QR generation.
- Pledge, transfer-reporting, host receipt-attestation, correction, dispute, and audit flows.
- Host dashboard.
- Moderation queue and campaign controls.
- Private document storage and access logging.

Exit criteria: Before intake, publish numeric pilot caps and thresholds for maximum queue age, unresolved-case rate, host-attestation latency, reviewer utilization, and automatic intake pause. Before expansion, meet those thresholds; independently test RLS and storage policies; complete the defined threat-model test scope; and have no known unresolved severity-1 or severity-2 privacy/security findings within that assessed scope.

Phase 1B — Blood Pilot

Launch only when:

- Named institutions or official sources authorize or validate directory data and use of their names, with source timestamps and revalidation intervals.
- Request creation, approval, update, extension, fulfillment, withdrawal, unreachable-requester, guardian, and consent procedures are defined.
- Auto-expiry, stale-data suppression, and resolved states work.
- Privacy templates, re-identification review, and medical disclaimers are approved.
- Urgent review staffing, official facility instructions, escalation, and incorrect-information response are operational.
- Health-information legal guidance (deferred from Stage 0) is obtained.

Phase 2 — Community Coordination

- Volunteer coordination.
- Event and cookout workflows.
- Improved notifications.
- Organization management.

Phase 3 — Growth and Sustainability

- Donor accounts and giving history.
- Sponsor portal.
- Premium organizational tools.
- Expanded partnerships.

Phase 4 — Payments Evolution

Explore direct account-to-account or other payment integrations only after legal, licensing, security, reconciliation, refund, and dispute requirements are understood.

10. Success Measures

Monetary MVP

- Campaign review turnaround by tier and campaign risk.
- Percentage of reported transfers marked received by hosts.
- Median time from transfer report to host receipt attestation.
- Percentage of reports marked not found, partially matched, disputed, expired, corrected, or voided.
- Host workload per 100 transfer reports.
- Campaign-page-to-pledge and pledge-to-host-attested conversion.
- Report rate and moderation resolution time.
- Badge/label comprehension and rate of users who incorrectly believe ChipIn verified settlement or use of funds.
- Number and severity of privacy, security, or access-control incidents.

Blood Pilot

- Percentage of requests reviewed within the staffed urgent target.
- Percentage of requests updated, fulfilled, or expired on time.
- Stale-request rate.
- Accuracy and freshness of blood-bank directory data.
- Donor response actions without publication of unnecessary patient information.

Targets should be set from pilot baselines rather than guessed before real usage.

11. Risks and Mitigations

Risk	Mitigation
Fraudulent or misleading campaigns	Tiered host verification, risk-based campaign review, precise labels, reports, audit history, and campaign pause controls.

Risk	Mitigation
Hosts mark fake reports received to inflate totals	Require donor-originated records; rate limits and anti-automation; duplicate/contact/evidence signals; risk-based reauthentication; precise public labels; compensating void events; campaign review.
Hosts fail to reconcile real transfers	Reminders, defined waiting period, moderation cases, review queue, and visible unresolved status.
High-volume reconciliation burden	Search and filters; explicit amount/attestation per row; pilot workload measurement; no unsafe mass confirmation.
Review queue becomes a bottleneck	Pilot-scale staffing with hard intake caps (Principle 7), urgent escalation, conflict rules, and controlled pilot volume.
Sensitive data exposure	Data minimization, private storage, RLS, least privilege, access logs, retention rules, and incident procedures.
Stale blood requests cause confusion	Automatic expiry, last-updated labels, named data owner, and fulfilled/resolved states.
Verification blocks legitimate community hosts	Organization and authorized-representative paths; pilot a capped community-vouch path before adoption.
Trust deficit at launch	Use a capped pilot with an intentional mix of organization and personal campaigns, partner due diligence, sponsor/reviewer independence, label-comprehension tests, aggregate incident reporting, and published pilot limitations.
Governance overhead stalls the project	Principle 7: proportional operations; enterprise controls are expansion gates, not pilot gates.
Revenue arrives later than expected	Define runway before launch; treat sponsorship, government partnerships, and tips as later-stage revenue.

Risk	Mitigation
Users assume ChipIn protects or transfers funds	Repeated disclosure that transfers occur outside ChipIn, totals are host-attested, and ChipIn does not offer settlement verification, escrow, refunds, chargebacks, recovery, donor protection, or funds-use verification.

12. Open Decisions Before Build

Schema-blocking (must close before schema freeze):

1. Does the bank/channel evidence matrix support ChipIn references, and what are their format, level, collision, expiry, reuse, and fallback rules?
2. What are the exact pledge, transfer-report, moderation-case, and campaign transitions, actors, timers, evidence, reopening, and public-total effects?
3. How long should a transfer report remain unresolved before reminders, moderation eligibility, and closure?

Closed owner decisions:

- Proportional operations is approved as Product Principle 7 for the controlled pilot (August 3, 2026).
- All personal campaigns remain free; organizations may later pay only for optional tools (August 3, 2026).

Pilot-closeable (may close during Phase 1A with pilot evidence): 5. What evidence and re-review rules apply to joint, caregiver, treasurer, organization, trading-name, and other receiving-account relationships? 6. Should a capped, community-vouched verification path exist, and what are its limits and abuse controls? 7. Who reviews campaigns, during what hours, under what intake caps, and against which numeric service and stop thresholds? (*Pilot-scale answer required before intake; enterprise answer before expansion.*) 8. What are the approved authority, retention, deletion, backup, legal-hold, ownership, and cache rules for every data category? 9. What committed runway covers the pilot, decision period, contingency, and safe wind-down? 10. Which accessibility, threat-model, privacy, RLS/storage, upload-security, account-change, and incident checks are mandatory release gates? 11. What campaign categories and content are prohibited or restricted, and what are the takedown, appeal, age, beneficiary-authorization, legal-request, tax, and receipt policies?

Phase 1B-blocking (defer until blood pilot preparation): 12. Which hospitals or blood banks will authorize or validate directory data, disclaimers, use of names, and request procedures?

13. Next Deliverables

1. ~~DESIGN.md~~ with brand foundation, tokens, components, and accessibility matrix — **DELIVERED v1.0** (flow wireframes for transfer, attestation, dispute, and blood-request screens remain working-draft items within it).
 2. **Bank/channel evidence matrix — ACTIVE, critical path.** Test protocol, live transfer testing across bank pairs and channels, findings, and the reference-vs-fallback decision.
 3. Pledge, transfer-reconciliation, moderation-case, and campaign state-machine specification.
 4. Review, moderation, acceptable-use, takedown, and material-change operations playbook (pilot-scale per Principle 7).
 5. Data-category matrix and privacy, authority, retention, deletion, consent, ownership, audit, and document-access policy reviewed per §5.3 pragmatic path.
 6. Threat model and testable security release checklist.
 7. Supabase schema with independently tested RLS, private storage policies, event history, correction, and deletion behavior.
 8. Controlled-pilot plan with campaign mix, partners, reviewer independence, staffing, committed runway, numeric success thresholds, and stop/wind-down conditions.
-

14. Position in the FGB Pipeline

ChipIn remains part of the broader First Glance Bahamas civic-infrastructure portfolio alongside LightWatch 242 and VAULT. Shared expertise and components may reduce delivery cost, but each product retains separate privacy, security, operational, and regulatory requirements. Build-in-public activity must never expose campaign, verification, banking, medical, moderation, or incident data.

ChipIn is in **Stage 0 validation** with its brand and design foundation complete. The central hypothesis remains clear: make direct local giving easier to share and reconcile while accurately representing that ChipIn records donor reports and host attestations without taking custody of, settling, recovering, or independently verifying the money.
