Capabilities by role

What a viewer, an operator, an administrator, and the people who run the deployment can do.

Application user

Sign-in role and workspace membership are both required. A viewer who owns a workspace is still read-only.

Area	Capability
Catalog	Browse jobs, workflows, and schedules in workspaces you can see, including Platform.
Run	Operators run jobs and workflows and can read status and logs. Viewers can read the log and cannot run.
Authoring	Operators create and edit in workspaces they manage. A viewer cannot.
Schedules	Cron on a job or a workflow. Turning a job off stops new runs and refuses a manual run.
History	Search executions. Open the error and the log.
Recovery	Operators cancel queued or running work and requeue an orphan after the process is gone.
Screen	Workspace filter, search, paging, and dark, medium, or light theme.

Administrator

Area	Capability
Visibility	Every workspace, definition, and execution.
Users	Create, enable, disable, set roles, set a password, and delete local users.
Groups	Create group workspaces and assign owner, manager, or member.
Platform	Company-shared definitions. Everyone signed in can see them. Only an administrator changes them.
Agents	Register, monitor, and remove agents. Assign a pool to a workspace.
Definitions	Export jobs, workflows, and schedules. Review the plan. Apply only confirmed lines. A removal starts unchecked. History is not in the file and is not restored.
Security	Local sign-in, company SSO, or SSO only. Map identity-provider groups to roles.
API	The catalog is for administrators. Operators and the agents call the API. Viewers do not.

Systems operator

Area	Capability
Topology	Application nodes, private PostgreSQL, and agent workers. One database lease keeps a single scheduler.
Modes	Agent mode for production. Local mode runs a job inside the control plane and is for a lab.
Docker Compose	PostgreSQL, the control plane, and agents.
Kubernetes	Helm chart for the control plane, agents, and optional Postgres.
Health	Health, readiness, metrics, and a Prometheus endpoint on the application.
Mail	Optional email on failure, and optional email on success.
Artifacts	A cache directory for GIT_RELEASE downloads on the server or the agent.
Agent sign-in	Remote agents use a confidential client and a short-lived token over HTTPS. Private-network agents may use a local operator login.
Agent host	On Linux the agent refuses to start as root. Packaged containers drop extra privileges.