




Day 21



Where Can Data be Persisted?






What are Databases?

- A system for storing data independent of an application
 - Consequence: a database may be access by many different applications
- Why?
 - Impose data integrity rules
 - Control access to the data
 - Manipulate the data independent of any application
 - Queried




Relational Database



- Relational database are organized like a spreadsheet
 - A table is like a sheet - storing similar data
 - A row is a record
 - Columns for storing different categories of data pertaining to a single record
- Need to know all schema (structure of the data) before storing any data in a relational database
- Relationships may existing between tables
 - Eg. A table storing authors may have multiple records (rows) in the book table
- Standard language to query and manipulate data
 - SQL - Structured Query Language
- Tables may be joined via relationships between fields
- Supports transactions - ACID properties
 - Atomicity, Consistency, Isolation, Durability




Structure of a Database Table





Database Schema

Schema refers to the organization of data






Creating a Database

Database/schema name



```
create database leisure;
```

```
use leisure;
```



Make this the current
working database



Creating a Table

Table name

Column name

```
create table tv_shows (  
  prog_id          int          not null,  
  name             char(64)     not null,  
  lang             char(16)     not null,  
  official_site    varchar(256),  
  rating           enum('G', 'PG', 'NC16', 'M18', 'R21') not null,  
  user_rating      float default '0.0',  
  release_date     date,  
  image            blob,  
  primary key (prog_id)  
);
```


Additional properties for the column

Data type of each column

The designated column to be the primary key



tv_shows Entity Diagram





Data Types

- Define the type of data a column can store
- Some common data type
 - Numbers - int, decimal
 - Characters - char, varchar, enum
 - Time - date, timestamp
 - Large text - text
 - Binary objects - blob
 - JSON



Primary Key

- A field from a record that is used to identify that record
 - This is the field that uniquely identifies a record
 - Eg. NRIC, product code
- Properties of a primary key field
 - Cannot be null/empty
 - The value of the field must be unique
 - Once assigned a primary key value should not be changed
 - A primary key is assigned to a newly inserted record
- Can be auto generated
 - Column type must be an integer
 - Add the `auto_increment` attribute



Primary Key

- Generating primary keys
 - Get the user to provide - eg. selecting a name for your Email account
 - Get the database to generate - field must be an integer
- Can create tables without primary key
 - Eg. many to many join table


```
create table tv_shows (  
  prog_id      int(11)    not null auto_increment,  
  ...  
  primary key (prog_id)  
)
```

Auto generated
primary key





CRUD





Read - SELECT

Retrieve all the records

```
select * from tv_shows;
```

All the fields

Table name

Retrieve the first 100 record

```
select * from tv_shows limit 100;
```

Retrieve only prog_id and name fields

```
select prog_id, name from tv_shows  
limit 100 offset 1000;
```

Retrieve the first 100 record
starting from the 1000

tv_shows	
🔑	prog_id INT(11)
💎	name CHAR(64)
💎	lang CHAR(16)
💎	official_site VARCHAR(256)
💎	rating ENUM(...)
💎	user_rating FLOAT
💎	release_date DATE
💎	image BLOB
Indexes	



Reading Specific Data

Find all records whose name
is Gotham

Provide a condition
for the query

Read = as 'is'

```
select * from tv_shows where name = "Gothan";
```

tv_shows	
🔑	prog_id INT(11)
💎	name CHAR(64)
💎	lang CHAR(16)
💎	official_site VARCHAR(256)
💎	rating ENUM(...)
💎	user_rating FLOAT
💎	release_date DATE
💎	image BLOB
Indexes	

Find all records whose name
has the string bad

Match a pattern
Case insensitive

'wildcard' - any
number of characters

```
select * from tv_shows where last_name like "%bad%";
```

```
select release_date from tv_shows  
where dob > "2012-01-01" and  
dob < "2012-12-31";
```

Find all TV shows release between
Jan 01 till Dec 31 in 2012



Reading Specific Data

tv_shows	
🔑	prog_id INT(11)
💎	name CHAR(64)
💎	lang CHAR(16)
💎	official_site VARCHAR(256)
💎	rating ENUM(...)
💎	user_rating FLOAT
💎	release_date DATE
💎	image BLOB
Indexes ▶	

```
select * from tv_shows where ratings  
in ("M18", "R21");
```

ratings is matches one of
the values in the given set

```
select name from tv_shows  
where ratings not between  
"2012-01-01" and "2012-12-31";
```

The between operator
makes conditions
more English like



Logical and Comparison Operators

- Logical -
<https://dev.mysql.com/doc/refman/8.0/en/comparison-operators.html>
 - and
 - or
 - not
- Comparison -
<https://dev.mysql.com/doc/refman/8.0/en/logical-operators.html>
 - > greater than
 - < less than
 - <= greater than or equal to
 - >= less than or equal to
 - <> not equals
 - = equals



Operators Example

- Comparison operators

```
select name
from tv_shows
where release_data between "2020-01-01" and "2022-31-12";
```

Return the first non null
column for each record




tv_shows	
prog_id	INT(11)
name	CHAR(64)
lang	CHAR(16)
official_site	VARCHAR(256)
rating	ENUM(...)
user_rating	FLOAT
release_date	DATE
image	BLOB
Indexes	

- Logical operators

```
select name
from tv_shows
where user_ratings > 5 and rating in ("M18", "R21");
```




Integrating Database to Spring





Connection Pool





Connecting to MySQL

Dependencies

ADD DEPENDENCIES... CTRL + B

Spring Boot DevTools

DEVELOPER TOOLS

Provides fast application restarts, LiveReload, and configurations for enhanced development experience.

Spring Web

WEB


Build web, including RESTful, applications using Spring MVC. Uses Apache Tomcat as the default embedded container.

JDBC API

SQL

Database Connectivity API that defines how a client may connect and query a database.

Add JDBC API dependency and MySQL Connector/J (from mvnrepository.com)





Configuring JDBC Connection Pool

```
application.properties
```

JDBC database connection string

```
spring.datasource.url=jdbc:mysql://localhost:3306/leisure
```

```
spring.datasource.username=fred
```

```
spring.datasource.password=fred
```

} Database user

```
spring.datasource.hikari.connectionTimeout=30000
```

```
spring.datasource.hikari.idleTimeout=600000
```

```
spring.datasource.hikari.minimumIdle=2
```


```
spring.datasource.hikari.maximumPoolSize=8
```

} Connection pool characteristics



@Repository

- Annotates a classes as a repository
 - Indicates that these classes are at the persistent layer
- Spring provides different persistent options
 - `JdbcTemplate` - directly accessing the records and fields
 - `CrudRepository` - maps records to Java objects. Repository automatically implements CRUD operation
 - `JpaRepository` - build on JPA ORM





Example - @Repository Example

@Repository

```
public class TVShowRepository {
```

Annotate this class as a repository
(data access object)

@Autowired

```
private JdbcTemplate template;
```

Inject an instance of JdbcTemplate.
Must be configured to a specific database

```
public List<TVShow> getTvShows(final int limit, final int offset) {  
    final List<TVShow> result = new LinkedList<>();
```

```
    final SqlRowSet rs = template.queryForRowSet(  
        "select * from tv_shows limit ? offset ?", limit, offset);
```

```
    while (rs.next()) {  
        TVShow tv = new TVShow();  
        tv.setProgramId(rs.getInt("prog_id");  
        tv.setName(rs.getString("name"));  
        ...  
        result.add(tv);  
    }
```

```
    return (Collections.unmodifiableList(result));
```

```
}
```

```
}
```




Example - @Repository Example

@Repository

```
public class TVShowRepository {
```

@Autowired

```
private JdbcTemplate template;
```

```
public List<TVShow> getTvShows(final int limit, final int offset) {
```

```
    final List<TVShow> result = template.query(
```

```
        "select * from tv_shows limit ? offset ?",
```

```
        (rs, int) -> {
```

```
            TVShow tv = new TVShow();
```

```
            tv.setProgramId(rs.getInt("prog_id");
```

```
            tv.setName(rs.getString("name"));
```

```
            ...
```

```
        },
```


```
        limit, offset);
```

```
    return (Collections.unmodifiableList(result));
```

```
}
```

```
}
```

Map records to
object with
RowMapper





Performing Query with Prepared Statement

```
final SqlRowSet rs = template.queryForRowSet(  
    "select * from tv_shows limit ? offset ?", limit, offset  
);
```

```
final SqlRowSet rs = template.queryForRowSet(  
    String.format("select * from tv_shows limit %d offset %d", limit, offset")  
);
```

- Use prepared statement to construct query
 - ? as placeholder for values
- Do not use string concatenation
 - Can result in SQL injection



Performing Query with Prepared Statement

```
final float userRating = 4f;  
final String rating = "M18";
```

```
final SqlRowSet rs = template.queryForRowSet(  
    "select * from tv_shows where user_rating > ? and rating = ?"  
    , userRating, rating  
);
```

user_rating is float in the schema
rating is char in the schema

Parameters for the prepared statement
are float and string respectively

- Use the correct type for the prepared statement's parameters
- Might get error or unexpected result



Reading the Result

- `SqlRowSet` holds the result from a `queryForRowSet()`
- Navigating
 - `next()` - moves the cursor to the next record,
 - Returns true if the next record exists, false otherwise; end of results
 - Must call `next()` before reading the first record
 - `previous()` - moves the cursor back a record, returns boolean as per `next()`
- Reading fields from record with `get<data type>(<column name>)`
 - Eg. `rs.getString("email")` - returns the value in email field of the current record
 - Will return unexpected data or throws exception if read with incorrect data type
- `SqlRowSet` holds the data in memory, can cause the JVM to throw `OutOfMemoryException` if may request holding large `SqlRowSet`



Example - Iterating over the Result

Return a RowSet object to hold the result

Prepared SQL statement with parameters

```
final SqlRowSet rs = template.queryForRowSet(  
    "select * from tv_shows limit ? offset ?", limit, offset);
```

Iterate through the row set

```
while (rs.next()) {  
    TVShow tv = new TVShow();  
    tv.setProgramId(rs.getInt("prog_id"));  
    tv.setName(rs.getString("name"));  
    ....  
}
```

Use the appropriate `getXXX()` method to read the fields

Instantiate an instance of the table's object - to hold the record (data transfer object)



Three Tier Application


Presentation tier

The top-most level of the application is the user interface. The main function of the interface is to translate tasks and results to something the user can understand.




Logic tier

This layer coordinates the application, processes commands, makes logical decisions and evaluations, and performs calculations. It also moves and processes data between the two surrounding layers.



Data tier

Here information is stored and retrieved from a database or file system. The information is then passed back to the logic tier for processing, and then eventually back to the user.



@Controller
@RestController

@Service

@Repository



Handling a Request - Controller

GET [/tvshow/1](#)

GET [/tvshow/2](#)

@RestController

```
@RequestMapping(path="/tvshow" , produces=MediaType.APPLICATION_JSON_VALUE)
public class TvShowController {
    @Autowired private TVShowService tvSvc;

    @GetMapping("/{tvId}")
    public ResponseEntity<String> getBook(@PathVariable Integer tvId) {
        Optional<TVShow> opt = tvSvc.findShowById(tvId);

        if (opt.isEmpty())
            return ResponseEntity.status(404).body(
                Json.createObjectBuilder().add("message", "Cannot find " + tvId)
                    .build().toString());

        return ResponseEntity.ok(opt.get().toJSON().toString());
    }
}
```



Handling a Request - Service

@Service

```
public class TVShowServie {  
    @Autowired  
    private TVShowRepository tvShowRepo;  
  
    public Optional<TVShow> findShowById(final Integer tvId) {  
        SqlRowSet rs = tvShowRepo.get(tvId);  
        if (rs.first())  
            return Optional.of(TVShow.populate(rs));  
        return Optional.empty();  
    }  
}
```

Can return TVShow or SqlRowSet

The latter provider more flexibility at the expense
of 'leaky abstraction' but more flexible

https://en.wikipedia.org/wiki/Leaky_abstraction



Handling a Request - Repository

@Repository

```
public class TVShowRepository {  
    @Autowired  
    private JdbcTemplate template;  
  
    public SqlRowSet get(final Integer tvId) {  
        return template.queryForRowSet(  
            "select * from tv_shows where prog_id = ?", tvId);  
    }  
}
```



Handling a Request - Data Transfer Object

```
public class TVShow {  
    private String tvId;  
    private String name;  
    ...  
  
    // getter and setters  
    public String getTVId() { return tvId; }  
    public void setTVId(String id) { tvId = id; }  
    ...  
  
    public static TVShow populate(SqlRowSet rs) {  
        final TVShow tv = new TVShow();  
        tv.setTVId(rs.getString("prog_id"));  
        tv.setName(rs.getString("name"));  
        ...  
        return (tv);  
    }  
}
```