

Chapter recap

Last updated April 2026

Congratulations on completing the Strings I chapter. We will dive deeper into strings in a future chapter, for now, make sure to review the key concepts from this chapter before we move on to the next one!

This is your first chapter recap! You can save it to your notes by clicking on the + icon on the top-right of the recap.

Fun story: Did you know why we use the words bug and debug in programming?

The term *bug* was actually engineering slang for glitches long before computers existed; Thomas Edison used it in his technical notes as early as the 1870s.

However, the word became legendary in computing in 1947. Operators on Grace Hopper's team at Harvard found an actual moth trapped in a relay of the Harvard Mark II computer. They taped the insect into their logbook with the caption: "First actual case of bug being found."

While they didn't invent the word, their literal *debugging* session turned an old engineering joke into a permanent part of programming history. Every time you fix your code today, you're participating in a tradition that's over 150 years old!

Chapter Recap

- You can create strings with " or '.
- **.length** is a property that gives you the length of a string.
- **.toUpperCase()** is a function that converts the string to upper case.
- **.toLowerCase()** is a function that converts the string to lower case.
- parentheses () on function calls are required. **.length** is a property that is already pre-computed; therefore, it does not need parentheses.
- **console.log(...)** is used for debugging and is NOT a replacement for **return**.
- Square brackets [index] are used to access a specific index from a string.
- The index starts at 0. So the first character is index 0.



- The `.at()` method allows you to read a character at an index (which can also be negative).
- A substring is a part or a portion of a string.
- `string.substring(indexStart, indexEnd)` is used to return a portion of the string.
- **indexStart**: the position of the first character you'd like to **include**.
- **indexEnd**: the position of the first character you'd like to **ignore**.
- the **indexEnd** argument is optional which means you can leave it out.
- The `+` operator is used to add 2 numbers
- The `+` operator is used to concatenate 2 strings
- A template string is a string created with the backtick character: ```
- Template strings can span multiple lines
- Template strings support interpolation with the `${variableName}` syntax

Was this helpful?

