

Chap 5. Trees (2)

Contents

5.1 Introduction

5.2 Binary Trees

5.3 Binary Trees Traversals

5.4 Additional Binary Tree Operations

5.6 Heaps

5.7 Binary Search Trees

5.4 Additional Binary Tree Operations

5.4.1 Copying Binary trees

- A slightly modified version of *postorder* traversal


```
treePointer copy(treePointer original)
{
    /* this function returns a treePointer to an exact copy
       of the original tree */
    treePointer temp;
    if (original) {
        MALLOC(temp, sizeof(*temp));
        temp->leftChild = copy(original->leftChild);
        temp->rightChild = copy(original->rightChild);
        temp->data = original->data;
        return temp;
    }
    return NULL;
}
```

Program 5.6: Copying a binary tree

```

treePointer copy(treePointer original)
{
    treePointer temp;
    if (original) {
        MALLOC(temp, sizeof(*temp));
        temp→leftChild = copy(original→leftChild); L
        temp→rightChild = copy(original→rightChild); R
        temp→data = original→data; V
        return temp;
    }
    return NULL;
}

```



5.4.2 Testing Equality

- Determining the equivalence of two binary trees
- Equivalent binary trees have the *same structure* and the *same information* in the corresponding nodes.
- A modification of *preorder* traversal

```
int equal(treePointer first, treePointer second)
{ /* function returns FALSE if the binary trees first and
   second are not equal, Otherwise it returns TRUE */
  return ((!first && !second) || (first && second &&
    (first->data == second->data) &&
    equal(first->leftChild, second->leftChild) &&
    equal(first->rightChild, second->rightChild)));
}
```


Program 5.7: Testing for equality of binary trees

```

int equal(treePointer first, treePointer second)
{
    /* function returns FALSE if the binary trees first and
       second are not equal, Otherwise it returns TRUE */
    return ((!first && !second) || (first && second &&
        (first->data == second->data) &&
        equal(first->leftChild, second->leftChild) &&
        equal(first->rightChild, second->rightChild)));
}

```

V
L
R



5.4.3 The Satisfiability Problem

- Consider the set of formulas from $\{x_1, \dots, x_n\}$ and $\{\wedge$ (and), \vee (or), \neg (not) $\}$
- The *variables* are *Boolean variables*
 - Have only two possible values, *true* or *false*
- Set of expressions are defined by the following rules
 - A variable is an expression
 - If x and y are expression, then $\neg x$, $x \wedge y$, $x \vee y$ are expressions
 - Parentheses can be used to alter the normal order of evaluation
- Propositional calculus: $x_1 \vee (x_2 \wedge \neg x_3)$
 - If x_1 and x_3 are *false* and x_2 is *true*, it is *true*

- *The satisfiability problem*
 - Is there an assignment of values to the variables that causes the value of the expression to be true?
- The most obvious algorithm
 - let (x_1, \dots, x_n) take on *all possible combinations of true and false values* and to check the formula for each combination
 - $O(g2^n)$, or exponential time, where g is the time to substitute values for x_1, x_2, \dots, x_n and evaluate the expression.
 - *Postorder* evaluation

- $(x_1 \wedge \neg x_2) \vee (\neg x_1 \wedge x_3) \vee \neg x_3$




Figure 5.18: Propositional formula in a binary tree

For $n = 3$,

All possible combinations :

(true, true, true)

(true, true, false)

(true, false, true)

(true, false, false)

(false, true, true)

(false, true, false)

(false, false, true)

(false, false, false)

```

typedef enum {not,and,or,true,false} logical;
typedef struct node *treePointer;
typedef struct node {
    treePointer leftChild;
    logical      data;    // the value of a variable or an operator
    short int     value;  // TRUE/FALSE
    treePointer rightChild;
} node;

```

<i>leftChild</i>	<i>data</i>	<i>value</i>	<i>rightChild</i>
------------------	-------------	--------------	-------------------

```

for (all  $2^n$  possible combinations) {
    generate the next combination;
    replace the variables by their values;
    evaluate root by traversing it in postorder;
    if (root→value) {
        printf(<combination>);
        return;
    }
}
printf("No satisfiable combination\n");

```

Program 5.8: First version of satisfiability algorithm

```

void postOrderEval(treePointer node)
{ /* modified post order traversal to evaluate a
   propositional calculus tree */
  if (node) {
    postOrderEval(node→leftChild);
    postOrderEval(node→rightChild);
    switch(node→data) {
      case not:   node→value =
                  !node→rightChild→value;
                  break;
      case and:   node→value =
                  node→rightChild→value &&
                  node→leftChild→value;
                  break;
      case or:    node→value =
                  node→rightChild→value ||
                  node→leftChild→value;
                  break;
      case true:  node→value = TRUE;
                  break;
      case false: node→value = FALSE;
    }
  }
}

```



not/and/or in the data field
of non-leaf nodes

true/false in the data field
of leaf nodes, x_1 , x_2 , and x_3

```

void postOrderEval(treePointer node)
{ /* modified post order traversal to evaluate a
   propositional calculus tree */
  if (node) {
    postOrderEval(node->leftChild); L
    postOrderEval(node->rightChild); R
    switch(node->data) { V
      case not:  node->value =
        !node->rightChild->value;
        break;
      case and:  node->value =
        node->rightChild->value &&
        node->leftChild->value;
        break;
      case or:   node->value =
        node->rightChild->value ||
        node->leftChild->value;
        break;
      case true: node->value = TRUE;
        break;
      case false: node->value = FALSE;
    }
  }
}


```



```

void postOrderEval(treePointer node)
{/* modified post order traversal to evaluate a
   propositional calculus tree */
  if (node) {
    postOrderEval(node->leftChild); L
    postOrderEval(node->rightChild); R
    switch(node->data) { V
      case not:  node->value =
        !node->rightChild->value;
        break;
      case and:  node->value =
        node->rightChild->value &&
        node->leftChild->value;
        break;
      case or:   node->value =
        node->rightChild->value ||
        node->leftChild->value;
        break;
      case true: node->value = TRUE;
        break;
      case false: node->value = FALSE;
    }
  }
}

```



ex) for a combination
 $(x_1, x_2, x_3) = (true, false, true)$

5.6 Heaps

5.6.1 Priority Queues

- *Priority queues*
 - *deletion*: deletes the element with the highest(or the lowest) priority
 - *insertion* : insert an element with arbitrary priority
(ex: job scheduling in OS)
- We use *max(min) heap* to implement the priority queues

ADT *MaxPriorityQueue* is

objects: a collection of $n > 0$ elements, each element has a key

functions:

for all $q \in \text{MaxPriorityQueue}$, $item \in \text{Element}$, $n \in \text{integer}$

MaxPriorityQueue $\text{create}(\text{max_size}) \quad ::= \quad \text{create an empty priority queue.}$

Boolean $\text{isEmpty}(q, n) \quad ::= \quad \text{if } (n > 0) \text{ return } \textit{FALSE}$
else return *TRUE*

Element $\text{top}(q, n) \quad ::= \quad \text{if } (!\text{isEmpty}(q, n)) \text{ return an instance}$
of the largest element in q
else return error.

Element $\text{pop}(q, n) \quad ::= \quad \text{if } (!\text{isEmpty}(q, n)) \text{ return an instance}$
of the largest element in q and
remove it from the heap **else return** error.

MaxPriorityQueue $\text{push}(q, \text{item}, n) \quad ::= \quad \text{insert } \textit{item} \text{ into } q \text{ and return the}$
resulting priority queue.

ADT 5.2: Abstract data type *MaxPriorityQueue*

5.6.2 Definition of a Max Heap

- **Definition :**

- A *max tree* is a tree in which the key value in each node is no smaller than the key values in its children (if any). *parent's key \geq children's keys*
- A *max heap* is a complete binary tree that is also a max tree

- **Definition :**

- A *min tree* is a tree in which the key value in each node is no larger than the key values in its children (if any). *parent's key \leq children's keys*
- A *min heap* is a complete binary tree that is also a min tree.




Figure 5.25: Max heaps





Figure 5.26: Min heaps

5.6.3 Insertion into a Max Heap



(a)
Insert(1)/
Insert(5)/
Insert(21)
↓
?

Figure 5.27: Insertion into a max heap

```

#define MAX_ELEMENTS 200 /* maximum heap size+1 */
#define HEAP_FULL(n) (n == MAX_ELEMENTS-1)
#define HEAP_EMPTY(n) (!n)
typedef struct {
    int key;
    /* other fields */
} element;
element heap[MAX_ELEMENTS];
int n = 0;



---


void push(element item, int *n)
{
    /* insert item into a max heap of current size *n */
    int i;
    if (HEAP_FULL(*n)) {
        fprintf(stderr, "The heap is full. \n");
        exit(EXIT_FAILURE);
    }
    i = ++(*n);
    while ((i != 1) && (item.key > heap[i/2].key)) {
        heap[i] = heap[i/2];
        i /= 2;
    }
    heap[i] = item;
}


```

Program 5.13: Insertion into a max heap

current size

n 5

	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]
heap	-	20	15	2	14	10		...






push(5, &n)



current size


n 6



current size

n 5

	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]
heap	-	20	15	2	14	10		...







push(21, &n)



current size

n 6



- Analysis of *push*
 - the height of heap with n elements : $\lceil \log_2(n+1) \rceil$
 - while loop is iterated $O(\log_2 n)$ times
 - time complexity: $O(\log_2 n)$

5.6.4 Deletion from a Max heap




Figure 5.27 (d)

delete() →




Figure 5.28 (a)

```


element pop(int *n)
{
    /* delete element with the highest key from the heap */
    int parent, child;
    element item, temp;
    if (HEAP_EMPTY(*n)) {
        fprintf(stderr, "The heap is empty\n");
        exit(EXIT_FAILURE);
    }
    /* save value of the element with the highest key */
    item = heap[1];
    /* use last element in heap to adjust heap */
    temp = heap[(*n)--];
    parent = 1;
    child = 2;
    while (child <= *n) {
        /* find the larger child of the current parent */
        if ((child < *n) && (heap[child].key < heap[child+1].key))
            child++;
        if (temp.key >= heap[child].key) break;
        /* move to the next lower level */
        heap[parent] = heap[child];
        parent = child;
        child *= 2;
    }
    heap[parent] = temp;
    return item;
}

```

current size

n 6

	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]
heap	-	21	15	20	14	10	2	...




pop(&n)




current size

n 5


item 21 temp 2




item 21




item 21



item 21




item 21



current size

n 5

	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]
heap	-	20	15	2	14	10	...	




pop(&n)




current size

n 4


item 20
temp 10




item 20




item 20




item 20




item 20



item 20



item 20



child

- Analysis of *pop*
 - the height of heap with n elements : $\lceil \log_2(n+1) \rceil$
 - while loop is iterated $O(\log_2 n)$ times
 - time complexity: $O(\log_2 n)$

5.7 Binary Search Trees

5.7.1 Definition

ADT Dictionary is

objects: a collection of $n > 0$ pairs, each pair has a key and an associated item

functions:

for all $d \in \text{Dictionary}$, $item \in \text{Item}$, $k \in \text{Key}$, $n \in \text{integer}$

Dictionary Create(*max_size*) ::= create an empty dictionary.

Boolean IsEmpty(*d*, *n*) ::= if ($n > 0$) return *FALSE*

else return *TRUE*

Element Search(*d*, *k*) ::= return item with key *k*,
return NULL if no such element.

Element Delete(*d*, *k*) ::= delete and return item (if any) with key *k*;


void Insert(*d*, *item*, *k*) ::= insert *item* with key *k* into *d*.

ADT 5.3: Abstract data type *dictionary*


- With a *binary search tree*, these functions can be performed both
 - By key value : eg. delete the element with key *x*
 - By rank : eg. delete the fifth smallest element
- search, insert, delete : $O(h)$, where h is the height of the BST.

Definition: A *binary search tree* is a binary tree. It may be empty. If it is not empty then it satisfies the following properties:

- (1) Each node has exactly one key and the keys in the tree are distinct.
- (2) The keys (if any) in the left subtree are smaller than the key in the root.
- (3) The keys (if any) in the right subtree are larger than the key in the root.
- (4) The left and right subtrees are also binary search trees. \square




(a)



(b)

BST



(c)

BST

Figure 5.29: Binary trees

5.7.2 Searching a Binary Search Tree


```
typedef int iType;
typedef struct{
    int key;
    iType item;
}element;

typedef struct node *treePointer;
typedef struct node{
    element data;
    treePointer leftChild, rightChild;
}node;
```

```
element* search(treePointer root, int k )
{ /* return a pointer to the element whose key is k, if
   there is no such element, return NULL. */
① if (!root) return NULL;
② if (k == root->data.key) return &(root->data);
③ if (k < root->data.key)
    return search(root->leftChild, k);
④ return search(root->rightChild, k);
}
```

Program 5.15: Recursive search of a binary search tree

- ① the search is unsuccessful
- ② the search terminates successfully
- ③ search the left subtree of the root
- ④ search the right subtree of the root




```
element* iterSearch(treePointer tree, int k)
{
    /* return a pointer to the element whose key is k, if
       there is no such element, return NULL. */
    while (tree) {
        if (k == tree->data.key) return &(tree->data);
        if (k < tree->data.key)
            tree = tree->leftChild;
        else
            tree = tree->rightChild;
    }
    return NULL;
}
```


Program 5.16: Iterative search of a binary search tree

- Time complexity of *search* and *iterSearch*:
 - Average case : $O(h)$, where h is the height of the BST
 - Worst case : $O(n)$ for skewed binary tree

5.7.3 Inserting into a Binary Search Tree



(a) insert 80



(b) insert 35

```

void insert(treePointer *node, int k, itemType theItem)
{
    /* if k is in the tree pointed at by node do nothing;
       otherwise add a new node with data = (k, theItem) */
    treePointer ptr, temp = modifiedSearch(*node, k);
    if (temp || !(*node)) {
        /* k is not in the tree */
        MALLOC(ptr, sizeof(*ptr));
        ptr->data.key = k;
        ptr->data.item = theItem;
        ptr->leftChild = ptr->rightChild = NULL;
        if (*node) /* insert as child of temp */
            if (k < temp->data.key) temp->leftChild = ptr;
            else temp->rightChild = ptr;
        else *node = ptr; /* insert into empty BST */
    }
}

```

Program 5.17: Inserting a dictionary pair into a bi





Figure 5.30: Inserting into a binary search tree

- function call *modifiedSearch(*node, k)*
 - Searches the BST **node* for the key *k*
 - A slightly modified version of *iterSearch*



```
if the BST is empty or k is present
    return NULL
else
    return the pointer to the last node of the tree
           that was encountered during the search
```

- Analysis of *insert*
 - *modifiedSearch*: $O(h)$, the remaining part : $\Theta(1)$
 - Overall time complexity : $O(h)$




5.7.4 Deletion from a Binary Search Tree

- Deletion from BST
 - (1) Deletion of a *leaf* node
 - (2) Deletion of a *nonleaf* node with one child
 - (3) Deletion of a *nonleaf* node with two children




Deletion of the
node with key 35 ?

5 ?



25 ?




30 ?

- Time complexity: $O(h)$


- Deletion from BST

- (1) Deletion of a *leaf* node



(a) delete 35


- (2) Deletion of a *nonleaf* node with one child



(b) delete 5

- Deletion from BST



(3) Deletion of a *nonleaf* node with two children





(c) delete 25

- Deletion from BST

(3) Deletion of a *nonleaf* node with two children



or




(d) delete 30

- Deletion from BST

(3) Deletion of a *nonleaf* node with two children

- how to find the successor node



(e) delete 18

5.7.5 Height of a Binary Search Tree

- The height of a BST can become as large as n .
 - $O(\log_2 n)$ on average
 - $O(n)$ on the worst case.
- Balanced Search Trees
 - Worst case height : $O(\log_2 n)$
 - Searching, insertion, or deletion is bounded by $O(h)$, where h is the height of a binary tree
 - Ex) AVL tree, 2-3 tree, red-black tree