Ansible for #NetworkAutomation

Josh VanDeraa

2019-09

Session Overview

Session Overview

At the end of this session you will be able to:

Session Overview

At the end of this session you will be able to:

- Review the playbook management keys and values *vars*, *connection*, *hosts*, *etc*

Session Overview

At the end of this session you will be able to:

- Review the playbook management keys and values
  vars, *connection*, *hosts*, *etc*
- Update the Ansible config file for a project with common values

Session Overview

At the end of this session you will be able to:

- Review the playbook management keys and values
  vars, *connection*, *hosts*, *etc*
- Update the Ansible config file for a project with common values
- Gather data from various devices *IOS*, *NXOS*, *Juniper*, *etc*

Session Overview

At the end of this session you will be able to:

- Review the playbook management keys and values
  vars, *connection*, *hosts*, *etc*
- Update the Ansible config file for a project with common values
- Gather data from various devices *IOS*, *NXOS*, *Juniper*, *etc*
- Use regex to parse data from a command with data gathered

Network Diagram



Video Test

Playbook Management Key Values

All Ansible playbooks are defined within YAML format. Leveraging key/value pair assignments. We will take a look at some common keys used, and what their corresponding value looks like.

```
- name: "PLAY 1: Gather data from router"
  connection: network_cli
  hosts: r1
  become: true
  become_method: enable
```

Gathering Data from Cisco IOS Devices

There are two methods to gather data from IOS devices, using:

Gathering Data from Cisco IOS Devices

There are two methods to gather data from IOS devices, using:

- **ios_command**

Gathering Data from Cisco IOS Devices

There are two methods to gather data from IOS devices, using:

- **ios_command**
- **cli_command**

IOS_COMMAND

This is used when working with Cisco IOS devices connecting with SSH.