

# INF5620 — Project 2

## 2D Wave Equation

Emilie Fjørner  
`e.s.fjorner@fys.uio.no`

Jonas van den Brink  
`j.v.d.brink@fys.uio.no`

October 23, 2013

### Description

## Partial Differential Equation

The PDE we will be solving has the following form,

$$\frac{\partial^2 u}{\partial t^2} + b \frac{\partial u}{\partial t} = \frac{\partial}{\partial x} \left( q(x, y) \frac{\partial u}{\partial x} \right) + \frac{\partial}{\partial y} \left( q(x, y) \frac{\partial u}{\partial y} \right) + f(x, y, t).$$

This is a two-dimensional, standard, linear wave equation, with damping. Here  $q(x, y) = c^2$  is the wave velocity, which is generally a field. The constant  $b$ , is a damping factor, and  $f(x, y, t)$  is a source term that will be used to verify our solver.

We solve the equation on the spatial domain  $\Omega = [0, L_x] \times [0, L_y]$ , with a Neumann boundary condition

$$\frac{\partial u}{\partial n} = 0,$$

here  $\partial/\partial n$  denotes the directional derivative out of the domain at the boundary.

Our PDE also has the initial conditions

$$u(x, y, 0) = I(x, y), \quad u_t(x, y, 0) = V(x, y).$$

## Discretizing the PDE

We discretize both the temporal domain  $[0, T]$ , and both spatial dimensions, using uniform meshes. This means we define mesh points

$$\begin{aligned} x_i &= i\Delta x, \text{ for } i = 0, \dots, N_x, \\ y_j &= j\Delta y, \text{ for } j = 0, \dots, N_y, \\ t_n &= n\Delta t, \text{ for } n = 0, \dots, N_t. \end{aligned}$$

We now evaluate our PDE in the point  $(x_i, y_j, t_n)$  and introduce the shorthand notation

$$u_{i,j}^n \equiv u(x_i, y_j, t_n).$$

We will use central difference approximations for the time derivatives, meaning we have

$$\left[ \frac{\partial u}{\partial t} \right]^n \approx \frac{u^{n+1} - 2u^n + u^{n-1}}{\Delta t^2} = \left[ D_t D_t u \right]^n,$$

and

$$b \frac{\partial u}{\partial t} \approx b \frac{u^{n+1} - u^{n-1}}{2\Delta t} = \left[ D_{2t} u \right]^n.$$

For the spatial derivatives, we first approximate the outer derivative using a central difference, we first introduce  $\phi \equiv q \partial u / \partial x$ , and find

$$\frac{\partial \phi}{\partial x} \approx \frac{\phi_{i+\frac{1}{2}} - \phi_{i-\frac{1}{2}}}{\Delta x} = [D_x \phi]_i.$$

where we approximate  $\phi_{i+\frac{1}{2}}$  and  $\phi_{i-\frac{1}{2}}$ , using a central difference yet again

$$\phi_{i+\frac{1}{2}} = q_{i+\frac{1}{2}} \left[ \frac{\partial u}{\partial x} \right]_{i+\frac{1}{2}} \approx q_{i+\frac{1}{2}} \frac{u_{i+1} - u_i}{\Delta x} = [q D_x u]_{i+\frac{1}{2}}.$$

$$\phi_{i-1} = q_{i-\frac{1}{2}} \left[ \frac{\partial \phi}{\partial x} \right]_{i-\frac{1}{2}} \approx q_{i-\frac{1}{2}} \frac{u_i - u_{i-1}}{\Delta x} = [q D_x u]_{i-\frac{1}{2}}.$$

If we have access to a continuous  $q$ , evaluating  $q$  in  $x_{i+\frac{1}{2}}$  is no problem, but we would also like to be able to use a discretized  $q$  known only in the mesh points, so we approximate  $q_{i+\frac{1}{2}}$  using an arithmetic mean

$$q_{i+\frac{1}{2}} \approx \frac{q_{i+1} + q_i}{2}, \quad q_{i-\frac{1}{2}} \approx \frac{q_i + q_{i-1}}{2}.$$

Inserting this, we have

$$\left[ \frac{\partial}{\partial x} \left( q \frac{\partial u}{\partial x} \right) \right]_i \approx \frac{1}{2\Delta x^2} \left[ (q_{i+1} + q_i)(u_{i+1} - u_i) + (q_{i-1} + q_i)(u_{i-1} - u_i) \right].$$

And we just the exact same approximation for the other spatial derivative.

Our discrete equation then becomes

$$[D_t D_t u + b D_{2t} u = D_x \bar{q}^x D_x u + D_y \bar{q}^y D_y u + f]_{i,j}^n.$$

Which written out and solved for  $u_{i,j}^{n+1}$  gives the following numerical scheme

$$\begin{aligned} u_{i,j}^{n+1} = & \left( \frac{2}{2 + b\Delta t} \right) \left[ 2u_{i,j}^n - \left( 1 - \frac{b\Delta t}{2} \right) u_{i,j}^{n-1} \right. \\ & + \frac{h_x}{2} \left( (q_{i+1,j} + q_{i,j})(u_{i+1,j}^n - u_{i,j}^n) + (q_{i-1,j} + q_{i,j})(u_{i-1,j}^n - u_{i,j}^n) \right) \\ & + \frac{h_y}{2} \left( (q_{i,j+1} + q_{i,j})(u_{i,j+1}^n - u_{i,j}^n) + (q_{i,j-1} + q_{i,j})(u_{i,j-1}^n - u_{i,j}^n) \right) \\ & \left. + \Delta t^2 f(x_i, y_j, t_n) \right], \end{aligned}$$

where  $h_x = \Delta t^2 / \Delta x^2$ .

## Testing the solver using constant solution

To test the solver, we try implementing a constant solution

$$u_e = C = \text{const.},$$

by inserting this solution into our discrete equation, we see that the source term vanishes

$$f(x, y, t) = 0.$$