Adaptive Bitmask Protocols:
Sub-10ms Coordination for 1000+ Agent Systems

Harry Jiang
Technical Research Draft — Version 3.3.5
February 2026

Abstract

Multi-agent systems (MAS) scaling beyond $N > 10^3$ encounter a dual bottleneck: quadratic coordination complexity and prohibitive bandwidth costs from rich state communication. We present an architecture enabling $O(N)$ coordination with deterministic sub-10 ms latency through *semantic bitmask encoding*.

Our design adapts semantic hashing to dynamic, stateful agent coordination, coupling: (1) **64-bit feature encoding** with frequency-based schema pruning; (2) **bicameral control/data separation** using Model Context Protocol (MCP) for asynchronous schema consensus and gRPC for synchronous transport; and (3) **hierarchical weighted arbitration** for decision synthesis under uncertainty.

We present two architectural variants: a *general-purpose* 4-layer design for bandwidth-constrained distributed systems, and a *financial trading* 5-layer design incorporating pattern detection for alpha generation. Comprehensive stress testing across $N = 10$ to $N = 5000$ agents demonstrates 85× payload reduction (24 bytes vs. 2 KB), 8.2 ms p99 decision latency at prototype scale, and 100% decision agreement between full-state and compressed encodings across all four market regimes. Information-theoretic analysis reveals 37.23 bits of feature entropy against 64-bit capacity (58.2% utilization), with 10.97 bits of joint pattern entropy exploitable for extreme compression. Scale testing identifies coordinator saturation at $N \approx 600$ under single-threaded aggregation ($\rho > 1.0$), motivating sharded coordination as a required production optimization.

Keywords: multi-agent coordination, semantic compression, bitmask protocols, low-latency communication, scalable consensus, financial trading systems

1 Introduction

1.1 The Coordination Bottleneck at Scale

Contemporary multi-agent systems built on large language models (LLMs) face a critical scaling threshold. As agent populations grow—whether trading bots, robotic swarms, IoT sensor networks, or distributed reasoning systems—coordination complexity grows as $O(N^2)$ in fully connected topologies, and even modest hierarchies incur bandwidth costs that dominate operational budgets.

Consider a 1000-agent system where each agent communicates state via natural language:

1. **NL state message:** 10–20 tokens (≈2 KB with headers)
2. **Per-round bandwidth:** $1000 \times 2\text{KB} = 2\text{MB}$
3. **At 100 Hz coordination:** 200 MB/s sustained, prohibitive for cross-region deployment and costly on cloud egress ($0.01–0.09/GB)

Semantic compression alternative: Encode state as 64-bit bitmasks (24 bytes with metadata) $\Rightarrow$ 85$\times$ reduction, enabling $O(N)$ bandwidth scaling and sub-10 ms coordination rounds.

This bottleneck is *domain-agnostic*. We validate across two distinct application contexts:

Financial Trading 1000+ LLM-based trading agents (market makers, risk monitors, compliance bots) coordinating market decisions with regulatory latency constraints

Robotic Swarm Coordination 1000+ autonomous units (drones, warehouse robots) coordinating spatial navigation and task allocation

1.2 Domain Constraints and Design Requirements

While our architecture generalizes, we ground design decisions in concrete requirements from financial trading, where constraints are most acute:

Latency bound Sub-50 ms end-to-end for regulatory compliance; sub-10 ms for competitive advantage

Bandwidth cost Minimize cross-AZ/cloud egress fees

Interpretability Human-auditable decision rationale (regulatory requirement in finance)

Dynamic schema Agent capabilities evolve; feature vocabularies expand

Fault tolerance Graceful degradation under partition, not catastrophic failure

Robotic applications relax latency to sub-100 ms but add strict requirements for spatial consistency and safety-critical feature preservation.

1.3 System Contributions

We describe an integrated architecture comprising:

1. **Semantic bitmask encoding** (Section 3), adapting Salakhutdinov and Hinton's semantic hashing [1] to real-time, stateful coordination with dynamic schema evolution and collision-aware pruning.
2. **Bicameral control/data separation** (Section 5), using MCP [2] for asynchronous schema consensus and gRPC for synchronous $O(N)$ bitmask transport in a star-hub topology.
3. **Dual architectural variants** (Section 4): a streamlined 4-layer design for general coordination, and an extended 5-layer design with pattern detection for financial alpha generation.
4. **Hardware and domain analysis of the 64-bit constraint** (Section 3.1), presenting both hardware-justified (atomic operations, cache lines) and domain-optimized (frequency pruning, variable-width extensions) perspectives.
5. **Information-theoretic analysis** (Section 7), quantifying Shannon entropy of feature activations, encoding efficiency, and exploitable redundancy through pairwise mutual information.
6. **Comprehensive stress testing** (Section 8), including scale analysis from $N = 10$ to $N = 5000$, regime-aware decision quality measurement, latency floor decomposition, and identification of the coordinator saturation boundary.

Scope. This work integrates established techniques into a unified system targeting a specific complexity class: bandwidth-constrained coordination of 10^2–10^4 semantic agents with millisecond latency requirements. We make no claims of fundamental algorithmic novelty; rather, we demonstrate architectural feasibility, quantify theoretical limits, and identify productionization requirements.

2 Background and Related Work

2.1 Semantic Compression

Semantic Hashing. Salakhutdinov and Hinton [1] demonstrated that binary codes can preserve semantic similarity for document retrieval, where Hamming distance approximates cosine similarity in embedding space. Their approach learns static codes for fixed corpora.

Our work adapts this encoding principle to *dynamic* agent states: features activate and deactivate in real-time, requiring continuous schema consensus and deterministic (not learned) mapping to enable auditability. The collision properties we analyze (Section 3.4) are inherent to our fixed-width constraint, not optimization objectives as in semantic hashing.

Feature Hashing. Weinberger et al. [5] introduced the "hashing trick" for high-dimensional machine learning, accepting random collisions for computational efficiency. Our protocol differs fundamentally: we require *reversible, deterministic* feature-to-bit mapping with explicit collision avoidance through schema pruning, as agent coordination requires exact (not approximate) state reconstruction.

2.2 Multi-Agent Communication

Learned Communication. Foerster et al.'s DIAL [3] and Sukhbaatar et al.'s CommNet [4] introduced differentiable communication channels for multi-agent reinforcement learning. These systems *learn what to communicate* through backpropagation, enabling emergent protocols.

Our agents use fixed LLM-based policies; communication compression is *architectural*, not learned. This trades flexibility for determinism: we guarantee bounded latency and interpretable messages, whereas learned protocols may converge to opaque encodings. The trade-off is appropriate for domains (finance, robotics) requiring audit trails and safety guarantees.

Hierarchical Coordination. Star-hub and layered topologies are well-established in swarm robotics [6] and distributed computing [7]. IBM's recent hierarchical MAS architecture [7] similarly uses layered coordination for complexity management.

Our contribution is the *application* of these patterns to bandwidth-constrained semantic agents, coupling hierarchical topology with aggressive semantic compression. The integration of MCP for schema management and gRPC for transport is, to our knowledge, novel in this context.

2.3 Low-Latency Infrastructure

High-frequency trading systems traditionally avoid LLMs due to inference latency ($> 100\,\text{ms}$). Recent work on quantized, edge-deployed models enables sub-10 ms inference through weight-only quantization (W4A8) and optimized inference frameworks [8], creating demand for coordination protocols matching this latency.

Existing low-latency middleware (Aeron [11], LMAX Disruptor [12]) provides mechanical sympathy (lock-free queues, cache-friendly layouts) but lacks semantic compression for rich agent state.

Our protocol complements these systems: we reduce payload *before* transport, enabling their optimizations to apply to compressed data.

gRPC with Protocol Buffers demonstrates 6–10× latency improvement over REST/JSON in production AI workloads, with 25 ms vs. 250 ms response times and 50–80% bandwidth reduction [9, 10]. Our bitmask encoding extends these gains: 24 bytes vs. 200 bytes for Protobuf with full field names, achieving an additional 8× reduction for boolean feature vectors.

Approach	**Latency**	**Bandwidth**	**Semantics**	**Scale**
Raw JSON/WebSocket	∼50 ms	High	Rich	10^2
Binary FIX/SBE	∼10 ms	Medium	Poor	10^3
Learned (DIAL)	Variable	Low	Opaque	10^2
gRPC/Protobuf raw	∼5 ms	Medium	Poor	10^3
Our Protocol	**8.2 ms**	**Very Low**	**Rich**	10^2–10^3*

Table 1: Comparison of coordination approaches. Our protocol achieves semantic richness with HFT-adjacent latency. *Single-coordinator topology scales to $N \approx 500$; sharded coordination (Section 9) extends to 10^3–10^4.

3 Semantic Encoding and Schema Management

3.1 The 64-Bit Design Space

We present two complementary perspectives on the 64-bit constraint, reflecting different deployment contexts:

3.1.1 Perspective A: Hardware-Justified Constraint

For performance-critical deployments, 64-bit encoding enables hardware optimizations:

- **Atomic operations:** Single CAS (compare-and-swap) instruction for consensus markers on x86-64 and ARM64, enabling lock-free coordination primitives
- **Cache efficiency:** 64-bit bitmask with 16-bit metadata (agent_id, version) fits in single 64-byte cache line
- **Register pressure:** Two 64-bit registers suffice for bitwise scoring operations, preserving registers for feature weights
- **Memory alignment:** Natural alignment on all modern architectures; no padding overhead

This perspective treats 64-bit as a *fundamental performance interface*, analogous to cache line size or page size—not arbitrary, but architectural.

Our variable-width analysis (Section 8.6) confirms that 64-bit is the minimum width achieving 0% information loss for our 55-feature financial vocabulary while preserving atomic operation support and cache-line residency. Narrower widths (32-bit, 48-bit) incur 40–52% feature exclusion.

3.1.2 Perspective B: Domain-Optimized Design Choice

For feature-rich domains, 64-bit is a *tunable parameter*:

- **Frequency pruning:** Power-law feature distributions mean 64 bits captures 80% of activations; long tail handled by schema rotation
- **Emergency reservation:** Bits 56–63 reserved for safety-critical signals (circuit breakers, collision avoidance) that bypass normal pruning and are preserved regardless of activation frequency
- **Variable-width extensions:** 128-bit and 256-bit schemas for high-volatility regimes (Section 9)

This perspective treats 64-bit as *sufficient for steady-state operation*, with dynamic expansion for exceptional conditions.

Synthesis: Both perspectives are valid. Hardware constraints motivate 64-bit as baseline; domain requirements motivate pruning strategies and expansion mechanisms. Our implementation supports both: 64-bit atomic operations where available, with multi-word fallback for extended schemas. Information-theoretic analysis (Section 7) further validates this choice: measured feature entropy of 37.23 bits sits comfortably within the 64-bit capacity.

3.2 Schema and Feature Mapping

At time t, each agent i observes features $F_i(t) = \{f_1, f_2, \ldots\}$ drawn from domain vocabulary. Examples:

Financial `price_trend_up`, `volatility_high`, `liquidity_low`, `news_sentiment_negative`

Robotic `obstacle_detected`, `path_clear`, `battery_low`, `task_assigned`

The global schema $S_t = \bigcup_{i=1}^{N} F_i(t)$ is the unified feature set.

The bitmask encoder maps features to bit positions via deterministic surjection:

$$\Phi_t : S_t \to \{0, 1, \ldots, 63\}$$

The resulting bitmask for agent i:

$$m_i(t) = \sum_{f \in F_i(t)} 2^{\Phi_t(f)}$$

Each bit k is set iff some feature $f \in F_i(t)$ maps to position k. Multiple features may share a bit (collision); we manage this through schema pruning rather than avoidance.

3.3 Schema Consensus Protocol

The MCP Control Plane negotiates schema updates asynchronously:

1. Agents propose feature-to-bit assignments when discovering new features
2. Schema Manager (Layer 0) collects proposals, resolves conflicts via frequency-based priority
3. Unified schema broadcast every $\Delta t_{\text{schema}} = 100\,\text{ms}$

4. Agents confirm receipt; bitmasks include version metadata during transitions

This decoupling of schema evolution from data transport is key to scaling: schema changes add latency (100 ms) but do not block real-time coordination (10 ms rounds).

Emergency bit preservation. Bits 56–63 are reserved for safety-critical features (circuit breakers, collision avoidance, compliance violations) and are *never pruned* regardless of activation frequency. This guarantees that rare but catastrophic signals are always representable, even during schema transitions. Stress testing confirms all 8 emergency bits remain intact through repeated prune cycles (Section 8.7).

3.4 Collision Analysis and Information Loss

With $|S_t| > 64$, feature-to-bit mapping is non-injective. We analyze *feature exclusion* (information loss) rather than bit collision.

Under uniform random assignment with m active features and 64 positions, the expected number of excluded features due to collisions:

$$E[\text{excluded}] = m - 64\left(1 - \left(1 - \frac{1}{64}\right)^m\right)$$

For $m = 128$ active features: $E[\text{excluded}] \approx 72.5$ under *uniform random* assignment. Monte Carlo validation over 10,000 trials confirms: $E_{\text{MC}}[\text{excluded}] = 72.52 \pm 0.3$. This represents 56.7% information loss—unacceptable for safety-critical features. For a typical $m = 80$ feature set, $E[\text{excluded}] \approx 34.2$, representing a **42.8% information loss** under uniform assignment. This high loss rate renders unpruned hashing unsuitable for safety-critical coordination.

Frequency-based pruning. We observe that feature activation follows power-law distributions in practice: 20% of features account for 80% of activations. The Schema Manager retains high-frequency features in positions 0–47, reserves positions 48–55 for medium-frequency, and 56–63 for emergency features (never pruned, regardless of frequency). By pruning the effective m to ≤ 64, we drive the collision probability to zero for the active vocabulary.

Collision probability bound. For m features distributed over 64 positions, the probability that a specific feature collides:

$$P(\text{collision}) = 1 - \left(1 - \frac{1}{64}\right)^{m-1}$$

With $m = 80$ (typical feature set): $P(\text{collision}) \approx 0.712$. This confirms that at scale, collisions are the dominant outcome (71.2%) rather than an edge case, making frequency-based schema coordination a mandatory architectural component.

Decision quality impact. Unlike prior versions of this work, we now quantify the decision impact of compression. Testing across 500 coordination rounds spanning all four market regimes (trending, crisis, ranging, low-volatility), the compressed 64-bit encoding produces *identical decisions* to full-state encoding in 100% of rounds, with zero dangerous disagreements in crisis conditions (Section 8.5). The pruning strategy successfully excludes only features that are redundant for decision purposes.

4 Architectural Variants

We present two architectural variants reflecting different application requirements. Both share the same encoding and transport mechanisms, differing only in processing layers.

4.1 Variant A: General-Purpose Coordination (4-Layer)

For bandwidth-constrained distributed systems without domain-specific processing requirements:

Layer 0: Schema Manager Maintains Φ_t mappings; replicated for availability

Layer 1: Meta-Coordinator Aggregates worker bitmasks, computes preliminary consensus scores; shards by domain for horizontal scaling

Layer 2: Worker Agents Domain specialists encoding observations as bitmasks; no inter-worker communication (prevents $O(N^2)$ explosion)

Layer 3: Final Arbiter Weighted scoring and decision synthesis; optimized for sub-millisecond execution

This streamlined design minimizes latency and complexity for robotic coordination, IoT aggregation, and general distributed inference.

4.2 Variant B: Financial Trading with Pattern Detection (5-Layer)

For quantitative trading requiring alpha generation from historical pattern recognition:

Layer 0: Schema Manager As above

Layer 1: Pattern Generator Detects recurring bitmask patterns in historical data, suggesting high-probability strategies. Currently rule-based (e.g., "momentum + volume spike $\rightarrow$ breakout"); ML extension in Section 9

Layer 2: Meta-Coordinator As above, with pattern-weighted preliminary scoring

Layer 3: Worker Agents Trading specialists (market-making, risk, compliance, options flow, etc.)

Layer 4: Final Arbiter Consensus scoring with pattern confidence integration

The Pattern Generator enables warm-starting: common bitmask combinations trigger pre-computed consensus outcomes, reducing Layer 4 scoring latency by $\sim$30% for frequent patterns.



Figure 1: Bicameral Architecture. Control Plane (MCP): Schema Manager maintains feature-to-bit mappings; broadcasts epoch updates. Data Plane (gRPC): Pattern Generator dispatches tasks to Layer 3 specialists; workers stream 64-bit bitmasks with schema-version metadata to Meta-Coordinator; Final Arbiter applies weighted scoring. Dashed lines indicate asynchronous control signals; solid lines indicate synchronous data. **Note:** Pattern Generator (Layer 1) present only in Variant B (financial trading).

4.3 Layer-Specific Processing

Both variants use identical 64-bit bitmask format, enabling composition: worker outputs are coordinator inputs without transformation. The gRPC message schema:

```
message BitmaskMessage {
  uint64 mask = 1;           // 64-bit feature bitmask
  uint32 agent_id = 2;       // Unique agent identifier
  int64 timestamp_ms = 3;    // Unix timestamp (millis)
  uint32 schema_version = 4; // Schema epoch for validation
}
```

This schema occupies 24 bytes on the wire ($8 + 4 + 8 + 4$ via struct packing). A JSON equivalent requires ≈93 bytes (3.9× larger), while full natural language with context requires ≈753 bytes (31.4× larger).

5 Bicameral Architecture and Failure Modes

5.1 Control Plane and Data Plane Separation

This separation reflects the fundamental distinction between *evolving vocabulary* (slow, requires consensus) and *exchanging state* (fast, requires consistency). MCP's request-response pattern handles the former; gRPC's streaming handles the latter.

Plane	Protocol	Timing	Purpose
Control	MCP (Request/Response)	Async, 100 ms	Schema negotiation, feature proposals, consensus
Data	gRPC (Streaming)	Sync, 10 ms	Bitmask broadcast, star-hub topology, decision distributio

Table 2: Bicameral separation enables schema evolution without blocking real-time coordination.

5.2 Failure Modes and Availability

Schema Manager partition. Agents retain last-known schema; bitmasks include 8-bit version field. Schema staleness > 500 ms triggers *conservative mode*: higher risk thresholds (finance) or reduced velocity (robotics). This is safe but reduces performance.

Final Arbiter crash. System fails *closed* (no decisions) pending hot standby promotion ($<$ 50 ms). Regulatory requirement in finance; safety requirement in robotics.

Network degradation. gRPC deadlines at 15 ms; missed deadlines trigger *last-valid-decision hold* for 100 ms, then fail closed. Prevents cascading decisions on stale data.

Byzantine agents. Malicious or faulty agents sending misleading bitmasks are not handled; assumed <Byzantine threshold. Section 9 discusses BFT extensions.

5.3 Transport Optimization

gRPC configuration for latency minimization:

- HTTP/2 stream multiplexing: Single TCP connection per agent, eliminating connection setup overhead
- Message size: 24 bytes fits in single Ethernet frame (1500 B), preventing fragmentation
- Flow control: Disabled for bitmask streams (application handles backpressure via decision hold)
- Serialization: Protobuf with packed repeated fields; no JSON fallback in production

Projected bandwidth at $N = 1000$: $1000 \times 24\text{B} \times 100\text{Hz} = 2.4\text{MB/s}$, well within 1 Gbps link capacity and cost-effective on cloud egress (\$0.43/hr vs. \$36.86/hr for NL baseline).

6 Decision Synthesis

The Final Arbiter converts aggregated bitmasks to actionable decisions via weighted linear scoring and confidence-weighted arbitration.

6.1 Weighted Linear Scoring

For received bitmask b (64-bit vector), compute the raw score:

$$\hat{s}_{\text{raw}} = \frac{\sum_{k=0}^{63} w_k \cdot b_k}{\sum_{k=0}^{63} w_k}$$

where w_k are domain-specific importance weights.

Financial example: `trend_confirmation` (bit 3) weighted 0.25, `volume_spike` (bit 7) weighted 0.20, `time_horizon` (bit 12) weighted 0.10.

Robotic example: `obstacle_proximity` (bit 0) weighted 0.30, `path_viability` (bit 4) weighted 0.25, `battery_critical` (bit 63) weighted 0.45 (emergency override).

To align with production requirements (Variant B), we utilize a composite scoring function that incorporates the mean confidence c reported by the top-performing agent subset:

$$\hat{s}_{\text{final}} = 0.6 \cdot \hat{s}_{\text{raw}} + 0.4 \cdot c$$

Strategies are ranked by $\hat{s}_{\text{final}}$. Selection logic:

- If top strategy leads by > 15 percentage points: select directly.
- If top 3 are within 15 points: synthesize hybrid via majority voting across their constituent features.
- Reject any strategy with $\hat{s}_{\text{final}} < 0.40$ (insufficient confidence).

The 15% threshold is empirically tuned; automated threshold selection via validation set is future work.

6.2 Scoring Optimizations

The arbiter maintains pre-computed weight vectors and uses bitwise operations:

- `popcnt` instruction counts set bits in 64-bit word
- Dot product via lookup table for 8-bit chunks (AVX-256 optimized)
- Branchless selection to prevent pipeline stalls

Result: 0.026 ms mean scoring latency (measured over 1,000 trials); projected linear at scale. The full pipeline excluding LLM inference (encode → serialize → aggregate → pattern detect → score) executes in 159 μs p99 (Section 8.3).

Limitation: Linear scoring assumes feature independence. Pairwise interactions (e.g., `trend_up` AND `volume_high`) are not captured. Our mutual information analysis (Section 7) quantifies this gap: 53.15 bits of pairwise MI exist in the feature space, with the strongest correlations between `liquidity_low` ↔ `tail_risk_elevated` (MI = 0.738 bits) and `price_trend_up` ↔ `momentum_strong` (MI = 0.722 bits). Section 9 discusses non-linear extensions.

7 Information-Theoretic Analysis

We quantify the encoding efficiency and theoretical compression limits of the bitmask protocol through Shannon entropy analysis.

7.1 Feature-Level Entropy

Over 2,000 simulated coordination rounds with regime shifts every 10 rounds, we measure per-feature activation entropy $H(f_k)$ for each feature f_k in the 55-feature financial vocabulary:

$$H(f_k) = -p_k \log_2 p_k - (1 - p_k) \log_2(1 - p_k)$$

where p_k is the activation probability of feature f_k. The total feature entropy assuming independence:

$$H_{\text{total}} = \sum_{k=1}^{55} H(f_k) = 37.23 \text{ bits}$$

This sits well within the 64-bit bitmask capacity, yielding an encoding efficiency of $37.23/64 = 58.2\%$. The highest-entropy features are `volatility_low` ($H = 0.982$, $p = 0.420$), `market_regime_ranging` ($H = 0.979$, $p = 0.415$), and `volatility_high` ($H = 0.938$, $p = 0.354$)—features whose activation is most unpredictable and therefore most informative.

7.2 Pattern-Level Entropy and Shannon Minimum

Analyzing the joint distribution of feature activations (treating each round's observation as a pattern), we find 2,000 unique patterns across 2,000 rounds, with a pattern entropy of:

$$H_{\text{pattern}} = -\sum_{p \in \mathcal{P}} P(p) \log_2 P(p) = 10.97 \text{ bits}$$

The Shannon minimum encoding is therefore $\lceil 10.97/8 \rceil = 2$ bytes. Our 24-byte message format represents a 12× overhead over the information-theoretic minimum, attributable to metadata (agent ID, timestamp, schema version) required for coordination.

7.3 Exploitable Redundancy

Pairwise mutual information analysis across the top 20 features reveals significant correlations:

$$I(f_j; f_k) = \sum_{a,b \in \{0,1\}} P(f_j = a, f_k = b) \log_2 \frac{P(f_j = a, f_k = b)}{P(f_j = a) \cdot P(f_k = b)}$$

Total pairwise MI: 53.15 bits. The strongest pairs are regime-driven: `liquidity_low` ↔ `tail_risk_elevated` (MI = 0.738 bits) co-activate in crisis regimes, while `price_trend_up` ↔ `momentum_strong` (MI = 0.722 bits) co-activate in trending regimes. This redundancy represents a concrete compression opportunity: a correlation-aware encoder could pack equivalent information into ∼**11 bits** by encoding feature *clusters* rather than individual features.

7.4 Conditional Entropy by Regime

When conditioned on market regime, pattern entropy decreases:

Crisis regimes show the lowest entropy (8.75 bits), consistent with the observation that crisis states activate a more concentrated, predictable set of features. This motivates *context-dependent encoding*: dynamically switching bit allocations based on detected regime (Section 9).

Regime	H (bits)	Rounds
Crisis	8.75	430
Low-volatility	8.78	440
Trending	9.13	560
Ranging	9.15	570

Table 3: Conditional entropy by market regime. Crisis and low-volatility regimes are more predictable (lower entropy), suggesting regime-adaptive encoding could further improve compression.

8 Empirical Evaluation and Scale Analysis

We present comprehensive stress testing across seven evaluation dimensions: compression limits, latency floor analysis, scale behavior ($N = 10$ to $N = 5000$), decision quality under compression, variable-width encoding, information-theoretic analysis (Section 7), and regime stress testing. All tests use Variant B (5-layer financial) unless noted.

8.1 Evaluation Scope

Our evaluation advances beyond mechanism validation to include *scale stress testing* and *decision quality measurement*:

- **Scale range:** $N = 10$ to $N = 5000$ (500× range)
- **Decision quality:** Full-state vs. compressed agreement across 500 rounds and 4 market regimes
- **Latency:** 1,000-trial component benchmarks at nanosecond resolution
- **Information theory:** 2,000-round entropy analysis
- **Limitations:** In-memory transport (not production gRPC/WAN); simulated agents (not real LLM inference); deterministic seed

8.2 Compression Results

Encoding	Size	vs. Bitmask
Full NL (LLM output)	553 B	23.0×
Tokenized NL + headers	753 B	31.4×
JSON serialized	93 B	3.9×
Bitmask Protocol	**24 B**	**1.0×**
Raw bitmask (no metadata)	8 B	0.3×
Shannon Minimum	**2 B**	**0.08×**

Table 4: Per-message size comparison for 20 active features. The bitmask protocol achieves 31.4× compression vs. tokenized NL, with 12× overhead vs. Shannon minimum (attributable to required coordination metadata).

Delta encoding. Consecutive bitmasks are highly correlated: averaging 3.2 bytes of XOR delta per round (2–5 bits changed). Delta encoding achieves an effective 232× compression vs. tokenized NL, at the cost of requiring ordered delivery and state synchronization on packet loss.

Bandwidth at scale. Compression ratio holds at exactly 85.3× across all tested scales ($N = 10$ to $N = 5000$), confirming $O(N)$ bandwidth scaling. At $N = 1000$, 100 Hz: 2.4 MB/s (bitmask) vs. 204.8 MB/s (NL baseline).

8.3 Latency Floor Analysis

We benchmark each pipeline component independently over 1,000 trials:

Component	**Mean**	**p99**
Feature encoding	2.0 μs	3.9 μs
Serialize (struct pack)	0.5 μs	0.8 μs
Deserialize	0.9 μs	1.4 μs
Aggregate (10 agents)	83.8 μs	121.7 μs
Pattern detection	5.0 μs	13.0 μs
Scoring (weighted linear)	14.6 μs	26.0 μs
Full pipeline (no LLM)	**110.4 μs**	**159.2 μs**
+ LLM inference (6.8 ms)	6.91 ms	6.96 ms

Table 5: Component latency breakdown (1,000 trials). The entire protocol pipeline excluding LLM inference executes in 159 μs p99. LLM inference accounts for 97.7% of end-to-end latency.

Theoretical floor: The minimum possible latency for serialize + score is ≈12.6 μs (hardware-bound by struct packing and bitwise operations). The protocol overhead is *negligible*; all optimization effort should target LLM inference time.

8.4 Scale Stress Test ($N = 10$ to $N = 5000$)

We test scaling behavior by measuring actual coordination latency and modeling queuing dynamics. For the Meta-Coordinator processing N simultaneous arrivals, we apply M/D/1 queuing analysis with utilization $\rho = \lambda/\mu$ where $\lambda = N/T_{\text{round}}$ is the arrival rate and $\mu = 1/T_{\text{scoring}}$ is the service rate.

Key findings:

- **Bandwidth:** Scales perfectly $O(N)$ from 0.024 to 12.0 MB/s; all within 1 Gbps link capacity
- **Coordinator bottleneck:** Single-threaded aggregation saturates at $\rho \approx 1.0$ ($N \approx 600$). This is a *compute bottleneck*, not a bandwidth bottleneck
- **Mitigation:** Sharded coordination (Section 9) partitions agents by domain (e.g., asset class, geographic region), reducing per-shard N below saturation threshold
- **Revised projection:** With 4-way sharding, $N = 2000$ yields $\rho = 0.93$ per shard (stable); $N = 4000$ yields $\rho = 0.93$ with 8-way sharding

N	**p99 (ms)**	**BW (MB/s)**	ρ	**Status**
10	0.9	0.024	0.01	Stable
50	3.6	0.120	0.07	Stable
100	6.9	0.240	0.14	Stable
250	13.6	0.600	0.35	Stable
500	28.7	1.200	0.77	Stable
1,000	59.1	2.400	1.58	Saturated
2,000	160.8	4.800	3.70	Saturated
5,000	294.2	12.000	10.65	Saturated

Table 6: Scale stress test results. The single-threaded coordinator saturates ($\rho \geq 1$) at $N \approx 600$. Bandwidth scales perfectly $O(N)$; compression ratio remains 85.3× at all scales.

8.5 Decision Quality Under Compression

We compare decisions made with full-state information against decisions made with 64-bit compressed encoding across 500 rounds spanning all four market regimes (trending: 190, crisis: 110, ranging: 130, low-volatility: 70).

Regime	**Rounds**	**Agreement**
Trending	190	100%
Crisis	110	100%
Ranging	130	100%
Low-volatility	70	100%
Overall	**500**	**100%**

Table 7: Full-state vs. compressed decision agreement. Zero disagreements across all regimes; zero dangerous disagreements (executing in crisis). The 64-bit encoding preserves all decision-relevant information for the 55-feature financial vocabulary.

Caveat: 100% agreement at $m = 55$ features does not generalize to larger vocabularies. At $m = 128$, theoretical information loss is 56.7%. The agreement rate will degrade as vocabulary size exceeds 64; quantifying this degradation curve is future work.

8.6 Variable-Width Encoding Analysis

We analyze information loss and compression trade-offs across bitmask widths for the 55-feature financial vocabulary:

8.7 Schema Stability Under Regime Stress

We test schema behavior under four volatility levels with $N = 50$ agents:

Width	Msg Size	Info Loss	Compression	Atomic	Cache Line
32-bit	20 B	52.0%	102×	✓	✓
48-bit	22 B	40.1%	93×	✓	✓
64-bit	**24 B**	**0.0%**	**85×**	✓	✓
96-bit	28 B	0.0%	73×		✓
128-bit	32 B	0.0%	64×		✓
256-bit	48 B	0.0%	43×		

Table 8: Variable-width encoding trade-offs. 64-bit is the minimum width achieving 0% information loss while preserving atomic CPU operations and cache-line residency. Wider encodings sacrifice compression for no quality gain.

Condition	Shift Interval	Regimes Seen	Schema Prunes
Stable	60 rounds	2	4
Moderate	15 rounds	4	4
Volatile	5 rounds	4	4
Extreme	1 round	4	4

Table 9: Schema prune count remains constant (4) regardless of regime volatility, confirming that frequency-based pruning converges to stable feature allocations even under rapid regime transitions. Decision diversity (variation in execute rate across regimes) reaches 1.0, confirming regime-adaptive behavior.

9 Deployment Roadmap, Limitations, and Open Problems

9.1 Immediate Term (0–6 Months)

Sharded Coordination. The primary bottleneck identified by stress testing (Section 8.4) is single-coordinator saturation at $N \approx 600$. We will implement k-way sharded Meta-Coordinators, partitioned by asset class (finance) or spatial sector (robotics), with cross-shard consensus via a lightweight arbiter-of-arbiters. Target: $N = 2000$ at $\rho < 0.8$ per shard with $k = 4$.

TypeScript SDK. To enable adoption in the Vercel/Next.js ecosystem, we will release a TypeScript implementation of the protocol as an open-source library (`npm install adaptive-bitmask`). The SDK will integrate with the Vercel AI SDK for multi-agent orchestration, providing developers with $O(N)$ coordination out of the box for serverless AI applications.

Real LLM Validation. Our current evaluation uses simulated agents. A critical next step is validating with real LLM agents (Claude, GPT-4) making actual inference calls on live or historical market data. This will test the LLM-to-bitmask encoding boundary: whether discretizing continuous model outputs into boolean features preserves decision-relevant information.

9.2 Medium Term (6–18 Months)

Correlation-Aware Encoding. Our information-theoretic analysis reveals 53.15 bits of pairwise mutual information across features. A correlation-aware encoder could exploit this redundancy to pack equivalent information into ∼11 bits, freeing capacity for additional features or reducing

bitmask width. Candidate approaches include Huffman-style adaptive bit allocation and feature-cluster encoding.

Delta Encoding. Consecutive bitmasks differ by only 3.2 bytes on average. XOR delta encoding with run-length compression could achieve 232× compression vs. NL baseline, at the cost of ordered delivery requirements and state resynchronization on packet loss.

Context-Dependent Encoding. Conditional entropy analysis shows crisis regimes have lower entropy (8.75 bits) than ranging regimes (9.15 bits). Dynamically switching bit allocations based on detected regime would improve encoding efficiency in concentrated-signal conditions.

Variable-Width Encoding. Extend to 128-bit and 256-bit schemas for high-feature domains. Implement adaptive width selection based on system load or volatility indices (VIX for finance, obstacle density for robotics).

Byzantine Fault Tolerance. Integrate BFT consensus (HotStuff [13]) for Schema Manager and Final Arbiter replication. Critical for production where agent compromise is a threat model.

Learned Pattern Generation. Replace rule-based Layer 1 with embedding-based pattern detection, training on historical bitmask sequences to predict high-probability consensus outcomes.

Non-Linear Scoring. Extend the arbiter's scoring function to include pairwise interaction terms $w_{jk} \cdot b_j \cdot b_k$, capturing the feature correlations identified in Section 7. With $\binom{64}{2} = 2{,}016$ pairwise terms and measured scoring latency of $\sim 15\,\mu$s for linear scoring, quadratic scoring remains sub-millisecond.

9.3 Fundamental Limitations

Information Loss Irreversibility. Bitmask compression is lossy; excluded features cannot be reconstructed. Unlike learned communication (DIAL), we cannot recover "what was lost." **Mitigation:** Parallel audit logging with full state for post-hoc analysis (not real-time coordination).

The 64-Bit Cap. Even with pruning, 64 bits limits expressiveness. At 58.2% entropy utilization, we have headroom for the current 55-feature vocabulary, but vocabularies exceeding ∼64 features will incur information loss. **Mitigation:** Reserved emergency bits (56–63) for safety-critical signals; variable-width extension for extreme regimes; correlation-aware encoding to increase effective capacity.

Single-Point Bottlenecks. The Meta-Coordinator saturates at $N \approx 600$ in single-threaded configuration. **Mitigation:** k-way sharding; stress testing confirms bandwidth remains $O(N)$ even past saturation—the bottleneck is compute, not network.

Simulated Validation. All evaluation uses simulated agents with synthetic market data. Real LLM agents produce messier, more ambiguous outputs that may be harder to discretize into boolean features. Validating the LLM-to-bitmask encoding boundary with real inference is the most critical open problem.

10 Conclusion

We have described an architecture enabling $O(N)$ coordination for multi-agent systems through semantic bitmask encoding and hierarchical consensus. By adapting semantic hashing to dynamic agent states, separating control from data planes, and providing both streamlined (4-layer) and pattern-enhanced (5-layer) variants, we achieve 85× bandwidth reduction with sub-10 ms latency at prototype scale.

Comprehensive stress testing from $N = 10$ to $N = 5000$ reveals three key findings: (1) the 64-bit encoding preserves 100% of decision-relevant information for the 55-feature financial vocabulary with zero dangerous disagreements across all market regimes; (2) LLM inference accounts for 97.7% of end-to-end latency, making the protocol overhead negligible; and (3) single-coordinator architectures saturates at $N \approx 600$, establishing sharded coordination as a required production optimization rather than an optional enhancement.

Information-theoretic analysis establishes concrete bounds: 37.23 bits of feature entropy within 64-bit capacity, 53.15 bits of exploitable pairwise mutual information, and a Shannon minimum of 2 bytes per observation. These results define both the current efficiency (58.2% capacity utilization) and the theoretical ceiling for future optimization.

Critical next steps include sharded coordinator implementation for $N > 600$, real LLM agent validation, and a TypeScript SDK targeting the Vercel AI ecosystem for production adoption.

Status: Technical research draft v3.3. Open-source reference implementation available. Production pilot targeting Q3 2026. Contact: [author email]

References

[1] Salakhutdinov, R., & Hinton, G. (2009). Semantic Hashing. *International Journal of Approximate Reasoning*, 50(7), 969–978.

[2] Anthropic. (2024). Model Context Protocol Specification. `https://modelcontextprotocol.io`

[3] Foerster, J., Assael, Y., de Freitas, N., & Whiteson, S. (2016). Learning to Communicate with Deep Multi-Agent Reinforcement Learning. *NeurIPS*.

[4] Sukhbaatar, S., Szlam, A., & Fergus, R. (2016). Learning Multiagent Communication with Backpropagation. *NeurIPS*.

[5] Weinberger, K., Dasgupta, A., Langford, J., Smola, A., & Attenberg, J. (2009). Feature Hashing for Large Scale Multitask Learning. *ICML*.

[6] Dorigo, M., Theraulaz, G., & Trianni, V. (2021). Swarm Robotics: From Source of Inspiration to Domains of Application. *Swarm Intelligence*, 14.

[7] IBM. (2025). Hierarchical Multi-Agent Systems: Architecture and Coordination Patterns. IBM Research Technical Report.

[8] Shen, Y., et al. (2025). Sustainable LLM Inference for Edge AI: Evaluating Quantized LLMs for Energy Efficiency, Output Accuracy, and Inference Latency. *ACM Transactions on Intelligent Systems*.

[9] SmartDev. (2025). AI-Powered APIs: REST vs GraphQL vs gRPC Performance. Technical Report. `https://smartdev.com/ai-powered-apis-grpc-vs-rest-vs-graphql/`

[10] Kim, N. (2023). Protocol Buffers vs JSON. *System Design Newsletter*. `https://newsletter.systemdesign.one/p/protocol-buffers-vs-json`

[11] Aeron. High-Performance Open Source Message Transport. `https://github.com/real-logic/aeron`

[12] Thompson, M., et al. (2011). Disruptor: High Performance Alternative to Bounded Queues for Exchanging Data. *QCon*.

[13] Yin, M., et al. (2019). HotStuff: BFT Consensus in the Lens of Blockchain. *arXiv:1803.05069*.