



---

# Spatial Databases: Project Documentation

SETUP-GUIDE AND DOCUMENTATION FOR SPATIAL-WEATHER-PROJECT

---

Johannes Dillmann (matr-nr)  
Christian Wirth (4498611)  
Jens Fischer (3923671)

February 27, 2015

# Contents

<b>Table of Contents</b>	<b>I</b>
<b>Table of Figures</b>	<b>II</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Topic . . . . .	1
1.2 Motivation . . . . .	1
1.3 Goal . . . . .	1
<b>2 Data Sources</b>	<b>2</b>
2.1 Global Forecast System (GFS) . . . . .	2
<b>3 Data Model</b>	<b>2</b>
3.1 Entity Relationship Diagram (ERD) . . . . .	2
3.2 Relational Schema . . . . .	3
<b>4 Architecture</b>	<b>4</b>
4.1 Data Sources and Importer . . . . .	4
4.2 Database Server . . . . .	5
4.3 Backend . . . . .	5
4.4 Webapp (Frontend) . . . . .	5
<b>5 Optimisations</b>	<b>5</b>
5.1 Indices . . . . .	5
5.2 Materialised Computations . . . . .	5
5.3 Border Simplifications . . . . .	6
<b>6 Usage</b>	<b>6</b>
<b>7 Conclusion</b>	<b>15</b>
<b>8 Setup Guide</b>	<b>16</b>
8.1 Prerequisites . . . . .	16
8.2 Step-by-step Setup . . . . .	16
8.3 Import OSM Data . . . . .	17
8.4 Import DWD Data (Historical) . . . . .	18
8.5 Download and Import NOAA GFS Data (Forecasts) . . . . .	19
8.6 Start Webapp-Server . . . . .	22
<b>Bibliography</b>	<b>22</b>
<b>9 Appendix</b>	<b>22</b>
9.1 Link to Repository . . . . .	22
9.2 Border Simplification Script . . . . .	22

## List of Figures

3.1	ER-Diagram . . . . .	2
4.1	Architecture . . . . .	4
5.1	Berlin Full Detail . . . . .	7
5.2	Berlin Simplified . . . . .	7
5.3	Germany Full Detail . . . . .	8
5.4	Germany Simplified . . . . .	9
5.5	Performance Gains From the Simplification . . . . .	10
6.1	Layer selection . . . . .	10
6.2	Weather control . . . . .	11
6.3	Date-time picker . . . . .	12
6.4	Raster comparison . . . . .	13
6.5	Temperature legend . . . . .	14
6.6	Rainfall legend . . . . .	14
6.7	Pop-up . . . . .	15

# 1 Introduction

## 1.1 Topic

The topic of this project is to combine OSM-data provided by Open Street Maps and weather-Data on a spatial database server running PostGIS.

## 1.2 Motivation

The motivation of this project can be seen from a educational as well as from a technical point of view.

The educational purpose of this project is to encourage the students to acquire domain-knowledge concerning the problem that needs to be solved with a system that is requested to be set up. In this particular case the domain is weather-data. By working hands-on with real data the students expand their range of skills in order to be able to work with problems that exceed the boundary of purely computational and mathematical problems. This focuses on an important trade every programmer will need once he leaves university and has to deal with real world problems.

## 1.3 Goal

The Goal is to find suitable sources for weather-forecast and historical weather-data as well as storing it on a PostGIS-server. In the end the system shall be able to overlay the OSM- and the collected weather data. In order to achieve this goal several technical problems have to be solved, like designing a data model, a suitable system architecture as well as setting up and configuring the whole system.

## 2 Data Sources

- kurze Beschreibung der drei Datenquellen - vielleicht die (konzeptuelle) Beschreibung der Download Prozesse auch hier?

### 2.1 Global Forecast System (GFS)

We use data from the Global Forecast System (GFS) in our application for weather forecasts. The GFS is a weather forecast model computed and freely distributed by the National Oceanic and Atmospheric Administration (NOAA) of the United States.

The GFS model is calculated every 6h hours and covers the entire globe at a resolution of 28 kilometers for weather predictions within 16 days. Furthermore it provides forecasts for up to two weeks, but with a lower resolution of 70 kilometers.

**Vielleicht noch auflisten was die alles haben**

The data is free of charge and can be downloaded as Gridded Binaries (GRIB) from the NOAA servers. They provide among other access methods like FTP services, a simple webinterface to extract certain levels and variables for a subregion.

Because we are only interested in the temperature and rainfall forecasts for Germany, we are using that interface to download the GRIB data

## 3 Data Model

### 3.1 Entity Relationship Diagram (ERD)




Figure 3.1: ER-Diagram

Geg. ER Model anpassen für Station Attribute

### 3.2 Relational Schema

Country : {[osm\_id: biginteger, name: string, geom: geometry]}

State : {[osm\_id: biginteger, name: string, geom: geometry]}

District : {[osm\_id: biginteger, name: string, geom: geometry]}

Station : {[dwd\_id: integer, name: string, altitude: integer, geometry: point, region: geometry]}

Observation : {[station\_id: integer, date: timestamp, temperature: double, rainfall: double]}

Forecast : {[date: timestamp, hour: integer, rast: raster]}

ContribState : {[state\_id: biginteger, station\_id: integer, area: double]}

ContribDistrict : {[district\_id: biginteger, station\_id: integer, area: double]}

The relational schema is following Kemper, Eickler (2009): Datenbanksysteme 7. Aufl.

Bibtex quelle einfügen

The schema is not identical to the schema used in the actual PostgreSQL DB where for example additional fields used solely for the import are still remaining. The presented schema is given for illustrating conceptual ideas.

As can be seen in the relational schema there are no foreign keys or junction tables used to reference the relation between countries, states, districts and stations. Those entities are related by their spatial component and will be joined by using spatial joins provided by the PostGIS extension.

## 4 Architecture

The architecture as shown in fig. 4.1 consist of 4 major parts:

The data sources and their corresponding downloaders and importers, the PostGIS-Server, running in a virtual machine, the backend and a webapp. In the following four subsections 4.1 to 4.4 it will be explained how those components work together and what parts they are made of as well as which technologies have been used to implement them.




Figure 4.1: Architecture

Schreibfehler korrigieren

### 4.1 Data Sources and Importer

The three data-sources used in this project are

add 3 sources

and have been discussed in section 2 very detailed. The importers write the collected data directly to the spatial database server so they can be used to answer the queries by the back-end. For further information on this part please refer to section 2 and the setup-guide at subsections 8.3 to 8.5

## 4.2 Database Server

## 4.2 Database Server

The database server is provided as Vagrant virtual machine. Vagrant is a tool to automate the setup of virtual machines. In this case vagrant initializes a Ubuntu x64 instance and installs postgres and PostGis along with other required packages and configures most of the things needed for the server to be used.

## 4.3 Backend

The backend runs Flask, a model-view-controller-based web framework. This framework contains methods to invoke data collection and data import as well as an ORM based on SQLAlchemy and GEOAlchemy to send queries to the database to retrieve data requested by the user via the frontend. The queries are written in python, the ORM translates those queries to SQL and the the response from the database is converted to GeoJSON, which is then forwarded to the frontend.

## 4.4 Webapp (Frontend)

The frontend is implemented as a webapp written in HTML5, CSS3 and Javascript and provides a user interface which is described in detail in section 8.3. To display the weather and OSM data the library Leaflet is used. The frontend receives the requested data from the backend in (Geo)JSON.

# 5 Optimisations

## 5.1 Indices

Indices were used on all primary keys, all geometry columns and some frequently queried attributes, like dates. All indices were used from the beginning, so no information on the performance gains is available.

## 5.2 Materialised Computations

When querying the forecast information for all the states, districts or stations our first implementation used nested queries within the ORM (i.e. multiple queries where send to the database). This queries took extremely long, several minutes in the case of districts. To improve performance, we reimplemented this query as one nested query (i.e. the nesting was done within one query). This already improved performance significantly. But we also noted that one of the nested subqueries was basically a static computation, namely the computation of the area contribution of the region of a weather station (i.e. the Voronoi cell of a weather station) to the area of a state or district. Therefore we decided to materialise this computation into two tables (Contrib\_State, Contrib\_District), which brought down the query time significantly.



### 5.3 Border Simplifications

When profiling the application further, we noticed that the huge amount of detail of the country, state and district borders seriously affected the performance, not only in terms of querying but also the sheer amount of data transmitted from the server to the client.

Initially, after the import from Open Street Maps, all the country, state and district geometry columns had a combined size of 38 MiB. In an attempt to further improve performance we wanted to simplify the geometries, especially as they were only used for querying and overlaying the respective regions, not for the rendering of the map itself.

The main problem here is that the simplification needs to preserve the topological relationships between the different polygons. Postgis provides the function `ST_Simplify`, but this function works on an object-by-object basis. Using this to simplify the borders produces holes and overlaps between the borders. Although the name seems to indicate otherwise, `ST_SimplifyPreserveTopology` doesn't solve the problem (it only tries to preserve topologic relationships of multilines and multipolygons).

The way to achieve simplification and preserve topological relationships is to use the topology feature of Postgis. This means to create a topology, add a layer for the borders, populate the topology from the polygons, simplify the borders within the topology and convert the borders back to polygons. This method was adapted from Strk [Str12]. The complete Script can be found in the Appendix. Figure 5.1, 5.2, 5.3 and 5.4 compare the effects of the simplification. We aimed at achieving meaningful reduction in size but still maintain the basic characteristics of the borders. As one can see at fig. 5.1 and 5.2, on the smallest level the differences in detail are clearly notable. When looking at a larger zoom level, as in fig. 5.3 and 5.4, one can hardly spot the difference. To total combined size of the geometry columns after the simplification was 895 KiB! A further optimisation could be to provide different levels of detail for different zoom levels.

Figure 5.5 summarises the performance gains for the most intensive query we perform. As you can see, the simplification achieved significant performance improvements.

## 6 Usage

As mentioned in the architecture section, the weather map is displayed with HTML5 and controlled with JavaScript. It has been developed as a control for the Leaflet library and tested on Google Chrome and Chromium. Other browsers are not officially supported.

By default Leaflet is using a zoom and a layer selection control. Instead of rendering the base tiles ourselves, we are using the freely available

### Sources

OSM Tile Server and tiles generated for free by Mapbox. The desired basemap layer can be selected as seen in fig. 6.1




Figure 5.1: Berlin Full Detail




Figure 5.2: Berlin Simplified



Figure 5.3: Germany Full Detail



Figure 5.4: Germany Simplified



The map can also be panned and zoomed by using a pointing device (e.g. mouse).  
The displayed weather data can be set by an additional control as seen in fig. 6.2




Figure 6.2: Weather control

It allows to choose either temperatures or reciprocal rainfall for a certain day. The day can be selected with an interactive date-time picker as seen in fig. 6.3




Figure 6.3: Date-time picker

The selected date and time is also used to pick the computed GFS used to display forecasts. If the forecast box is checked, the forecasts slider is activated and allows to select point of forecast in hours, starting from the chosen date and time.



As mentioned before, the data can be displayed for different rasters: a voronoi tessellation based on official weather stations, german states or districts as shown in fig. 6.4. The desired raster can be selected with the control. Once the selection did change, the weather control is loading the matching data from the backend via a JSON interface and displays the raster on the map.




Figure 6.4: Raster comparison

The cells are colored according to selected data and a legend is shown on the lower right for reference (see fig. 6.5 and 6.6)






Figure 6.5: Temperature legend




Figure 6.6: Rainfall legend

Each cell is clickable and highlights its border or, in case of the voronoi tessellation, the position of the weather station. Furthermore a pop-up as in fig. 6.7 is shown, which provides additional data associated to the selected cell by calling the backends JSON interface.




Figure 6.7: Pop-up

Currently this is just the alphanumeric attributes, but could be used to show automatically generated temperature timelines or recent webcam photos or ...

noch mehr ausblick kram...

## 7 Conclusion

- lessons learned

## 8 Setup Guide

### 8.1 Prerequisites

This Setup-Guide has been written for and tested with Ubuntu 14.10 'Utopic Unicorn'. The Following Packages or Programs need to be installed before you proceed with this set-up-guide: Git, Vagrant, Python 3, PostGIS

```
1 sudo apt-get install gdal-bin postgis git vagrant python
```

#### check packages

It is strongly advised to install scipy, numpy and shapely (globally) as binary packages and not through virtualenv, because of their large number of non-python dependencies. E.g. on Debian/Ubuntu systems use

```
1 sudo apt-get install python3-numpy python3-scipy python3-shapely
```

to install. Make sure access to the global packages is activated in the virtual environment (e.g. through `toggleglobalsitepackages` in `virtualenvwrapper`).

When compiling entirely from source, You also might need to install the following libraries: (for shapely): `libgeos-dev`; (for scipy): `libblas-dev`, `liblapack-dev`, `gfortran`.

### 8.2 Step-by-step Setup

Now switch to directory that should later contain your project-source-code  
Clone Repository by typing into console:

```
1 git clone https://<<your_username>>@bitbucket.org/kleingeist/spatial-weather.git
```

Change directory to spatial-weather

```
1 cd spatial-weather
```

Install and configure the virtual machine by entering in console:

```
1 vagrant up
```

You can open a new console and proceed with the following steps on your local machine:

Install miniconda from the website:

<http://conda.pydata.org/miniconda.html>

`-conda install -file requirements.conda`

This command has to be executed every time the server has been started in order to activate the Python virtual environment.

```
1 source ~/miniconda3/bin/activate spatial-weather
```

install database-driver for python3:

```
1 sudo apt-get install python3-psycopg2 libpq-dev python3-dev
```

### 8.3 Import OSM Data

install additional requirements for python:  
(take a look at requirements.txt for further details.)

TDOD

```
1 pip install -r requirements.txt
```

These steps will only work once the Virtual Machine has been successfully provisioned.  
Create database and Postgis extensions:

```
1 vagrant ssh -c "sudo -u postgres psql -c \"CREATE DATABASE
    spatial OWNER myapp LC_COLLATE 'en_US.UTF-8' LC_CTYPE '
    en_US.UTF-8';\""
2 vagrant ssh -c "sudo -u postgres psql -d spatial -c \"CREATE
    EXTENSION postgis; CREATE EXTENSION postgis_topology;\""
3 vagrant ssh -c "sudo -u postgres psql -d spatial -c \"GRANT
    ALL ON DATABASE spatial TO myapp; ALTER DATABASE spatial
    OWNER TO myapp; ALTER TABLE topology OWNER to myapp; ALTER
    TABLE layer OWNER to myapp; ALTER SCHEMA topology OWNER
    TO myapp;\""
```

### 8.3 Import OSM Data

Imports the OSM data for Germany. The following tables are created: Country, State, District and Cities. The data is imported from `germany-latest.osm.pbf`, obtained from <http://download.geofabrik.de/europe/germany-latest.osm.pbf>.

Quelle: (last access: 05.02.15)

The pbf file needs to be placed in `data/` located in your Project-Folder.  
The importer used is `imposm3`, which is included in the vagrant setup (and will be executed within the VM). The import uses a custom mapping, which is provided in `importer/mapping.json`. The import is conducted in two steps: First, the data is imported to the tables `Osm_Admin` and `Osm_Places`. Second the Country, State, District and Cities tables are created from these tables.

#### Usage

Prerequisite: No contrib tables, delete if existing:

```
python manage.py drop_tables -t contrib
```

To import all the OSM data use the manage script. To invoke the whole pipeline use the following command (will take several hours):

```
python manage.py import_osm --imposm --simplify --load --drop_tables
```

- `--imposm` the first import step (see above)
- `--simplify` simplify all map data (borders)

## 8.4 Import DWD Data (Historical)

- `--load` the second import step (see above)
- `--drop-tables` deletes the `Osm_Admin` and `Osm_Places` tables after a successful import

All the above steps can be invoked separately.

### Mac OS X

```
1 python manage.py import_osm --drop_tables --imposm --load
2 DYLD_LIBRARY_PATH=/Applications/Postgres.app/Contents/
  Versions/9.3/lib python manage.py import_osm --drop_tables
  --load
```

## 8.4 Import DWD Data (Historical)

Imports weather observation data from the DWD (Deutscher Wetterdienst). The importer is a adopted version from cholin.

### Quelle

Per default, it downloads all the [recent daily observations]  
([ftp://ftp.dwd.de/pub/CDC/observations\\_germany/climate/daily/kl](ftp://ftp.dwd.de/pub/CDC/observations_germany/climate/daily/kl)).  
Details on the importer from cholin:

### Quelle

The importer downloads the station summary file to get a list of all weather stations. After that it downloads for each station the corresponding zip file (with measurement data), extracts it in-memory and parses it. To get information about which weather station is the nearest for a given point, it also calculates a region polygon for each station. This is done by computing the voronoi diagram for all stations. The resulting regions may be outside of the country germany. To avoid this there is a polygon of the border of germany (data is from [naturalearthdata.com](http://naturalearthdata.com) - country extraction and exportation as geojson with qgis). For each region we calculate the intersection with this polygon and use the result as final region (Multi)Polygon.

### Usage

Use the importer with the `manage.py` script:

To download all data and import all observation data:

```
python manage.py import_dwd
```

Create an intermediate result in `data/weather.json`:

```
python manage.py import_dwd --to_json
```

## 8.5 Download and Import NOAA GFS Data (Forecasts)

Import the intermediate result from `data/weather.json`:

```
python manage.py import_dwd --from_json
```

### Mac OS X

```
1 python manage.py import_dwd --to_json
2 DYLD_LIBRARY_PATH=/Applications/Postgres.app/Contents/
  Versions/9.3/lib python manage.py import_dwd --from_json
```

## 8.5 Download and Import NOAA GFS Data (Forecasts)

Importing the Forecast Data is done in two steps. First you have to download the GRIB files from the NOAA FTP servers. Then you have to import them as Postgis Raster.

### Download

For downloading the GFS data a date range and a target directory has to be specified. The format for the start and enddate is YYYYMMDDHH or latest for the most recently available GFS calculation.

Optionally the forecast hours can be specified as a range (Defaults to download from 0 to 129 in 3 hour steps).

```
usage: run_gfs.py download [-h] [--hours_start HOURS_START]
                           [--hours_stop HOURS_STOP] [--hours_step HOURS_STEP]
                           [startdate] [enddate] datadir
```

For example, assuming data should be stored to `data/forecasts`:

```
./run_gfs.py download 2014121112 2015011306 data/forecasts
```

### Import

To import the downloaded data, the download directory and a data range has to be specified:

```
usage: run_gfs.py import [-h] datadir [startdate] [enddate]
```

For example, assuming the data is stored in `data/forecasts`:

```
./run_gfs.py import data/forecasts 2014121112 2015011306
```

### Build Contrib Tables

To speed up some queries, the area contribution of the region (voronoi cell) of weather stations to states and districts is precomputed and materialized.

Run `python manage.py calculate_contrib_area` to create and fill the `ContribState` and `ContribDistrict` tables.

### Troubleshooting (Mac OS X)

#### UnicodeEncodeError

Python inherits the standard locale from the current shell environment. If this is not set to utf8 it tries to convert to ASCII, which produces.

UnicodeEncodeError: 'ascii' codec can't encode character

Test with `$ locale`, this should show utf-8. If not, fix with

```
export LANG=en_US.UTF-8
export LC_ALL=en_US.UTF-8
```

#### libssl / libcrypto Error from psycopq

The libssl version Mac OS X uses might be too old for psycopq, resulting in an error like the following:

```
1 ...
2 ImportError: dlopen(...lib/python3.4/site-packages/psycopg2/
   _psycopg.so, 2): Library not loaded: libssl.1.0.0.dylib
3   Referenced from: ...lib/python3.4/site-packages/psycopg2/
   _psycopg.so
4   Reason: image not found
```

This can be solved by changing the dynamic shared library install names in the psycopq binary. First, find out the version psycopq is using:

```
1 otool -L /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site-
   packages/psycopg2/_psycopg.so
2 $ /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site-
   packages/psycopg2/_psycopg.so:
3   /usr/local/lib/libpq.5.dylib (compatibility version
   5.0.0, current version 5.6.0)
4   libssl.1.0.0.dylib (compatibility version 1.0.0, current
   version 1.0.0)
5   libcrypto.1.0.0.dylib (compatibility version 1.0.0,
   current version 1.0.0)
6   /usr/lib/libSystem.B.dylib (compatibility version 1.0.0,
   current version 1213.0.0)
7   /usr/lib/libgcc_s.1.dylib (compatibility version 1.0.0,
   current version 283.0.0)
```

Now, change the the shared libraries for libssl and libcrypto (using the libraries provided by Postgres.app):

```
1 install_name_tool -change libssl.1.0.0.dylib /Applications/
   Postgres.app/Contents/Versions/9.3/lib/libssl.1.0.0.dylib
   /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site-
   packages/psycopg2/_psycopg.so
```

## 8.5 Download and Import NOAA GFS Data (Forecasts)

```
2 install_name_tool -change libcrypto.1.0.0.dylib /Applications
  /Postgres.app/Contents/Versions/9.3/lib/libcrypto.1.0.0.
  dylib /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site
  -packages/psycopg2/_psycopg.so
```

psycopq now uses the correct libraries:

```
1 otool -L /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site
  -packages/psycopg2/_psycopg.so
2 $ /Users/jvf/miniconda3/envs/env-sw/lib/python3.4/site-
  packages/psycopg2/_psycopg.so:
3   /usr/local/lib/libpq.5.dylib (compatibility version
      5.0.0, current version 5.6.0)
4   /Applications/Postgres.app/Contents/Versions/9.3/lib/
      libssl.1.0.0.dylib (compatibility version 1.0.0,
      current version 1.0.0)
5   /Applications/Postgres.app/Contents/Versions/9.3/lib/
      libcrypto.1.0.0.dylib (compatibility version 1.0.0,
      current version 1.0.0)
6   /usr/lib/libSystem.B.dylib (compatibility version 1.0.0,
      current version 1213.0.0)
7   /usr/lib/libgcc_s.1.dylib (compatibility version 1.0.0,
      current version 283.0.0)
```

It is strongly recommended to do all this in a virtual environment to not mess up your system!

Source: More Information: [superuser.com](http://superuser.com)

Another possibility is to prefix commands with DYLD\_LIBRARY\_PATH and DYLD\_FRAMEWORK\_PATH, but this works less reliable and potentially messes up the linking of other libraries. Example:

```
1 DYLD_LIBRARY_PATH=$(HOME)/lib:/usr/local/lib:/lib:/usr/lib:/
  Applications/Postgres.app/Contents/Versions/9.3/lib,
  DYLD_FRAMEWORK_PATH=/Library/Frameworks:/Network/Library/
  Frameworks:/System/Library/Frameworks python manage.py
  import_dwd
```

providing an alternative path for a newer version of libssl to the dynamic linker (in this example the libs from Postgres.app are used, but can link against a homebrew installed version as well):

```
1 export DYLD_LIBRARY_PATH=$(HOME)/lib:/usr/local/lib:/lib:/usr
  /lib:/Applications/Postgres.app/Contents/Versions/9.3/lib
2 export DYLD_FRAMEWORK_PATH=/Library/Frameworks:/Network/
  Library/Frameworks:/System/Library/Frameworks
```

Source: [stackoverflow.com](http://stackoverflow.com)

TODO



## 8.6 Start Webapp-Server

## 8.6 Start Webapp-Server

Remember to set the virtual environment first:

```
source ~/miniconda3/bin/activate spatial-weather
```

Then you can run the Webserver:

```
python manage.py runserver
```

## Bibliography

[Str12] Strk, Simplifying a map layer using PostGIS topology. 2012. URL: <http://strk.keybit.net/blog/2012/04/13/simplifying-a-map-layer-using-postgis-topology>.

## 9 Appendix

### 9.1 Link to Repository

### 9.2 Border Simplification Script

```
1  -- Delete all unneeded admin levels
2  DELETE FROM osm_admin
3      WHERE admin_level != 2 AND
4             admin_level != 4 AND
5             admin_level != 6 AND
6             admin_level != 9
7  ;
8
9  -- Delete all unneeded rows with admin level 9 (keep only
   rows of admin level 9 contained in the states hamburg and
   berlin)
10 WITH
11 berlin AS
12 (
13     SELECT geometry
14     FROM osm_admin
15     WHERE admin_level = 4 AND name = 'Berlin'
16 ),
17 hamburg AS
18 (
19     SELECT geometry
20     FROM osm_admin
21     WHERE admin_level = 4 AND name = 'Hamburg'
22 ),
23 quarter AS
```

## 9.2 Border Simplification Script

```
24 (
25     SELECT a.id, a.osm_id, a.name, a.type, a.admin_level, a.
        population, a.geometry
26     FROM osm_admin a, berlin b, hamburg h
27     WHERE a.admin_level = 9 AND ST_Contains(ST_Union(b.
        geometry, h.geometry), a.geometry)
28 )
29
30 DELETE FROM osm_admin
31 WHERE admin_level = 9 AND id NOT IN (SELECT id FROM quarter);
32
33 -- Change Projection
34 ALTER TABLE osm_admin ALTER COLUMN geometry TYPE geometry(
    Geometry);
35 UPDATE osm_admin SET geometry = ST_Transform(geometry, 4326);
36 ALTER TABLE osm_admin ALTER COLUMN geometry TYPE geometry(
    Geometry, 4326);
37
38 -- Install SimplifyEdgeGeom function
39 CREATE OR REPLACE FUNCTION SimplifyEdgeGeom(atopo varchar,
    anedge int, maxtolerance float8)
40 RETURNS float8 AS $$
41 DECLARE
42     tol float8;
43     sql varchar;
44 BEGIN
45     tol := maxtolerance;
46     LOOP
47         sql := 'SELECT topology.ST_ChangeEdgeGeom(' ||
            quote_literal(atopo) || ', ' || anedge
48         || ', ST_Simplify(geom, ' || tol || ')) FROM '
49         || quote_ident(atopo) || '.edge WHERE edge_id = ' ||
            anedge;
50     BEGIN
51         RAISE DEBUG 'Running %', sql;
52         EXECUTE sql;
53         RETURN tol;
54     EXCEPTION
55     WHEN OTHERS THEN
56         RAISE WARNING 'Simplification of edge % with tolerance
            % failed: %', anedge, tol, SQLERRM;
57         tol := round( (tol/2.0) * 1e8 ) / 1e8; -- round to get
            to zero quicker
58     IF tol = 0 THEN RAISE EXCEPTION '%', SQLERRM; END IF;
```

## 9.2 Border Simplification Script

```
59     END;
60 END LOOP;
61 END
62 $$ LANGUAGE 'plpgsql' STABLE STRICT;
63
64 -- Create a topology
65 SELECT topology.CreateTopology('osm_admin_topo', find_srid('
    public', 'osm_admin', 'geometry'));
66
67 -- Add a layer
68 SELECT AddTopoGeometryColumn('osm_admin_topo', 'public', '
    osm_admin', 'topogeom', 'MULTIPOLYGON');
69
70 -- Populate the layer and the topology
71 UPDATE osm_admin SET topogeom = toTopoGeom(geometry, '
    osm_admin_topo', 1);
72
73 -- Simplify all edges up to 0.01 units
74 SELECT SimplifyEdgeGeom('osm_admin_topo', edge_id, 0.01) FROM
    osm_admin_topo.edge;
75
76 -- Convert the TopoGeometries to Geometries for visualization
77 ALTER TABLE osm_admin ADD geomfull Geometry(Geometry, 4326);
78
79 UPDATE osm_admin
80     SET geomfull = geometry,
81         geometry = topogeom::geometry;
```