

CS2100

<http://www.comp.nus.edu.sg/~cs2100/>

COMPUTER ORGANISATION

Lecture #5b

Arrays, Strings and Structures



NUS
National University
of Singapore

School of
Computing



Questions?

IMPORTANT: DO NOT SCAN THE QR CODE IN THE VIDEO RECORDINGS. THEY NO LONGER WORK

Ask at

<https://sets.netlify.app/module/676ca3a07d7f5ffc1741dc65>

OR

Scan and ask your questions here!
(May be obscured in some slides)



3. Strings (1/2)

```
#include <stdio.h>
```

ArrayOfChar.c

```
void modifyArray(char [], int);  
void printArray(char [], int);
```

```
int main(void) {  
    char chars[4] = {'C', 'h', 'a', 'r'};  
    modifyArray(chars, 4);  
    printArray(chars, 4);  
    return 0;  
}
```

```
void modifyArray(char arr[], int size) {  
    int i;  
  
    for (i=0; i<size; i++) {  
        arr[i]++;  
    }  
}
```

```
void printArray(char arr[], int size) {  
    int i;  
  
    for (i=0; i<size; i++) {  
        printf("%c", arr[i]);  
    }  
    printf("\n");  
}
```

■ Array of characters

The following code is very similar to [ArrayModify.c](#).
What does it do?
What is the output?

Dibs



3. Strings (2/2)

- We can turn an array of characters into a **string** by adding a **null character '\0'** at the end of the array
- A **string** is an array of characters, terminated by a null character '\0' (which has an ASCII value of zero)
- We can use **string functions** (include <string.h>) to manipulate strings.

Example:

c	s	1	0	1	0	\0
---	---	---	---	---	---	----



3.1 Strings: Basic

- Declaration of an array of characters

- `char str[6];`

- Assigning character to an element of an array of characters

- `str[0] = 'e';`
 - `str[1] = 'g';`
 - `str[2] = 'g';`
 - `str[3] = '\\0';`



Without '\\0', it is just an array of character, not a string.

Do not need '\\0' as it is automatically added.

- Initializer for string

- Two ways:

- `char fruit_name[] = "apple";`
 - `char fruit_name[] = {'a', 'p', 'p', 'l', 'e', '\\0'};`



3.2 Strings: I/O (1/3)

- Read string from stdin (keyboard)

```
fgets(str, size, stdin) // reads size - 1 char,  
                        // or until newline  
scanf("%s", str); // reads until white space
```

- Print string to stdout (monitor)

```
puts(str); // terminates with newline  
printf("%s\n", str);
```

Note: There is another function `gets(str)` to read a string interactively. However, due to security reason, we avoid it and use `fgets()` function instead.



3.2 Strings: I/O (2/3)

- `fgets()`
 - On interactive input, `fgets()` also reads in the newline character

User input: **eat**

e	a	t	\n	\0	?	?
---	---	---	----	----	---	---

- Hence, we may need to replace it with `'\0'` if necessary

```
fgets(str, size, stdin);  
len = strlen(str);  
if (str[len - 1] == '\n')  
    str[len - 1] = '\0';
```



3.2 Strings: I/O (3/3)

StringIO1.c

```
#include <stdio.h>
#define LENGTH 10

int main(void) {
    char str[LENGTH];

    printf("Enter string (at most %d characters): ", LENGTH-1);
    scanf("%s", str);
    printf("str = %s\n", str);
    return 0;
}
```

Test out the programs with this input:
My book

Output:
str = My

StringIO2.c

```
#include <stdio.h>
#define LENGTH 10

int main(void) {
    char str[LENGTH];

    printf("Enter string (at most %d characters): ", LENGTH-1);
    fgets(str, LENGTH, stdin);
    printf("str = ");
    puts(str);
    return 0;
}
```

Output:
str = My book

Note that puts(str) adds
a newline automatically.



3.3 Example: Remove Vowels (1/2)

- Write a program `RemoveVowels.c` to remove all vowels in a given input string.
- Assume the input string has at most 100 characters.
- Sample run:

```
Enter a string:  How HAVE you been, James?  
Changed string: Hw HV y bn, Jms?
```



3.3 Example: Remove Vowels (2/2)

RemoveVowels.c

```
#include <stdio.h>
#include <string.h>
#include <ctype.h>
int main(void) {
    int i, len, count = 0;
    char str[101], newstr[101];

    printf("Enter a string (at most 100 characters): ");
    fgets(str, 101, stdin); //what happens if you use scanf() here?
    len = strlen(str); // strlen() returns number of char in string
    if (str[len - 1] == '\n')
        str[len - 1] = '\0';
    len = strlen(str); // check length again

    for (i=0; i<len; i++) {
        switch (toupper(str[i])) {
            case 'A': case 'E':
            case 'I': case 'O': case 'U': break;
            default: newstr[count++] = str[i];
        }
    }
    newstr[count] = '\0';
    printf("New string: %s\n", newstr);
    return 0;
}
```

Need to include `<string.h>` to use string functions such as `strlen()`.

Need to include `<ctype.h>` to use character functions such as `toupper()`.



3.4 String Functions (1/2)

- C provides a library of string functions
 - Must include `<string.h>`
 - Here are a few commonly used string functions
- **strlen(s)**
 - Return the number of characters in s
- **strcmp(s1, s2)**
 - Compare the ASCII values of the corresponding characters in strings s1 and s2.
 - Return
 - a negative integer if s1 is lexicographically less than s2, or
 - a positive integer if s1 is lexicographically greater than s2, or
 - 0 if s1 and s2 are equal.
- **strncmp(s1, s2, n)**
 - Compare first n characters of s1 and s2.



3.4 String Functions (2/2)

■ strcpy(s1, s2)

- Copy the string pointed to by s2 into array pointed to by s1.
- Function returns s1.
- Example:

```
char name[10];  
strcpy(name, "Matthew");
```

M	a	t	t	h	e	w	\0	?	?
---	---	---	---	---	---	---	----	---	---

- The following assignment statement does not work:

```
name = "Matthew";
```

- What happens when string to be copied is too long?

```
strcpy(name, "A very long name");
```

A		v	e	r	y		l	o	n	g		n	a	m	e	\0
---	--	---	---	---	---	--	---	---	---	---	--	---	---	---	---	----

■ strncpy(s1, s2, n)

- Copy first n characters of string pointed to by s2 to s1.



3.5 Importance of '\0' in a String (1/2)

- To be treated as a string, the array of characters must be terminated with the null character '\0'.
- Otherwise, string functions will not work properly on it.
- For instance, the `printf("%s", str)` statement will print until it encounters a null character in `str`.
- Likewise, `strlen(str)` will count the number of characters up to (but not including) the null character.
- In many cases, a string that is not properly terminated with '\0' will result in illegal access of memory.



3.5 Importance of '\0' in a String (2/2)

- What is the output of this code?

```
#include <stdio.h>
#include <string.h>
```

```
int main(void) {
    char str[10];
```

```
    str[0] = 'a';
    str[1] = 'p';
    str[2] = 'p';
    str[3] = 'l';
    str[4] = 'e';
```

```
    printf("Length = %d\n", strlen(str));
    printf("str = %s\n", str);
```

```
    return 0;
```

```
}
```

WithoutNullChar.c

One possible output:

Length = 8
str = apple;ø<

Compare the output if you add:

str[5] = '\0';

or, you have:

char str[10] = "apple";

printf() will print %s from the starting address of str until it encounters the '\0' character.



%s and string functions work only on “true” strings. Without the terminating null character '\0', string functions will not work properly.



Quiz

- Please Arrays, Strings and Structures Quiz 1 before 3 pm on 23 August 2022.



CS2100 Arrays, Strings and Structures Quiz 1

Not available until 17 Aug at 0:00 | Due 23 Aug at 15:55



End of File

