

AP COMPUTER quiz11

Time—1 hour and 30 minutes for total 40 questions.

Average: 2.25 for each question.

If you finish 5 questions within 11 minutes, that's good enough.

1. A math teacher is writing a program that will correctly calculate the area of a circle. Recall that the area of a circle is pi times the radius squared (πr^2). Assuming Math.PI returns an accurate decimal approximation of pi, which of the following statements **WILL NOT** calculate an accurate area of a circle with radius 22 ?

- (A) `r*r*Math.PI; //r is the int 22`
- (B) `r*r*Math.PI; // r is the double 22.0`
- (C) `(double) r*r*Math.PI; //r is the int 22`
- (D) `(double) (r*r) *Math.PI; // r is the int 22`
- (E) All of the above choices will calculate an accurate area.

2. Consider the following code segment:

```
String s = "This is the beginning";  
String t = s.substring(5);  
int n = t.indexOf ("the");
```

Which of the following will be the value of n ?

- (A) -1
- (B) 3
- (C) 7
- (D) 9
- (E) 8

Use class Chair and method sitOnChair to answer Questions 3 and 4.

```

public class Chair
{
    private int numberOfLegs = 4;
    private boolean padded;

    public Chair (boolean soft)
    {
        if (soft) padded = true;
        else padded = false;
    }

    public void sitOnChair ( )
    {
        /* program statements */
    }
}

```

3. method sitOnChair belongs to another class and is supposed to allow the user to “sit” on a Chair if the chair is padded. Which of the following code segments could be used to replace so that sitOnChair will work as intended?

- I. Chair c =new Chair (true);
c.sit();
- II. Chair c = new Chair(true);
- III. Chair c = new Chair(true);
if (c.padded) System.out.print ("You are sitting.");

- (A) I only
- (B) II only
- (C) III only
- (D) I, II and III
- (E) None

4. Which of the following modifications, if any, would help to make the Chair class MOST useful to the sitOnChair method, based on the task attempted in Question 3?

- (A) Adding an accessor method that returns the value of numberOfLegs
- (B) Adding an accessor method that returns the value of padded
- (C) Adding a mutator method that changes the value of numberOfLegs
- (D) Adding a mutator method that changes the value of padded
- (E) Adding an accessor method that returns the values of both numberOfLegs and padded

5. Consider the following method:

```
public int halfRoot(int n)
{
    return Math.sqrt(n) /2;
}
```

Which of the following method calls would cause a run-time error?

- (A) halfRoot(-2)
- (B) halfRoot (3)
- (C) halfRoot ((int) 2.0)
- (D) halfRoot (3.0)
- (E) None will cause a run-time error.