

Announcement: Midterm Prep

Midterm is Tuesday, 3/10 here

List of topics

- Up to and including lecture on Tuesday's the 5th

Length 1hr 10min

No extra material allowed – just bring a pen

Sample midterm available online

- Recommended that you do this by Thursday
- We'll review it in class

Syntax Directed Translation for Top-Down Parsing

Last Time: Built LL(1) Predictive Parser

FIRST and FOLLOW sets define the parse table

If the grammar is LL(1), the table is unambiguous

- i.e., each cell has at most one entry

If the grammar is not LL(1) we can attempt a transformation sequence:

1. Remove left recursion
2. Left-factoring

Grammar transformations affect the structure of the parse tree. How does this affect syntax-directed translation (in particular, parse tree \rightarrow AST)?

Today

Review Parse Table Construction

- 2 examples

Show how to do Syntax-Directed Translation
using an LL(1) parser

FIRST(α) for $\alpha = Y_1 Y_2 \dots Y_k$

Add FIRST(Y_1) - $\{\epsilon\}$

If ϵ is in FIRST($Y_{1 \text{ to } i-1}$): add FIRST(Y_i) - $\{\epsilon\}$

If ϵ is in all RHS symbols, add ϵ

FOLLOW(A) for $X \rightarrow \alpha A \beta$

If A is the start, add **eof**

Add FIRST(β) - $\{\epsilon\}$

Add FOLLOW(X) if ϵ in FIRST(β) or β empty

Table[X][t]

for each production $X \rightarrow \alpha$

for each terminal **t** in FIRST(α)

put α in Table[X][**t**]

if ϵ is in FIRST(α) {

for each terminal **t** in FOLLOW(X) {

put α in Table[X][**t**]

FIRST (S) = { **a, c, d** }

FIRST (B) = { **a, c** }

FIRST (D) = { **d, ϵ** }

FIRST (B c) = { **a, c** }

FIRST (D B) = { **d, a, c** }

FIRST (a b) = { **a** }

FIRST (c S) = { **c** }

FIRST (d) = { **d** }

FIRST (ϵ) = { **ϵ** }

FOLLOW (S) = { **eof, c** }

FOLLOW (B) = { **c, eof** }

FOLLOW (D) = { **a, c** }

CFG

S \rightarrow B c | D B

B \rightarrow a b | c S

D \rightarrow d | ϵ



	a	b	c	d	eof
S	B c D B		B c D B	D B	
B	a b		c S		
D	ϵ		ϵ	d	

FIRST(α) for $\alpha = Y_1 Y_2 \dots Y_k$

Add FIRST(Y_1) - $\{\epsilon\}$

If ϵ is in FIRST($Y_{1 \text{ to } i-1}$): add FIRST(Y_i) - $\{\epsilon\}$

If ϵ is in all RHS symbols, add ϵ

FOLLOW(A) for $X \rightarrow \alpha A \beta$

If A is the start, add **eof**

Add FIRST(β) - $\{\epsilon\}$

Add FOLLOW(X) if ϵ in FIRST(β) or β empty

Table[X][t]

for each production $X \rightarrow \alpha$

 for each terminal **t** in FIRST(α)

 put α in Table[X][**t**]

 if ϵ is in FIRST(α) {

 for each terminal **t** in FOLLOW(X) {

 put α in Table[X][**t**]

CFG

$S \rightarrow (S) \mid \{S\} \mid \epsilon$

FIRST (S) = { { , (, ϵ }

FIRST ((S)) = { (}

FIRST ({ S }) = { { }

FIRST (ϵ) = { ϵ }

FOLLOW (S) = { **eof**,), } }

	()	{	}	eof
S	(S)	ϵ	{ S }	ϵ	ϵ

FIRST(α) for $\alpha = Y_1 Y_2 \dots Y_k$

Add FIRST(Y_1) - $\{\epsilon\}$

If ϵ is in FIRST($Y_{1 \text{ to } i-1}$): add FIRST(Y_i) - $\{\epsilon\}$

If ϵ is in all RHS symbols, add ϵ

FOLLOW(A) for $X \rightarrow \alpha A \beta$

If A is the start, add **eof**

Add FIRST(β) - $\{\epsilon\}$

Add FOLLOW(X) if ϵ in FIRST(β) or β empty

Table[X][t]

for each production $X \rightarrow \alpha$

 for each terminal **t** in FIRST(α)

 put α in Table[X][**t**]

 if ϵ is in FIRST(α) {

 for each terminal **t** in FOLLOW(X) {

 put α in Table[X][**t**]

CFG

$S \rightarrow + S \mid \epsilon$

FIRST (S) = { **+**, **ϵ** }


FIRST (+ S) = { **+** }

FIRST (ϵ) = { ϵ }

FOLLOW (S) = { **eof** }

	+	eof
S	+ S	ϵ

How's that Compiler Looking?



Implementing SDT for LL(1) Parser

So far, SDT shown as second (bottom-up) pass over parse tree

The LL(1) parser never needed to explicitly build the parse tree (implicitly tracked via stack)

Naïve approach: build the parse tree explicitly

Semantic Stack

Instead of building the parse tree, give parser second, *semantic* stack

- Holds nonterminals' translations

SDT rules converted to

- Pop translations of RHS nonterminals
- Push computed translation of LHS nonterm on

Translation goal:

- Count the number of occurrences of matched pairs of rounded parens: “(...)”
- Ignore occurrences of matched pairs of square brackets: “[...]”

<u>CFG</u>	<u>SDT Rules</u>	<u>SDT Actions</u>
$Expr \rightarrow \epsilon$	$Expr.trans = 0$	push 0
$ (Expr)$	$Expr.trans = Expr_2.trans + 1$	$Expr_2.trans = pop$; push $Expr_2.trans + 1$
$ [Expr]$	$Expr.trans = Expr_2.trans$	$Expr_2.trans = pop$; push $Expr_2.trans$

Action Numbers

Need to define *when* to fire the SDT Action

- Not immediately obvious since SDT is bottom-up

Solution

- Number actions and put them on the symbol stack!
- Add action number symbols at end of the productions

CFG

$Expr \rightarrow \varepsilon$ #1
| (Expr) #2
| [Expr] #3

SDT Actions

#1 push 0
#2 $Expr_2.trans = pop$; push $Expr_2.trans + 1$
#3 $Expr_2.trans = pop$; push $Expr_2.trans$


Action Numbers: Example 1

CFG

$Expr \rightarrow \epsilon \text{ \#1}$
 $| (Expr) \text{ \#2}$
 $| [Expr] \text{ \#3}$

SDT Actions: Counting Max Parens Depth

\#1 push 0
 $\text{\#2 } Expr_2.trans = \text{pop}; \text{push}(Expr_2.trans + 1)$
 $\text{\#3 } Expr_2.trans = \text{pop}; \text{push}(Expr_2.trans)$



No-op SDT Actions

CFG

$Expr \rightarrow \varepsilon$ #1
| $(Expr)$ #2
| $[Expr]$ #3

SDT Actions: Counting Max Parens Depth

#1 push 0
#2 $Expr_2.trans = pop; push(Expr_2.trans + 1)$
#3 $Expr_2.trans = pop; push(Expr_2.trans)$

Useless rule



CFG

$Expr \rightarrow \varepsilon$ #1
| $(Expr)$ #2
| $[Expr]$

SDT Actions: Counting Max Parens Depth

#1 push 0
#2 $Expr_2.trans = pop; push(Expr_2.trans + 1)$

Placing Action Numbers

Action numbers go after their corresponding nonterminals, before their corresponding terminal

Translations popped right to left in action

CFG

$Expr \rightarrow Expr + Term \#1$
 | $Term$
 $Term \rightarrow Term * Factor \#2$
 | $Factor$
 $Factor \rightarrow \#3 \text{ intlit}$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(tTrans + eTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(fTrans * tTrans)$
#3 $push(\text{intlit.value})$

Placing Action Numbers: Example

Write SDT Actions and place action numbers to get the **product** of a *Val/List* (i.e. multiply all elements)

CFG

List \rightarrow *Val List'* #1
List' \rightarrow *Val List'* #2
 | ϵ #3
Val \rightarrow #4 **intlit**

SDT Actions


#1 $LTrans = pop ; vTrans = pop ; push(LTrans * vTrans)$
#2 $LTrans = pop ; vTrans = pop ; push(LTrans * vTrans)$
#3 $push(1)$
#4 $push(intlit.value)$

Action Numbers: Benefits

Plans SDT actions using the work stack

Robust to previously introduced grammar transformations

CFG

$$\begin{array}{l} \text{Expr} \rightarrow \text{Expr} + \text{Term} \#1 \\ \quad | \quad \text{Term} \\ \text{Term} \rightarrow \text{Term} * \text{Factor} \#2 \\ \quad | \quad \text{Factor} \\ \text{Factor} \rightarrow \#3 \text{ intlit} \end{array}$$

$$\begin{array}{l} \text{Expr} \rightarrow \text{Term Expr}' \\ \text{Expr}' \rightarrow + \text{Term} \#1 \text{ Expr}' \\ \quad | \quad \epsilon \\ \text{Term} \rightarrow \text{Factor Term}' \\ \text{Term}' \rightarrow * \text{Factor} \#2 \text{ Term}' \\ \quad | \quad \epsilon \\ \text{Factor} \rightarrow \#3 \text{ intlit} \end{array}$$

SDT Actions

- #1 tTrans = pop ; eTrans = pop ; push(tTrans + eTrans)
- #2 fTrans = pop; tTrans = pop ; push(fTrans * tTrans)
- #3 push(intlit.value)

Example: SDT on Transformed Grammar

CFG

$Expr \rightarrow Term\ Expr'$

$Expr' \rightarrow +\ Term\ \#1\ Expr'$
| ϵ

$Term \rightarrow Factor\ Term'$

$Term' \rightarrow *\ Factor\ \#2\ Term'$
| ϵ

$Factor \rightarrow \#3\ \mathbf{intlit}$
| $(\ Expr\)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$

#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$

#3 $push(\mathbf{intlit.value})$

Example: SDT on Transformed Grammar

CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow +\ Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow *\ Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ intlit$
 $\quad \quad \quad | \ (\ Expr \)$

SDT

#1 tTr

#2 fTr

$First(Factor) = \{ intlit, (\}$

$First(Term') = \{ *, \}$

$First(Term) = \{ intlit, (\}$

$First(Expr') = \{ +, \}$

$First(Expr) = \{ intlit, (\}$

$First(Term\ Expr') = \{ intlit, (\}$

$First(+\ Term\ \#1\ Expr') = \{ + \}$

$First() = \{ \}$

$First(Factor\ Term') = \{ intlit, (\}$

$First(*\ Factor\ \#2\ Term) = \{ * \}$

$First() = \{ \}$

$First(\#3\ intlit) = \{ intlit \}$

$First((\ Expr \)) = \{ (\}$

$Follow(Expr) = \{ eof,) \}$

$Follow(Expr') = \{ eof,) \}$

$Follow(Term) = \{ +, eof,) \}$

$Follow(Term') = \{ +, eof,) \}$

$Follow(Factor) = \{ *, +, eof,) \}$

ans + tTrans)

ans * fTrans)

Example: SDT on Transformed Grammar

CFG

$Expr \rightarrow Term\ Expr'$

$Expr' \rightarrow +\ Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$

$Term \rightarrow Factor\ Term'$

$Term' \rightarrow *\ Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$

$Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (\ Expr \)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$

#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$

#3 $push(\text{intlit.value})$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	<i>+ Term #1 Expr'</i>			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	<i>* Factor #2 Term'</i>		ϵ		ϵ
<i>Factor</i>			<i>(Expr)</i>		#3 intlit	


CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow + Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow * Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (Expr)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$
#3 $push(intlit.value)$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	<i>+ Term #1 Expr'</i>			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	<i>* Factor #2 Term'</i>		ϵ		ϵ
<i>Factor</i>			<i>(Expr)</i>		<i>#3 intlit</i>	



Input: 5 + 3 * 2 eof



current


CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow + Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow * Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (Expr)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$
#3 $push(intlit.value)$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	$+ Term\ \#1\ Expr'$			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	$* Factor\ \#2\ Term'$		ϵ		ϵ
<i>Factor</i>			$(Expr)$		$\#3\ \text{intlit}$	



Input: 5 + 3 * 2 eof



current


CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow + Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow * Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (Expr)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$
#3 $push(intlit.value)$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	$+ Term\ \#1\ Expr'$			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	$* Factor\ \#2\ Term'$		ϵ		ϵ
<i>Factor</i>			$(Expr)$		$\#3\ \text{intlit}$	



Input: 5 + 3 * 2 eof




CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow + Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow * Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (Expr)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$
#3 $push(intlit.value)$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	$+ Term\ \#1\ Expr'$			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	$* Factor\ \#2\ Term'$		ϵ		ϵ
<i>Factor</i>			$(Expr)$		$\#3\ \text{intlit}$	



Input: 5 + 3 * 2 eof

↑ ↑
current
current


CFG

$Expr \rightarrow Term\ Expr'$
 $Expr' \rightarrow + Term\ \#1\ Expr'$
 $\quad \quad \quad | \ \epsilon$
 $Term \rightarrow Factor\ Term'$
 $Term' \rightarrow * Factor\ \#2\ Term'$
 $\quad \quad \quad | \ \epsilon$
 $Factor \rightarrow \#3\ \text{intlit}$
 $\quad \quad \quad | \ (Expr)$

SDT Actions

#1 $tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)$
#2 $fTrans = pop ; tTrans = pop ; push(tTrans * fTrans)$
#3 $push(intlit.value)$

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	$+ Term\ \#1\ Expr'$			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	$* Factor\ \#2\ Term'$		ϵ		ϵ
<i>Factor</i>			$(Expr)$		$\#3\ \text{intlit}$	



Input: 5 + 3 * 2 eof

Two blue arrows point upwards from the text "current" to the tokens '2' and 'eof' in the input string.

CFG

$$Expr \rightarrow Term \ Expr'$$
$$Expr' \rightarrow + Term \#1 Expr'$$

3 |

$$Term \rightarrow Factor Term'$$
$$Term' \rightarrow * Factor \#2 Term'$$

| 3

Factor \rightarrow #3 **intlit**

 $| \text{ (Expr)}$


SDT Actions

```
#1 tTrans = pop ; eTrans = pop ; push(eTrans + tTrans)
```

```
#2 fTrans = pop; tTrans = pop ; push(tTrans * fTrans)
```

#3 push(intlit.value)

	+	*	()	intlit	eof
<i>Expr</i>			<i>Term Expr'</i>		<i>Term Expr'</i>	
<i>Expr'</i>	+ <i>Term</i> #1 <i>Expr'</i>			ϵ		ϵ
<i>Term</i>			<i>Factor Term'</i>		<i>Factor Term'</i>	
<i>Term'</i>	ϵ	* <i>Factor</i> #2 <i>Term'</i>		ϵ		ϵ
<i>Factor</i>			(<i>Expr</i>)		#3 intlit	



What about ASTs?

Push and pop AST nodes on the stack

Keep field references to nodes that we pop

CFG

$$\begin{array}{l} \text{Expr} \rightarrow \text{Expr} + \text{Term} \#1 \\ \quad \quad | \quad \text{Term} \\ \text{Term} \rightarrow \#2 \text{ intlit} \end{array}$$

Transformed CFG

$$\begin{array}{l} \text{Expr} \rightarrow \text{Term Expr}' \\ \text{Expr}' \rightarrow + \text{Term} \#1 \text{ Expr}' \\ \quad \quad | \quad \epsilon \\ \text{Term} \rightarrow \#2 \text{ intlit} \end{array}$$

“Evaluation” SDT Actions

#1 $tTrans = pop ;$
 $eTrans = pop ;$
 $push(eTrans + tTrans)$

#2 $push(intlit.value)$

“AST” SDT Actions

#1 $tTrans = pop ;$
 $eTrans = pop ;$
 $push(new PlusNode(tTrans, eTrans))$

#2 $push(new IntLitNode(intlit.value))$

AST Example

Transformed CFG


$$\begin{aligned}
 E &\rightarrow T E' \\
 E' &\rightarrow + T \#1 E' \\
 &\quad | \quad \epsilon \\
 T &\rightarrow \#2 \text{intlit}
 \end{aligned}$$

"AST" SDT Actions

```

#1 tTrans = pop ;
   eTrans = pop ;
   push(new PlusNode(tTrans, eTrans))
#2 push(new IntLitNode(intlit.value))
    
```

	intlit	+	EOF
E	$T E'$		
E'		$+ T$ $\#1 E'$	ϵ
T	$\#2$ intlit		



We now have an AST

At this point, we have completed the frontend for (a) compiler

- Only recognize LL(1)

LL(1) is not a great class of languages

```
if (e1)
  stmt1
if (e2)
  stmt2
else
  stmt3
```

Grammar Snippet

```
IfStmt -> if lparens Exp rparens Stmts
        | if lparens Exp rparens Stmts else Stmts
```